

RF Exposure Evaluation declaration

Product Name : BLUETOOTH DATA LOGGER & RECEIVER

Model No. : LR9553D

FCC ID : I2ILR9553D

Applicant : Leadtek Research Inc.

Address : 18F, No. 166, Chien yi Rd., Chung Ho, Taipei County,
Taiwan, (23511) R.O.C.

Date of Receipt : Aug. 17, 2007

Date of Declaration : Sep. 05, 2007

Report No. : 078241R-RFUSP06V01

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of QuieTek Corporation.
This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Average Time (Minutes) |
|---|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| (A) Limits for Occupational/ Control Exposures | | | | |
| 300-1500 | -- | -- | F/300 | 6 |
| 1500-100,000 | -- | -- | 5 | 6 |
| (B) Limits for General Population/ Uncontrolled Exposures | | | | |
| 300-1500 | -- | -- | F/1500 | 6 |
| 1500-100,000 | -- | -- | 1 | 30 |

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm^2

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm^2 . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product : BLUETOOTH DATA LOGGER & RECEIVER
Test Item : RF Exposure Evaluation
Test Site : CTR1

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.66 dBi in logarithm scale.

Output Power Into Antenna & RF Exposure Evaluation Distance (2.66dBi):

| Channel | Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20cm (mW/cm ²) |
|---------|-----------------|------------------------------|---|
| 00 | 2402.00 | 0.2291 | 0.000084 |
| 39 | 2441.00 | 0.2138 | 0.000078 |
| 78 | 2480.00 | 0.2089 | 0.000077 |

The distance r (4th column) calculated from the Fries transmission formula is far shorter than 20cm separation requirement.