



American Telecommunications Certification Body Inc.
6731 Whittier Ave, McLean, VA 22101

July 3, 2003

RE: REMEC Inc.

FCC ID: I2ODPA4040G

After a review of the submitted information, I have a few comments on the above referenced Application.

- 1) Your response for item 2 is confusing. It appears that the amplifier was tested with a 43 dBm per carrier combined output (43 dBm per carrier/46.0 combined power). If so, the Isolated output actually is higher power per channel (46.5 dBm) and would therefore be considered worse case to test at the bandedges.
Note:

Users Manual:

GSM Isolated Mode = 49.5 dBm per carrier

GSM Combined Mode = 46 dBm per carrier / 49.0 combined power

Edge Isolate Mode = 46.5 dBm per carrier

Edge Combined Mode = 43 dBm per carrier / 46.0 combined power

Please provide further information and/or plots as necessary.

Timothy R. Johnson
Examining Engineer

[mailto: tjohnson@AmericanTCB.com](mailto:tjohnson@AmericanTCB.com)

The items indicated above must be submitted before processing can continue on the above referenced application. Failure to provide the requested information may result in application termination. Correspondence should be considered part of the permanent submission and may be viewed from the Internet after a Grant of Equipment Authorization is issued.

Please do not respond to this correspondence using the email reply button. In order for your response to be processed expeditiously, you must submit your documents through the AmericanTCB.com website. Also, please note that partial responses increase processing time and should not be submitted.

Any questions about the content of this correspondence should be directed to the sender.