



**FCC 47 CFR PART 15 SUBPART C AND ANSI C63.10:2009  
TEST REPORT**

**For**

**Tablet**

**Model : INP-120Q**

**Trade Name : InFocus**

**Issued for**

**InFocus Corporation**

**13190 SW 68th Parkway Suite 200, Portland, OR97223, USA**

**Issued by**

**Compliance Certification Services Inc.  
Hsinchu Lab.**

**NO. 989-1 Wen Shan Rd., Shang Shan Village,  
Qionglin Shiang Hsinchu County 30741, Taiwan, R.O.C**

**TEL: +886-3-5921698**

**FAX: +886-3-5921108**

**<http://www.ccsrf.com>**

**E-Mail : [service@ccsrf.com](mailto:service@ccsrf.com)**

**Issued Date: November 05, 2014**



**Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF or any government agencies. The test results of this report relate only to the tested sample identified in this report.



## Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	11/05/2014	Initial Issue	All Page 110	Dola Hsieh



---

**TABLE OF CONTENTS**

<b>TITLE</b>	<b>PAGE NO.</b>
<b>1. TEST REPORT CERTIFICATION .....</b>	<b>4</b>
<b>2. EUT DESCRIPTION .....</b>	<b>5</b>
<b>3. DESCRIPTION OF TEST MODES .....</b>	<b>7</b>
<b>4. TEST METHODOLOGY .....</b>	<b>9</b>
<b>5. FACILITIES AND ACCREDITATION .....</b>	<b>9</b>
5.1 FACILITIES .....	9
5.2 ACCREDITATIONS.....	9
5.3 MEASUREMENT UNCERTAINTY .....	10
<b>6. SETUP OF EQUIPMENT UNDER TEST.....</b>	<b>11</b>
<b>7. FCC PART 15.247 REQUIREMENTS .....</b>	<b>13</b>
7.1 6dB BANDWIDTH .....	13
7.2 MAXIMUM PEAK OUTPUT POWER .....	26
7.3 AVERAGE POWER .....	30
7.4 POWER SPECTRAL DENSITY .....	33
7.5 CONDUCTED SPURIOUS EMISSION .....	47
7.6 RADIATED EMISSION.....	63
7.7 CONDUCTED EMISSION.....	103
<b>APPENDIX SETUP PHOTOS .....</b>	<b>108</b>



### 1. TEST REPORT CERTIFICATION

**Applicant** : InFocus Corporation  
**Address** : 13190 SW 68th Parkway Suite 200, Portland, OR97223, USA  
**Equipment Under Test** : Tablet  
**Model** : INP-120Q  
**Trade Name** : InFocus  
**Tested Date** : October 15 ~ 30, 2014

APPLICABLE STANDARD	
Standard	Test Result
FCC Part 15 Subpart C AND ANSI C63.10:2009	PASS

WE HEREBY CERTIFY THAT: The above equipment has been tested by Compliance Certification Services Inc., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

**Approved by:**

Sb. Lu  
Sr. Engineer

**Reviewed by:**

Gundam Lin  
Sr. Engineer



## 2. EUT DESCRIPTION

<b>Product Name</b>	Tablet
<b>Model Number</b>	INP-120Q
<b>Identify Number</b>	T141015D05
<b>Received Date</b>	October 15, 2014
<b>Frequency Range</b>	IEEE 802.11b/g, 802.11gn HT20 : 2412MHz ~ 2462MHz IEEE 802.11gn HT40 : 2422MHz ~ 2452MHz Bluetooth 4.0 : 2402MHz ~ 2480MHz
<b>Transmit Power</b>	IEEE 802.11b : 19.77 dBm (0.0948 W) IEEE 802.11g : 23.93 dBm (0.2472 W) IEEE 802.11gn HT20 : 23.46 dBm (0.2218 W) IEEE 802.11gn HT40 : 22.53 dBm (0.1791 W) Bluetooth 4.0 : 5.96 dBm (0.0039W)
<b>Channel Spacing</b>	IEEE 802.11b/g, 802.11gn HT20/HT40 : 5MHz Bluetooth 4.0: 2MHz
<b>Channel Number</b>	IEEE 802.11b/g, 802.11gn HT20 : 11 Channels IEEE 802.11gn HT40 : 7 Channels Bluetooth 4.0 : 40 Channels
<b>Transmit Data Rate</b>	IEEE 802.11b : 11, 5.5, 2, 1 Mbps IEEE 802.11g : 54, 48, 36, 24, 18, 12, 9, 6 Mbps IEEE 802.11gn HT20 : 72.2, 65, 58.5, 57.78, 52, 43.33, 39, 28.89, 26, 21.7, 19.5, 14.44, 13, 7.2, 6.5 Mbps IEEE 802.11gn HT40 : 150, 135, 121.5, 120, 108, 90, 81, 60, 54, 45, 40.5, 30, 27, 15, 13.5Mbps Bluetooth 4.0 : 1Mbps
<b>Type of Modulation</b>	IEEE 802.11b : DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g : OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11gn HT20/40 : OFDM (64QAM, 16QAM, QPSK, BPSK) Bluetooth 4.0 : GFSK
<b>Antenna Type</b>	PIFA Antenna × 1, Antenna Gain : 1.86 dBi
<b>Power Rating</b>	3.7Vdc, 6400mAh, 23.68Wh (For Battery) 5.0Vdc, 2A (For Charging)
<b>Test Voltage</b>	120Vac, 60Hz
<b>DC Power Cable Type</b>	Non-shielded cable, 1m × 1 (Detachable)
<b>I/O Port</b>	USB Port × 1, Audio Port × 1, SD Card Port × 1, USB Power Port × 1



**Power Adapter :**

No.	Manufacturer	Model No.	Power Input	Power Output
1	Chicony	W12-010N3A	100-240Vac, 50/60Hz, 0.3A	5Vdc, 2A

**Remark :**

- 1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.*
- 2. For more details, please refer to the User's manual of the EUT.*
- 3. This submittal(s) (test report) is intended for FCC ID: I46-INP-120Q filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.*



### 3. DESCRIPTION OF TEST MODES

The EUT is an 802.11n transceiver in Tablet form factor.

For IEEE 802.11b/g, 802.11gn HT20/HT40 mode (1TX / 1RX) : transmit/receive.

For Bluetooth(1TX/1RX) : transmit/receive.

#### Conducted Emission / Radiated Emission Test (Below 1 GHz)

1. The following test modes were scanned during the preliminary test:

No.	Pre-Test Mode
1	TX Mode

2. After the preliminary scan, the following test mode was found to produce the highest emission level.

Final Test Mode		
Emission	Radiated Emission	TX Mode
	Conducted Emission	TX Mode

**Remark :** Then, the above highest emission mode of the configuration of the EUT and cable was chosen for all final test items.



**Conducted / Radiated Emission Test (Above 1 GHz)**

**IEEE 802.11b, 802.11g, 802.11gn HT20 mode**

The EUT had been tested under operating condition.

There are three channels have been tested as following :

Channel	Frequency (MHz)
Low	2412
Middle	2437
High	2462

IEEE 802.11b mode : 1Mbps data rate (worst case) were chosen for full testing.

IEEE 802.11g mode : 6Mbps data rate (worst case) were chosen for full testing.

IEEE 802.11gn HT20 mode : 6.5Mbps data rate (worst case) were chosen for full testing.

**IEEE 802.11gn HT40 mode**

The EUT had been tested under operating condition.

There are three channels have been tested as following :

Channel	Frequency (MHz)
Low	2422
Middle	2437
High	2452

IEEE 802.11gn HT40 mode : 13.5Mbps data rate (worst case) were chosen for full testing.

**Bluetooth 4.0 mode**

The EUT had been tested under operating condition.

There are three channels have been tested as following :

Channel	Frequency (MHz)
Low	2402
Middle	2440
High	2480

**Remark :** The field strength of spurious emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X, Y axis). The worst emission was found in stand-up position(Z axis) and the worst case was recorded.





## 4. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10:2009 and FCC CFR 47, 15.207, 15.209 and 15.247.

## 5. FACILITIES AND ACCREDITATION

### 5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

NO. 989-1 Wen Shan Rd., Shang Shan Village,  
Qionglin Shiang Hsinchu County 30741, Taiwan, R.O.C

The sites are constructed in conformance with the requirements of ANSI C63.10:2009 and CISPR 22. All receiving equipment conforms to CISPR 16-1-1, CISPR 16-1-2, CISPR 16-1-3, CISPR 16-1-4, CISPR 16-1-5.

### 5.2 ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

<b>Taiwan</b>	TAF
---------------	-----

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

<b>Canada</b>	INDUSTRY CANADA
<b>Japan</b>	VCCI
<b>Taiwan</b>	BSMI
<b>USA</b>	FCC MRA

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.ccsrf.com>

**Remark:** FCC Designation Number TW1027.



### 5.3 MEASUREMENT UNCERTAINTY

The following table is for the measurement uncertainty, which is calculated as per the document CISPR 16-4-2.

PARAMETER	UNCERTAINTY
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 30 to 1000 MHz	+/- 3.97
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 1 to 18GHz	+/- 3.58
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 18 to 26 GHz	+/- 3.59
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 26 to 40 GHz	+/- 3.81
Conducted Emission (Mains Terminals), 9kHz to 30MHz	+/- 2.48

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

Consistent with industry standard (e.g. CISPR 22, clause 11, Measurement Uncertainty) determining compliance with the limits shall be base on the results of the compliance measurement. Consequently the measure emissions being less than the maximum allowed emission result in this be a compliant test or passing test.

The acceptable measurement uncertainty value without requiring revision of the compliance statement is base on conducted and radiated emissions being less than  $U_{CISPR}$  which is 3.6dB and 5.2dB respectively. CCS values (called  $U_{Lab}$  in CISPR 16-4-2) is less than  $U_{CISPR}$  as shown in the table above. Therefore, MU need not be considered for compliance.



## 6. SETUP OF EQUIPMENT UNDER TEST

### SUPPORT EQUIPMENT

No.	Signal Cable Description
1	Non-shielded RJ-45 cable, 12m × 1
2	Non-shielded USB cable, 0.2m × 1

### SETUP DIAGRAM FOR TESTS

EUT & peripherals setup diagram is shown in appendix setup photos.

### EUT OPERATING CONDITION

#### WiFi

1. EUT & peripherals setup diagram is shown in appendix setup photos.

(1) **TX Mode:**

- ⇒ **Tx Data Rate:** CCK; 1Mbps Bandwidth 20 (IEEE 802.11b mode)  
OFDM; 6Mbps Bandwidth 20 (IEEE 802.11g mode)  
MCS=0; 6.5Mbps Bandwidth 20 (IEEE 802.11gn HT20 mode)  
MCS=0; 13.5Mbps Bandwidth 40 (IEEE 802.11gn HT40 mode)

⇒ **Power control**

- IEEE 802.11b Channel Low (2412MHz) TX Power 53
- IEEE 802.11b Channel Mid (2437MHz) TX Power 53
- IEEE 802.11b Channel High (2472MHz) TX Power 53
- IEEE 802.11g Channel Low (2412MHz) TX Power 60
- IEEE 802.11g Channel Mid (2437MHz) TX Power 63
- IEEE 802.11g Channel High (2472MHz) TX Power 61
- IEEE 802.11n HT20 Channel Low (2412MHz) TX Power 57
- IEEE 802.11n HT20 Channel Mid (2437MHz) TX Power 57
- IEEE 802.11n HT20 Channel High (2472MHz) TX Power 57
- IEEE 802.11n HT40 Channel Low (2422MHz) TX Power 55
- IEEE 802.11n HT40 Channel Mid (2437MHz) TX Power 59
- IEEE 802.11n HT40 Channel High (2462MHz) TX Power 57

2. All of the functions are under run.

3. Start test.



**Bluetooth 4.0**

1. EUT & peripherals setup diagram is shown in appendix setup photos.
2. Run "REALTEK 11n 8723BE PCIE WLAN NIC" to test
3. PACKET TRANSMIT (TX Mode)
  - Freq: 2402, 2440, 2480 (Channel 0 ,19 ,39)
  - DataRate =LE
  - Power set=4
4. All of the functions are under run.
5. Start test



## 7. FCC PART 15.247 REQUIREMENTS

### 7.1 6dB BANDWIDTH

#### LIMITS


§ 15.247(a) (2) For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz.

#### TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY43360132	06/10/2015

*Remark: Each piece of equipment is scheduled for calibration once a year.*

#### TEST SETUP



#### TEST PROCEDURE

1. The transmitter output was connected to a spectrum analyzer.
2. Set RBW = 100 kHz.
3. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
4. Detector = Peak.
5. Trace mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize.
8. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

**TEST RESULTS****IEEE 802.11b Mode**

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (kHz)	Pass / Fail
Low	2412	10.045	500	PASS
Middle	2437	10.035	500	PASS
High	2462	10.015	500	PASS

**IEEE 802.11g Mode**

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (kHz)	Pass / Fail
Low	2412	16.575	500	PASS
Middle	2437	16.575	500	PASS
High	2462	16.565	500	PASS

**IEEE 802.11gn HT20 Mode**

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (kHz)	Pass / Fail
Low	2412	17.785	500	PASS
Middle	2437	17.775	500	PASS
High	2462	17.800	500	PASS

**IEEE 802.11gn HT40 Mode**

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (kHz)	Pass / Fail
Low	2422	36.435	500	PASS
Middle	2437	36.400	500	PASS
High	2452	36.400	500	PASS





**Bluetooth 4.0 Mode**


<b>Channel</b>	<b>Channel Frequency (MHz)</b>	<b>6dB Bandwidth (kHz)</b>	<b>Minimum Limit (kHz)</b>	<b>Pass / Fail</b>
Low	2402	796.8	500	PASS
Middle	2440	796.8	500	PASS
High	2480	786.6	500	PASS






**6dB BANDWIDTH**




































## 7.2 MAXIMUM PEAK OUTPUT POWER

### LIMITS

§ 15.247(b) The maximum peak output power of the intentional radiator shall not exceed the following :

§ 15.247(b) (3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands : 1 watt.


§ 15.247(b) (4) Except as shown in paragraphs (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Power Meter	Anritsu	ML2495A	1149001	12/06/2014
Power Sensor	Anritsu	MA2411B	1126148	12/06/2014

*Remark: Each piece of equipment is scheduled for calibration once a year.*

### TEST SETUP



### TEST PROCEDURE

The transmitter output is connected to the power meter. The power meter is set to the peak power detection.



**TEST RESULTS**

**IEEE 802.11b Mode**

Channel	Channel Frequency (MHz)	Peak Power (dBm)		Peak Power Limit		Pass / Fail
		(dBm)	(W)	(dBm)	(W)	
Low	2412	19.77	0.0948	30	1	PASS
Middle	2437	19.68	0.0929	30	1	PASS
High	2462	19.61	0.0914	30	1	PASS

**Remark:**

1. At final test to get the worst-case emission at 1Mbps.
2. The cable assembly insertion loss of 10.5dB (including 10 dB pad and 0.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.

**IEEE 802.11g Mode**

Channel	Channel Frequency (MHz)	Peak Power (dBm)		Peak Power Limit		Pass / Fail
		(dBm)	(W)	(dBm)	(W)	
Low	2412	23.48	0.2228	30	1	PASS
Middle	2437	23.93	0.2472	30	1	PASS
High	2462	23.43	0.2203	30	1	PASS

**Remark:**

1. At final test to get the worst-case emission at 6Mbps.
2. The cable assembly insertion loss of 10.5dB (including 10 dB pad and 0.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.



IEEE 802.11gn HT20 Mode

Channel	Channel Frequency (MHz)	Peak Power		Peak Power Limit		Pass / Fail
		(dBm)	(W)	(dBm)	(W)	
Low	2412	23.46	0.2218	30	1	PASS
Middle	2437	22.57	0.1807	30	1	PASS
High	2462	22.24	0.1675	30	1	PASS

Remark:

1. At final test to get the worst-case emission at 6.5Mbps.
2. The cable assembly insertion loss of 10.5dB (including 10 dB pad and 0.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.

IEEE 802.11gn HT40 Mode

Channel	Channel Frequency (MHz)	Peak Power		Peak Power Limit		Pass / Fail
		(dBm)	(W)	(dBm)	(W)	
Low	2412	21.14	0.1300	30	1	PASS
Middle	2437	22.53	0.1791	30	1	PASS
High	2462	21.85	0.1531	30	1	PASS

Remark:

1. At final test to get the worst-case emission at 13.5Mbps.
2. The cable assembly insertion loss of 10.5dB (including 10 dB pad and 0.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.



**Bluetooth 4.0 Mode**

Channel	Channel Frequency (MHz)	Peak Power		Peak Power Limit		Pass / Fail
		(dBm)	(W)	(dBm)	(W)	
Low	2402	5.86	0.0039	30	1	PASS
Middle	2440	5.96	0.0039	30	1	PASS
High	2480	5.55	0.0036	30	1	PASS

**Remark:** The cable assembly insertion loss of 10.5 dB (including 10 dB pad and 0.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.



### 7.3 AVERAGE POWER

#### LIMITS

None; for reporting purposes only.

#### TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Power Meter	ANRITSU	ML2495A	1149001	12/06/2014
Power Sensor	ANRITSU	MA2411B	1126148	12/06/2014

*Remark: Each piece of equipment is scheduled for calibration once a year.*

#### TEST SETUP



#### TEST PROCEDURE

The transmitter output is connected to the power meter. The power meter is set to the average power detection.



**TEST RESULTS**

**IEEE 802.11b Mode**

Channel	Channel Frequency (MHz)	Average Power (dBm)
Low	2412	17.59
Middle	2437	17.52
High	2462	17.40

**Remark:**

1. At final test to get the worst-case emission at 1Mbps.
2. The cable assembly insertion loss of 10.5 dB (including 10 dB pad and 0.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.

**IEEE 802.11g Mode**

Channel	Channel Frequency (MHz)	Average Power (dBm)
Low	2412	15.70
Middle	2437	17.00
High	2462	16.03

**Remark:**

1. At final test to get the worst-case emission at 6Mbps.
2. The cable assembly insertion loss of 10.5 dB (including 10 dB pad and 0.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.



**IEEE 802.11gn HT20 Mode**

Channel	Channel Frequency (MHz)	Average Power Output (dBm)
Low	2412	14.49
Middle	2437	14.53
High	2462	14.43

**Remark:**

1. At final test to get the worst-case emission at 6.5Mbps.
2. The cable assembly insertion loss of 10.5 dB (including 10 dB pad and 0.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.

**IEEE 802.11gn HT40 Mode**

Channel	Channel Frequency (MHz)	Average Power Output (dBm)
Low	2412	12.80
Middle	2437	14.62
High	2462	13.74

**Remark:**

1. At final test to get the worst-case emission at 13.5Mbps.
2. The cable assembly insertion loss of 10.5 dB (including 10 dB pad and 0.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.

**Bluetooth 4.0 Mode**

Channel	Channel Frequency (MHz)	Average Power (dBm)
Low	2402	5.05
Middle	2440	5.08
High	2480	4.63

**Remark:** The cable assembly insertion loss of 10.5 dB (including 10 dB pad and 0.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.





## 7.4 POWER SPECTRAL DENSITY

### LIMITS

§ 15.247(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY43360132	06/10/2015

*Remark: Each piece of equipment is scheduled for calibration once a year.*

### TEST SETUP



### TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer.
2. Set analyzer center frequency to DTS channel center frequency.
3. Set the span to 1.5 times the DTS channel bandwidth.
4. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
5. Set the VBW  $\geq 3 \times \text{RBW}$ .
6. Detector = peak.
7. Sweep time = auto couple.
8. Trace mode = max hold.
9. Allow trace to fully stabilize.
10. Use the peak marker function to determine the maximum amplitude level within the RBW.
11. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



**TEST RESULTS**

**IEEE 802.11b Mode**

Channel	Channel Frequency (MHz)	Final RF Power Level in 3KHz BW (dBm)	Minimum Limit (dBm)	Pass / Fail
Low	2412	-12.18	8	PASS
Middle	2437	-12.21	8	PASS
High	2462	-12.49	8	PASS

**Remark:**

1. At final test to get the worst-case emission at 1Mbps.
2. The cable assembly insertion loss of 10.5dB (including 10 dB pad and 0.5 dB cable) was Entered as an offset in the spectrum analyzer to allow for direct reading of power.

**IEEE 802.11g Mode**

Channel	Channel Frequency (MHz)	Final RF Power Level in 3KHz BW (dBm)	Minimum Limit (dBm)	Pass / Fail
Low	2412	-13.18	8	PASS
Middle	2437	-11.61	8	PASS
High	2462	-12.81	8	PASS

**Remark:**

1. At final test to get the worst-case emission at 6Mbps.
2. The cable assembly insertion loss of 10.5dB (including 10 dB pad and 0.5 dB cable) was Entered as an offset in the spectrum analyzer to allow for direct reading of power.



**IEEE 802.11gn HT20 Mode**

Channel	Channel Frequency (MHz)	Final RF Power Level in 3KHz BW (dBm)	Minimum Limit (dBm)	Pass / Fail
Low	2412	-13.77	8	PASS
Middle	2437	-13.53	8	PASS
High	2462	-13.56	8	PASS

**Remark:**

1. At final test to get the worst-case emission at 6.5Mbps.
2. The cable assembly insertion loss of 10.5dB (including 10 dB pad and 0.5 dB cable) was Entered as an offset in the spectrum analyzer to allow for direct reading of power.

**IEEE 802.11gn HT40 Mode**

Channel	Channel Frequency (MHz)	Final RF Power Level in 3KHz BW (dBm)	Minimum Limit (dBm)	Pass / Fail
Low	2412	-17.27	8	PASS
Middle	2437	-15.28	8	PASS
High	2462	-16.59	8	PASS

**Remark:**

1. At final test to get the worst-case emission at 13.5Mbps.
2. The cable assembly insertion loss of 10.5dB (including 10 dB pad and 0.5 dB cable) was Entered as an offset in the spectrum analyzer to allow for direct reading of power.





**Bluetooth 4.0 Mode**


Channel	Channel Frequency (MHz)	Final RF Power Level in 3KHz BW (dBm)	Minimum Limit (dBm)	Pass / Fail
Low	2402	-11.20	8	PASS
Middle	2440	-10.99	8	PASS
High	2480	-11.47	8	PASS



*Remark: The cable assembly insertion loss of 10.5 dB (including 10 dB pad and 0.5 dB cable) was Entered as an offset in the spectrum analyzer to allow for direct reading of power.*




**POWER SPECTRAL DENSITY**


































## 7.5 CONDUCTED SPURIOUS EMISSION

### LIMITS

§ 15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

### TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY43360132	06/10/2015

*Remark: Each piece of equipment is scheduled for calibration once a year.*

### TEST SETUP



### TEST PROCEDURE



The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

The spectrum from 30 MHz to 26.5 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.







TEST RESULTS



OUT-OF-BAND SPURIOUS EMISSIONS-CONDUCTED MEASUREMENT



























































### 7.6 RADIATED EMISSION

#### LIMITS

(1) According to § 15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3338	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )
13.36 - 13.41			

**Remark:**

1. <sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.
2. <sup>2</sup> Above 38.6

(2) According to § 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.



(3) According to § 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table :

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(KHz)	300
0.490 – 1.705	24000/F(KHz)	30
1.705 – 30.0	30	30
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3

**Remark:** \*\*Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

(4) According to § 15.209 (b) In the emission table above, the tighter limit applies at the band edges.

**TEST EQUIPMENT**

**Radiated Emission / 966Chamber\_B**

Name of Equipment	Manufacture	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY46180323	04/15/2015
EMI Test Receiver	ROHDE & SCHWARZ	ESCS 30	835418/008	10/14/2015
Bi-log Antenna	SCHWARZBECK	VULB 9168	9168-250	08/21/2015
Broad-Band Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-778	08/19/2015
Double-Ridged Waveguide Horn	ETS-LINDGREN	3117	00078733	12/05/2014
Horn Antenna	COM-POWER	AH-840	03077	12/18/2014
Pre-Amplifier	Agilent	8447D	2944A10052	07/15/2015
Pre-Amplifier	Agilent	8449B	3008A01916	07/15/2015
LOOP Antenna	EMCO	6502	8905-2356	09/23/2015
Notch Filters Band Reject	Micro-Tronics	BRM05702-01	026	N.C.R

**Remark:** 1. Each piece of equipment is scheduled for calibration once a year.  
2. N.C.R = No Calibration Request.







**TEST SETUP**

The diagram below shows the test setup that is utilized to make the measurements for emission below 1GHz.

**9kHz ~ 30MHz**




**30MHz ~ 1GHz**





The diagram below shows the test setup that is utilized to make the measurements for emission above 1GHz.



### **TEST PROCEDURE**

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground. The table was rotated 360 degrees to determine the position of the highest radiation.
2. While measuring the radiated emission below 1GHz, the EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. While measuring the radiated emission above 1GHz, the EUT was set 3 meters away from the interference-receiving antenna.
3. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarization of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

#### **Remark :**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.



**TEST RESULTS**

**Below 1 GHz (9kHz ~ 30MHz)**

No emission found between lowest internal used/generated frequency to 30MHz.

**Below 1 GHz (30MHz ~ 1GHz)**

<b>Product Name</b>	Tablet	<b>Test By</b>	Rex Chiu
<b>Test Model</b>	INP-120Q	<b>Test Date</b>	2014/10/24
<b>Test Mode</b>	TX Mode	<b>Temp. &amp; Humidity</b>	27°C, 54%

966 Chamber_B at 3Meter / Horizontal						
Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Remark
109.54	56.22	-17.43	38.79	43.50	-4.71	Peak
203.63	51.40	-15.95	35.45	43.50	-8.05	QP
335.55	44.90	-11.18	33.72	46.00	-12.28	QP
384.05	50.67	-10.24	40.43	46.00	-5.57	Peak
480.08	50.14	-8.46	41.68	46.00	-4.32	Peak
719.67	47.10	-4.28	42.82	46.00	-3.18	QP

966 Chamber_B at 3Meter / Vertical						
Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Remark
48.43	40.80	-13.90	26.90	40.00	-13.10	QP
156.10	52.94	-13.50	39.44	43.50	-4.06	Peak
240.49	56.80	-14.07	42.73	46.00	-3.27	Peak
252.13	44.90	-13.64	31.26	46.00	-14.74	QP
312.27	50.30	-11.66	38.64	46.00	-7.36	QP
384.05	52.99	-10.24	42.75	46.00	-3.25	Peak

**Remark:**

1. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit.
2. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
3. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) – PreAmp.Gain (dB)
4. Result (dBµV/m) = Reading (dBµV) + Correction Factor (dB/m)
5. Margin (dB) = Remark result (dBµV/m) - Quasi-peak limit (dBµV/m).



Above 1 GHz

<b>Product Name</b>	Tablet	<b>Test By</b>	Davis Tseng
<b>Test Model</b>	INP-120Q	<b>Test Date</b>	2014/10/23
<b>Test Mode</b>	IEEE 802.11b TX / CH Low	<b>Temp. &amp; Humidity</b>	25°C, 61%

966 Chamber_B at 3Meter / Horizontal									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1742.00	49.17	---	-0.62	48.55	---	74.00	54.00	-5.45	Peak
2064.00	47.55	---	1.95	49.50	---	74.00	54.00	-4.50	Peak
2496.00	48.15	---	2.80	50.96	---	74.00	54.00	-3.04	Peak
4830.00	42.65	---	8.09	50.74	---	74.00	54.00	-3.26	Peak
5340.00	43.33	---	9.03	52.36	---	74.00	54.00	-1.64	Peak
7755.00	38.35	---	13.47	51.82	---	74.00	54.00	-2.18	Peak

966 Chamber_B at 3Meter / Vertical									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1296.00	50.07	---	-2.89	47.18	---	74.00	54.00	-6.82	Peak
2138.00	47.82	---	2.09	49.91	---	74.00	54.00	-4.09	Peak
2494.00	47.14	---	2.80	49.94	---	74.00	54.00	-4.06	Peak
4830.00	43.87	---	8.09	51.96	---	74.00	54.00	-2.04	Peak
6180.00	38.34	---	11.33	49.67	---	74.00	54.00	-4.33	Peak
7350.00	38.28	---	13.22	51.49	---	74.00	54.00	-2.51	Peak

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor  
 Margin = Result - Limit  
 Remark Peak = Result(PK) - Limit(AV)  
 Remark AVG = Result(AV) - Limit(AV)



<b>Product Name</b>	Tablet	<b>Test By</b>	Davis Tseng
<b>Test Model</b>	INP-120Q	<b>Test Date</b>	2014/10/23
<b>Test Mode</b>	IEEE 802.11b TX / CH Middle	<b>Temp. &amp; Humidity</b>	25°C, 61%

**966 Chamber\_B at 3Meter / Horizontal**

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2332.00	48.72	---	2.48	51.20	---	74.00	54.00	-2.80	Peak
2388.00	49.86	40.34	2.59	52.45	42.93	74.00	54.00	-11.07	AVG
2486.00	48.51	---	2.78	51.29	---	74.00	54.00	-2.71	Peak
4875.00	44.14	---	8.18	52.32	---	74.00	54.00	-1.68	Peak
5340.00	44.85	28.12	9.03	53.88	37.15	74.00	54.00	-16.85	AVG
7485.00	38.22	---	13.63	51.85	---	74.00	54.00	-2.15	Peak

**966 Chamber\_B at 3Meter / Vertical**

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2292.00	47.67	---	2.40	50.07	---	74.00	54.00	-3.93	Peak
2498.00	46.98	---	2.81	49.78	---	74.00	54.00	-4.22	Peak
2866.00	47.78	---	3.74	51.52	---	74.00	54.00	-2.48	Peak
4875.00	44.56	43.87	8.18	52.75	52.05	74.00	54.00	-1.95	AVG
6435.00	38.00	---	12.08	50.08	---	74.00	54.00	-3.92	Peak
7515.00	38.54	---	13.67	52.21	---	74.00	54.00	-1.79	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor  
Margin = Result - Limit  
Remark Peak = Result(PK) - Limit(AV)  
Remark AVG = Result(AV) - Limit(AV)



<b>Product Name</b>	Tablet	<b>Test By</b>	Davis Tseng
<b>Test Model</b>	INP-120Q	<b>Test Date</b>	2014/10/23
<b>Test Mode</b>	IEEE 802.11b TX / CH High	<b>Temp. &amp; Humidity</b>	25°C, 61%

966 Chamber_B at 3Meter / Horizontal									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2338.00	47.94	---	2.49	50.42	---	74.00	54.00	-3.58	Peak
2386.00	48.52	---	2.58	51.11	---	74.00	54.00	-2.89	Peak
2666.00	50.98	43.11	3.23	54.21	46.34	74.00	54.00	-7.66	AVG
2834.00	47.00	---	3.66	50.66	---	74.00	54.00	-3.34	Peak
4920.00	42.40	---	8.28	50.67	---	74.00	54.00	-3.33	Peak
5325.00	44.79	26.89	9.01	53.80	35.90	74.00	54.00	-18.10	AVG
6660.00	39.60	---	12.23	51.82	---	74.00	54.00	-2.18	Peak

966 Chamber_B at 3Meter / Vertical									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2086.00	47.11	---	1.99	49.10	---	74.00	54.00	-4.90	Peak
2332.00	47.73	---	2.48	50.21	---	74.00	54.00	-3.79	Peak
2970.00	46.64	---	4.00	50.65	---	74.00	54.00	-3.35	Peak
4050.00	41.26	---	6.02	47.28	---	74.00	54.00	-6.72	Peak
4920.00	41.86	---	8.28	50.13	---	74.00	54.00	-3.87	Peak
6825.00	38.78	---	12.18	50.96	---	74.00	54.00	-3.04	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor  
Margin = Result - Limit  
Remark Peak = Result(PK) - Limit(AV)  
Remark AVG = Result(AV) - Limit(AV)



<b>Product Name</b>	Tablet	<b>Test By</b>	Davis Tseng
<b>Test Model</b>	INP-120Q	<b>Test Date</b>	2014/10/23
<b>Test Mode</b>	IEEE 802.11g TX / CH Low	<b>Temp. &amp; Humidity</b>	25°C, 61%

**966 Chamber\_B at 3Meter / Horizontal**

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1996.00	48.36	---	1.78	50.14	---	74.00	54.00	-3.86	Peak
2494.00	46.48	---	2.80	49.28	---	74.00	54.00	-4.72	Peak
2666.00	51.10	43.03	3.23	54.33	46.26	74.00	54.00	-7.74	AVG
4815.00	39.87	---	8.06	47.93	---	74.00	54.00	-6.07	Peak
5340.00	42.95	---	9.03	51.98	---	74.00	54.00	-2.02	Peak
7710.00	38.62	---	13.51	52.12	---	74.00	54.00	-1.88	Peak

**966 Chamber\_B at 3Meter / Vertical**

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2036.00	47.66	---	1.89	49.55	---	74.00	54.00	-4.45	Peak
2496.00	47.21	---	2.80	50.01	---	74.00	54.00	-3.99	Peak
2930.00	46.84	---	3.90	50.75	---	74.00	54.00	-3.25	Peak
4710.00	39.95	---	7.84	47.79	---	74.00	54.00	-6.21	Peak
6960.00	39.07	---	12.14	51.21	---	74.00	54.00	-2.79	Peak
7455.00	38.62	---	13.54	52.16	---	74.00	54.00	-1.84	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor  
Margin = Result - Limit  
Remark Peak = Result(PK) - Limit(AV)  
Remark AVG = Result(AV) - Limit(AV)



<b>Product Name</b>	Tablet	<b>Test By</b>	Davis Tseng
<b>Test Model</b>	INP-120Q	<b>Test Date</b>	2014/10/23
<b>Test Mode</b>	IEEE 802.11g TX / CH Middle	<b>Temp. &amp; Humidity</b>	25°C, 61%

966 Chamber_B at 3Meter / Horizontal									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2364.00	48.69	---	2.54	51.23	---	74.00	54.00	-2.77	Peak
2498.00	47.52	---	2.81	50.32	---	74.00	54.00	-3.68	Peak
2666.00	50.97	43.04	3.23	54.20	46.27	74.00	54.00	-7.73	AVG
4755.00	39.65	---	7.94	47.58	---	74.00	54.00	-6.42	Peak
5340.00	42.92	---	9.03	51.95	---	74.00	54.00	-2.05	Peak
7770.00	38.54	---	13.46	52.00	---	74.00	54.00	-2.00	Peak

966 Chamber_B at 3Meter / Vertical									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2130.00	48.73	---	2.08	50.81	---	74.00	54.00	-3.19	Peak
2362.00	47.79	---	2.54	50.32	---	74.00	54.00	-3.68	Peak
2484.00	46.50	---	2.78	49.28	---	74.00	54.00	-4.72	Peak
4695.00	40.22	---	7.81	48.03	---	74.00	54.00	-5.97	Peak
6735.00	38.87	---	12.20	51.07	---	74.00	54.00	-2.93	Peak
7320.00	39.32	---	13.12	52.44	---	74.00	54.00	-1.56	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor  
Margin = Result - Limit  
Remark Peak = Result(PK) - Limit(AV)  
Remark AVG = Result(AV) - Limit(AV)





<b>Product Name</b>	Tablet	<b>Test By</b>	Davis Tseng
<b>Test Model</b>	INP-120Q	<b>Test Date</b>	2014/10/23
<b>Test Mode</b>	IEEE 802.11g TX / CH High	<b>Temp. &amp; Humidity</b>	25°C, 61%

966 Chamber_B at 3Meter / Horizontal									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2134.00	47.83	---	2.09	49.91	---	74.00	54.00	-4.09	Peak
2384.00	48.64	---	2.58	51.22	---	74.00	54.00	-2.78	Peak
2666.00	51.03	42.98	3.23	54.26	46.21	74.00	54.00	-7.79	AVG
4770.00	39.59	---	7.97	47.56	---	74.00	54.00	-6.44	Peak
5340.00	42.74	---	9.03	51.77	---	74.00	54.00	-2.23	Peak
7485.00	37.96	---	13.63	51.60	---	74.00	54.00	-2.40	Peak

966 Chamber_B at 3Meter / Vertical									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2116.00	47.12	---	2.05	49.17	---	74.00	54.00	-4.83	Peak
2342.00	47.54	---	2.50	50.03	---	74.00	54.00	-3.97	Peak
2990.00	47.30	---	4.05	51.35	---	74.00	54.00	-2.65	Peak
4800.00	39.93	---	8.03	47.96	---	74.00	54.00	-6.04	Peak
6660.00	39.82	---	12.23	52.05	---	74.00	54.00	-1.95	Peak
7485.00	38.00	---	13.63	51.64	---	74.00	54.00	-2.36	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor  
Margin = Result - Limit  
Remark Peak = Result(PK) - Limit(AV)  
Remark AVG = Result(AV) - Limit(AV)



<b>Product Name</b>	Tablet	<b>Test By</b>	Rex Chiu
<b>Test Model</b>	INP-120Q	<b>Test Date</b>	2014/10/24
<b>Test Mode</b>	IEEE 802.11gn HT20 TX / CH Low	<b>Temp. &amp; Humidity</b>	27°C, 54%

**966 Chamber\_B at 3Meter / Horizontal**

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1908.00	46.03	---	0.95	46.98	---	74.00	54.00	-7.02	Peak
2492.00	46.31	---	2.79	49.11	---	74.00	54.00	-4.89	Peak
2666.00	46.77	---	3.23	50.00	---	74.00	54.00	-4.00	Peak
4770.00	38.91	---	7.97	46.87	---	74.00	54.00	-7.13	Peak
5340.00	45.93	29.05	9.03	54.96	38.08	74.00	54.00	-15.92	AVG
7455.00	38.64	---	13.54	52.18	---	74.00	54.00	-1.82	Peak

**966 Chamber\_B at 3Meter / Vertical**

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2240.00	47.31	---	2.30	49.60	---	74.00	54.00	-4.40	Peak
2492.00	46.33	---	2.79	49.13	---	74.00	54.00	-4.87	Peak
2872.00	46.96	---	3.75	50.72	---	74.00	54.00	-3.28	Peak
4830.00	40.92	---	8.09	49.01	---	74.00	54.00	-4.99	Peak
6180.00	38.27	---	11.33	49.60	---	74.00	54.00	-4.40	Peak
7245.00	39.36	---	12.89	52.25	---	74.00	54.00	-1.75	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor  
Margin = Result - Limit  
Remark Peak = Result(PK) - Limit(AV)  
Remark AVG = Result(AV) - Limit(AV)



<b>Product Name</b>	Tablet	<b>Test By</b>	Rex Chiu
<b>Test Model</b>	INP-120Q	<b>Test Date</b>	2014/10/24
<b>Test Mode</b>	IEEE 802.11gn HT20 TX / CH Middle	<b>Temp. &amp; Humidity</b>	27°C, 54%

966 Chamber_B at 3Meter / Horizontal									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2092.00	45.39	---	2.00	47.40	---	74.00	54.00	-6.60	Peak
2390.00	52.54	36.85	2.59	55.13	39.44	74.00	54.00	-14.56	AVG
2666.00	47.77	---	3.23	51.00	---	74.00	54.00	-3.00	Peak
4875.00	38.94	---	8.18	47.12	---	74.00	54.00	-6.88	Peak
5340.00	45.40	28.63	9.03	54.43	37.66	74.00	54.00	-16.34	AVG
6660.00	41.17	30.16	12.23	53.40	42.39	74.00	54.00	-11.61	AVG

966 Chamber_B at 3Meter / Vertical									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2108.00	45.08	---	2.03	47.11	---	74.00	54.00	-6.89	Peak
2366.00	47.72	---	2.54	50.26	---	74.00	54.00	-3.74	Peak
2486.00	47.43	---	2.78	50.21	---	74.00	54.00	-3.79	Peak
4890.00	40.98	---	8.21	49.19	---	74.00	54.00	-4.81	Peak
6195.00	38.20	---	11.37	49.58	---	74.00	54.00	-4.42	Peak
7305.00	39.26	---	13.08	52.33	---	74.00	54.00	-1.67	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor  
Margin = Result - Limit  
Remark Peak = Result(PK) - Limit(AV)  
Remark AVG = Result(AV) - Limit(AV)



<b>Product Name</b>	Tablet	<b>Test By</b>	Rex Chiu
<b>Test Model</b>	INP-120Q	<b>Test Date</b>	2014/10/24
<b>Test Mode</b>	IEEE 802.11gn HT20 TX / CH High	<b>Temp. &amp; Humidity</b>	27°C, 54%

**966 Chamber\_B at 3Meter / Horizontal**

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2378.00	47.63	---	2.57	50.20	---	74.00	54.00	-3.80	Peak
2542.00	46.68	---	2.92	49.59	---	74.00	54.00	-4.41	Peak
2666.00	49.20	---	3.23	52.44	---	74.00	54.00	-1.56	Peak
4755.00	39.83	---	7.94	47.77	---	74.00	54.00	-6.23	Peak
5325.00	44.13	27.39	9.01	53.13	36.40	74.00	54.00	-17.60	AVG
7410.00	37.90	---	13.40	51.30	---	74.00	54.00	-2.70	Peak

**966 Chamber\_B at 3Meter / Vertical**

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2288.00	45.77	---	2.39	48.16	---	74.00	54.00	-5.84	Peak
2390.00	46.27	---	2.59	48.86	---	74.00	54.00	-5.14	Peak
2620.00	45.28	---	3.11	48.40	---	74.00	54.00	-5.60	Peak
4800.00	39.31	---	8.03	47.34	---	74.00	54.00	-6.66	Peak
6165.00	38.29	---	11.29	49.58	---	74.00	54.00	-4.42	Peak
7545.00	38.04	---	13.64	51.69	---	74.00	54.00	-2.31	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor  
Margin = Result - Limit  
Remark Peak = Result(PK) - Limit(AV)  
Remark AVG = Result(AV) - Limit(AV)



<b>Product Name</b>	Tablet	<b>Test By</b>	Rex Chiu
<b>Test Model</b>	INP-120Q	<b>Test Date</b>	2014/10/24
<b>Test Mode</b>	IEEE 802.11gn HT40 TX / CH Low	<b>Temp. &amp; Humidity</b>	27°C, 54%

**966 Chamber\_B at 3Meter / Horizontal**

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2284.00	46.21	---	2.38	48.59	---	74.00	54.00	-5.41	Peak
2486.00	47.74	---	2.78	50.52	---	74.00	54.00	-3.48	Peak
2666.00	51.27	36.41	3.23	54.50	39.64	74.00	54.00	-14.36	AVG
4695.00	39.29	---	7.81	47.10	---	74.00	54.00	-6.90	Peak
5340.00	44.49	27.69	9.03	53.53	36.72	74.00	54.00	-17.28	AVG
7650.00	38.61	---	13.56	52.17	---	74.00	54.00	-1.83	Peak

**966 Chamber\_B at 3Meter / Vertical**

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2012.00	45.24	---	1.84	47.08	---	74.00	54.00	-6.92	Peak
2294.00	45.50	---	2.40	47.90	---	74.00	54.00	-6.10	Peak
2636.00	45.34	---	3.16	48.49	---	74.00	54.00	-5.51	Peak
4770.00	39.99	---	7.97	47.95	---	74.00	54.00	-6.05	Peak
6675.00	38.64	---	12.22	50.86	---	74.00	54.00	-3.14	Peak
7650.00	38.78	---	13.56	52.34	---	74.00	54.00	-1.66	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor  
Margin = Result - Limit  
Remark Peak = Result(PK) - Limit(AV)  
Remark AVG = Result(AV) - Limit(AV)



<b>Product Name</b>	Tablet	<b>Test By</b>	Rex Chiu
<b>Test Model</b>	INP-120Q	<b>Test Date</b>	2014/10/24
<b>Test Mode</b>	IEEE 802.11gn HT40 TX / CH Middle	<b>Temp. &amp; Humidity</b>	27°C, 54%

966 Chamber_B at 3Meter / Horizontal									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2390.00	65.84	50.30	2.59	68.44	52.89	74.00	54.00	-1.11	AVG
2484.00	64.63	48.99	2.78	67.41	51.77	74.00	54.00	-2.23	AVG
2666.00	50.20	36.32	3.23	53.43	39.55	74.00	54.00	-14.45	AVG
4710.00	40.01	---	7.84	47.86	---	74.00	54.00	-6.14	Peak
5325.00	41.03	---	9.01	50.04	---	74.00	54.00	-3.96	Peak
7425.00	37.67	---	13.45	51.12	---	74.00	54.00	-2.88	Peak

966 Chamber_B at 3Meter / Vertical									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2390.00	58.79	46.74	2.59	61.38	49.33	74.00	54.00	-4.67	AVG
2484.00	58.26	44.51	2.78	61.04	47.29	74.00	54.00	-6.71	AVG
2772.00	45.51	---	3.50	49.02	---	74.00	54.00	-4.98	Peak
4755.00	39.38	---	7.94	47.32	---	74.00	54.00	-6.68	Peak
6495.00	38.50	---	12.26	50.75	---	74.00	54.00	-3.25	Peak
7305.00	38.15	---	13.08	51.23	---	74.00	54.00	-2.77	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor  
Margin = Result - Limit  
Remark Peak = Result(PK) - Limit(AV)  
Remark AVG = Result(AV) - Limit(AV)



<b>Product Name</b>	Tablet	<b>Test By</b>	Rex Chiu
<b>Test Model</b>	INP-120Q	<b>Test Date</b>	2014/10/24
<b>Test Mode</b>	IEEE 802.11gn HT40 TX / CH High	<b>Temp. &amp; Humidity</b>	27°C, 54%

966 Chamber_B at 3Meter / Horizontal									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2098.00	45.18	---	2.01	47.20	---	74.00	54.00	-6.80	Peak
2390.00	50.92	38.55	2.59	53.51	41.14	74.00	54.00	-12.86	AVG
2666.00	51.95	36.74	3.23	55.18	39.97	74.00	54.00	-14.03	AVG
5010.00	39.67	---	8.46	48.13	---	74.00	54.00	-5.87	Peak
5340.00	41.71	---	9.03	50.74	---	74.00	54.00	-3.26	Peak
7725.00	38.22	---	13.50	51.71	---	74.00	54.00	-2.29	Peak

966 Chamber_B at 3Meter / Vertical									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2216.00	45.32	---	2.25	47.57	---	74.00	54.00	-6.43	Peak
2390.00	46.75	---	2.59	49.34	---	74.00	54.00	-4.66	Peak
2808.00	44.75	---	3.59	48.34	---	74.00	54.00	-5.66	Peak
4845.00	39.20	---	8.12	47.32	---	74.00	54.00	-6.68	Peak
6975.00	38.56	---	12.14	50.70	---	74.00	54.00	-3.30	Peak
7770.00	37.78	---	13.46	51.24	---	74.00	54.00	-2.76	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor  
 Margin = Result - Limit  
 Remark Peak = Result(PK) - Limit(AV)  
 Remark AVG = Result(AV) - Limit(AV)



<b>Product Name</b>	Tablet	<b>Test By</b>	Rex Chiu
<b>Test Model</b>	INP-120Q	<b>Test Date</b>	2014/10/24
<b>Test Mode</b>	Bluetooth 4.0 TX / CH Low	<b>Temp. &amp; Humidity</b>	27°C, 54%

**966 Chamber\_B at 3Meter / Horizontal**

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1334.00	45.59	---	-2.89	42.70	---	74.00	54.00	-11.30	Peak
2000.00	45.77	---	1.82	47.59	---	74.00	54.00	-6.41	Peak
2666.00	49.23	---	3.23	52.46	---	74.00	54.00	-1.54	Peak
5340.00	43.82	27.98	9.03	52.85	37.01	74.00	54.00	-16.99	AVG
6675.00	39.09	---	12.22	51.31	---	74.00	54.00	-2.69	Peak
7320.00	38.74	---	13.12	51.86	---	74.00	54.00	-2.14	Peak

**966 Chamber\_B at 3Meter / Vertical**

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1992.00	43.67	---	1.74	45.41	---	74.00	54.00	-8.59	Peak
2142.00	42.97	---	2.10	45.07	---	74.00	54.00	-8.93	Peak
2636.00	42.87	---	3.16	46.03	---	74.00	54.00	-7.97	Peak
4950.00	39.33	---	8.34	47.67	---	74.00	54.00	-6.33	Peak
6660.00	39.30	---	12.23	51.53	---	74.00	54.00	-2.47	Peak
7785.00	38.29	---	13.45	51.74	---	74.00	54.00	-2.26	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor  
Margin = Result - Limit  
Remark Peak = Result(PK) - Limit(AV)  
Remark AVG = Result(AV) - Limit(AV)





<b>Product Name</b>	Tablet	<b>Test By</b>	Rex Chiu
<b>Test Model</b>	INP-120Q	<b>Test Date</b>	2014/10/24
<b>Test Mode</b>	Bluetooth 4.0 TX / CH Middle	<b>Temp. &amp; Humidity</b>	27°C, 54%

**966 Chamber\_B at 3Meter / Horizontal**

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2328.00	48.21	---	2.47	50.68	---	74.00	54.00	-3.32	Peak
2520.00	47.20	---	2.86	50.06	---	74.00	54.00	-3.94	Peak
2666.00	49.65	36.75	3.23	52.88	39.98	74.00	54.00	-14.02	AVG
4665.00	40.36	---	7.75	48.11	---	74.00	54.00	-5.89	Peak
5340.00	43.84	27.94	9.03	52.87	36.97	74.00	54.00	-17.03	AVG
7425.00	38.65	---	13.45	52.10	---	74.00	54.00	-1.90	Peak

**966 Chamber\_B at 3Meter / Vertical**

Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2388.00	44.62	---	2.59	47.21	---	74.00	54.00	-6.79	Peak
2520.00	45.61	---	2.86	48.47	---	74.00	54.00	-5.53	Peak
2770.00	43.22	---	3.50	46.71	---	74.00	54.00	-7.29	Peak
4005.00	43.07	---	5.88	48.95	---	74.00	54.00	-5.05	Peak
6660.00	39.61	---	12.23	51.84	---	74.00	54.00	-2.16	Peak
7440.00	38.09	---	13.49	51.58	---	74.00	54.00	-2.42	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor  
Margin = Result - Limit  
Remark Peak = Result(PK) - Limit(AV)  
Remark AVG = Result(AV) - Limit(AV)



<b>Product Name</b>	Tablet	<b>Test By</b>	Rex Chiu
<b>Test Model</b>	INP-120Q	<b>Test Date</b>	2014/10/24
<b>Test Mode</b>	Bluetooth 4.0 TX / CH High	<b>Temp. &amp; Humidity</b>	27°C, 54%

966 Chamber_B at 3Meter / Horizontal									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2000.00	46.04	---	1.82	47.86	---	74.00	54.00	-6.14	Peak
2560.00	45.97	---	2.96	48.93	---	74.00	54.00	-5.07	Peak
2666.00	48.34	---	3.23	51.57	---	74.00	54.00	-2.43	Peak
5340.00	41.95	---	9.03	50.98	---	74.00	54.00	-3.02	Peak
6675.00	40.23	---	12.22	52.45	---	74.00	54.00	-1.55	Peak
7515.00	38.26	---	13.67	51.92	---	74.00	54.00	-2.08	Peak



966 Chamber_B at 3Meter / Vertical									
Frequency (MHz)	Reading-PK (dBuV)	Reading-AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1984.00	44.16	---	1.67	45.83	---	74.00	54.00	-8.17	Peak
2332.00	43.52	---	2.48	46.00	---	74.00	54.00	-8.00	Peak
2560.00	44.59	---	2.96	47.56	---	74.00	54.00	-6.44	Peak
4860.00	39.44	---	8.15	47.59	---	74.00	54.00	-6.41	Peak
6480.00	38.33	---	12.21	50.55	---	74.00	54.00	-3.45	Peak
7650.00	38.60	---	13.56	52.15	---	74.00	54.00	-1.85	Peak

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Average test would be performed if the peak result were greater than the average limit.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Result = Reading + Correction Factor  
Margin = Result - Limit  
Remark Peak = Result(PK) - Limit(AV)  
Remark AVG = Result(AV) - Limit(AV)




Restricted Band Edges






Detector Mode : Peak

Polarity : Vertical



Detector Mode : Average


Polarity : Vertical






Detector Mode : Peak

Polarity : Horizontal



Detector Mode : Average


Polarity : Horizontal






Detector Mode : Peak

Polarity : Vertical



Detector Mode : Average


Polarity : Vertical






Detector Mode : Peak

Polarity : Horizontal



Detector Mode : Average


Polarity : Horizontal






Detector Mode : Peak

Polarity : Vertical



Detector Mode : Average

Polarity : Vertical









Detector Mode : Peak

Polarity : Horizontal



Detector Mode : Average


Polarity : Horizontal






Detector Mode : Peak

Polarity : Vertical



Detector Mode : Average


Polarity : Vertical






Detector Mode : Peak

Polarity : Horizontal



Detector Mode : Average


Polarity : Horizontal






Detector Mode : Peak

Polarity : Vertical



Detector Mode : Average


Polarity : Vertical






Detector Mode : Peak

Polarity : Horizontal



Detector Mode : Average


Polarity : Horizontal






Detector Mode : Peak

Polarity : Vertical



Detector Mode : Average


Polarity : Vertical






Detector Mode : Peak

Polarity : Horizontal



Detector Mode : Average


Polarity : Horizontal






Detector Mode : Peak

Polarity : Vertical



Detector Mode : Average

Polarity : Vertical









Detector Mode : Peak

Polarity : Horizontal



Detector Mode : Average


Polarity : Horizontal






Detector Mode : Peak

Polarity : Vertical



Detector Mode : Average


Polarity : Vertical






Detector Mode : Peak

Polarity : Horizontal



Detector Mode : Average


Polarity : Horizontal






Detector Mode : Peak

Polarity : Vertical



Detector Mode : Average


Polarity : Vertical






Detector Mode : Peak

Polarity : Horizontal



Detector Mode : Average


Polarity : Horizontal






Detector Mode : Peak

Polarity : Vertical



Detector Mode : Average

Polarity : Vertical





## 7.7 CONDUCTED EMISSION

### LIMITS

§ 15.207 (a) Except as shown in paragraph (b) and (c) this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Conducted Limit (dB $\mu$ v)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5.00	56	46
5.00 - 30.0	60	50



### TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
L.I.S.N	SCHWARZBECK	NSLK 8127	8127-465	08/06/2015
L.I.S.N	SCHWARZBECK	NSLK 8127	8127-473	03/10/2015
EMI Receiver	ROHDE & SCHWARZ	ESHS 30	838550/003	11/07/2014
Pulse Limiter	ROHDE & SCHWARZ	ESH3-Z2	100111	06/30/2015

*Remark: Each piece of equipment is scheduled for calibration once a year.*



**TEST SETUP**







## **TEST PROCEDURE**

The basic test procedure was in accordance with ANSI C63.10:2009.

The test procedure is performed in a 4m × 3m × 2.4m (L×W×H) shielded room.

The EUT along with its peripherals were placed on a 1.0m (W) × 1.5m (L) and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.

The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.


The EUT was located so that the distance between the boundary of the EUT and the closest surface of the LISN is 0.8 m. Where a mains flexible cord was provided by the manufacturer shall be 1 m long, or if in excess of 1 m, the excess cable was folded back and forth as far as possible so as to form a bundle not exceeding 0.4 m in length.



TEST RESULTS

Product Name	Tablet	Test By	Waternil Guan
Test Model	INP-120Q	Test Date	2014/10/25
Test Mode	TX Mode	Temp. & Humidity	24°C, 53%

LINE




Remark:

1. Correction Factor = Insertion loss + Cable loss
2. Emission level = Reading Value + Correction factor
3. Margin value = Emission level - Limit value



Product Name	Tablet	Test By	Waternil Guan
Test Model	INP-120Q	Test Date	2014/10/25
Test Mode	TX Mode	Temp. & Humidity	24°C, 53%

NEUTRAL



Remark:

1. Correction Factor = Insertion loss + Cable loss
2. Emission level = Reading Value + Correction factor
3. Margin value = Emission level – Limit value