

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: I46-M8

### EUT Specification

<b>EUT</b>	<b>Android tv box</b>
<b>Frequency band (Operating)</b>	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input checked="" type="checkbox"/> Others    BT4.0 BLE: 2.402GHz ~ 2.480GHz
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others _____
<b>Exposure classification</b>	<input type="checkbox"/> Occupational/Controlled exposure ( $S = 5\text{mW/cm}^2$ ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure ( $S=1\text{mW/cm}^2$ )
<b>Antenna diversity</b>	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	15.65dBm (0.0367W)
<b>Antenna gain (Max)</b>	0 dBi
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
<b>300-1500</b>	--	--	<b>F/300</b>	<b>6</b>
<b>1500-100000</b>	--	--	<b>5</b>	<b>6</b>
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
<b>300-1500</b>	--	--	<b>F/1500</b>	<b>6</b>
<b>1500-100000</b>	--	--	<b>1</b>	<b>30</b>

## Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$ = Power density in  $\text{mW/cm}^2$

$P_{out}$ =output power to antenna in  $\text{Mw}$

$G$ = gain of antenna in linear scale

$\pi=3.1416$

$R$ = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE,  $1\text{mW/cm}^2$ . If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Measurement Result

Operating Mode	Channel Frequency (MHz)	Measured Power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm ( $\text{mW/cm}^2$ )	Power density Limits ( $\text{mW/cm}^2$ )
802.11b	2412	15.21	$15.21 \pm 1$	16.21	0	0.0083	1
	2437	15.16	$15.16 \pm 1$	16.16	0	0.0082	1
	2462	15.57	$15.57 \pm 1$	16.57	0	0.0090	1
802.11g	2412	13.66	$13.66 \pm 1$	14.66	0	0.0058	1
	2437	15.65	$15.65 \pm 1$	16.65	0	0.0092	1
	2462	13.63	$13.63 \pm 1$	14.63	0	0.0058	1
802.11n (HT20)	2412	13.03	$13.03 \pm 1$	14.03	0	0.0050	1
	2437	15.32	$15.32 \pm 1$	16.32	0	0.0085	1
	2462	13.51	$13.51 \pm 1$	14.51	0	0.0056	1
802.11n (HT40)	2422	12.09	$12.09 \pm 1$	13.09	0	0.0041	1
	2437	14.36	$14.36 \pm 1$	15.36	0	0.0068	1
	2452	11.80	$11.80 \pm 1$	12.80	0	0.0038	1
BT4.0 BLE	2402	0.845	$0.845 \pm 1$	1.845	0	0.0003	1
	2440	1.115	$1.115 \pm 1$	2.115	0	0.0003	1
	2480	1.621	$1.621 \pm 1$	2.621	0	0.0004	1