



FCC PART 15E TEST REPORT FOR CERTIFICATION

On Behalf of

InFocus Corporation

65" LCD PC

Model Number: INF6502

FCC ID: I46INF6502

Prepared for : InFocus Corporation

13190 SW 68th Parkway Suite 200 Portland, OR 97223-8368
USA

Prepared By : Audix Technology (Shenzhen) Co., Ltd.

No. 6, Ke Feng Rd., 52 Block,
Shenzhen Science & Industrial Park,
Nantou, Shenzhen, Guangdong, China

Tel: (0755) 26639496

Report Number : ACS-F15315

Date of Test : Nov.06~18, 2015

Date of Report : Dec.18, 2015

TABLE OF CONTENTS

Description	Page
1. SUMMARY OF STANDARDS AND RESULTS	1-1
1.1. Description of Standards and Results	1-1
2. GENERAL INFORMATION	2-1
2.1. Description of Device (EUT)	2-1
2.2. Test Information	2-2
2.1. Block diagram of connection between the EUT and simulators	2-2
2.2. Test Facility	2-3
2.3. Measurement Uncertainty (95% confidence levels, k=2).....	2-3
3. POWER LINE CONDUCTED EMISSION TEST.....	3-1
3.1. Test Equipments	3-1
3.2. Block Diagram of Test Setup	3-1
3.3. Power Line Conducted Emission Test Limits	3-1
3.4. Configuration of EUT on Test.....	3-2
3.5. Operating Condition of EUT	3-2
3.6. Test Procedure	3-2
3.7. Power Line Conducted Emission Test Results	3-2
4. RADIATED EMISSION TEST	4-1
4.1. Test Equipment.....	4-1
4.2. Block Diagram of Test Setup	4-2
4.3. Radiated Emission Limit	4-3
4.4. EUT Configuration on Test.....	4-3
4.5. Operating Condition of EUT	4-4
4.6. Test Procedure	4-4
4.7. Radiated Emission Test Results	4-5
5. BAND EDGE COMPLIANCE TEST.....	5-1
5.1. Test Equipment.....	5-1
5.2. Limit	5-1
5.3. Test Produce	5-1
5.4. Test Results	5-1
6. 6dB&26dB Bandwidth Test	6-1
6.1. Test Equipment.....	6-1
6.2. Limit	6-1
6.3. Test Procedure	6-1
6.4. Test Results	6-1
7. OUTPUT POWER TEST	7-1
7.1. Test Equipment.....	7-1
7.2. Limit	7-1
7.3. Test Procedure	7-1
7.4. Test Results	7-2
8. SPECTRAL DENSITY TEST	8-1
8.1. Test Equipment.....	8-1
8.2. Limit	8-1
8.3. Test Procedure	8-1
8.4. Test Results	8-2
9. MPE ESTIMATION	9-1
9.1. Limit for General Population/ Uncontrolled Exposures	9-1
9.2. Estimation Result.....	9-1
10. ANTENNA REQUIREMENT	10-1
10.1. Standard Applicable	10-1



10.2.	Antenna Connected Construction	10-1
11.	DEVIATION TO TEST SPECIFICATIONS	11-1
12.	PHOTOGRAPH OF TEST.....	12-1
12.1.	Photos of Power Line Conducted Emission Test	12-1
12.2.	Photos of Radiated Emission Test	12-2
13.	PHOTOGRAPH OF EUT.....	13-1

TEST REPORT CERTIFICATION

Applicant : InFocus Corporation
Manufacturer : InFocus Corporation
EUT Description : 65" LCD PC
FCC ID : I46INF6502
(A) Model No. : INF6502
(B) Power Supply : N/A
(C) Test Voltage : AC 120V/60Hz

Tested for comply with:
FCC CFR47 Part 15 Subpart C: 2014

Test procedure used:
ANSI C63.10: 2013
KDB789033D01

The device described above is tested by AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. to confirm comply with all the FCC Part 15 Subpart E requirements. The test results are contained in this test report and AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. is assumed full responsibility for the accuracy and completeness of these tests. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC and IC requirements. This report contains data that are not covered by the NVLAP accreditation.

This Report is made under FCC Part 2.1075. No modifications were required during testing to bring this product into compliance.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Date of Test : Nov.06~18, 2015 Report of date: Dec.18, 2015

Prepared by : Cindy Zhu Reviewed by : Sunny Lu
Cindy Zhu / Assistant Sunny Lu / Assistant Manager



信華科技(深圳)有限公司

Audix Technology (Shenzhen) Co., Ltd.

EMC 部門報告專用章

Stamp only for EMC Dept. Report

Approved & Authorized Signer :

Signature:

David Jin / Manager

1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION		
Description of Test Item	Standard	Results
Power Line Conducted Emission	FCC Part 15: 15.207	PASS
Radiated Emission	FCC Part 15: 15.209	PASS
Band Edge Compliance	FCC Part 15: 15.407	PASS
6dB&26Bandwidth Test	FCC Part 15: 15.407(a)	PASS
Output Power Test	FCC Part 15: 15.407(a)	PASS
Power Spectral Density Test	FCC Part 15: 15.407(a)	PASS
Frequency Stability	FCC Part 15: 15.407(g)	N/A
Antenna requirement	FCC Part 15: 15.203	PASS
N/A is an abbreviation for Not Applicable.		

2. GENERAL INFORMATION

2.1. Description of Device (EUT)


Product Name	: 65" LCD PC
Model Number	: INF6502
FCC ID	: I46INF6502
Radio	: IEEE802.11 a/b/g/n; Bluetooth V3.0+EDR; Bluetooth V4.0
Operation Frequency	: IEEE 802.11a: 5180MHz—5240MHz; 5745MHz—5825MHz IEEE 802.11b: 2412MHz—2462MHz IEEE 802.11g: 2412MHz—2462MHz IEEE802.11n HT20: 2412MHz—2462MHz; 5180MHz—5240MHz; 5745MHz—5825MHz IEEE802.11n HT40: 2422MHz—2452MHz; 5190MHz—5230MHz; 5755MHz—5795MHz Bluetooth : 2402-2480MHz
Modulation Technology	: IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11a/g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20, HT40: OFDM (64QAM, 16QAM,QPSK,BPSK) Bluetooth V3.0+EDR: GFSK, $\pi/4$ DQPSK,8-DPSK Bluetooth V4.0:GFSK
Antenna Assembly Gain	: PIFA Antenna: 2.4GHz: 3dBi gain 5180~5240MHz: 3dBi gain 5745~5825MHz: 4dBi gain
Applicant	: InFocus Corporation 13190 SW 68th Parkway Suite 200 Portland, OR 97223-8368 USA
Manufacturer	: InFocus Corporation 13190 SW 68th Parkway Suite 200 Portland, OR 97223-8368 USA
Factory	: Hong Fu Jin Precision Industry (Wuhan) Co., Ltd. Foxconn Technological Park, 1#, 2nd Guang Gu Road,Donghu New Technology Development District, Wuhan City, Hubei Province, China
Power Cable	: Unshielded, Detachable, 2.0m
Control Pen	: Manufacturer: InFocus
Wireless Keyboard	: Manufacturer: InFocus M/N:KG-0917
Wireless Mouse	: Manufacturer: InFocus M/N:MG-0919
Date of Test	: Nov.06~18, 2015
Date of Receipt	: Nov.04, 2015

2.2.Test Information

A special test software was used to control EUT work in Continuous TX mode (nearly 100% duty cycle), and select test channel, wireless mode and data rate.

Tested mode, channel, and data rate information			
Mode	data rate (Mbps)(see Note)	Channel	Frequency (MHz)
IEEE 802.11a	6	Low :CH36	5180
	6	Middle: CH40	5200
	6	High: CH48	5240
	6	Low :CH149	5745
	6	Middle: CH157	5785
	6	High: CH165	5825
IEEE 802.11nHT20	MCS0	Low :CH36	5180
	MCS0	Middle: CH40	5200
	MCS0	High: CH48	5240
	MCS0	Low :CH149	5745
	MCS0	Middle: CH157	5785
	MCS0	High: CH165	5825
IEEE 802.11nHT40	MCS0	Low :CH38	5190
	MCS0	High: CH46	5230
	MCS0	Low :CH151	5755
	MCS0	High: CH159	5795

2.1.Block diagram of connection between the EUT and simulators



(EUT: 65" LCD PC)

2.2. Test Facility

Site Description

Name of Firm	:	Audix Technology (Shenzhen) Co., Ltd. No. 6, Ke Feng Rd., 52 Block, Shenzhen Science & Industrial Park, Nantou, Shenzhen, Guangdong, China
3m Anechoic Chamber	:	Certificated by FCC, USA Registration Number: 90454 Valid Date: Dec.30, 2017
3m & 10m Anechoic Chamber	:	Certificated by FCC, USA Registration Number: 794232 Valid Date: Jul.12, 2016
EMC Lab.	:	Certificated by Industry Canada Registration Number: IC 5183A-1 Valid Date: May.14, 2017
	:	Certificated by DAkkS, Germany Registration No: D-PL-12151-01-00 Valid Date: Dec.15, 2016
	:	Accredited by NVLAP, USA NVLAP Code: 200372-0 Valid Date: Mar.31, 2016

2.3. Measurement Uncertainty (95% confidence levels, k=2)


Test Item	Uncertainty
Uncertainty for Conduction emission test in No. 1 Conduction	3.4dB (150KHz to 30MHz)
Uncertainty for Radiation Emission test in 3m chamber	2.6 dB(30~200MHz, Polarization: H)
	2.6 dB(30~200MHz, Polarization: V)
	3.0 dB(200M~1GHz, Polarization: H)
	2.8 dB(200M~1GHz, Polarization: V)
Uncertainty for Radiation Emission test in 3m chamber (1GHz-18GHz)	6.3 dB (1~6GHz, Distance: 3m)
	5.7 dB (6~18GHz, Distance: 3m)
Uncertainty for Radiated Spurious Emission test in RF chamber	3.6 dB
Uncertainty for Conduction Spurious emission test	2.0 dB
Uncertainty for Output power test	0.8 dB
Uncertainty for Bandwidth test	83 kHz
Uncertainty for DC power test	0.1 %
Uncertainty for test site temperature and humidity	0.6
	3%

3. POWER LINE CONDUCTED EMISSION TEST

3.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	1# Shielding Room	AUDIX	N/A	N/A	Apr.17,15	1 Year
2.	Test Receiver	Rohde & Schwarz	ESCI	100842	Apr.28,15	1 Year
3.	L.I.S.N.#1	Rohde & Schwarz	ESH2-Z5	100429	Oct.18,15	1 Year
4.	L.I.S.N.#2	Kyoritsu	K NW-403D	8-1750-2	Apr.28,15	1 Year
5.	Terminator	Hubersuhner	50Ω	No.1	Apr.28,15	1 Year
6.	Terminator	Hubersuhner	50Ω	No.2	Apr.28,15	1 Year
7.	RF Cable	MIYAZAKI	3D-2W	No.1	Apr.28,15	1 Year
8.	Coaxial Switch	Anritsu	MP59B	6200766906	Apr.28,15	1 Year
9.	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	101838	Oct.17,15	1 Year
10.	Test Software	AUDIX	E3	6.100913a	N/A	N/A

3.2. Block Diagram of Test Setup



3.3. Power Line Conducted Emission Test Limits

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

3.4.Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

3.4.1.65" LCD PC (EUT)

Model Number : INF6502

Serial Number : N/A

3.4.2. Support Equipment: As Tested Supporting System Details, in Section 2.2.

3.5.Operating Condition of EUT

3.5.1. Setup the EUT and simulator as shown as Section 3.2.

3.5.2. Turned on the power of all equipment.

3.5.3. PC run test software to control EUT work in Tx mode(WiFi5GHz).

3.6.Test Procedure

The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power Via PC connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#). This provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs). The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Test.


The bandwidth of test receiver (R & S ESCI) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.7.Power Line Conducted Emission Test Results

PASS. (All emissions not reported below are too low against the prescribed limits.)

5180-5240MHz Band:




Trace: (Discrete)
Site no :1# Conduction
Dis./Lism :2014 ESH2-Z5 LINE
Limit :FCC PART 15 C
Env./Ins. :23.1°C/56%
EUT :65" LCD PC
Power Rating :AC 120V/60Hz
Test Mode :Tx Mode
M/N: INF6502

Data No :3
Engineer :Leo_Li

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.158	0.14	9.96	24.12	34.22	65.56	31.34	QP
2	0.302	0.13	9.95	21.03	31.11	63.54	32.43	QP
3	0.330	0.14	9.94	26.05	36.13	59.44	23.31	QP
4	1.810	0.18	9.97	27.74	37.89	56.00	18.11	QP
5	2.110	0.18	9.97	28.67	38.82	56.00	17.18	QP
6	3.491	0.22	9.99	29.26	39.47	56.00	16.53	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)+Reading.
2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.




Trace: (Discrete)
Site no :1# Conduction
Dis./Lism :2014 ESH2-Z5 NEUTRAL
Limit :FCC PART 15 C
Env./Ins. :23.1°C/56%
EUT :65" LCD PC
Power Rating :AC 120V/60Hz
Test Mode :Tx Mode
M/N: INF6502

Data No :4
Engineer :Leo_Li

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.194	0.13	9.95	25.54	35.62	63.84	28.22	QP
2	0.330	0.15	9.94	26.57	36.66	59.44	22.78	QP
3	1.602	0.18	9.96	27.98	38.12	56.00	17.88	QP
4	1.810	0.19	9.97	27.50	37.66	56.00	18.34	QP
5	3.207	0.23	9.98	29.78	39.99	56.00	16.01	QP
6	3.491	0.24	9.99	28.46	38.69	56.00	17.31	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)+Reading.
2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

5745-5825MHz Band:




Trace: (Discrete)
Site no :1# Conduction
Dis./Lism :2014 ESH2-Z5 LINE
Limit :FCC PART 15 C
Env./Ins. :23.1°C/56%
EUT :65" LCD PC
Power Rating :AC 120V/60Hz
Test Mode :Tx Mode
M/N: INF6502

Data No :6
Engineer :Leo_Li

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.158	0.14	9.96	25.07	35.17	65.56	30.39	QP
2	0.330	0.14	9.94	25.82	35.90	59.44	23.54	QP
3	1.519	0.18	9.96	27.59	37.73	56.00	18.27	QP
4	1.800	0.18	9.97	28.17	38.32	56.00	17.68	QP
5	2.077	0.18	9.97	27.94	38.09	56.00	17.91	QP
6	3.528	0.22	9.99	30.54	40.75	56.00	15.25	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)+Reading.
2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.



Trace: (Discrete)
Site no :1# Conduction
Dis./Lism :2014 ESH2-Z5 NEUTRAL
Limit :FCC PART 15 C
Env./Ins. :23.1°C/56%
EUT :65" LCD PC
Power Rating :AC 120V/60Hz
Test Mode :Tx Mode
M/N: INF6502

Data No :5
Engineer :Leo_Li

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.194	0.13	9.95	24.62	34.70	63.84	29.14	QP
2	0.330	0.15	9.94	25.98	36.07	59.44	23.37	QP
3	1.396	0.18	9.96	28.28	38.42	56.00	17.58	QP
4	2.110	0.20	9.97	28.56	38.73	56.00	17.27	QP
5	2.487	0.22	9.97	28.62	38.81	56.00	17.19	QP
6	3.454	0.24	9.99	28.47	38.70	56.00	17.30	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)+Reading.
2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

4. RADIATED EMISSION TEST

4.1. Test Equipment

4.1.1. For frequency range 30 MHz ~1000MHz (In Anechoic Chamber)


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	3#Chamber	AUDIX	N/A	N/A	Mar.28,15	1 Year
2.	EMI Spectrum	Agilent	E4407B	MY41440292	Apr.28,15	1 Year
3.	Test Receiver	Rohde & Schwarz	ESVS10	834468/011	Apr.28,15	1 Year
4.	Amplifier	HP	8447D	2648A04738	Apr.28,15	1 Year
5.	Trilog-Broadband Antenna	SCHWARZBECK	VULB 9168	9168-493	May.06,15	1 Year
6.	RF Cable	MIYAZAKI	CFD400-N W(3.5M)	No.3	Apr.28,15	1 Year
7.	RF Cable	MIYAZAKI	CFD400-L W(22M)	No.7	Apr.28,15	1 Year
8.	Coaxial Switch	Anritsu	MP59B	6201397222	Apr.28,15	1 Year
9.	Test Software	AUDIX	E3	6.2009-5-21a(n)	N/A	N/A

4.1.2. For frequency range 1GHz~40GHz (In Anechoic Chamber)


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	E4446A	US44300459	Apr.28,15	1 Year
2.	Horn Antenna	ETC	MCTD 1209	DRH15F03007	Feb.03,15	1 Year
3.	Amplifier	Agilent	8449B	3008A02495	Apr.28,15	1 Year
4.	RF Cable	Hubersuhner	SUCOFLEX106	77977/6	Apr.28,15	1 Year
5.	Horn Antenna	ETS	3116	00060088	Nov.18.15	1 Year
6.	Test Software	AUDIX	E3	6.2009-5-21a(n)	N/A	N/A

4.2. Block Diagram of Test Setup

For frequency range 30MHz-1000MHz



For frequency range 1GHz-40GHz



4.3.Radiated Emission Limit

For transmitters operating in the 5.15-5.25 GHz; 5.25-5.35GHz; 5.47-5.725GHz, 5.725-5.850GHz band: all emissions outside of those band shall not exceed an EIRP of -27 dBm/MHz.Unwanted emissions below 1 GHz and those emissions appearing within 15.205 restricted frequency bands must comply with the general field strength limits set forth in Section 15.209

4.3.1.15.209 limits

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Remark : (1) Emission level dBμV = 20 log Emission level μV/m

(2) The smaller limit shall apply at the cross point between two frequency bands.

(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

4.3.2.15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

4.4.EUT Configuration on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

4.4.1.65" LCD PC (EUT)

Model Number : INF6502

Serial Number : N/A

4.4.2.Support Equipment: As Tested Supporting System Details, in Section 2.2.

4.5. Operating Condition of EUT

4.5.1. Setup the EUT and simulator as shown as Section 4.2.

4.5.2. Turned on the power of all equipment.

4.5.3. Let EUT work in Tx mode.

4.6. Test Procedure

EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground for frequency 30MHz~1000MHz, 1.5 meter high above ground for frequency above 1GHz and put the absorbing with 2.4m(L)*2.4m(W)*0.3m(H) on the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna for frequency 30MHz~1000MHz, and the Horn antenna is used as receiving antenna for frequency above 1GHz. Both horizontal and vertical polarization of the antenna is set on Test. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.10-2013 on radiated emission Test.

For emissions below 1GHz and those emissions appearing within 15.205 restricted frequency bands use below procedure:

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's VBW is set at 1MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz

For the emissions above 1GHz and not appearing within 15.205 restricted frequency bands use below procedure:

- (1). The maximum emission at 3m distance was measured and recorded with receive antenna in both vertical and horizontal by rotating the turntable and by lowering the receive antenna.
- (2). The EUT was then removed and replaced with a substitution antenna in the same position and the substitution antenna must have the same polarization with the receive antenna.
- (3). A signal which have the same frequency obtained in step 2 was fed to the substitution, the receive antenna was raised and lowered to obtain a maximum reading at the test receiver, the level of the signal generator was adjusted until the measured field strength level in step 2 was obtained, recorded the level of the signal generator.
- (4). Repeated step 4 with both antenna polarizations
- (5). The spurious emissions is equal to the power supplied by the signal generator and corrections due to the gain of the substitution antenna and the cable loss between the signal generator and the substitution antenna. or use procedure (6).
- (6). Per KDB789033 clause H 2)d). if the test distance is 3m, the $EIRP(dBm) = E(dBuV/m) - 95.2$ Get the result of all unwanted emission outside the restricted band is less than the -27dBm/MHz.

We had checked frequency range that is 30MHz to 10th harmonic (40GHz) and no any emissions were found from 18GHz to 40GHz, so the radiated emission from 18GHz to 40GHz were not record.


4.7. Radiated Emission Test Results

PASS.


All the emissions from 30MHz to 1 GHz were comply with 15.209 limits.
All other emission comply with 15.407 (b)(1) requirements.

Duty cycle

5180-5240MHz Band:




5745-5825MHz Band:




Note: The Duty Cycle is close to 100%.

5180-5240MHz Band: Frequency: 30MHz~1GHz



No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	154.160	11.59	1.32	27.67	40.58	43.50	2.92	QP
2	241.460	12.67	1.65	20.36	34.68	46.00	11.32	QP
3	532.460	18.49	2.60	13.80	34.89	46.00	11.11	QP
4	720.640	20.11	3.07	21.74	44.92	46.00	1.08	QP
5	742.950	20.53	3.12	18.76	42.41	46.00	3.59	QP
6	961.200	22.60	3.62	15.43	41.65	54.00	12.35	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	136.700	12.43	1.27	22.48	36.18	43.50	7.32	QP
2	154.160	11.59	1.32	23.26	36.17	43.50	7.33	QP
3	241.460	12.67	1.65	20.95	35.27	46.00	10.73	QP
4	532.460	18.49	2.60	14.15	35.24	46.00	10.76	QP
5	720.640	20.11	3.07	13.18	36.36	46.00	9.64	QP
6	961.200	22.60	3.62	12.93	39.15	54.00	14.85	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Frequency: 1GHz~18GHz




Site no. : 3m Chamber Data no. : 1
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5180MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 2
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5180MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5180.000	33.71	9.63	35.37	85.79	93.76	74.00	-19.76	Peak
2	10360.000	38.30	13.71	35.61	31.22	47.62	54.00	6.38	Average
3	10360.000	38.30	13.71	35.61	45.38	61.78	74.00	12.22	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 3
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5180MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 4
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5180MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5180.000	33.71	9.63	35.37	91.35	99.32	74.00	-25.32	Peak
2	10360.000	38.30	13.71	35.61	31.28	47.68	54.00	6.32	Average
3	10360.000	38.30	13.71	35.61	43.44	59.84	74.00	14.16	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 9
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5240MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 10
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5240MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5240.000	33.62	9.66	35.34	99.64	107.58	74.00	-33.58	Peak
2	10480.000	38.47	13.81	35.58	30.56	47.26	54.00	6.74	Average
3	10480.000	38.47	13.81	35.58	44.38	61.08	74.00	12.92	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 11
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5240MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 12
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5240MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5240.000	33.62	9.66	35.34	95.71	103.65	74.00	-29.65	Peak
2	10480.000	38.47	13.81	35.58	30.36	47.06	54.00	6.94	Average
3	10480.000	38.47	13.81	35.58	45.29	61.99	74.00	12.01	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 17
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5200MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 18
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5200MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5200.000	33.68	9.64	35.36	91.62	99.58	74.00	-25.58	Peak
2	10400.000	38.36	13.74	35.60	30.30	46.80	54.00	7.20	Average
3	10400.000	38.36	13.74	35.60	42.56	59.06	74.00	14.94	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 19
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5200MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 20
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5200MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5200.000	33.68	9.64	35.36	85.39	93.35	74.00	-19.35	Peak
2	10400.000	38.36	13.74	35.60	30.38	46.88	54.00	7.12	Average
3	10400.000	38.36	13.74	35.60	45.41	61.91	74.00	12.09	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 21
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5180MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 22
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5180MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5180.000	33.71	9.63	35.37	85.83	93.80	74.00	-19.80	Peak
2	10360.000	38.30	13.71	35.61	31.64	49.04	54.00	5.96	Average
3	10360.000	38.30	13.71	35.61	45.48	61.88	74.00	12.12	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




Site no. : 3m Chamber Data no. : 23
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5180MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 24
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5180MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5180.000	33.71	9.63	35.37	88.99	96.96	74.00	-22.96	Peak
2	10360.000	38.30	13.71	35.61	31.29	47.69	54.00	6.31	Average
3	10360.000	38.30	13.71	35.61	45.75	62.15	74.00	11.85	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




Site no. : 3m Chamber Data no. : 29
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5200MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 30
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5200MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5200.000	33.68	9.64	35.36	85.26	93.22	74.00	-19.22	Peak
2	10400.000	38.36	13.74	35.60	30.41	46.91	54.00	7.09	Average
3	10400.000	38.36	13.74	35.60	45.38	61.88	74.00	12.12	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




Site no. : 3m Chamber Data no. : 31
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5200MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 32
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5200MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5200.000	33.68	9.64	35.36	90.12	98.08	74.00	-24.08	Peak
2	10400.000	38.36	13.74	35.60	32.15	48.65	54.00	5.35	Average
3	10400.000	38.36	13.74	35.60	46.48	62.98	74.00	11.02	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




Site no. : 3m Chamber Data no. : 33
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5240MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 34
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5240MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5240.000	33.62	9.66	35.34	86.90	94.84	74.00	-20.84	Peak
2	10480.000	38.47	13.81	35.58	30.45	47.15	54.00	6.85	Average
3	10480.000	38.47	13.81	35.58	45.41	62.11	74.00	11.89	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 35
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5240MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 36
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5240MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5240.000	33.62	9.66	35.34	90.28	98.22	74.00	-24.22	Peak
2	10480.000	38.47	13.81	35.58	31.38	48.08	54.00	5.92	Average
3	10480.000	38.47	13.81	35.58	44.62	61.32	74.00	12.68	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 41
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5190MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 42
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5190MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5190.000	33.70	9.63	35.36	80.44	88.41	74.00	-14.41	Peak
2	10380.000	38.33	13.73	35.61	31.29	47.74	54.00	6.26	Average
3	10380.000	38.33	13.73	35.61	45.41	61.86	74.00	12.14	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




Site no. : 3m Chamber Data no. : 43
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5190MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 44
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5190MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5190.000	33.70	9.63	35.36	90.20	98.17	74.00	-24.17	Peak
2	10380.000	38.33	13.73	35.61	30.52	46.97	54.00	7.03	Average
3	10380.000	38.33	13.73	35.61	45.33	61.78	74.00	12.22	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




Site no. : 3m Chamber Data no. : 49
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5230MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 50
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5230MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5230.000	33.63	9.65	35.35	85.91	93.84	74.00	-19.84	Peak
2	10460.000	38.44	13.78	35.59	34.53	51.16	54.00	2.84	Average
3	10460.000	38.44	13.78	35.59	46.49	63.12	74.00	10.88	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



Site no. : 3m Chamber Data no. : 51
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5230MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 52
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5230MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5230.000	33.63	9.65	35.35	90.68	98.61	74.00	-24.61	Peak
2	10460.000	38.44	13.78	35.59	31.72	48.35	54.00	5.65	Average
3	10460.000	38.44	13.78	35.59	46.14	62.77	74.00	11.23	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.

5745-5825MHz Band: Frequency: 30MHz~1GHz



No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	154.160	11.59	1.32	27.85	40.76	43.50	2.74	QP
2	532.460	18.49	2.60	14.80	35.89	46.00	10.11	QP
3	720.640	20.11	3.07	21.63	44.81	46.00	1.19	QP
4	742.950	20.53	3.12	18.34	41.99	46.00	4.01	QP
5	825.400	21.14	3.32	12.85	37.31	46.00	8.69	QP
6	961.200	22.60	3.62	14.59	40.81	54.00	13.19	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. The emission levels that are 20dB below the official limit are not reported.




No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	136.700	12.43	1.27	23.48	37.18	43.50	6.32	QP
2	154.160	11.59	1.32	23.26	36.17	43.50	7.33	QP
3	241.460	12.67	1.65	21.95	36.27	46.00	9.73	QP
4	720.640	20.11	3.07	14.18	37.36	46.00	8.64	QP
5	742.950	20.53	3.12	12.36	36.01	46.00	9.99	QP
6	961.200	22.60	3.62	13.93	40.15	54.00	13.85	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Frequency: 1GHz~18GHz




Site no. : 3m Chamber Data no. : 57
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5745MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 58
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5745MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5745.000	33.44	9.90	35.11	89.03	97.26	74.00	-23.26	Peak
2	11490.000	38.31	14.54	35.33	30.09	47.61	54.00	6.39	Average
3	11490.000	38.31	14.54	35.33	46.39	63.91	74.00	10.09	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 59
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5745MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 60
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5745MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5745.000	33.44	9.90	35.11	90.61	98.84	74.00	-24.84	Peak
2	11490.000	38.31	14.54	35.33	29.82	47.34	54.00	6.66	Average
3	11490.000	38.31	14.54	35.33	45.30	62.82	74.00	11.18	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 65
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5785MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 66
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5785MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5785.000	33.49	9.91	35.10	88.34	96.64	74.00	-22.64	Peak
2	11570.000	38.26	14.60	35.31	29.84	47.39	54.00	6.61	Average
3	11570.000	38.26	14.60	35.31	44.91	62.46	74.00	11.54	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




Site no. : 3m Chamber Data no. : 67
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5785MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 68
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5785MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5785.000	33.49	9.91	35.10	91.08	99.38	74.00	-25.38	Peak
2	11570.000	38.26	14.60	35.31	29.57	47.12	54.00	6.88	Average
3	11570.000	38.26	14.60	35.31	44.41	61.96	74.00	12.04	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




Site no. : 3m Chamber Data no. : 69
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5825MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 70
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5825MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss factor (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5825.000	33.53	9.93	35.08	86.91	95.29	74.00	-21.29	Peak
2	11650.000	38.21	14.66	35.29	29.81	47.39	54.00	6.61	Average
3	11650.000	38.21	14.66	35.29	44.41	61.99	74.00	12.01	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 71
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5825MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 72
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5825MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss factor (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5825.000	33.53	9.93	35.08	89.64	98.02	74.00	-24.02	Peak
2	11650.000	38.21	14.66	35.29	29.33	46.91	54.00	7.09	Average
3	11650.000	38.21	14.66	35.29	44.31	61.89	74.00	12.11	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 77
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5745MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 78
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5745MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5745.000	33.44	9.90	35.11	87.36	95.59	74.00	-21.59	Peak
2	11490.000	38.31	14.54	35.33	29.16	46.68	54.00	7.32	Average
3	11490.000	38.31	14.54	35.33	44.79	62.31	74.00	11.69	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




Site no. : 3m Chamber Data no. : 79
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5745MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 80
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5745MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5745.000	33.44	9.90	35.11	88.75	96.98	74.00	-22.98	Peak
2	11490.000	38.31	14.54	35.33	28.96	46.48	54.00	7.52	Average
3	11490.000	38.31	14.54	35.33	44.42	61.94	74.00	12.06	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




Site no. : 3m Chamber Data no. : 85
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5785MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 86
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5785MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss factor (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5785.000	33.49	9.91	35.10	86.91	95.21	74.00	-21.21	Peak
2	11570.000	38.26	14.60	35.31	29.36	46.91	54.00	7.09	Average
3	11570.000	38.26	14.60	35.31	44.51	62.06	74.00	11.94	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 87
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5785MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 88
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5785MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss factor (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5785.000	33.49	9.91	35.10	88.70	97.00	74.00	-23.00	Peak
2	11570.000	38.26	14.60	35.31	29.11	46.66	54.00	7.34	Average
3	11570.000	38.26	14.60	35.31	44.42	61.97	74.00	12.03	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 89
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5825MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 90
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5825MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss factor (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5825.000	33.53	9.93	35.08	87.42	95.80	74.00	-21.80	Peak
2	11650.000	38.21	14.66	35.29	28.73	46.31	54.00	7.69	Average
3	11650.000	38.21	14.66	35.29	43.52	61.10	74.00	12.90	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




Site no. : 3m Chamber Data no. : 91
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5825MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 92
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5825MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss factor (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5825.000	33.53	9.93	35.08	91.38	99.76	74.00	-25.76	Peak
2	11650.000	38.21	14.66	35.29	29.61	47.19	54.00	6.81	Average
3	11650.000	38.21	14.66	35.29	44.36	61.94	74.00	12.06	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




Site no. : 3m Chamber Data no. : 97
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5755 MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 98
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5755 MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5755.000	33.46	9.91	35.11	87.91	96.17	74.00	-22.17	Peak
2	11510.000	38.29	14.56	35.33	29.36	46.88	54.00	7.12	Average
3	11510.000	38.29	14.56	35.33	43.65	61.17	74.00	12.83	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




Site no. : 3m Chamber Data no. : 99
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5755MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 100
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5755MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5755.000	33.46	9.91	35.11	89.81	98.07	74.00	-24.07	Peak
2	11510.000	38.29	14.56	35.33	29.26	46.78	54.00	7.22	Average
3	11510.000	38.29	14.56	35.33	43.38	60.90	74.00	13.10	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




Site no. : 3m Chamber Data no. : 105
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5795MHz Tx
 INF6502




Site no. : 3m Chamber Data no. : 106
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5795MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss factor (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5795.000	33.49	9.92	35.09	86.83	95.15	74.00	-21.15	Peak
2	11590.000	38.25	14.61	35.30	29.28	46.84	54.00	7.16	Average
3	11590.000	38.25	14.61	35.30	43.27	60.83	74.00	13.17	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



Site no. : 3m Chamber Data no. : 107
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5795MHz Tx
 INF6502



Site no. : 3m Chamber Data no. : 108
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5795MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss factor (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5795.000	33.49	9.92	35.09	90.27	98.59	74.00	-24.59	Peak
2	11590.000	38.25	14.61	35.30	29.36	46.92	54.00	7.08	Average
3	11590.000	38.25	14.61	35.30	44.31	61.87	74.00	12.13	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.

5. BAND EDGE COMPLIANCE TEST

5.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4446A	US44300459	Apr.28,15	1 Year
2.	Amp	HP	8449B	3008A02495	Apr.28,15	1 Year
3.	Horn Antenna	ETC	MCTD 1209	DRH15F03007	Feb.03,15	1 Year
4.	HF Cable	Hubersuhner	Sucoflex104	274094/4	Apr.28,15	1 Year

5.2. Limit

For transmitters operating in the band 5150-5250 MHz, all emissions outside the band 5150-5350 MHz shall not exceed -27 dBm/MHz e.i.r.p.

For devices with both operating frequencies and channel bandwidths contained within the band 5250-5350 MHz,

All emissions outside the band 5250-5350 MHz shall not exceed -27 dBm/MHz e.i.r.p.

For transmitters operating in the band 5470-5725MHz, Emissions outside the band 5470-5725 MHz shall not exceed -27 dBm/MHz e.i.r.p.

For the band 5725-5850 MHz, emissions at frequencies from the band edges to 10 MHz above or below the band edges shall not exceed -17 dBm/MHz e.i.r.p.

For emissions at frequencies more than 10 MHz above or below the band edges, the emissions power shall not exceed -27 dBm/MHz.


5.3. Test Produce

1. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=1MHz; VBW=3MHz; Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz; VBW=10Hz; Sweep=AUTO
5. Per KDB789033 clause H 2)d).if the test distance is 3m,the EIRP(dBm)=E(dBuv/m)-95.2
Get the final compare with limit.

5.4. Test Results

Pass (The testing data was attached in the next pages.)


5180-5240MHz Band:



Site no. : 3m Chamber Data no. : 5
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5180MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5139.400	33.78	9.61	35.38	50.18	58.19	74.00	15.81	Peak
2	5150.000	33.76	9.62	35.38	48.12	56.12	74.00	17.88	Peak
3	5181.100	33.71	9.63	35.37	90.49	98.46	74.00	-24.46	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 6
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5180MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5140.790	33.77	9.61	35.38	34.05	42.05	54.00	11.95	Average
2	5150.000	33.76	9.62	35.38	31.75	39.75	54.00	14.25	Average
3	5181.100	33.71	9.63	35.37	78.46	86.43	54.00	-32.43	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 7
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5180MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4611.200	33.38	9.36	35.63	45.87	52.98	74.00	21.02	Peak
2	5150.000	33.76	9.62	35.38	42.72	50.72	74.00	23.28	Peak
3	5181.100	33.71	9.63	35.37	84.36	92.33	74.00	-18.33	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 8
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5180MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5140.790	33.77	9.61	35.38	31.88	39.88	54.00	14.12	Average
2	5150.000	33.76	9.62	35.38	31.02	39.02	54.00	14.98	Average
3	5181.100	33.71	9.63	35.37	73.45	81.42	54.00	-27.42	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 13
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5240MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5237.250	33.62	9.66	35.35	86.95	94.88	74.00	-20.88	Peak
2	5350.000	33.44	9.71	35.29	42.63	50.49	74.00	23.51	Peak
3	5453.340	33.27	9.76	35.25	44.33	52.11	74.00	21.89	Peak
4	5460.000	33.26	9.76	35.25	42.39	50.16	74.00	23.84	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 14
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5240MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5240.925	33.61	9.66	35.34	76.09	84.02	54.00	-30.02	Average
2	5350.000	33.44	9.71	35.29	31.74	39.60	54.00	14.40	Average
3	5460.000	33.26	9.76	35.25	31.83	39.60	54.00	14.40	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 15
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5240MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5240.925	33.61	9.66	35.34	91.46	99.39	74.00	-25.39	Peak
2	5350.000	33.44	9.71	35.29	43.86	51.72	74.00	22.28	Peak
3	5355.585	33.43	9.71	35.29	45.37	53.22	74.00	20.78	Peak
4	5460.000	33.26	9.76	35.25	43.76	51.53	74.00	22.47	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 16
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5240MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5234.310	33.63	9.66	35.35	80.11	88.05	54.00	-34.05	Average
2	5350.000	33.44	9.71	35.29	32.08	39.94	54.00	14.06	Average
3	5460.000	33.26	9.76	35.25	31.86	39.63	54.00	14.37	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 25
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5180MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5141.584	33.77	9.61	35.38	48.74	56.74	74.00	17.26	Peak
2	5150.000	33.76	9.62	35.38	46.38	54.38	74.00	19.62	Peak
3	5182.176	33.71	9.63	35.37	86.96	96.93	74.00	-22.93	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 26
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5180MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5140.896	33.77	9.61	35.38	36.57	44.57	54.00	9.43	Average
2	5150.000	33.76	9.62	35.38	34.58	42.58	54.00	11.42	Average
3	5180.800	33.71	9.63	35.37	80.86	88.83	54.00	-34.83	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 27
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5180MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5136.080	33.78	9.61	35.39	34.11	42.11	54.00	11.89	Average
2	5150.000	33.76	9.62	35.38	33.27	41.27	54.00	12.73	Average
3	5179.424	33.71	9.63	35.37	74.76	82.73	54.00	-28.73	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 28
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5180MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5140.896	33.77	9.61	35.38	44.53	52.53	74.00	21.47	Peak
2	5150.000	33.76	9.62	35.38	42.55	50.55	74.00	23.45	Peak
3	5178.736	33.71	9.63	35.37	82.76	90.73	74.00	-16.73	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 37
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5240MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5238.475	33.62	9.66	35.34	90.03	97.97	74.00	-23.97	Peak
2	5350.000	33.44	9.71	35.29	42.79	50.65	74.00	23.35	Peak
3	5433.250	33.31	9.75	35.26	44.26	52.06	74.00	21.94	Peak
4	5460.000	33.26	9.76	35.25	42.59	50.36	74.00	23.64	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Ant Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 38
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5240MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5239.210	33.62	9.66	35.34	81.89	89.83	54.00	-35.83	Average
2	5350.000	33.44	9.71	35.29	34.16	42.02	54.00	11.98	Average
3	5396.990	33.36	9.74	35.27	34.25	42.08	54.00	11.92	Average
4	5460.000	33.26	9.76	35.25	34.30	42.07	54.00	11.93	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Ant Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 39
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5240MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5240.925	33.61	9.66	35.34	78.65	86.58	54.00	-32.58	Average
2	5350.000	33.44	9.71	35.29	33.95	41.81	54.00	12.19	Average
3	5449.665	33.28	9.76	35.25	34.92	42.71	54.00	11.29	Average
4	5460.000	33.26	9.76	35.25	34.62	42.39	54.00	11.61	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Ant Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 40
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5240MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5238.475	33.62	9.66	35.34	86.72	94.66	74.00	-20.66	Peak
2	5350.000	33.44	9.71	35.29	42.63	50.49	74.00	23.51	Peak
3	5356.565	33.43	9.71	35.29	43.75	51.60	74.00	22.40	Peak
4	5460.000	33.26	9.76	35.25	43.20	50.97	74.00	23.03	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Ant Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 45
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5190MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5148.505	33.76	9.62	35.38	47.92	55.92	74.00	18.08	Peak
2	5150.000	33.76	9.62	35.38	47.14	55.14	74.00	18.86	Peak
3	5188.545	33.70	9.63	35.36	89.11	97.08	74.00	-23.08	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 46
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5190MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5149.500	33.77	9.62	35.38	36.52	44.53	54.00	9.47	Average
2	5150.000	33.76	9.62	35.38	36.14	44.14	54.00	9.86	Peak
3	5188.545	33.70	9.63	35.36	80.18	88.15	54.00	-34.15	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 47
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5190MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4750.250	33.60	9.43	35.56	45.38	52.85	74.00	21.15	Peak
2	5150.000	33.76	9.62	35.38	43.40	51.40	74.00	22.60	Peak
3	5195.695	33.69	9.63	35.36	81.92	89.88	74.00	-15.88	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 48
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5190MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5150.000	33.76	9.62	35.38	34.44	42.44	54.00	11.56	Average
2	5188.545	33.70	9.63	35.36	74.36	82.33	54.00	-28.33	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 53
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5230MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5232.030	33.63	9.65	35.35	86.13	94.06	74.00	-20.06	Peak
2	5350.000	33.44	9.71	35.29	42.41	50.27	74.00	23.73	Peak
3	5407.725	33.35	9.74	35.27	44.82	52.64	74.00	21.36	Peak
4	5460.000	33.26	9.76	35.25	41.57	49.34	74.00	24.66	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 54
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5230MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5229.380	33.63	9.65	35.35	78.53	86.46	54.00	-32.46	Average
2	5350.000	33.44	9.71	35.29	34.05	41.91	54.00	12.09	Average
3	5451.980	33.28	9.76	35.25	34.92	42.71	54.00	11.29	Average
4	5460.000	33.26	9.76	35.25	34.42	42.19	54.00	11.81	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 55
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5230MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5230.970	33.63	9.65	35.35	90.01	97.94	74.00	-23.94	Average
2	5350.000	33.44	9.71	35.29	43.11	50.97	74.00	23.03	Peak
3	5396.330	33.37	9.74	35.27	44.01	51.85	74.00	22.15	Average
4	5460.000	33.26	9.76	35.25	43.49	51.26	74.00	22.74	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 56
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5230MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5231.500	33.63	9.65	35.35	82.69	90.82	54.00	-36.82	Average
2	5350.000	33.44	9.71	35.29	34.21	42.07	54.00	11.93	Average
3	5446.945	33.28	9.75	35.25	35.06	42.84	54.00	11.16	Average
4	5460.000	33.26	9.76	35.25	34.53	42.30	54.00	11.70	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.


5745-5825MHz Band:



Site no. : 3m Chamber Data no. : 61
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5745MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5418.880	33.33	9.74	35.26	44.24	52.05	74.00	21.95	Peak
2	5459.880	33.26	9.76	35.25	43.77	51.54	74.00	22.46	Peak
3	5715.000	33.42	9.88	35.12	46.47	54.65	74.00	19.35	Peak
4	5725.000	33.42	9.89	35.12	51.32	59.51	74.00	14.49	Peak
5	5745.650	33.45	9.90	35.11	89.82	98.06	74.00	-24.06	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 62
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5745MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5453.730	33.27	9.76	35.25	34.93	42.71	54.00	11.29	Average
2	5459.880	33.26	9.76	35.25	34.72	42.49	54.00	11.51	Average
3	5715.000	33.42	9.88	35.12	36.02	44.20	54.00	9.80	Average
4	5725.000	33.42	9.89	35.12	40.05	48.24	54.00	5.76	Average
5	5744.420	33.44	9.90	35.11	81.92	90.15	54.00	-36.15	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 63
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5745MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5454.550	33.27	9.76	35.25	44.22	52.00	74.00	22.00	Peak
2	5459.880	33.26	9.76	35.25	42.53	50.30	74.00	23.70	Peak
3	5715.000	33.42	9.88	35.12	45.40	53.58	74.00	20.42	Peak
4	5725.000	33.42	9.89	35.12	57.03	65.22	74.00	8.78	Peak
5	5740.320	33.44	9.90	35.11	90.67	98.90	74.00	-24.90	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 64
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5745MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5438.970	33.30	9.75	35.25	34.82	42.62	54.00	11.38	Average
2	5460.000	33.26	9.76	35.25	34.30	42.07	54.00	11.93	Average
3	5715.000	33.42	9.88	35.12	36.63	44.81	54.00	9.19	Average
4	5725.000	33.42	9.89	35.12	42.51	50.70	54.00	3.30	Average
5	5744.420	33.44	9.90	35.11	83.71	91.94	54.00	-37.94	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 73
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5825MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5828.340	33.53	9.94	35.08	87.42	95.81	74.00	-21.81	Peak
2	5850.000	33.55	9.95	35.07	46.23	54.66	74.00	19.34	Peak
3	5860.000	33.56	9.95	35.07	45.46	53.90	74.00	20.10	Peak
4	7250.000	36.00	10.74	35.50	43.69	54.93	74.00	19.07	Peak
5	7695.540	36.45	11.18	35.68	44.67	56.62	74.00	17.38	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Ant Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 74
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5825MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5824.450	33.52	9.93	35.08	79.90	88.27	54.00	-34.27	Average
2	5850.000	33.55	9.95	35.07	35.03	43.46	54.00	10.54	Average
3	5860.000	33.56	9.95	35.07	35.68	44.12	54.00	9.88	Average
4	7250.000	36.00	10.74	35.50	33.59	44.83	54.00	9.17	Average
5	7726.660	36.51	11.20	35.69	34.72	46.74	54.00	7.26	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Ant Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 75
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5825MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5824.450	33.52	9.93	35.08	89.46	97.83	74.00	-23.83	Peak
2	5850.000	33.55	9.95	35.07	46.32	56.75	74.00	17.25	Peak
3	5860.000	33.56	9.95	35.07	45.81	54.25	74.00	19.75	Peak
4	7250.000	36.00	10.74	35.50	43.15	54.39	74.00	19.61	Peak
5	7637.190	36.35	11.11	35.65	44.82	56.63	74.00	17.37	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Ant Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 76
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11a 5825MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5824.450	33.52	9.93	35.08	82.74	91.11	54.00	-37.11	Average
2	5850.000	33.55	9.95	35.07	36.52	44.95	54.00	9.05	Average
3	5860.000	33.56	9.95	35.07	36.58	45.02	54.00	8.98	Average
4	7250.000	36.00	10.74	35.50	33.45	44.69	54.00	9.31	Average
5	7724.715	36.50	11.20	35.69	34.66	46.67	54.00	7.33	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Ant Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 81
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5745MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5436.000	33.30	9.75	35.26	44.41	52.20	74.00	21.80	Peak
2	5460.080	33.26	9.76	35.25	43.74	51.51	74.00	22.49	Peak
3	5715.000	33.42	9.88	35.12	45.28	53.46	74.00	20.54	Peak
4	5724.100	33.42	9.89	35.12	50.76	58.95	74.00	15.05	Peak
5	5725.000	33.42	9.89	35.12	49.82	58.01	74.00	15.99	Peak
6	5743.450	33.44	9.90	35.11	86.54	94.77	74.00	-20.77	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 82
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5745MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5449.220	33.28	9.76	35.25	34.95	42.74	54.00	11.26	Average
2	5459.880	33.26	9.76	35.25	34.16	41.93	54.00	12.07	Average
3	5715.000	33.42	9.88	35.12	34.57	42.75	54.00	11.25	Average
4	5723.920	33.42	9.89	35.12	36.26	44.45	54.00	9.55	Average
5	5725.000	33.42	9.89	35.12	36.18	44.37	54.00	9.63	Average
6	5744.420	33.44	9.90	35.11	76.62	84.85	54.00	-30.85	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 83
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5745MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5416.830	33.33	9.74	35.26	43.99	51.80	74.00	22.20	Peak
2	5460.000	33.26	9.76	35.25	42.97	50.74	74.00	23.26	Peak
3	5715.000	33.42	9.88	35.12	44.17	52.35	74.00	21.65	Peak
4	5723.920	33.42	9.89	35.12	57.74	65.93	74.00	8.07	Peak
5	5725.000	33.42	9.89	35.12	50.92	59.11	74.00	14.89	Peak
6	5744.830	33.44	9.90	35.11	88.54	96.77	74.00	-22.77	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 84
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5745MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5453.320	33.27	9.76	35.25	34.82	42.60	54.00	11.40	Average
2	5459.880	33.26	9.76	35.25	34.10	41.87	54.00	12.13	Average
3	5715.000	33.42	9.88	35.12	35.92	44.10	54.00	9.90	Average
4	5725.000	33.42	9.89	35.12	40.82	49.01	54.00	4.99	Average
5	5744.420	33.44	9.90	35.11	82.80	91.03	54.00	-37.03	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 93
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5825MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5820.560	33.52	9.93	35.08	89.13	97.50	74.00	-23.50	Peak
2	5850.000	33.55	9.95	35.07	47.12	55.55	74.00	18.45	Peak
3	5860.000	33.56	9.95	35.07	46.09	54.53	74.00	19.47	Peak
4	7250.000	36.00	10.74	35.50	42.73	53.97	74.00	20.03	Peak
5	7672.200	36.41	11.15	35.67	44.52	56.41	74.00	17.59	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 94
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5825MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5824.450	33.52	9.93	35.08	79.37	87.74	54.00	-33.74	Average
2	5850.000	33.55	9.95	35.07	35.42	43.85	54.00	10.15	Average
3	5860.000	33.56	9.95	35.07	35.89	44.33	54.00	9.67	Average
4	7250.000	36.00	10.74	35.50	33.45	44.69	54.00	9.31	Average
5	7685.815	36.43	11.16	35.67	35.03	46.95	54.00	7.05	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 95
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5825MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5820.560	33.52	9.93	35.08	85.51	93.88	74.00	-19.88	Peak
2	5850.000	33.55	9.95	35.07	45.62	54.05	74.00	19.95	Peak
3	5860.000	33.56	9.95	35.07	44.65	53.09	74.00	20.91	Peak
4	7250.000	36.00	10.74	35.50	42.48	53.72	74.00	20.28	Peak
5	7619.685	36.32	11.09	35.65	44.63	56.39	74.00	17.61	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 96
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 5825MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5824.450	33.52	9.93	35.08	78.22	86.59	54.00	-32.59	Average
2	5850.000	33.55	9.95	35.07	35.15	43.58	54.00	10.42	Average
3	5860.000	33.56	9.95	35.07	34.98	43.42	54.00	10.58	Average
4	7250.000	36.00	10.74	35.50	33.61	44.85	54.00	9.15	Average
5	7701.375	36.46	11.18	35.68	34.63	46.59	54.00	7.41	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 101
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5755 MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5375.800	33.40	9.72	35.28	44.12	51.96	74.00	22.04	Peak
2	5460.000	33.26	9.76	35.25	43.97	51.74	74.00	22.26	Peak
3	5715.000	33.42	9.88	35.12	49.10	57.28	74.00	16.72	Peak
4	5722.810	33.42	9.89	35.12	56.81	65.00	74.00	9.00	Peak
5	5725.000	33.42	9.89	35.12	53.84	62.03	74.00	11.97	Peak
6	5753.340	33.45	9.90	35.11	88.85	97.09	74.00	-23.09	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 102
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5755 MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5459.010	33.30	9.75	35.25	34.88	42.68	54.00	11.32	Average
2	5460.000	33.26	9.76	35.25	34.52	42.29	54.00	11.71	Average
3	5715.000	33.42	9.88	35.12	37.61	45.79	54.00	8.21	Average
4	5722.810	33.42	9.89	35.12	41.51	49.70	54.00	4.30	Average
5	5725.000	33.42	9.89	35.12	41.42	49.61	54.00	4.39	Average
6	5753.340	33.45	9.90	35.11	77.31	85.55	54.00	-31.55	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 103
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5755MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5426.540	33.32	9.74	35.26	44.49	52.29	74.00	21.71	Peak
2	5460.000	33.26	9.76	35.25	44.49	52.26	74.00	21.74	Peak
3	5715.000	33.42	9.88	35.12	51.90	60.08	74.00	13.92	Peak
4	5725.000	33.42	9.89	35.12	56.82	65.01	74.00	8.99	Peak
5	5752.050	33.45	9.90	35.11	89.66	97.90	74.00	-23.90	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 104
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5755MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5460.000	33.26	9.76	35.25	34.10	41.87	54.00	12.13	Average
2	5715.000	33.42	9.88	35.12	42.17	50.35	54.00	3.65	Average
3	5722.810	33.42	9.89	35.12	46.70	54.89	54.00	-0.89	Average
4	5725.000	33.42	9.89	35.12	47.21	55.40	54.00	-1.40	Average
5	5753.340	33.45	9.90	35.11	82.96	91.20	54.00	-37.20	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 109
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5795MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5793.830	33.49	9.92	35.09	86.52	94.84	74.00	-20.84	Peak
2	5850.000	33.55	9.95	35.07	48.91	53.34	74.00	20.66	Peak
3	5860.000	33.56	9.95	35.07	43.73	52.17	74.00	21.83	Peak
4	7250.000	36.00	10.74	35.50	43.35	54.59	74.00	19.41	Peak
5	7684.330	36.43	11.16	35.67	46.23	58.15	74.00	15.85	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 110
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5795MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5795.820	33.50	9.92	35.09	79.08	87.41	54.00	-33.41	Average
2	5850.000	33.55	9.95	35.07	34.85	43.28	54.00	10.72	Average
3	5860.000	33.56	9.95	35.07	35.15	43.59	54.00	10.41	Average
4	7250.000	36.00	10.74	35.50	33.84	45.08	54.00	8.92	Average
5	7714.180	36.49	11.20	35.69	46.62	54.00	7.38	Average	


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 111
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5795MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5793.880	33.48	9.91	35.10	88.64	96.03	74.00	-22.93	Peak
2	5850.000	33.55	9.95	35.07	44.72	53.15	74.00	20.85	Peak
3	5860.000	33.56	9.95	35.07	43.57	52.01	74.00	21.99	Peak
4	7250.000	36.00	10.74	35.50	43.98	55.22	74.00	18.78	Peak
5	7750.000	36.55	11.23	35.70	45.03	57.11	74.00	16.89	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 112
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23°C/54%
 Engineer : Leo-Li
 EUT : 65" LCD PC
 Power rating : AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 5795MHz Tx
 INF6502

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5795.820	33.50	9.92	35.09	81.52	89.85	54.00	-35.85	Average
2	5850.000	33.55	9.95	35.07	35.66	44.09	54.00	9.91	Average
3	5860.000	33.56	9.95	35.07	34.61	43.05	54.00	10.95	Average
4	7250.000	36.00	10.74	35.50	33.85	45.09	54.00	8.91	Average
5	7710.200	36.48	11.18	35.68	34.82	46.80	54.00	7.20	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official limit are not reported.

6. 6dB&26dB Bandwidth Test

6.1.Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4446A	US44300459	Apr.28,15	1 Year
2.	Spectrum	Agilent	N9030A	MY51380221	Oct.18,15	1Year
3.	Attenuator (20dB)	Agilent	8491B	MY39262165	Apr.28,15	1 Year
4.	RF Cable	Marvelous Microwave Inc	SFL402105FLEX	NO.1	Oct.17.15	1 Year

6.2.Limit

6dB Bandwidth should be not less than 500kHz

6.3.Test Procedure

6dB Bandwidth:

The transmitter output was connected to a spectrum analyzer, The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 300 KHz VBW for signal width below 20MHz and 300KHz RBW ,1MHz VBW for Above 20MHz signal Bandwidth.

26dB Bandwidth:

The transmitter output was connected to a spectrum analyzer, The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 300 KHz VBW The 26dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 26dB.

6.4.Test Results

5180-5240MHz Band:
6dB bandwidth

EUT: 65'' LCD PC		
M/N: INF6502		
Test date: 2015-11-17	Pressure: 101.3±1.0 kpa	Humidity: 52.5±3.0%
Tested by: Leo-Li	Test site: RF site	Temperature: 22.7±0.6

Test Mode	Frequency (MHz)	6dB bandwidth (MHz)	Limit (KHz)
11a	5180	15.14	500
	5200	15.13	500
	5240	15.13	500
11n HT20	5180	16.10	500
	5200	15.14	500
	5240	15.13	500
11n HT40	5190	35.17	500
	5230	35.16	500
Conclusion : PASS			

26dB bandwidth

EUT: 65'' LCD PC		
M/N: INF6502		
Test date: 2015-11-17	Pressure: 101.2±1.0 kpa	Humidity: 52.6±3.0%
Tested by: Leo-Li	Test site: RF site	Temperature: 22.6±0.6

Test Mode	Frequency (MHz)	-26dB bandwidth (MHz)	Limit (KHz)
11a	5180	18.45	N/A
	5200	18.28	N/A
	5240	18.33	N/A
11n HT20	5180	18.82	N/A
	5200	18.81	N/A
	5240	18.71	N/A
11n HT40	5190	38.00	N/A
	5230	38.22	N/A
Conclusion : PASS			

5745-5825MHz Band:
6dB bandwidth

EUT: 65'' LCD PC		
M/N: INF6502		
Test date: 2015-11-18	Pressure: 101.2±1.0 kpa	Humidity:52.6±3.0%
Tested by: Leo-Li	Test site: RF site	Temperature:22.3±0.6

Test Mode	Frequency (MHz)	6dB bandwidth (MHz)	Limit (KHz)
11a	5745	15.13	500
	5785	15.13	500
	5825	15.11	500
11n HT20	5745	15.13	500
	5785	15.13	500
	5825	15.13	500
11n HT40	5755	35.15	500
	5795	35.16	500
Conclusion : PASS			

26dB bandwidth

EUT: 65'' LCD PC		
M/N: INF6502		
Test date: 2015-11-17	Pressure: 101.2±1.0 kpa	Humidity:52.6±3.0%
Tested by: Leo-Li	Test site: RF site	Temperature:22.2±0.6


Test Mode	Frequency (MHz)	26dB Bandwidth (MHz)	Limit (KHz)
11a	5745	18.37	N/A
	5785	18.52	N/A
	5825	18.21	N/A
11n HT20	5745	18.82	N/A
	5785	18.73	N/A
	5825	18.82	N/A
11n HT40	5755	38.12	N/A
	5795	38.15	N/A
Conclusion : PASS			

5180-5240MHz Band:

6dB bandwidth


11a

5180MHz




11n HT20


5180MHz




5200MHz




5200MHz



5240MHz




5240MHz




11n HT40

5190MHz



5230MHz




5180-5240MHz Band:

26dB bandwidth


11a

5180MHz




11n HT20


5180MHz




5200MHz




5200MHz



5240MHz




5240MHz




11n HT40

5190MHz



5230MHz




5745-5825MHz Band:

6dB bandwidth


11a

5745MHz




11n HT20


5745MHz




5785MHz




5785MHz



5825MHz




5825MHz




11n HT40

5755MHz



5795MHz




5745-5825MHz Band:

26dB bandwidth


11a

5745MHz




11n HT20


5745MHz




5785MHz




5785MHz



5825MHz




5825MHz




11n HT40

5755MHz



5795MHz



7. OUTPUT POWER TEST

7.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4446A	US44300459	Apr.28,15	1 Year
2.	Spectrum	Agilent	N9030A	MY51380221	Oct.18,15	1 Year
3.	Power meter	Anritsu	ML2487A	6K00002472	Aug.21,15	1 Year
4.	Power sensor	Anritsu	MA2491A	0033005	Aug.21,15	1 Year
5.	Attenuator (20dB)	Agilent	8491B	MY39262165	Apr.28,15	1 Year
6.	RF Cable	Marvelous Microwave Inc	SFL402105FLEX	NO.1	Oct.17,15	1 Year

7.2. Limit

For the band 5.15–5.25 GHz.

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi.

For the 5.25–5.35 GHz and 5.47–5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz.

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

7.3. Test Procedure

1. Connected the EUT's antenna port to measure device by 26dB attenuator.
2. For IEEE 802.11a and IEEE802.11n HT20 and 802.11ac VHT20 mode, use a PK power meter which's bandwidth is 20MHz and above 26dB bandwidth of signal to measure out each test modes' PK output power.
3. For IEEE802.11n HT40 mode, because the signal's bandwidth is about 40MHz and above 20MHz bandwidth of power sensor ML2491A. So use the test method described in KBD789033 clause E Method SA-1
 - 1) Connect the antenna port to the spectrum analyzer and Set span of the spectrum to encompass the entire emission bandwidth (EBW) of the signal.
 - 2) Set the RBW=1MHz and VBW =3MHz
 - 3) Number of points in sweep $\geq 2 \text{ Span} / \text{RBW}$
 - 4) Detector = RMS
 - 5) Sweep time = auto couple
 - 6) Allow the sweep to "free run" and set the Trace average at least 100 traces in power averaging (i.e., RMS) mode.
 - 7) Compute power by integrating the spectrum across the 26 dB EBW of the signal using the instrument's band power measurement function with band limits set equal to the EBW band edges.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

7.4. Test Results

5180-5240MHz Band:

EUT: 65'' LCD PC			
M/N: INF6502			
Test date: 2015-11-18		Pressure: 101.4±1.0 kpa	Humidity: 52.8±3.0%
Tested by: Leo-Li		Test site: RF site	Temperature: 24.2±0.6
Test Mode	Frequency (MHz)	Maximum Conducted Output Power (dBm)	Limit (dBm)
11a	5180	6.84	24
	5200	7.16	24
	5240	6.54	24
11n HT20	5180	6.27	24
	5200	6.29	24
	5240	5.88	24
11n HT40	5190	6.55	24
	5230	7.21	24
Conclusion: PASS			


5745-5825MHz Band:

EUT: 65'' LCD PC			
M/N: INF6502			
Test date: 2015-11-18		Pressure: 101.2±1.0 kpa	Humidity: 52.5±3.0%
Tested by: Leo-Li		Test site: RF site	Temperature: 22.9±0.6
Test Mode	Frequency (MHz)	Maximum Conducted Output Power (dBm)	Limit (dBm)
11a	5745	8.82	30
	5785	9.03	30
	5825	8.79	30
11n HT20	5745	8.93	30
	5785	9.31	30
	5825	8.74	30
11n HT40	5755	9.61	30
	5795	9.55	30
Conclusion: PASS			

5180-5240MHz Band:

11n HT40

5190MHz



5230MHz



5745-5825MHz Band:

11n HT40

5755MHz



5795MHz



8. SPECTRAL DENSITY TEST

8.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4446A	US44300459	Apr.28,15	1 Year
2.	Spectrum	Agilent	N9030A	MY51380221	Oct.18,15	1 Year
3.	Attenuator (20dB)	Agilent	8491B	MY39262165	Apr.28,15	1 Year
4.	RF Cable	Marvelous Microwave Inc	SFL402105FLEX	NO.1	Oct.17,15	1 Year

8.2. Limit

Band 5150-5250 MHz:

The e.i.r.p spectral density shall not exceed 11 dBm in any 1.0 MHz band.

Band 5250-5350 MHz:

The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.

Band 5470-5725 MHz:

The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.

Band 5725-5850 MHz:

The power spectral density shall not exceed 30 dBm in any 500 KHz band.

8.3. Test Procedure

For the Band 5.15-5.25GHz:

The transmitter output was connected to a spectrum analyzer. Power density was measured by spectrum analyzer with 1MHz RBW and 3MHz VBW; Detector: RMS mode.

For the band 5.725-5.85 GHz:

The transmitter output was connected to a spectrum analyzer. Power density was measured by spectrum analyzer with 1MHz RBW and 3MHz VBW, RMS Detector.

So use the test method described in KDB789033 clause E

- 1) Set the RBW=100kHz and VBW =3MHz
- 2) Number of points in sweep ≥ 2 Span / RBW. (This ensures that bin-to-bin spacing is $\leq$ RBW/2, so that narrowband signals are not lost between frequency bins.)
- 3) Sweep time = auto
- 4) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- 5) Use the "peak search" function of spectrum analyzer find the max value, then add $10\log(500\text{kHz}/\text{RBW})$ to the measured result.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

8.4. Test Results

5180-5240MHz Band:

EUT: 65" LCD PC		
M/N: INF6502		
Test date: 2015-11-17	Pressure: 101.2±1.0 kpa	Humidity: 52.9±3.0%
Tested by: Leo-Li	Test site: RF site	Temperature: 23.2±0.6

Test Mode	Frequency (MHz)	Power Density (dBm/MHz)	Limit (dBm/MHz)
11a	5180	-4.066	11
	5200	-3.349	11
	5240	-2.770	11
11n HT20	5180	-4.510	11
	5200	-4.220	11
	5240	-3.782	11
11n HT40	5190	-6.621	11
	5230	-6.027	11
Conclusion: PASS			

5745-5825MHz Band:

EUT: 65" LCD PC		
M/N: INF6502		
Test date: 2015-11-18	Pressure: 101.2±1.0 kpa	Humidity: 53.5±3.0%
Tested by: Leo-Li	Test site: RF site	Temperature: 22.4±0.6

Test Mode	Frequency (MHz)	Power density (dBm/500KHz)	Limit (dBm/500KHz)
11a	5745	-3.384	30
	5785	-2.770	30
	5825	-3.335	30
11n HT20	5745	-4.353	30
	5785	-3.627	30
	5825	-4.324	30
11n HT40	5755	-6.685	30
	5795	-6.701	30
Conclusion: PASS			

Note 1:

1. Correction factor = $10\log(500\text{kHz}/100\text{kHz}) = 6.9897$
2. Result = Reading value + Correction factor

5180-5240MHz Band:

11a

5180MHz



11n HT20

5180MHz




5200MHz



5200MHz



5240MHz



5240MHz



11n HT40

5190MHz



5230MHz



5745-5825MHz Band:

11a

5745MHz




11n HT20


5745MHz




5785MHz




5785MHz



5825MHz



5825MHz



11n HT40

5755MHz



5795MHz



9. MPE ESTIMATION

9.1. Limit for General Population/ Uncontrolled Exposures

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

Note: F= Frequency in MHz

9.2. Estimation Result

U-NII 5180-5240MHz Band

EUT: 65" LCD PC		
M/N: INF6502		
Test date: 2015-11-18	Pressure: 101.5±1.0 kpa	Humidity: 53.1±3.0%
Tested by: Leo-Li	Test site: RF site	Temperature: 23.9±0.6

Test Mode	CH	Frequency (MHz)	Peak Output Power (dBm)	Output Power (mW)	Antenna Gain (dBi)	Antenna Gain (Linear)	MPE
11a	CH36	5180	6.84	4.83	3.43	2.20	0.2117
	CH40	5200	7.16	5.20	3.43	2.20	0.2279
	CH48	5240	6.54	4.51	3.43	2.20	0.1976
11n HT20	CH36	5180	6.27	4.24	3.43	2.20	0.1856
	CH40	5200	6.29	4.26	3.43	2.20	0.1865
	CH48	5240	5.88	3.87	3.43	2.20	0.1697
11n HT40	CH38	5190	6.55	4.52	3.43	2.20	0.1980
	CH46	5230	7.21	4.83	3.43	2.20	0.2117

$$MPE = \frac{PG}{4\pi R^2} \quad (R=20 \text{ cm})$$

U-NII 5745-5825MHz Band

EUT: 65'' LCD PC		
M/N: INF6502		
Test date: 2015-11-18	Pressure: 101.2±1.0 kpa	Humidity: 52.4±3.0%
Tested by: Leo-Li	Test site: RF site	Temperature:23.2±0.6

Test Mode	Frequency (MHz)	Peak Output Power (dBm)	Output Power (mW)	Antenna Gain (dBi)	Antenna Gain (Linear)	MPE
11a	5745	8.82	7.62	3.43	2.20	0.3340
	5785	9.03	8.00	3.43	2.20	0.3505
	5825	8.79	7.57	3.43	2.20	0.3317
11n HT20	5745	8.93	7.82	3.43	2.20	0.3425
	5785	9.31	8.53	3.43	2.20	0.3738
	5825	8.74	7.48	3.43	2.20	0.3279
11n HT40	5755	9.61	9.14	3.43	2.20	0.4006
	5795	9.55	9.02	3.43	2.20	0.3951

$$MPE = \frac{PG}{4\pi R^2} \quad (R=20 \text{ cm})$$

10. ANTENNA REQUIREMENT

10.1. Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.407 (a), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

10.2. Antenna Connected Construction

The antennas used for this product are PIFA antenna that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is 4dBi.

11. DEVIATION TO TEST SPECIFICATIONS

[NONE]