

## RF Exposure Evaluation declaration

Product Name : Notebook

Model No. : MS-1242, U200

FCC ID : I4L-12-EM7306891

Applicant : MICRO-STAR INT'L Co., LTD.

Address : No. 69, Li-De St., Jung-He City, Taipei Hsien, Taiwan,  
R.O.C.

Date of Receipt : Mar. 26, 2009

Date of Declaration : Aug. 25, 2009

Report No. : 096001R-RF-US-RFEXP

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of Quietek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

## 1. RF Exposure Evaluation

### 1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
<b>(A) Limits for Occupational/ Control Exposures</b>				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
<b>(B) Limits for General Population/ Uncontrolled Exposures</b>				
300-1500	--	--	F/1500	30
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $Pd = (Pout * G) / (4 * \pi * R^2)$

Where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 23°C and 58% RH.

### 1.3. Test Result of RF Exposure Evaluation

Product : Notebook  
 Test Item : RF Exposure Evaluation  
 Test Site : N/A

#### GSM 850 GPRS-Peak Gain: 2.45dBi

Frequency (MHz)	Conducted Power (dBm)	Duty Cycle	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Pass/Fail
824.2	32.03	1/8	199.5	0.0698	0.55	Pass
836.4	31.97	1/8	196.7	0.0688	0.55	Pass
848.8	31.84	1/8	190.9	0.0668	0.55	Pass

#### GSM 850 EGPRS-Peak Gain: 2.45dBi

Frequency (MHz)	Conducted Power (dBm)	Duty Cycle	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Pass/Fail
824.2	25.43	1/8	43.6	0.0153	0.55	Pass
836.4	25.39	1/8	43.2	0.0151	0.55	Pass
848.8	25.36	1/8	42.9	0.0150	0.55	Pass

#### PCS 1900 GPRS-Peak Gain: 2.45dBi

Frequency (MHz)	Conducted Power (dBm)	Duty Cycle	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Pass/Fail
1850.2	28.41	1/8	86.7	0.0303	1	Pass
1880	28.68	1/8	92.2	0.0323	1	Pass
1909.8	28.71	1/8	92.9	0.0325	1	Pass

**PCS 1900 EGPRS-Peak Gain: 2.45dBi**

Frequency (MHz)	Conducted Power (dBm)	Duty Cycle	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Pass/Fail
1850.2	23.88	1/8	30.5	0.0107	1	Pass
1880	24.18	1/8	32.7	0.0114	1	Pass
1909.8	24.20	1/8	32.9	0.0115	1	Pass

**WCDMA V-Peak Gain: 2.45dBi**

Frequency (MHz)	Conducted Power (dBm)	Duty Cycle	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Pass/Fail
824.2	21.06	1	127.6	0.0446	0.55	Pass
836.6	21.18	1	131.2	0.0459	0.55	Pass
846.6	21.16	1	130.6	0.0457	0.55	Pass

**WCDMA V HSDPA-Peak Gain: 2.45dBi**

Frequency (MHz)	Conducted Power (dBm)	Duty Cycle	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Pass/Fail
824.2	20.96	1	124.7	0.0436	0.55	Pass
836.6	21.23	1	132.7	0.0464	0.55	Pass
846.6	20.89	1	122.7	0.0429	0.55	Pass

**WCDMA II -Peak Gain: 2.45dBi**

Frequency (MHz)	Conducted Power (dBm)	Duty Cycle	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Pass/Fail
1852.4	21.18	1	131.2	0.0459	1	Pass
1880	21.12	1	129.4	0.0453	1	Pass
1907.6	21.07	1	127.9	0.0447	1	Pass

**WCDMA II HSDPA-Peak Gain: 2.45dBi**

Frequency (MHz)	Conducted Power (dBm)	Duty Cycle	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Pass/Fail
1852.4	21.45	1	139.6	0.0488	1	Pass
1880	21.24	1	133.0	0.0465	1	Pass
1907.6	21.27	1	134.0	0.0469	1	Pass

**802.11n(20M)-Peak Gain: 3.3dBi**

Frequency (MHz)	Conducted Power (dBm)	Duty Cycle	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Pass/Fail
2412	20.65	1	116.1	0.0494	1	Pass
2437	20.63	1	115.6	0.0492	1	Pass
2462	20.73	1	118.3	0.0503	1	Pass

Note: The conducted output power is refer to report No.: 096001R-HPUSP07V01, 096001R-RFUSP05V01-A from the Quietek.