

## RF Test Report

Applicant : Micro-Star Int'l Co., Ltd.

Product Name : Wireless Mouse

Trade Name : msi

Model Number : 8ZB5

Applicable Standard : FCC 47 CFR PART 15 SUBPART C  
ANSI C63.10:2013

Received Date : Oct. 17, 2022

Test Period : Oct. 31 ~ Nov. 02, 2022

Issued Date : Nov. 24, 2022

### Issued by

Eurofins E&E Wireless Taiwan Co., Ltd.  
No. 140-1, Changan Street, Bade District,  
Taoyuan City 334025, Taiwan (R.O.C.)  
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330  
Frequency Range: 9 kHz to 325 GHz (Bade test site)  
Frequency Range: 9 kHz to 40 GHz (Wugu test site)  
Test Firm MRA designation number: TW0010

### Note:

1. The test results are valid only for samples provided by customers and under the test conditions described in this report.
2. This report shall not be reproduced except in full, without the written approval of Eurofins E&E Wireless Taiwan Co., Ltd.
3. The relevant information is provided by customers in this test report. According to the correctness, appropriateness or completeness of the information provided by the customer, if there is any doubt or error in the information which affects the validity of the test results, the laboratory does not take the responsibility.

**Revision History**

Version	Issued Date	Revisions	Revised By
00	Nov. 24, 2022	Initial Issue	Snow Wang

## Verification of Compliance

Applicant : Micro-Star Int'l Co., Ltd.

Product Name : Wireless Mouse

Trade Name : msi

Model Number : 8ZB5

FCC ID : I4L-8ZB5

Applicable Standard : FCC 47 CFR PART 15 SUBPART C  
ANSI C63.10:2013

Test Result : Complied

Performing Lab. : Eurofins E&E Wireless Taiwan Co., Ltd.  
No. 140-1, Changan Street, Bade District,  
Taoyuan City 334025, Taiwan (R.O.C.)  
Tel : +886-3-2710188 / Fax : +886-3-2710190  
Taiwan Accreditation Foundation accreditation number: 1330



Eurofins E&E Wireless Taiwan Co., Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by Eurofins E&E Wireless Taiwan Co., Ltd. based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Approved By : \_\_\_\_\_

## TABLE OF CONTENTS

<b>1</b>	<b>General Information .....</b>	<b>5</b>
1.1.	Summary of Test Result .....	5
1.2.	Testing Location .....	6
1.3.	Measurement Uncertainty .....	6
<b>2</b>	<b>EUT Description.....</b>	<b>7</b>
<b>3</b>	<b>Test Methodology.....</b>	<b>8</b>
3.1.	Mode of Operation.....	8
3.2.	EUT Test Step.....	8
3.3.	Configuration of Test System Details.....	9
3.4.	Test Instruments .....	11
3.5.	Test Site Environment.....	14
<b>4</b>	<b>Measurement Procedure.....</b>	<b>15</b>
4.1.	AC Power Line Conducted Emission Measurement.....	15
4.2.	Radiated Emission Measurement.....	17
4.3.	Maximum Conducted Output Power Measurement.....	21
4.4.	6 dB RF Bandwidth Measurement.....	22
4.5.	Maximum Power Density Measurement.....	23
4.6.	Out of Band Conducted Emissions Measurement.....	24
4.7.	Antenna Measurement .....	24
<b>5</b>	<b>Test Results .....</b>	<b>25</b>
5.1.	Conducted Emission .....	25
5.2.	Conducted Test Results.....	27
5.3.	Radiated Emission Measurement.....	35

### Appendix A. Test Setup Photographs

# 1 General Information

## 1.1. Summary of Test Result

Standard	Item	Result	Remark
15.207	AC Power Conducted Emission	PASS	-----
15.247(d)	Transmitter Radiated Emissions	PASS	-----
15.247(b)(3)	Max. Output Power	PASS	-----
15.247(a)(2)	6 dB RF Bandwidth	PASS	-----
15.247(e)	Maximum Power Spectral Density	PASS	-----
15.247(d)	Out of Band Conducted Spurious Emission	PASS	-----
15.203	Antenna Requirement	PASS	-----

### Decision Rule

- ☒ Uncertainty is not included.
- ☐ Uncertainty is included.

Standard	Description
CFR47, Part 15, Subpart C	Intentional Radiators
ANSI C63. 10: 2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
KDB 558074 D01 15.247 Meas Guidance v05r02	GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES

## 1.2. Testing Location

Lab Name: Eurofins E&E Wireless Taiwan Co., Ltd.

Site Address: ☒ No. 140-1, Changan Street, Bade District, Taoyuan City 334025, Taiwan (R.O.C.)

Site Address: ☐ No. 2, Wuquan 5th Rd. Wugu Dist., New Taipei City, Taiwan (R.O.C.)

## 1.3. Measurement Uncertainty

Test Item	Frequency Range	Uncertainty
Conducted Emission	150 kHz ~ 30 MHz	2.7 dB
Radiated Emission	9 kHz ~ 30 MHz	2.2 dB
	30 MHz ~ 1000 MHz	5.1 dB
	1000 MHz ~ 18000 MHz	5.2 dB
	18000 MHz ~ 26500 MHz	4.6 dB
	26500 MHz ~ 40000 MHz	4.6 dB
Conducted Output Power	1.1 dB	
RF Bandwidth	4.7 %	
Power Spectral Density	1.1 dB	

## 2 EUT Description

Applicant	Micro-Star Int'l Co., Ltd. No.69, Lide St., Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C.)	
Product Name	Wireless Mouse	
Trade Name	msi	
Model No.	8ZB5	
FCC ID	I4L-8ZB5	
Frequency Range	2406 ~ 2474 MHz	
Modulation Type	GFSK	
Operate Temp. Range	0 ~ +40 °C	
EUT Power Rating	DC 5 V · 600 mA	
Antenna information	Type	Max. Gain (dBi)
	PCB Antenna	1.17
RF Output Power	0.00081 W	

Channel list									
CH	MHz	CH	MHz	CH	MHz	CH	MHz	CH	MHz
0	2406	7	2420	14	2434	21	2448	28	2462
1	2408	8	2422	15	2436	22	2450	29	2464
2	2410	9	2424	16	2438	23	2452	30	2466
3	2412	10	2426	17	2440	24	2454	31	2468
4	2414	11	2428	18	2442	25	2456	32	2470
5	2416	12	2430	19	2444	26	2458	33	2472
6	2418	13	2432	20	2446	27	2460	34	2474

### 3 Test Methodology

#### 3.1. Mode of Operation

Decision of Test Eurofins has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Test Mode
Transmit Mode
SRD

Software used to control the EUT for staying in continuous transmitting mode was programmed.

After verification, all tests were carried out with the worst case test modes.

By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "Y axis" position was the worst, then the final test was executed the worst condition and test data were recorded in this report.


#### 3.2. EUT Test Step

1	Setup the EUT shown on "Configuration of Test System Details".
2	Turn on the power of all equipment.
3	Turn on TX function.
4	EUT run test program.




### 3.3. Configuration of Test System Details

#### Conducted Emission



#### Radiated Emissions



Devices Description					
	Product	Manufacturer	Model Number	Serial Number	Power Cord
(1)	NB	acer	N19C1	---	---
(2)	AC Adapter	chiicony	A18-045N2A	---	---
(3)	USB Type C cable	msi	GM51W USB cable	---	---
(4)	NB	HP	5CG1116V9K	---	---
(5)	AC Adapter	HP	TPN-DA17	---	---

### 3.4. Test Instruments

For Conducted Emission

Test Period: Nov. 02 ~ Nov. 02, 2022

Testing Engineer: Jayson Hsieh

Test Site		Conduction01-BD				
Use	Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
<input checked="" type="checkbox"/>	Test Receiver	R&S	ESCI	100367	May 19, 2022	1 year
<input type="checkbox"/>	Test Receiver	R&S	ESCI	100722	Nov. 02, 2021	1 year
<input type="checkbox"/>	Test Receiver	R&S	ESCI	101000	Nov. 26, 2021	1 year
<input checked="" type="checkbox"/>	LISN	R&S	ENV216	101040	Apr. 06, 2022	1 year
<input checked="" type="checkbox"/>	LISN	R&S	ENV216	101140	Jan. 25, 2022	1 year
<input checked="" type="checkbox"/>	RF Cable	Woken	00100D1380194M	TE-02-03	May 27, 2022	1 year
<input checked="" type="checkbox"/>	Software	EZ EMC	1.1.4.3	N/A	N.C.R.	---

Note: N.C.R. = No Calibration Request.

For Conducted  
 Test Period: Oct. 31, 2022  
 Testing Engineer: Brian Lin

Test Site		RF01-BD				
Use	Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
<input checked="" type="checkbox"/>	Power Sensor	Anritsu	MA2411B	1126022	Sep. 04, 2022	1 year
<input checked="" type="checkbox"/>	Power Meter	Anritsu	ML2495A	1135009	Sep. 04, 2022	1 year
<input type="checkbox"/>	Power Sensor	Agilent	N1921A	MY45241957	Dec. 06, 2021	1 year
<input type="checkbox"/>	Power Meter	Agilent	N1911A	MY45101619	Dec. 06, 2021	1 year
<input checked="" type="checkbox"/>	Spectrum Analyzer (10 Hz~26.5 GHz)	Keysight	N9010B	MY59071418	Mar. 16, 2022	1 year
<input type="checkbox"/>	Spectrum Analyzer (9 kHz~26.5 GHz)	Agilent	N9010A	MY48030518	Jul. 21, 2022	1 year
<input type="checkbox"/>	Spectrum Analyzer (20 Hz~26.5 GHz)	Agilent	N9020A	US47520902	Sep. 01, 2022	1 year
<input type="checkbox"/>	Spectrum Analyzer (3 Hz~50 GHz)	Agilent	N9030A	MY53120541	Jan. 05, 2022	1 year
<input type="checkbox"/>	Temperature & Humidity Chamber	TAICHY	MHU-225LA	980729	Mar. 28, 2022	1 year
<input type="checkbox"/>	Signal Generator	Keysight	N5182B	MY53052569	Apr. 16, 2022	1 year
<input type="checkbox"/>	Signal Generator	Keysight	N5182BX07	MY59360221	Apr. 16, 2022	1 year
<input type="checkbox"/>	Bluetooth Tester	R&S	CBT	100350	Mar. 17, 2021	2 years
<input type="checkbox"/>	Wireless Connectivity Tester	R&S	CMW270	102208	Jun. 01, 2022	1 year
<input type="checkbox"/>	Power Supply	KEITHLEY	2303	4045290	Jan. 19, 2022	1 year

Note: N.C.R. = No Calibration Request.

For Radiated Emissions  
Test Period: Nov. 01, 2022  
Testing Engineer: Eason Lee

Test Site		96601-BD				
Radiation test sites		Semi Anechoic Room				
Use	Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
<input checked="" type="checkbox"/>	Spectrum Analyzer (10 Hz~44 GHz)	Keysight	N9010A	MY52221312	Jan. 13, 2022	1 year
<input type="checkbox"/>	Spectrum Analyzer (3 Hz~50 GHz)	Agilent	N9030A	MY53120541	Jan. 05, 2022	1 year
<input checked="" type="checkbox"/>	Amplifier (10 kHz~3 GHz)	Agilent	EMC001330	980862	Nov. 30, 2021	1 year
<input type="checkbox"/>	Amplifier (100 kHz~1.3 GHz)	Agilent	8447D	2944A10961	Jul. 07, 2022	1 year
<input checked="" type="checkbox"/>	Pre Amplifier (1~26.5 GHz)	Agilent	8449B	3008A02455	Jul. 07, 2022	1 year
<input type="checkbox"/>	Preamplifier (1 GHz~26.5 GHz)	EMCI	EMC012645SE	980289	Jan. 13, 2022	1 year
<input type="checkbox"/>	Preamplifier (26.5 GHz~40 GHz)	EMCI	EMC2654045	980028	Sep. 02, 2022	1 year
<input checked="" type="checkbox"/>	Loop Antenna (9 kHz~30 MHz)	COM-POWER CORPORATION	AL-130	121014	Mar. 28, 2022	1 year
<input type="checkbox"/>	Trilog Broadband Antenna (30 kHz~1 GHz)	Schwarzbeck Mess-Elektronik	VULB9168	01146	Jul. 22, 2022	1 year
<input checked="" type="checkbox"/>	Trilog Broadband Antenna (30 kHz~1 GHz)	Schwarzbeck Mess-Elektronik	VULB9168	416	Nov. 17, 2021	1 year
<input type="checkbox"/>	Broadband Horn Antenna (1 GHz~18 GHz)	Schwarzbeck Mess-Elektronik	9120D	02207	Jul. 13, 2022	1 year
<input checked="" type="checkbox"/>	Broadband Horn Antenna (1 GHz~18 GHz)	Schwarzbeck Mess-Elektronik	9120D	9120D-550	Aug. 25, 2022	1 year
<input checked="" type="checkbox"/>	Broadband Horn Antenna (18 GHz~40 GHz)	Schwarzbeck Mess-Elektronik	9170	9170-320	Aug. 25, 2022	1 year
<input type="checkbox"/>	Preamplifier (26.5 GHz~40 GHz)	EMCI	EMC2654045	980028	Sep. 02, 2022	1 year
<input type="checkbox"/>	Horn Antenna (18 GHz~40 GHz)	ETS	3116	00086467	Dec. 03, 2021	1 year

Note: N.C.R. = No Calibration Request

Test Site		96601-BD				
Radiation test sites		Semi Anechoic Room				
Use	Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
<input checked="" type="checkbox"/>	Microwave Cable	EMCI	EMC104-SM-SM-13000	170814	Feb. 18, 2022	1 year
<input checked="" type="checkbox"/>	Microwave Cable	EMCI	EMCCFD400-NM-NM-6000	210902	Feb. 18, 2022	1 year
<input checked="" type="checkbox"/>	Microwave Cable	SUHNER	suflex104	313229/4	Feb. 18, 2022	1 year
<input type="checkbox"/>	Microwave Cable	EMCI	EMC102-KM-KM-14000	151001	Feb. 18, 2022	1 year
<input type="checkbox"/>	RF Cable (30-1000 MHz)	EMCI	EMC104-N-N-2000	TE01-2	Feb. 18, 2022	1 year
<input type="checkbox"/>	RF Cable (30-1000 MHz)	EMCI	EMC104-N-N-6000	TE01-1	Feb. 18, 2022	1 year
<input type="checkbox"/>	RF Cable (30-1000 MHz)	EMCI	EMC 106-SM-NM-1000	171219 (TE01-3)	Feb. 18, 2022	1 year
<input type="checkbox"/>	Bluetooth Tester	R&S	CBT	100350	Mar. 17, 2021	2 years
<input type="checkbox"/>	Wireless Connectivity Tester	R&S	CMW270	102208	Jun. 01, 2022	1 year
<input type="checkbox"/>	Power Supply	KEITHLEY	2303	4045290	Jan. 19, 2022	1 year
<input checked="" type="checkbox"/>	Software	EZ EMC	1.1.4.4	N/A	N.C.R.	---

Note: N.C.R. = No Calibration Request

### 3.5. Test Site Environment

Items	Required (IEC 60068-1)	Actual
Temperature (°C)	15-35	20-30
Humidity (%RH)	25-75	45-75


## 4 Measurement Procedure

### 4.1. AC Power Line Conducted Emission Measurement

#### ■ Limit

Frequency (MHz)	Quasi-peak	Average
0.15 - 0.5	66 to 56	56 to 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

#### ■ Test Setup



#### ■ Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a  $50\ \Omega // 50\ \mu\text{H}$  coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a  $50\ \Omega // 50\ \mu\text{H}$  coupling impedance with 50 ohm termination.

Tabletop device shall be placed on a non-conducting platform, of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The wall of screened room shall be located 40 cm to the rear of the EUT. Other surfaces of tabletop or floor standing EUT shall be at least 80 cm from any other ground conducting surface including one or more LISNs. For floor-standing device shall be placed under the EUT with a 12 mm insulating material.

Conducted emissions were investigated over the frequency range from 0.15 MHz to 30 MHz using a resolution bandwidth of 9 kHz. The equipment under test (EUT) shall be meet the limits in section 4.1, as applicable, including the average limit and the quasi-peak limit when using respectively, an average detector and quasi-peak detector measured in accordance with the methods described of related standard. When all of peak value were complied with quasi-peak and average limit from 150 kHz to 30 MHz then quasi-peak and average measurement was unnecessary.

The AMN shall be placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for AMNs mounted on top of the ground reference plane. This distance is between the closest points of the AMN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8 m from the AMN. If the mains power cable is longer than 1 m then the cable shall be folded back and forth at the centre of the lead to form a bundle no longer than 0.4 m. All of interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long. All of EUT and AE shall be separate place more than 0.1 m. All 50  $\Omega$  ports of the LISN shall be resistively terminated into 50  $\Omega$  loads when not connected to the measuring instrument.

If the reading of the measuring receiver shows fluctuations close to the limit, the reading shall be observed for at least 15 s at each measurement frequency; the higher reading shall be recorded with the exception of any brief isolated high reading which shall be ignored.



## 4.2. Radiated Emission Measurement

### ■ Limit


According to §15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ( $\mu\text{V/m}$ at meter)	Measurement Distance (meters)
0.009 – 0.490	$2400 / F$ (kHz)	300
0.490 – 1.705	$24000 / F$ (kHz)	30
1.705 – 30.0	30	30
30 - 88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3


\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

### ■ Setup


9 kHz ~ 30 MHz



Below 1 GHz



Above 1 GHz



## ■ Test Procedure

Final radiation measurements were made on a three-meter, Semi Anechoic Chamber. The EUT system was placed on a nonconductive turntable which is 0.8 or 1.5 meters height, top surface 1.0 x 1.5 meter. The spectrum was examined from 250 MHz to 2.5 GHz in order to cover the whole spectrum below 10th harmonic which could generate from the EUT. During the test, EUT was set to transmit continuously & Measurements spectrum range from 9 kHz to 26.5 GHz is investigated.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 3 MHz for peak measurements and 10 Hz for average measurements when Duty cycle  $>0.98$  /  $1/T$  for average measurements when Duty cycle  $<0.98$ . A nonconductive material surrounded the EUT to supporting the EUT for standing on three orthogonal planes. At each condition, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

SCHWARZBECK MESS-ELEKTRONIK Biconilog Antenna at 3 Meter and the SCHWARZBECK Double Ridged Guide Antenna was used in frequencies 1 –26.5 GHz at a distance of 3 meter. The antenna at an angle toward the source of the emission. All test results were extrapolated to equivalent signal at 3 meters utilizing an inverse linear distance extrapolation Factor (20 dB/decade).

For testing above 1 GHz, the emission level of the EUT in peak mode was 20 dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. No post – detector video filters were used in the test.

The spectrum analyzer's 6 dB bandwidth was set to 1 MHz, and the analyzer was operated in the peak detection mode, for frequencies both below and up 1 GHz. The average levels were obtained by subtracting the duty cycle correction factor from the peak readings.

The following procedures were used to convert the emission levels measured in decibels referenced to 1 microvolt (dBuV) into field intensity in micro volts pre meter (uV/m).

The actual field intensity in decibels referenced to 1 microvolt in to field intensity in micro volts per meter (dBuV/m).

The actual field is intensity in referenced to 1 microvolt per meter (dBuV/m) is determined by algebraically adding the measured reading in dBuV, the antenna factor (dB), and cable loss (dB) and Subtracting the gain of preamplifier (dB) is auto calculate in spectrum analyzer.

$$(1) \text{ Amplitude (dBuV/m) = FI (dBuV) + AF (dBuV) + CL (dBuV) - Gain (dB)}$$

FI= Reading of the field intensity.

AF= Antenna factor.

CL= Cable loss.

P.S Amplitude is auto calculate in spectrum analyzer.

$$(2) \text{ Actual Amplitude (dBuV/m) = Amplitude (dBuV) - Dis(dB)}$$

The FCC specified emission limits were calculated according the EUT operating frequency and by following linear interpolation equations:

(a) For fundamental frequency : Transmitter Output < +30 dBm

(b) For spurious frequency : Spurious emission limits = fundamental emission limit /10


Data of measurement within this frequency range without mark in the table above means the reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.

### 4.3. Maximum Conducted Output Power Measurement

#### ■ Limit

For systems using digital modulation in the 2400-2483.5 MHz, the limit for peak output power is 30 dBm.

#### ■ Test Setup



#### ■ Test Procedure

The testing follows the Measurement Procedure of ANSI C63.10:2013 section 11.9.2.3.2 Method AVGPM.

The tests below are run with the EUT's transmitter set at high power in TX mode. The EUT is needed to force selection of output power level and channel number. While testing, EUT was set to transmit continuously. Remove the Subjective device's antenna and connect the RF output port to power sensor..


#### 4.4. 6 dB RF Bandwidth Measurement

##### ■ Limit

6 dB RF Bandwidth: Systems using digital modulation techniques may operate in the 2400–2483.5 MHz bands. The minimum 6 dB band-width shall be at least 500 kHz.

99 % Occupied Bandwidth: N/A

##### ■ Test Setup



##### ■ Test Procedure

The EUT tested to DTS test procedure of ANSI C63.10-2013 section 11.8.2 option2 for compliance to FCC 47CFR 15.247 requirements.

6 dB RF Bandwidth: The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RBW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A peak output reading was taken, a DISPLAY line was drawn 6 dB lower than peak level. The 6 dB bandwidth was determined from where the channel output spectrum intersected the display line.


The test was performed at 3 channels (Channel low, middle, high)

## 4.5. Maximum Power Density Measurement

### ■ Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### ■ Test Setup



### ■ Test Procedure

The EUT tested to DTS test procedure of ANSI C63.10:2013 section 11.10.2 Method PKPSD.


1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
4. Set the VBW  $\geq 3 \times \text{RBW}$ .
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

## 4.6. Out of Band Conducted Emissions Measurement

### ■ Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

### ■ Test Setup



### ■ Test Procedure

In any 100 kHz bandwidth outside the EUT pass band, the RF power produced by the modulation products of the spreading sequence, the information sequence, and the carrier frequency shall be at least 20 dB below that of the maximum in-band 100 kHz emission, antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the pass band. The test was performed at 3 channels.

## 4.7. Antenna Measurement

### ■ Limit

For intentional device, according to 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And According to 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### ■ Antenna Connector Construction


See section 2 – antenna information.



## 5 Test Results

### 5.1. Conducted Emission

Standard:	Part 15C	Line:	L1
Test item:	Conducted Emission	Power:	AC 120 V/60 Hz
Mode:	Transmit Mode		
Description:			




No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	0.1580	31.76	15.83	9.54	41.30	25.37	65.57	55.57	-24.27	-30.20	Pass
2	0.1700	33.15	16.15	9.54	42.69	25.69	64.96	54.96	-22.27	-29.27	Pass
3	0.1860	32.26	16.65	9.54	41.80	26.19	64.21	54.21	-22.41	-28.02	Pass
4	0.1940	28.23	11.10	9.54	37.77	20.64	63.86	53.86	-26.09	-33.22	Pass
5	0.2060	25.94	13.41	9.54	35.48	22.95	63.37	53.37	-27.89	-30.42	Pass
6	0.2140	26.82	12.04	9.54	36.36	21.58	63.05	53.05	-26.69	-31.47	Pass

Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).

2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).

Standard:	Part 15C	Line:	N
Test item:	Conducted Emission	Power:	AC 120 V/60 Hz
Mode:	Transmit Mode		
Description:			




No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	0.1500	38.05	15.20	9.60	47.65	24.80	66.00	56.00	-18.35	-31.20	Pass
2	0.1740	33.39	11.60	9.60	42.99	21.20	64.77	54.77	-21.78	-33.57	Pass
3	0.1980	29.19	8.65	9.60	38.79	18.25	63.69	53.69	-24.90	-35.44	Pass
4	0.2500	23.68	7.58	9.60	33.28	17.18	61.76	51.76	-28.48	-34.58	Pass
5	0.4060	23.76	15.11	9.61	33.37	24.72	57.73	47.73	-24.36	-23.01	Pass
6	0.4180	25.89	22.27	9.61	35.50	31.88	57.49	47.49	-21.99	-15.61	Pass

Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).  
2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).

## 5.2. Conducted Test Results

### Duty cycle

Test Mode	Frequency (MHz)	on time (ms)	on+off time (ms)	Duty cycle	Duty Factor (dB)	1/T Minimum VBW (kHz)
SRD	2406	2.160	2.504	0.863	20.642	0.463



Maximum Conducted Output Power Measurement								
Test Mode	Frequency (MHz)	Average Power		Peak Power		Power Limit	RF Power setting in Test	Test Software
		dBm	W	dBm	W	dBm	Software	Version
SRD	2406	-0.99	0.00080	-0.92	0.00081	30.00	0.00	GM51W 0DB0 0D5B
	2440	-1.31	0.00074	-1.23	0.00075	30.00	0.00	
	2474	-1.63	0.00069	-1.52	0.00070	30.00	0.00	

6 dB RF Bandwidth			
Test mode	Frequency	6 dB Bandwidth	6 dB Limit
	(MHz)	(kHz)	(kHz)
SRD	2406	711.4000	$\geq 500$
	2440	707.3000	$\geq 500$
	2474	711.3000	$\geq 500$

## ■ Test Graphs

The figure displays three sequential screenshots of a Keysight Spectrum Analyzer interface, each showing a different center frequency. The interface includes a main plot area, a top control bar, a right-hand settings panel, and a bottom status/metrics section.

### Screenshot 1: 2406 MHz

- Center Frequency:** 2.406000 GHz
- #Video BW:** 300.00 kHz
- Span:** 3 MHz
- Ref Lvl Offset:** 0.80 dB
- Ref Value:** 20.00 dBm
- Metrics:**
  - Occupied Bandwidth: 1.0724 MHz
  - Total Power: 5.89 dBm
  - Transmit Freq Error: 11.214 kHz
  - % of OBW Power: 99.00 %
  - x dB Bandwidth: 711.4 kHz
  - x dB: -6.00 dB

### Screenshot 2: 2440 MHz

- Center Frequency:** 2.440000 GHz
- #Video BW:** 300.00 kHz
- Span:** 3 MHz
- Ref Lvl Offset:** 0.80 dB
- Ref Value:** 20.00 dBm
- Metrics:**
  - Occupied Bandwidth: 1.0738 MHz
  - Total Power: 5.64 dBm
  - Transmit Freq Error: 11.612 kHz
  - % of OBW Power: 99.00 %
  - x dB Bandwidth: 707.3 kHz
  - x dB: -6.00 dB

### Screenshot 3: 2474 MHz


- Center Frequency:** 2.474000 GHz
- #Video BW:** 300.00 kHz
- Span:** 3 MHz
- Ref Lvl Offset:** 0.80 dB
- Ref Value:** 20.00 dBm
- Metrics:**
  - Occupied Bandwidth: 1.0754 MHz
  - Total Power: 5.41 dBm
  - Transmit Freq Error: 12.187 kHz
  - % of OBW Power: 99.00 %
  - x dB Bandwidth: 711.3 kHz
  - x dB: -6.00 dB

Maximum Power Density Measurement			
Test mode	Frequency	Reading	Limit
	(MHz)	(dBm/3 kHz)	(dBm/3 kHz)
SRD	2406	-17.120	$\leq 8$
	2440	-16.980	$\leq 8$
	2474	-17.190	$\leq 8$

## Test Graphs

SRD


2406 MHz



2440 MHz



2474 MHz





## Out of Band Conducted Emissions Measurement




### ■ Test Graphs

#### Reference level







## Out of Band Conducted Emissions

SRD	
2406 MHz	 <p>2406 MHz</p>
2440 MHz	 <p>2440 MHz</p>
2474 MHz	 <p>2474 MHz</p>


## Conducted Band Edge

SRD																																	
2406 MHz	 <p>Marker Table:</p> <table><thead><tr><th>Mode</th><th>Trace</th><th>Scale</th><th>X</th><th>Y</th><th>Function</th><th>Function Width</th><th>Function Value</th></tr></thead><tbody><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>2.406 017 5 GHz</td><td>-0.9913 dBm</td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>2.400 000 0 GHz</td><td>-53.47 dBm</td><td></td><td></td></tr><tr><td>3</td><td>N</td><td>1</td><td>f</td><td>2.390 207 5 GHz</td><td>-53.98 dBm</td><td></td><td></td></tr></tbody></table>	Mode	Trace	Scale	X	Y	Function	Function Width	Function Value	1	N	1	f	2.406 017 5 GHz	-0.9913 dBm			2	N	1	f	2.400 000 0 GHz	-53.47 dBm			3	N	1	f	2.390 207 5 GHz	-53.98 dBm		
Mode	Trace	Scale	X	Y	Function	Function Width	Function Value																										
1	N	1	f	2.406 017 5 GHz	-0.9913 dBm																												
2	N	1	f	2.400 000 0 GHz	-53.47 dBm																												
3	N	1	f	2.390 207 5 GHz	-53.98 dBm																												
2474 MHz	 <p>Marker Table:</p> <table><thead><tr><th>Mode</th><th>Trace</th><th>Scale</th><th>X</th><th>Y</th><th>Function</th><th>Function Width</th><th>Function Value</th></tr></thead><tbody><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>2.474 018 8 GHz</td><td>-1.416 dBm</td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>2.483 500 0 GHz</td><td>-56.44 dBm</td><td></td><td></td></tr><tr><td>3</td><td>N</td><td>1</td><td>f</td><td>2.550 424 8 GHz</td><td>-54.04 dBm</td><td></td><td></td></tr></tbody></table>	Mode	Trace	Scale	X	Y	Function	Function Width	Function Value	1	N	1	f	2.474 018 8 GHz	-1.416 dBm			2	N	1	f	2.483 500 0 GHz	-56.44 dBm			3	N	1	f	2.550 424 8 GHz	-54.04 dBm		
Mode	Trace	Scale	X	Y	Function	Function Width	Function Value																										
1	N	1	f	2.474 018 8 GHz	-1.416 dBm																												
2	N	1	f	2.483 500 0 GHz	-56.44 dBm																												
3	N	1	f	2.550 424 8 GHz	-54.04 dBm																												

### 5.3. Radiated Emission Measurement


Below 1 GHz

Standard:	Part 15C	Test Distance:	3 m
Frequency:	2474 MHz		
Mode:	SRD		
Ant.Polar.:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	224.0000	46.08	-13.20	32.88	46.00	-13.12	QP
2	329.7300	42.79	-8.89	33.90	46.00	-12.10	QP
3	390.8400	40.23	-7.09	33.14	46.00	-12.86	QP
4	418.9700	37.71	-6.25	31.46	46.00	-14.54	QP
5	558.6500	35.60	-3.46	32.14	46.00	-13.86	QP
6	805.0300	33.35	0.85	34.20	46.00	-11.80	QP

Standard:	Part 15C	Test Distance:	3 m
Frequency:	2474 MHz		
Mode:	SRD		
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	222.0600	44.15	-13.21	30.94	46.00	-15.06	QP
2	332.6400	37.73	-8.84	28.89	46.00	-17.11	QP
3	398.6000	38.55	-6.84	31.71	46.00	-14.29	QP
4	493.6600	33.80	-4.63	29.17	46.00	-16.83	QP
5	561.5600	39.89	-3.37	36.52	46.00	-9.48	QP
6	831.2200	32.32	1.06	33.38	46.00	-12.62	QP

## Harmonic


Above 1 GHz

Standard:	Part 15C	Test Distance:	3 m
Test item:	Harmonic		
Frequency:	2406 MHz		
Mode:	SRD		
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4812.000	48.40	5.26	53.66	74.00	-20.34	peak
2	4812.000	35.28	5.26	40.54	54.00	-13.46	AVG
3	7218.000	38.87	13.00	51.87	74.00	-22.13	peak
4	7218.000	27.35	13.00	40.35	54.00	-13.65	AVG

Standard:	Part 15C	Test Distance:	3 m
Test item:	Harmonic		
Frequency:	2406 MHz		
Mode:	SRD		
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4812.000	43.59	5.26	48.85	74.00	-25.15	peak
2	4812.000	34.82	5.26	40.08	54.00	-13.92	AVG
3	7218.000	41.94	13.00	54.94	74.00	-19.06	peak
4	7218.000	29.13	13.00	42.13	54.00	-11.87	AVG

Standard:	Part 15C	Test Distance:	3 m
Test item:	Harmonic		
Frequency:	2440 MHz		
Mode:	SRD		
Ant.Polar.:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4880.000	43.16	5.47	48.63	74.00	-25.37	peak
2	7320.000	34.93	12.90	47.83	74.00	-26.17	peak


Standard:	Part 15C	Test Distance:	3 m
Test item:	Harmonic		
Frequency:	2440 MHz		
Mode:	SRD		
Ant.Polar.:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4880.000	42.30	5.47	47.77	74.00	-26.23	peak
2	7320.000	38.27	12.90	51.17	74.00	-22.83	peak




Standard:	Part 15C	Test Distance:	3 m
Test item:	Harmonic		
Frequency:	2474 MHz		
Mode:	SRD		
Ant.Polar.:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4948.000	39.52	5.38	44.90	74.00	-29.10	peak
2	7422.000	36.62	12.98	49.60	74.00	-24.40	peak

Standard:	Part 15C	Test Distance:	3 m
Test item:	Harmonic		
Frequency:	2474 MHz		
Mode:	SRD		
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4948.000	42.12	5.38	47.50	74.00	-26.50	peak
2	7422.000	38.76	12.98	51.74	74.00	-22.26	peak

## Band edge


### Peak

Standard:	Part 15C	Test Distance:	3 m
Test item:	Band edge		
Frequency:	2406 MHz		
Mode:	SRD		
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.800	61.66	-1.90	59.76	74.00	-14.24	peak
2	2390.000	61.62	-1.90	59.72	74.00	-14.28	peak
3	2406.460	103.34	-1.92	101.42	74.00	27.42	peak

Standard:	Part 15C	Test Distance:	3 m
Test item:	Band edge		
Frequency:	2406 MHz		
Mode:	SRD		
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.660	53.65	-1.90	51.75	74.00	-22.25	peak
2	2390.000	56.70	-1.90	54.80	74.00	-19.20	peak
3	2405.900	96.73	-1.92	94.81	74.00	20.81	peak

Standard:	Part 15C	Test Distance:	3 m
Test item:	Band edge		
Frequency:	2474 MHz		
Mode:	SRD		
Ant.Polar.:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2473.890	105.37	-1.73	103.64	74.00	29.64	peak
2	2483.500	57.15	-1.68	55.47	74.00	-18.53	peak
3	2490.270	65.84	-1.64	64.20	74.00	-9.80	peak


Standard:	Part 15C	Test Distance:	3 m
Test item:	Band edge		
Frequency:	2474 MHz		
Mode:	SRD		
Ant.Polar.:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2474.380	98.46	-1.73	96.73	74.00	22.73	peak
2	2483.500	50.75	-1.68	49.07	74.00	-24.93	peak
3	2489.710	61.29	-1.64	59.65	74.00	-14.35	peak


Average

Standard:	Part 15C	Test Distance:	3 m
Test item:	Band edge		
Frequency:	2406 MHz		
Mode:	SRD		
Ant.Polar.:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.800	53.80	-1.90	51.90	54.00	-2.10	AVG
2	2390.000	53.40	-1.90	51.50	54.00	-2.50	AVG


Standard:	Part 15C	Test Distance:	3 m
Test item:	Band edge		
Frequency:	2406 MHz		
Mode:	SRD		
Ant.Polar.:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.800	52.21	-1.90	50.31	54.00	-3.69	AVG
2	2390.000	53.41	-1.90	51.51	54.00	-2.49	AVG




Standard:	Part 15C	Test Distance:	3 m
Test item:	Band edge		
Frequency:	2474 MHz		
Mode:	SRD		
Ant.Polar.:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	41.52	-1.68	39.84	54.00	-14.16	AVG
2	2489.990	53.27	-1.64	51.63	54.00	-2.37	AVG

Standard:	Part 15C	Test Distance:	3 m
Test item:	Band edge		
Frequency:	2474 MHz		
Mode:	SRD		
Ant.Polar.:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	39.88	-1.68	38.20	54.00	-15.80	AVG
2	2489.920	52.02	-1.64	50.38	54.00	-3.62	AVG

---END---