

RF Exposure Report

Report No.: SA190807C14B-2

FCC ID: I4L-BM25SD

Test Model: MS-5776-A-H

Received Date: Aug. 16, 2019

Date of Evaluation: Sep. 10, 2019

Issued Date: Sep. 16, 2019

Applicant: Micro Star International Co., Ltd.

Address: No. 69, Li-De Street, Jung He City, Taipei Hsien, R.O.C. TAIWAN

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, TAIWAN

**FCC Registration /
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specifically mentioned, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
2.5 Calculation Result of Maximum Conducted Power	6



Release Control Record

Issue No.	Description	Date Issued
SA190807C14B-2	Original Release	Sep. 16, 2019

1 Certificate of Conformity

Product: Edge Computing Gateway

Brand: Conexio

Test Model: MS-5776-A-H

Sample Status: Mass Product

Applicant: Micro Star International Co., Ltd.


Date of Evaluation: Sep. 10, 2019


Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.3 -2002

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by :  , **Date:** Sep. 16, 2019
Lena Wang / Specialist

Approved by :  , **Date:** Sep. 16, 2019
Dylan Chiou / Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

WLAN Antenna

Antenna Type	Manufacturer	Model	Antenna Gain (dBi)	
			BT / WLAN 2.4G	WLAN 5G
Couple antenna	INPAQ	GNCLTEWIFI36U5W-S3-07-A	0.78	-0.45

2.5 Calculation Result of Maximum Conducted Power

<WLAN Antenna >

Band	Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN	2412-2462	23.44	0.78	20	0.053	1.00
	5180-5240	17.80	-0.45	20	0.011	1.00
	5260-5320	17.92	-0.45	20	0.011	1.00
	5500-5700	17.83	-0.45	20	0.011	1.00
	5745-5825	17.98	-0.45	20	0.011	1.00
BT	2402-2480	5.86	0.78	20	0.001	1.00

Note:

- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

--- END ---