

RF Exposure Report

Report No.: SABGSN-WTW-P21080119

FCC ID: I4L-BM25SD

Test Model: BM25

Received Date: Aug. 13, 2021

Date of Evaluation: Sep. 29, 2021

Issued Date: Oct. 15, 2021

Applicant: Micro-Star INT'L Co., Ltd

Address: No. 69, Lide St., Zhonghe Dist., 235 New Taipei City Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, TAIWAN

**FCC Registration /
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SABGSN-WTW-P21080119	Original Release	Oct. 15, 2021

1 Certificate of Conformity

Product: 802.11a/b/g/n/ac + BT 4.2 Module

Brand: MSI

Test Model: BM25

Sample Status: Identical Prototype

Applicant: Micro-Star INT'L Co., Ltd

Date of Evaluation: Sep. 29, 2021

Standards: FCC Part 2 (Section 2.1093)

References Test Guidance : KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Vera Huang, **Date:** Oct. 15, 2021

Vera Huang / Specialist

Approved by : Dylan Chiou, **Date:** Oct. 15, 2021

Dylan Chiou / Senior Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Calculation Result of Maximum Conducted Power

Band	Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN	2412-2462	17.67	1.67	20	0.017	1.00
	5180-5240	17.55	2.14	20	0.019	1.00
	5260-5320	17.47	1.44	20	0.015	1.00
	5500-5700	15.67	2.95	20	0.014	1.00
	5745-5825	16.81	2.37	20	0.016	1.00
BT	2402-2480	5.86	1.67	20	0.001	1.00

Note:

1. Refer to original report (BV CPS report no. SA180518C15) for BT conducted power.
2. The EUT is authorized for use in specific End-product. All models are electrically identical, different model names are for marketing purpose. Please refer to below for more details.

Sample	Product Name	Brand Name	Model Name	Remark
A	Display System	Trimble	137000-99, GFX-1260, XCN-1260, TME-1260	12 inch
B	Display System	Trimble	134000-99, GFX-1060, XCN-1060, TME-1060	10 inch

3. The antenna information is listed as below.

Sample	Antenna type	Antenna Gain (dBi)				
		BT / 2412 ~ 2462 MHz	5180 ~ 5240 MHz	5260 ~ 5320 MHz	5500 ~ 5700 MHz	5745 ~ 5825 MHz
A	PIFA	1.67	2.14	0.79	2.37	2.37
B	PIFA	-0.09	1.24	1.44	2.95	2.29

4. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.
5. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Conclusion:

2.4GHz, 5GHz, and BT can transmit simultaneously, the formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

$$WLAN\ 2.4GHz + WLAN\ 5GHz + BT = 0.017/1 + 0.019/1 + 0.001/1 = 0.037$$

Therefore the maximum calculations of above situations are less than the "1" limit.

--- END ---