

# RF Exposure Evaluation declaration

Product Name : Access Point

Model No.: MS-6809

FCC ID.: I4L-MS6809

Applicant : MICRO-STAR INT'L Co., LTD

Address : No 69, Li-De st., Jung-He City, Taipei Hsien,  
Taiwan, R.O.C

Date of Receipt : June 10, 2003

Date of Declaration : June 13, 2003

Report No. : 036L117FI

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of QuieTek Corporation.

## 1. RF Exposure Evaluation

### 1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency Range (MHz)                                     | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm <sup>2</sup> ) | Average Time (Minutes) |
|---|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| (A) Limits for Occupational/ Control Exposures            |                               |                               |                                     |                        |
| 300-1500  | --                            | --                            | F/300                               | 6                      |
| 1500-100,000  | --                            | --                            | 5                                   | 6                      |
| (B) Limits for General Population/ Uncontrolled Exposures |                               |                               |                                     |                        |
| 300-1500  | --                            | --                            | F/1500                              | 6                      |
| 1500-100,000  | --                            | --                            | 1                                   | 30                     |

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $Pd = (Pout * G) / (4 * \pi * r^2)$

Where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

### 1.3. Test Result of RF Exposure Evaluation

Product : Access Point  
 Test Item : RF Exposure Evaluation  
 Test Site : No.1 OATS  
 Test Mode : Normal Operation

#### Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.5dBi or 2dBi in linear scale.

#### Output Power Into Antenna & RF Exposure Evaluation Distance: (2.5dBi)

| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm <sup>2</sup> ) |
|---------|-------------------------|------------------------------|--|
| 1       | 2412.00                 | 169.8244                     | 0.0601   |
| 6       | 2437.00                 | 121.8990                     | 0.0431   |
| 11      | 2462.00                 | 185.3532                     | 0.0656   |

#### Output Power Into Antenna & RF Exposure Evaluation Distance: (2dBi)

| Channel | Channel Frequency (MHz) | Output Power to Antenna (mW) | Power Density at R = 20 cm (mW/cm <sup>2</sup> ) |
|---------|-------------------------|------------------------------|--|
| 1       | 2412.00                 | 169.8244                     | 0.0535   |
| 6       | 2437.00                 | 121.8990                     | 0.0384   |
| 11      | 2462.00                 | 185.3532                     | 0.0584   |

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.