



**FCC 47 CFR PART 15 SUBPART C**

**TEST REPORT**

**For**

**MICRO-STAR INT'L CO., LTD.**

**MINI PCI CARD**

**Model: MS-6827**

**Trade Name: MSI**

*Prepared for*

**MICRO-STAR INT'L CO., LTD.  
No. 69, Li-De St., Jung-He City,  
Taipei Hsien, Taiwan**

*Prepared by*

**Compliance Certification Services Inc.  
No. 81-1, Lane 210, Bade Rd. 2, Luchu Hsiang,  
Taoyuan Hsien, (338) Taiwan, R.O.C.  
TEL: 886-3-324-0332  
FAX: 886-3-324-5235**



---

*Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document*



**TABLE OF CONTENTS**

1. TEST RESULT CERTIFICATION ..... 3

2. EUT DESCRIPTION ..... 4

3. TEST METHODOLOGY ..... 5

    3.1 EUT CONFIGURATION ..... 5

    3.2 EUT EXERCISE ..... 5

    3.3 GENERAL TEST PROCEDURES ..... 5

    3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS ..... 6

    3.5 DESCRIPTION OF TEST MODES ..... 6

4. INSTRUMENT CALIBRATION ..... 7

5. FACILITIES AND ACCREDITATIONS ..... 8

    5.1 FACILITIES ..... 8

    5.2 EQUIPMENT ..... 8

    5.3 LABORATORY ACCREDITATIONS AND LISTING ..... 8

    5.4 TABLE OF ACCREDITATIONS AND LISTINGS ..... 9

6. SETUP OF EQUIPMENT UNDER TEST ..... 10

    6.1 SUPPORT EQUIPMENT ..... 10

7. FCC PART 15.247 REQUIREMENTS ..... 11

    7.1 BAND EDGES MEASUREMENT ..... 11

    7.2 RADIATED EMISSIONS ..... 17



# 1. TEST RESULT CERTIFICATION

**Applicant:** MICRO-STAR INT'L CO., LTD.  
 No. 69, Li-De St., Jung-He City,  
 Taipei Hsien, Taiwan

**Equipment Under Test:** MINI PCI CARD

**Trade Name:** MSI

**Model:** MS-6827

**Report Number:** B31231402-RP

**Date of Test:** MARCH 2, 2004

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC Part 15 Subpart C	No non-compliance noted

### We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2001) and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247.

The test results of this report relate only to the tested sample identified in this report.

Approved by:

Reviewed by:

\_\_\_\_\_  
 Harris.W. Lai  
 Executive Vice President  
 Compliance Certification Services Inc.

\_\_\_\_\_  
 Devin Chang  
 Section Manager  
 Compliance Certification Services Inc.



## 2. EUT DESCRIPTION

<b>Product</b>	MINI PCI CARD
<b>Trade Name</b>	MSI
<b>Model Number</b>	MS-6827
<b>Model Discrepancy</b>	N/A
<b>Power Supply</b>	Powered by the host
<b>Frequency Range</b>	2412 ~ 2462 MHz
<b>Transmit Power</b>	18.18 dBm
<b>Modulation Technique</b>	DSSS (CCK; DQPSK; DBPSK)
<b>Antenna Specification</b>	PIFA Antennas Ant Gain: -0.34 dBi (max)

*Note: This submittal(s) (test report) is intended for FCC ID:I4L-MS6827 Class II permissive change filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.*

*The major change is added a new antenna. The new antenna information, please refer to antenna spec.*



### **3. TEST METHODOLOGY**

The tests documented in this report were performed in accordance with ANSI C63.4. Radiated testing was performed at an antenna to EUT distance 3 meters.

#### **3.1 EUT CONFIGURATION**

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

#### **3.2 EUT EXERCISE**

The EUT (MINI PCI CARD) was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.247 under the FCC Rules Part 15 Subpart C.

#### **3.3 GENERAL TEST PROCEDURES**

##### **Conducted Emissions**

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4-2001. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

##### **Radiated Emissions**

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4-2001.

### 3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

- (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	( <sup>2</sup> )
13.36 - 13.41	322 - 335.4		

<sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup> Above 38.6

- (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

### 3.5 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

Software used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Based on the Rules, this equipment is subjected to be tested on all the possible operating condition including the positional plane: Only x-plane, y-plane and z-plane be possible in the typical usage – both orthogonal plane have been evaluated and only the worst case data (y-plane) to be filed in the report.

Channel 1 (2412MHz), Channel 6 (2437MHz) and Channel 11 (2462MHz) with 11Mbps highest data rate (worst case) are chosen for the final testing.



#### **4. INSTRUMENT CALIBRATION**

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.



## 5. FACILITIES AND ACCREDITATIONS

### 5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

No. 81-1, Lane 210, Bade Rd. 2, Luchu Hsiang, Taoyuan Hsien, Taiwan, R.O.C.

No. 199, Chunghsen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

### 5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.








All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

### 5.3 LABORATORY ACCREDITATIONS AND LISTING

The test facilities used to perform radiated and conducted emissions tests are accredited by National Voluntary Laboratory Accreditation Program for the specific scope of accreditation under Lab Code: 200600-0 to perform Electromagnetic Interference tests according to FCC PART 15 AND CISPR 22 requirements. No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government. In addition, the test facilities are listed with Federal Communications Commission (registration no: 93105 and 90471).




**5.4 TABLE OF ACCREDITATIONS AND LISTINGS**

Country	Agency	Scope of Accreditation	Logo
USA	NVLAP*	EN 55011, EN 55014-1, AS/NZS 1044, CNS 13783-1, EN 55022, CNS 13438, EN 61000-3-2, EN 61000-3-3, ANSI C63.4, FCC OST/MP-5, AS/NZS 3548, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11	 200600-0
USA	FCC	3/10 meter Open Area Test Sites to perform FCC Part 15/18 measurements	 93105, 90471
Japan	VCCI	4 3/10 meter Open Area Test Sites to perform conducted/radiated measurements	 R-393/1066/725/879 C-402/747/912
Norway	NEMKO	EN 50081-1/2, EN 50082-1/2, IEC 61000-6-1/2, EN 50091-2, EN 50130-4, EN 55011, EN 55013, EN 55014-1/2, EN 55015, EN 55022, EN 55024, EN 61000-3-2/3, EN 61326-1, IEC 61000-4-2/3/4/5/6/8/11, EN 60601-1-2, EN 300 328-2, EN 300 422-2, EN 301 419-1, EN 301 489-01/03/07/08/09/17, EN 301 419-2/3, EN 300 454-2, EN 301 357-2	 ELA 124a ELA 124b ELA 124c
Taiwan	CNLA	EN 300 328-1, EN 300 328-2, EN 300 220-1, EN 300 220-2, EN 300 220-3, 47 CFR FCC Part 15 Subpart C, EN 61000-3-2, EN 61000-3-3, CNS 13439, CNS 13783-1, CNS 14115, CNS 13438, AS/NZS 3548, CNS 13022-1, IEC 61000-4-2/3/4/5/6/8/11, CNS 13022-2/3	 <b>0 3 6 3</b> ILAC MRA
Taiwan	BSMI	CNS 13438, CNS 13783-1, CNS 13439, CNS 14115	 SL2-IS-E-0014 SL2-IN-E-0014 SL2-A1-E-0014 SL2-R1-E-0014 SL2-R2-E-0014 SL2-L1-E-0014
Canada	Industry Canada	RSS212, Issue 1	 IC 3991-3 IC 3991-4

\* No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government.

## 6. SETUP OF EQUIPMENT UNDER TEST

### 6.1 SUPPORT EQUIPMENT



Device Type	Brand	Model	FCC ID	Series No.	Data Cable	Power Cord
Notebook PC	IBM	2656	FCC DoC	AK-VF0HT	N/A	Unshielded, 2.5m

**Notes:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

## 7. FCC PART 15.247 REQUIREMENTS

### 7.1 BAND EDGES MEASUREMENT

#### LIMIT


According to §15.247(c), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

#### MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	US42510252	04/28/2004
Spectrum Analyzer	R&S	FSP30	1093.4495.30	07/22/2004

*Remark: Each piece of equipment is scheduled for calibration once a year.*

#### Test Configuration



#### TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
  - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
  - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.



## **TEST RESULTS**


Refer to attach spectrum analyzer data chart.



### Band Edges (CH Low)

Detector mode: Peak


Polarity: Vertical



Date: 14.JAN.2004 11:43:53

Detector mode: Average

Polarity: Vertical




Date: 14.JAN.2004 11:41:45



Detector mode: Peak


Polarity: Horizontal



Date: 14.JAN.2004 11:45:10

Detector mode: Average

Polarity: Horizontal




Date: 14.JAN.2004 11:48:36



### Band Edges (CH High)

Detector mode: Peak


Polarity: Vertical



Date: 14.JAN.2004 11:35:43

Detector mode: Average

Polarity: Vertical




Date: 14.JAN.2004 11:37:04



Detector mode: Peak


Polarity: Horizontal



Date: 14.JAN.2004 11:31:43

Detector mode: Average

Polarity: Horizontal



Date: 14.JAN.2004 11:33:00





## 7.2 RADIATED EMISSIONS

### LIMIT

1. Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

*Note: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.*

2. In the above emission table, the tighter limit applies at the band edges.

Frequency (Hz)	Field Strength ( $\mu$ V/m at 3-meter)	Field Strength (dB $\mu$ V/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54


**MEASUREMENT EQUIPMENT USED**


Open Area Test Site #3				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	US42510252	04/27/2004
EMI Test Receiver	R&S	ESVS20	838804/004	01/08/2005
Pre-Amplifier	HP	8447D	2944A09173	03/01/2005
Bilog Antenna	SCHWAZBECK	VULB9163	145	07/05/2004
Turn Table	EMCO	2081-1.21	9709-1885	N.C.R
Antenna Tower	EMCO	2075-2	9707-2060	N.C.R
Controller	EMCO	2090	9709-1256	N.C.R
RF Switch	ANRITSU	MP59B	M53867	N.C.R
Site NSA	C&C	N/A	N/A	09/06/2004
Horn Antenna	EMCO	3115	00022250	03/15/2004

**Remark:** Each piece of equipment is scheduled for calibration once a year.

**Test Configuration**

**Below 1 GHz**



**Above 1 GHz****TEST PROCEDURE**

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.



**TEST RESULTS**

**Below 1 GHz**

**Operation Mode:** TX CH Low Mode      **Test Date:** March 2, 2004  
**Temperature:** 20°C      **Tested by:** Max  
**Humidity:** 70 % RH      **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
57.45	V	QP	35.00	-6.82	28.18	40.00	-11.82
66.45	V	QP	44.67	-12.15	32.52	40.00	-7.48
100.20	V	QP	49.67	-18.20	31.47	43.50	-12.03
125.85	V	QP	52.17	-17.89	34.28	43.50	-9.22
199.65	V	QP	48.17	-15.57	32.60	43.50	-10.90
562.50	V	QP	41.67	-7.68	33.99	46.00	-12.01
66.45	H	QP	45.34	-14.57	30.77	40.00	-9.23
126.30	H	QP	52.50	-18.34	34.16	43.50	-9.34
373.50	H	QP	52.34	-10.76	41.58	46.00	-4.42
498.33	H	QP	42.34	-8.21	34.13	46.00	-11.87
561.33	H	QP	43.34	-7.68	35.66	46.00	-10.34
870.50	H	QP	37.67	-4.21	33.46	46.00	-12.54

**Notes:**

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.



**Operation Mode:** TX CH Mid Mode      **Test Date:** March 2, 2004  
**Temperature:** 20°C      **Tested by:** Max  
**Humidity:** 70 % RH      **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
57.45	V	QP	35.00	-6.82	28.18	40.00	-11.82
66.45	V	QP	45.50	-12.15	33.35	40.00	-6.65
99.75	V	QP	49.50	-18.23	31.27	43.50	-12.23
124.50	V	QP	51.34	-17.86	33.48	43.50	-10.02
199.65	V	QP	47.84	-15.57	32.27	43.50	-11.23
498.33	V	QP	42.67	-8.21	34.46	46.00	-11.54
84.45	H	QP	45.84	-18.81	27.03	40.00	-12.97
99.75	H	QP	56.50	-18.23	38.27	43.50	-5.23
199.65	H	QP	48.34	-15.57	32.77	43.50	-10.73
299.10	H	QP	44.17	-12.46	31.71	46.00	-14.29
497.17	H	QP	40.34	-8.23	32.11	46.00	-13.89
561.33	H	QP	41.17	-7.68	33.49	46.00	-12.51

**Notes:**

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown " - " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.



**Operation Mode:** TX CH High Mode      **Test Date:** March 2, 2004  
**Temperature:** 20°C      **Tested by:** Max  
**Humidity:** 70 % RH      **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
35.40	V	QP	29.17	-2.05	27.12	40.00	-12.88
57.45	V	QP	33.67	-6.82	26.85	40.00	-13.15
66.45	V	QP	43.50	-12.15	31.35	40.00	-8.65
124.05	V	QP	51.34	-17.86	33.48	43.50	-10.02
521.67	V	QP	39.84	-8.05	31.79	46.00	-14.21
561.33	V	QP	41.00	-7.68	33.32	46.00	-12.68
34.95	H	QP	29.00	-1.93	27.07	40.00	-12.93
66.90	H	QP	42.17	-14.73	27.44	40.00	-12.56
86.25	H	QP	47.17	-18.90	28.27	40.00	-11.73
100.20	H	QP	56.34	-18.21	38.13	43.50	-5.37
199.65	H	QP	48.17	-15.57	32.60	43.50	-10.90
562.50	H	QP	41.50	-7.68	33.82	46.00	-12.18

**Notes:**

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown " - " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.



**Above 1 GHz**

**Operation Mode:** TX CH Low Mode      **Test Date:** March 2, 2004  
**Temperature:** 20°C      **Humidity:** 70 % RH  
**Tested by:** Max

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
2413.33	V	97.81	Fundamental							
2413.33	H	85.67								
2783.33	V	53.17	---	-2.01	51.16	---	74.00	54.00	-2.84	P
2783.33	H	52.50	---	-2.01	50.49	---	74.00	54.00	-3.51	P
7206.00	V/H	---	---	---	---	---	74.00	54.00	---	
9608.00	V/H	---	---	---	---	---	74.00	54.00	---	
12010.00	V/H	---	---	---	---	---	74.00	54.00	---	
14412.00	V/H	---	---	---	---	---	74.00	54.00	---	
16814.00	V/H	---	---	---	---	---	74.00	54.00	---	
19216.00	V/H	---	---	---	---	---	74.00	54.00	---	
21618.00	V/H	---	---	---	---	---	74.00	54.00	---	
24020.00	V/H	---	---	---	---	---	74.00	54.00	---	

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
5. Spectrum AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms



**Operation Mode:** TX CH Mid Mode      **Test Date:** March 2, 2004  
**Temperature:** 20°C      **Humidity:** 70 % RH  
**Tested by:** Max

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
2436.67	V	102.50	Fundamental							
2430.00	H	101.17								
2060.00	V	57.50	52.14	-4.19	53.31	47.95	74.00	54.00	-6.05	A
2303.33	V	49.34	---	-3.36	45.98	---	74.00	54.00	-8.02	P
2060.00	H	56.17	---	-4.19	51.98	---	74.00	54.00	-2.02	P
2303.33	H	49.34	---	-3.36	45.98	---	74.00	54.00	-8.02	P
7323.00	V/H	---	---	---	---	---	74.00	54.00	---	
9764.00	V/H	---	---	---	---	---	74.00	54.00	---	
12205.00	V/H	---	---	---	---	---	74.00	54.00	---	
14646.00	V/H	---	---	---	---	---	74.00	54.00	---	
17087.00	V/H	---	---	---	---	---	74.00	54.00	---	
19528.00	V/H	---	---	---	---	---	74.00	54.00	---	
21969.00	V/H	---	---	---	---	---	74.00	54.00	---	
24410.00	V/H	---	---	---	---	---	74.00	54.00	---	

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
5. Spectrum AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.





**Operation Mode:** TX CH High Mode      **Test Date:** March 2, 2004  
**Temperature:** 20°C      **Humidity:** 70 % RH  
**Tested by:** Max

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
2463.33	V	98.47	Fundamental							
2463.33	H	99.80								
2086.67	V	55.84	---	-4.10	51.74	---	74.00	54.00	-2.26	P
2326.67	V	50.84	---	-3.29	47.55	---	74.00	54.00	-6.45	P
2086.67	H	55.00	---	-4.10	50.90	---	74.00	54.00	-3.10	P
2326.67	H	51.00	---	-3.29	47.71	---	74.00	54.00	-6.29	P
7440.00	V	---	---	---	---	---	74.00	54.00	---	
9920.00	V	---	---	---	---	---	74.00	54.00	---	
12400.00	V	---	---	---	---	---	74.00	54.00	---	
14880.00	V	---	---	---	---	---	74.00	54.00	---	
17360.00	V	---	---	---	---	---	74.00	54.00	---	
19840.00	V	---	---	---	---	---	74.00	54.00	---	
22320.00	V	---	---	---	---	---	74.00	54.00	---	
24800.00	V	---	---	---	---	---	74.00	54.00	---	

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
5. Spectrum AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms