



## FCC 47 CFR PART 15 SUBPART C

### TEST REPORT

### FOR

Force GC30 GAMING Controller

Model : GC30

Trade Name: msi

Issued to

MICRO-STAR INT'L CO., LTD.

No.69, Lide St., Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C.)

Issued by

WH Technology Corp.



<b>Open Site</b>	<b>No. 120, Ln. 5, Hudong St., Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)</b>	
<b>EMC Test Site</b>	<b>Xizhi Office and Lab</b>	<b>12F.-3, No.27-1, Ln. 169, Kangning St., Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)</b>

*Note: This test refers exclusively to the test presented test model and sample. This report shall not be reproduced except in full, without the written approval of WH Technology Corp. This document may be altered or revised by WH Technology Corp. Personnel only, and shall be noted in the revision section of the document.*



---

<b>TABLE OF CONTENTS</b>	<b>2</b>
<b>1. GENERAL INFORMATION</b>	<b>3</b>
1.1 DESCRIPTION OF THE TESTED SAMPLES	4
<b>2. TEST METHODOLOGY</b>	<b>6</b>
2.1 GENERAL TEST PROCEDURES	6
2.2 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS	7
2.3 DESCRIPTION OF TEST MODES	8
2.4 DESCRIPTION OF THE SUPPORT EQUIPMENTS	8
<b>3. TEST AND MEASUREMENT EQUIPMENT</b>	<b>10</b>
3.1 CALIBRATION	10
3.2 EQUIPMENT	10
<b>4. SECTION 15.249 REQUIREMENTS (FUNDAMENTAL/ HARMONICS)</b>	<b>12</b>
4.1 TEST SETUP	12
4.2 LIMIT	12
4.3 RESULT: PASSED	12
4.4 TEST DATA:	12
<b>5. SECTION 15.205 REQUIREMENTS (BAND EDGE)</b>	<b>18</b>
5.1 TEST SETUP	26
5.2 LIMIT	26
5.3 RESULT: PASSED	19
5.4 TEST DATA:	27
<b>6. SECTION 15.209 REQUIREMENTS (GENERAL RADIATED EMISSION)</b>	<b>22</b>
6.1 TEST SETUP	22
6.2 LIMIT	23
6.3 TEST PROCEDURE	34
6.4 RESULT: PASSED	34
6.5 TEST DATA:	35
<b>7. SECTION 15.207 REQUIREMENTS (POWERLINE CONDUCTED EMISSIONS)</b>	<b>28</b>
<b>APPENDIX 1 PHOTOS OF TEST CONFIGURATION</b>	
<b>APPENDIX 2 PHOTOS OF EUT</b>	



## 1. GENERAL INFORMATION

**Applicant** : MICRO-STAR INT'L CO., LTD.  
**Address** : No.69, Lide St., Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C.)  
**Manufacturer** : MICRO-STAR INT'L CO., LTD.  
**Address** : No.69, Lide St., Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C.)  
**EUT** : Force GC30 GAMING Controller  
**Model Name** : GC30  
**Model Differences** : N/A

Is here with confirmed to comply with the requirements set out in the FCC Rules and Regulations Part 15 Subpart C and the measurement procedures were according to ANSI C63.4-2014. The said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment are within the compliance requirements.

### FCC part 15 subpart C


Receipt Date : 08/23/2017

Final Test Date : 10/17/2017

**Tested By:**

**Reviewed by:**

Oct. 17, 2017  
**Date**

  
Bell Wei/ Engineer

Oct. 17, 2017  
**Date**

  
Mike Lee / Manager

Designation Number: TW1083



---

**1.1 DESCRIPTION OF THE TESTED SAMPLES**

EUT Name : Force GC30 GAMING Controller

Model Number :: GC30

FCCID Number I4LGC30TX

Receipt Date : 10/17/2017

Input Voltage : 5 Vdc (From PC)

Power From  Inside  Outside  
 Adaptor  BATTERY  AC Power Source  
 DC Power Source  Support Unit PC

Operate Frequency : Refer to the channel list as described below

Modulation Technique : GFSK

Number of Channels : 63

Channel spacing :  N/A  1 MHz

Operating Mode :  Simplex  Half Duplex

Antenna Type :  integral antenna: PCB Printing  
 a dedicated antenna

Antenna gain 0 dBi



Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2412	20	2432	40	2452	60	2472
01	2413	21	2433	41	2453	61	2473
02	2414	22	2434	42	2454	62	2474
03	2415	23	2435	43	2455	63	2475
04	2416	24	2436	44	2456	---	---
05	2417	25	2437	45	2457	---	---
06	2418	26	2438	46	2458	---	---
07	2419	27	2439	47	2459	---	---
08	2420	28	2440	48	2460	---	---
09	2421	29	2441	49	2461	---	---
10	2422	30	2442	50	2462	---	---
11	2423	31	2443	51	2463	---	---
12	2424	32	2444	52	2464	---	---
13	2425	33	2445	53	2465	---	---
14	2426	34	2446	54	2466	---	---
15	2427	35	2447	55	2467	---	---
16	2428	36	2448	56	2468	---	---
17	2429	37	2449	57	2469	---	---
18	2430	38	2450	58	2470	---	---
19	2431	39	2451	59	2471	---	---



## **2. TEST METHODOLOGY**

All testing as described bellowed were performed in accordance with ANSI C63.4:2014 and FCC CFR 47 Part 15 Subpart C.

### **2.1 GENERAL TEST PROCEDURES**

#### **Conducted Emissions**

The EUT is placed on a wood table, which is at 0.8 m above ground plane acceding to clause 15.207 and requirements of ANSI C63.4:2014. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz are using CISPR Quasi-Peak / Average detectors.

#### **Radiated Emissions**

The EUT is a placed on a turn table, which is 0.8 m above ground plane. The turntable was rotated through 360 degrees to determine the position of maximum emission level. The EUT is placed at 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.



**2.2 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS**

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

<b>MHz</b>	<b>MHz</b>	<b>MHz</b>	<b>GHz</b>
0.090 - 0.110	16.42 - 16.423		
10.495 - 0.505	16.69475 -	399.9 - 410	4.5 - 5.15
2.1735 - 2.1905	16.69525	608 - 614	5.35 - 5.46
4.125 - 4.128	16.80425 -	960 - 1240	7.25 - 7.75
4.17725 - 4.17775	16.80475	1300 - 1427	8.025 - 8.5
4.20725 - 4.20775	25.5 - 25.67	1435 - 1626.5	9.0 - 9.2
6.215 - 6.218	37.5 - 38.25	1645.5 - 1646.5	9.3 - 9.5
6.26775 - 6.26825	73 - 74.6	1660 - 1710	10.6 - 12.7
6.31175 - 6.31225	74.8 - 75.2	1718.8 - 1722.2	13.25 - 13.4
8.291 - 8.294	108 - 121.94	2200 - 2300	14.47 - 14.5
8.362 - 8.366	123 - 138	2310 - 2390	15.35 - 16.2
8.37625 - 8.38675	149.9 - 150.05	2483.5 - 2500	17.7 - 21.4
8.41425 - 8.41475	156.52475 -	2655 - 2900	22.01 - 23.12
12.29 - 12.293	156.52525	3260 - 3267	23.6 - 24.0
12.51975 - 12.52025	156.7 - 156.9	3332 - 3339	31.2 - 31.8
12.57675 - 12.57725	162.0125 - 167.17	3345.8 - 3358	36.43 - 36.5
13.36 - 13.41	167.72 - 173.2	3600 - 4400	( )
	240 - 285		
	322 - 335.4		

1 Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

2 Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

**2.3 DESCRIPTION OF TEST MODES**

The EUT was tested under following modes:

**Modes:**

- 1. Continuous transmitting**

**Channels:**

- 1. 2.412 GHz (Lowest Channel)**
- 2. 2.440 GHz (Middle Channel)**
- 3. 2.475 GHz (Highest Channel)**



## **2.4 DESCRIPTION OF THE SUPPORT EQUIPMENTS**

### **Setup Diagram**

See test photographs attached in appendix 1 for the actual connections between EUT and support equipment.







**Support Equipment**

Peripherals Devices:

OUTSIDE SUPPORT EQUIPMENT							
No.	Equipment	Model	Serial No.	FCC ID/ BSMI ID	Trade name	Data Cable	Power Cord
1.	N/A	N/A	N/A	N/A	N/A	N/A	N/A
INSIDE SUPPORT EQUIPMENT							
No.	Equipment	Model	Serial No.	FCC ID/ BSMI ID	Trade name	Data Cable	Power Cord
1.	N/A	N/A	N/A	N/A	N/A	N/A	N/A

**Note:** All the above equipment /cable were placed in worse case position to maximize emission signals during emission test

**Grounding:** Grounding was in accordance with the manufacturer's requirement and conditions for the intended use.



### 3. TEST AND MEASUREMENT EQUIPMENT

#### 3.1 CALIBRATION

The measuring equipment utilized to perform the tests documented in the report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

#### 3.2 EQUIPMENT

The following list contains measurement equipment used for testing. The equipment conforms to the requirement of CISPR 16-1, ANSI C63.2 and. Other required standards.

Calibration of all test and measurement, including any accessories that may effect such calibration, is checked frequently to ensure the accuracy. Adjustments are made and correction factors are applied in accordance with the instructions contained in the respective.

**Table 1 List of Test and Measurement Equipment**

Test Site	Instrument	Manufacturer	Model No.	S/N	Next Cal. Date
Conduction	Spectrum (9K--3GHz)	R&S	FSP3	833387/010	2018/09/20
	EMI Receiver	R&S	ESHS10	830223/008	2018/06/06
	LISN	Rolf Heine Hochfrequenztech nik	NNB-2/16z	98062	2018/06/11
	ISN	Schwarzbeck	8-Wire ISN CAT5	CAT5-8158-0094	2018/09/21
	RF Cable	N/A	N/A	EMI-3	2017/10/19
Radiation	Bilog antenna(30M-1G)	ETC	MCTD2786B	BLB16M04004/JB-5-004	2018/05/18
	Double Ridged Guide Horn antenna(1G-18G)	ETC	MCTD 1209	DRH15N02009	2017/11/23
	Horn antenna (18G-26G)	com-power	AH-826	81000	2018/08/16
	LOOP Antenna (Below 30M)	com-power	AL-130	17117	2018/10/04
	Pre amplifier (30M-1G)	EMC INSTRUMENT	EMC9135	980334	2018/05/03
	Microwave Preamplifier (1G-18G)	EMC INSTRUMENT	EMC051845	980108&AT-18001	2017/10/23
	Pre amplifier	MITEQ	JS4-18002600-30-	808329	2018/08/09



	(18G~26G)		5A		
	EMI Test Receiver	R&S	ESVS30 (20M-1000MHz)	826006/002	2017/11/28
	RF Cable (open site)	EMCI	N male on end of both sides (EMI4)	30m	2017/10/19
	RF CABLE (1~26G)	HARBOUT INDUSTRIES	LL142MI(4M+4M)	NA	2018/04/17
	RF CABLE (1~26G)	HARBOUR INDUSTRIES	LL142MI(7M)	NA	2018/08/09
	Spectrum (9K--7GHz)	R&S	FSP7	830180/006	2018/04/14
	Spectrum (9K--40GHz)	AGILENT	8564EC	4046A0032	2018/03/01
Software	e3	AUDIX	N/A	N/A	N/A
SG	SINGAL GENERATOR (100k-1GHz)	HP	8648A	3619U0042 6	N/A

● CALIBRATION INTERVAL OF INSTRUMENTS LISTED ABOVE IS ONE YEAR



#### **4. SECTION 15.249 REQUIREMENTS (FUNDAMENTAL/ HARMONICS)**

##### **4.1 TEST SETUP**

Refer to paragraph 6.1.

##### **4.2 LIMIT**

<b>Fundamental Frequency (MHz)</b>	<b>Field Strength of Fundamental (dB<math>\mu</math>V/m at 3-meter)</b>	<b>Detector</b>
902 - 928 2400 - 2483 5725 - 5875	114	Peak
902 - 928 2400 - 2483 5725 - 5875	94	AV

<b>Fundamental Frequency (MHz)</b>	<b>Field Strength of Harmonics (dB<math>\mu</math>V/m at 3-meter)</b>	<b>Detector</b>
902 - 928 2400 - 2483 5725 - 5875	74	Peak
902 - 928 2400 - 2483 5725 - 5875	54	AV


##### **4.3 RESULT: PASSED**

##### **4.4 TEST DATA:**



**Fundamental**

Power	: DC 5V	Pol/Phase	: HORIZONTAL
Test Mode 1	: TX-LO 2412-MI 2440-HI 2475MHz	Temperature	: 33 °C
Memo	:	Humidity	: 64 %




**Remarks:**  
 : 1.Result=Read Value+Factor  
 : 2.Factor=Antenna Factor+Cable loss-  
 : Amplifier Factor

	Read			Limit	Over	
Freq	Level	Factor	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2412.000	94.65	-14.00	80.65	114.00	-33.35 Peak
2 @	2440.000	94.86	-13.93	80.93	114.00	-33.07 Peak
3	2475.000	94.23	-13.85	80.38	114.00	-33.62 Peak



Power	: DC 5V	Pol/Phase	: VERTICAL
Test Mode 1	: TX-LO 2412-MI 2440-HI 2475MHz	Temperature	: 33 °C
Memo	:	Humidity	: 64 %




**Remarks:**  
 : 1.Result=Read Value+ Factor  
 : 2.Factor=Antenna Factor+Cable loss-  
 : Amplifier Factor

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2412.000	96.20	-14.00	82.20	114.00	-31.80	Peak
2 @	2440.000	96.54	-13.93	82.61	114.00	-31.39	Peak
3	2475.000	95.77	-13.85	81.92	114.00	-32.08	Peak



**Harmonics**

Power	: DC 5V	Pol/Phase	: HORIZONTAL
Test Mode 1	: TX-LO 2412-MI 2440-HI 2475MHz	Temperature	: 33 °C
Memo	:	Humidity	: 64 %




**Remarks:**  
 : 1.Result=Read Value+ Factor  
 : 2.Factor=Antenna Factor+Cable loss-  
 : Amplifier Factor

	Read	Limit	Over				
Freq	Level	Factor	Level	Line			
MHz	dBuV	dB/m	dBuV/m	dBuV/m			
1	4824.000	53.11	-6.32	46.79	74.00	-27.21	Peak
2 @	4880.000	53.00	-6.17	46.83	74.00	-27.17	Peak
3	4950.000	52.51	-5.97	46.54	74.00	-27.46	Peak



Power	: DC 5V	Pol/Phase	: VERTICAL
Test Mode 1	: TX-LO 2412-MI 2440-HI 2475MHz	Temperature	: 33 °C
Memo	:	Humidity	: 64 %



**Remarks:** : 1.Result=Read Value+Factor  
: 2.Factor=Antenna Factor+Cable loss-  
: Amplifier Factor

	Read Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	4824.000	54.65	-6.32	48.33	74.00	-25.67	Peak
2 @	4880.000	54.85	-6.17	48.68	74.00	-25.32	Peak
3	4950.000	54.01	-5.97	48.04	74.00	-25.96	Peak





Note:

1. Emission level = Reading level + Correction factor
2. Correction factor : Antenna factor, Cable loss, Pre-Amp, etc.
3. All emissions as described above were determining by rotating the EUT through three orthogonal axes to maximizing the emissions if the EUT belongs to hand-held or body-worn devices.
4. Measurements above 1000 MHz, Peak detector setting: use a 1 MHz RBW, a 3 MHz VBW.
5. Measurements above 1000 MHz, Average detector setting: 1 MHz RBW with 10 Hz VBW
6. Peak detector measurement data will represent the worst case results.
7. “---” denotes the data which is not available.



**5. SECTION 15.205 REQUIREMENTS (BAND EDGE)**

**5.1 TEST SETUP**

Refer to paragraph 6.1.

**5.2 LIMIT**

Restricted Bands:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )
13.36 - 13.41			

Operation within the bands:

902 - 928 MHz, 2400 - 2483.5 MHz, 5725 - 5875 MHz, and 24.0 - 24.25 GHz.


Frequency (Hz)	Field Strength ( $\mu$ V/m at 3-meter)	Field Strength (dB $\mu$ V/m at 3-meter)
1.705-30	30 (at 30-meter)	49.5
30-88	100	40
88-216	150	43
216-960	200	46
Above 960	500	54



5.3 RESULT: PASSED

5.4 TEST DATA:

Power	: DC 5V	Pol/Phase	: HORIZONTAL
Test Mode 1	: CH LO & HI –Restricted Bands	Temperature	: 33 °C
Memo	:	Humidity	: 64 %




Remarks: : 1.Result=Read Value+Factor  
: 2.Factor=Antenna Factor+Cable loss-  
: Amplifier Factor

	Read			Limit	Over	
Freq	Level	Factor	Level	Line	Limit	Remark
-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	2376.300	54.59	-14.08	40.51	74.00	-33.49 Peak
2 @	2506.400	54.57	-13.78	40.79	74.00	-33.21 Peak



Power	: DC 5V	Pol/Phase	: VERTICAL
Test Mode 1	: CH LO & HI –Restricted Bands	Temperature	: 33 °C
Memo	:	Humidity	: 64 %



**Remarks:**  
 : 1.Result=Read Value+Factor  
 : 2.Factor=Antenna Factor+Cable loss-  
 : Amplifier Factor

	Read	Limit	Over				
Freq	Level	Factor	Level	Line			
MHz	dBuV	dB/m	dBuV/m	dBuV/m			
1	2378.200	56.36	-14.08	42.28	74.00	-31.72	Peak
2 @	2506.600	56.37	-13.78	42.59	74.00	-31.41	Peak




Note:

1. Emission level = Reading level + Correction factor
2. Correction factor : Antenna factor, Cable loss, Pre-Amp, etc.
3. All emissions as described above were determining by rotating the EUT through three orthogonal axes to maximizing the emissions if the EUT belongs to hand-held or body-worn devices.
4. Measurements above 1000 MHz, Peak detector setting: use a 1 MHz RBW, a 3 MHz VBW.
5. Measurements above 1000 MHz, Average detector setting: 1 MHz RBW with 10 Hz VBW.
6. Peak detector measurement data will represent the worst case results.



## 6. SECTION 15.209 REQUIREMENTS (GENERAL RADIATED EMISSION)

### 6.1 TEST SETUP





## 6.2 LIMIT

The field strength of any emissions which appear outside of this band shall not exceed the general radiated emission limits in section 15.209 as below.

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
1.705-30	30	30
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500*	3

*\*Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under*

*other sections of this Part, e.g., Sections 15.231 and 15.241.*

*In the above emission table, the tighter limit applies at the band edges.*

Frequency (Hz)	Field Strength ( $\mu\text{V/m}$ at 3-meter)	Field Strength (dB $\mu\text{V/m}$ at 3-meter)
1.705-30	30 (at 30-meter)	49.5
30-88	100	40
88-216	150	43
216-960	200	46
Above 960	500	54



### **6.3 TEST PROCEDURE**

1. The EUT was placed on a turntable, which was 0.8m above ground plane.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT was set at 3m away from the receiving antenna, which was varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was maximized by changing the polarization of receiving antenna, both horizontal and vertical.
6. Repeated above procedures until the measurements for all frequencies are completed.

### **6.4 RESULT: PASSED**






**6.5 TEST DATA:**

All frequencies not described in this test report and within the range of the general radiated emission limits are not detectable significantly. The table as below is representing worst emissions found.

Power	: DC 5V	Pol/Phase	: HORIZONTAL
Test Mode 1	: TX 2440MHz	Temperature	: 33 °C
Memo	:	Humidity	: 64 %




Remarks: : 1.Result=Read Value+Factor  
: 2.Factor=Antenna Factor+Cable loss-  
: Amplifier Factor

	Read Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1 @	119.240	52.12	-15.03	37.09	43.50	-6.41	QP
2	179.380	55.21	-19.18	36.03	43.50	-7.47	QP
3	431.580	46.38	-10.51	35.87	46.00	-10.13	QP
4	527.610	44.24	-9.03	35.21	46.00	-10.79	QP
5	768.170	44.78	-5.87	38.91	46.00	-7.09	QP
6	858.380	39.24	-4.05	35.19	46.00	-10.81	QP



Power	: DC 5V	Pol/Phase	: VERTICAL
Test Mode 1	: TX 2440MHz	Temperature	: 33 °C
Memo	:	Humidity	: 64 %



**Remarks:** : 1.Result=Read Value+Factor  
: 2.Factor=Antenna Factor+Cable loss-  
: Amplifier Factor

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1 @	179.380	57.94	-19.18	38.76	43.50	-4.74	QP
2	224.000	51.05	-17.72	33.33	46.00	-12.67	QP
3	696.390	37.95	-7.08	30.87	46.00	-15.13	QP
4	768.170	38.78	-5.87	32.91	46.00	-13.09	QP
5	864.200	37.63	-4.04	33.59	46.00	-12.41	QP
6	925.310	36.75	-2.74	34.01	46.00	-11.99	QP




Note:

1. Emission level = Reading level + Correction factor
2. Correction factor : Antenna factor, Cable loss, Pre-Amp, etc.
3. All emissions as described above were determining by rotating the EUT through three orthogonal axes to maximizing the emissions if the EUT belongs to hand-held or body-worn devices.
4. Measurements from 9 kHz to 150 kHz, Peak detector setting: 100 Hz RBW
5. Measurements from 150 kHz to 30MHz, Peak detector setting: 10 kHz RBW
6. Measurements from 30 MHz to 1000 MHz, Peak detector setting: 100 kHz RBW
7. Measurements from 9 kHz to 150 kHz, CISPR Quasi-Peak detector: 200 Hz RBW
8. Measurements from 150 kHz to 30MHz, CISPR Quasi-Peak detector: 9 kHz RBW
9. Measurements from 30 MHz to 1000 MHz, CISPR Quasi-Peak detector: 120 kHz RBW
10. Peak detector measurement data will represent the worst case results.



## 7. SECTION 15.207 REQUIREMENTS (POWERLINE CONDUCTED EMISSIONS)

### 7.1 TEST SETUP



### 7.2 LIMIT

Frequency range (MHz)	CLASS B	
	QP dB(uV)	Average dB(uV)
0.15-0.5	66 - 56 dBuV	56 - 46 dBuV
0.5-5.0	56 dBuV	46 dBuV
5.0-30.0	60 dBuV	50 dBuV

Remark: In the above table, the tighter limit applies at the band edges.

### 7.3 TEST PROCEDURE

The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). It provides a 50 ohm / 50 μH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50 ohm / 50 μH coupling impedance with 50 ohm termination. (Please refer to the block diagram of the test setup and photograph.)

Both sides of AC line are checked for the maximum conducted emission interference. In order to find the maximum emissions, the relating positions of equipment and all of the interference cables must be changed according to EN 55022 regulations: The measurement procedure on conducted emission interference.

The resolution bandwidth of the field strength meter is set at 9 KHz.



**7.4 TEST SPECIFICATION**

According to PART15.207

**7.5 RESULT: PASSED**


EMI Receiver/Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range:	150KHz--30MHz
Detector Function:	Quasi-Peak / Average Mode
Resolution Bandwidth:	9KHz

**7.6 TEST DATA:**



Power	: DC 5V	Pol/Phase	: LINE
Test Mode 1	: TX 2440 MHz	Temperature	: 25.1 °C
Memo	:	Humidity	: 42 %




Remarks: : Factor=Insertion loss+Cable loss

	Read	Over	Limit	Limit	Line	Remark
Freq	Level	Level	Factor	Limit	Line	Remark
MHz	dBuV	dBuV	dB	dB	dBuV	
1	0.20	34.63	44.74	10.11	-18.88	63.62 Peak
2	0.48	30.03	40.17	10.14	-16.15	56.32 Peak
3	1.04	24.00	34.17	10.17	-21.83	56.00 Peak
4 @	3.24	33.71	43.98	10.27	-12.02	56.00 Peak
5	7.25	32.97	43.36	10.39	-16.64	60.00 Peak
6	24.14	37.16	47.93	10.77	-12.07	60.00 Peak





Power	: DC 5V	Pol/Phase	: NEUTRAL
Test Mode 1	: TX 2440MHz	Temperature	: 25.1 °C
Memo	:	Humidity	: 42 %



Remarks:

: Factor=Insertion loss+Cable loss

	Freq	Read Level	Level	Factor	Over Limit	Limit Line	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	
1	0.20	33.05	43.24	10.19	-20.34	63.58	Peak
2	0.41	29.34	39.57	10.23	-18.16	57.73	Peak
3	1.22	26.53	36.81	10.28	-19.19	56.00	Peak
4	3.33	33.07	43.47	10.40	-12.53	56.00	Peak
5	7.65	31.97	42.51	10.54	-17.49	60.00	Peak
6 @	23.76	37.87	48.61	10.74	-11.39	60.00	Peak