

**Date: 2001-10-26**

# **TEST REPORT**

**Page 1 of 20**

**No.: HM106103**

## **FCC PART 15 SUBPART C CERTIFICATION REPORT**

### **FOR LOW POWER TRANSMITTER**

**TEST REPORT No.: HM106103**

Equipment Under Test [EUT]:

Model Number:

Applicant:

FCC ID :

WALKIE TALKIE

66446

TIGER ELECTRONICS INC.

I54-66446

Date: 2001-10-26

# **TEST REPORT**

Page 2 of 20

No.: HM106103

## **CONTENT:**

Cover  
Content  
Conclusion

Page 1 of 20  
Page 2-3 of 20  
Page 4 of 20

### **1.0 General Details**

|     |                                                                                   |              |
|-----|-----------------------------------------------------------------------------------|--------------|
| 1.1 | Test Laboratory                                                                   | Page 5 of 20 |
| 1.2 | Applicant Details<br>Applicant<br>HKSTC Code Number for Applicant<br>Manufacturer | Page 5 of 20 |
| 1.3 | Equipment Under Test [EUT]<br>Description of EUT operation                        | Page 6 of 20 |
| 1.4 | Date of Order                                                                     | Page 6 of 20 |
| 1.5 | Submitted Sample                                                                  | Page 6 of 20 |
| 1.6 | Test Duration                                                                     | Page 6 of 20 |
| 1.7 | Country of Origin                                                                 | Page 6 of 20 |
| 1.8 | Additional Information of EUT                                                     | Page 7 of 20 |

### **2.0 Technical Details**

|     |                                    |              |
|-----|------------------------------------|--------------|
| 2.1 | Investigations Requested           | Page 8 of 20 |
| 2.2 | Test Standards and Results Summary | Page 8 of 20 |

### **3.0 Test Results**

|     |                       |                  |
|-----|-----------------------|------------------|
| 3.1 | Emission              | Page 9-14 of 20  |
| 3.2 | Bandwidth Measurement | Page 15-17 of 20 |

Date: 2001-10-26

# **TEST REPORT**

Page 3 of 20

No.: HM106103

## **Appendix A**

List of Measurement Equipment

Page 18 of 20

## **Appendix B**

Photographs

Page 19-20 of 20

Date: 2001-10-26

## **TEST REPORT**

Page 4 of 20

No.: HM106103

### **CONCLUSION**

The submitted product was deemed to have COMPLIED with the requirements of Federal Communications Commission [FCC] Rules and Regulations Part 15. The tests were performed in accordance with the standards described above and on Section 2.2 in this Test Report.

Law Man Kit

---

Verify by

Patrick Wong

---

Patrick Wong  
for Managing Director

Date: 2001-10-26

## **TEST REPORT**

Page 5 of 20

No.: HM106103

### **1.0 General Details**

#### **1.1 Test Laboratory**

The Hong Kong Standards and Testing Centre Ltd.  
EMC Laboratory  
10 Dai Wang Street, Taipo Industrial Estate  
New Territories, Hong Kong

Telephone: 852 2666 1888  
Fax: 852 2664 4353

#### **1.2 Applicant Details** **Applicant**

TIGER ELECTRONICS INC.  
980 Woodlands Parkway, Vernon Hills, IL 60061, USA

Telephone: 879 913 8100  
Fax: 847 913 8118

**HKSTC Code Number for Applicant**

**TIE003**

#### **Manufacturer**

TSUEN SHING ENTERPRISES LTD.  
Flat 8-10, 8/F., Kar Wah Industrial Building,  
Hei Yip Street, YLTL #356, Yuen Long, N.T., Hong Kong

Telephone: 852 24740130  
Fax: 852 24731801

Date: 2001-10-26

## **TEST REPORT**

Page 6 of 20

No.: HM106103

### **1.3 Equipment Under Test [EUT] Description of Sample**

Product: Walkie Talkie  
Manufacturer: Tsuen Shing Enterprises Ltd.  
Brand Name: B.U.M. Wrist Gauntlet  
Model Number: 66446  
Input Voltage: 9Vd.c ("6F22" size battery x 1)

#### **1.3.1 Description of EUT Operation**

The Equipment Under Test(EUT) is an Tiger Electronics Inc., 49.86MHz Walkie Talkie. The transmitter is a 2 button transmitter. The EUT continues to transmit while button is being pressed. It is voice transmission, Modulation by Mic. and tape is frequency modulation.

### **1.4 Date of Order**

2001-10-16

### **1.5 Submitted Sample(s):**

2 Samples per model

### **1.6 Test Duration**

2001-10-23

### **1.7 Country of Origin**

China

Date: 2001-10-26

**TEST REPORT**

Page 7 of 20

No.: HM106103

**1.8 Additional Information of EUT**

|                                    | Submitted                           | Not Available            |
|------------------------------------|-------------------------------------|--------------------------|
| User Manual                        | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| Part List                          | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| Circuit Diagram                    | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| Printed Circuit Board [PCB] Layout | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| Rating Label                       | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| Block diagram                      | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| FCC ID Label                       | <input checked="" type="checkbox"/> | <input type="checkbox"/> |

Date: 2001-10-26

## **TEST REPORT**

Page 8 of 20

No.: HM106103

### **2.0 Technical Details**

#### **2.1 Investigations Requested**

Perform ElectroMagnetic Interference measurement in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15 and ANSI C63.4: 2000 for FCC Certification.

#### **2.2 Test Standards and Results Summary Tables**

| <b>EMISSION<br/>Results Summary</b>                                |                  |                  |                     |                                     |                          |                                     |
|--------------------------------------------------------------------|------------------|------------------|---------------------|-------------------------------------|--------------------------|-------------------------------------|
| Test Condition                                                     | Test Requirement | Test Method      | Class /<br>Severity | Test Result                         |                          |                                     |
|                                                                    |                  |                  |                     | Pass                                | Failed                   | N/A                                 |
| Field Strength of<br>Fundamental Emissions<br>& Spurious Emissions | FCC 47CFR 15.235 | ANSI C63.4: 2000 | N/A                 | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>            |
| Radiated Emissions,<br>30MHz to 1GHz                               | FCC 47CFR 15.209 | ANSI C63.4: 2000 | Class B             | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>            |
| Conducted Emissions on<br>AC, 0.45MHz to 30MHz                     | FCC 47CFR 15.207 | ANSI C63.4: 2000 | Class B             | <input type="checkbox"/>            | <input type="checkbox"/> | <input checked="" type="checkbox"/> |

Note: N/A - Not Applicable


**3.0 Test Results****3.1 Emission****3.1.1 Radiated Emissions**

|                    |                  |
|--------------------|------------------|
| Test Requirement:  | FCC 47CFR 15.235 |
| Test Method:       | ANSI C63.4:2000  |
| Test Date:         | 2001-10-23       |
| Mode of Operation: | On mode          |

**Test Method:**

The sample was placed 0.8m above the ground plane on the OATS \*. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigate all operating modes, rotated about all 3 axis (X, Y & Z) to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

\*: OATS [Open Area Test Site] located at HKSTC with a metal ground plane on filed with the FCC pursuant to section 2.948 of the FCC rules, with Registration Number: 90657.

**Test Setup:**

Date: 2001-10-26

## TEST REPORT

Page 10 of 20

No.: HM106103

### Limits for Field Strength of Fundamental Emissions [FCC 47CFR 15.235]:

| Frequency Range of<br>Fundamental<br>[MHz] | Field Strength of<br>Fundamental Emission<br>[Peak]<br>[μV/m] | Field Strength of<br>Fundamental Emission<br>[Average]<br>[μV/m] |
|--------------------------------------------|---------------------------------------------------------------|------------------------------------------------------------------|
| 49.82-49.90                                | 100,000                                                       | 10,000                                                           |

### Results:

#### Transmitter

| Field Strength of Fundamental Emissions<br>Peak Value |                      |                              |                             |                           |                         |                     |
|-------------------------------------------------------|----------------------|------------------------------|-----------------------------|---------------------------|-------------------------|---------------------|
| Frequency<br>MHz                                      | Level<br>@3m<br>dBμV | Correction<br>Factor<br>dB/m | Field<br>Strength<br>dBμV/m | Field<br>Strength<br>μV/m | Limit **<br>@3m<br>μV/m | Antenna<br>Polarity |
| 49.86                                                 | 40.3                 | 15.0                         | 55.3                        | 582.1                     | 100,000                 | Vertical            |

According to FCC 47CFR15.35, the limit on the radio frequency emissions as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

### Remarks:

\*: Linear interpolations

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty = 30MHz to 300MHz ±3.7dB  
300MHz to 1GHz +3.0dB / -2.7dB

Date: 2001-10-26

## **TEST REPORT**

Page 11 of 20

No.: HM106103

**Results:**

| Field Strength of Fundamental Emissions |              |                      |                   |                   |                 |                     |
|-----------------------------------------|--------------|----------------------|-------------------|-------------------|-----------------|---------------------|
| Average Value *                         |              |                      |                   |                   |                 |                     |
| Frequency                               | Level<br>@3m | Correction<br>Factor | Field<br>Strength | Field<br>Strength | Limit **<br>@3m | Antenna<br>Polarity |
| MHz                                     | dB $\mu$ V   | dB/m                 | dB $\mu$ V/m      | $\mu$ V/m         | $\mu$ V/m       |                     |
| 49.86                                   | 40.1         | 15.0                 | 55.1              | 568.9             | 100,00          | Vertical            |

**Remarks:**

For effective averaging, the bandwidth of the video filter must be smaller than the resolution bandwidth. The higher the ratio of resolution bandwidth to video bandwidth, the greater the averaging will be recorded. Below setting for HP8572A EMI Receiver.

Resolution Bandwidth = 3MHz

Video Bandwidth = 1Hz

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty = 30MHz to 300MHz  $\pm 3.7$ dB  
300MHz to 1GHz  $+3.0$ dB /  $-2.7$ dB

Date: 2001-10-26

## **TEST REPORT**

Page 12 of 20

No.: HM106103

Limited for Radiated Emissions [FCC 47 CFR 15.209 Class B]:

| Frequency Range<br>[MHz] | Quasi-Peak Limits<br>[ $\mu\text{V/m}$ ] |
|--------------------------|------------------------------------------|
| 30-88                    | 100                                      |
| 88-216                   | 150                                      |
| 216-960                  | 200                                      |
| Above 960                | 500                                      |

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

### **Results:**

#### **Transmitter**

| Radiated Emissions<br>Quasi-Peak |                                  |                              |                                         |                                      |                                 |                     |
|----------------------------------|----------------------------------|------------------------------|-----------------------------------------|--------------------------------------|---------------------------------|---------------------|
| Frequency<br>MHz                 | Level<br>@3m<br>dB $\mu\text{V}$ | Correction<br>Factor<br>dB/m | Field<br>Strength<br>dB $\mu\text{V/m}$ | Field<br>Strength<br>$\mu\text{V/m}$ | Limit<br>@3m<br>$\mu\text{V/m}$ | Antenna<br>Polarity |
| 99.7                             | <1.0                             | 12.2                         | <13.2                                   | <4.6                                 | 150                             | Vertical            |
| 149.5                            | <1.0                             | 9.8                          | <10.8                                   | <3.5                                 | 150                             | Vertical            |
| 199.3                            | <1.0                             | 11.5                         | <12.5                                   | <4.2                                 | 150                             | Vertical            |
| 249.2                            | <1.0                             | 15.9                         | <16.9                                   | <7.0                                 | 200                             | Vertical            |
| 299.0                            | <1.0                             | 17.0                         | <18.0                                   | <7.9                                 | 200                             | Vertical            |
| 348.8                            | <1.0                             | 17.2                         | <18.2                                   | <8.1                                 | 200                             | Vertical            |
| 398.6                            | <1.0                             | 18.8                         | <19.8                                   | <9.8                                 | 200                             | Horizontal          |
| 448.5                            | <1.0                             | 19.7                         | <20.7                                   | <10.8                                | 200                             | Horizontal          |
| 498.6                            | <1.0                             | 20.6                         | <21.6                                   | <12.0                                | 200                             | Horizontal          |

Date: 2001-10-26

## TEST REPORT

Page 13 of 20

No.: HM106103

### Limits for Field Strength of Fundamental Emissions [FCC 47CFR 15.235]:

| Frequency Range of Fundamental<br>[MHz] | Field Strength of Fundamental Emission<br>[Peak]<br>[μV/m] | Field Strength of Fundamental Emission<br>[Average]<br>[μV/m] |
|-----------------------------------------|------------------------------------------------------------|---------------------------------------------------------------|
| 49.82-49.90                             | 100,000                                                    | 10,000                                                        |

### Results:

#### Receiver

| Field Strength of Radiated Emissions<br>Quasi-Peak Value |                      |                              |                             |                           |                         |                     |
|----------------------------------------------------------|----------------------|------------------------------|-----------------------------|---------------------------|-------------------------|---------------------|
| Frequency<br>MHz                                         | Level<br>@3m<br>dBμV | Correction<br>Factor<br>dB/m | Field<br>Strength<br>dBμV/m | Field<br>Strength<br>μV/m | Limit **<br>@3m<br>μV/m | Antenna<br>Polarity |
| 49.86                                                    | 20.1                 | 15.0                         | 35.1                        | 56.9                      | 100                     | Vertical            |
| 99.7                                                     | <1.0                 | 12.2                         | <13.2                       | <4.6                      | 150                     | Vertical            |
| 149.5                                                    | <1.0                 | 9.8                          | <10.8                       | <3.5                      | 150                     | Vertical            |
| 199.3                                                    | <1.0                 | 11.5                         | <12.5                       | <4.2                      | 150                     | Vertical            |
| 249.2                                                    | <1.0                 | 15.9                         | <16.9                       | <7.0                      | 200                     | Vertical            |
| 299.0                                                    | <1.0                 | 17.0                         | <18.0                       | <7.9                      | 200                     | Vertical            |
| 348.8                                                    | <1.0                 | 17.2                         | <18.2                       | <8.1                      | 200                     | Vertical            |
| 398.6                                                    | <1.0                 | 18.8                         | <19.8                       | <9.8                      | 200                     | Horizontal          |
| 448.5                                                    | <1.0                 | 19.7                         | <20.7                       | <10.8                     | 200                     | Horizontal          |
| 498.6                                                    | <1.0                 | 20.6                         | <21.6                       | <12.0                     | 200                     | Horizontal          |

#### Remarks:

For effective averaging, the bandwidth of the video filter must be smaller than the resolution bandwidth. The higher the ratio of resolution bandwidth to video bandwidth, the greater the averaging will be recorded. Below setting for HP8572A EMI Receiver.

Resolution Bandwidth = 3MHz  
Video Bandwidth = 1Hz

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty = 30MHz to 300MHz ±3.7dB  
300MHz to 1GHz +3.0dB / -2.7dB

Date: 2001-10-26

## **TEST REPORT**

Page 14 of 20

No.: HM106103


### **3.1.1 Conducted Emissions (0.45MHz to 30MHz)**

|                    |                  |
|--------------------|------------------|
| Test Requirement:  | FCC 47CFR 15.207 |
| Test Method:       | ANSI C63.4:2000  |
| Test Date:         | 2001-10-23       |
| Mode of Operation: | On mode          |

#### **Test Method:**

The test was performed in accordance with ANSI C63.4: 2000, with the following: an initial measurement was performed in peak and average detection mode on the live line. Any emissions recorded within 30dB of the relevant limit line were re-measured using quasi-peak and average detection on the live and neutral lines with the worst case recorded in the table of results.

#### **Test Setup:**



Date: 2001-10-26

## **TEST REPORT**

Page 15 of 20

No.: HM106103

**Limit for Conducted Emissions (FCC 47 CFR 15.207):**

| Frequency Range<br>[MHz] | Quasi-Peak Limits<br>[μV/m] |
|--------------------------|-----------------------------|
| 0.45-30                  | 250                         |

Limits for Conducted Emissions Test, please refer to limit lines (Quasi-Peak and Average) in the following diagram labelled as (QP and AV).

**Results: N/A**

**The EUT is operated by internal battery power only, therefore power line conducted emission was deemed unnecessary.**

Remarks:

Calculated measurement uncertainty =  $\pm 2.3\text{dB}$

### **3.2 26dB Bandwidth of Fundamental Emission**

|                    |                                   |
|--------------------|-----------------------------------|
| Test Requirement:  | FCC 47 CFR 15.235                 |
| Test Method:       | ANSI C63.4: 2000 (Section 13.1.7) |
| Test Date:         | 2001-10-23                        |
| Mode of Operation: | On mode                           |

#### **Test Method:**

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

A 1KHz tone and other audio signal were used with audio volume set to maximum for worst case.

#### **Test Setup:**

As Test Setup of clause 3.1.1 in this test report.

Date: 2001-10-26

## TEST REPORT


Page 17 of 20

No.: HM106103

Limits for 26 dB Bandwidth of Fundamental Emission:

| Frequency Range<br>[MHz] | 26dB Bandwidth<br>[KHz] | FCC Limits *<br>[KHz] |
|--------------------------|-------------------------|-----------------------|
| 49.86                    | 38.8                    | within 49.82-49.90    |

### 26dB Bandwidth of Fundamental Emission



Date: 2001-10-26

## TEST REPORT

Page 18 of 20

No.: HM106103

### Appendix A

#### Test Equipment Audit

##### Radiated Emission

| EQP NO. | DESCRIPTION                                                                  | MANUFACTURER                                          | MODEL NO.                      | SERIAL NO.                             | LAST CAL. |
|---------|------------------------------------------------------------------------------|-------------------------------------------------------|--------------------------------|----------------------------------------|-----------|
| EM007   | SPECTRUM ANALYZER                                                            | HEWLETT PACKARD                                       | HP85660B                       | 3144A21192                             | 07/09/01  |
| EM008   | SPECTRUM ANALYZER DISPLAY                                                    | HEWLETT PACKARD                                       | HP85662A                       | 3144A20514                             | 07/09/01  |
| EM009   | QUASI PEAK ADAPTOR                                                           | HEWLETT PACKARD                                       | HP85650A                       | 3303A01702                             | 07/09/01  |
| EM010   | RF PRESELECTOR                                                               | HEWLETT PACKARD                                       | HP85685A                       | 3221A01410                             | 07/09/01  |
| EM011   | ATTENUATOR/SWITCH                                                            | HEWLETT PACKARD                                       | HP11713A                       | 2508A10595                             | 07/09/01  |
| EM012   | PRE-AMPLIFIER                                                                | HEWLETT PACKARD                                       | HP8449B                        | 3008A00262                             | 07/09/01  |
| EM013   | CONTROLLER (COMPUTER),<br>COLOR MONITOR, KEYBOARD &<br>MOUSE<br>FLOPPY DRIVE | HEWLETT PACKARD<br>HEWLETT PACKARD<br>HEWLETT PACKARD | HP9000<br>HP A1097C<br>HP9133L | 6226A60314<br>3151J39517<br>2623A02468 | CM        |
| EM131   | PORTABLE SPECTRUM<br>ANALYSER                                                | HEWLETT PACKARD                                       | 8595EM                         | 3710A00155                             | 10/07/00  |
| EM017   | ANTENNA                                                                      | ARA INC.                                              | LPB-2513/A                     | 1069                                   | 17/02/00  |
| EM020   | HORN ANTENNA                                                                 | EMCO                                                  | 3115                           | 4032                                   | 09/08/00  |
| EM072   | SIGNAL GENERATOR                                                             | HEWLETT PACKARD                                       | 8640B                          | 1948A11892                             | 30/03/98  |
| EM083   | HKSTC OPEN AREA TEST SITE                                                    | HKSTC                                                 | N/A                            | N/A                                    | 15/02/01  |
| EM145   | EMI TEST RECEIVER                                                            | R & S                                                 | ESCS 30                        | 830245/021                             | 31/05/00  |

##### Conducted Emission

| EQP NO. | DESCRIPTION                         | MANUFACTURER     | MODEL NO.  | SERIAL NO.   | LAST CAL |
|---------|-------------------------------------|------------------|------------|--------------|----------|
| EM078   | VARIAC                              | SHANGHAI VOLTAGE | TDGC-3/0.5 | N/A          | CM       |
| EM081   | SMALL SCREENED ROOM                 | MIKO INST HK     | N/A        | N/A          | 10/09/00 |
| EM002   | LISN                                | EMCO             | 3825-2     | 9005-1657    | 22/08/01 |
| EM119   | LISN                                | R & S            | ESH3-Z5    | 0831.5518.52 | 31/08/00 |
| EM145   | EMI TEST RECEIVER                   | R & S            | ESCS 30    | 830245/021   | 31/05/00 |
| EM120   | EMI TEST RECEIVER                   | R&S              | ESHS10     | 1004.0401.10 | 04/09/00 |
| EM127   | ISOLATION TRANSFORMER 220<br>TO 300 | WING SUN         | N/A        | N/A          | N/A      |
| EM142   | PLUSE LIMITER                       | R & S            | ESH3Z2     | 357.8810.52  | TBD      |

Remarks:

CM      Corrective Maintenance  
N/A     Not Applicable or Not Available  
TBD    To Be Determined

Date: 2001-10-26

## **TEST REPORT**

Page 19 of 20

No.: HM106103

### **Appendix B**

#### **Photographs of EUT**

**Front View of the product**




**Rear View of the product**



**Inner Circuit Top View**



**Inner Circuit Bottom View**



Date: 2001-10-26

## **TEST REPORT**

Page 20 of 20

No.: HM106103

### Photographs of EUT

Measurement of Radiated Emission Test Set Up



End of Document