

THE OPERATION MANUAL FOR MODEL

TO OPERATE:

1. Switch the ON/OFF VOLUME control ON by pushing the dial down. To turn OFF, move the dial up until you hear it click.
2. To transit, press the PUSH TO TALK button and speak into the microphone. Speak in a normal voice.
3. To receive, release the PUSH TO TALK button, and listen to the sender's message.
4. Your voice will transmit up to 100 feet in areas with clear reception.
5. The walkie talkie can attach to your belt with the BELT CLIPS for ease and portability.

“THE FOLLOWING FACTORS CAN AFFECT THE PERFORMANCE AND OPERATING RANGE OF THE WALKIE TALKIE; COMPUTERS, ACTIVE ELECTRONIC EQUIPMENT, FLUORESCENT LIGHTS AND TALL BUILDINGS”

CAUTION

1. If your walkie talkie does not operate properly try a new set of batteries since your batteries may be defective or have low voltage even though they appear to be new.
2. After use always return the ON/OFF control to the off position.
3. Do not touch antenna with your fingers or hand. it will cause weak transmission.
4. Your walkie talkie set has been fully adjusted prior to shipment from the factory. Do not touch the internal parts other than replacing the battery.
5. Manufacturer recommends alkaline batteries for maximum performance.
6. To prevent damage, do not expose the set to rain or moisture
7. The user changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

To ensure proper function:

- Do not mix new & old batteries.
- Do not mix alkaline, standard or rechargeable batteries.
- Battery installation should be done by an adult.
- Non-rechargeable batteries are not to be recharged.
- Rechargeable batteries are to be removed from the toy before being charged (if removable).
- Only batteries of the same or equivalent type as recommended are to be used.
- Batteries are to be inserted with correct polarity.
- Exhausted batteries are to be removed from the toy.
- The supply terminals are not to be short circuited.

BATTERY INSTALLATION:

1. Slide the ON/OFF SWITCH to the OFF position.
2. To open the BATTERY COVER, slide the BATTERY COVER in downward notice to release the door.
3. To install 9 volt or “6LR61” battery observe the battery polarity by matching the map on connector with the proper snap terminals on the battery. Use care not to bend the connector terminals. Push the battery connector firmly on the battery. Reinstall the BATTERY COVER .

.