APPENDIX I RADIO FREQUENCY EXPOSURE

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

Date of Issue: March 30, 2011

EUT Specification

EUT	BT Stereo Headset
Frequency band (Operating)	 WLAN: 2.412GHz ~ 2.462GHz WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz WLAN: 5.745GHz ~ 5.825GHz ✓ Others: Bluetooth: 2.402GHz ~ 2.480GHz
Device category	Portable (<20cm separation) Mobile (>20cm separation) Others
Exposure classification	Occupational/Controlled exposure $(S = 5mW/cm^2)$ Seneral Population/Uncontrolled exposure $(S=1mW/cm^2)$
Antenna diversity	 Single antenna Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power	4.39 dBm (2.75 mW)
Antenna gain (Max)	-2.02 dBi (Numeric gain: 0.63)
Evaluation applied	
Remark: 1. The maximum output power is <u>4.39 dBm (2.75 mW) a</u> t <u>2441MHz</u> (with <u>0.63 numeric antenna gain</u> .)	

TEST RESULTS

No non-compliance noted.

(SAR evaluation is not required for the PORTABLE device while its maximum output power is lower than the general population low threshold: $60/f_{(GHz)}=60/2.441=24.58$ mW)

Page 64 Rev. 00