

**POWER DENSITY ESTIMATIONS BASED ON POWER OUTPUT, ANTENNA GAIN, AND
DISTANCE FROM ANTENNA**

$$(P G) / (4 R^2 \pi) = S$$

where: $S =$ maximum power density (mW/cm ²)		transmitter operating variables:		must be blank if dB values are entered	
$P =$	power input to the antenna ----->>	=	27.37	(dBm) - or -	(mW)
$G =$	gain of the antenna - worst case ----->>	=	2.5	(dBi) - or -	(numeric gain)
$R =$	distance to the center of the radiation of the antenna -->>	=	20		(cm)

$(P \quad G)$	$/$	$(4 * R^2 * \pi)$	$=$	S	(mW/cm^2)
---------------	-----	-------------------	-----	-----	-------------

$(\begin{matrix} 545.7578611 \\ (mw) \end{matrix} \quad \begin{matrix} 1.77828 \\ (gain) \end{matrix})$	$/$	$(4 * \begin{matrix} 20 \\ (cm) \end{matrix}^2 * \pi)$	$=$	S	(mW/cm^2)
---	-----	--	-----	-----	-------------

(970.5099672)	$/$	$(4 * 400 * \pi)$	$=$	S	(mW/cm^2)
-----------------	-----	-------------------	-----	-----	-------------

(970.5099672)	$/$	(5026.548246)	$=$	0.193077	(mW/cm^2)
-----------------	-----	-----------------	-----	----------	-------------