

FCC Co-Location Test Report

FCC ID :	I8811ACAP22
Equipment :	802.11ac Wave 2 Dual-Radio Ceiling Mount PoE Access Point (Refer to item 1.1.1 for more details)
Model No. :	NWA1123ACv3 (Refer to item 1.1.1 for more details)
Brand Name :	ZYXEL
Applicant :	Zyxel Communications Corporation
Address :	No.2 Industry East RD. IX, Hsinchu Science Park, Hsinchu 30075, Taiwan, R.O.C
Standard :	47 CFR FCC Part 15.247 47 CFR FCC Part 15.407
Received Date :	Jul. 07, 2020
Tested Date :	Jul. 10 ~ Jul. 17, 2020

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:

Approved by:



Along Chem

Along Chen/ Assistant Manager

Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information	
1.2	The Equipment List	6
1.3	Test Standards	7
1.4	Reference Guidance	
1.5	Deviation from Test Standard and Measurement Procedure	7
1.6	Measurement Uncertainty	7
2	TEST CONFIGURATION	8
2.1	Testing Facility	8
2.2	The Worst Test Modes and Channel Details	8
3	TRANSMITTER TEST RESULTS	9
3.1	Unwanted Emissions into Restricted Frequency Bands	9
4	TEST LABORATORY INFORMATION	18



Release Record

Report No.	Version	Description	Issued Date
FR070801CO	Rev. 01	Initial issue	Sep. 24, 2020



Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.247(d)			
15.407(b)		[dBuV/m at 3m]: 41.64MHz 36.59(Margin -3.41dB) - PK	Pass
15.209			

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1 General Description

1.1 Information

1.1.1 Product Details

The following models are provided to this EUT.

Brand Name	Model Name	Product Name	Description		
ZYXEL	NWA1123ACv3	802.11ac Wave 2 Dual-Radio Ceiling Mount PoE Access Point	Software difference		
ZYXEL	WAC500	802.11ac Wave 2 Dual-Radio Unified Access Point	Software difference		
+ The above models, model NWA1123ACv3 was selected as a representative one for the final test and only its data was recorded in this report.					

1.1.2 Specification of the Equipment under Test (EUT)

Operating Frequency	802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n/ac: 5180 MHz ~ 5240 MHz, 5745 ~ 5825 MHz
Modulation Type	802.11b: DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n/ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)

1.1.3 Antenna Details

Ant. No.	Brand	Model	Туре	Connector	Operating Frequency (MHz) / G (dBi)		1Hz) / Gain
NO.						5150~5250	5725~5850
1	ARISTOTLE	RFA-25-G528	PIFA	N/A	0	0	0
2	ARISTOTLE	RFA-25-G526	PIFA	N/A	0	0	0

1.1.4 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	12Vdc from adapter 30~57Vdc from PoE
-------------------	---

Note: The PoE power supply is not bundled in market.

1.1.5 Accessories

	Accessories			
No.	Equipment	Description		
1		Brand: DEE VAN ENTERPRISE CO. LTD. Model: DSA-12PFU-12 FCA 120100 I/P: 100-240Vac, 50/60Hz, 0.5A O/P: 12Vdc, 1.0A, 12W Power Line: 1.5m non-shielded without core		



1.2 The Equipment List

Test Item	Radiated Emission					
Test Site	966 chamber 3 / (03CH03-WS)					
Tested Date	Jul. 10 ~ Jul. 17, 2020					
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until	
Spectrum Analyzer	R&S	FSV40	101499	Jan. 09, 2020	Jan. 08, 2021	
Receiver	R&S	ESR3	101657	Feb. 14, 2020	Feb. 13, 2021	
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-685	Apr. 29, 2020	Apr. 28, 2021	
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1206	Dec. 27, 2019	Dec. 26, 2020	
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 15, 2019	Nov. 14, 2020	
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 13, 2019	Nov. 12, 2020	
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 07, 2019	Oct. 06, 2020	
Preamplifier	EMC	EMC02325	980187	Aug. 14, 2019	Aug. 13, 2020	
Preamplifier	Agilent	83017A	MY39501309	Sep. 24, 2019	Sep. 23, 2020	
Preamplifier	EMC	EMC184045B	980192	Aug. 01, 2019	Jul. 31, 2020	
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22620/ 4	Sep. 27, 2019	Sep. 26, 2020	
RF cable-8M	EMC	EMC104-SM-SM-80 00	181107	Sep. 27, 2019	Sep. 26, 2020	
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22624/4	Sep. 27, 2019	Sep. 26, 2020	
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800 -001	Sep. 27, 2019	Sep. 26, 2020	
LF cable-3M	EMC	EMC8D-NM-NM-300 0	131103	Sep. 27, 2019	Sep. 26, 2020	
LF cable-13M	EMC	EMC8D-NM-NM-130 00	131104	Sep. 27, 2019	Sep. 26, 2020	
Measurement Software	AUDIX	e3	6.120210g	NA	NA	
Note: Calibration Inter	val of instruments liste	d above is one year.				

Test Item	RF Conducted	RF Conducted				
Test Site	(TH01-WS)					
Tested Date	Jul. 10 ~ Jul. 17, 2020	Jul. 10 ~ Jul. 17, 2020				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until	
Spectrum Analyzer	R&S	FSV40	101063	Apr. 30, 2020	Apr. 29, 2021	
Power Meter	Anritsu	ML2495A	1241002	Oct. 23, 2019	Oct. 22, 2020	
Power Sensor	Anritsu	MA2411B	1207366	Oct. 23, 2019	Oct. 22, 2020	
DC POWER SOURCE	GW INSTEK	GPC-6030D	GES855395	Oct. 29, 2019	Oct. 28, 2020	
AC POWER SOURCE	APC	AFC-500W	F312060012	Dec. 02, 2019	Dec. 01, 2020	
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA	
Note: Calibration Interval of instruments listed above is one year.						



1.3 Test Standards

47 CFR FCC Part 15.247 47 CFR FCC Part 15.407 ANSI C63.10-2013 FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01

1.4 Reference Guidance

FCC KDB 558074 D01 15.247 Meas Guidance v05r02 FCC KDB 662911 D01 Multiple Transmitter Output v02r01 FCC KDB 412172 D01 Determining ERP and EIRP v01r01

1.5 Deviation from Test Standard and Measurement Procedure

None

1.6 Measurement Uncertainty

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).

Measurement Uncertainty				
Parameters	Uncertainty			
Radiated emission ≤ 1GHz	±3.96 dB			
Radiated emission > 1GHz	±4.51 dB			



2 Test Configuration

2.1 Testing Facility

Test Laboratory	International Certification Corp.
Test Site	TH01-WS
Address of Test Site	No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.
Test Site	03CH03-WS
Address of Test Site	No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.
► ECC Designation No.	TW/0000

FCC Designation No.: TW0009

➢ FCC site registration No.: 207696

- ➢ ISED#: 10807A
- ➤ CAB identifier: TW2732

2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Configuration			
Radiated Emissions ≤1GHz		1, 2			
Radiated Emissions >1GHz	2.4G 11g CH6 + 5G 11A CH40	1			
Conducted Emissions		1			
NOTE: 1. The selected channel is the maximum power channel of Wi-Fi mode. 2. The EUT had been tested by following test configurations.					
1) Configuration 1: Adapter mode					
2) Configuration 2: PoE mode					



3 Transmitter Test Results

3.1 Unwanted Emissions into Restricted Frequency Bands

3.1.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit					
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)		
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300		
0.490~1.705	24000/F(kHz)	33.8 - 23	30		
1.705~30.0	30	29	30		
30~88	100	40	3		
88~216	150	43.5	3		
216~960	200	46	3		
Above 960	500	54	3		

Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit **Note 2**:

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.1.2 Test Procedures


- Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m.
- Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- 3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:

- 1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
- 2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
- 3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.




3.1.3 Test Setup






Adapter mode


3.1.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)












3.1.5 Transmitter Radiated Unwanted Emissions (Above 1GHz)









PoE mode

3.1.6 Transmitter Radiated Unwanted Emissions (Below 1GHz)












3.1.7 Conducted Emissions (30MHz~40GHz)









4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <u>http://www.icertifi.com.tw</u>.

Linkou Tel: 886-2-2601-1640 No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan, R.O.C. Kwei Shan Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C. Kwei Shan Site II Tel: 886-3-271-8640 No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C..

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666 Fax: 886-3-318-0155 Email: ICC_Service@icertifi.com.tw

—END—