

# **FCC RF Exposure Report**

FCC ID : 18811AXAP22

Equipment : 802.11ax (WiFi 6) Dual-Radio Unified Access Point

Model No. : WAX510D, NWA110AX

Multiple Listing : Refer to item 1.1.1 for more details.

Brand Name : ZYXEL

**Applicant**: Zyxel Communications Corporation

Address : No.2 Industry East RD. IX, Hsinchu Science Park,

Hsinchu 30075, Taiwan, R.O.C

Standard : 47 CFR FCC Part 2.1091

Received Date : Dec. 18, 2019

Tested Date : Dec. 23, 2019 ~ Jan. 14, 2020

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by: Approved by:

Along Chen // Assistant Manager Gary Chang / Manag

ager Testing Laboratory

Report No.: FA9D0202 Page: 1 of 8

Report Version: Rev. 02



## **Table of Contents**

1	GENERAL DESCRIPTION	4
1.1	Information	
2	MPE EVALUATION OF MOBILE DEVICES	5
2.1	LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE	5
2.2	MPE EVALUATION FORMULA	5
2.3	DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE	5
2.4	MEASUREMENT UNCERTAINTY	5
2.5	MPE EVALUATION RESULTS	6
2.6	MPE EVALUATION OF SIMULTANEOUS TRANSMISSION	7
3	TEST I ABORATORY INFORMATION	۶



## **Release Record**

Report No.	Version	Description	Issued Date
FA9D0202	Rev. 01	Initial issue	Jan. 21, 2020
FA9D0202	Rev. 02	<ol> <li>Adding B2 &amp; B3 information.</li> <li>Revising the FCC ID</li> </ol>	Apr. 23, 2020

Report No.: FA9D0202 Page: 3 of 8

Report Version: Rev. 02



## 1 General Description

## 1.1 Information

#### 1.1.1 Product Details

The following models are provided to this EUT.

WAX510D  802.11ax (WiFi 6) Dual-Radio Unified Access Point  Difference between two r software.	n
	o models is
NWA110AX 802.11ax (WiFi 6) Dual-Radio NWA110AX (FAT/Cloud A	

The above models, model **WAX510D** was selected as a representative one for the final test and only its data was recorded in this report.



### 2 MPE EVALUATION OF MOBILE DEVICES

#### 2.1 LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

Frequency Range (MHz)	Power Density (mW /cm²)	Averaging Time (minutes)
300~1500	F/1500	30
1500~100000	1.0	30

#### 2.2 MPE EVALUATION FORMULA

$$Pd = \frac{Pt}{4 * Pi * R^2}$$

Where

Pd= Power density in mW/cm<sup>2</sup>

Pt= EIRP in mW

Pi= 3.1416

R= Measurement distance

#### 2.3 DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE

None

#### 2.4 MEASUREMENT UNCERTAINTY

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Parameters	Uncertainty
Conducted power	±0.808 dB

#### **Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

#### **Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Report No.: FA9D0202 Page: 5 of 8

Report Version: Rev. 02

The previous version of the test report has been cancelled and replaced by new version.



#### 2.5 MPE EVALUATION RESULTS

### Non-beamforming mode

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Rated Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)	Ratio*	Pass / Fail
2412 ~ 2462 (Wi-Fi)	23.62	24	0	20	0.050	1	0.050	Pass
5180 ~ 5240 (Wi-Fi)	25.67	26	4.5	20	0.223	1	0.223	Pass
5260 ~ 5320 (Wi-Fi)	23.79	24	4.5	20	0.141	1	0.141	Pass
5500~5700 (Wi-Fi)	23.77	24	5.2	20	0.165	1	0.165	Pass
5745 ~ 5825 (Wi-Fi)	26.02	26.5	5.5	20	0.315	1	0.315	Pass

Note: \*Ratio = Power density / Limit.

### Beamforming mode

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Rated Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)	Ratio*	Pass / Fail
2412 ~ 2462 (Wi-Fi)	20.38	20.5	3.01	20	0.045	1	0.045	Pass
5180 ~ 5240 (Wi-Fi)	21.28	21.5	7.51	20	0.158	1	0.158	Pass
5260 ~ 5320 (Wi-Fi)	20.78	21	7.51	20	0.141	1	0.141	Pass
5500~5700 (Wi-Fi)	20.76	21	8.21	20	0.166	1	0.166	Pass
5745 ~ 5825 (Wi-Fi)	23.01	23.5	8.51	20	0.316	1	0.316	Pass

Note 1: \*Ratio = Power density / Limit.

2412 ~ 2462 MHz: Directional gain = 0 + 10 \* log(2/1) =3.01 dBi

5150 ~ 5250 MHz, Directional gain = 4.5 + 10 \* log(2/1) =7.51 dBi

5250 ~ 5350 MHz, Directional gain = 4.5 + 10 \* log(2/1) = 7.51 dBi 5470 ~ 5725Hz, Directional gain = 5.2 + 10 \* log(2/1) = 8.21 dBi

5745~ 5850 MHz, Directional gain = 5.5 + 10 \* log(2/1) =8.51dBi

Report No.: FA9D0202 Page: 6 of 8

Report Version: Rev. 02

The previous version of the test report has been cancelled and replaced by new version.



## 2.6 MPE EVALUATION OF SIMULTANEOUS TRANSMISSION.

M. I.	Max Ratio of Each Mode					
Mode	Non-beamforming mode	Beamforming mode				
WLAN 2.4GHz	0.050	0.045				
WLAN 5GHz	0.315	0.316				
Sum	0.365	0.361				
Limit	1	1				
Pass / Fail	Pass	Pass				

Report No.: FA9D0202 Page: 7 of 8



## 3 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <a href="http://www.icertifi.com.tw">http://www.icertifi.com.tw</a>.

#### Linkou

Tel: 886-2-2601-1640 No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan, R.O.C.

#### Kwei Shan

Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

#### Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C..

Page: 8 of 8

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC\_Service@icertifi.com.tw

==END==

Report No.: FA9D0202

Report Version: Rev. 02