




Modulation	be EHT20	Test Freq. (MHz)	5700
Polarization	Vertical		

Test By : Sean Yu Temperature(°C): 25 Humidity(%): 61




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1 *	5700.00	102.76			101.86	0.90	Average	219	272
2 *	5700.00	117.08			116.18	0.90	Peak	219	272
3	5725.00	68.02	68.20	-0.18	67.07	0.95	Peak	219	288
4	11400.00	42.36	54.00	-11.64	34.30	8.06	Average	100	39
5	11400.00	55.21	74.00	-18.79	47.15	8.06	Peak	100	39
6	17100.00	57.34	68.20	-10.86	51.57	5.77	Peak	100	24

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: "*" is Peak / Average value of fundamental frequency



Modulation	be EHT20	Test Freq. (MHz)	5720
Polarization	Horizontal		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5460.00	42.71	54.00	-11.29	42.21	0.50	Average	100	265
2	5460.00	56.63	74.00	-17.37	56.13	0.50	Peak	100	265
3	5470.00	56.75	68.20	-11.45	56.23	0.52	Peak	100	265
4 *	5720.00	101.68			100.74	0.94	Average	100	265
5 *	5720.00	115.52			114.58	0.94	Peak	100	265
6	5850.00	57.96	68.20	-10.24	56.88	1.08	Peak	100	265
7	11440.00	41.63	54.00	-12.37	33.49	8.14	Average	100	35
8	11440.00	54.65	74.00	-19.35	46.51	8.14	Peak	100	35
9	17160.00	56.28	68.20	-11.92	50.82	5.46	Peak	100	21

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: "*" is Peak / Average value of fundamental frequency



Modulation	be EHT20	Test Freq. (MHz)	5720
Polarization	Vertical		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5460.00	42.83	54.00	-11.17	42.33	0.50	Average	223	258
2	5460.00	56.66	74.00	-17.34	56.16	0.50	Peak	223	258
3	5470.00	56.86	68.20	-11.34	56.34	0.52	Peak	223	258
4 *	5720.00	106.61			105.67	0.94	Average	223	258
5 *	5720.00	120.48			119.54	0.94	Peak	223	258
6	5850.00	58.03	68.20	-10.17	56.95	1.08	Peak	223	258
7	11440.00	41.64	54.00	-12.36	33.50	8.14	Average	100	28
8	11440.00	54.69	74.00	-19.31	46.55	8.14	Peak	100	28
9	17160.00	56.15	68.20	-12.05	50.69	5.46	Peak	100	39

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: "*" is Peak / Average value of fundamental frequency



Modulation	be EHT20	Test Freq. (MHz)	5745
Polarization	Horizontal		

Test By : Sean Yu Temperature(°C): 25 Humidity(%): 63



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5585.00	59.76	68.20	-8.44	59.23	0.53	Peak	100	261
2	5650.00	59.01	68.20	-9.19	58.35	0.66	Peak	100	261
3	5700.00	68.29	105.20	-36.91	67.39	0.90	Peak	100	261
4	5720.00	85.24	110.80	-25.56	84.30	0.94	Peak	100	261
5	5725.00	92.01	122.20	-30.19	91.06	0.95	Peak	100	261
6	* 5745.00	105.57			104.57	1.00	Average	100	261
7	* 5745.00	119.91			118.91	1.00	Peak	100	261
8	5925.00	59.36	68.20	-8.84	57.92	1.44	Peak	100	261
9	11490.00	44.78	54.00	-9.22	36.39	8.39	Average	100	115
10	11490.00	57.21	74.00	-16.79	48.82	8.39	Peak	100	115
11	17235.00	59.16	68.20	-9.04	53.72	5.44	Peak	100	251
12	22980.00	48.65	54.00	-5.35	41.79	6.86	Average	124	77
13	22980.00	63.24	74.00	-10.76	56.38	6.86	Peak	124	77

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: "*" is Peak / Average value of fundamental frequency



Modulation	be EHT20	Test Freq. (MHz)	5745
Polarization	Vertical		

Test By : Sean Yu Temperature(°C): 25 Humidity(%): 63



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5585.00	60.89	68.20	-7.31	60.36	0.53	Peak	216	258
2	5650.00	61.48	68.20	-6.72	60.82	0.66	Peak	216	258
3	5700.00	71.89	105.20	-33.31	70.99	0.90	Peak	216	258
4	5720.00	89.77	110.80	-21.03	88.83	0.94	Peak	216	258
5	5725.00	97.84	122.20	-24.36	96.89	0.95	Peak	216	258
6 *	5745.00	111.78			110.78	1.00	Average	216	258
7 *	5745.00	124.92			123.92	1.00	Peak	216	258
8	5925.00	60.01	68.20	-8.19	58.57	1.44	Peak	216	258
9	11490.00	43.15	54.00	-10.85	34.76	8.39	Average	100	262
10	11490.00	56.18	74.00	-17.82	47.79	8.39	Peak	100	262
11	17235.00	58.72	68.20	-9.48	53.28	5.44	Peak	100	116
12	22980.00	44.21	54.00	-9.79	37.35	6.86	Average	276	135
13	22980.00	58.15	74.00	-15.85	51.29	6.86	Peak	276	135

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: "*" is Peak / Average value of fundamental frequency



Modulation	be EHT20	Test Freq. (MHz)	5785
Polarization	Horizontal		

Test By : Sean Yu Temperature(°C): 25 Humidity(%): 63



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5625.00	59.76	68.20	-8.44	59.16	0.60	Peak	100	260
2	5650.00	59.07	68.20	-9.13	58.41	0.66	Peak	100	260
3 *	5785.00	105.74			104.70	1.04	Average	100	260
4 *	5785.00	119.71			118.67	1.04	Peak	100	260
5	5925.00	59.24	68.20	-8.96	57.80	1.44	Peak	100	260
6	11570.00	44.42	54.00	-9.58	36.09	8.33	Average	100	27
7	11570.00	56.51	74.00	-17.49	48.18	8.33	Peak	100	27
8	17355.00	57.38	68.20	-10.82	51.54	5.84	Peak	100	118
9	23140.00	64.11	68.20	-4.09	57.02	7.09	Peak	132	91

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: "*" is Peak / Average value of fundamental frequency



Modulation	be EHT20	Test Freq. (MHz)	5785
Polarization	Vertical		

Test By : Sean Yu Temperature(°C): 25 Humidity(%): 63



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5625.00	61.21	68.20	-6.99	60.61	0.60	Peak	221	279
2	5650.00	60.55	68.20	-7.65	59.89	0.66	Peak	221	257
3 *	5785.00	111.21			110.17	1.04	Average	221	257
4 *	5785.00	125.48			124.44	1.04	Peak	221	257
5	5925.00	59.79	68.20	-8.41	58.35	1.44	Peak	221	257
6	11570.00	44.01	54.00	-9.99	35.68	8.33	Average	100	97
7	11570.00	56.08	74.00	-17.92	47.75	8.33	Peak	100	97
8	17355.00	57.66	68.20	-10.54	51.82	5.84	Peak	100	206
9	23140.00	59.45	68.20	-8.75	52.36	7.09	Peak	266	125

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: "*" is Peak / Average value of fundamental frequency



Modulation	be EHT20	Test Freq. (MHz)	5825
Polarization	Horizontal		

Test By : Sean Yu Temperature(°C): 25 Humidity(%): 63



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5650.00	58.40	68.20	-9.80	57.74	0.66	Peak	100	259
2	5665.00	61.31	79.33	-18.02	60.58	0.73	Peak	100	259
3 *	5825.00	105.40			104.34	1.06	Average	100	259
4 *	5825.00	119.84			118.78	1.06	Peak	100	259
5	5850.00	91.26	122.20	-30.94	90.18	1.08	Peak	100	259
6	5855.00	76.83	110.80	-33.97	75.71	1.12	Peak	100	259
7	5875.00	61.48	105.20	-43.72	60.23	1.25	Peak	100	259
8	5925.00	59.57	68.20	-8.63	58.13	1.44	Peak	100	259
9	11650.00	44.95	54.00	-9.05	37.03	7.92	Average	100	109
10	11650.00	57.28	74.00	-16.72	49.36	7.92	Peak	100	109
11	17475.00	59.28	68.20	-8.92	52.96	6.32	Peak	100	251
12	23300.00	60.22	68.20	-7.98	53.05	7.17	Peak	126	81

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: "*" is Peak / Average value of fundamental frequency



Modulation	be EHT20	Test Freq. (MHz)	5825
Polarization	Vertical		

Test By : Sean Yu Temperature(°C): 25 Humidity(%): 63



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5650.00	59.56	68.20	-8.64	58.90	0.66	Peak	210	260
2	5665.00	62.98	79.33	-16.35	62.25	0.73	Peak	210	260
3 *	5825.00	111.50			110.44	1.06	Average	210	260
4 *	5825.00	125.62			124.56	1.06	Peak	210	260
5	5850.00	90.87	122.20	-31.33	89.79	1.08	Peak	210	260
6	5855.00	84.57	110.80	-26.23	83.45	1.12	Peak	210	260
7	5875.00	62.91	105.20	-42.29	61.66	1.25	Peak	210	260
8	5925.00	59.22	68.20	-8.98	57.78	1.44	Peak	210	260
9	11650.00	43.12	54.00	-10.88	35.20	7.92	Average	100	256
10	11650.00	55.98	74.00	-18.02	48.06	7.92	Peak	100	256
11	17475.00	58.86	68.20	-9.34	52.54	6.32	Peak	100	124
12	23300.00	56.52	68.20	-11.68	49.35	7.17	Peak	271	135

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


Note 3: "*" is Peak / Average value of fundamental frequency



Unwanted Emissions (Above 1GHz) for be EHT40

Modulation	be EHT40	Test Freq. (MHz)	5190
Polarization	Horizontal		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5150.00	52.34	54.00	-1.66	51.69	0.65	Average	130	109
2	5150.00	70.54	74.00	-3.46	69.89	0.65	Peak	130	109
3 *	5190.00	98.36			97.79	0.57	Average	130	109
4 *	5190.00	111.33			110.76	0.57	Peak	130	109
5	10380.00	54.77	68.20	-13.43	46.47	8.30	Peak	100	29
6	15570.00	40.81	54.00	-13.19	36.01	4.80	Average	100	16
7	15570.00	54.74	74.00	-19.26	49.94	4.80	Peak	100	16

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3:"*" is Peak / Average value of fundamental frequency



Modulation	be EHT40	Test Freq. (MHz)	5190
Polarization	Vertical		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61




	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5150.00	53.58	54.00	-0.42	52.93	0.65	Average	216	236
2	5150.00	67.44	74.00	-6.56	66.79	0.65	Peak	216	236
3 *	5190.00	101.80			101.23	0.57	Average	216	236
4 *	5190.00	114.99			114.42	0.57	Peak	216	236
5	10380.00	54.32	68.20	-13.88	46.02	8.30	Peak	100	41
6	15570.00	41.03	54.00	-12.97	36.23	4.80	Average	100	26
7	15570.00	55.25	74.00	-18.75	50.45	4.80	Peak	100	26

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).
 Note 3:"*" is Peak / Average value of fundamental frequency



Modulation	be EHT40	Test Freq. (MHz)	5230
Polarization	Horizontal		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5150.00	50.28	54.00	-3.72	49.63	0.65	Average	132	111
2	5150.00	67.29	74.00	-6.71	66.64	0.65	Peak	132	111
3 *	5230.00	100.52			100.13	0.39	Average	132	111
4 *	5230.00	114.39			114.00	0.39	Peak	132	111
5	5350.00	45.69	54.00	-8.31	45.55	0.14	Average	132	111
6	5350.00	60.82	74.00	-13.18	60.68	0.14	Peak	132	111
7	10460.00	54.89	68.20	-13.31	46.35	8.54	Peak	100	31
8	15690.00	41.15	54.00	-12.85	36.29	4.86	Average	100	14
9	15690.00	55.02	74.00	-18.98	50.16	4.86	Peak	100	14

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3:"*" is Peak / Average value of fundamental frequency



Modulation	be EHT40	Test Freq. (MHz)	5230
Polarization	Vertical		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5150.00	53.57	54.00	-0.43	52.92	0.65	Average	198	238
2	5150.00	71.06	74.00	-2.94	70.41	0.65	Peak	198	238
3 *	5230.00	104.53			104.14	0.39	Average	198	238
4 *	5230.00	118.14			117.75	0.39	Peak	198	238
5	5350.00	46.03	54.00	-7.97	45.89	0.14	Average	198	238
6	5350.00	63.49	74.00	-10.51	63.35	0.14	Peak	198	238
7	10460.00	54.87	68.20	-13.33	46.33	8.54	Peak	100	25
8	15690.00	41.02	54.00	-12.98	36.16	4.86	Average	100	28
9	15690.00	55.05	74.00	-18.95	50.19	4.86	Peak	100	28

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: "*" is Peak / Average value of fundamental frequency



Modulation	be EHT40	Test Freq. (MHz)	5270
Polarization	Horizontal		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5150.00	43.12	54.00	-10.88	42.47	0.65	Average	132	112
2	5150.00	56.75	74.00	-17.25	56.10	0.65	Peak	132	112
3 *	5270.00	96.68			96.42	0.26	Average	132	112
4 *	5270.00	110.15			109.89	0.26	Peak	132	112
5	5350.00	44.29	54.00	-9.71	44.15	0.14	Average	132	112
6	5350.00	59.81	74.00	-14.19	59.67	0.14	Peak	132	112
7	10540.00	54.43	68.20	-13.77	46.14	8.29	Peak	100	48
8	15810.00	40.85	54.00	-13.15	36.28	4.57	Average	100	29
9	15810.00	54.66	74.00	-19.34	50.09	4.57	Peak	100	29

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: "*" is Peak / Average value of fundamental frequency



Modulation	be EHT40	Test Freq. (MHz)	5270
Polarization	Vertical		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5150.00	44.07	54.00	-9.93	43.42	0.65	Average	272	245
2	5150.00	57.27	74.00	-16.73	56.62	0.65	Peak	272	245
3 *	5270.00	101.12			100.86	0.26	Average	272	245
4 *	5270.00	115.11			114.85	0.26	Peak	272	245
5	5350.00	46.92	54.00	-7.08	46.78	0.14	Average	272	245
6	5350.00	60.91	74.00	-13.09	60.77	0.14	Peak	272	245
7	10540.00	54.44	68.20	-13.76	46.15	8.29	Peak	100	51
8	15810.00	40.78	54.00	-13.22	36.21	4.57	Average	100	29
9	15810.00	54.53	74.00	-19.47	49.96	4.57	Peak	100	29

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: "*" is Peak / Average value of fundamental frequency



Modulation	be EHT40	Test Freq. (MHz)	5310
Polarization	Horizontal		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61




	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		cm	deg
1 *	5310.00	97.81			97.61	0.20	Average	129	104
2 *	5310.00	111.41			111.21	0.20	Peak	129	104
3	5350.00	47.05	54.00	-6.95	46.91	0.14	Average	129	104
4	5350.00	60.56	74.00	-13.44	60.42	0.14	Peak	129	104
5	10620.00	41.84	54.00	-12.16	33.47	8.37	Average	100	15
6	10620.00	54.88	74.00	-19.12	46.51	8.37	Peak	100	15
7	15930.00	42.16	54.00	-11.84	37.51	4.65	Average	100	42
8	15930.00	55.05	74.00	-18.95	50.40	4.65	Peak	100	42

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3:"*" is Peak / Average value of fundamental frequency



Modulation	be EHT40	Test Freq. (MHz)	5310
Polarization	Vertical		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61




	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		cm	deg
1 *	5310.00	101.64			101.44	0.20	Average	297	240
2 *	5310.00	116.08			115.88	0.20	Peak	297	240
3	5350.00	52.90	54.00	-1.10	52.76	0.14	Average	297	240
4	5350.00	66.65	74.00	-7.35	66.51	0.14	Peak	297	240
5	10620.00	41.44	54.00	-12.56	33.07	8.37	Average	100	22
6	10620.00	54.36	74.00	-19.64	45.99	8.37	Peak	100	22
7	15930.00	42.24	54.00	-11.76	37.59	4.65	Average	100	18
8	15930.00	55.13	74.00	-18.87	50.48	4.65	Peak	100	18

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3:"*" is Peak / Average value of fundamental frequency



Modulation	be EHT40	Test Freq. (MHz)	5510
Polarization	Horizontal		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5460.00	46.47	54.00	-7.53	45.97	0.50	Average	142	115
2	5460.00	60.34	74.00	-13.66	59.84	0.50	Peak	142	115
3	5470.00	63.80	68.20	-4.40	63.28	0.52	Peak	142	115
4 *	5510.00	98.43			97.86	0.57	Average	142	115
5 *	5510.00	112.50			111.93	0.57	Peak	142	115
6	11020.00	42.44	54.00	-11.56	33.87	8.57	Average	100	28
7	11020.00	54.21	74.00	-19.79	45.64	8.57	Peak	100	28
8	16530.00	56.78	68.20	-11.42	50.74	6.04	Peak	100	15

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3:"*" is Peak / Average value of fundamental frequency



Modulation	be EHT40	Test Freq. (MHz)	5510
Polarization	Vertical		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5460.00	50.08	54.00	-3.92	49.58	0.50	Average	256	258
2	5460.00	63.96	74.00	-10.04	63.46	0.50	Peak	256	258
3	5470.00	67.91	68.20	-0.29	67.39	0.52	Peak	256	258
4 *	5510.00	101.65			101.08	0.57	Average	256	258
5 *	5510.00	115.98			115.41	0.57	Peak	256	258
6	11020.00	42.43	54.00	-11.57	33.86	8.57	Average	100	22
7	11020.00	54.15	74.00	-19.85	45.58	8.57	Peak	100	22
8	16530.00	56.81	68.20	-11.39	50.77	6.04	Peak	100	36

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3:"*" is Peak / Average value of fundamental frequency



Modulation	be EHT40	Test Freq. (MHz)	5590
Polarization	Horizontal		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5460.00	43.72	54.00	-10.28	43.22	0.50	Average	141	112
2	5460.00	57.95	74.00	-16.05	57.45	0.50	Peak	141	112
3	5470.00	58.41	68.20	-9.79	57.89	0.52	Peak	141	112
4 *	5590.00	97.94			97.41	0.53	Average	141	112
5 *	5590.00	111.58			111.05	0.53	Peak	141	112
6	5725.00	59.24	68.20	-8.96	58.29	0.95	Peak	141	112
7	11180.00	43.29	54.00	-10.71	35.07	8.22	Average	100	55
8	11180.00	55.38	74.00	-18.62	47.16	8.22	Peak	100	55
9	16770.00	56.95	68.20	-11.25	50.60	6.35	Peak	100	27

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3:"*" is Peak / Average value of fundamental frequency



Modulation	be EHT40	Test Freq. (MHz)	5590
Polarization	Vertical		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5460.00	43.83	54.00	-10.17	43.33	0.50	Average	248	259
2	5460.00	57.99	74.00	-16.01	57.49	0.50	Peak	248	259
3	5470.00	58.52	68.20	-9.68	58.00	0.52	Peak	248	259
4 *	5590.00	101.50			100.97	0.53	Average	248	259
5 *	5590.00	115.96			115.43	0.53	Peak	248	259
6	5725.00	59.41	68.20	-8.79	58.46	0.95	Peak	248	259
7	11180.00	42.81	54.00	-11.19	34.59	8.22	Average	100	29
8	11180.00	55.15	74.00	-18.85	46.93	8.22	Peak	100	29
9	16770.00	56.62	68.20	-11.58	50.27	6.35	Peak	100	33

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3:"*" is Peak / Average value of fundamental frequency



Modulation	be EHT40	Test Freq. (MHz)	5670
Polarization	Horizontal		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61




	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		cm	deg
1 *	5670.00	97.41			96.65	0.76	Average	139	116
2 *	5670.00	111.21			110.45	0.76	Peak	139	116
3	5725.00	62.68	68.20	-5.52	61.73	0.95	Peak	139	116
4	11340.00	42.25	54.00	-11.75	34.11	8.14	Average	100	52
5	11340.00	55.14	74.00	-18.86	47.00	8.14	Peak	100	52
6	17010.00	57.53	68.20	-10.67	51.60	5.93	Peak	100	36

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3:"*" is Peak / Average value of fundamental frequency



Modulation	be EHT40	Test Freq. (MHz)	5670
Polarization	Vertical		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1 *	5670.00	102.04			101.28	0.76	Average	235	259
2 *	5670.00	116.37			115.61	0.76	Peak	235	259
3	5725.00	68.06	68.20	-0.14	67.11	0.95	Peak	235	259
4	11340.00	42.33	54.00	-11.67	34.19	8.14	Average	100	39
5	11340.00	55.21	74.00	-18.79	47.07	8.14	Peak	100	39
6	17010.00	57.34	68.20	-10.86	51.41	5.93	Peak	100	22

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3:"*" is Peak / Average value of fundamental frequency



Modulation	be EHT40	Test Freq. (MHz)	5710
Polarization	Horizontal		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5460.00	42.52	54.00	-11.48	42.02	0.50	Average	143	116
2	5460.00	56.08	74.00	-17.92	55.58	0.50	Peak	143	116
3	5470.00	57.06	68.20	-11.14	56.54	0.52	Peak	143	116
4 *	5710.00	97.93			97.02	0.91	Average	143	116
5 *	5710.00	111.40			110.49	0.91	Peak	143	116
6	5850.00	57.67	68.20	-10.53	56.59	1.08	Peak	143	116
7	11420.00	41.63	54.00	-12.37	33.53	8.10	Average	100	25
8	11420.00	54.66	74.00	-19.34	46.56	8.10	Peak	100	25
9	17130.00	56.18	68.20	-12.02	50.60	5.58	Peak	100	19

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: "*" is Peak / Average value of fundamental frequency



Modulation	be EHT40	Test Freq. (MHz)	5710
Polarization	Vertical		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5460.00	42.95	54.00	-11.05	42.45	0.50	Average	232	256
2	5460.00	56.39	74.00	-17.61	55.89	0.50	Peak	232	256
3	5470.00	57.14	68.20	-11.06	56.62	0.52	Peak	232	256
4 *	5710.00	102.15			101.24	0.91	Average	232	256
5 *	5710.00	116.45			115.54	0.91	Peak	232	256
6	5850.00	57.68	68.20	-10.52	56.60	1.08	Peak	232	256
7	11420.00	41.71	54.00	-12.29	33.61	8.10	Average	100	35
8	11420.00	54.72	74.00	-19.28	46.62	8.10	Peak	100	35
9	17130.00	56.04	68.20	-12.16	50.46	5.58	Peak	100	27

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: "*" is Peak / Average value of fundamental frequency



Modulation	be EHT40	Test Freq. (MHz)	5755
Polarization	Horizontal		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5650.00	63.84	68.20	-4.36	63.18	0.66	Peak	138	114
2	5700.00	75.45	105.20	-29.75	74.55	0.90	Peak	138	114
3	5720.00	92.21	110.80	-18.59	91.27	0.94	Peak	138	114
4	5725.00	92.41	122.20	-29.79	91.46	0.95	Peak	138	114
5 *	5755.00	104.13			103.11	1.02	Average	138	114
6 *	5755.00	118.43			117.41	1.02	Peak	138	114
7	5925.00	58.76	68.20	-9.44	57.32	1.44	Peak	138	114
8	11510.00	44.79	54.00	-9.21	36.33	8.46	Average	100	116
9	11510.00	57.16	74.00	-16.84	48.70	8.46	Peak	100	116
10	17265.00	59.04	68.20	-9.16	53.58	5.46	Peak	100	248
11	23020.00	46.68	54.00	-7.32	39.78	6.90	Average	125	79
12	23020.00	61.05	74.00	-12.95	54.15	6.90	Peak	125	79

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3:"*" is Peak / Average value of fundamental frequency



Modulation	be EHT40	Test Freq. (MHz)	5755
Polarization	Vertical		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5650.00	65.47	68.20	-2.73	64.81	0.66	Peak	236	259
2	5700.00	76.68	105.20	-28.52	75.78	0.90	Peak	236	259
3	5720.00	94.81	110.80	-15.99	93.87	0.94	Peak	236	259
4	5725.00	96.25	122.20	-25.95	95.30	0.95	Peak	236	259
5 *	5755.00	107.61			106.59	1.02	Average	236	259
6 *	5755.00	122.16			121.14	1.02	Peak	236	259
7	5925.00	60.84	68.20	-7.36	59.40	1.44	Peak	236	259
8	11510.00	43.12	54.00	-10.88	34.66	8.46	Average	100	262
9	11510.00	56.14	74.00	-17.86	47.68	8.46	Peak	100	262
10	17265.00	58.72	68.20	-9.48	53.26	5.46	Peak	100	126
11	23020.00	44.62	54.00	-9.38	37.72	6.90	Average	275	134
12	23020.00	58.41	74.00	-15.59	51.51	6.90	Peak	275	134

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3:"*" is Peak / Average value of fundamental frequency



Modulation	be EHT40	Test Freq. (MHz)	5795
Polarization	Horizontal		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61



	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		cm	deg
1	5650.00	61.48	68.20	-6.72	60.82	0.66	Peak	157	117
2 *	5795.00	103.28			102.24	1.04	Average	157	117
3 *	5795.00	116.65			115.61	1.04	Peak	157	117
4	5850.00	74.83	122.20	-47.37	73.75	1.08	Peak	157	117
5	5855.00	71.23	110.80	-39.57	70.11	1.12	Peak	157	117
6	5875.00	58.74	105.20	-46.46	57.49	1.25	Peak	157	117
7	5925.00	57.64	68.20	-10.56	56.20	1.44	Peak	157	117
8	11590.00	44.81	54.00	-9.19	36.64	8.17	Average	100	110
9	11590.00	57.22	74.00	-16.78	49.05	8.17	Peak	100	110
10	17385.00	58.96	68.20	-9.24	52.95	6.01	Peak	100	258
11	23180.00	61.22	68.20	-6.98	54.07	7.15	Peak	135	86

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3:"*" is Peak / Average value of fundamental frequency



Modulation	be EHT40	Test Freq. (MHz)	5795
Polarization	Vertical		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5650.00	63.82	68.20	-4.38	63.16	0.66	Peak	238	259
2	* 5795.00	107.40			106.36	1.04	Average	238	259
3	* 5795.00	121.36			120.32	1.04	Peak	238	259
4	5850.00	80.86	122.20	-41.34	79.78	1.08	Peak	238	259
5	5855.00	75.78	110.80	-35.02	74.66	1.12	Peak	238	259
6	5875.00	61.46	105.20	-43.74	60.21	1.25	Peak	238	259
7	5925.00	57.92	68.20	-10.28	56.48	1.44	Peak	238	259
8	11590.00	43.14	54.00	-10.86	34.97	8.17	Average	100	277
9	11590.00	56.12	74.00	-17.88	47.95	8.17	Peak	100	277
10	17385.00	58.84	68.20	-9.36	52.83	6.01	Peak	100	114
11	23180.00	58.29	68.20	-9.91	51.14	7.15	Peak	264	122

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


Note 3:"*" is Peak / Average value of fundamental frequency



Unwanted Emissions (Above 1GHz) for be EHT80

Modulation	be EHT80	Test Freq. (MHz)	5210
Polarization	Horizontal		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5150.00	50.93	54.00	-3.07	50.28	0.65	Average	127	211
2	5150.00	65.38	74.00	-8.62	64.73	0.65	Peak	127	211
3 *	5210.00	95.26			94.76	0.50	Average	127	211
4 *	5210.00	108.49			107.99	0.50	Peak	127	211
5	5350.00	45.09	54.00	-8.91	44.95	0.14	Average	127	211
6	5350.00	58.17	74.00	-15.83	58.03	0.14	Peak	127	211
7	10420.00	54.72	68.20	-13.48	46.22	8.50	Peak	100	22
8	15630.00	40.85	54.00	-13.15	36.19	4.66	Average	100	12
9	15630.00	54.77	74.00	-19.23	50.11	4.66	Peak	100	12

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: "*" is Peak / Average value of fundamental frequency



Modulation	be EHT80	Test Freq. (MHz)	5210
Polarization	Vertical		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5150.00	53.56	54.00	-0.44	52.91	0.65	Average	206	239
2	5150.00	65.81	74.00	-8.19	65.16	0.65	Peak	206	239
3 *	5210.00	98.60			98.10	0.50	Average	193	242
4 *	5210.00	112.06			111.56	0.50	Peak	193	242
5	5350.00	46.43	54.00	-7.57	46.29	0.14	Average	193	242
6	5350.00	59.59	74.00	-14.41	59.45	0.14	Peak	193	242
7	10420.00	54.32	68.20	-13.88	45.82	8.50	Peak	100	44
8	15630.00	41.09	54.00	-12.91	36.43	4.66	Average	100	29
9	15630.00	55.28	74.00	-18.72	50.62	4.66	Peak	100	29

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3:"*" is Peak / Average value of fundamental frequency



Modulation	be EHT80	Test Freq. (MHz)	5290
Polarization	Horizontal		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5150.00	43.88	54.00	-10.12	43.23	0.65	Average	128	106
2	5150.00	56.93	74.00	-17.07	56.28	0.65	Peak	128	106
3 *	5290.00	93.64			93.42	0.22	Average	128	106
4 *	5290.00	106.68			106.46	0.22	Peak	128	106
5	5350.00	48.94	54.00	-5.06	48.80	0.14	Average	128	106
6	5350.00	62.23	74.00	-11.77	62.09	0.14	Peak	128	106
7	10580.00	54.43	68.20	-13.77	46.14	8.29	Peak	100	51
8	15870.00	40.86	54.00	-13.14	36.25	4.61	Average	100	13
9	15870.00	54.81	74.00	-19.19	50.20	4.61	Peak	100	13

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: "*" is Peak / Average value of fundamental frequency



Modulation	be EHT80	Test Freq. (MHz)	5290
Polarization	Vertical		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5150.00	43.19	54.00	-10.81	42.54	0.65	Average	100	271
2	5150.00	57.04	74.00	-16.96	56.39	0.65	Peak	100	271
3 *	5290.00	97.78			97.56	0.22	Average	100	271
4 *	5290.00	111.22			111.00	0.22	Peak	100	271
5	5350.00	53.59	54.00	-0.41	53.45	0.14	Average	100	271
6	5350.00	66.06	74.00	-7.94	65.92	0.14	Peak	100	271
7	10580.00	54.55	68.20	-13.65	46.26	8.29	Peak	100	53
8	15870.00	40.88	54.00	-13.12	36.27	4.61	Average	100	39
9	15870.00	54.86	74.00	-19.14	50.25	4.61	Peak	100	39

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: "*" is Peak / Average value of fundamental frequency



Modulation	be EHT80	Test Freq. (MHz)	5530
Polarization	Horizontal		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5460.00	48.60	54.00	-5.40	48.10	0.50	Average	232	132
2	5460.00	62.75	74.00	-11.25	62.25	0.50	Peak	232	132
3	5470.00	64.50	68.20	-3.70	63.98	0.52	Peak	232	132
4 *	5530.00	95.06			94.52	0.54	Average	232	132
5 *	5530.00	108.32			107.78	0.54	Peak	232	132
6	11060.00	42.39	54.00	-11.61	34.00	8.39	Average	100	26
7	11060.00	54.02	74.00	-19.98	45.63	8.39	Peak	100	26
8	16590.00	56.75	68.20	-11.45	50.91	5.84	Peak	100	32

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3:"*" is Peak / Average value of fundamental frequency



Modulation	be EHT80	Test Freq. (MHz)	5530
Polarization	Vertical		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5460.00	51.81	54.00	-2.19	51.31	0.50	Average	131	256
2	5460.00	66.38	74.00	-7.62	65.88	0.50	Peak	131	256
3	5470.00	67.89	68.20	-0.31	67.37	0.52	Peak	131	256
4 *	5530.00	98.58			98.04	0.54	Average	131	256
5 *	5530.00	112.55			112.01	0.54	Peak	131	256
6	11060.00	42.45	54.00	-11.55	34.06	8.39	Average	100	38
7	11060.00	54.08	74.00	-19.92	45.69	8.39	Peak	100	38
8	16590.00	56.72	68.20	-11.48	50.88	5.84	Peak	100	22

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3:"*" is Peak / Average value of fundamental frequency



Modulation	be EHT80	Test Freq. (MHz)	5610
Polarization	Horizontal		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1 *	5610.00	94.37			93.80	0.57	Average	235	135
2 *	5610.00	108.25			107.68	0.57	Peak	235	135
3	5725.00	63.11	68.20	-5.09	62.16	0.95	Peak	235	135
4	11220.00	43.28	54.00	-10.72	35.14	8.14	Average	100	51
5	11220.00	55.34	74.00	-18.66	47.20	8.14	Peak	100	51
6	16830.00	56.85	68.20	-11.35	50.46	6.39	Peak	100	43

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: "*" is Peak / Average value of fundamental frequency



Modulation	be EHT80	Test Freq. (MHz)	5610
Polarization	Vertical		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61




	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		cm	deg
1 *	5610.00	99.22			98.65	0.57	Average	243	258
2 *	5610.00	112.40			111.83	0.57	Peak	243	258
3	5725.00	68.09	68.20	-0.11	67.14	0.95	Peak	243	258
4	11220.00	42.74	54.00	-11.26	34.60	8.14	Average	100	39
5	11220.00	55.08	74.00	-18.92	46.94	8.14	Peak	100	39
6	16830.00	56.52	68.20	-11.68	50.13	6.39	Peak	100	39

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: "*" is Peak / Average value of fundamental frequency



Modulation	be EHT80	Test Freq. (MHz)	5690
Polarization	Horizontal		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5460.00	43.68	54.00	-10.32	43.18	0.50	Average	233	136
2	5460.00	57.22	74.00	-16.78	56.72	0.50	Peak	233	136
3	5470.00	58.05	68.20	-10.15	57.53	0.52	Peak	233	136
4 *	5690.00	94.68			93.83	0.85	Average	233	136
5 *	5690.00	108.49			107.64	0.85	Peak	233	136
6	5850.00	59.49	68.20	-8.71	58.41	1.08	Peak	233	136
7	11380.00	41.64	54.00	-12.36	33.54	8.10	Average	100	13
8	11380.00	54.65	74.00	-19.35	46.55	8.10	Peak	100	13
9	17070.00	56.14	68.20	-12.06	50.18	5.96	Peak	100	19

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: "*" is Peak / Average value of fundamental frequency



Modulation	be EHT80	Test Freq. (MHz)	5690
Polarization	Vertical		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5460.00	44.81	54.00	-9.19	44.31	0.50	Average	235	257
2	5460.00	58.34	74.00	-15.66	57.84	0.50	Peak	235	257
3	5470.00	59.26	68.20	-8.94	58.74	0.52	Peak	235	257
4 *	5690.00	100.14			99.29	0.85	Average	235	257
5 *	5690.00	114.54			113.69	0.85	Peak	235	257
6	5850.00	63.50	68.20	-4.70	62.42	1.08	Peak	235	257
7	11380.00	41.72	54.00	-12.28	33.62	8.10	Average	100	27
8	11380.00	54.69	74.00	-19.31	46.59	8.10	Peak	100	27
9	17070.00	56.05	68.20	-12.15	50.09	5.96	Peak	100	36

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: "*" is Peak / Average value of fundamental frequency



Modulation	be EHT80	Test Freq. (MHz)	5775
Polarization	Horizontal		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61



	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m		cm	deg
1	5650.00	65.22	68.20	-2.98	64.56	0.66	Peak	169	116
2	5700.00	79.94	105.20	-25.26	79.04	0.90	Peak	169	116
3	5720.00	84.19	110.80	-26.61	83.25	0.94	Peak	169	116
4	5725.00	83.94	122.20	-38.26	82.99	0.95	Peak	169	116
5 *	5775.00	97.93			96.90	1.03	Average	169	116
6 *	5775.00	111.42			110.39	1.03	Peak	169	116
7	5850.00	76.60	122.20	-45.60	75.52	1.08	Peak	169	116
8	5855.00	72.35	110.80	-38.45	71.23	1.12	Peak	169	116
9	5875.00	59.51	105.20	-45.69	58.26	1.25	Peak	169	116
10	5925.00	58.52	68.20	-9.68	57.08	1.44	Peak	169	116
11	11550.00	44.86	54.00	-9.14	36.38	8.48	Average	100	114
12	11550.00	57.21	74.00	-16.79	48.73	8.48	Peak	100	114
13	17325.00	58.94	68.20	-9.26	53.27	5.67	Peak	100	261
14	23100.00	44.85	54.00	-9.15	37.87	6.98	Average	125	88
15	23100.00	58.82	74.00	-15.18	51.84	6.98	Peak	125	88

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3:"*" is Peak / Average value of fundamental frequency



Modulation	be EHT80	Test Freq. (MHz)	5775
Polarization	Vertical		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61



	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn
	MHz	level	dBuV/m	dB	reading	dB/m		High	Table
		dBuV/m			dBuV			cm	deg
1	5650.00	67.91	68.20	-0.29	67.25	0.66	Peak	219	258
2	5700.00	85.59	105.20	-19.61	84.69	0.90	Peak	219	258
3	5720.00	88.36	110.80	-22.44	87.42	0.94	Peak	219	258
4	5725.00	89.16	122.20	-33.04	88.21	0.95	Peak	219	258
5 *	5775.00	102.32			101.29	1.03	Average	219	248
6 *	5775.00	116.14			115.11	1.03	Peak	219	248
7	5850.00	82.52	122.20	-39.68	81.44	1.08	Peak	219	258
8	5855.00	80.86	110.80	-29.94	79.74	1.12	Peak	219	258
9	5875.00	67.35	105.20	-37.85	66.10	1.25	Peak	219	258
10	5925.00	57.89	68.20	-10.31	56.45	1.44	Peak	219	258
11	11550.00	43.12	54.00	-10.88	34.64	8.48	Average	100	279
12	11550.00	56.14	74.00	-17.86	47.66	8.48	Peak	100	279
13	17325.00	58.76	68.20	-9.44	53.09	5.67	Peak	100	124
14	23100.00	44.76	54.00	-9.24	37.78	6.98	Average	275	125
15	23100.00	58.67	74.00	-15.33	51.69	6.98	Peak	275	125

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3:"*" is Peak / Average value of fundamental frequency



Unwanted Emissions (Above 1GHz) for be EHT160


Modulation	be EHT160	Test Freq. (MHz)	5250						
Polarization	Horizontal								
<p>Test By : Sean Yu Temperature(°C): 25 Humidity(%): 61</p>									
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5150.00	47.88	54.00	-6.12	47.23	0.65	Average	132	211
2	5150.00	64.12	74.00	-9.88	63.47	0.65	Peak	132	211
3 *	5250.00	92.46			92.18	0.28	Average	132	211
4 *	5250.00	105.33			105.05	0.28	Peak	132	211
5	5350.00	49.65	54.00	-4.35	49.51	0.14	Average	132	211
6	5350.00	65.76	74.00	-8.24	65.62	0.14	Peak	132	211
7	10500.00	54.41	68.20	-13.79	45.95	8.46	Peak	100	36
8	15750.00	40.78	54.00	-13.22	35.78	5.00	Average	100	33
9	15750.00	54.72	74.00	-19.28	49.72	5.00	Peak	100	33

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3:"*" is Peak / Average value of fundamental frequency



Modulation	be EHT160	Test Freq. (MHz)	5250
Polarization	Vertical		

Test By : Sean Yu Temperature(°C): 25 Humidity(%): 61




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5150.00	49.78	54.00	-4.22	49.13	0.65	Average	323	225
2	5150.00	64.94	74.00	-9.06	64.29	0.65	Peak	323	225
3 *	5250.00	95.76			95.48	0.28	Average	146	256
4 *	5250.00	108.77			108.49	0.28	Peak	146	256
5	5350.00	53.85	54.00	-0.15	53.71	0.14	Average	146	256
6	5350.00	69.05	74.00	-4.95	68.91	0.14	Peak	146	256
7	10500.00	54.38	68.20	-13.82	45.92	8.46	Peak	100	24
8	15750.00	40.79	54.00	-13.21	35.79	5.00	Average	100	31
9	15750.00	54.81	74.00	-19.19	49.81	5.00	Peak	100	31

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: "*" is Peak / Average value of fundamental frequency



Modulation	be EHT160	Test Freq. (MHz)	5570
Polarization	Horizontal		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5460.00	47.39	54.00	-6.61	46.89	0.50	Average	103	222
2	5460.00	62.02	74.00	-11.98	61.52	0.50	Peak	103	222
3	5470.00	63.51	68.20	-4.69	62.99	0.52	Peak	103	222
4 *	5570.00	89.33			88.81	0.52	Average	103	222
5 *	5570.00	103.01			102.49	0.52	Peak	103	222
6	5725.00	61.51	68.20	-6.69	60.56	0.95	Peak	103	222
7	11140.00	43.26	54.00	-10.74	34.96	8.30	Average	100	52
8	11140.00	55.29	74.00	-18.71	46.99	8.30	Peak	100	52
9	16710.00	56.84	68.20	-11.36	50.61	6.23	Peak	100	31

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: "*" is Peak / Average value of fundamental frequency



Modulation	be EHT160	Test Freq. (MHz)	5570
Polarization	Vertical		

Test By :Brad Wu Temperature(°C):25 Humidity(%):61



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB/m	Remark	ANT High cm	Turn Table deg
1	5460.00	51.41	54.00	-2.59	50.91	0.50	Average	138	256
2	5460.00	65.66	74.00	-8.34	65.16	0.50	Peak	138	256
3	5470.00	67.86	68.20	-0.34	67.34	0.52	Peak	138	256
4 *	5570.00	94.33			93.81	0.52	Average	138	256
5 *	5570.00	108.08			107.56	0.52	Peak	138	256
6	5725.00	65.52	68.20	-2.68	64.57	0.95	Peak	138	256
7	11140.00	43.25	54.00	-10.75	34.95	8.30	Average	100	38
8	11140.00	55.36	74.00	-18.64	47.06	8.30	Peak	100	38
9	16710.00	56.85	68.20	-11.35	50.62	6.23	Peak	100	27

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV) + Factor* (dB/m)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: "*" is Peak / Average value of fundamental frequency




Frequency: 5300 MHz	Frequency Drift (ppm)			
	0 minute	2 minutes	5 minutes	10 minutes
T20°CVmax	-6.11	-5.74	-5.88	-5.70
T20°CVmin	-5.91	-5.48	-6.34	-5.76
T40°CVnom	-9.32	-9.01	-9.18	-8.81
T30°CVnom	-7.32	-7.24	-6.84	-6.70
T20°CVnom	-6.02	-5.65	-5.75	-6.03
T10°CVnom	-2.79	-2.11	-2.22	-2.15
T0°CVnom	2.81	3.27	2.85	3.38
Vnom [V]: 120	Vmax [V]: 138		Vmin [V]: 102	
Tnom [°C]: 20	Tmax [°C]: 40		Tmin [°C]: 0	

Frequency: 5785 MHz	Frequency Drift (ppm)			
	0 minute	2 minutes	5 minutes	10 minutes
T20°CVmax	-5.60	-5.58	-5.74	-5.65
T20°CVmin	-5.41	-5.16	-5.41	-4.95
T40°CVnom	-8.54	-8.22	-8.40	-7.90
T30°CVnom	-6.71	-6.01	-5.88	-6.92
T20°CVnom	-5.51	-4.83	-5.24	-5.04
T10°CVnom	-2.56	-3.05	-1.95	-2.20
T0°CVnom	2.58	2.53	2.72	2.59
Vnom [V]: 120	Vmax [V]: 138		Vmin [V]: 102	
Tnom [°C]: 20	Tmax [°C]: 40		Tmin [°C]: 0	



Modulation Mode	be EHT20	Test Freq. (MHz)	5240
Power Phase	Line		

Test by : Joe Liao Temperature: 23°C Humidity: 63%




	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	Factor dB	Cable loss dB	Aux dB	Remark
1	0.150	29.72	56.00	-26.28	19.81	9.63	0.08	0.20	Average
2	0.150	44.10	66.00	-21.90	34.19	9.63	0.08	0.20	QP
3	0.240	27.48	52.08	-24.60	17.52	9.62	0.07	0.27	Average
4	0.240	36.12	62.08	-25.96	26.16	9.62	0.07	0.27	QP
5	0.267	26.28	51.20	-24.92	16.31	9.62	0.07	0.28	Average
6	0.267	34.64	61.20	-26.56	24.67	9.62	0.07	0.28	QP
7*	0.322	31.82	49.66	-17.84	21.83	9.62	0.07	0.30	Average
8	0.322	38.00	59.66	-21.66	28.01	9.62	0.07	0.30	QP
9	0.358	25.64	48.78	-23.14	15.62	9.62	0.08	0.32	Average
10	0.358	36.64	58.78	-22.14	26.62	9.62	0.08	0.32	QP
11	0.683	20.22	46.00	-25.78	10.15	9.63	0.09	0.35	Average
12	0.683	31.98	56.00	-24.02	21.91	9.63	0.09	0.35	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB) + Aux (dB).
 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).



Modulation Mode	be EHT20	Test Freq. (MHz)	5240
Power Phase	Neutral		

Test by : Joe Liao Temperature: 23°C Humidity: 63%




	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	Factor dB	Cable loss dB	Aux dB	Remark
1	0.150	31.15	56.00	-24.85	21.32	9.63	0.08	0.12	Average
2	0.150	44.72	66.00	-21.28	34.89	9.63	0.08	0.12	QP
3	0.258	31.87	51.51	-19.64	21.97	9.63	0.07	0.20	Average
4	0.258	41.91	61.51	-19.60	32.01	9.63	0.07	0.20	QP
5	0.312	30.60	49.93	-19.33	20.69	9.62	0.07	0.22	Average
6	0.312	38.85	59.93	-21.08	28.94	9.62	0.07	0.22	QP
7*	0.322	35.02	49.66	-14.64	25.11	9.62	0.07	0.22	Average
8	0.322	41.14	59.66	-18.52	31.23	9.62	0.07	0.22	QP
9	0.348	31.07	49.00	-17.93	21.14	9.62	0.08	0.23	Average
10	0.348	38.48	59.00	-20.52	28.55	9.62	0.08	0.23	QP
11	0.672	20.88	46.00	-25.12	10.88	9.63	0.09	0.28	Average
12	0.672	31.49	56.00	-24.51	21.49	9.63	0.09	0.28	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB) + Aux (dB).
 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).



Modulation Mode	be EHT20	Test Freq. (MHz)	5825
Power Phase	Line		

Test by : Joe Liao Temperature: 23°C Humidity: 63%




	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	Factor dB	Cable loss dB	Aux dB	Remark
1	0.240	27.19	52.08	-24.89	17.23	9.62	0.07	0.27	Average
2	0.240	35.92	62.08	-26.16	25.96	9.62	0.07	0.27	QP
3	0.276	28.58	50.94	-22.36	18.60	9.62	0.07	0.29	Average
4*	0.276	39.68	60.94	-21.26	29.70	9.62	0.07	0.29	QP
5	0.339	23.53	49.22	-25.69	13.52	9.62	0.08	0.31	Average
6	0.339	37.00	59.22	-22.22	26.99	9.62	0.08	0.31	QP
7	0.365	22.66	48.61	-25.95	12.64	9.62	0.08	0.32	Average
8	0.365	36.35	58.61	-22.26	26.33	9.62	0.08	0.32	QP
9	0.529	20.96	46.00	-25.04	10.92	9.62	0.08	0.34	Average
10	0.529	27.86	56.00	-28.14	17.82	9.62	0.08	0.34	QP
11	0.683	20.15	46.00	-25.85	10.08	9.63	0.09	0.35	Average
12	0.683	32.03	56.00	-23.97	21.96	9.63	0.09	0.35	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB) + Aux (dB).
 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).



Modulation Mode	be EHT20	Test Freq. (MHz)	5825
Power Phase	Neutral		

Test by : Joe Liao Temperature: 23°C Humidity: 63%



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	Factor dB	Cable loss dB	Aux dB	Remark
1	0.213	27.93	53.10	-25.17	18.06	9.63	0.06	0.18	Average
2	0.213	37.36	63.10	-25.74	27.49	9.63	0.06	0.18	QP
3	0.258	25.99	51.51	-25.52	16.09	9.63	0.07	0.20	Average
4	0.258	34.54	61.51	-26.97	24.64	9.63	0.07	0.20	QP
5	0.266	27.67	51.25	-23.58	17.77	9.63	0.07	0.20	Average
6	0.266	36.32	61.25	-24.93	26.42	9.63	0.07	0.20	QP
7*	0.322	35.08	49.66	-14.58	25.17	9.62	0.07	0.22	Average
8	0.322	41.16	59.66	-18.50	31.25	9.62	0.07	0.22	QP
9	0.348	30.89	49.00	-18.11	20.96	9.62	0.08	0.23	Average
10	0.348	38.51	59.00	-20.49	28.58	9.62	0.08	0.23	QP
11	0.538	19.26	46.00	-26.74	9.29	9.62	0.08	0.27	Average
12	0.538	25.90	56.00	-30.10	15.93	9.62	0.08	0.27	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB) + Aux (dB).
 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).