

# EMC TEST REPORT


**Report No. : EME-070049****Model No. : G-210H****Issued Date : Jan. 29, 2007**

**Applicant : ZyXEL Communications Corporation**  
**6, Innovation Rd II, Science-Based Industrial Park,**  
**Hsin-Chu, Taiwan**

**Test By : Intertek Testing Services Taiwan Ltd.**  
**No. 11, Lane 275, Ko-Nan 1 Street, Chia-Tung Li,**  
**Shiang-Shan District, Hsinchu City, Taiwan**

This test report consists of 43 pages in total. It may be duplicated completely for legal use with the allowance of the applicant. It shall not be reproduced except in full, without the written approval of Intertek Laboratory. The test result(s) in this report only applies to the tested sample(s).

Project Engineer



Marx Yan

Reviewed By



Kevin Chen

## Table of Contents

Summary of Tests .....	3
1. General information .....	4
1.1 Identification of the EUT .....	4
1.2 Additional information about the EUT .....	4
1.3 Antenna description .....	4
1.4 Peripherals equipment .....	5
2. Test specifications .....	6
2.1 Test standard .....	6
2.2 Operation mode .....	6
2.3 Test equipment .....	7
3. Minimum 6dB Bandwidth test .....	8
3.1 Operating environment .....	8
3.2 Test setup & procedure .....	8
3.3 Measured data of Minimum 6dB Bandwidth test results .....	8
4. Maximum Output Power test .....	15
4.1 Operating environment .....	15
4.2 Test setup & procedure .....	15
4.3 Measured data of Maximum Output Power test results .....	15
5. Radiated Emission test .....	16
5.1 Operating environment .....	16
5.2 Test setup & procedure .....	16
5.3 Emission limits .....	18
5.4 Radiated spurious emission test data .....	19
5.4.1 Measurement results: frequencies equal to or less than 1 GHz .....	19
5.4.2 Measurement results: frequency above 1GHz .....	21
6. Power Spectrum Density test .....	27
6.1 Operating environment .....	27
6.2 Test setup & procedure .....	27
6.3 Measured data of Power Spectrum Density test results .....	27
7. Emission on the band edge .....	34
7.1 Operating environment .....	34
7.2 Test setup & procedure .....	34
7.3 Test Result .....	39
8. Power Line Conducted Emission test §FCC 15.207 .....	40
8.1 Operating environment .....	40
8.2 Test setup & procedure .....	40
8.3 Emission limit .....	41
8.4 Uncertainty of Conducted Emission .....	41
8.5 Power Line Conducted Emission test data .....	42

**Summary of Tests****802.11b/g Wireless USB Adapter-Model: G-210H  
FCC ID: I88G210H**

Test	Reference	Results
Minimum 6dB Bandwidth test	15.247(a)(2)	Pass
Maximum Output Power test	15.247(b)	Pass
Radiated Spurious Emission test	15.205, 15.209	Pass
Power Spectrum Density test	15.247(e)	Pass
Emission on the Band Edge test	15.247(d)	Pass
AC Power Line Conducted Emission test	15.207	Pass

## 1. General information

### 1.1 Identification of the EUT

Applicant	: ZyXEL Communications Corporation
Product	: 802.11b/g Wireless USB Adapter
Model No.	: G-210H
FCC ID.	: I88G210H
Frequency Range	: 2412MHz to 2462MHz
Channel Number	: 11 channels
Frequency of Each Channel	: 2412MHz, 2417MHz, 2422MHz, 2427MHz, 2432MHz, 2437MHz, 2442MHz, 2447MHz, 2452MHz, 2457MHz, 2462MHz
Type of Modulation	: DSSS, OFDM
Rated Power	: 5Vdc from PC
Power Cord	: N/A
Sample Received	: Oct. 11, 2005
Test Date(s)	: Oct. 11. 2005 ~ Oct. 26, 2005

A FCC DoC report has been generated for the client.

### 1.2 Additional information about the EUT

The EUT is a 802.11b/g Wireless USB Adapter, and was defined as information technology equipment.

For more detail features, please refer to User's manual as file name "Installation guide.pdf"

### 1.3 Antenna description

The EUT uses a permanently connected antenna.

Antenna Gain	: 5dBi max
Antenna Type	: Patch antenna
Connector Type	: Integral

**1.4 Peripherals equipment**

Peripherals	Manufacturer	Product No.	Serial No.
Note PC	IBM	2887	99XML12
Printer	HP	DeskJet 400	TH86K1N2ZB

## **2. Test specifications**

### **2.1 Test standard**

The EUT was performed according to the procedures in FCC Part 15 Subpart C Section § 15.205, §15.207, §15.209, §15.247 and ANSI C63.4/2003.

The test of radiated measurements according to FCC Part15 Section 15.33(a) had been conducted and the field strength of this frequency band were all meet limit requirement, thus we evaluate the EUT pass the specified test.

### **2.2 Operation mode**

The EUT was run the test program “QAU2751W.exe” under windows OS, which provide by manufacturer.

The EUT was operating in continuously transmitting status during all the tests except conducted emission during which the EUT was tested in normal operating mode with AP.

With individual verifying, the maximum output power were found at 1Mbps data rate for 802.11b mode and 6Mbps data rate for 802.11g mode. The final tests were executed under these conditions recorded in this report individually.

### 2.3 Test equipment

Equipment	Brand	Frequency range	Model No.	Intertek ID No.	Next Cal. Date
EMI Test Receiver	Rohde & Schwarz	9kHz~2.75GHz	ESCS 30	EC303	04/17/2006
EMI Test Receiver	Rohde & Schwarz	20Hz~26.5GHz	ESMI	EC317	07/14/2006
Spectrum Analyzer	Rohde & Schwarz	9kHz~30GHz	FSP 30	EC353	07/13/2006
Spectrum Analyzer	Rohde & Schwarz	20Hz~40GHz	FSEK 30	EC365	10/18/2006
Horn Antenna	SCHWARZBECK	1GHz~18GHz	BBHA 9120 D	EC371	12/22/2007
Horn Antenna	SCHWARZBECK	14GHz~40GHz	BBHA 9170	EC351	07/08/2007
Bilog Antenna	SCHWARZBECK	25MHz~2GHz	VULB 9168	EC347	12/23/2007
Pre-Amplifier	MITEQ	100MHz~26.5GHz	919981	EC373	12/30/2005
Pre-Amplifier	MITEQ	26GHz~40GHz	828825	EC374	01/28/2006
Wideband Peak Power Meter/ Sensor	Anritsu	100MHz~18GHz	ML2497A/MA2491A	EC396	10/18/2006
Controller	HDGmbH	N/A	CM 100	EP346	N/A
Antenna Tower	HDGmbH	N/A	MA 240	EP347	N/A
LISN	Rohde & Schwarz	9KHz~30MHz	ESH3-Z5	EC344	01/13/2006

Note: 1. The above equipments are within the valid calibration period.

2. The test antennas (receiving antenna) are calibration per 3 years.

### 3. Minimum 6dB Bandwidth test

#### 3.1 Operating environment

Temperature: 23  
 Relative Humidity: 53 %  
 Atmospheric Pressure: 1023 hPa

#### 3.2 Test setup & procedure

The minimum 6dB bandwidth per FCC §15.247(a)(2) was measured using a 50 ohm spectrum analyzer with the resolutions bandwidth set at 100kHz, the video bandwidth set at 300kHz, and the SPAN>>RBW. The test was performed at 3 channels (lowest, middle and highest channel). The minimum 6-dB modulation bandwidth is in the following Table.

#### 3.3 Measured data of Minimum 6dB Bandwidth test results

Test Mode: 802.11b (DSSS Modulation) operating mode

Channel	Frequency (MHz)	Bandwidth (MHz)	Limit
1 (lowest)	2412	12.22	> 500kHz
6 (middle)	2437	12.30	> 500kHz
11 (highest)	2462	12.30	> 500kHz


Test Mode: 802.11g (OFDM Modulation) operating mode

Channel	Frequency (MHz)	Bandwidth (MHz)	Limit
1 (lowest)	2412	16.55	> 500kHz
6 (middle)	2437	16.59	> 500kHz
11 (highest)	2462	16.59	> 500kHz

Please see the plot below.




## Test Mode: 802.11b(DSSS Modulation) operating mode




Comment A: 6dB bandwidth at ch 1 (EC365) 802.11b

Date: 19.OCT.2005 16:16:43



Comment A: 6dB bandwidth at ch 6 (EC365) 802.11b


Date: 19.OCT.2005 16:19:43



Comment A: 6dB bandwidth at ch 11 (EC365) 802.11b


Date: 19.OCT.2005 16:21:31

## Test Mode: 802.11g(OFDM Modulation) operating mode




Comment A: 6dB bandwidth at ch 1 (EC365) 802.11g

Date: 19.OCT.2005 16:30:10



Comment A: 6dB bandwidth at ch 6 (EC365) 802.11g  
Date: 19.OCT.2005 16:28:37



Comment A: 6dB bandwidth at ch 11 (EC365) 802.11g  
Date: 19.OCT.2005 16:26:57

## 4. Maximum Output Power test

### 4.1 Operating environment

Temperature: 23  
 Relative Humidity: 53 %  
 Atmospheric Pressure: 1023 hPa

### 4.2 Test setup & procedure

The power output per FCC §15.247(b) was measured on the EUT using a 50 ohm SMA cable connected to peak power meter via power sensor. Power was read directly and cable loss correction (1.2 dB) was added to the reading to obtain power at the EUT antenna terminals. The test was performed at 3 channels (lowest, middle and highest channel).

### 4.3 Measured data of Maximum Output Power test results

Test Mode: 802.11b (DSSS Modulation) operating mode

Channel	Freq. (MHz)	C.L. (dB)	Reading (dBm)	Conducted Peak Output Power		Limit (dBm)
				(dBm)	(mW)	
1 (lowest)	2412	1.2	10.16	11.36	10.38	30
6 (middle)	2437	1.2	9.83	11.03	9.62	30
11 (highest)	2462	1.2	10.08	11.28	10.19	30

Remark:

Conducted Peak Output Power = Reading + C.L.

Test Mode: 802.11g (DSSS Modulation) operating mode

Channel	Freq. (MHz)	C.L. (dB)	Reading (dBm)	Conducted Peak Output Power		Limit (dBm)
				(dBm)	(mW)	
1 (lowest)	2412	1.2	13.75	14.95	23.71	30
6 (middle)	2437	1.2	13.28	14.48	21.28	30
11 (highest)	2462	1.2	13.59	14.79	22.86	30

Remark:

Conducted Peak Output Power = Reading + C.L.


## 5. Radiated Emission test

### 5.1 Operating environment

Temperature: 23  
Relative Humidity: 53 %  
Atmospheric Pressure: 1023 hPa

### 5.2 Test setup & procedure

The Diagram below shows the test setup, which is utilized to make these measurements.



Radiated emissions were investigated cover the frequency range from 30MHz to 1000MHz using a receiver RBW of 120kHz record QP reading, and the frequency over 1GHz using a spectrum analyzer RBW of 1MHz and 10Hz VBW record Average reading. (15.209 paragraph), the Peak reading (1MHz RBW/VBW) recorded also on the report.

The EUT for testing is arranged on a wooden turntable. If some peripherals apply to the EUT, the peripherals will be connected to EUT and the whole system. During the test, all cables were arranged to produce worst-case emissions. The signal is maximized through rotation. The height of antenna and polarization is changing constantly for exploring for maximum signal level. The height of antenna can be up to 4 meters and down to 1 meter.



The measurement for radiated emission will be done at the distance of three meters unless the signal level is too low to measure at that distance. In the case of the reading under noise floor, a pre-amplifier is used and/or the test is conducted at a closer distance. And then all readings are extrapolated back to the equivalent 3meter reading using inverse scaling with distance.

The signal is maximized through rotation and placement in the three orthogonal axes.

**Setup 1****Setup 2****Setup 3**

After verifying three setup configurations, the maximum electromagnetic field was found at setup 1 configuration. The final test data was executed under this configuration.

The EUT configuration please refer to the “Spurious set-up photo.pdf”.

### 5.3 Emission limits

The spurious Emission shall test through the 10th harmonic. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

Frequency (MHz)	Limits (dB $\mu$ V/m@3m)
30-88	40
88-216	43.5
216-960	46
Above 960	54

Remark:

1. In the above table, the tighter limit applies at the band edges.
2. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system

Uncertainty was calculated in accordance with NAMAS NIS 81.

Expanded uncertainty (k=2) of radiated emission measurement is 4.98 dB.

## 5.4 Radiated spurious emission test data

The radiated spurious emissions at

Frequency(MHz)	Margin
598.420	-3.42

are less than uncertainty. This is within the stated measurement uncertainty, this may affect compliance determined in other test arrangements.

### 5.4.1 Measurement results: frequencies equal to or less than 1 GHz

The test was performed on EUT under 802.11b continuously transmitting mode. Channel 1, 6, 11 were verified. The worst case occurred at 802.11b Tx channel 1.

EUT : G-210H

Worst Case : 802.11b Tx at channel 1

Antenna Polariz. (V/H)	Freq. (MHz)	Receiver Detector	Corr. Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)
V	480.080	QP	18.21	10.73	28.94	46.00	-17.06
V	518.880	QP	18.92	15.62	34.54	46.00	-11.46
V	575.140	QP	20.14	16.34	36.48	46.00	-9.52
V	598.420	QP	20.71	14.95	35.66	46.00	-10.34
V	664.380	QP	21.73	18.45	40.18	46.00	-5.82
V	838.980	QP	23.61	14.20	37.81	46.00	-8.19
H	70.740	QP	11.20	21.29	32.49	40.00	-7.51
H	134.760	QP	12.76	21.53	34.29	43.50	-9.21
H	289.960	QP	14.16	22.49	36.65	46.00	-9.35
H	359.800	QP	15.74	20.12	35.86	46.00	-10.14
H	480.080	QP	18.53	13.57	32.10	46.00	-13.90
H	598.420	QP	20.84	13.21	34.05	46.00	-11.95

Remark:

1. Corr. Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Corr. Factor

The test was performed on EUT under 802.11g continuously transmitting mode. Channel 1, 6, 11 were verified. The worst case occurred at 802.11g Tx channel 1.

EUT : G-210H

Worst Case : 802.11g Tx at channel 1

Antenna Polariz. (V/H)	Freq. (MHz)	Receiver Detector	Corr. Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)
V	235.640	QP	12.20	15.84	28.04	46.00	-17.96
V	359.800	QP	15.34	14.90	30.24	46.00	-15.76
V	518.880	QP	18.92	17.74	36.66	46.00	-9.34
V	575.140	QP	20.14	18.04	38.18	46.00	-7.82
V	598.420	QP	20.71	15.31	36.02	46.00	-9.98
V	666.320	QP	21.76	12.50	34.26	46.00	-11.74
H	70.740	QP	11.20	21.66	32.86	40.00	-7.14
H	119.240	QP	11.53	20.18	31.71	43.50	-11.79
H	134.760	QP	12.76	22.23	34.99	43.50	-8.51
H	289.960	QP	14.16	20.83	34.99	46.00	-11.01
H	575.140	QP	20.30	17.36	37.66	46.00	-8.34
H	598.420	QP	20.84	21.74	42.58	46.00	-3.42

Remark:

1. Corr. Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Corr. Factor

### 5.4.2 Measurement results: frequency above 1GHz

EUT : G-210H

Test Condition : 802.11b Tx at channel 1

Frequency (MHz)	Spectrum Analyzer Detector	Antenna Polariz. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)
4824	PK	V	36.07	37.77	55.34	57.04	74	-16.96
4824	AV	V	36.07	37.77	40.83	42.53	54	-11.47
7236	PK	V	-	-	-	-	54	-
9648	PK	V	-	-	-	-	54	-
4824	PK	H	36.07	37.77	61.88	63.58	74	-10.42
4824	AV	H	36.07	37.77	47.37	49.07	54	-4.93
7236	PK	H	-	-	-	-	54	-
9648	PK	H	-	-	-	-	54	-

#### Remark:

1. Correction Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Correction Factor – Preamp. Gain
3. The frequency measured ranges from 1GHz to 25GHz. The data value listed above which is higher than the noise floor, the others please refer to noise floor level.

Noise floor level is :

For PK:

1GHz-3GHz: 20dBuV

3GHz-14GHz: 27dBuV

14GHz-26.5GHz: 39dBuV

For AV:

1GHz-3GHz: 10dBuV

3GHz-14GHz: 16dBuV

14GHz-26.5GHz: 28dBuV

EUT : G-210H  
Test Condition : 802.11b Tx at channel 6

Frequency (MHz)	Spectrum Analyzer Detector	Antenna Polariz. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)
4874	PK	V	36.07	37.77	54.57	56.27	74	-17.73
4874	AV	V	36.07	37.77	40.06	41.76	54	-12.24
7311	PK	V	-	-	-	-	54	-
9748	PK	V	-	-	-	-	54	-
4874	PK	H	36.07	37.77	60.85	62.55	74	-11.45
4874	AV	H	36.07	37.77	46.34	48.04	54	-5.96
7311	PK	H	-	-	-	-	54	-
9748	PK	H	-	-	-	-	54	-

#### Remark:

1. Correction Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Correction Factor – Preamp. Gain
3. The frequency measured ranges from 1GHz to 25GHz. The data value listed above which is higher than the noise floor, the others please refer to noise floor level.

Noise floor level is:

For PK:

1GHz-3GHz: 20dBuV

3GHz-14GHz: 27dBuV

14GHz-26.5GHz: 39dBuV

For AV:

1GHz-3GHz: 10dBuV

3GHz-14GHz: 16dBuV

14GHz-26.5GHz: 28dBuV

EUT : G-210H  
Test Condition : 802.11b Tx at channel 11

Frequency (MHz)	Spectrum Analyzer Detector	Antenna Polariz. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)
4924	PK	V	36.07	37.77	56.61	58.31	74	-15.69
4924	AV	V	36.07	37.77	42.10	43.80	54	-10.20
7386	PK	V	-	-	-	-	54	-
9848	PK	V	-	-	-	-	54	-
4924	PK	H	36.07	37.77	64.95	66.65	74	-7.35
4924	AV	H	36.07	37.77	50.44	52.14	54	-1.86
7386	PK	H	-	-	-	-	54	-
9848	PK	H	-	-	-	-	54	-

#### Remark:

1. Correction Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Correction Factor – Preamp. Gain
3. The frequency measured ranges from 1GHz to 25GHz. The data value listed above which is higher than the noise floor, the others please refer to noise floor level.

Noise floor level is:

For PK:

1GHz-3GHz: 20dBuV

3GHz-14GHz: 27dBuV

14GHz-26.5GHz: 39dBuV

For AV:

1GHz-3GHz: 10dBuV

3GHz-14GHz: 16dBuV

14GHz-26.5GHz: 28dBuV

EUT : G-210H  
Test Condition : 802.11g Tx at channel 1

Frequency (MHz)	Spectrum Analyzer Detector	Antenna Polariz. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)
4824	PK	V	-	-	-	-	54	-
6420	PK	V	36.65	40.87	48	52.22	74	-21.78
6420	AV	V	36.65	40.87	35.36	39.58	54	-14.42
7236	PK	V	-	-	-	-	54	-
4824	PK	H	36.07	37.77	51.8	53.5	74	-20.5
4824	AV	H	36.07	37.77	32.56	34.26	54	-19.74
7236	PK	H	-	-	-	-	54	-
9648	PK	H	-	-	-	-	54	-

#### Remark:

1. Correction Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Correction Factor – Preamp. Gain
3. The frequency measured ranges from 1GHz to 25GHz.The data value listed above which is higher than the noise floor, the others please refer to noise floor level.

Noise floor level is :

For PK:

1GHz-3GHz: 20dBuV

3GHz-14GHz: 27dBuV

14GHz-26.5GHz: 39dBuV

For AV:

1GHz-3GHz: 10dBuV

3GHz-14GHz: 16dBuV

14GHz-26.5GHz: 28dBuV



EUT : G-210H  
Test Condition : 802.11g Tx at channel 6

Frequency (MHz)	Spectrum Analyzer Detector	Antenna Polariz. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)
4874	PK	V	-	-	-	-	54	-
6480	PK	V	36.65	40.87	52.87	57.09	74	-16.91
6480	AV	V	36.65	40.87	40.23	44.45	54	-9.55
7311	PK	V	-	-	-	-	54	-
4874	PK	H	36.07	37.77	59.88	61.58	74	-12.42
4874	AV	H	36.07	37.77	40.64	42.34	54	-11.66
7311	PK	H	-	-	-	-	54	-
9748	PK	H	-	-	-	-	54	-

#### Remark:

1. Correction Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Correction Factor – Preamp. Gain
3. The frequency measured ranges from 1GHz to 25GHz. The data value listed above which is higher than the noise floor, the others please refer to noise floor level.

Noise floor level is:

For PK:

1GHz-3GHz: 20dBuV

3GHz-14GHz: 27dBuV

14GHz-26.5GHz: 39dBuV

For AV:

1GHz-3GHz: 10dBuV

3GHz-14GHz: 16dBuV

14GHz-26.5GHz: 28dBuV

EUT : G-210H  
Test Condition : 802.11b Tx at channel 11

Frequency (MHz)	Spectrum Analyzer Detector	Antenna Polariz. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)
4924	PK	V	-	-	-	-	54	-
6570	PK	V	36.58	42.96	46.7	53.08	74	-20.92
6570	AV	V	36.58	42.96	34.06	40.44	54	-13.56
7386	PK	V	-	-	-	-	54	-
4924	PK	H	36.07	37.77	56.42	58.12	74	-15.88
4924	AV	H	36.07	37.77	37.18	38.88	54	-15.12
7386	PK	H	-	-	-	-	54	-
9848	PK	H	-	-	-	-	54	-

#### Remark:

1. Correction Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Correction Factor – Preamp. Gain
3. The frequency measured ranges from 1GHz to 25GHz. The data value listed above which is higher than the noise floor, the others please refer to noise floor level.

Noise floor level is:

For PK:

1GHz-3GHz: 20dBuV

3GHz-14GHz: 27dBuV

14GHz-26.5GHz: 39dBuV

For AV:

1GHz-3GHz: 10dBuV

3GHz-14GHz: 16dBuV

14GHz-26.5GHz: 28dBuV

## 6. Power Spectrum Density test

### 6.1 Operating environment

Temperature: 23  
 Relative Humidity: 53 %  
 Atmospheric Pressure 1023 hPa

### 6.2 Test setup & procedure

The power spectrum density per FCC §15.247(e) was measured from the antenna port of the EUT using a 50ohm spectrum analyzer with the resolution bandwidth set at 3kHz, the video bandwidth set at 10kHz, a span of 1.5 MHz, and the sweep time set at 500 seconds. Power Density was read directly was added to the reading to obtain power at the EUT antenna terminals. The test was performed at 3 channels (lowest, middle and highest channel). The Power Spectral Density measured result is in the following table.

### 6.3 Measured data of Power Spectrum Density test results

Test Mode: 802.11b (DSSS Modulation) operating mode


Channel	Frequency (MHz)	Power spectrum density (dBm)	Limit (dBm)
1 (lowest)	2412	-17.78	8
6 (middle)	2437	-20.75	8
11 (highest)	2462	-18.26	8

Test Mode: 802.11g (OFDM Modulation) operating mode


Channel	Frequency (MHz)	Power spectrum density (dBm)	Limit (dBm)
1 (lowest)	2412	-23.09	8
6 (middle)	2437	-24.31	8
11 (highest)	2462	-23.92	8

Please see the plot below.

Test Mode: 802.11b (DSSS Modulation) operating mode




Comment A: Power spectral density at low channel  
Date: 27.OCT.2005 10:06:33



Comment A: Power spectral density at middle channel


Date: 27.OCT.2005 10:08:22



Comment A: Power spectral density at high channel


Date: 27.OCT.2005 10:09:30

## Test Mode: 802.11g (OFDM Modulation) operating mode



Comment A: Power spectral density at low channel


Date: 27.OCT.2005 10:10:38



Comment A: Power spectral density at middle channel

Date: 27.OCT.2005 10:11:37





Comment A: Power spectral density at high channel

Date: 27.OCT.2005 10:12:53

## 7. Emission on the band edge

In any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### 7.1 Operating environment

Temperature:	23	
Relative Humidity:	53	%
Atmospheric Pressure	1023	hPa

### 7.2 Test setup & procedure


The output of EUT was connected to spectrum analyzer via a 50ohm cable.

The setting of spectrum analyzer is:

Peak:	RBW = 100kHz ;	VBW = 100kHz
Average:	RBW = 1MHz ;	VBW = 10Hz

Please see the test plot below.


## Test Mode: 802.11b (DSSS Modulation) operating mode



Comment A: Band-edge at 802.11b CH1

F1=2390MHz, F2=2400MHz


Date: 19.OCT.2005 17:20:36



Comment A: Band-edge at 802.11b CH1

F1=2390MHz, F2=2400MHz


Date: 19.OCT.2005 17:24:21



Comment A: Band-edge at 802.11b CH11

F1=2483.5MHz

Date: 19.OCT.2005 17:18:01



Comment A: Band-edge at 802.11b CH11

F1=2483.5MHz

Date: 19.OCT.2005 17:15:15

### 7.3 Test Result

Test Mode: 802.11b (DSSS Modulation) operating mode

Channel	Detector	Radiated Method	Conducted Method	The Max. Field Strength in Restrict Band (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)
		Max. Field Strength of Fundamental @3m (dBuV/m)	Between Carrier Max. Power and Local Max. Emission in Restrict Band (dBc)			
		A	B			
1 (lowest)	PK	106.34	52.83	53.51	74	-20.49
	AV	96.54	54.57	41.97	54	-12.03
11 (highest)	PK	108.22	48.81	59.41	74	-14.59
	AV	98.10	51.18	46.92	54	-7.08

Remark: 1.  $C = A - B$

2.  $E = C - D$

Test Mode: 802.11g (OFDM Modulation) operating mode

Channel	Detector	Radiated Method	Conducted Method	The Max. Field Strength in Restrict Band (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)
		Max. Field Strength of Fundamental @3m (dBuV/m)	Between Carrier Max. Power and Local Max. Emission in Restrict Band (dBc)			
		A	B			
1 (lowest)	PK	104.16	46.73	57.43	74	-16.57
	AV	78.71	50.37	28.34	54	-25.66
11 (highest)	PK	104.95	44.83	60.12	74	-13.88
	AV	79.40	47.37	32.03	54	-21.97

Remark: 1.  $C = A - B$


2.  $E = C - D$

## 8. Power Line Conducted Emission test §FCC 15.207

### 8.1 Operating environment

Temperature: 26  
Relative Humidity: 53 %  
Atmospheric Pressure 1023 hPa

### 8.2 Test setup & procedure



The EUT are connected to the main power through a line impedance stabilization network (LISN). This provides a 50 ohm/50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination.

Both sides (Line and Neutral) of AC line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4/2003 on conducted measurement. The bandwidth of the field strength meter (R & S Test Receiver ESCS 30) is set at 9kHz.

The EUT configuration please refer to the “Conducted set-up photo.pdf”.



### 8.3 Emission limit

Freq. (MHz)	Conducted Limit (dBuV)	
	Q.P.	Ave.
0.15~0.50	66 – 56*	56 – 46*
0.50~5.00	56	46
5.00~30.0	60	50

\*Decreases with the logarithm of the frequency.

### 8.4 Uncertainty of Conducted Emission

Expanded uncertainty (k=2) of conducted emission measurement is 2.6 dB.


## 8.5 Power Line Conducted Emission test data

Phase: Line  
 Model No.: G-210H  
 Test Condition: Normal operating mode

Frequency (MHz)	Corr. Factor (dB)	Level Qp (dBuV)	Limit Qp (dBuV)	Level AV (dBuV)	Limit Av (dBuV)	Margin (dB)	
						Qp	Av
0.179	0.10	52.54	64.51	33.16	54.51	-11.97	-21.35
0.258	0.10	41.28	61.50	32.76	51.50	-20.22	-18.74
0.387	0.10	40.46	58.12	30.47	48.12	-17.66	-17.65
0.496	0.10	34.80	56.07	25.95	46.07	-21.27	-20.12
0.645	0.10	35.80	56.00	20.33	46.00	-20.20	-25.67
1.191	0.10	35.93	56.00	23.06	46.00	-20.07	-22.94

Remark:

1. Corr. Factor (dB)= LISN Factor (dB) + Cable Loss (dB)
2. Margin (dB) = Level (dBuV) – Limit (dBuV)



Phase: Neutral  
 Model No.: G-210H  
 Test Condition: Normal operating mode

Frequency (MHz)	Corr. Factor (dB)	Level	Limit	Level	Limit	Margin	
		Qp (dBuV)	Qp (dBuV)	Av (dBuV)	Av (dBuV)	Qp	Av
0.173	0.10	43.65	64.81	19.53	54.81	-21.16	-35.28
0.260	0.10	40.42	61.43	32.49	51.43	-21.01	-18.94
0.372	0.10	37.04	58.46	29.79	48.46	-21.42	-18.67
0.660	0.10	37.72	56.00	27.03	46.00	-18.28	-18.97
1.191	0.10	37.26	56.00	24.01	46.00	-18.74	-21.99
4.364	0.20	35.83	56.00	20.67	46.00	-20.17	-25.33

Remark:

1. Corr. Factor (dB)= LISN Factor (dB) + Cable Loss (dB)
2. Margin (dB) = Level (dBuV) – Limit (dBuV)

