

EMC TEST REPORT

Report No. : EME-050687
Model No. : ZyAIR G-220F, G-220F
Issued Date : Aug. 1,2005

Applicant : ZyXEL Communiations Corporation
No. 6, Innovation Rd. II, Science-Based Industrial Park,
Hsin-Chu, Taiwan

Test By : Intertek Testing Services Taiwan Ltd.
No. 11, Lane 275, Ko-Nan 1 Street, Chia-Tung Li,
Shiang-Shan District, Hsinchu City, Taiwan


This test report consists of 47 pages in total. It may be duplicated completely for legal use with the allowance of the applicant. It shall not be reproduced except in full, without the written approval of Intertek Laboratory. The test result(s) in this report only applies to the tested sample(s).

Project Engineer



Kevin Chen

Reviewed By



Jerry Liu

Table of Contents

Summary of Tests 4

1. General information 5

 1.1 Identification of the EUT 5

 1.2 Additional information about the EUT 5

 1.3 Antenna description 6

 1.4 Peripherals equipment 6

2. Test specifications 7

 2.1 Test standard 7

 2.2 Operation mode 7

 2.3 Test equipment 8

3. Minimum 6dB Bandwidth test 9

 3.1 Operating environment 9

 3.2 Test setup & procedure 9

 3.3 Measured data of Minimum 6dB Bandwidth test results 9

4. Maximum Output Power test 16

 4.1 Operating environment 16

 4.2 Test setup & procedure 16

 4.3 Measured data of Maximum Output Power test results 16

5. Radiated Emission test 17

 5.1 Operating environment 17

 5.2 Test setup & procedure 17

 5.3 Emission limits 18

 5.4 Radiated spurious emission test data 19

 5.4.1 Measurement results: frequencies equal to or less than 1 GHz 19

 5.4.2 Measurement results: frequency above 1GHz 21

6. Power Spectrum Density test 27

 6.1 Operating environment 27

 6.2 Test setup & procedure 27

 6.3 Measured data of Power Spectrum Density test results 27

7. Emission on the band edge 34

 7.1 Operating environment 34

 7.2 Test setup & procedure 34

 7.3 Test Result 35

8. Power Line Conducted Emission test §FCC 15.20744

 8.1 Operating environment.....44

 8.2 Test setup & procedure.....44

 8.3 Emission limit45

 8.4 Uncertainty of Conducted Emission45

 8.5 Power Line Conducted Emission test data.....46

Summary of Tests**802.11g Wireless USB 2.0 Adapter-Model: ZyAIR G-220F
FCC ID: I88G-220F**

Test	Reference	Results
Minimum 6dB Bandwidth test	15.247(a)(2)	Complies
Maximum Output Power test	15.247(b)	Complies
Radiated Spurious Emission test	15.205, 15.209	Complies
Power Spectrum Density test	15.247(e)	Complies
Emission on the Band Edge test	15.247(d)	Complies
AC Power Line Conducted Emission test	15.207	Complies

1. General information

1.1 Identification of the EUT

Applicant	: ZyXEL Communications Corporation
Product	: 802.11g Wireless USB 2.0 Adapter
Model No.	: ZyAIR G-220F
FCC ID.	: I88G-220F
Frequency Range	: 2412MHz ~ 2462MHz
Channel Number	: 11 channels
Frequency of Each Channel	: 2412MHz, 2417MHz, 2422MHz, 2427MHz, 2432MHz, 2437MHz, 2442MHz, 2447MHz, 2452MHz, 2457MHz, 2462MHz
Type of Modulation	: DSSS, OFDM
Rated Power	: 5Vdc
Power Cord	: N/A
Sample Received	: July 1, 2005
Test Date(s)	: July 12, 2005 ~ July 27, 2005

A FCC DoC report has been generated for the client.

1.2 Additional information about the EUT

The ZyAIR G-220F is an IEEE 802.11g compliant wireless LAN adapter.

The following lists the main features of your ZyAIR G-220F. See the product specifications in the appendix for detailed features.

- Automatic rate selection.
- Security: WEP (Wired Equivalent Privacy), IEEE 802.1x, WPA-PSK, WPA(Wi-Fi Protected Access), WPA2-PSK and WPA2.
- Proprietary SoftAP feature turns your ZyAIR G-220F into an access point (AP).
- A built-in antenna.
- Plug-and-play installation for Windows ME, Windows 2000 and Windows XP.
- Driver and utility support for Windows 98 Second Edition, Windows ME, Windows 2000 and Windows XP.

The model G-220F is identical to model ZyAIR G-220F (EUT), the different model number for different brand serves as marketing strategy.

For more detail features, please refer to User's manual as file name "Installation guide.pdf"

1.3 Antenna description

The EUT uses a permanently connected antenna.

Antenna Gain : 0dBi max
Antenna Type : Ceramic Antenna
Connector Type : Female

1.4 Peripherals equipment

Peripherals	Manufacturer	Product No.	Serial No.	FCC ID
Notebook PC	DELL	PP02X	8Y210A04	FCC DoC Approved
AP	SMC	SMC	C-G 3030232-1-1-3*1000	FCC DoC Approved
Printer	HP	C2642A	TH86K1N2ZB	FCC DoC Approved
Modem	Dynalink	V1456VQE	00V230A00051494	FCC DoC Approved

2. Test specifications

2.1 Test standard

The EUT was performed according to the procedures in FCC Part 15 Subpart C Section § 15.205 、 §15.207 、 §15.209 、 §15.247 and ANSI C63.4/2003.

The test of radiated measurements according to FCC Part15 Section 15.33(a) had been conducted and the field strength of this frequency band were all meet limit requirement, thus we evaluate the EUT pass the specified test.

2.2 Operation mode

The EUT was supplied with 5Vdc from Notebook PC and it was running in operating mode.

Plug the EUT into Notebook PC via USB interface, then turn on the Notebook PC power and run the test program “ZD1211EVL.exe” under windows OS, which provide by manufacturer.

During conducted emission test, the EUT works in normal mode communication with AP. While in other test, it worked in the status of continuously transmitting.

After verifying the maximum output power, the maximum output power was occurred at 11Mbps data rate in 802.11b and at 24Mbps data rate in 802.11g. The final test was executed under this condition and recorded in this report individually.

2.3 Test equipment

Equipment	Brand	Frequency range	Model No.	Intertek ID No.	Next Cal. Date
EMI Test Receiver	Rohde & Schwarz	9kHz~2.75GHz	ESCS 30	EC303	04/17/2006
EMI Test Receiver	Rohde & Schwarz	20Hz~26.5GHz	ESMI	EC317	07/13/2006
Spectrum Analyzer	Rohde & Schwarz	9kHz~30GHz	FSP 30	EC353	07/12/2006
Spectrum Analyzer	Rohde & Schwarz	20Hz~40GHz	FSEK 30	EC365	10/18/2005
Horn Antenna	SCHWARZBECK	1GHz~18GHz	BBHA 9120 D	EC371	12/22/2007
Horn Antenna	SCHWARZBECK	14GHz~40GHz	BBHA 9170	EC351	07/08/2007
Bilog Antenna	SCHWARZBECK	25MHz~2GHz	VULB 9168	EC347	12/23/2007
Pre-Amplifier	MITEQ	100MHz~26.5GHz	919981	EC373	12/30/2005
Pre-Amplifier	MITEQ	26GHz~40GHz	828825	EC374	01/28/2006
Wideband Peak Power Meter/ Sensor	Anritsu	100MHz~18GHz	ML2497A/ MA2491A	EC396	10/18/2005
Controller	HDGmbH	N/A	CM 100	EP346	N/A
Antenna Tower	HDGmbH	N/A	MA 240	EP347	N/A
LISN	Rohde & Schwarz	9KHz~30MHz	ESH3-Z5	EC344	01/13/2006

Note: 1. The above equipments are within the valid calibration period.

2. The test antennas (receiving antenna) are calibration per 3 years.

3. Minimum 6dB Bandwidth test

3.1 Operating environment

Temperature: 25 °C
 Relative Humidity: 55 %
 Atmospheric Pressure: 1023 hPa

3.2 Test setup & procedure

The minimum 6dB bandwidth per FCC §15.247(a)(2) was measured using a 50 ohm spectrum analyzer with the resolutions bandwidth set at 100kHz, the video bandwidth set at 300kHz, and the SPAN>>RBW. The test was performed at 3 channels (lowest, middle and highest channel). The minimum 6-dB modulation bandwidth is in the following Table.

3.3 Measured data of Minimum 6dB Bandwidth test results

Test Mode: 802.11b (DSSS Modulation) operating mode


Channel	Frequency (MHz)	Bandwidth (MHz)	Limit
1 (lowest)	2412	9.62	> 500kHz
6 (middle)	2437	9.22	> 500kHz
11 (highest)	2462	10.34	> 500kHz

Test Mode: 802.11g (OFDM Modulation) operating mode

Channel	Frequency (MHz)	Bandwidth (MHz)	Limit
1 (lowest)	2412	16.59	> 500kHz
6 (middle)	2437	16.59	> 500kHz
11 (highest)	2462	16.55	> 500kHz


Please see the plot below.

Test Mode: 802.11b(DSSS Modulation) operating mode




Comment A: 6dB BW 11b_ch1
EC365

Date: 12.JUL.2005 18:01:04




Comment A: 6dB BW 11b_ch6
EC365
Date: 12.JUL.2005 18:03:27




Comment A: 6dB BW 11b_ch11
EC365

Date: 12.JUL.2005 18:05:16

Test Mode: 802.11g(OFDM Modulation) operating mode




Comment A: 6dB BW 11g_ch1
EC365
Date: 12.JUL.2005 18:48:19



Comment A: 6dB BW 11g_ch6
EC365

Date: 12.JUL.2005 18:44:57



Comment A: 6dB BW 11g_ch11
EC365
Date: 12.JUL.2005 18:42:35

4. Maximum Output Power test

4.1 Operating environment

Temperature: 21 °C
 Relative Humidity: 55 %
 Atmospheric Pressure: 1023 hPa

4.2 Test setup & procedure

The power output per FCC §15.247(b) was measured on the EUT using a 50 ohm SMA cable connected to peak power meter via power sensor. Power was read directly and cable loss correction (2 dB) was added to the reading to obtain power at the EUT antenna terminals. The test was performed at 3 channels (lowest, middle and highest channel).

4.3 Measured data of Maximum Output Power test results

Test Mode: 802.11b (DSSS Modulation) operating mode

Channel	Freq. (MHz)	C.L. (dB)	Reading (dBm)	Conducted Peak Output Power		Limit (dBm)
				(dBm)	(mW)	
1 (lowest)	2412	2.00	18.12	20.12	102.80	30
6 (middle)	2437	2.00	18.15	20.15	103.51	30
11 (highest)	2462	2.00	17.65	19.65	92.26	30

Test Mode: 802.11g (OFDM Modulation) operating mode

Channel	Freq. (MHz)	C.L. (dB)	Reading (dBm)	Conducted Peak Output Power		Limit (dBm)
				(dBm)	(mW)	
1 (lowest)	2412	2.00	20.69	22.69	185.78	30
6 (middle)	2437	2.00	20.70	22.70	186.21	30
11 (highest)	2462	2.00	20.65	22.65	184.08	30

Remark:

Conducted Peak Output Power = Reading + C.L.


5. Radiated Emission test

5.1 Operating environment

Temperature: 23 °C
Relative Humidity: 53 %
Atmospheric Pressure: 1023 hPa

5.2 Test setup & procedure

The Diagram below shows the test setup, which is utilized to make these measurements.



Radiated emissions were investigated cover the frequency range from 30MHz to 1000MHz using a receiver RBW of 120kHz record QP reading, and the frequency over 1GHz using a spectrum analyzer RBW of 1MHz and 10Hz VBW record Average reading. (15.209 paragraph), the Peak reading (1MHz RBW/VBW) recorded also on the report.

The EUT for testing is arranged on a wooden turntable. If some peripherals apply to the EUT, the peripherals will be connected to EUT and the whole system. During the test, all cables were arranged to produce worst-case emissions. The signal is maximized through rotation. The height of antenna and polarization is changing constantly for exploring for maximum signal level. The height of antenna can be up to 4 meters and down to 1 meter.

The measurement for radiated emission will be done at the distance of three meters unless the signal level is too low to measure at that distance. In the case of the reading under noise floor, a pre-amplifier is used and/or the test is conducted at a closer distance. And then all readings are extrapolated back to the equivalent 3meter reading using inverse scaling with distance.

The EUT configuration please refer to the “Spurious set-up photo.pdf”.

5.3 Emission limits

The spurious Emission shall test through the 10th harmonic. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

Frequency (MHz)	Limits (dB μ V/m@3m)
30-88	40
88-216	43.5
216-960	46
Above 960	54

Remark:

1. In the above table, the tighter limit applies at the band edges.
2. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system

Uncertainty was calculated in accordance with NAMAS NIS 81.

Expanded uncertainty (k=2) of radiated emission measurement is 4.98 dB.

5.4 Radiated spurious emission test data

The radiated spurious emissions at

Frequency(MHz)	Margin
664.380	-4.61
4824.000	-4.46
4874.000	-3.78
4924.000	-3.53
4924.000	-4.34

are less than uncertainty. This is within the stated measurement uncertainty, this may affect compliance determined in other test arrangements.

5.4.1 Measurement results: frequencies equal to or less than 1 GHz

The test was performed on EUT under 802.11b continuously transmitting mode. Channel 1, 6, 11 were verified. The worst case occurred at 802.11b Tx channel 1.

EUT : ZyAIR G-220F
 Worst Case : Tx at channel 1

Antenna Polariz. (V/H)	Freq. (MHz)	Receiver Detector	Corr. Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV)	Limit @ 3 m (dBuV)	Margin (dB)	Antenna high (cm)	Turn Table angle (degree)
V	274.440	QP	13.44	16.84	30.28	46.00	-15.72	100.00	322.00
V	439.340	QP	17.42	14.87	32.29	46.00	-13.71	100.00	302.00
V	480.080	QP	18.21	13.40	31.61	46.00	-14.39	100.00	210.00
V	526.640	QP	19.07	16.03	35.10	46.00	-10.90	100.00	110.00
V	575.140	QP	20.14	16.42	36.56	46.00	-9.44	100.00	53.00
V	672.140	QP	21.85	13.73	35.58	46.00	-10.42	100.00	172.00
H	278.320	QP	13.74	21.27	35.01	46.00	-10.99	374.00	198.00
H	319.060	QP	14.76	19.31	34.07	46.00	-11.93	291.00	101.00
H	359.800	QP	15.74	18.91	34.65	46.00	-11.35	218.00	244.00
H	439.340	QP	17.87	20.40	38.27	46.00	-7.73	199.00	127.00
H	575.140	QP	20.30	17.60	37.90	46.00	-8.10	143.00	344.00
H	718.700	QP	22.66	15.48	38.14	46.00	-7.86	142.00	104.00

Remark:

1. Corr. Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Corr. Factor

The test was performed on EUT under 802.11g continuously transmitting mode. Channel 1, 6, 11 were verified. The worst case occurred at 802.11g Tx channel 1.

EUT : ZyAIR G-220F
 Worst Case : Tx at channel 1

Antenna Polariz. (V/H)	Freq. (MHz)	Receiver Detector	Corr. Factor (dB/m)	Reading (dBUV)	Corrected Level (dBUV)	Limit @ 3 m (dBUV)	Margin (dB)	Antenna high (cm)	Turn Table angle (degree)
V	167.740	QP	15.12	16.10	31.22	43.50	-12.28	100.00	24.00
V	439.340	QP	17.42	14.88	32.30	46.00	-13.70	100.00	99.00
V	526.640	QP	19.07	17.96	37.03	46.00	-8.97	100.00	112.00
V	575.140	QP	20.14	17.15	37.29	46.00	-8.71	100.00	178.00
V	664.380	QP	21.73	19.66	41.39	46.00	-4.61	100.00	15.00
V	767.200	QP	22.98	13.04	36.02	46.00	-9.98	232.00	68.00
H	237.580	QP	12.21	21.69	33.90	46.00	-12.10	400.00	167.00
H	359.800	QP	15.74	18.57	34.31	46.00	-11.69	218.00	15.00
H	439.340	QP	17.87	19.67	37.54	46.00	-8.46	199.00	35.00
H	575.140	QP	20.30	16.94	37.24	46.00	-8.76	143.00	262.00
H	718.700	QP	22.66	15.60	38.26	46.00	-7.74	142.00	103.00
H	838.980	QP	24.01	13.29	37.30	46.00	-8.70	107.00	173.00

Remark:

1. Corr. Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Corr. Factor

5.4.2 Measurement results: frequency above 1GHz

EUT : ZyAIR G-220F

Test Condition : 802.11b Tx at channel 1

Frequency (MHz)	Spectrum Analyzer Detector	Antenna Polariz. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV)	Limit @ 3 m (dBuV)	Margin (dB)	Ant. high (cm)	Turn Table angle (degree)
2412.000	PK	V	0.00	30.31	82.39	112.70	-	-	-	-
2412.000	AV	V	0.00	30.31	74.93	105.24	-	-	-	-
*4824.000	PK	V	36.07	37.77	47.84	49.54	54.00	-4.46	112.00	96.00
9648.000	PK	V	34.28	48.31	55.90	69.93	92.70	-22.77	125.01	258.32
9648.000	AV	V	34.28	48.31	51.31	65.34	85.24	-19.90	125.01	258.32
2412.000	PK	H	0.00	30.31	87.25	117.56	-	-	-	-
2412.000	AV	H	0.00	30.31	79.22	108.53	-	-	-	-
*4824.000	PK	H	36.07	37.77	43.80	45.50	54.00	-8.50	126.00	211.00
9648.000	PK	H	34.28	48.31	52.86	66.89	97.56	-30.67	197.32	143.31
9648.000	AV	H	34.28	48.31	47.80	61.83	88.53	-26.70	197.32	143.31

Remark:

1. Correction Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Correction Factor – Preamp. Gain
3. “*” means the emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209.
4. The frequency measured ranges from 1GHz to 25GHz. The data value listed above which is higher than the noise floor, the others please refer to noise floor level.

Noise floor level is :

For PK:

- 1GHz-3GHz: 20dBuV
- 3GHz-14GHz: 27dBuV
- 14GHz-26.5GHz: 39dBuV

For AV:

- 1GHz-3GHz: 10dBuV
- 3GHz-14GHz: 16dBuV
- 14GHz-26.5GHz: 28dBuV

EUT : ZyAIR G-220F
 Test Condition : 802.11b Tx at channel 6

Frequency (MHz)	Spectrum Analyzer Detector	Antenna Polariz. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV)	Limit @ 3 m (dBuV)	Margin (dB)	Ant. high (cm)	Turn Table angle (degree)
2437.000	PK	V	0.00	30.31	81.07	111.38	-	-	-	-
2437.000	AV	V	0.00	30.31	73.41	103.72	-	-	-	-
*4874.000	PK	V	36.07	37.77	48.52	50.22	54.00	-3.78	145.00	71.00
9748.100	PK	V	34.28	48.31	57.36	71.39	91.38	-19.99	149.48	43.41
9748.100	AV	V	34.28	48.31	51.14	65.17	83.72	-18.55	149.48	43.41
2437.000	PK	H	0.00	30.31	86.71	117.02	-	-	-	-
2437.000	AV	H	0.00	30.31	78.60	108.91	-	-	-	-
*4874.000	PK	H	36.07	37.77	46.56	48.26	54.00	-5.74	117.00	69.00
9748.100	PK	H	34.28	48.31	53.36	67.39	97.02	-29.63	180.99	284.49
9748.100	AV	H	34.28	48.31	48.67	62.70	88.91	-26.21	180.99	284.49

Remark:

1. Correction Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Correction Factor – Preamp. Gain
3. “*” means the emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209.
4. The frequency measured ranges from 1GHz to 25GHz. The data value listed above which is higher than the noise floor, the others please refer to noise floor level.

Noise floor level is:

For PK:

- 1GHz-3GHz: 20dBuV
- 3GHz-14GHz: 27dBuV
- 14GHz-26.5GHz: 39dBuV

For AV:

- 1GHz-3GHz: 10dBuV
- 3GHz-14GHz: 16dBuV
- 14GHz-26.5GHz: 28dBuV

EUT : ZyAIR G-220F
 Test Condition : 802.11b Tx at channel 11

Frequency (MHz)	Spectrum Analyzer Detector	Antenna Polariz. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV)	Limit @ 3 m (dBuV)	Margin (dB)	Ant. high (cm)	Turn Table angle (degree)
2462.000	PK	V	0.00	30.31	81.20	111.51	-	-	-	-
2462.000	AV	V	0.00	30.31	73.21	103.52	-	-	-	-
*4924.000	PK	V	36.07	37.77	48.77	50.47	54.00	-3.53	101.52	189.00
9848.000	PK	V	34.28	48.31	53.14	67.17	91.51	-24.34	100.31	219.96
9848.000	AV	V	34.28	48.31	48.47	62.50	83.52	-21.02	100.31	219.96
2462.000	PK	H	0.00	30.31	85.99	116.30	-	-	-	-
2462.000	AV	H	0.00	30.31	78.03	108.34	-	-	-	-
*4924.000	PK	H	36.07	37.77	47.29	48.99	54.00	-5.01	134.00	53.00
9848.000	PK	H	34.28	48.31	50.86	64.89	96.30	-31.41	175.92	163.39
9848.000	AV	H	34.28	48.31	45.55	59.58	88.34	-28.76	175.92	163.39

Remark:

1. Correction Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Correction Factor – Preamp. Gain
3. “*” means the emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209.
4. The frequency measured ranges from 1GHz to 25GHz. The data value listed above which is higher than the noise floor, the others please refer to noise floor level.

Noise floor level is:

For PK:

- 1GHz-3GHz: 20dBuV
- 3GHz-14GHz: 27dBuV
- 14GHz-26.5GHz: 39dBuV

For AV:

- 1GHz-3GHz: 10dBuV
- 3GHz-14GHz: 16dBuV
- 14GHz-26.5GHz: 28dBuV

EUT : ZyAIR G-220F
 Test Condition : 802.11g Tx at channel 1

Frequency (MHz)	Spectrum Analyzer Detector	Antenna Polariz. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV)	Limit @ 3 m (dBuV)	Margin (dB)	Ant. high (cm)	Turn Table angle (degree)
2412.000	PK	V	0.00	30.31	75.11	105.42	-	-	-	-
2412.000	AV	V	0.00	30.31	64.37	94.68	-	-	-	-
*4824.000	PK	V	36.07	37.77	47.11	48.81	54.00	-5.19	121.24	45.12
9651.700	PK	V	34.28	48.31	53.33	67.36	85.42	-18.06	147.52	7.63
9651.700	AV	V	34.28	48.31	38.09	52.12	74.68	-22.56	147.52	7.63
2412.000	PK	H	0.00	30.31	81.19	111.50	-	-	-	-
2412.000	AV	H	0.00	30.31	70.31	100.62	-	-	-	-
*4824.000	PK	H	36.07	37.77	43.80	45.50	54.00	-8.50	110.12	78.13
9651.700	PK	H	34.28	48.31	54.89	68.92	91.50	-22.58	108.15	23.89
9651.700	AV	H	34.28	48.31	40.08	54.11	80.62	-26.51	108.15	23.89

Remark:

1. Correction Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Correction Factor – Preamp. Gain
3. “*” means the emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209.
4. The frequency measured ranges from 1GHz to 25GHz. The data value listed above which is higher than the noise floor, the others please refer to noise floor level.

Noise floor level is :

For PK:

- 1GHz-3GHz: 20dBuV
- 3GHz-14GHz: 27dBuV
- 14GHz-26.5GHz: 39dBuV

For AV:

- 1GHz-3GHz: 10dBuV
- 3GHz-14GHz: 16dBuV
- 14GHz-26.5GHz: 28dBuV

EUT : ZyAIR G-220F
 Test Condition : 802.11g Tx at channel 6

Frequency (MHz)	Spectrum Analyzer Detector	Antenna Polariz. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV)	Limit @ 3 m (dBuV)	Margin (dB)	Ant. high (cm)	Turn Table angle (degree)
2437.000	PK	V	0.00	30.31	75.94	106.25	-	-	-	-
2437.000	AV	V	0.00	30.31	65.01	95.32	-	-	-	-
*4874.000	PK	V	36.07	37.77	47.28	48.98	54.00	-5.02	114.00	68.00
9748.700	PK	V	34.28	48.31	50.43	64.46	86.25	-21.79	191.38	186.28
9748.700	AV	V	34.28	48.31	35.94	49.97	75.32	-25.35	191.38	186.28
2437.000	PK	H	0.00	30.31	81.08	111.39	-	-	-	-
2437.000	AV	H	0.00	30.31	70.01	100.32	-	-	-	-
*4874.000	PK	H	36.07	37.77	46.48	48.18	54.00	-5.82	133.45	89.00
9748.700	PK	H	34.28	48.31	56.44	70.47	91.39	-20.92	132.27	299.97
9748.700	AV	H	34.28	48.31	42.72	56.75	80.32	-23.57	132.27	299.97

Remark:

1. Correction Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Correction Factor – Preamp. Gain
3. “*” means the emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209.
4. The frequency measured ranges from 1GHz to 25GHz. The data value listed above which is higher than the noise floor, the others please refer to noise floor level.

Noise floor level is:

For PK:

- 1GHz-3GHz: 20dBuV
- 3GHz-14GHz: 27dBuV
- 14GHz-26.5GHz: 39dBuV

For AV:

- 1GHz-3GHz: 10dBuV
- 3GHz-14GHz: 16dBuV
- 14GHz-26.5GHz: 28dBuV

EUT : ZyAIR G-220F
Test Condition : 802.11g Tx at channel 11

Frequency (MHz)	Spectrum Analyzer Detector	Antenna Polariz. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV)	Limit @ 3 m (dBuV)	Margin (dB)	Ant. high (cm)	Turn Table angle (degree)
2462.000	PK	V	0.00	30.31	75.54	105.85	-	-	-	-
2462.000	AV	V	0.00	30.31	64.52	94.83	-	-	-	-
*4924.000	PK	V	36.07	37.77	47.96	49.66	54.00	-4.34	100.00	61.00
9848.500	PK	V	34.28	48.31	45.51	59.54	85.85	-26.31	137.04	1.38
9848.500	AV	V	34.28	48.31	32.41	46.44	74.83	-28.39	137.04	1.38
2462.000	PK	H	0.00	30.31	80.80	111.11	-	-	-	-
2462.000	AV	H	0.00	30.31	69.86	100.17	-	-	-	-
*4924.000	PK	H	36.07	37.77	44.16	45.86	54.00	-8.14	105.00	78.00
9848.500	PK	H	34.28	48.31	54.92	68.95	91.11	-22.16	119.20	199.48
9848.500	AV	H	34.28	48.31	40.33	54.36	80.17	-25.81	119.20	199.48

Remark:

1. Correction Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Correction Factor – Preamp. Gain
3. “*” means the emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209.
4. The frequency measured ranges from 1GHz to 25GHz. The data value listed above which is higher than the noise floor, the others please refer to noise floor level.

Noise floor level is:

For PK:

1GHz-3GHz: 20dBuV
3GHz-14GHz: 27dBuV
14GHz-26.5GHz: 39dBuV

For AV:

1GHz-3GHz: 10dBuV
3GHz-14GHz: 16dBuV
14GHz-26.5GHz: 28dBuV

6. Power Spectrum Density test

6.1 Operating environment

Temperature: 25 °C
 Relative Humidity: 56 %
 Atmospheric Pressure 1023 hPa

6.2 Test setup & procedure

The power spectrum density per FCC §15.247(e) was measured from the antenna port of the EUT using a 50ohm spectrum analyzer with the resolution bandwidth set at 3kHz, the video bandwidth set at 10kHz, a span of 1.5 MHz, and the sweep time set at 500 seconds. Power Density was read directly correction was added to the reading to obtain power at the EUT antenna terminals. The test was performed at 3 channels (lowest, middle and highest channel). The Power Spectral Density measured result is in the following table.

6.3 Measured data of Power Spectrum Density test results

Test Mode: 802.11b (DSSS Modulation) operating mode


Channel	Frequency (MHz)	Measured level (dBm)	Calculated level (dBm)	Limit (dBm)
1 (lowest)	2412	-8.36	-8.36	8
6 (middle)	2437	-8.17	-8.17	8
11 (highest)	2462	-9.13	-9.13	8

Test Mode: 802.11g (OFDM Modulation) operating mode


Channel	Frequency (MHz)	Measured level (dBm)	Calculated level (dBm)	Limit (dBm)
1 (lowest)	2412	-13.75	-13.75	8
6 (middle)	2437	-13.75	-13.75	8
11 (highest)	2462	-13.82	-13.82	8

Please see the plot below.

Test Mode: 802.11b (DSSS Modulation) operating mode




Comment A: Power Density 11b_ch1
EC365
Date: 12.JUL.2005 19:03:46



Comment A: Power Density 11b_ch6
EC365


Date: 12.JUL.2005 19:02:19




Comment A: Power Density 11b_ch11
EC365

Date: 12.JUL.2005 19:00:51

Test Mode: 802.11g (OFDM Modulation) operating mode




Comment A: Power Density 11g_ch1
EC365
Date: 12.JUL.2005 18:54:16



Comment A: Power Density 11g_ch6
EC365

Date: 12.JUL.2005 18:56:41



Comment A: Power Density 11g_ch11
EC365

Date: 12.JUL.2005 18:58:46

7. Emission on the band edge

In any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 KHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

7.1 Operating environment

Temperature:	23	°C
Relative Humidity:	53	%
Atmospheric Pressure	1023	hPa

7.2 Test setup & procedure

The output of EUT was connected to spectrum analyzer via a 50ohm cable.

The setting of spectrum analyzer is:

Peak: RBW = VBW = 100KHz
Average : RBW= 1MHz, VBW = 10Hz

Please see the test plot below.

7.3 Test Result

Test Mode: 802.11b (DSSS Modulation) operating mode

Channel	Detector	Radiated Method	Conducted Method	The Max. Field Strength in Restrict Band (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)
		Max. Field Strength of Fundamental @3m (dBuV/m)	Between Carrier Max. Power and Local Max. Emission in Restrict Band (dBc)			
		A	B			
1 (lowest)	PK	117.56	49.17	68.39	74.00	-5.61
	AV	108.53	54.75	53.78	54.00	-0.22
11 (highest)	PK	116.30	47.90	68.40	74.00	-5.60
	AV	108.34	55.11	53.23	54.00	-0.77


Remark: 1. $C = A - B$
 2. $E = C - D$

Test Mode: 802.11g (OFDM Modulation) operating mode


Channel	Detector	Radiated Method	Conducted Method	The Max. Field Strength in Restrict Band (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)
		Max. Field Strength of Fundamental @3m (dBuV/m)	Between Carrier Max. Power and Local Max. Emission in Restrict Band (dBc)			
		A	B			
1 (lowest)	PK	111.50	40.42	71.08	74.00	-2.92
	AV	100.62	46.84	53.78	54.00	-0.22
11 (highest)	PK	111.11	40.69	70.42	74.00	-3.58
	AV	100.17	46.77	53.40	54.00	-0.60

Remark: 1. $C = A - B$
 2. $E = C - D$


Test Mode: 802.11b (DSSS Modulation) operating mode




Comment A: Band-Edge 11b_ch1
 PK F1=2390MHz, F2=2400MHz (EC365)
 Date: 12.JUL.2005 19:46:00



Comment A: Band-Edge 11b_ch1
 AV F1=2390MHz, F2=2400MHz (EC365)
 Date: 12.JUL.2005 19:50:47




Comment A: Band-Edge 11b_ch11
 PK F1=2483.5MHz (EC365)
 Date: 12.JUL.2005 19:53:43




Comment A: Band-Edge 11b_ch11
AV F1=2483.5MHz (EC365)
Date: 12.JUL.2005 19:56:52

Test Mode: 802.11g (OFDM Modulation) operating mode



Comment A: Band-Edge 11g_ch1
PK F1=2390MHz, F2=2400MHz (EC365)
Date: 12.JUL.2005 20:20:47




Comment A: Band-Edge 11g_ch1
 AV F1=2390MHz, F2=2400MHz (EC365)
 Date: 12.JUL.2005 20:23:41

Intertek ETL SEMKO


FCC ID. : I88G-220F

Report No.: EME-050687

Page 42 of 47



Comment A: Band-Edge 11g_ch11
 PK F1=2483.5MHz (EC365)
 Date: 12.JUL.2005 20:13:28




Comment A: Band-Edge 11g_ch11
 AV F1=2483.5MHz (EC365)
 Date: 12.JUL.2005 20:15:45

8. Power Line Conducted Emission test §FCC 15.207

8.1 Operating environment

Temperature: 23 °C
Relative Humidity: 60 %
Atmospheric Pressure 1010 hPa

8.2 Test setup & procedure



The EUT are connected to the main power through a line impedance stabilization network (LISN). This provides a 50 ohm/50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination.

Both sides (Line and Neutral) of AC line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4/2003 on conducted measurement. The bandwidth of the field strength meter (R & S Test Receiver ESCS 30) is set at 9kHz.

The EUT configuration please refer to the “Conducted set-up photo.pdf”.

8.3 Emission limit

Freq. (MHz)	Conducted Limit (dBuV)	
	Q.P.	Ave.
0.15~0.50	66 – 56*	56 – 46*
0.50~5.00	56	46
5.00~30.0	60	50

*Decreases with the logarithm of the frequency.

8.4 Uncertainty of Conducted Emission

Expanded uncertainty (k=2) of conducted emission measurement is 2.6 dB.

8.5 Power Line Conducted Emission test data


The test was performed the 802.11b and 802.11g normal operating modes, the worst case was occurred at 802.11g normal operating mode.

Phase : Line
 EUT : ZyAIR G-220F
 Test Condition : 802.11g normal operating mode

Frequency (MHz)	Corr. Factor (dB)	Level Qp (dBuV)	Limit Qp (dBuV)	Level AV (dBuV)	Limit Av (dBuV)	Margin (dB)	
						Qp	Av
0.150	0.10	50.73	66.00	28.89	56.00	-15.27	-27.11
0.191	0.10	42.46	64.01	24.65	54.01	-21.55	-29.36
1.704	0.10	34.65	56.00	22.21	46.00	-21.35	-23.79
2.080	0.10	36.90	56.00	32.32	46.00	-19.10	-13.68
2.363	0.12	34.49	56.00	24.66	46.00	-21.51	-21.34
2.663	0.13	34.80	56.00	22.61	46.00	-21.20	-23.39
4.505	0.22	36.81	56.00	29.75	46.00	-19.19	-16.25

Remark:

1. Correction Factor (dB)= LISN Factor (dB) + Cable Loss (dB)
2. Margin (dB) = Level (dBuV) – Limit (dBuV)



Phase : Neutral
 EUT : ZyAIR G-220F
 Test Condition : 802.11g normal operating mode

Frequency (MHz)	Corr. Factor (dB)	Level Qp (dBuV)	Limit Qp (dBuV)	Level AV (dBuV)	Limit Av (dBuV)	Margin (dB)	
						Qp	Av
0.150	0.10	53.43	66.00	33.85	56.00	-12.57	-22.15
2.080	0.10	38.60	56.00	36.35	46.00	-17.40	-9.65
2.663	0.13	39.11	56.00	24.19	46.00	-16.89	-21.81
2.954	0.15	30.96	56.00	30.23	46.00	-25.04	-15.77
4.690	0.20	37.05	56.00	26.42	46.00	-18.95	-19.58
10.401	0.22	37.91	60.00	31.72	50.00	-22.09	-18.28

Remark:

1. Correction Factor (dB) = LISN Factor (dB) + Cable Loss (dB)
2. Margin (dB) = Level (dBuV) – Limit (dBuV)

