

EMC TEST REPORT

Report No. : EME-061433

Model No. : NBG-334SH


Issued Date : Jan. 12, 2007

Applicant : ZyXEL Communications Corporation
6, Innovation Rd. II, Science-Based Industrial Park,
Hsin-Chu, Taiwan

Test By : Intertek Testing Services Taiwan Ltd.
No. 11, Lane 275, Ko-Nan 1 Street, Chia-Tung Li,
Shiang-Shan District, Hsinchu City, Taiwan


This test report consists of 64 pages in total. It may be duplicated completely for legal use with the allowance of the applicant. It shall not be reproduced except in full, without the written approval of Intertek Laboratory. The test result(s) in this report only applies to the tested sample(s).

Project Engineer



Kevin Chen

Reviewed By



Jerry Liu

Table of Contents

Summary of Tests4

1. General information5

 1.1 Identification of the EUT5

 1.2 Additional information about the EUT.....5

 1.3 Antenna description.....6

 1.4 Peripherals equipment6

2. Test specifications7

 2.1 Test standard.....7

 2.2 Operation mode7

 2.3 Test equipment8

3. Minimum 6dB Bandwidth test9

 3.1 Operating environment.....9

 3.2 Test setup & procedure.....9

 3.3 Measured data of Minimum 6dB Bandwidth test results9

4. Maximum Output Power test16

 4.1 Operating environment.....16

 4.2 Test setup & procedure.....16

 4.3 Measured data of Maximum Output Power test results16

5. RF Antenna Conducted Spurious test.....17

 5.1 Operating environment.....17

 5.2 Test setup & procedure.....17

 5.3 Measured data of the highest RF Antenna Conducted Spurious test result17

6. Radiated Emission test36

 6.1 Operating environment.....36

 6.2 Test setup & procedure.....36

 6.3 Emission limits.....37

 6.4 Radiated spurious emission test data.....38

 6.4.1 Measurement results: frequencies equal to or less than 1 GHz.....38

 6.4.2 Measurement results: frequency above 1GHz39

7. Power Spectrum Density test45

 7.1 Operating environment.....45

 7.2 Test setup & procedure.....45

7.3 Measured data of Power Spectrum Density test results45

8. Emission on the band edge52

 8.1 Operating environment.....52

 8.2 Test setup & procedure52

9. Power Line Conducted Emission test §FCC 15.20761

 9.1 Operating environment.....61

 9.2 Test setup & procedure61

 9.3 Emission limit62

 9.4 Uncertainty of Conducted Emission62

 9.5 Power Line Conducted Emission test data63

Summary of Tests**802.11g Wireless Firewall Router -Model: NBG-334SH
FCC ID: I88NBG334SH**

Test	Reference	Results
Minimum 6dB Bandwidth test	15.247(a)(2)	Pass
Maximum Output Power test	15.247(b)	Pass
RF Antenna Conducted Spurious test	15.247(d)	Pass
Radiated Spurious Emission test	15.205, 15.209	Pass
Power Spectrum Density test	15.247(e)	Pass
Emission on the Band Edge test	15.247(d)	Pass
AC Power Line Conducted Emission test	15.207	Pass

1. General information

1.1 Identification of the EUT

Applicant	: 802.11g Wireless Firewall Router
Product	: NBG-334SH
Model No.	: NBG-334SH
FCC ID.	: I88NBG334SH
Frequency Range	: 2412MHz ~ 2462MHz
Channel Number	: 11 channels
Frequency of Each Channel	: 2412MHz, 2417MHz, 2422MHz, 2427MHz, 2432MHz, 2437MHz, 2442MHz, 2447MHz, 2452MHz, 2457MHz, 2462MHz
Type of Modulation	: DSSS, OFDM
Rated Power	: 120Vac, 60Hz with adapter (Model No.: AA-121A)
Power Cord	: N/A
Sample Received	: Dec. 18, 2006
Test Date(s)	: Dec. 25, 2006 ~ Jan. 10, 2007

A FCC DoC report has been generated for the client.

1.2 Additional information about the EUT

The EUT is an 802.11g Wireless Firewall Router, and was defined as information technology equipment.

For more detail features, please refer to User's manual as file name "Installation guide.pdf"

1.3 Antenna description

The antenna is affixed to the EUT using a unique connector, which allows for replacement of a broken antenna, but DOES NOT use a standard antenna jack or electrical connector.

Antenna Gain : 5dBi max

Antenna Type : Dipole antenna

Connector Type : SMA Reverse

1.4 Peripherals equipment

Peripherals	Manufacturer	Product No.	Serial No.	FCC ID
Notebook PC	DELL	Latitude D610	6YWZK1S	FCC DoC Approved
Notebook PC	DELL	Latitude D610	4YWZK1S	FCC DoC Approved
Notebook PC	DELL	Latitude D610	FXWZK1S	FCC DoC Approved
Notebook PC	DELL	Latitude D610	3YWZK1S	FCC DoC Approved
Notebook PC	DELL	Latitude D610	1YWZK1S	FCC DoC Approved

2. Test specifications

2.1 Test standard

The EUT was performed according to the procedures in FCC Part 15 Subpart C Section § 15.205, §15.207, §15.209, §15.247 and ANSI C63.4/2003.

The test of radiated measurements according to FCC Part15 Section 15.33(a) had been conducted and the field strength of this frequency band were all meet limit requirement, thus we evaluate the EUT pass the specified test.

2.2 Operation mode

The EUT was transmitted continuously during the test.

All of adapters (Model No.: AA-121A, MU12-2120100-A1) had been verified, of which the worst condition was operated by AA-121A, therefore the final test was executed under worst condition than recorded the data in this report.

With individual verifying, the maximum output power was found at 1Mbps data rate for 802.11b mode and 6Mbps data rate for 802.11g mode. The final tests were executed under these conditions and recorded in this report individually.

2.3 Test equipment

Equipment	Brand	Frequency range	Model No.	Intertek ID No.	Next Cal. Date
EMI Test Receiver	Rohde & Schwarz	9kHz~2.75GHz	ESCS 30	EC303	04/16/2007
Spectrum Analyzer	Rohde & Schwarz	9kHz~30GHz	FSP 30	EC353	07/23/2007
Spectrum Analyzer	Rohde & Schwarz	20Hz~40GHz	FSEK 30	EC365	10/31/2007
Horn Antenna	SCHWARZBECK	1GHz~18GHz	BBHA 9120 D	EC371	12/22/2007
Horn Antenna	SCHWARZBECK	14GHz~40GHz	BBHA 9170	EC351	07/08/2007
Bilog Antenna	SCHWARZBECK	25MHz~2GHz	VULB 9168	EC347	12/23/2007
Pre-Amplifier	MITEQ	100MHz~26.5GHz	919981	EC373	02/11/2007
Wideband Peak Power Meter/ Sensor	Anritsu	100MHz~18GHz	ML2497A/ MA2491A	EC396	11/09/2007
Controller	HDGmbH	N/A	CM 100	EP346	N/A
Antenna Tower	HDGmbH	N/A	MA 240	EP347	N/A
LISN	Rohde & Schwarz	9KHz~30MHz	ESH3-Z5	EC344	01/13/2007

Note: 1. The above equipments are within the valid calibration period.

3. Minimum 6dB Bandwidth test

3.1 Operating environment

Temperature: 23
 Relative Humidity: 55 %
 Atmospheric Pressure: 1023 hPa

3.2 Test setup & procedure

The minimum 6dB bandwidth per FCC §15.247(a)(2) was measured using a 50 ohm spectrum analyzer with the resolutions bandwidth set at 100kHz, the video bandwidth set at 100kHz, and the SPAN>>RBW. The test was performed at 3 channels (lowest, middle and highest channel). The minimum 6-dB modulation bandwidth is in the following Table.

3.3 Measured data of Minimum 6dB Bandwidth test results

Test Mode: 802.11b(DSSS Modulation) operating mode


Channel	Frequency (MHz)	Bandwidth (MHz)	Limit
1 (lowest)	2412	13.12	> 500kHz
6 (middle)	2437	12.64	> 500kHz
11 (highest)	2462	12.64	> 500kHz

Test Mode: 802.11g(OFDM Modulation) operating mode

Channel	Frequency (MHz)	Bandwidth (MHz)	Limit
1 (lowest)	2412	16.56	> 500kHz
6 (middle)	2437	16.56	> 500kHz
11 (highest)	2462	16.56	> 500kHz

Please see the plot below.


Test Mode: 802.11b(DSSS Modulation) operating mode



Title: 6dB Band-Width
 Comment A: CH 1 at 802.11b mode
 Date: 11.JAN.2007 11:19:28

Test Mode: 802.11b(DSSS Modulation) operating mode


	Delta 2 [T1]	RBW 100 kHz	RF Att 10 dB
Ref Lvl	-0.67 dB	VBW 100 kHz	
21 dBm	12.64000000 MHz	SWT 10 ms	Unit dBm



Title: 6dB Band-Width
 Comment A: CH 6 at 802.11b mode
 Date: 11.JAN.2007 11:24:47


Test Mode: 802.11b(DSSS Modulation) operating mode

	Delta 2 [T1]	RBW 100 kHz	RF Att 10 dB
Ref Lvl	-1.51 dB	VBW 100 kHz	
21 dBm	12.64000000 MHz	SWT 10 ms	Unit dBm




Title: 6dB Band-Width
 Comment A: CH 11 at 802.11b mode
 Date: 11.JAN.2007 11:28:03

Test Mode: 802.11g(OFDM Modulation) operating mode



Title: 6dB Band-Width
 Comment A: CH 1 at 802.11g mode
 Date: 11.JAN.2007 11:33:10


Test Mode: 802.11g(OFDM Modulation) operating mode



Title: 6dB Band-Width
 Comment A: CH 6 at 802.11g mode
 Date: 11.JAN.2007 11:37:50

Test Mode: 802.11g(OFDM Modulation) operating mode

	Delta 2 [T1]	RBW	100 kHz	RF Att	0 dB
	Ref Lvl			VBW	100 kHz
	11 dBm			SWT	10 ms
				Unit	dBm



Title: 6dB Band-Width
 Comment A: CH 11 at 802.11g mode
 Date: 11.JAN.2007 11:41:07

4. Maximum Output Power test

4.1 Operating environment

Temperature: 23
 Relative Humidity: 55 %
 Atmospheric Pressure: 1023 hPa

4.2 Test setup & procedure

The power output per FCC §15.247(b) was measured on the EUT using a 50 ohm SMA cable connected to peak power meter via power sensor. Power was read directly and cable loss correction (1 dB) was added to the reading to obtain power at the EUT antenna terminals. The test was performed at 3 channels (lowest, middle and highest channel).

4.3 Measured data of Maximum Output Power test results

Test Mode: 802.11b(DSSS Modulation) operating mode

Channel	Freq. (MHz)	C.L. (dB)	Reading (dBm)	Conducted Peak Output Power		Limit (W)
				(dBm)	(mW)	
1 (lowest)	2412	1	20	21	125.89	1
6 (middle)	2437	1	20	21	125.89	1
11 (highest)	2462	1	19	20	100.00	1

Test Mode: 802.11g(OFDM Modulation) operating mode

Channel	Freq. (MHz)	C.L. (dB)	Reading (dBm)	Conducted Peak Output Power		Limit (W)
				(dBm)	(mW)	
1 (lowest)	2412	1	20.5	21.5	141.25	1
6 (middle)	2437	1	21	22	158.49	1
11 (highest)	2462	1	21	22	158.49	1

Remark:

Conducted Peak Output Power = Reading + C.L.

5. RF Antenna Conducted Spurious test

5.1 Operating environment

Temperature: 23
Relative Humidity: 55 %

5.2 Test setup & procedure


The measurements were performed from 30MHz to 25GHz RF antenna conducted per FCC 15.247 (d) was measured from the EUT antenna port using a 50ohm spectrum analyzer with the resolution bandwidth set at 100 kHz, and the video bandwidth set at 100 kHz.

Harmonics and spurious noise must be at least 20dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW. The table below is the results from the highest emission for each channel within the authorized band. This table was used to determine the spurious limits for each channel.

5.3 Measured data of the highest RF Antenna Conducted Spurious test result


The test results please see the plot below.

Test Mode: 802.11b mode (CH1)




Title: Conductive-Spurious
 Comment A: CH 1 at 802.11b mode 30MHz~2400MHz
 Date: 11.JAN.2007 11:22:34

Test Mode: 802.11b mode (CH1)




Title: Conductive-Spurious
 Comment A: CH 1 at 802.11b mode 2400MHz~2483.5MHz
 Date: 11.JAN.2007 11:22:12

Test Mode: 802.11b mode (CH1)




Title: Conductive-Spurious
Comment A: CH 1 at 802.11b mode 2483.5MHz~25GHz
Date: 11.JAN.2007 11:23:01

Test Mode: 802.11b mode (CH6)




Title: Conductive-Spurious
 Comment A: CH 6 at 802.11b mode 30MHz~2400MHz
 Date: 11.JAN.2007 11:25:55

Test Mode: 802.11b mode (CH6)




Title: Conductive-Spurious
 Comment A: CH 6 at 802.11b mode 2400MHz~2483.5MHz
 Date: 11.JAN.2007 11:25:34

Test Mode: 802.11b mode (CH6)




Title: Conductive-Spurious
 Comment A: CH 6 at 802.11b mode 2483.5MHz~25GHz
 Date: 11.JAN.2007 11:26:23

Test Mode: 802.11b mode (CH11)




Title: Conductive-Spurious
 Comment A: CH 11 at 802.11b mode 30MHz~2400MHz
 Date: 11.JAN.2007 11:30:31

Test Mode: 802.11b mode (CH11)




Title: Conductive-Spurious
 Comment A: CH 11 at 802.11b mode 2400MHz~2483.5MHz
 Date: 11.JAN.2007 11:30:10

Test Mode: 802.11b mode (CH11)




Title: Conductive-Spurious
 Comment A: CH 11 at 802.11b mode 2483.5MHz~25GHz
 Date: 11.JAN.2007 11:30:59

Test Mode: 802.11g mode (CH1)




Title: Conductive-Spurious
 Comment A: CH 1 at 802.11g mode 30MHz~2400MHz
 Date: 11.JAN.2007 11:36:05

Test Mode: 802.11g mode (CH1)




Title: Conductive-Spurious
 Comment A: CH 11 at 802.11g mode 2400MHz~2483.5MHz
 Date: 11.JAN.2007 11:43:06

Test Mode: 802.11g mode (CH1)




Title: Conductive-Spurious
 Comment A: CH 1 at 802.11g mode 2483.5MHz~25000MHz
 Date: 11.JAN.2007 11:36:32

Test Mode: 802.11g mode (CH6)




Title: Conductive-Spurious
 Comment A: CH 6 at 802.11g mode 30MHz~2400MHz
 Date: 11.JAN.2007 11:38:53

Test Mode: 802.11g mode (CH6)




Title: Conductive-Spurious
 Comment A: CH 6 at 802.11g mode 2400MHz~2483.5MHz
 Date: 11.JAN.2007 11:38:31

Test Mode: 802.11g mode (CH6)




Title: Conductive-Spurious
 Comment A: CH 6 at 802.11g mode 2483.5MHz~25000MHz
 Date: 11.JAN.2007 11:39:20

Test Mode: 802.11g mode (CH11)




Title: Conductive-Spurious
Comment A: CH 11 at 802.11g mode 30MHz~2400MHz
Date: 11.JAN.2007 11:43:32

Test Mode: 802.11g mode (CH11)



Title: Conductive-Spurious
 Comment A: CH 11 at 802.11g mode 2400MHz~2483.5MHz
 Date: 11.JAN.2007 11:43:06

Test Mode: 802.11g mode (CH11)



Title: Conductive-Spurious
Comment A: CH 11 at 802.11g mode 2483.5MHz~25000MHz
Date: 11.JAN.2007 11:44:00


6. Radiated Emission test

6.1 Operating environment

Temperature: 25
Relative Humidity: 55 %
Atmospheric Pressure: 1023 hPa

6.2 Test setup & procedure

The Diagram below shows the test setup, which is utilized to make these measurements. The frequency spectrum from 30MHz to 1000MHz was investigated by bilog antenna. The frequency spectrum from over 1GHz was investigated by horn antenna.



Radiated emissions were investigated cover the frequency range from 30MHz to 1000MHz using a receiver RBW of 120kHz record QP reading, and the frequency over 1GHz using a spectrum analyzer RBW of 1MHz and 10Hz VBW record Average reading. (15.209 paragraph), the Peak reading (1MHz RBW/VBW) recorded also on the report.

The EUT for testing is arranged on a wooden turntable. If some peripherals apply to the EUT, the peripherals will be connected to EUT and the whole system. During the test, all cables were arranged to produce worst-case emissions. The signal is maximized through rotation. The height of antenna and polarization is changing constantly for exploring for maximum signal level. The height of antenna can be up to 4 meters and down to 1 meter.

The measurement for radiated emission will be done at the distance of three meters unless the signal level is too low to measure at that distance. In the case of the reading under noise floor, a pre-amplifier is used and/or the test is conducted at a closer distance. And then all readings are extrapolated back to the equivalent 3 meter reading using inverse scaling with distance.

The EUT configuration please refer to the “Spurious set-up photo.pdf”.

6.3 Emission limits

The spurious Emission shall test through the 10th harmonic. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

Frequency (MHz)	Limits (dB μ V/m@3m)
30-88	40
88-216	43.5
216-960	46
Above 960	54

Remark:

1. In the above table, the tighter limit applies at the band edges.
2. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system

Uncertainty was calculated in accordance with NAMAS NIS 81.

Expanded uncertainty (k=2) of radiated emission measurement is ± 4.98 dB.

6.4 Radiated spurious emission test data

The radiated spurious emissions at

Frequency(MHz)	Margin
373.380	-1.62

are less than uncertainty. This is within the stated measurement uncertainty, this may affect compliance determined in other test arrangements.

6.4.1 Measurement results: frequencies equal to or less than 1 GHz

The test was performed on EUT under 802.11b and 802.11g continuously transmitting mode. Channel 1, 6, 11 were verified. The worst case occurred at 802.11b Tx channel 1.

EUT : NBG-334SH
 Worst Case : 802.11b Tx at channel 1

Antenna Polariz. (V/H)	Freq. (MHz)	Receiver Detector	Corr. Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)
V	249.220	QP	12.22	21.62	33.97	46.00	-12.03
V	274.440	QP	13.24	21.50	34.94	46.00	-11.06
V	373.380	QP	15.06	25.48	41.20	46.00	-4.80
V	499.480	QP	18.43	17.77	36.32	46.00	-9.68
V	749.740	QP	22.74	12.21	35.02	46.00	-10.98
V	873.900	QP	23.70	12.26	36.26	46.00	-9.74
H	249.220	QP	12.36	26.02	38.64	46.00	-7.36
H	274.440	QP	13.21	29.31	42.80	46.00	-3.20
H	373.380	QP	15.48	28.28	44.38	46.00	-1.62
H	499.480	QP	18.64	14.42	33.18	46.00	-12.82
H	749.740	QP	22.95	14.31	37.33	46.00	-8.67
H	873.900	QP	24.12	10.92	35.26	46.00	-10.74

Remark:

1. Corr. Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Corr. Factor

6.4.2 Measurement results: frequency above 1GHz

EUT : NBG-334SH
 Test Condition : 802.11b Tx at channel 1

Frequency (MHz)	Spectrum Analyzer Detector	Antenna Polariz. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)
3210.00	PK	V	35.54	34.62	50.57	49.65	54	-4.35
4824.00	PK	V	36.07	37.77	49.98	51.68	54	-2.32
4824.00	PK	H	36.07	37.77	45.61	47.31	54	-6.69

Remark:

1. Correction Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Correction Factor – Preamp. Gain
3. The frequency measured ranges from 1GHz to 25GHz. The data value listed above which is higher than the noise floor, the others please refer to noise floor level.

Noise floor level is :

For PK:

- 1GHz-3GHz: 20dBuV
- 3GHz-14GHz: 27dBuV
- 14GHz-26.5GHz: 39dBuV

For AV:

- 1GHz-3GHz: 10dBuV
- 3GHz-14GHz: 16dBuV
- 14GHz-26.5GHz: 28dBuV

EUT : NBG-334SH
 Test Condition : 802.11b Tx at channel 6

Frequency (MHz)	Spectrum Analyzer Detector	Antenna Polariz. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)
3240.00	PK	V	35.54	34.62	46.83	45.91	54	-8.09
4874.00	PK	V	36.07	37.77	51.4	53.1	54	-0.9
3240.00	PK	H	35.54	34.62	41.64	40.72	54	-13.28
4874.00	PK	H	36.07	37.77	44.3	46	54	-8

Remark:

1. Correction Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Correction Factor – Preamp. Gain
3. The frequency measured ranges from 1GHz to 25GHz. The data value listed above which is higher than the noise floor, the others please refer to noise floor level.

Noise floor level is :

For PK:

- 1GHz-3GHz: 20dBuV
- 3GHz-14GHz: 27dBuV
- 14GHz-26.5GHz: 39dBuV

For AV:

- 1GHz-3GHz: 10dBuV
- 3GHz-14GHz: 16dBuV
- 14GHz-26.5GHz: 28dBuV

EUT : NBG-334SH
Test Condition : 802.11b Tx at channel 11

Frequency (MHz)	Spectrum Analyzer Detector	Antenna Polariz. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)
3270.00	PK	V	35.54	34.62	49.58	48.66	54	-5.34
4924.00	PK	V	36.07	37.77	48.82	50.52	54	-3.48
7386.00	PK	V	36.18	43.97	44.79	52.58	54	-1.42
9848.00	PK	V	34.28	48.31	41.26	55.29	74	-18.71
9848.00	AV	V	34.28	48.31	35.19	49.22	54	-4.78
3270.00	PK	H	35.54	34.62	43.29	42.37	54	-11.63
4924.00	PK	H	36.07	37.77	42.77	44.47	54	-9.53

Remark:

1. Correction Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Correction Factor – Preamp. Gain
3. The frequency measured ranges from 1GHz to 25GHz. The data value listed above which is higher than the noise floor, the others please refer to noise floor level.

Noise floor level is :

For PK:

1GHz-3GHz: 20dBuV
3GHz-14GHz: 27dBuV
14GHz-26.5GHz: 39dBuV

For AV:

1GHz-3GHz: 10dBuV
3GHz-14GHz: 16dBuV
14GHz-26.5GHz: 28dBuV

EUT : NBG-334SH
 Test Condition : 802.11g Tx at channel 1

Frequency (MHz)	Spectrum Analyzer Detector	Antenna Polariz. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)
3210.00	PK	V	35.54	34.62	49.45	48.53	54	-5.47
4824.00	PK	V	36.07	37.77	59.59	61.29	74	-12.71
4824.00	AV	V	36.07	37.77	43.63	45.33	54	-8.67
7236.00	PK	V	36.18	43.97	55.58	63.37	74	-10.63
7236.00	AV	V	36.18	43.97	39.88	47.67	54	-6.33
9648.00	PK	V	34.28	48.31	47.44	61.47	74	-12.53
9648.00	AV	V	34.28	48.31	27.8	41.83	54	-12.17
4824.00	PK	H	36.07	37.77	47.28	48.98	54	-5.02

Remark:

1. Correction Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Correction Factor – Preamp. Gain
3. The frequency measured ranges from 1GHz to 25GHz. The data value listed above which is higher than the noise floor, the others please refer to noise floor level.

Noise floor level is :

For PK:

- 1GHz-3GHz: 20dBuV
- 3GHz-14GHz: 27dBuV
- 14GHz-26.5GHz: 39dBuV

For AV:

- 1GHz-3GHz: 10dBuV
- 3GHz-14GHz: 16dBuV
- 14GHz-26.5GHz: 28dBuV

EUT : NBG-334SH
 Test Condition : 802.11g Tx at channel 6

Frequency (MHz)	Spectrum Analyzer Detector	Antenna Polariz. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)
3240.00	PK	V	35.54	34.62	48.31	47.39	54	-6.61
4874.00	PK	V	36.07	37.77	57.61	59.31	74	-14.69
4874.00	AV	V	36.07	37.77	42.24	43.94	54	-10.06
7311.00	PK	V	36.18	43.97	54.77	62.56	74	-11.44
7311.00	AV	V	36.18	43.97	40.51	48.3	54	-5.7
9748.00	PK	V	34.28	48.31	47.69	61.72	74	-12.28
9748.00	AV	V	34.28	48.31	29.97	44	54	-10
3240.00	PK	H	35.54	34.62	42.04	41.12	54	-12.88
4874.00	PK	H	36.07	37.77	45.86	47.56	54	-6.44
7311.00	PK	H	36.18	43.97	40.67	48.46	54	-5.54
9748.00	PK	H	34.28	48.31	37.53	51.56	54	-2.44

Remark:

1. Correction Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Correction Factor – Preamp. Gain
3. The frequency measured ranges from 1GHz to 25GHz. The data value listed above which is higher than the noise floor, the others please refer to noise floor level.

Noise floor level is :

For PK:

- 1GHz-3GHz: 20dBuV
- 3GHz-14GHz: 27dBuV
- 14GHz-26.5GHz: 39dBuV

For AV:

- 1GHz-3GHz: 10dBuV
- 3GHz-14GHz: 16dBuV
- 14GHz-26.5GHz: 28dBuV

EUT : NBG-334SH
Test Condition : 802.11g Tx at channel 11

Frequency (MHz)	Spectrum Analyzer Detector	Antenna Polariz. (H/V)	Preamp. Gain (dB)	Correction Factor (dB/m)	Reading (dBuV)	Corrected Level (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)
3270.00	PK	V	35.54	34.62	50.66	49.74	54	-4.26
4874.00	PK	V	36.07	37.77	51.5	53.2	54	-0.8
7386.00	PK	V	36.18	43.97	56.45	64.24	74	-9.76
7386.00	AV	V	36.18	43.97	40.87	48.66	54	-5.34
9848.00	PK	V	34.28	48.31	56.1	70.13	74	-3.87
9848.00	AV	V	34.28	48.31	37.28	51.31	54	-2.69
3270.00	PK	H	35.54	34.62	42.35	41.43	54	-12.57
4924.00	PK	H	36.07	37.77	46.62	48.32	54	-5.68
9848.00	PK	H	34.28	48.31	39.08	53.11	54	-0.89

Remark:

1. Correction Factor = Antenna Factor + Cable Loss
2. Corrected Level = Reading + Correction Factor – Preamp. Gain
3. The frequency measured ranges from 1GHz to 25GHz. The data value listed above which is higher than the noise floor, the others please refer to noise floor level.

Noise floor level is :

For PK:

1GHz-3GHz: 20dBuV
3GHz-14GHz: 27dBuV
14GHz-26.5GHz: 39dBuV

For AV:

1GHz-3GHz: 10dBuV
3GHz-14GHz: 16dBuV
14GHz-26.5GHz: 28dBuV

7. Power Spectrum Density test

7.1 Operating environment

Temperature: 23
 Relative Humidity: 55 %
 Atmospheric Pressure 1023 hPa

7.2 Test setup & procedure

The power spectrum density per FCC §15.247(e) was measured from the antenna port of the EUT using a 50ohm spectrum analyzer with the resolution bandwidth set at 3kHz, the video bandwidth set at 10kHz, a span of 1.5MHz, and the sweep time set at 500 seconds. Power Density was read directly correction was added to the reading to obtain power at the EUT antenna terminals. The test was performed at 3 channels (lowest, middle and highest channel). The Power Spectral Density measured result is in the following table.

7.3 Measured data of Power Spectrum Density test results

Test Mode: 802.11b(DSSS Modulation) operating mode

Channel	Frequency (MHz)	Power spectrum density (dBm)	Limit (dBm)
1 (lowest)	2412	-4.45	8
6 (middle)	2437	-4.52	8
11 (highest)	2462	-4.63	8


Test Mode: 802.11g(OFDM Modulation) operating mode

Channel	Frequency (MHz)	Power spectrum density (dBm)	Limit (dBm)
1 (lowest)	2412	-13.34	8
6 (middle)	2437	-12.25	8
11 (highest)	2462	-12.79	8

Please see the plot below.

Test Mode: 802.11b(DSSS Modulation) operating mode


	Max/Ref Lvl	Marker 1 [T1]	RBW	3 kHz	RF Att	10 dB
	25 dBm	-4.45 dBm	VBW	10 kHz		
	1 dBm	2.41118888 GHz	SWT	500 s	Unit	dBm



Title: Power density
 Comment A: CH 1 at 802.11b mode
 Date: 11.JAN.2007 11:19:45

Test Mode: 802.11b(DSSS Modulation) operating mode


	Max/Ref Lvl	Marker 1 [T1]	RBW	3 kHz	RF Att	10 dB
	25 dBm	-4.52 dBm	VBW	10 kHz		
	1 dBm	2.43497745 GHz	SWT	500 s	Unit	dBm



Title: Power density
 Comment A: CH 6 at 802.11b mode
 Date: 11.JAN.2007 11:25:04

Test Mode: 802.11b(DSSS Modulation) operating mode


	Max/Ref Lvl	Marker 1 [T1]	RBW	3 kHz	RF Att	10 dB
	25 dBm	-4.63 dBm	VBW	10 kHz		
	1 dBm	2.46276904 GHz	SWT	500 s	Unit	dBm



Title: Power density
 Comment A: CH 11 at 802.11b mode
 Date: 11.JAN.2007 11:28:20

Test Mode: 802.11g(OFDM Modulation) operating mode


	Max/Ref Lvl	Marker 1 [T1]	RBW	3 kHz	RF Att	10 dB
	25 dBm	-13.34 dBm	VBW	10 kHz		
	1 dBm	2.41477004 GHz	SWT	500 s	Unit	dBm



Title: Power density
 Comment A: CH 1 at 802.11g mode
 Date: 11.JAN.2007 11:33:26

Test Mode: 802.11g(OFDM Modulation) operating mode


	Max/Ref Lvl	Marker 1 [T1]	RBW	3 kHz	RF Att	10 dB
	25 dBm	-12.25 dBm	VBW	10 kHz		
	1 dBm	2.43260772 GHz	SWT	500 s	Unit	dBm



Title: Power density
 Comment A: CH 6 at 802.11g mode
 Date: 11.JAN.2007 11:38:06

Test Mode: 802.11g(OFDM Modulation) operating mode

	Max/Ref Lvl	Marker 1 [T1]	RBW	3 kHz	RF Att	10 dB
	25 dBm	-12.79 dBm	VBW	10 kHz		
	1 dBm	2.46346242 GHz	SWT	500 s	Unit	dBm



Title: Power density
 Comment A: CH 11 at 802.11g mode
 Date: 11.JAN.2007 11:41:24

8. Emission on the band edge

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 KHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Radiated emissions, which fall in the restricted band, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

8.1 Operating environment

Temperature: 23
 Relative Humidity: 55 %
 Atmospheric Pressure 1023 hPa

8.2 Test setup & procedure

Please refer to the clause 6.2 of this report.

8.3 Measured data of Band-Edge test results

802.11b

Channel	Measurement Freq. (MHz)	Detector	The Max. Field Strength in (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)
1	2310-2390	PK	62.21	74	-11.79
		AV	52.09	54	-1.91
11	2483.5-2500	PK	68.84	74	-5.16
		AV	53.84	54	-0.16

802.11g

Channel	Measurement Freq. (MHz)	Detector	The Max. Field Strength in (dBuV/m)	Limit @ 3 m (dBuV/m)	Margin (dB)
1	2310-2390	PK	62.75	74	-11.25
		AV	49.26	54	-4.74
11	2483.5-2500	PK	67.13	74	-6.87
		AV	51.21	54	-2.79

Test Mode: 802.11b ch 1 PK (2310MHz ~2390MHz)




*RBW 1 MHz Marker 1 [T1]
*VBW 1 MHz 62.21 dBμV
SWT 2.5 ms 2.387440000 GHz

Ref 97 dBμV

*Att 0 dB

1 PK
MAXH



Start 2.31 GHz

8 MHz/

Stop 2.39 GHz

Comment: 11b ch1 PK

Date: 11.JAN.2007 21:13:45

Test Mode: 802.11b ch 1 AV (2310MHz ~2390MHz)




*RBW 1 MHz Marker 1 [T1]
*VBW 10 Hz 52.09 dBμV
SWT 20 s 2.386320000 GHz

Ref 97 dBμV

*Att 0 dB

1 PK
MAXH



Start 2.31 GHz

8 MHz/

Stop 2.39 GHz


Comment: 11b ch1 AV

Date: 11.JAN.2007 21:11:55

Test Mode: 802.11b ch11 PK (2483.5MHz ~2500MHz)



Ref 97 dB μ V *Att 0 dB *RBW 1 MHz Marker 1 [T1]
*VBW 1 MHz 68.84 dB μ V
SWT 2.5 ms 2.487823000 GHz



Comment: 11b ch11 pk

Date: 11.JAN.2007 21:59:21

Test Mode: 802.11b ch11 AV (2483.5MHz ~2500MHz)




*RBW 1 MHz Marker 1 [T1]
*VBW 10 Hz 53.84 dBµV
SWT 4.2 s 2.487790000 GHz

Ref 97 dBµV

*Att 0 dB

1 PK
MAXH

2 PK *
CLRWR




Comment: 11b ch11 av
Date: 11.JAN.2007 22:04:39

Test Mode: 802.11g ch1 PK (2310MHz ~2390MHz)



Ref 97 dB μ V *Att 0 dB *RBW 1 MHz Marker 1 [T1]
*VBW 1 MHz 62.75 dB μ V
SWT 2.5 ms 2.390000000 GHz

1 PK
MAXH



Start 2.31 GHz 8 MHz/ Stop 2.39 GHz

Comment: 11g ch1 PK
Date: 11.JAN.2007 21:26:56

Test Mode: 802.11g ch1 AV (2310MHz ~2390MHz)




* RBW 1 MHz Marker 1 [T1]
* VBW 10 Hz 49.26 dBμV
SWT 20 s 2.390000000 GHz

Ref 97 dBμV

* Att 0 dB

1 PK
MAXH



Start 2.31 GHz

8 MHz/

Stop 2.39 GHz

Comment: 11g ch1 AV

Date: 11.JAN.2007 21:26:03

Test Mode: 802.11g ch 11 PK (2483.5MHz ~2500MHz)




*RBW 1 MHz Marker 1 [T1]
*VBW 1 MHz 67.13 dBμV
SWT 2.5 ms 2.484127000 GHz

Ref 97 dBμV

*Att 0 dB


1 PK
MAXH



Comment: 11g ch11 pk

Date: 11.JAN.2007 21:47:17

Test Mode: 802.11g ch 11 AV (2483.5MHz ~2500MHz)




Comment: 11g ch11 av
Date: 11.JAN.2007 21:46:14

9. Power Line Conducted Emission test §FCC 15.207

9.1 Operating environment

Temperature: 22
Relative Humidity: 55 %
Atmospheric Pressure 1023 hPa

9.2 Test setup & procedure



The EUT are connected to the main power through a line impedance stabilization network (LISN). This provides a 50 ohm/50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination.

Both sides (Line and Neutral) of AC line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4/2003 on conducted measurement. The bandwidth of the field strength meter (R & S Test Receiver ESCS 30) is set at 9kHz.

The EUT configuration please refer to the “Conducted set-up photo.pdf”.

9.3 Emission limit

Freq. (MHz)	Conducted Limit (dBuV)	
	Q.P.	Ave.
0.15~0.50	66 – 56*	56 – 46*
0.50~5.00	56	46
5.00~30.0	60	50

*Decreases with the logarithm of the frequency.

9.4 Uncertainty of Conducted Emission

Expanded uncertainty (k=2) of conducted emission measurement is ± 2.26 dB.

9.5 Power Line Conducted Emission test data


The test was performed the 802.11b and 802.11g normal operating modes, the worst case was occurred at 802.11b normal operating mode.

Phase: Line
 Model No.: NBG-334SH
 Worst case: 802.11b normal operating mode

Frequency (MHz)	Corr. Factor (dB)	Level Qp (dBuV)	Limit Qp (dBuV)	Level AV (dBuV)	Limit Av (dBuV)	Margin (dB)	
						Qp	Av
0.150	0.10	45.07	66.00	16.44	56.00	-20.93	-39.56
0.305	0.10	23.39	60.11	6.13	50.11	-36.72	-43.98
0.352	0.10	30.29	58.92	22.94	48.92	-28.63	-25.98
0.518	0.10	39.38	56.00	37.79	46.00	-16.62	-8.21
12.006	0.63	29.27	60.00	23.92	50.00	-30.73	-26.08
13.970	0.75	30.44	60.00	26.66	50.00	-29.56	-23.34

Remark:

1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)
2. Margin (dB) = Level (dBuV) – Limit (dBuV)



Phase: Neutral
 Model No.: NBG-334SH
 Test Condition: Normal operation mode

Frequency (MHz)	Corr. Factor (dB)	Level Qp (dBuV)	Limit Qp (dBuV)	Level AV (dBuV)	Limit Av (dBuV)	Margin (dB)	
						Qp	Av
0.150	0.10	45.87	66.00	17.17	56.00	-20.13	-38.83
0.302	0.10	27.49	60.18	7.14	50.18	-32.69	-43.04
0.450	0.10	24.13	56.87	21.05	46.87	-32.74	-25.82
0.524	0.10	38.04	56.00	32.71	46.00	-17.96	-13.29
11.910	0.38	29.87	60.00	27.71	50.00	-30.13	-22.29
17.882	0.65	23.25	60.00	14.75	50.00	-36.75	-35.25

Remark:

1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)
2. Margin (dB) = Level (dBuV) - Limit (dBuV)

