

Maximum Permissible Exposure (MPE) Evaluation Report

Report No. : TS10080164-EME

Model No. : NBG4615

Issued Date : Dec. 15, 2010

Applicant: ZyXEL Communications Corporation
6, Innovation Rd II, Science-Based Industrial Park,
Hsin-Chu, Taiwan

Test Method/ Standard: FCC 1.1310

Test By: Intertek Testing Services Taiwan Ltd.
No. 11, Lane 275, Ko-Nan 1 Street, Chia-Tung Li,
Shiang-Shan District, Hsinchu City, Taiwan

It may be duplicated completely for legal use with the allowance of the applicant. It shall not be reproduced except in full, without the written approval of Intertek Laboratory. The test result(s) in this report only applies to the tested sample(s).

The test report was prepared by: Sign on File
Julie Wang / Assistant

These measurements were taken by: Sign on File
Leon Cheng/ Engineer

The test report was reviewed by:

Name Rex Liao
Title Engineer



Table of Contents

Summary of Tests	3
1. Introduction	4
2. RF Exposure Limit	4
3. RF Exposure calculations	5
4. Description of EUT	5
5. Test results	7
6. Set-up Photo	8



Summary of Tests

MPE Evaluation meet FCC OET No. 65: 1997, IEEE C95.1-2005

Wireless N Gigabit NetUSB Router -Model: NBG4615
FCC ID: I88NBG4615

Test	Reference	Results
MPE Evaluation	FCC Guidelines for Human Exposure IEEE C95.1	Complies

1. Introduction

The EUT operates in the 2.4 GHz ISM band. Due to the EUT (include antenna) at its normal operation distance is at least 20 cm from the human body, the EUT was defined as a Mobile Device.

The reason to do the MPE Evaluation is to avoid the RF hazard to human body. The maximum output power and gain of the antenna were used to calculate the limited Power density (S) at 20 cm distance away from the product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 and Safety Code 6 are followed.

According to 1.1307 (b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

2. RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b).

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A) Limits for Occupational / Control Exposures				
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6
(B) Limits for General Population / Uncontrolled Exposure				
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

F= Frequency in MHz

3. RF Exposure calculations

From §FCC 1.1310 table 1, the maximum permissible RF exposure for an uncontrolled environment is 1 mW/(cm²) (or 10 W/m²)*

Power density (S) is calculated by the following formula:

$$S = (P * G) / 4\pi R^2$$

where, S = Power density (mW/cm²)

P = Output power to antenna (mW)

R = Distance between radiating structure and observation point (cm)

G = Gain of antenna in numeric

$\pi = 3.1416$

Example:

Assume a mobile device operates at 2412MHz and its maximum output power is 50mW, and the maximum gain of antenna is 1 (numeric) /0dBi.

then the power density (S) = $(50 * 1) / 4 * \pi * 20^2 = 0.00995$ (mW/cm²) (or = 0.0995 W/m²)

4. Description of EUT

The EUT is a Wireless N Gigabit NetUSB Router, and was defined as information technology equipment.

There are two types of antenna for the device, one is 2 dBi dipole antenna, and another is 5 Dbi dipole antenna.

4.1 Peripherals equipment

Peripherals	Brand	Model No.	Serial No.	Description of Data Cable	FCC ID
3G USB Dongle	Huawei	E169	N/A	N/A	QISE169

4.2 Antenna description

Antenna 0

The antenna is affixed to the EUT using a unique connector, which allows for replacement of a broken antenna, but DOES NOT use a standard antenna jack or electrical connector.

	Antenna type 1	Antenna type 2
Antenna Gain	: 2 dBi max	: 5 dBi max
Antenna Type	: Diople antenna	: Diople antenna
Connector Type	: SMA Reverse	: SMA Reverse

Antenna 1


The antenna is affixed to the EUT using a unique connector, which allows for replacement of a broken antenna, but DOES NOT use a standard antenna jack or electrical connector.

	Antenna type 1	Antenna type 2
Antenna Gain	: 2 dBi max	: 5 dBi max
Antenna Type	: Diople antenna	: Diople antenna
Connector Type	: SMA Reverse	: SMA Reverse

All the antennas were verified, the worst case was antenna gain 5 dBi.

5. Test results

Antenna No.		Total	1	2	3
Tx Status			On	On	On
Frequency	MHz		850	2450	2450
MPE Limit	mW/cm ²		0.57	1.00	1.00
Max % MPE	%	99.0	77.8	13.5	13.8
Power	(W)	2.195	1.760	0.215	0.219
Antenna Gain	dBi		1.00	5.00	5.00
EIRP	(W)	3.59	2.216	0.681	0.693
X	(cm)		-14.0	-6.0	6.0
Y	(cm)		2.0	8.0	8.0
Sector			FALSE	FALSE	FALSE
Arc			FALSE	FALSE	FALSE
q ₁	degs	input	180	180	180
q ₂			179	179	179
q ₁		actual	180	180	180
q ₂			179	179	179



The Notice in Installation Manual has been stated as below:

While installing and operating this transmitter, the radio frequency exposure limit of 1 mW/ (cm²) may be exceeded at distances close to the transmitter. therefore, the user must maintain a minimum distance of 20 cm from the device at all time.

6. Set-up Photo

