



RADIO FREQUENCY EXPOSURE

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

EUT Specification

EUT	802.11n VDSL2 4-port Gateway
Frequency band (Operating)	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz <input type="checkbox"/> Others
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure ($S = 5\text{mW}/\text{cm}^2$) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure ($S=1\text{mW}/\text{cm}^2$)
Antenna diversity	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input checked="" type="checkbox"/> Tx/Rx diversity
Max. output power	IEEE 802.11b mode: 20.35dBm(108.4mW) IEEE 802.11g mode: 19.58dBm(90.8mW) draft 802.11n Standard-20 MHz Channel mode: 19.14 dBm(82.0mW) draft 802.11n Wide-40 MHz Channel mode: 17.53dBm(56.6mW)
Antenna gain (Max)	an external antenna gain 2.0dBi and RF PCB Antenna(S/N:C034-510726-A)gain 1.4 dBi /Total gain 4.72 dBi
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A

Remark:

1. The maximum output power is 20.35dBm (108.4mW) at 2462MHz (with 1.5849numeric antenna gain.);
2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.
3. For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.



TEST RESULTS

No non-compliance noted.

Calculation

$$\text{Given } E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{3770}$$

Where $E = \text{Field strength in Volts / meter}$

$P = \text{Power in Watts}$

$G = \text{Numeric antenna gain}$

$d = \text{Distance in meters}$

$S = \text{Power density in milliwatts / square centimeter}$

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$$P (mW) = P (W) / 1000 \text{ and}$$

$$d (cm) = d(m) / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where $d = \text{Distance in cm}$

$P = \text{Power in mW}$

$G = \text{Numeric antenna gain}$

$S = \text{Power density in mW / cm}^2$

Maximum Permissible Exposure

Substituting the MPE safe distance using $d = 20 \text{ cm}$ into Equation 1:

Yields

$$S = 0.000199 \times P \times G$$

Where $P = \text{Power in mW}$

$G = \text{Numeric antenna gain}$

$S = \text{Power density in mW / cm}^2$



IEEE 802.11b:

EUT output power = 108.4mW

Numeric Antenna gain = 1.5849

\rightarrow Power density = 0.0342 mW / cm²

IEEE 802.11g:

EUT output power = 90.8mW

Numeric Antenna gain = 1.5849

\rightarrow Power density = 0.0286 mW / cm²

draft 802.11gn Standard-20 MHz Channel mode

EUT output power = 82.0mW

Total Numeric Antenna gain = 2.9648

\rightarrow Power density = 0.0484 mW / cm²

draft 802.11gn Wide-40 MHz Channel mode

EUT output power = 56.6mW

Total Numeric Antenna gain = 2.9648

\rightarrow Power density = 0.0334 mW / cm²

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.)