

Exhibit C - Measurement Report



Industrial Technology Research Institute

Electronics Research & Service Organization

Bldg. 17, 195-4 Sec. 4, Chung Hsing Rd., Chutung, Hsinchu, 310
Taiwan, Republic Of China
TEL : 886-3-5917069 FAX : 886-3-5825720

FCC ID : I88PRESTIGE153

Report No. : CEW-8704-008

Page 3 of 16

1. GENERAL INFORMATION

1.1 DESCRIPTION OF EUT

MANUFACTURER : ZyXEL COMMUNICATIONS CORPORATION.

SAMPLE NAME : WAN Bridge/Router

MODEL NUMBER : Prestige 153

SERIAL NO. : -----

POWER SUPPLY : 18VAC(From Power Adapter)



ELECTROMAGNETIC INTERFERENCE TEST REPORT

Company : ZyxEL COMMUNICATIONS CORPORATION.
 Address : NO.6, Innovation Rd. II, Science- Based
 Industrial Park, Hsin-Chu, Taiwan , R.O.C
 Sample Name : WAN Bridge/Router
 Model : Prestige153
 Date Received : APR. 13, 1998
 Date Tested : APR. 22, 1998

MEASUREMENT PORCEDURE USED :

FCC RULES AND REGULATION PART 15 SUBPART B
 CLASS B OCTOBER 1996 AND ANSI C63.4 MAY 1992

WE HEREBY CERTIFY THAT: The measurements shown in the attachment were made in accordance with the procedures indicated, and the energy emitted by the equipment was found to be within the limits applicable. We assume full responsibility for the accuracy and completeness of these measurements and vouch for the qualifications of all persons taking them.

	Name	Signature	Date
Testing Engineer	C.F.Wu/NVLAP	<i>C.F. Wu</i>	MAY 20, 1998
Approving Manager	Paul Y. Liaw/NVLAP	<i>Paul Y. Liaw</i>	May 20, 1998

Notes :

1. This report will be invalid if duplicated or photocopied in part.
2. This report refers only to the specimen(s) submitted to testing, and be invalid as seperately used.
3. This report is invalid with out examination stamp and signature of this institute.
4. The tested specimen(s) will be preserved for thirty days from the date issued.
5. This is a NIST/NVLAP accredited report but not constituted and eudorsed by U.S. government.

15-16	3.7 PHOTOS OF OPEN SITE
14	3.6 RADIATED RF NOISE MEASUREMENT
13	3.5 UNCERTAINTY OF RADIATED EMISSION
13	3.4 TEST PROCEDURE
13	3.3 RADIATION LIMIT
12	3.2 TEST SETUP
12	3.1 TEST EQUIPMENTS
12	3. RADIATED EMISSION TEST
11	2.7 PHOTOS OF CONDUCTION TEST
10	2.6 LINE CONDUCTED RF VOLTAGE MEASUREMENT
9	2.5 UNCERTAINTY OF CONDUCTED EMISSION
9	2.4 TEST PROCEDURE
9	2.3 CONDUCTED POWER LINE EMISSION LIMIT
8	2.2 TEST SETUP
8	2.1 TEST EQUIPMENTS
8	2. CONDUCTED POWERLINE TEST
7	1.5 DESCRIPTION OF TEST SITE
7	1.4 EUT OPERATING CONDITION
6	1.3 EUT & PERIPHERALS SETUP DIAGRAM
4	1.2 DESCRIPTION OF PERIPHERALS
3	1.1 DESCRIPTION OF EUT
3	1. GENERAL INFORMATION

TEST REPORT CERTIFICATION

TABLE OF CONTENTS

TITLE	PAGE NO.
-------	----------





3. RADIATED EMISSION TEST


3.1 TEST EQUIPMENTS

The following test equipments are utilized in making the measurements contained in this report.

MANUFACTURER OR TYPE	MODEL NO	SERIAL NO.	DATE OF CALIBRATION
CHASE BI-LOG ANTENNA	CBL6111A	1546	MAY.26, 1997
R/S TEST RECEIVER	ESMI	842088/005 841978/008	MAY.22, 1997
ANECHOIC/SHIELDED ROOM	KEENE 5981	N/A	N/A

3.2 TEST SETUP

The diagram below shows the test setup which is utilized to make these measurements.



Antenna Elevation Variable



3.3 RADIATION LIMIT

All emanation from a class B computing device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified below :

FREQUENCY (MHz)	FIELD STRENGTHS(dB μ V/M)	
	CLASS A(10m)	CLASS B(3m)
30-88	39.0	40.0
88-216	43.5	43.5
216-960	46.4	46.0
960-1000	49.5	54.0

Note : (1)The tighter limit shall apply at the edge between two frequency bands.

(2)Distance refers to the distance in meters between the measuring instrument antenna and the closest point of any part of the device or system.

3.4 TEST PROCEDURE

The devices under test were placed on a rotatable table top 0.8 meter above ground. The table was rotated 360 degrees to determine the position of the highest radiation. EUT is set 10 meters from the interference receiving antenna which is mounted on the top of a variable height mast. The antenna height is varied between one meter and four meters above ground to find the maximum value of the field strength Both horizontal polarization and vertical polarization of the antenna are set to make the measurement.

The bandwidth setting on the E.M.I. meter (R/S TEST RECEIVER ESMI) is 120 KHz.

The levels are quasi peak value readings. The frequency spectrum from 30MHz to 1000MHz was investigated.

3.5 UNCERTAINTY OF RADIATED EMISSION

The uncertainty of radiated emission is ± 2.72 dB.



3.6 RADIATED RF NOISE MEASUREMENT

The frequency spectrum from 30 MHz to 1000 MHz was investigated. All emissions not reported below are more than 20 dB below the prescribed limits.

All readings are quasi-peak values.

Temperature : 27 °C

Humidity : 71% RH

FREQ- UENCY (MHz)	ANTENNA FACTOR (dB)	CABLE LOSS (dB)	METER READING AT10m (dB μ V/M)		LIMITS (dB μ V/M)	EMISSION LEVEL AT3m (dB μ V/M)	
			HORIZON- TAL	VERTICAL		HORIZON- TAL	VERTICAL
30.00	19.71	1.20	*	*	40.00	*	*
80.00	8.73	1.90	*	16.34	40.00	*	36.97
138.25	11.93	2.39	6.54	8.78	43.50	30.86	33.10
150.00	11.15	2.50	6.54	*	43.50	30.19	*
184.02	9.13	2.72	*	2.90	43.50	*	24.75
184.33	9.13	2.72	7.10	11.02	43.50	28.95	32.87
200.00	8.95	2.80	8.78	12.14	43.50	30.53	33.89
215.05	9.99	2.89	5.42	4.58	46.00	28.30	27.16
225.00	10.69	2.95	4.86	8.22	46.00	28.50	31.86
245.77	12.15	3.08	14.94	11.30	46.00	40.17	36.53
368.66	15.01	3.64	15.78	13.54	46.00	44.43	42.19
400.00	15.79	3.80	9.06	*	46.00	38.65	*
441.68	16.65	3.97	*	4.02	46.00	*	34.64
466.68	17.16	4.07	*	4.3	46.00	*	35.53
491.54	17.68	4.17	*	5.7	46.00	*	37.55
491.68	17.68	4.17	5.42	*	46.00	37.27	*
541.68	18.66	4.33	*	5.14	46.00	*	38.13
575.01	19.30	4.42	3.46	3.18	46.00	37.18	36.90
1000.00	24.69	5.70	*	*	54.00	*	*

REMARKS :

1. * Undetectable
2. Emission level at 3m (dB μ V/M) = Antenna Factor (dB) + Cable loss (dB) + Meter Reading at 10 m (dB μ V/M) + transferred factor 10(dB).
3. 10m measured data are transferred to 3m by the formula
 $L2=L1(d1/d20) \mu$ V/ M from CISPR 22
 $20\text{Log}L2=20\text{Log}L1+20\text{Log} (d1/d2) \text{ dB } \mu$ V/M




(6) Cable

NO.	TYPE	Connector	Shielded	Length
A	D Type	RS232, metal	No	1.5m
B	WAN cable	RJ-45, plastic	No	10m
C	LAN cable	RJ-45, plastic	No	10m



1.3 EUT & PERIPHERALS SETUP DIAGRAM



The indicated numbers (1)(2)(A)(B)---please refer to item 1.2.



1.4 EUT OPERATING CONDITION

1. Turn on EUT's power.
2. EUT will send/receive pockets to/from Terminal via WAN#1 cable.
3. EUT will send/receive pockets to/from Terminal via WAN#2 cable.
4. EUT will send/receive pockets to/from Terminal via WAN#3 cable.
5. EUT will send/receive pockets to/from Terminal via LAN cable.
6. EUT will show statistics message to PC via RS-232 cable.
7. Repeat step 1~6.

1.5 DESCRIPTION OF TEST SITE

SITE DESCRIPTION : FCC certificate NO. :31040/SIT
DNV certificate NO. :510-96-1016
TUV certificate NO. : I9664582-9610
Lloyd's certificate NO. :LA003
BCIQ certificate NO. :SL2-IN-E-02
NVLAP Lab code : 200118-0
CNLA certificate NO. : CNLA-ZL97018
VCCI certificate NO. : R-629, C-650

NAME OF SITE : Electronics Research & Service Organization
Industrial Technology Research Institute

SITE LOCATION : K500, 195-4 , sec. 4, Chung Hsing Rd.,
Chu-Tung Chen. Hsin-Chu, Taiwan 31015 R.O.C.




2. CONDUCTED POWERLINE TEST

2.1 TEST EQUIPMENTS

The following test equipments are used during the conducted powerline tests :

MANUFACTURER OR TYPE	MODEL No	SERIAL NO.	DATE OF CALIBRATION
SPECTRUM ANALYZER & DISPLAY	HP 8568A	2235A02320	MAR. 05, 1998
QUASI-PEAK ADAPTER	HP 85650 A	2341A00672	MAR. 05, 1998
ISOLATION TRANSFORMER	SOLAR 7032-1	N/A	N/A
L.I.S.N.	EMCO 3850/2	9311-1025 9401-1028	MAR. 24, 1998
TEST RECEIVER	R/S ESH3	8720791118	MAR. 13, 1998
SHIELDED ROOM	KEENE 5983	N/A	N/A

2.2 TEST SETUP





2.3 CONDUCTED POWER LINE EMISSION LIMIT

FREQUENCY (MHz)	MAXIMUM RF LINE VOLTAGE (dB μ V)	
	CLASS A	CLASS B
0.45 - 1.705	60	48
1.705 - 30.0	69.5	48

2.4 TEST PROCEDURE

The test procedure is performed in a 12ft \times 12ft \times 8ft(L \times W \times H) shielded room. the EUT along with its peripherals were placed on a 1.0m(W) \times 1.5m(L) and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chasis ground was bounded to the horizontal ground plane of shielded room. All peripherals were connected to the second LISN and the chasis ground also bounded to the horizontal ground plane of shielded room. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.

2.5 UNCERTAINTY OF CONDUCTED EMISSION

The uncertainty of conducted emission is ± 1.36 dB.



2.6 LINE CONDUCTED RF VOLTAGE MEASUREMENT

The frequency spectrum from 0.45 MHz to 30 MHz was investigated. All emissions not reported below are more than 20 dB below the prescribed limits.

All readings are Quasi-peak values.

Temperature : 23 °C

Humidity : 54 % R.H.

FREQUENCY (MHz)	READING(dB μ V)		LIMITS (dB μ V)
	ONE END & GRD'D	THE OTHER END & GRD'D	
	Q.P.	Q.P.	Q.P.
0.450	*	*	48.00
2.174	38.77	37.17	48.00
4.590	*	39.41	48.00
4.740	27.90	*	48.00
4.951	*	40.71	48.00
5.185	27.90	*	48.00
5.295	*	40.32	48.00
5.407	41.32	*	48.00
5.522	*	38.72	48.00
6.107	38.22	37.12	48.00
7.278	36.33	*	48.00
7.409	*	35.13	48.00
8.024	37.94	36.14	48.00
22.833	37.49	*	48.00
23.813	41.59	39.69	48.00
28.646	*	35.60	48.00
30.000	*	*	48.00

REMARKS : * Undetectable