



Test Report

For

Applicant : ZyXEL Communications Corporation
Equipment Type : HDSL-2 DSU (Data Service Unit)
Model : PRESTIGE 760V
FCC ID : I88PRESTIGE760V

Report No.: 007H001FI

Test Report Certification

QuieTek Corporation

No.75-1, Wang-Yeh Valley, Yung-Hsing, Chiung-Lin,
Hsin-Chu County, Taiwan, R.O.C.
Tel : 886-3-592-8858, Fax: 886-3-592-8859
E-Mail : quietek@ms24.hinet.net

Accredited by NIST(NVLAP), VCCI, BSMI, DNV, TUV

Applicant : ZyXEL Communications Corporation
Address : No.6, Innovation Rd II, Science-Based Industrial Park,
Hsin-Chu, Taiwan, R.O.C.
Equipment Type : HDSL-2 DSU (Data Service Unit)
Model : PRESTIGE 760V
FCC ID. : I88PRESTIGE760V
Measurement Standard : CISPR 22/1985
Measurement Procedure : ANSI C63.4 /1992
Operation Voltage : 120VAC/60Hz
Classification : Class B
Test Result : Complied
Test Date : July 13, 2000
Report No. : 007H001FI



The Test Results relate only to the samples tested.
The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.
This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Documented by: Zoe Lee

Test Engineer: Calien Kang

Approved: Kevin Wang



TABLE OF CONTENTS

Description	Page
1. GENERAL INFORMATION	4
1.1 EUT Description.....	4
1.2 Tested System Details.....	5
1.3 EUT Configuration.....	9
1.4 EUT Exercise Software.....	10
1.5 Test performed.....	10
1.6 Test Facility.....	11
2. CONDUCTED EMISSION	12
2.1 Test Equipment List.....	12
2.2 Test Setup	12
2.3 Limits.....	12
2.4 Test Procedure.....	13
2.5 Test Results	13
3. RADIATED EMISSION	14
3.1 Test Equipment	14
3.2 Test Setup	14
3.3 Limits.....	15
3.4 Test Procedure.....	15
3.5 Test Results	15
4. EMI REDUCTION METHOD DURING COMPLIANCE TESTING	16
5. ATTACHMENT.....	17
ATTACHMENT 1: SUMMARY OF TEST RESULTS	
ATTACHMENT 2: EUT TEST PHOTOGRAPHS	
ATTACHMENT 3: EUT DETAILED PHOTOGRAPHS	

1. General Information

1.1 EUT Description

Applicant	: ZyXEL Communications Corporation
Address	: No.6, Innovation Rd II, Science-Based Industrial Park, Hsin-Chu, Taiwan, R.O.C.
Equipment Type	: HDSL-2 DSU (Data Service Unit)
Model	: PRESTIGE 760V
FCC ID	: I88PRESTIGE760V
Operation Voltage	: 120VAC/60Hz
V 3.5 Cable	: Non-Shielded, 1.8m, 1pc
Telephone Line	: Non-Shielded, 1.8m, 1pc
Y Type RS 232 Cable	: Non-Shielded, 1.6m, 1pc
Power Adapter	: ZyXEL, MW48-1601000A Non-Shielded, 1.8m

Remark : 1.This device a HDSL-2 DSU (Data Service Unit).
2. QuieTek had verified the construction and function, then shown in this test report.

1.2 Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

1.2.1 HDSL-2 DSU (Data Service Unit) (EUT)

Model Number : PRESTIGE 760V
Serial Number : N/A
FCC ID : DoC
Manufacturer : ZyXEL
V 3.5 Cable : Non-Shielded, 1.8m, 1pc
Telephone Line : Non-Shielded, 1.8m, 1pc
Y Type RS 232 Cable : Non-Shielded, 1.6m, 1pc
Power Adapter : ZyXEL, MW48-1801000A
Non-Shielded, 1.8m

1.2.2 Host Personal Computer

Model Number : P2L97
Serial Number : 92M4Y00777
FCC ID : DoC
Manufacturer : ASUS
Power Cord : Non-Shielded, 1.8m

1.2.3 Monitor

Model Number : CM752ET-311
Serial Number : T8E004443
FCC ID : DoC
Manufacturer : HITACHI
Data Cable : Shielded, 1.5m
Power Cord : Shielded, 1.8m

1.2.4 Keyboard

Model Number : SK-2502
Serial Number : M971237059
FCC ID : GYUR41SK
Manufacturer : HP

1.2.5 Modem

Model Number : 1414
Serial Number : 980033032
FCC ID : IFAXDM1414
Manufacturer : ACEEX
Data Cable : Shielded, 1.5m
Power Adapter : ACCEX, SCP41-91000A
Cable Output : Shielded, 1.5m

1.2.6 Printer

Model Number : C2642A
Serial Number : MY75J1D1D2
FCC ID : B94C2642X
Manufacturer : HP
Data Cable : Shielded, 1.2m
Power Adapter : NMB, C2175A
Cable for AC IN: Non-Shielded, 0.7m
Cable for AC Out: Non-Shielded, 1.5m

1.2.7 Mouse

Model Number : M-S34
Serial Number : LZB75078428
FCC ID : DZL211029
Manufacturer : HP
Data Cable : Shielded, 1.8m

1.2.8 Mouse

Model Number : M-UB48
Serial Number : LTC74800118
FCC ID : DZL211137
Manufacturer : Logitech
Data Cable : Shielded, 1.8m

1.2.9 Mouse

Model Number : M-UB48
Serial Number : LTC74800118
FCC ID : DZL211137
Manufacturer : Logitech
Data Cable : Shielded, 1.8m

1.2.10 Earphone

Model Number : PH136
Serial Number : N/A
Manufacturer : BSD
Data Cable : Shielded, 1.2m

1.2.11 Video Camera

Model Number : Wcam 3X
Serial Number : N/A
FCC ID : DoC
Manufacturer : Mustek
Data Cable (USB) : Shielded, 1.5m

1.2.12 LAN Cable: Shielded, 1.8m, 2pcs

1.2.13 V 3.5 Cable: Shielded, 4.5m, 1pc

1.2.14 V 3.5 Cable: Shielded, 1.8m, 1pc

1.2.15 Telephone Line: Non-Shielded, 5m, 1pc

Partner PC System

1.2.16 Notebook PC

Model Number : 500
Serial Number : 9145B0160C9100170EM
Manufacturer : ACER
FCC ID : DoC
Power Adapter : DELTA, ADP-45GB
Cable In: Non-shielded, 1.6m
Cable Out: Non-shielded, 1.8m

1.2.17 Notebook PC

Model Number : 500
Serial Number : 9145B0160C91000CF2M
Manufacturer : ACER
FCC ID : DoC
Power Adapter : DELTA, ADP-45GB
Cable In: Non-shielded, 1.6m
Cable Out: Non-shielded, 1.8m

1.2.18 HDSL-2 DSU (Data Service Unit)

Model Number : PRESTIGE A760V
Serial Number : 9145B0160C9100170EM
Manufacturer : ZyXEL
FCC ID : DoC
Power Adapter : LUCENT
Cable Out: Non-shielded, 1.8m


1.2.19 WAN Access Router

Model Number : PRESTIGE 1100
Serial Number : 9145B0160C9100170EM
Manufacturer : ZyXEL
FCC ID : DoC
Power Cord :Non-Shielded, 1.6m

1.2.20 WAN Access Router

Model Number : PRESTIGE 1100
Serial Number : 9145B0160C9100170EM
Manufacturer : ZyXEL
FCC ID : DoC
Power Cord :Non-Shielded, 1.6m

1.3 EUT Configuration



1.4 EUT Exercise Software

The EUT exercise program used during conducted testing was designed to exercise the EUT in a manner similar to a typical use. The exercise sequence is listed as below:

- 1.4.1 Setup the EUT and simulators as shown on 1.3.
- 1.4.2 Turn on the power of all equipment.
- 1.4.3 Boot the PC from Hard Disk .
- 1.4.4 Data will communicate between personal computer and partner notebook personal notebook through EUT.
- 1.4.5 The personal computer's and partner notebook personal notebook monitor will show the transmitting and receiving characteristics when the communication is success.
- 1.4.6 Printer and modem will keep at standby mode during Scanner operation.
- 1.4.7 Repeat the above procedure 1.4.4 to 1.4.7

1.5 Test performed

Conducted emissions were invested over the frequency range from **0.15MHz to 30MHz** using a receiver bandwidth of 9kHz.

Radiated emissions were invested over the frequency range from **30MHz to 1000MHz** using a receiver bandwidth of 120kHz. Radiated testing was performed at an antenna to EUT distance of 10 meters.

1.6 Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	50-65
Barometric pressure (mbar)	860-1060	950-1000

Site Description: November 3, 1998 File on
Federal Communications Commission
FCC Engineering Laboratory
7435 Oakland Mills Road
Columbia, MD 21046
Reference 31040/SIT1300F2



September 30, 1998 Accreditation on NVLAP
NVLAP Lab Code: 200347-0

February 23, 1999 Accreditation on DNV
Statement No.: 413-99-LAB11



December 8, 1998 Registration on VCCI
Registration No. for No.2 Shielded Room C-858
Registration No. for No.1 Open Area Test Site R-823
Registration No. for No.2 Open Area Test Site R-835



January 04, 1999 Accreditation on TÜV Rheinland
Certificate No.: I9865712-9901



Name of firm : QuieTek Corporation

Site location : No.75-1, Wang-Yeh Valley, Yung-Hsing Tsuen,
Chiung-Lin, Hsin-Chu County, Taiwan, R.O.C.

2. Conducted Emission


2.1 Test Equipment List

The following test equipment are used during the conducted emission test:

Item	Instrument	Manufacturer	Type No./Serial No	Last Cal.	Remark
1	Test Receiver	R & S	ESCS 30/825442/17	May, 2000	
2	L.I.S.N.	R & S	ESH3-Z5/825016/6	May, 2000	EUT
3	L.I.S.N.	Kyoritsu	KNW-407/8-1420-3	May, 2000	Peripherals
4	Pulse Limiter	R & S	ESH3-Z2	N/A	
5	N0.2 Shielded Room			N/A	

Note: All equipment upon which need to calibrated are with calibration period of 1 year.

2.2 Test Setup



2.3 Limits

CISPR 22 Limits (dBuV)					FCC Part 15 Subpart B (dBuV)				
Frequency MHz	Class A		Class B		Frequency MHz	Class A		Class B	
	QP	AV	QP	AV		uV	dBuV	uV	dBuV
0.15 - 0.50	79	66	66-56	56-46	0.45-1.705	1000	60.0	250	48.0
0.50-5.0	73	60	56	46	1.705-30	3000	69.5	250	48.0
5.0 - 30	73	60	60	50					

Remarks : In the above table, the tighter limit applies at the band edges.

2.4 Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4 /1992 on conducted measurement.

The bandwidth of the field strength meter (R & S Test Receiver ESCS 30) is set at 9kHz.

2.5 Test Results

The conducted emission from the EUT is measured and shown in attachment 1 of test report. The acceptance criterion was met and the EUT passed the test.

3. Radiated Emission


3.1 Test Equipment

The following test equipment are used during the radiated emission test:

Test Site		Equipment	Manufacturer	Model No./Serial No.	Last Cal.
Site # 1	X	Test Receiver	R & S	ESCS 30 / 825442/14	May, 2000
		Spectrum Analyzer	Advantest	R3261C / 71720140	May, 2000
		Pre-Amplifier	HP	8447D/3307A01812	May, 2000
	X	Bilog Antenna	Chase	CBL6112B / 12452	Sep., 1999
	X	Horn Antenna	EM	EM6917 / 103325	May, 2000
Site # 2	X	Test Receiver	R & S	ESCS 30 / 825442/17	May, 2000
		Spectrum Analyzer	Advantest	R3261C / 71720609	May, 2000
		Pre-Amplifier	HP	8447D/3307A01814	May, 2000
	X	Bilog Antenna	Chase	CBL6112B / 2455	Sep., 1999
	X	Horn Antenna	EM	EM6917 / 103325	May, 2000

- Note:
1. All equipment upon which need to calibrated are with calibration period of 1 year.
 - 2.. Mark "X" test instruments are used to measure the final test results.

3.2 Test Setup



3.3 Limits

CISPR 22					FCC Part 15 Subpart B				
Frequency	Class A		Class B		Frequency	Class A		Class B	
MHz	Distance (m)	dBuV/m	Distance (m)	dBuV/m		UV/m	DBuV/m	UV/m	DBuV/m
30 – 230	10	40	10	30	30 – 88	90	39	100	40.0
230 – 1000	10	47	10	37	88 – 216	150	43.5	150	43.5
					216 – 960	210	46.5	200	46.0
					960 - 2000	300	49.5	500	54.0

Remark: 1. The tighter limit shall apply at the edge between two frequency bands.

2. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

3. RF Line Voltage (dBuV/m) = 20 log RF Line Voltage (uV/m)

3.4 Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 10 meters . The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4 /1992 on radiated measurement.

The bandwidth below 1GHz setting on the field strength meter (R&S Test Receiver ESCS 30) is 120 kHz.

3.5 Test Results

The radiated emission from the EUT is measured and shown in attachment 1 of test report.

The acceptance criterion was met and the EUT passed the test.

4. EMI Reduction Method During Compliance Testing

No modification was made during testing.



5. Attachment

Attachment 1: Summary of Test Results	Number of Pages: 5
Attachment 2: EUT Test Photographs	Number of Pages: 2
Attachment 3: EUT Detailed Photographs	Number of Pages: 10

Attachment 1 : Summary of Test Results

The test results in the emission and immunity were performed according to the requirements of measurement standard and process. QuieTek Corporation is assumed full responsibility for the accuracy and completeness of these measurements. The test data of the emission and immunity are listed as the attached data.

All the tests were carried out with the EUT in normal operation, which was defined as:

Mode 1: PRESTIGE 760V

The EUT passed all the tests.

The uncertainty is calculated in accordance with NAMAS NIS 81, The total uncertainty for this test is as follows:

➤ **Emission Test**

- Uncertainty in the Conducted Emission Test: $< \pm 2.0 \text{ dB}$
- Uncertainty in the field strength measured: $< \pm 4.0 \text{ dB}$

CONDUCTED EMISSION DATA

Date of Test : July 13, 2000 EUT : HDSL-2 DSU (Data Service Unit)
 Test Mode : Mode 1 Detect Mode : Quasi-Peak & Average

Frequency	Cable Loss	LISN Factor	Reading Level	Measurement Level	Limits
MHz	dB	dB	Line1 dBuV	Line1 dBuV	dBuV
3.088	0.17	0.15	29.60	29.92	56.00
9.263	0.27	0.20	40.00	40.47	60.00
*15.441	0.33	0.36	44.33	45.01	60.00
18.529	0.35	0.42	42.97	43.74	60.00
21.619	0.36	0.48	43.74	44.58	60.00
27.795	0.39	0.57	43.12	44.08	60.00

Average:

3.688	0.18	0.16	28.50	28.84	46.00
9.263	0.27	0.20	38.90	39.37	50.00
15.441	0.33	0.36	43.10	43.78	50.00
18.529	0.35	0.42	40.40	41.17	50.00
21.619	0.36	0.48	39.90	40.74	50.00
27.795	0.39	0.57	41.20	42.16	50.00

Remarks :

1. “ * ” means that this data is the worst emission level.

CONDUCTED EMISSION DATA

Date of Test : July 13, 2000 EUT : HDSL-2 DSU (Data Service Unit)
 Test Mode : Mode 1 Detect Mode : Quasi-Peak & Average

Frequency	Cable Loss	LISN Factor	Reading Level	Measurement Level	Limits
MHz	dB	dB	Line2 dBuV	Line2 dBuV	dBuV
3.807	0.18	0.16	30.78	31.12	56.00
9.265	0.27	0.20	41.72	42.19	60.00
*15.442	0.33	0.36	46.64	47.32	60.00
18.530	0.35	0.42	46.09	46.86	60.00
21.619	0.36	0.48	46.57	47.41	60.00
27.795	0.39	0.57	42.66	43.62	60.00

Average:

3.087	0.17	0.15	29.80	30.12	46.00
9.265	0.27	0.20	40.60	41.07	50.00
15.442	0.33	0.36	45.40	46.08	50.00
18.530	0.35	0.42	43.40	44.17	50.00
21.619	0.36	0.48	42.70	43.54	50.00
27.795	0.39	0.57	40.70	41.66	50.00

Remarks :

1. “ * ” means that this data is the worst emission level.



RADIATED EMISSION DATA

Date of Test : July 13, 2000 EUT : HDSL-2 DSU (Data Service Unit)
 Test Mode : Mode 1 Test Site : No.2 Open Test Site

Freq.	Cable	Probe	PreAMP	Reading	Measurement	Margin	Limit	Ant	Turn
MHz	Loss Factor	dB/m	dB	Level	Horizontal				
	dB			dB	dBuV	dBuV/m	dB	dBuV/m	cm deg
*30.880	1.16	16.49	0.00	5.68	23.33	6.67	30.00	401	202
67.936	1.51	6.19	0.00	0.53	8.23	21.77	30.00	401	95
150.000	2.31	10.72	0.00	1.18	14.21	15.79	30.00	401	23
200.000	2.78	9.30	0.00	7.61	19.69	10.31	30.00	401	88
250.000	3.27	12.61	0.00	1.14	17.02	19.98	37.00	401	17
302.624	3.77	13.18	0.00	-2.28	14.67	22.33	37.00	401	202
501.130	4.80	17.36	0.00	4.48	26.64	10.36	37.00	186	97
525.000	4.92	17.54	0.00	5.02	27.49	9.51	37.00	186	128
575.000	5.18	18.69	0.00	3.29	27.16	9.84	37.00	186	10
614.585	5.39	19.03	0.00	3.21	27.63	9.37	37.00	186	80
700.000	5.83	19.19	0.00	2.54	27.56	9.44	37.00	137	26
725.000	5.97	19.84	0.00	1.24	27.05	9.95	37.00	137	110

Remarks:

- 1.All Readings below 1GHz are Quasi-Peak, above are average value.
- 2.“ * ”, means this data is the worst emission level.
- 3.Emission Level = Reading Level + Antenna Factor + Cable loss



RADIATED EMISSION DATA

Date of Test : July 13, 2000 EUT : HDSL-2 DSU (Data Service Unit)
 Test Mode : Mode 1 Test Site : No.2 Open Test Site

Freq.	Cable	Probe	PreAMP	Reading	Measurement	Margin	Limit	Ant	Turn
MHz	Loss Factor	dB/m	dB	Level	Vertical	dB	dBuV/m	dB	dBuV/m
	dB			dB	dBuV	dBuV/m		cm	deg
30.880	1.16	17.79	0.00	2.80	21.75	8.25	30.00	100	96
43.232	1.28	10.67	0.00	6.57	18.52	11.48	30.00	100	202
50.000	1.35	7.39	0.00	11.60	20.34	9.66	30.00	100	30
60.000	1.44	6.00	0.00	10.73	18.17	11.83	30.00	100	203
67.944	1.51	5.47	0.00	13.54	20.52	9.48	30.00	100	83
74.120	1.58	6.83	0.00	14.47	22.88	7.12	30.00	100	202
80.000	1.64	7.12	0.00	11.29	20.05	9.95	30.00	100	202
117.356	1.99	11.23	0.00	3.62	16.84	13.16	30.00	100	201
123.534	2.06	11.39	0.00	6.25	19.70	10.30	30.00	100	25
129.710	2.11	11.99	0.00	2.76	16.87	13.13	30.00	100	124
138.240	2.20	11.20	0.00	1.34	14.73	15.27	30.00	100	96
150.000	2.31	10.43	0.00	10.29	23.03	6.97	30.00	100	190
172.800	2.52	9.16	0.00	1.33	13.02	16.98	30.00	100	161
*200.000	2.78	9.07	0.00	12.21	24.07	5.93	30.00	100	23
207.360	2.86	9.42	0.00	5.35	17.63	12.37	30.00	100	60
216.262	2.94	9.13	0.00	8.33	20.40	9.60	30.00	100	6
224.640	3.03	9.68	0.00	4.35	17.05	12.95	30.00	100	1
241.920	3.19	11.46	0.00	1.59	16.23	20.77	37.00	100	60
350.000	4.01	14.80	0.00	0.91	19.72	17.28	37.00	100	30
530.730	4.95	17.45	0.00	1.67	24.07	12.93	37.00	348	130
620.792	5.42	18.57	0.00	3.53	27.52	9.48	37.00	348	117
703.758	5.86	18.72	0.00	1.91	26.49	10.51	37.00	348	146

Remarks:

- 1.All Readings below 1GHz are Quasi-Peak, above are average value.
- 2.“ * ”, means this data is the worst emission level.
- 3.Emission Level = Reading Level + Antenna Factor + Cable loss

