



# SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.  
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

## FCC RADIO TEST REPORT

Applicant's company	ZyXEL Communications Corporation
Applicant Address	No. 6, Innovation Road II, Science Park, Hsin-Chu, Taiwan
FCC ID	I88V630
Manufacturer's company	Z-Com, Inc.
Manufacturer Address	7F-2, No. 9. Prosperity RD.I Science-Based Industrial, Park Hsinchu, 300 Taiwan

Product Name	VoIP Wi-Fi Phone
Brand Name	ZyXEL
Model Name	V630
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Received Date	Nov. 21, 2007
Final Test Date	Apr. 15, 2008
Submission Type	Original Equipment



### Statement

**Test result included is only for the 802.11b/g part of the product.**

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.





## Table of Contents

<b>1. CERTIFICATE OF COMPLIANCE .....</b>	<b>1</b>
<b>2. SUMMARY OF THE TEST RESULT .....</b>	<b>2</b>
<b>3. GENERAL INFORMATION .....</b>	<b>3</b>
3.1. Product Details.....	3
3.2. Accessories.....	3
3.3. Table for Filed Antenna.....	3
3.4. Table for Carrier Frequencies .....	4
3.5. Table for Test Modes .....	4
3.6. Table for Testing Locations.....	5
3.7. Table for Supporting Units .....	5
3.8. Table for Parameters of Test Software Setting .....	6
3.9. Test Configurations .....	7
<b>4. TEST RESULT .....</b>	<b>9</b>
4.1. AC Power Line Conducted Emissions Measurement.....	9
4.2. Maximum Peak Output Power Measurement .....	16
4.3. Power Spectral Density Measurement .....	18
4.4. 6dB Spectrum Bandwidth Measurement .....	23
4.5. Radiated Emissions Measurement .....	28
4.6. Band Edge Emissions Measurement .....	46
4.7. Antenna Requirements .....	51
<b>5. LIST OF MEASURING EQUIPMENTS .....</b>	<b>52</b>
<b>6. TEST LOCATION.....</b>	<b>54</b>
<b>7. TAF CERTIFICATE OF ACCREDITATION .....</b>	<b>55</b>
<b>APPENDIX A. PHOTOGRAPHS OF EUT.....</b>	<b>A1 ~ A13</b>
<b>APPENDIX B. TEST PHOTOS.....</b>	<b>B1 ~ B6</b>





## 1. CERTIFICATE OF COMPLIANCE

Product Name : VoIP Wi-Fi Phone  
Brand Name : ZyXEL  
Model Name : V630  
Applicant : ZyXEL Communications Corporation  
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Nov. 21, 2007 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

A handwritten signature in blue ink that reads 'Wayne Hsu 11.6.08'. The signature is written over a horizontal line.

Wayne Hsu

SPORTON INTERNATIONAL INC.

## 2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	7.22 dB
4.2	15.247(b)(3)	Maximum Peak Conducted Output Power	Complies	12.20 dB
4.3	15.247(e)	Power Spectral Density	Complies	17.04 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	5.24 dB
4.6	15.247(d)	Band Edge Emissions	Complies	2.12 dB
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Peak Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 <sup>-8</sup>	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

### 3. GENERAL INFORMATION

#### 3.1. Product Details

Items	Description
Power Type	Power Adapter / Battery
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11
Channel Band Width (99%)	11b: 15.76 MHz ; 11g: 16.50 MHz
Conducted Output Power	11b: 14.31 dBm ; 11g: 17.80 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

#### 3.2. Accessories

Power	Brand	Model	Rating
Adapter 1	LEADER	MU03-F050060-A1	Input: 100-240V, 50/60Hz, 0.15A Output: 5V, 600mA
Accessories	Brand	Model	Rating
Li-ion Battery	SkyPower	WP-520	3.7V, 920mAh
Others			
USB Cable			

#### 3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	WANSHIH	WPF027	PIFA Antenna	NA	3.15

### 3.4. Table for Carrier Frequencies

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz		

### 3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	11 Mbps	6	1
Maximum Peak Conducted Output Power	11b/BPSK	1 Mbps	1/6/11	NA
	11g/BPSK	6 Mbps	1/6/11	NA
Power Spectral Density 6dB Spectrum Bandwidth	11b/BPSK	1 Mbps	1/6/11	NA
	11g/BPSK	6 Mbps	1/6/11	NA
Radiated Emissions 9kHz~1GHz	Normal Link	Auto	6	1
Radiated Emissions 1GHz~10 <sup>th</sup> Harmonic	11b/BPSK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
Band Edge Emissions	11b/BPSK	1 Mbps	1/11	1
	11g/BPSK	6 Mbps	1/11	1

Test Mode 1: EUT+ Adapter +Earphone

Test Mode 2: EUT + USB +Earphone

Note:

For Conducted Emission:

Due to Mode 1 generated the worst test result, so it was recorded in this report.

For Radiated Emission:

Mode 1, Mode 2 for Radiated emission and Band-edge tests were performed at its 3-axis and the worst-case was found at x-axis in Mode 2.

### 3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH03-HY	SAC	Hwa Ya	101377	IC 4088	-
CO04-HY	Conduction	Hwa Ya	101377	IC 4088	-
TH01-HY	OVEN Room	Hwa Ya	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

### 3.7. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	PP20L	E2KWM3945ABG
Printer	EPSON	LQ-300	DoC
Modem	ACEEX	DM1414	IFAXDM1414
AP	PLANEX	GW-AP54SGX	0090CC0F670
Earphone	-	-	DoC
Mouse	QSKY	Lx-619B	DoC
Wireless IP Phone	ZCOM	WP-520	DoC
Wireless AP	Planex	GW-AP54SGX	DoC



### 3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

#### Power Parameters of IEEE 802.11b/g

Test Software Version	Terminal		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	12	12	13
IEEE 802.11g	12	12	13

An executive program, EMCTEST.EXE under WIN XP, which generates a complete line of continuously repeating " H " pattern was used as the test software.

The program was executed as follows :

- a. Turn on the power of all equipment.
- b. The NB sends " H " messages to the panel, and the panel displays " H " patterns on the screen.
- c. The NB sends " H " messages to the printer, then the printer prints them on the paper.
- d. The NB sends " H " messages to the modem.
- e. Repeat the steps from b to d.

At the same time, the following programs were executed:


Executed "Terminal " to control the EUT continuously transmitter RF signal.

Executed "ping.exe" to link with the remote workstation to receive and transmit data by WLAN.


### 3.9. Test Configurations

#### 3.9.1. Radiation Emissions Test Configuration


Test configuration: 30MHz~1GHz



Test configuration: Above 1GHz



### 3.9.2. AC Power Line Conduction Emissions Test Configuration



## 4. TEST RESULT

### 4.1. AC Power Line Conducted Emissions Measurement

#### 4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

#### 4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

#### 4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

#### 4.1.4. Test Setup Layout



#### LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in  $50 \Omega$ . LISN can be placed on top of, or immediately beneath, reference ground plane.
  - (3.1) All other equipment powered from additional LISN(s).
  - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
  - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

#### **4.1.5. Test Deviation**


There is no deviation with the original standard.

#### **4.1.6. EUT Operation during Test**

The EUT was placed on the test table and programmed in normal function.

4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	23°C	Humidity	54%
Test Engineer	Cloud Peng	Phase	Line
Configuration	Normal Link / Mode 1		




	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.56929	41.79	-14.21	56.00	41.52	0.07	0.20	QP
2	0.56929	30.93	-15.07	46.00	30.66	0.07	0.20	AVERAGE
3	0.86185	39.15	-16.85	56.00	38.93	0.02	0.20	QP
4	0.86185	27.29	-18.71	46.00	27.07	0.02	0.20	AVERAGE
5	0.98391	37.62	-18.38	56.00	37.42	0.00	0.20	QP
6	0.98391	23.17	-22.83	46.00	22.97	0.00	0.20	AVERAGE
7	1.269	38.99	-17.01	56.00	38.85	0.00	0.14	QP
8	1.269	25.35	-20.65	46.00	25.21	0.00	0.14	AVERAGE
9	1.441	34.93	-21.07	56.00	34.82	0.00	0.11	QP
10	1.441	20.43	-25.57	46.00	20.32	0.00	0.11	AVERAGE
11	1.734	37.47	-18.53	56.00	37.32	0.00	0.15	QP
12	1.734	23.10	-22.90	46.00	22.95	0.00	0.15	AVERAGE
13	2.023	35.80	-20.20	56.00	35.60	0.00	0.20	QP
14	2.023	22.97	-23.03	46.00	22.77	0.00	0.20	AVERAGE
15	3.173	36.47	-19.53	56.00	36.23	0.00	0.24	QP
16	3.173	24.60	-21.40	46.00	24.36	0.00	0.24	AVERAGE
17	3.603	38.33	-17.67	56.00	38.03	0.00	0.30	QP
18	3.603	26.10	-19.90	46.00	25.80	0.00	0.30	AVERAGE
19	3.922	37.44	-18.56	56.00	37.14	0.00	0.30	QP
20	3.922	26.98	-19.02	46.00	26.68	0.00	0.30	AVERAGE
21	4.247	38.18	-17.82	56.00	37.88	0.00	0.30	QP
22	4.247	28.30	-17.70	46.00	28.00	0.00	0.30	AVERAGE
23	4.696	37.86	-18.14	56.00	37.55	0.01	0.30	QP

	<b>Freq</b>	<b>Level</b>	<b>Over</b>	<b>Limit</b>	<b>Read</b>	<b>LISN</b>	<b>Cable</b>	<b>Remark</b>
	<b>MHz</b>	<b>dBuV</b>	<b>dB</b>	<b>dBuV</b>	<b>dBuV</b>	<b>dB</b>	<b>dB</b>	
24	4.696	27.92	-18.08	46.00	27.61	0.01	0.30	AVERAGE



Temperature	23°C	Humidity	54%
Test Engineer	Cloud Peng	Phase	Neutral
Configuration	Normal Link / Mode 1		



	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.16414	41.89	-23.36	65.25	41.39	0.30	0.20	QP
2	0.16414	26.13	-29.12	55.25	25.63	0.30	0.20	AVERAGE
3	0.17584	44.07	-20.61	64.68	43.62	0.25	0.20	QP
4	0.17584	21.82	-32.86	54.68	21.37	0.25	0.20	AVERAGE
5	0.28935	46.00	-14.54	60.54	45.65	0.15	0.20	QP
6	0.28935	36.22	-14.32	50.54	35.87	0.15	0.20	AVERAGE
7	0.43281	44.71	-12.49	57.20	44.41	0.10	0.20	QP
8	0.43281	34.85	-12.35	47.20	34.55	0.10	0.20	AVERAGE
9	0.56709	48.61	-7.39	56.00	48.31	0.10	0.20	QP
10	0.56709	38.78	-7.22	46.00	38.48	0.10	0.20	AVERAGE
11	0.87103	47.09	-8.91	56.00	46.79	0.10	0.20	QP
12	0.87103	34.93	-11.07	46.00	34.63	0.10	0.20	AVERAGE
13	0.98914	44.47	-11.53	56.00	44.17	0.10	0.20	QP
14	0.98914	33.97	-12.03	46.00	33.67	0.10	0.20	AVERAGE
15	1.135	41.41	-14.59	56.00	41.14	0.10	0.17	QP
16	1.135	28.00	-18.00	46.00	27.73	0.10	0.17	AVERAGE
17	1.310	45.26	-10.74	56.00	45.03	0.10	0.13	QP
18	1.310	31.73	-14.27	46.00	31.50	0.10	0.13	AVERAGE
19	1.418	39.84	-16.16	56.00	39.63	0.10	0.11	QP
20	1.418	28.09	-17.91	46.00	27.88	0.10	0.11	AVERAGE
21	1.585	44.67	-11.33	56.00	44.45	0.10	0.12	QP
22	1.585	30.99	-15.01	46.00	30.77	0.10	0.12	AVERAGE
23	1.725	43.51	-12.49	56.00	43.26	0.10	0.15	QP



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
24	1.725	31.41	-14.59	46.00	31.16	0.10	0.15	AVERAGE
25	1.928	42.42	-13.58	56.00	42.13	0.10	0.19	QP
26	1.928	25.36	-20.64	46.00	25.07	0.10	0.19	AVERAGE
27	2.178	40.96	-15.04	56.00	40.66	0.10	0.20	QP
28	2.178	28.13	-17.87	46.00	27.83	0.10	0.20	AVERAGE
29	2.321	41.82	-14.18	56.00	41.52	0.10	0.20	QP
30	2.321	28.78	-17.22	46.00	28.48	0.10	0.20	AVERAGE
31	2.448	43.02	-12.98	56.00	42.72	0.10	0.20	QP
32	2.448	30.37	-15.63	46.00	30.07	0.10	0.20	AVERAGE
33	2.692	43.02	-12.98	56.00	42.72	0.10	0.20	QP
34	2.692	29.46	-16.54	46.00	29.16	0.10	0.20	AVERAGE
35	2.993	40.97	-15.03	56.00	40.67	0.10	0.20	QP
36	2.993	28.85	-17.15	46.00	28.55	0.10	0.20	AVERAGE
37	3.328	41.28	-14.72	56.00	40.91	0.10	0.27	QP
38	3.328	29.58	-16.42	46.00	29.21	0.10	0.27	AVERAGE
39	3.779	43.46	-12.54	56.00	43.06	0.10	0.30	QP
40	3.779	31.73	-14.27	46.00	31.33	0.10	0.30	AVERAGE
41	4.202	43.25	-12.75	56.00	42.85	0.10	0.30	QP
42	4.202	32.08	-13.92	46.00	31.68	0.10	0.30	AVERAGE
43	4.478	44.84	-11.16	56.00	44.44	0.10	0.30	QP
44	4.478	33.75	-12.25	46.00	33.35	0.10	0.30	AVERAGE
45	4.772	43.85	-12.15	56.00	43.45	0.10	0.30	QP
46	4.772	33.81	-12.19	46.00	33.41	0.10	0.30	AVERAGE
47	5.194	44.66	-15.34	60.00	44.26	0.10	0.30	QP
48	5.194	33.83	-16.17	50.00	33.43	0.10	0.30	AVERAGE
49	5.362	42.76	-17.24	60.00	42.36	0.10	0.30	QP
50	5.362	32.75	-17.25	50.00	32.35	0.10	0.30	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.

## 4.2. Maximum Peak Output Power Measurement

### 4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

### 4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RB	1000 kHz
VB	3000 kHz
Detector	Sample
Trace	Average 100 traces.
Sweep Time	20ms

### 4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Test was performed in accordance with method #1 of FCC Public Notice DA-02-2138.

### 4.2.4. Test Setup Layout



### 4.2.5. Test Deviation

There is no deviation with the original standard.

### 4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.2.7. Test Result of Maximum Peak Output Power

<b>Temperature</b>	26°C	<b>Humidity</b>	55%
<b>Test Engineer</b>	Beck Wu	<b>Configurations</b>	802.11b/g

##### Configuration IEEE 802.11b

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	14.01	30.00	Complies
6	2437 MHz	14.11	30.00	Complies
11	2462 MHz	14.31	30.00	Complies

##### Configuration IEEE 802.11g

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	17.80	30.00	Complies
6	2437 MHz	17.70	30.00	Complies
11	2462 MHz	17.09	30.00	Complies

### 4.3. Power Spectral Density Measurement

#### 4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

#### 4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	1.5MHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	500s

#### 4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 1.5MHz and the sweep time to 500s and record the maximum peak value.

#### 4.3.4. Test Setup Layout



#### 4.3.5. Test Deviation

There is no deviation with the original standard.

#### 4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.3.7. Test Result of Power Spectral Density

<b>Temperature</b>	26°C	<b>Humidity</b>	55%
<b>Test Engineer</b>	Beck Wu	<b>Configurations</b>	802.11b/g


##### Configuration IEEE 802.11b

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-12.94	8.00	Complies
6	2437 MHz	-12.17	8.00	Complies
11	2462 MHz	-12.05	8.00	Complies

##### Configuration IEEE 802.11g


Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-9.63	8.00	Complies
6	2437 MHz	-9.51	8.00	Complies
11	2462 MHz	-9.04	8.00	Complies

## Power Density Plot on Configuration IEEE 802.11b / 2412 MHz



Date: 23.NOV.2007 10:14:22

## Power Density Plot on Configuration IEEE 802.11b / 2437 MHz



Date: 23.NOV.2007 10:02:36







#### 4.4. 6dB Spectrum Bandwidth Measurement

##### 4.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

##### 4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

##### 4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.

##### 4.4.4. Test Setup Layout



#### 4.4.5. Test Deviation

There is no deviation with the original standard.

#### 4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.4.7. Test Result of 6dB Spectrum Bandwidth

<b>Temperature</b>	26°C	<b>Humidity</b>	55%
<b>Test Engineer</b>	Beck Wu	<b>Configurations</b>	802.11b/g


##### Configuration IEEE 802.11b

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	10.03	15.60	500	Complies
6	2437 MHz	11.08	15.76	500	Complies
11	2462 MHz	10.06	15.54	500	Complies

##### Configuration IEEE 802.11g


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.31	16.50	500	Complies
6	2437 MHz	16.37	16.47	500	Complies
11	2462 MHz	16.37	16.44	500	Complies

### 6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 23.NOV.2007 10:13:56

### 6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2437 MHz




Date: 23.NOV.2007 10:02:19

### 6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 23.NOV.2007 10:01:13

### 6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2412 MHz




Date: 23.NOV.2007 10:15:14

### 6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2437 MHz



Date: 23.NOV.2007 10:29:56

### 6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2462 MHz



Date: 23.NOV.2007 10:17:23

## 4.5. Radiated Emissions Measurement

### 4.5.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100KHz / 100KHz for peak

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP


### 4.5.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.




#### 4.5.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1.5m.

Distance extrapolation factor =  $20 \log (\text{specific distance [3m]} / \text{test distance [1.5m]})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

#### 4.5.5. Test Deviation

There is no deviation with the original standard.

#### 4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.5.7. Results of Radiated Emissions (9kHz~30MHz)

<b>Temperature</b>	26°C	<b>Humidity</b>	58%
<b>Test Engineer</b>	Sam Chen		

<b>Freq. (MHz)</b>	<b>Level (dBuV)</b>	<b>Over Limit (dB)</b>	<b>Limit Line (dBuV)</b>	<b>Remark</b>
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log(\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	26°C	Humidity	58%
Test Engineer	Barry Chen	Configurations	Normal Link / Mode 2

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Table Pos	Ant Pos	Ant Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		deg	cm	
1	202.660	34.63	-8.87	43.50	51.14	8.87	27.09	1.71	Peak	0	100	HORIZONTAL
2	238.550	35.28	-10.72	46.00	49.82	10.63	27.02	1.85	Peak	0	100	HORIZONTAL
3	431.580	34.43	-11.57	46.00	43.31	16.38	27.76	2.49	Peak	0	100	HORIZONTAL
4	700.270	35.69	-10.31	46.00	41.06	19.33	27.99	3.30	Peak	0	100	HORIZONTAL
5	766.230	38.18	-7.82	46.00	42.62	19.87	27.74	3.43	Peak	0	100	HORIZONTAL
6	800.180	38.62	-7.38	46.00	43.02	19.90	27.60	3.30	Peak	0	100	HORIZONTAL

**Vertical**



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Table Pos	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		deg	cm	
1	202.660	28.10	-15.40	43.50	44.62	8.87	27.09	1.71	Peak	0	400	VERTICAL
2	431.580	32.05	-13.95	46.00	40.94	16.38	27.76	2.49	Peak	0	400	VERTICAL
3	591.630	38.18	-7.82	46.00	44.85	18.55	28.10	2.88	Peak	0	400	VERTICAL
4	696.390	34.69	-11.31	46.00	40.17	19.20	28.00	3.32	Peak	0	400	VERTICAL
5	762.350	35.72	-10.28	46.00	40.23	19.79	27.75	3.45	Peak	0	400	VERTICAL
6	800.180	39.16	-6.84	46.00	43.56	19.90	27.60	3.30	Peak	258	144	VERTICAL

**Note:**

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Emission level (dBUV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10<sup>th</sup> Harmonic)


Temperature	26°C	Humidity	58%
Test Engineer	Sam Chen	Configurations	802.11b CH 1/ Mode 2

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Table Pos	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		deg	cm	
1	4823.740	39.59	-14.41	54.00	35.97	32.49	35.26	6.39	AVERAGE	54	100	HORIZONTAL
2	4824.340	48.86	-25.14	74.00	45.24	32.49	35.26	6.39	PEAK	54	100	HORIZONTAL


**Vertical**



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Table Pos	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		deg	cm	
1	4824.140	51.77	-22.23	74.00	48.15	32.49	35.26	6.39	PERK	16	100	VERTICAL
2	4824.240	44.71	-9.29	54.00	41.09	32.49	35.26	6.39	AVERAGE	16	100	VERTICAL


Temperature	26°C	Humidity	58%
Test Engineer	Sam Chen	Configurations	802.11b CH 6 / Mode 2

**Horizontal**



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Table Pos	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		deg	cm	
1	4873.780	41.11	-12.89	54.00	37.11	32.58	35.15	6.56	AVERAGE	54	100	HORIZONTAL
2	4874.180	49.90	-24.10	74.00	45.90	32.58	35.15	6.56	PEAK	54	100	HORIZONTAL

**Vertical**




	Freq	Level	Over	Limit	Read	Antenna	Preamp	Cable	Table	Ant
	MHz	dBUV/m	dB	dBUV/m	Level	Factor	Factor	Loss	Pos	Pos
					dBuV	dB/m	dB	dB	deg	cm
1	4874.220	52.96	-21.04	74.00	48.96	32.58	35.15	6.56	23	153
2	4874.240	46.41	-7.59	54.00	42.41	32.58	35.15	6.56	23	153




Temperature	26°C	Humidity	58%
Test Engineer	Sam Chen	Configurations	802.11b CH 11 / Mode 2

**Horizontal**



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Table Pos	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		deg	cm	
1	4923.850	52.72	-21.28	74.00	48.34	32.68	35.03	6.73	PEAK	330	103	HORIZONTAL
2	4924.230	45.35	-8.65	54.00	40.98	32.68	35.03	6.73	AVERAGE	330	103	HORIZONTAL


**Vertical**



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Table Pos	Ant Pos	Ant Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		deg	cm	
1	4923.900	53.49	-20.51	74.00	49.12	32.68	35.03	6.73	PEAK	22	218	VERTICAL
2	4924.270	48.76	-5.24	54.00	44.38	32.68	35.03	6.73	AVERAGE	22	218	VERTICAL


Temperature	26°C	Humidity	58%
Test Engineer	Sam Chen	Configurations	802.11g CH 1 / Mode 2

**Horizontal**



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Table Pos	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		deg	cm	
1	4822.520	47.91	-26.09	74.00	44.29	32.49	35.26	6.39	PEAK	198	196	HORIZONTAL
2	4823.200	33.96	-20.04	54.00	30.34	32.49	35.26	6.39	AVERAGE	198	196	HORIZONTAL


**Vertical**



	Freq	Level	Over	Limit	ReadAntenna	Preamp	Cable	Remark	Table	Ant
	MHz	dBuV/m	dB	dBuV/m	Level	Factor	Loss		Pos	Pos
					Factor	Factor	Factor		deg	cm
					dB	dB/m	dB			
1	4821.900	48.76	-25.24	74.00	45.14	32.49	35.26	6.39 PEAK	13	230 VERTICAL
2	4822.100	36.41	-17.59	54.00	32.79	32.49	35.26	6.39 AVERAGE	13	230 VERTICAL


Temperature	26°C	Humidity	58%
Test Engineer	Sam Chen	Configurations	802.11g CH 6 / Mode 2

**Horizontal**



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Table Pos	Ant Pos	Pol/Phase
	MHz	dBUV/m	dB	dBUV/m	dBuV	dB/m	dB	dB		deg	cm	
1	4870.280	49.71	-24.29	74.00	45.71	32.58	35.15	6.56	PEAK	329	133	HORIZONTAL
2	4873.600	35.20	-18.80	54.00	31.20	32.58	35.15	6.56	AVERAGE	329	133	HORIZONTAL


**Vertical**



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Table Pos	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		deg	cm	
1	4873.720	36.71	-17.29	54.00	32.71	32.58	35.15	6.56	AVERAGE	75	102	VERTICAL
2	4874.240	44.19	-29.81	74.00	40.19	32.58	35.15	6.56	PEAK	75	102	VERTICAL


Temperature	26°C	Humidity	58%
Test Engineer	Sam Chen	Configurations	802.11g CH 11 / Mode 2

**Horizontal**



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Table Pos	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		deg	cm	
1	4922.000	35.71	-18.29	54.00	31.33	32.68	35.03	6.73	Average	184	110	HORIZONTAL
2	4922.100	48.74	-25.26	74.00	44.37	32.68	35.03	6.73	PERK	184	110	HORIZONTAL

**Vertical**



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Table Pos	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		deg	cm	
1	4923.700	49.75	-24.25	74.00	45.37	32.68	35.03	6.73	PEAK	330	103	VERTICAL
2	4923.760	36.43	-17.57	54.00	32.05	32.68	35.03	6.73	AVERAGE	330	103	VERTICAL

**Note:**

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.



## 4.6. Band Edge Emissions Measurement

### 4.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micovolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1 MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 KHz /100 KHz for Peak

### 4.6.3. Test Procedures

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

### 4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

### 4.6.5. Test Deviation

There is no deviation with the original standard.

### 4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	26°C	Humidity	58%
Test Engineer	Sam Chen	Configurations	802.11b CH 1, 6, 11

##### Channel 1

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Table Pos	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		deg	cm	
1 ☒	2386.400	59.40	-14.60	74.00	28.59	27.94	0.00	2.86	PEAK	331	100	HORIZONTAL
2 ☒	2386.800	51.88	-2.12	54.00	21.07	27.94	0.00	2.86	AVERAGE	331	100	HORIZONTAL
3 ☒	2413.800	103.74			72.94	27.92	0.00	2.88	PEAK	331	100	HORIZONTAL
4 ☒	2414.800	99.42			68.62	27.92	0.00	2.88	AVERAGE	331	100	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

##### Channel 6

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Table Pos	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		deg	cm	
1 ☒	2438.800	104.40			73.63	27.87	0.00	2.90	PEAK	275	104	HORIZONTAL
2 ☒	2439.800	99.91			69.14	27.87	0.00	2.90	AVERAGE	275	104	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2437 MHz.

##### Channel 11

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Table Pos	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		deg	cm	
1 ☒	2459.200	100.87			70.11	27.85	0.00	2.91	AVERAGE	179	105	VERTICAL
2 ☒	2460.400	105.15			74.39	27.85	0.00	2.91	PEAK	179	105	VERTICAL
3 ☒	2487.100	50.29	-3.71	54.00	19.54	27.82	0.00	2.93	AVERAGE	179	105	VERTICAL
4 ☒	2487.900	58.41	-15.59	74.00	27.69	27.80	0.00	2.93	PEAK	179	105	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.



<b>Temperature</b>	26°C	<b>Humidity</b>	58%
<b>Test Engineer</b>	Sam Chen	<b>Configurations</b>	802.11g CH 1, 6, 11

**Channel 1**

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Table Pos	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		deg	cm	
1 ☺	2390.000	51.88	-2.12	54.00	21.06	27.94	0.00	2.88	AVERAGE	32	100	HORIZONTAL
2 ☺	2390.000	67.29	-6.71	74.00	36.46	27.94	0.00	2.88	PEAK	32	100	HORIZONTAL
3 ☺	2406.800	95.84			65.04	27.92	0.00	2.88	AVERAGE	32	100	HORIZONTAL
4 ☺	2413.200	106.26			75.46	27.92	0.00	2.88	PEAK	32	100	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

**Channel 6**

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Table Pos	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		deg	cm	
1 ☺	2432.400	106.80			76.01	27.90	0.00	2.90	PEAK	31	100	HORIZONTAL
2 ☺	2435.400	95.31			64.52	27.90	0.00	2.90	AVERAGE	31	100	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2437 MHz.

**Channel 11**

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Remark	Table Pos	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		deg	cm	
1 ☺	2456.600	105.89			75.13	27.85	0.00	2.91	PEAK	145	100	VERTICAL
2 ☺	2458.200	94.48			63.72	27.85	0.00	2.91	AVERAGE	145	100	VERTICAL
3 ☺	2483.500	49.93	-4.07	54.00	19.18	27.82	0.00	2.93	AVERAGE	145	100	VERTICAL
4 ☺	2483.700	63.27	-10.73	74.00	32.52	27.82	0.00	2.93	PEAK	145	100	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


**For Emission not in Restricted Band**

**Low Band Edge Plot on Configuration IEEE 802.11b / 2412 MHz**




Date: 23.NOV.2007 10:14:30

**High Band Edge Plot on Configuration IEEE 802.11b / 2462 MHz**




Date: 23.NOV.2007 10:01:37

### Low Band Edge Plot on Configuration IEEE 802.11g / 2412 MHz



Date: 23.NOV.2007 10:15:48

### High Band Edge Plot on Configuration IEEE 802.11g / 2462 MHz



Date: 23.NOV.2007 13:23:59

## 4.7. Antenna Requirements

### 4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

### 4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

## 5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	Mar. 03, 2008	Conduction (CO04-HY)
LISN	MessTec	NNB-2/16Z	99079	9kHz – 30MHz	Mar. 31, 2008	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9703-1839	9kHz – 30MHz	Mar. 22, 2008	Conduction (CO04-HY)
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9kHz – 30MHz	Apr. 20, 2007	Conduction (CO04-HY)
ISN	SCHAFFNER	ISN T400	21653	9kHz – 30MHz	Mar. 27, 2008	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 14, 2007	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	COA9231A	18667	9 kHz - 2 GHz	Jan. 14, 2008	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1 GHz - 26.5 GHz	Jun. 07, 2007	Radiation (03CH03-HY)
Amplifier	MITEQ	AMF-6F-260400	9121372	26.5 GHz - 40 GHz	Jan. 22, 2007*	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP40	100305	9 kHz - 40 GHz	Sep. 27, 2007	Radiation (03CH03-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	May 23, 2006*	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30 MHz – 1 GHz	Jul. 21, 2007	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	May 04, 2007	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	Jan.18, 2008	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Dec. 03, 2007	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Dec. 03, 2007	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 – 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP30	100023	9kHz ~ 30GHz	Jan. 10, 2008	Conducted (TH01-HY)
Power Meter	R&S	NRVS	100444	DC ~ 40GHz	Jun. 27, 2007	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z51	100458	DC ~ 30GHz	Jun. 27, 2007	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Jun. 27, 2007	Conducted (TH01-HY)
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	May 04, 2007*	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Mar. 13, 2008	Conducted (TH01-HY)
Temp. and Humidity Chamber	KSON	THS-C3L	612	N/A	Oct. 01, 2007	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 01, 2007	Conducted (TH01-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 01, 2007	Conducted (TH01-HY)
Vector Signal Generator	R&S	SMU200A	102098	100kHz ~ 6GHz	Nov. 14, 2007	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Mar. 10, 2008	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

Note: \* Calibration Interval of instruments listed above is two year.



## 6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 <sup>nd</sup> Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

## 7. TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-070110

財團法人全國認證基金會  
Taiwan Accreditation Foundation

### Certificate of Accreditation

This is to certify that

**Sporton International Inc.**  
**EMC & Wireless Communications Laboratory**  
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,  
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2007 to January 09, 2010
Accredited Scope	: Testing Field, see described in the Appendix
Specific Accreditation Program	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection : Accreditation Program for Telecommunication Equipment Testing Laboratory

  
Jay-San Chen  
President, Taiwan Accreditation Foundation  
Date : January 10, 2007

P1, total 9 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when used without the Appendix.