

FCC Test Report

FCC ID	:	I88WSQ50
Equipment	:	Multy X AC3000 Tri-Band WiFi System
Model No.	:	WSQ50
Brand Name	:	ZYXEL
Applicant	:	Zyxel Communications Corporation
Address	:	No.2, Industry East Road IX, Hsinchu Science Park, Hsinchu, 30075, Taiwan, R.O.C.
Standard	:	47 CFR FCC Part 15.247
Received Date	:	May 26, 2017
Tested Date	:	Jun. 07 ~ Aug. 21, 2017

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:

Approved by:

ong Cher





Along Cherly/ Assistant Manager Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	.5
1.1	Information	.5
1.2	Local Support Equipment List	.7
1.3	Test Setup Chart	.7
1.4	Test Equipment List and Calibration Data	.8
1.5	Test Standards	.9
1.6	Measurement Uncertainty	.9
2	TEST CONFIGURATION	10
2.1	Testing Condition	10
2.2	The Worst Test Modes and Channel Details	10
3	TRANSMITTER TEST RESULTS	11
3.1	Conducted Emissions	11
3.2	6dB and Occupied Bandwidth	14
3.3	RF Output Power	16
3.4	Power Spectral Density	18
3.5	Emissions in Restricted Frequency Bands	
3.6	Emissions in non-restricted Frequency Bands	30
4	TEST LABORATORY INFORMATION	32



Release Record

Report No.	Version	Description	Issued Date
FR760801AE	Rev. 01	Initial issue	Sep. 04, 2017



Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	AC Power Line Conducted Emissions	[dBuV]: 0.481MHz 27.86 (Margin -18.46dB) - AV	Pass
15.247(d)	Radiated Emissions	[dBuV/m at 3m]: 48.43MHz	Pass
15.209		36.33 (Margin -3.67dB) - PK	F 855
15.247(b)(3)	Maximum Output Power	Power [dBm]: 4.05	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass



1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information						
Frequency Range (MHz)	Bluetooth Mode	Ch. Freq. (MHz)	Data Rate			
2400-2483.5 V4.1 LE 2402-2480 0-39 [40] 1 Mbps						
Note 1: Bluetooth LE	(Low energy) uses G	FSK modulation.				

1.1.2 Main Chipset / RF Chipset

Function	Model No.
Main Chipset	IPQ4019
2.4G	IPQ4019
5G 2T2R	IPQ4019
5G 4T4R	QCA9984
Bluetooth LE	CSR8811

1.1.3 Antenna Details

Ant. No.	Model	Туре	Connector	Gain (dBi)	Remarks
1	ALX17M-126XX3-A	PIFA	UFL	4.94	

1.1.4 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	12Vdc from adapter
-------------------	--------------------

1.1.5 Accessories

Accessories				
No.	Equipment	Description		
1	Adapter	Brand Name: APD Model Name: WA-36A12FU I/P: 100-240Vac, 50-60Hz 0.9 Max O/P: 12Vdc, 3A Power line: 1.75m non-shielded without core		




1.1.6 Channel List

	Frequency band (MHz)				2400~2	2483.5	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
37	2402	9	2422	18	2442	28	2462
0	2404	10	2424	19	2444	29	2464
1	2406	38	2426	20	2446	30	2466
2	2408	11	2428	21	2448	31	2468
3	2410	12	2430	22	2450	32	2470
4	2412	13	2432	23	2452	33	2472
5	2414	14	2434	24	2454	34	2474
6	2416	15	2436	25	2456	35	2476
7	2418	16	2438	26	2458	36	2478
8	2420	17	2440	27	2460	39	2480

1.1.7 Test Tool and Duty Cycle

Test tool	putty, ver. 0.6
Duty cycle of test signal (%)	64.29%
Duty Factor (dB)	1.92






1.1.8 Power Setting

Modulation Mode		Test Frequency (MHz)			
	2402 2440 2480				
GFSK/1Mbps	default	default	default		

1.2 Local Support Equipment List

	Support Equipment List						
No.	Equipment	Brand	Model	FCC ID	Signal cable / Length (m)		
1	Notebook	DELL	Latitude E6430	DoC	RJ45, 10m non-shielded.		
2	Notebook	DELL	Latitude E5420	DoC	RJ45, 10m non-shielded.		
3	USB Flash	Kingston	DTSE9				

1.3 Test Setup Chart





Test Equipment List and Calibration Data 1.4

Test Item	Conducted Emission	Conducted Emission						
Test Site	Conduction room 1 / (Conduction room 1 / (CO01-WS)						
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until			
Receiver	R&S	ESR3	101657	Dec. 21, 2016	Dec. 20, 2017			
LISN	R&S	ENV216	101579	Jan. 19, 2017	Jan. 18, 2018			
RF Cable-CON	EMC	EMCCFD300-BM-B M-6000	50821	Dec. 20, 2016	Dec. 19, 2017			
Measurement Software	AUDIX	e3	6.120210k	NA	NA			
Note: Calibration Inte	rval of instruments liste	d above is one year.		•	•			

Test Item	Radiated Emission							
Test Site	966 chamber1 / (03C	966 chamber1 / (03CH01-WS)						
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until			
Spectrum Analyzer	R&S	FSV40	101498	Nov. 25, 2016	Nov. 24, 2017			
Receiver	R&S	ESR3	101658	Nov. 24, 2016	Nov. 23, 2017			
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-524	Oct. 13, 2016	Oct. 12, 2017			
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 21, 2016	Dec. 20, 2017			
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Oct. 25, 2016	Oct. 24, 2017			
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 10, 2016	Nov. 09, 2017			
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Dec. 09, 2016	Dec. 08, 2017			
Preamplifier	EMC	EMC02325	980146	Oct. 08, 2016	Oct. 07, 2017			
Preamplifier	Agilent	83017A	MY39501308	Oct. 06, 2016	Oct. 05, 2017			
Preamplifier	EMC	EMC184045B	980192	Aug. 24, 2016	Aug. 23, 2017			
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Dec. 09, 2016	Dec. 08, 2017			
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Dec. 09, 2016	Dec. 08, 2017			
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16139/4	Dec. 09, 2016	Dec. 08, 2017			
LF cable 1M	EMC	EMCCFD400-NM-N M-1000	16052	Dec. 09, 2016	Dec. 08, 2017			
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Dec. 09, 2016	Dec. 08, 2017			
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Dec. 09, 2016	Dec. 08, 2017			
Measurement Software	AUDIX	e3	6.120210g	NA	NA			



Test Item	RF Conducted				
Test Site	(TH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Mar. 15, 2017	Mar. 14, 2018
Power Meter	Anritsu	ML2495A	1241002	Oct. 06, 2016	Oct. 05, 2017
Power Sensor	Anritsu	MA2411B	1207366	Oct. 06, 2016	Oct. 05, 2017
AC POWER SOURCE	APC	AFC-500W	F312060012	Oct. 28, 2016	Oct. 27, 2017
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247 ANSI C63.10-2013 FCC KDB 558074 D01 DTS Meas Guidance v04

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty					
Parameters	Uncertainty				
Bandwidth	±34.134 Hz				
Conducted power	±0.808 dB				
Power density	±0.463 dB				
Conducted emission	±2.670 dB				
AC conducted emission	±2.90 dB				
Radiated emission ≤ 1GHz	±3.66 dB				
Radiated emission > 1GHz	±5.63 dB				



2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	23°C / 57%	Alex Tsai
Radiated Emissions	03CH01-WS	24°C / 60%	Vincent Yeh
RF Conducted	TH01-WS	23°C / 64%	Felix Sung

➢ FCC Designation No.: TW2732

➢ FCC site registration No.: 181692

➢ IC site registration No.: 10807A-1

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate	Test Configuration
AC Power Line Conducted Emissions Radiated Emissions ≤ 1GHz	BT LE	2480	1Mbps	
Maximum Output Power 6dB bandwidth Power spectral density Radiated Emissions > 1GHz	BT LE	2402, 2440, 2480	1Mbps	



3 Transmitter Test Results

3.1 Conducted Emissions


3.1.1 Limit of Conducted Emissions

Conducted Emissions Limit						
Frequency Emission (MHz)	Quasi-Peak	Average				
0.15-0.5	66 - 56 *	56 - 46 *				
0.5-5	56	46				
5-30	60	50				
Note 1: * Decreases with the logarith	Note 1: * Decreases with the logarithm of the frequency.					

3.1.2 Test Procedures

- 1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
- The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
- 3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
- 4. This measurement was performed with AC 120V/60Hz


3.1.3 Test Setup



Note: 1. Support units were connected to second LISN.


2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes





3.1.4 Test Result of Conducted Emissions







3.2 6dB and Occupied Bandwidth

3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

3.2.2 Test Procedures


6dB Bandwidth

- 1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
- 2. Detector = Peak, Trace mode = max hold.
- 3. Sweep = auto couple, Allow the trace to stabilize.
- 4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth

- 1. Set resolution bandwidth (RBW) = 30 kHz, Video bandwidth = 100 kHz.
- 2. Detector = Sample, Trace mode = max hold.
- 3 Sweep = auto couple, Allow the trace to stabilize.
- 4. Use the OBW measurement function of spectrum analyzer to measure the occupied bandwidth.

3.2.3 Test Setup





Mode	Freq. (MHz)	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit of 6dB Bandwidth (kHz)
BT LE	2402	0.700	1.02	500
BT LE	2440	0.696	1.02	500
BT LE	2480	0.696	1.02	500

3.2.4 Test Result of 6dB and Occupied Bandwidth

6dB Bandwidth	99% Occupied Bandwidth
Spectrum Røf Level 20.00 dBm Offset 11.00 dB ⊕ RBW 100 kHz	Imp Spectrum Ref Level 20.00 dBm Offset 11.00 dB ● RBW 30 idd2
Att 30 dB SWT 1 ms WBW 300 kHz Mode Sweep	Att 30 dB SWT 3 ms VBW 100 kHz Mode Sweep
10 dBm Occ Bw 1.046: D1[1]	-3.33 dBm -3.33 dBm -3.34 dBm 10 dBm -0.01 dB -0.01 dBm -10
	-70 doin
-60 dBm	CF 2.48 GHz 3000 pts Span 3.0 M
-70 dBm	Marker
F1 F2	Type Ref Trc X-value Y-value Function Function Result M1 1 2.479975 GHz 0.20 dBm Function Result 10.23 MHz T1 1 2.4794955 GHz -15.91 dBm Occ Bw 1.023 MHz T2 1 2.4690125 GHz -15.94 dBm 1.023 MHz 1.023 MHz



3.3 **RF Output Power**

3.3.1 Limit of RF Output Power

Conducted power shall not exceed 1Watt.

- Antenna gain <= 6dBi, no any corresponding reduction is in output power limit.
- Antenna gain > 6dBi
 - Non Fixed, point to point operations.

The conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB

Fixed, point to point operations

Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point Operations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point operations ,no any corresponding reduction is in transmitter peak output power

3.3.2 Test Procedures

Maximum Peak Conducted Output Power

- Spectrum analyzer
 - 1. Set RBW = 1MHz, VBW = 3MHz, Detector = Peak.
 - 2. Sweep time = auto, Trace mode = max hold, Allow trace to fully stabilize.
 - 3. Use the spectrum analyzer channel power measurement function with the band limits set equal to the DTS bandwidth edges.


Power meter

- 1. A broadband Peak RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.
- Maximum Conducted Average Output Power (For reference only)

Power meter

1. A broadband Average RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

3.3.3 Test Setup





			Peak Power		Antenna		EIRP
Mode	Freq. (MHz)	Power (mW)	Power (dBm)	Limit (dBm)	gain (dBi)	EIRP (dBm)	Limit (dBm)
BT LE	2402	1.072	0.30	30	4.94	5.24	36
BT LE	2440	1.968	2.94	30	4.94	7.88	36
BT LE	2480	2.541	4.05	30	4.94	8.99	36

3.3.4 Test Result of Maximum Output Power

Mode	Freq. (MHz)	AV Power (mW)	AV Power (dBm)	Limit (dBm)
BT LE	2402	0.971	-0.13	
BT LE	2440	1.795	2.54	
BT LE	2480	2.275	3.57	

Note: Average power is for reference only



3.4 **Power Spectral Density**


3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

3.4.2 Test Procedures

- Maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit.
 - 1. Set the RBW = 3kHz, VBW = 10kHz.
 - 2. Detector = Peak, Sweep time = auto couple.
 - 3. Trace mode = max hold, allow trace to fully stabilize.
 - 4. Use the peak marker function to determine the maximum amplitude level.
- Maximum (average) conducted output power was used to demonstrate compliance to the fundamental output power limit.
 - 1. Set the RBW = 100kHz, VBW = 300 kHz.
 - 2. Detector = RMS, Sweep time = auto couple.
 - 3. Set the sweep time to: ≥ 10 x (number of measurement points in sweep) x (maximum data rate per stream).
 - 4. Perform the measurement over a single sweep.
 - 5. Use the peak marker function to determine the maximum amplitude level.


3.4.3 Test Setup





3.4.4 Test Result of Power Spectral Density

Mode	Freq. (MHz)	Total Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)			
BT LE	2402	-16.44	8			
BT LE	2440	-13.72	8			
BT LE	2480	-12.82	8			





3.5 Emissions in Restricted Frequency Bands

3.5.1 Limit of Emissions in Restricted Frequency Bands

Restricted Band Emissions Limit							
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)				
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300				
0.490~1.705	24000/F(kHz)	33.8 - 23	30				
1.705~30.0	30	29	30				
30~88	100	40	3				
88~216	150	43.5	3				
216~960	200	46	3				
Above 960	500	54	3				

Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit **Note 2:**

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.5.2 Test Procedures


- Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
- Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- 3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


- 1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
- 2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
- 3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.



3.5.3 Test Setup








3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)









Modulation	ulation GFSK			FSK Test Freq. (MHz)						24	2402		
Polarization		Horiz	ontal										
90	evel (dBu	v/m)											
80-													
-										F	CC CLAS	S-B	
70-													
60											ASS-B (A		
50	2										.A.3 3-D (F	<u>(VG)</u>	
		6			1								
40-	-1	-											
30-		Ť_											
20													
20													
10													
0	000 4	4000. 6	5000. 80	00 100	00 420	00 140	0 46	000. 180	00 200	00 22	2000	25000	
	000 -			00. 100		uency (N		. 100	00. 200	00. 24		23000	
	F	req. E	mission	Limit	Margi			Factor	Rema	ark	ANT	Turn	
			level	10.14	10	read	-	10			_	Table	
		MHz	dBuV/m	dBuV/r	n dB	dBu	IV	dB			cm	deg	
1	23	90.00	38.17	54.00	-15.83	41	35	-3.18	Aver	age	390	198	
2			49.76	74.00	-24.24		94	-3.18	Peak		390		
3 * 4 *			93.11				24	-3.13		_	390		
4 * 5			94.18 32.89	51 00	-21 11		31 15	-3.13 3.74	Peak Aver		390 100		
6			44.55				81	3.74	Peak	_	100		
7			42.93			29	38	13.55	Aver	rage	100	172	
8	120	10.00	54.16	74.00	-19.84	40	61	13.55	Peak	c	100	172	
Note 1: Emission L *Factor inclu													
Note 2: Margin (dB) Note 3:"*" is Peak /							′/m).						

3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK


























3.6 Emissions in non-restricted Frequency Bands

3.6.1 Emissions in non-restricted frequency bands limit

The peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.6.2 Test Procedures


Reference Level Measurement

- 1. Set the RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
- 2. Set Sweep time = auto couple, Trace mode = max hold.
- 3. Allow trace to fully stabilize.
- 4. Use the peak marker function to determine the maximum amplitude level.


Unwanted Emissions Level Measurement

- 1. Set RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
- 2. Trace Mode = max hold, Sweep = auto couple.
- 3. Allow the trace to stabilize.
- 4. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

3.6.3 Test Setup







3.6.4 Test Result of Emissions in non-restricted Frequency Bands



4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <u>http://www.icertifi.com.tw</u>.

Linkou Tel: 886-2-2601-1640 No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan, R.O.C. Kwei Shan Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C. Kwei Shan Site II Tel: 886-3-271-8640 No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666 Fax: 886-3-318-0155 Email: ICC_Service@icertifi.com.tw

—END—