



FCC PART 95  
MEASUREMENT AND TEST REPORT

For

**Kiddesigns Inc**

1299 Main Street, Rahway NJ 07065-0901 USA

**FCC ID: IAJ202C**

<b>Report Type:</b> Original Report	<b>Product Type:</b> XX-202 Walkie Talkies
<b>Test Engineer:</b> Hill He	<i>Hill He</i>
<b>Report Number:</b> RSZ160520K1452E-00B	
<b>Report Date:</b> 2016-06-16	
<b>Reviewed By:</b> Candy Li RF Engineer	<i>Candy Li</i>
<b>Test Laboratory:</b>	Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>

**Note:** This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

**TABLE OF CONTENTS**

**GENERAL INFORMATION.....3**

    PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....3

    OBJECTIVE .....3

    RELATED SUBMITTAL(S)/GRANT(S).....3

    TEST METHODOLOGY .....3

    TEST FACILITY .....3

**SYSTEM TEST CONFIGURATION.....4**

    DESCRIPTION OF TEST CONFIGURATION .....4

    EQUIPMENT MODIFICATIONS .....4

    BLOCK DIAGRAM OF TEST SETUP .....4

**SUMMARY OF TEST RESULTS .....5**

**FCC §2.1093 - RF EXPOSURE INFORMATION .....6**

    APPLICABLE STANDARD .....6

**FCC §2.1046 & §95.639(d) - RF OUTPUT POWER.....7**

    APPLICABLE STANDARD .....7

    TEST PROCEDURE .....7

    TEST EQUIPMENT LIST AND DETAILS.....7

    TEST DATA .....8

**FCC §2.1047 & §95.637(a) - MODULATION CHARACTERISTIC .....9**

    APPLICABLE STANDARD .....9

    TEST EQUIPMENT LIST AND DETAILS.....9

    TEST PROCEDURE .....9

    TEST DATA .....9

**FCC §2.1049 & §95.633(c) & §95.635 (b) (1) (3) (7) - AUTHOURIZED BANDWIDTH AND EMISSION MASK.....15**

    APPLICABLE STANDARD .....15

    TEST PROCEDURE .....15

    TEST EQUIPMENT LIST AND DETAILS.....15

    TEST DATA .....16

**FCC §2.1053 & §95.635(b) (7) - RADIATED SPURIOUS EMISSION.....18**

    APPLICABLE STANDARD .....18

    TEST PROCEDURE .....18

    TEST EQUIPMENT LIST AND DETAILS.....18

    TEST DATA .....19

**FCC§2.1055 (d) & §95.626(b) - FREQUENCY STABILITY .....20**

    APPLICABLE STANDARD .....20

    TEST PROCEDURE .....20

    TEST EQUIPMENT LIST AND DETAILS.....20

    TEST DATA .....21

## GENERAL INFORMATION

---

### Product Description for Equipment Under Test (EUT)

The *Kiddesigns Inc's* product, model number: *TR-202(FCC ID: IAJ202C)* in this report is a *XX-202 Walkie Talkies*, which was measured approximately: 20 cm (L) x 12 cm (W) x 6.5cm (H), rated with input voltage: DC 1.5V\*4 LR44 cell battery.

*Note: This series products model: AV-202, DX-202, DP-202, FD-202, HY-202, LG-202, MA-202, MS-202MM, PK-202, PW-202, PW-202CH, PW-202MA, SL-202, SM-202, SW-202B7, SW-202E7 and TR-202 are identical in schematics, just product appearance color is different, the detailed information can be referred to the declaration letter that stated and guaranteed by the applicant.*

*\* All measurement and test data in this report was gathered from production sample serial number: 1605801. (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2016-05-20.*

### Objective

This report is prepared on behalf of *Kiddesigns Inc* in accordance with Part 2 and Part 95, Subpart B & Subpart E of the Federal Communication Commissions rules.

### Related Submittal(s)/Grant(s)

No related submittal(s).

### Test Methodology

All tests and measurements indicated in this document were performed in accordance with Part 95 Subpart B and Subpart E of the Federal Communication Commissions rules with TIA-603-D, Land Mobile FM or PM-Communications Equipment-Measurement and Performance Standards.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

### Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on October 31, 2013. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

## SYSTEM TEST CONFIGURATION

---

### Description of Test Configuration


The system was configured for testing in a typical fashion (as normally used by a typical user).

Note: EUT Transmit only at Frequency 462.5625 MHz for FRS Unit.

### Equipment Modifications

No modification was made to the EUT tested.

### Block Diagram of Test Setup



**SUMMARY OF TEST RESULTS**

<b>FCC Rules</b>	<b>Description of Test</b>	<b>Results</b>
§2.1093	RF Exposure	Compliance
§2.1046, §95.639(d)	RF Output Power	Compliance
§2.1047, §95.637(a)	Modulation Characteristic	Compliance
§2.1049, §95.633 (c), §95.635 (b) (1) (3) (7)	Authorized Bandwidth & Emission Mask	Compliance
§2.1053, §95.635(b) (7)	Spurious Radiated Emissions	Compliance
§2.1055(d), §95.626(b)	Frequency Stability	Compliance

## **FCC §2.1093 - RF EXPOSURE INFORMATION**

### **Applicable Standard**

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

1.  $f(\text{GHz})$  is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test Exclusion.

For worst case:

The Max Tune-up Output Power:

3mW@462.5625MHz

3mW\*50%=1.5mW

$(1.5/5) \cdot \sqrt{0.462} = 0.2 < 3.0$

**Result: SAR test is not needed.**

## FCC §2.1046 & §95.639(d) - RF OUTPUT POWER

### Applicable Standard

Per FCC §2.1046, and §95.639(d), No FRS Unit, under any condition of modulation, shall exceed a 0.5 W effective radiated power (ERP).

### Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load, which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the emissions were measured by the substitution.

### Test Equipment List and Details

Manufacturer	Description	Model NO.	Serial NO.	Calibration Date	Calibration Due Date
HP	Signal Generator	8648C	3426A01345	2016-06-09	2017-06-09
HP	Amplifier	8447E	1937A01046	2016-05-06	2017-05-06
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2015-12-15	2016-12-14
Sunol Sciences	Bi-log Antenna	JB1	A040904-2	2014-12-07	2017-12-06
Ducommun technologies	RF Cable	UFA210A-1-4724-30050U	MFR64369 223410-001	2016-06-15	2017-06-15
Ducommun technologies	RF Cable	104PEA	218124002	2016-06-15	2017-06-15
Com Power	Dipole Antenna	AD-100	041000	2015-08-18	2016-08-18

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

**Test Data**

**Environmental Conditions**

<b>Temperature:</b>	26 °C
<b>Relative Humidity:</b>	60 %
<b>ATM Pressure:</b>	101.0 kPa

The testing was performed by Hill He on 2016-08-12.

Test Mode: Transmitting

Indicated		Table Angle Degree	Test Ant.		Substituted			Absolute Level (dBm)	FCC Part 95	
Frequency (MHz)	S.A. Reading (dBµV)		Height (m)	Polar (H/V)	S.G. Level (dBm)	Cable Loss (dB)	Ant. Gain (dB)		ERP (mW)	Limit (Watt)
FRS 462.5625MHz										
462.5625	98.17	259	2.1	H	2.2	0.47	0	1.73	1.49	0.5
462.5625	100.36	347	2.3	V	4.4	0.47	0	3.93	2.47	0.5

**Test Result:** Compliance.



## FCC §2.1047 & §95.637(a) - MODULATION CHARACTERISTIC

### Applicable Standard

Per FCC §2.1047 and §95.637(a): A GMRS transmitter that transmits emission type F3E must not exceed a peak frequency deviation of plus or minus 5 kHz. A FRS unit that transmits emission type F3E must not exceed a peak frequency deviation of plus or minus 2.5 kHz, and the audio frequency response must not exceed 3.125 kHz .

Each GMRS transmitter, except a mobile station transmitter with a power output of 2.5 W or less, must automatically prevent a greater than normal audio level from causing over-modulation. The transmitter also must include audio frequency low pass filtering, unless it complies with the applicable paragraphs of § 95.631 (without filtering.) The filter must be between the modulation limiter and the modulated stage of the transmitter. At any frequency (f in kHz) between 3 and 20 kHz, the filter must have an attenuation of at least  $60 \log_{10} (f/3)$  dB greater than the attenuation at 1 kHz. Above 20 kHz, it must have an attenuation of at least 50 dB greater than the attenuation at 1 kHz.

### Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due Date
HP	RF Communication Test Set	HP8920A	3438A05201	2015-06-14	2016-06-13
Ducommun technologies	RF Cable	RG-214	4	2015-06-15	2016-06-15

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

### Test Procedure

Test Method: TIA/EIA-603-D

### Test Data

#### Environmental Conditions

Temperature:	26 °C
Relative Humidity:	60 %
ATM Pressure:	101.0 kPa

*The testing was performed by Hill He on 2016-06-04.*


Please refer to the following tables and plots.

*Test Mode: Transmitting*

**Audio Frequency Response**

Carrier Frequency: 462.5625 MHz


<b>Audio Frequency (Hz)</b>	<b>Response Attenuation (dB)</b>
300	-10.19
400	-7.82
500	-5.88
600	-4.17
700	-3.12
800	-2.18
900	-1.26
1000	0.00
1200	1.28
1400	2.39
1600	3.38
1800	4.60
2000	5.15
2100	5.45
2200	5.88
2300	6.29
2400	6.49
2500	6.56
2600	6.56
2700	6.81
2800	7.06
2900	7.08
3000	6.29



**MODULATION LIMITING**

Carrier Frequency: 462.5625MHz


Audio Frequency (Hz)	Instantaneous		Steady-state		FCC Limit [kHz]
	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	
300	2.339	0.117	2.333	0.100	2.5
400	2.464	0.123	2.370	0.114	2.5
500	2.454	0.141	2.419	0.135	2.5
600	2.349	0.150	2.315	0.146	2.5
700	2.314	0.161	2.273	0.154	2.5
800	2.390	0.175	2.334	0.170	2.5
900	2.339	0.181	2.336	0.177	2.5
1000	2.457	0.197	2.456	0.191	2.5
1200	2.434	0.231	2.367	0.225	2.5
1400	2.456	0.249	2.382	0.247	2.5
1600	2.391	0.286	2.316	0.270	2.5
1800	2.451	0.331	2.360	0.308	2.5
2000	2.406	0.335	2.368	0.321	2.5
2100	2.362	0.341	2.310	0.334	2.5
2200	2.404	0.359	2.366	0.354	2.5
2300	2.386	0.386	2.376	0.372	2.5
2400	2.396	0.381	2.335	0.376	2.5
2500	2.403	0.389	2.340	0.378	2.5
2600	2.399	0.391	2.310	0.385	2.5
2700	2.406	0.414	2.367	0.397	2.5
2800	2.419	0.414	2.336	0.406	2.5
2900	2.418	0.413	2.338	0.404	2.5
3000	2.407	0.389	2.357	0.373	2.5



**Audio frequency Low Pass Filter Response**

Carrier Frequency: 462.5625 MHz

Audio Frequency (kHz)	Response Attenuation (dB)	FCC Limit (dB)
2.5	-3.79	/
3.0	-6.16	0.0
3.5	-9.23	-4.0
4.0	-13.16	-7.5
5.0	-18.59	-13.3
7.0	-30.31	-22.1
10.0	-42.34	-31.4
15.0	-54.49	-42.0
20.0	-56.07	-50.0
30.0	-55.39	-50.0
50.0	-56.56	-50.0
70.0	-56.07	-50.0



## FCC §2.1049 & §95.633(c) & §95.635 (b) (1) (3) (7) - AUTHORIZED BANDWIDTH AND EMISSION MASK

### Applicable Standard

According to §95.633(c), the authorized bandwidth for emission type F3E or F2D transmitted by a FRS unit is 12.5 kHz.

According to §95.635(b) (1) (3) (7), the power of each unwanted emission shall be less than TP as specified in the applicable paragraphs listed in the following :

1) At least 25 dB (decibels) on any frequency removed from the center of the authorized bandwidth by more than 50% up to and including 100% of the authorized bandwidth.

3) At least 35 dB on any frequency removed from the center of the authorized bandwidth by more than 100% up to and including 250% of the authorized bandwidth.

7) At least  $43 + 10 \log_{10}(T)$  dB on any frequency removed from the center of the authorized bandwidth by more than 250%.

### Test Procedure

TIA-603-D, section 2.2.11

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	RF Communication Test Set	HP8920A	3438A05201	2016-06-14	2017-06-13
Ducommun technologies	RF Cable	RG-214	4	2015-06-15	2016-06-15
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2015-12-11	2016-12-11

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

**Test Data**

**Environmental Conditions**


<b>Temperature:</b>	26 °C
<b>Relative Humidity:</b>	60 %
<b>ATM Pressure:</b>	101.0 kPa

The testing was performed by Hill He on 2016-06-14.

Test Mode: Transmitting


Item	Frequency (MHz)	20dB Bandwidth (kHz)	Limit (kHz)	Result
FRS	462.5625	5.61	12.5	Pass

**20dB Bandwidth**





### Emission Mask



## **FCC §2.1053 & §95.635(b) (7) - RADIATED SPURIOUS EMISSION**

### **Applicable Standard**

FCC §2.1053 and §95.635(b) (7)

### **Test Procedure**

The transmitter was placed on a wooden turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = 10 lg (TXpwr in Watts/0.001)-the absolute level  
Spurious attenuation limit in dB = 43+10 Log<sub>10</sub> (power out in Watts)

### **Test Equipment List and Details**

<b>Manufacturer</b>	<b>Description</b>	<b>Model</b>	<b>Serial Number</b>	<b>Calibration Date</b>	<b>Calibration Due Date</b>
Sunol Sciences	Horn Antenna	DRH-118	A052604	2014-12-29	2017-12-28
Sunol Sciences	Bi-log Antenna	JB1	A040904-2	2014-12-07	2017-12-06
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2015-12-11	2016-12-11
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2015-12-15	2016-12-14
Mini	Pre-amplifier	ZVA-183-S+	5969001149	201604-23	2017-04-23
HP	Amplifier	HP8447E	1937A01046	2016-05-06	2017-05-06
HP	Signal Generator	HP 8341B	2624A00116	2015-07-02	2016-07-01
COM POWER	Dipole Antenna	AD-100	041000	2015-08-18	2016-08-18
Ducommun technologies	RF Cable	UFA210A-1-4724-30050U	MFR64369 223410-001	2015-06-15	2016-06-15
Ducommun technologies	RF Cable	104PEA	218124002	2015-06-15	2016-06-15
Ducommun technologies	RF Cable	RG-214	1	2015-06-15	2016-06-15
Ducommun technologies	RF Cable	RG-214	2	2015-06-15	2016-06-15

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

**Test Data**

**Environmental Conditions**

<b>Temperature:</b>	26 °C
<b>Relative Humidity:</b>	60 %
<b>ATM Pressure:</b>	101.0 kPa

The testing was performed by Hill He on 2016-06-14.

Test Mode: Transmitting

Indicated		Table Angle Degree	Test Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
Frequency (MHz)	Receiver Reading (dBuV)		Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)			
FRS: 462.5625 MHz										
925.13	44.77	228	1.6	H	-52.2	0.70	0	-52.90	-13	39.90
925.13	46.61	71	1.6	V	-50.4	0.70	0	-51.10	-13	38.10
1387.69	52.98	100	1.7	H	-55.5	1.20	6.40	-50.30	-13	37.30
1387.69	52.68	283	1.3	V	-55.8	1.20	6.40	-50.60	-13	37.60
1850.25	45.26	349	1.4	H	-62.1	1.40	7.30	-56.20	-13	43.20
1850.25	45.81	160	1.0	V	-62.1	1.40	7.30	-56.20	-13	43.20
2312.81	57.09	265	1.2	H	-46.3	1.30	8.30	-39.30	-13	26.30
2312.81	57.61	176	1.5	V	-46.0	1.30	8.30	-39.00	-13	26.00
2775.38	51.66	268	1.1	H	-52.8	1.60	9.40	-45.00	-13	32.00
2775.38	53.41	300	1.5	V	-51.2	1.60	9.40	-43.40	-13	30.40
3237.94	58.81	101	1.4	H	-42.6	1.70	9.70	-34.60	-13	21.60
3237.94	57.54	277	1.2	V	-43.8	1.70	9.70	-35.80	-13	22.80
3700.50	41.17	340	1.6	H	-60.1	1.80	10.00	-51.90	-13	38.90
3700.50	41.93	25	1.5	V	-59.7	1.80	10.00	-51.50	-13	38.50

**Note:**

- 1) Absolute Level = SG Level - Cable loss + Antenna Gain
- 2) Margin = Limit- Absolute Level

## **FCC§2.1055 (d) & §95.626(b) - FREQUENCY STABILITY**

### **Applicable Standard**

According to FCC §2.1055(a) (1), the frequency stability shall be measured with variation of ambient temperature from –30 °C to +50 °C, and according to FCC 2.1055(d) (2), the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point which is specified by the manufacturer.

According to FCC §95.626(b), Each FRS unit must be maintained within a frequency tolerance of 0.00025%( 2.5 ppm).

### **Test Procedure**

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to a Frequency Counter via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the Frequency Counter.

Frequency Stability vs. Voltage:

1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

(2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.

The output frequency was recorded for each voltage.

### **Test Equipment List and Details**

<b>Manufacturer</b>	<b>Description</b>	<b>Model NO.</b>	<b>Serial NO.</b>	<b>Calibration Date</b>	<b>Calibration Due Date</b>
Hewlett-Packard	Frequency Counter	5343A	2232A00827	2016-05-09	2019-05-08
Ducommun technologies	RF Cable	RG-214	4	2015-06-15	2016-06-15
ESPEC	Temperature & Humidity Chamber	EL-10KA	09107726	2015-11-24	2016-11-23

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

**Test Data**

**Environmental Conditions**

<b>Temperature:</b>	26 °C
<b>Relative Humidity:</b>	60 %
<b>ATM Pressure:</b>	101.0 kPa

The testing was performed by Hill He on 2016-06-14.

Test Mode: Transmitting

**FRS – 462.5625 MHz**

<b>Reference Frequency: 462.5625 MHz, Limit: ±2.5 ppm</b>			
<b>Environment Temperature (°C)</b>	<b>Voltage Supplied (V<sub>DC</sub>)</b>	<b>Measurement Frequency (MHz)</b>	<b>Frequency Error (ppm)</b>
Frequency Stability Ver. Temperature			
50	6.0	462.562734	0.506
40	6.0	462.562799	0.646
30	6.0	462.562859	0.776
20	6.0	462.562812	0.675
10	6.0	462.562831	0.716
0	6.0	462.562807	0.664
-10	6.0	462.562936	0.943
-20	6.0	462.562619	0.257
-30	6.0	462.562577	0.166
Frequency Stability Ver. Input Voltage			
20	4.5	462.562879	0.819

**\*\*\*\*\* END OF REPORT \*\*\*\*\***