



2.2 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories are used to form representative test configuration during the tests.

No.	Product	Brand	Model No.	FCC ID.	I/O Cable
1.	PERSONAL COMPUTER	HP	D5220B	FCC Doc Approved	Nonshielded Power (1.8m)
2.	KEYBOARD	FORWARD	FDA-104GA	F4ZDA-104G	Shielded Signal (1.5m)
3.	PRINTER	HP	2225C+	DSI6XU2225	Shielded Signal (1.5m) Nonshielded Power (1.8m)
4.	MODEM	ACEEX	1414	IFAXDM1414	Shielded signal (1.5m) Nonshielded Power (1.8m)
5.	MOUSE	DEXIN	A2P800A	NIYA2P800A	Shielded signal (1.5m)
6.	CCD CAMERA	COMPAQ	YC72-CPQ	EDUYC72-CPQ	Shielded signal (1.5m)
7.	VGA CARD	GORDIA	DSV3365	LUT-DSV3365	N/A
8.	SOUND CARD	AZTECH	5064-2620	I38-SN96116	N/A

Note: 1. Support unit 6 was connected to the USB port of EUT.

2. Three USB cables (each 1.8m) were connected to the three USB ports of EUT to form three open loop cables.

3. A USB cable (1.5m) was connected from EUT to PC.

4. An audio cable (1.5m) was connected from the EUT to PC.

2.3 TEST METHODOLOGY AND CONFIGURATION

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4:1992. Radiated testing was performed at an antenna to EUT distance of 10m on an open area test site.

Please refer to the photos of test configuration in Item 5.