



6. ATTACHMENT 1 - TECHNICAL DESCRIPTION OF EUT

Specifications:

* Panel Part:

LCD: 15.0" 1024x768 TFT (Thin Film Transistor)

* Monitor part:

Effective Display Size: (Diagonal) 15.0 inch (304 mm x 228 mm) – near 17"
CRT>A4 paper size

Resolution & Display Colors: XGA 1024x768 120 HZ/a-si
TFT 64/256K Color

Pixel pitch: 0.297 mm RGB Stripe

Brightness (Luminance): Two Lamps (CCFT) for Monitor 200 cd/m2
Type.

Contrast ratio: 200:1

Response time: 50 ms Type

View angle: Left/Right +/- 65 deg. (H), Up/Down +40/-60
deg. (V)

User controls:

Front panel POWER LED, POWER Key, Adjust/Brightness
(+/-), Volume (+/-), Left, Right, Menu

Rear Cover Analog Video In, DC In Jack (+12V/+6V),
USB In/Out, Audio In

Signal Cable: 1.8 m Long 15Pin VGA analog signal Cable

Signal Cable: Locally (Self) powered pure Hub, supporting
full speed USB 1 upstream(B Type Receptacle),
4 downstream (A Type Dualport Receptacle)

* Power Supply:

35 Watts Max. (ON), Power Down Mode < 8
Watts (SUSPEND/OFF)

AC/DC Adapter: Input: 100-240 Vac, 1A, 50-60 Hz

Output: 12 Vdc, 3A
6Vdc, 1A

* Dimension & Weight:

Size: Landscape: 380 x 376.5 x 170 mm (W x H x D)

Weight: Gross: TBD

Net: TBD