



Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Test Report

Prepared for: L-3 Aviation Products

Model: 228E5733-00

Description: AFIRS 228S Satellite Data Unit

Serial Number: N/A

FCC ID: IB2AFIRS228S0

To

FCC Part 1.1310

Date of Issue: November 14, 2017

On the behalf of the applicant:

L-3 Aviation Products
PO Box 3041
Sarasota, FL 34232

Attention of:

Dan Gross, Program Manager
Ph: (941)371-0811
E-Mail: Dan.Gross@L3T.com

Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p1790002

Alex Macon
Project Test Engineer

This report may not be reproduced, except in full, without written permission from Compliance Testing
All results contained herein relate only to the sample tested



Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	October 20, 2017	Alex Macon	Original Document
2.0	November 14, 2017	Amanda Reed	Updated FCC ID

ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

EUT Description

Model: 228E5733-00

Description: AFIRS 228S Satellite Data Unit

Firmware: N/A

Software: N/A

Serial Number: N/A

Additional Information: The unit is a sitcom system used within aircrafts



Average Power calculations

Average Power = Peak Power * duty-cycle%

Tuned Frequency (MHz)	Conducted Peak Output Power (mW)	Duty Cycle (%)	Average Power (mW)
1620.9825	7570	100	7570



MPE Evaluation

This is a portable device used in Uncontrolled Exposure environment.

**Limits Uncontrolled Exposure
47 CFR 1.1310
Table 1, (B)**

0.3-1.234 MHz:	Limit [mW/cm ²] = 100
1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
30-300 MHz:	Limit [mW/cm ²] = 0.2
300-1500 MHz:	Limit [mW/cm ²] = f/1500
1500-100,000 MHz	Limit [mW/cm ²] = 1.0

Test Data

Test Frequency, MHz	1620.9825
Power, Conducted, mW (P)	7570
Antenna Gain Isotropic	3 dBi
Antenna Gain Numeric (G)	2
Antenna Type	Dipole
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$
Power Density (S) mw/cm ²

Power Density (S) = 3.012
Limit = (from above table) = 1

Minimum Safe Distance Evaluation

This is a mobile device used in Uncontrolled Exposure environment.

**Limits Uncontrolled Exposure
47 CFR 1.1310
Table 1, (B)**

0.3-1.234 MHz:	Limit [mW/cm ²] = 100
1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
30-300 MHz:	Limit [mW/cm ²] = 0.2
300-1500 MHz:	Limit [mW/cm ²] = f/1500
1500-100,000 MHz	Limit [mW/cm ²] = 1.0

Test Data

Test Frequency, MHz	1620.9825
Power, Conducted, mW (P)	7570
Antenna Gain Isotropic	3 dBi
Antenna Gain Numeric (G)	2
Antenna Type	Dipole
Limit (L)	1.0 mW/cm ²

R= $\sqrt{(PG/4\pi L)}$			
Distance (R) cm	Power mW (P)	Numeric Gain (G)	Limit (L)
34.72	7570	2	1

34.7cm is the minimum safe distance when utilized with a 3dBi antenna.

Note: Max output power value is obtained from associated report.

END OF TEST REPORT