

SAR TEST REPORT

REPORT NO.: SA980330H03

MODEL NO.: SB1170

RECEIVED: Mar. 30, 2009

TESTED: May 22, 2009

ISSUED: May 26, 2009

APPLICANT: Creative Technology Ltd

ADDRESS: 31 International Business Park, Creative Resource,
Singapore 609921

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,
Taipei Hsien 244, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan
Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This test report consists of 47 pages in total except Appendix. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by TAF or any government agencies. The test results in the report only apply to the tested sample.





A D T

TABLE OF CONTENTS

| | | |
|-------|---|----|
| 1. | CERTIFICATION..... | 3 |
| 2. | GENERAL INFORMATION..... | 4 |
| 2.1 | GENERAL DESCRIPTION OF EUT | 4 |
| 2.2 | GENERAL DESCRIPTION OF APPLIED STANDARDS | 5 |
| 2.3 | GENERAL INFORMATION OF THE SAR SYSTEM | 6 |
| 2.4 | GENERAL DESCRIPTION OF THE SPATIAL PEAK SAR EVALUATION | 9 |
| 3. | DESCRIPTION OF SUPPORT UNITS | 12 |
| 4. | DESCRIPTION OF TEST MODES AND CONFIGURATIONS | 13 |
| 4.1. | DESCRIPTION OF ANTENNA LOCATION | 13 |
| 4.2. | DESCRIPTION OF ASSESSMENT POSITION | 14 |
| 4.3. | DESCRIPTION OF TEST MODE | 16 |
| 4.4. | SUMMARY OF TEST RESULTS | 17 |
| 4.5. | CHECK FOR SCAN RESOLUTION | 17 |
| 4.6. | ENHANCED ENERGY COUPLING AT INCREASED SEPARATION DISTANCES..... | 18 |
| 5. | TEST RESULTS | 19 |
| 5.1 | TEST PROCEDURES | 19 |
| 5.2 | MEASURED SAR RESULTS..... | 21 |
| 5.3 | SAR LIMITS | 22 |
| 5.4 | RECIPES FOR TISSUE SIMULATING LIQUIDS | 23 |
| 5.5 | TEST EQUIPMENT FOR TISSUE PROPERTY | 26 |
| 6. | SYSTEM VALIDATION | 27 |
| 6.1 | TEST EQUIPMENT | 27 |
| 6.2 | TEST PROCEDURE..... | 28 |
| 6.3 | VALIDATION RESULTS..... | 30 |
| 6.4 | SYSTEM VALIDATION UNCERTAINTIES | 31 |
| 7. | MEASUREMENT SAR PROCEDURE UNCERTAINTIES | 32 |
| 7.1. | PROBE CALIBRATION UNCERTAINTY | 32 |
| 7.2. | ISOTROPY UNCERTAINTY..... | 33 |
| 7.3. | BOUNDARY EFFECT UNCERTAINTY..... | 33 |
| 7.4. | PROBE LINEARITY UNCERTAINTY | 34 |
| 7.5. | READOUT ELECTRONICS UNCERTAINTY | 34 |
| 7.6. | RESPONSE TIME UNCERTAINTY | 34 |
| 7.7. | INTEGRATION TIME UNCERTAINTY | 35 |
| 7.8. | PROBE POSITIONER MECHANICAL TOLERANCE | 36 |
| 7.9. | PROBE POSITIONING..... | 36 |
| 7.10. | PHANTOM UNCERTAINTY | 37 |
| 7.11. | DASY4 UNCERTAINTY BUDGET | 38 |
| 8. | PHOTOGRAPHS OF THE EUT | 39 |
| 9. | INFORMATION ON THE TESTING LABORATORIES..... | 47 |
| | APPENDIX A: TEST CONFIGURATIONS AND TEST DATA | |
| | APPENDIX B: BV ADT SAR MEASUREMENT SYSTEM | |
| | APPENDIX C: PHOTOGRAPHS OF SYSTEM VALIDATION | |
| | APPENDIX D: SYSTEM CERTIFICATE & CALIBRATION | |

1. CERTIFICATION

PRODUCT: Wireless Transmitter
MODEL: SB1170
TRADE NAME: Creative Labs
APPLICANT: Creative Technology Ltd
TESTED: May 22, 2009
TEST SAMPLE: 2P Samples
STANDARDS: **FCC Part 2 (Section 2.1093)**
FCC OET Bulletin 65, Supplement C (01-01)
RSS-102

The above equipment (model: SB1170) have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Wendy Liao , **DATE:** May 26, 2009
Wendy Liao / Senior Specialist

TECHNICAL ACCEPTANCE : James Fan , **DATE:** May 26, 2009
Responsible for RF
James Fan / Engineer

APPROVED BY : Gary Chang , **DATE:** May 26, 2009
Gary Chang / Assistant Manager

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

| | |
|--|---|
| PRODUCT | Wireless Transmitter |
| MODEL NO. | SB1170 |
| FCC ID | IBAAVPSB1170 |
| POWER SUPPLY | 5Vdc from host equipment |
| CLASSIFICATION | Portable device, production unit |
| MODULATION TYPE | QPSK |
| RADIO TECHNOLOGY | DSSS |
| TRANSFER RATE | 22.0Mbps |
| FREQUENCY RANGE | 2412MHz ~ 2464MHz |
| NUMBER OF CHANNEL | 3 |
| CHANNEL FREQUENCIES UNDER TEST AND ITS CONDUCTED OUTPUT POWER | 39.628mW / Low channel: 2412MHz 34.514mW / Middle channel: 2438MHz 29.376mW / High channel: 2464MHz |
| MAXIMUM SAR (1g) | 1.070W/kg |
| ANTENNA TYPE | Dipole antenna with 1.79dBi gain |
| DATA CABLE | NA |
| I/O PORTS | Refer to user's manual |
| ACCESSORY DEVICES | NA |

NOTE: The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

2.2 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to the specifications of the manufacturer, this product must comply with the requirements of the following standards:

FCC Part 2 (2.1093)

FCC OET Bulletin 65, Supplement C (01- 01)

RSS-102

IEEE 1528-2003

All test items have been performed and recorded as per the above standards.

2.3 GENERAL INFORMATION OF THE SAR SYSTEM

DASY4 (**software 4.7 Build 80**) consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY4 software defined. The DASY4 software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.

EX3DV3 ISOTROPIC E-FIELD PROBE

| | |
|----------------------|--|
| CONSTRUCTION | Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE) |
| FREQUENCY | 10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz) |
| DIRECTIVITY | ± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis) |
| DYNAMIC RANGE | 10 μ W/g to > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g) |
| DIMENSIONS | Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm |
| APPLICATION | High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%. |

NOTE

1. The Probe parameters have been calibrated by the SPEAG. Please reference "APPENDIX D" for the Calibration Certification Report.
2. For frequencies above 800MHz, calibration in a rectangular wave-guide is used, because wave-guide size is manageable.
3. For frequencies below 800MHz, temperature transfer calibration is used because the wave-guide size becomes relatively large.

TWIN SAM V4.0

CONSTRUCTION

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528-2003, EN 62209-1 and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.

SHELL THICKNESS

$2 \pm 0.2\text{mm}$

FILLING VOLUME

Approx. 25liters

DIMENSIONS

Height: 810mm; Length: 1000mm; Width: 500mm

SYSTEM VALIDATION KITS:

CONSTRUCTION

Symmetrical dipole with $1/4$ balun enables measurement of feedpoint impedance with NWA matched for use near flat phantoms filled with brain simulating solutions. Includes distance holder and tripod adaptor

CALIBRATION

Calibrated SAR value for specified position and input power at the flat phantom in brain simulating solutions

FREQUENCY

2450MHz

RETURN LOSS

> 20dB at specified validation position

POWER CAPABILITY

> 100W ($f < 1\text{GHz}$); > 40W ($f > 1\text{GHz}$)

OPTIONS

Dipoles for other frequencies or solutions and other calibration conditions upon request

DEVICE HOLDER FOR SAM TWIN PHANTOM

CONSTRUCTION

The device holder for the mobile phone device is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation centers for both scales is the ear reference point (ERP). Thus the device needs no repositioning when changing the angles. The holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity $\varepsilon = 3$ and loss tangent $\delta = 0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered. The device holder for the portable device makes up of the polyethylene foam. The dielectric parameters of material close to the dielectric parameters of the air.

DATA ACQUISITION ELECTRONICS

CONSTRUCTION

The data acquisition electronics (DAE4) consists of a highly sensitive electrometer grade preamplifier with auto-zeroing, a channel and gain-switching multiplex, a fast 16 bit AD converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock. The mechanical probe is mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection. The input impedance of the DAE4 box is 200M Ω ; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

2.4 GENERAL DESCRIPTION OF THE SPATIAL PEAK SAR EVALUATION

The DASY4 post-processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the micro-volt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

| | | |
|--------------------|---------------------------|---|
| Probe parameters: | - Sensitivity | Norm _i , a _{i0} , a _{i1} , a _{i2} |
| | - Conversion factor | ConvF _i |
| | - Diode compression point | dcp _i |
| Device parameters: | - Frequency | F |
| | - Crest factor | Cf |
| Media parameters: | - Conductivity | σ |
| | - Density | ρ |

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

| | | |
|------------------|----------------------------------|------------------|
| V _i | =compensated signal of channel i | (i = x, y, z) |
| U _i | =input signal of channel i | (i = x, y, z) |
| Cf | =crest factor of exciting field | (DASY parameter) |
| dcp _i | =diode compression point | (DASY parameter) |

From the compensated input signals the primary field data for each channel can be evaluated:

$$\text{E-field probes: } E_i = \sqrt{\frac{V_i}{\text{Norm}_i \cdot \text{ConvF}}}$$

$$\text{H-field probes: } H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

| | | |
|-----------------|--|---------------|
| V_i | =compensated signal of channel i | (i = x, y, z) |
| Norm_i | =sensor sensitivity of channel i $\mu\text{V}/(\text{V/m})^2$ for E-field Probes | (i = x, y, z) |
| ConvF | = sensitivity enhancement in solution | |
| a_{ij} | = sensor sensitivity factors for H-field probes | |
| f | = carrier frequency [GHz] | |
| E_i | = electric field strength of channel i in V/m | |
| H_i | = magnetic field strength of channel i in A/m | |

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1'000}$$

| | |
|-----------|--|
| SAR | = local specific absorption rate in mW/g |
| E_{tot} | = total field strength in V/m |
| σ | = conductivity in [mho/m] or [Siemens/m] |
| ρ | = equivalent tissue density in g/cm ³ |

Note that the density is set to 1, to account for actual head tissue density rather than the density of the tissue simulating liquid. The entire evaluation of the spatial peak values is performed within the Post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

1. The extraction of the measured data (grid and values) from the Zoom Scan
2. The calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
3. The generation of a high-resolution mesh within the measured volume
4. The interpolation of all measured values from the measurement grid to the high-resolution grid
5. The extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
6. The calculation of the averaged SAR within masses of 1g and 10g.

The probe is calibrated at the center of the dipole sensors that is located 1 to 2.7mm away from the probe tip. During measurements, the probe stops shortly above the phantom surface, depending on the probe and the surface detecting system. Both distances are included as parameters in the probe configuration file. The software always knows exactly how far away the measured point is from the surface. As the probe cannot directly measure at the surface, the values between the deepest measured point and the surface must be extrapolated. The angle between the probe axis and the surface normal line is less than 30 degree.

The maximum search is automatically performed after each area scan measurement. It is based on splines in two or three dimensions. The procedure can find the maximum for most SAR distributions even with relatively large grid spacing. After the area scanning measurement, the probe is automatically moved to a position at the interpolated maximum. The following scan can directly use this position for reference, e.g., for a finer resolution grid or the cube evaluations. The 1g and 10g peak evaluations are only available for the predefined cube 7 x 7 x 7 scans. The routines are verified and optimized for the grid dimensions used in these cube measurements. The measured volume of 30 x 30 x 30mm contains about 30g of tissue. The first procedure is an extrapolation (incl. boundary correction) to get the points between the lowest measured plane and the surface. The next step uses 3D interpolation to get all points within the measured volume in a 1mm grid (42875 points). In the last

step, a 1g cube is placed numerically into the volume and its averaged SAR is calculated. This cube is moved around until the highest averaged SAR is found. If the highest SAR is found at the edge of the measured volume, the system will issue a warning: higher SAR values might be found outside of the measured volume. In that case the cube measurement can be repeated, using the new interpolated maximum as the center.

3. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| NO. | PRODUCT | BRAND | MODEL NO. | SERIAL NO. | FCC ID |
|-----|----------|-------|-----------|-------------|------------------|
| 1 | NOTEBOOK | DELL | PP18L | 29144041120 | CXSMM01BRD02D330 |

| NO. | SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS |
|-----|---|
| 1 | NA |

NOTE: All power cords of the above support units are non shielded (1.8m).





4. DESCRIPTION OF TEST MODES AND CONFIGURATIONS

4.1. DESCRIPTION OF ANTENNA LOCATION




4.2. DESCRIPTION OF ASSESSMENT POSITION

The following test configurations have been applied in this test report:


| | |
|---|---|
|  |  |
| <p style="text-align: center;">A</p> <p>The bottom of the EUT faces to the phantom with 5mm-separation distance.</p> | <p style="text-align: center;">B</p> <p>The right edge of the EUT faces to the phantom with 5mm-separation distance.</p> |
|  |  |
| <p style="text-align: center;">C</p> <p>The front of the EUT faces to the phantom with 5mm-separation distance.</p> | <p style="text-align: center;">D</p> <p>The left edge of the EUT faces to the phantom with 5mm-separation distance.</p> |


E

The tip of the EUT faces to the phantom with 0mm-separation distance.


F

The bottom of the EUT faces to the phantom with 5mm-separation distance.


SETUP PHOTO

4.3. DESCRIPTION OF TEST MODE

Test tool is embeded in the EUT. It can control EUT to transmit continuously at specific channel, output power level, data rates and 100 % duty signal.

“Per KDB 248277, for each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of these configurations is less than $\frac{1}{4}$ dB higher than those measured at the lowest data rate.”

This EUT only support one modulation type and data rates. Therefore, no concern about this issue.

“Per KDB 447498, when the SAR procedures require multiple channels to be tested and the 1-g SAR for the highest output channel is less than 0.8 W/kg and peak SAR is less than 1.6W/kg, where the transmission band corresponding to all channels is \leq 100 MHz, testing for the other channels is not required.”

According to test data from table of section 4.4, except mode 4, SAR value of highest output power channel for other modes are less than 0.8 W/kg and Peak SAR values are less than 1.6W/kg. Therefore, testing for other channels is not required except mode 4.

| ITEM | TEST MODE | MODULATION | ASSESSMENT POSTITION | TESTED CHANNEL |
|------|-----------|------------|----------------------|----------------|
| 1 | DSSS | QPSK | A | L |
| 2 | DSSS | QPSK | B | L |
| 3 | DSSS | QPSK | C | L |
| 4 | DSSS | QPSK | D | L, M, H |
| 5 | DSSS | QPSK | E | L |
| 6 | DSSS | QPSK | F | L |

4.4. SUMMARY OF TEST RESULTS

| ITEM | | 1 | 2 | 3 |
|-----------|-------------|----------------------------------|-------|-------|
| TEST MODE | | DSSS | | |
| CHAN. | FREQ. (MHz) | MEASURED VALUE OF 1g SAR (W/kg) | | |
| Low | 2412 | 0.743 | 0.021 | 0.665 |

| ITEM | | 4 | 5 | 6 |
|-----------|-------------|----------------------------------|-------|-------|
| TEST MODE | | DSSS | | |
| CHAN. | FREQ. (MHz) | MEASURED VALUE OF 1g SAR (W/kg) | | |
| Low | 2412 | 1.070 | 0.491 | 0.273 |
| Mid. | 2438 | 0.907 | - | - |
| High | 2464 | 0.769 | - | - |

NOTE: The worst value has been marked by boldface.

4.5. CHECK FOR SCAN RESOLUTION

COMPARE WITH DIFFERENT SCAN RESOLUTION

With EUT hold on the worst case configuration (Low channel in test mode 4) with no any change in position or setting, 2 scans with different resolutions are preformed to evaluate the impact on the SAR value.

Test data as below:

| SCAN RESOLUTION (mm) | SAR VALUE (W/kg) |
|----------------------|------------------|
| 5 | 1.070 |
| 2.5 | 1.050 |

CONCLUSION: No meaningful change detected.

4.6. ENHANCED ENERGY COUPLING AT INCREASED SEPARATION DISTANCES

INITIAL POSITION:

With EUT hold on the worst channel of each configuration with no any change in position or setting, 2 scans with different resolutions are preformed to evaluate the impact on the SAR value.

5mm INCREMENTS FROM INITIAL POSITION:

With the probe fixed at this location, the device is moved away from the phantom in 5 mm increments from the initial touching or minimum separation position. A single point SAR is measured for each of these device positions until the SAR is less than 50% of that measured at the initial position.

| CHAN. | FREQ. (MHZ) | DEVICE TEST POSITION MODE | INITIAL POSITION MEASURED 1g SAR (W/kg) | 5 mm INCREMENTS FROM INITIAL POSITION MEASURED 1g SAR (W/kg) | 10mm INCREMENTS FROM INITIAL POSITION MEASURED 1g SAR (W/kg) |
|-------|----------------|------------------------------|---|---|---|
| Low | 2412 | Bottom | 0.950 | 0.468 | - |
| Low | 2412 | Right edge | 0.135 | 0.077 | 0.048 |
| Low | 2412 | Front | 0.891 | 0.427 | - |
| Low | 2412 | Left edge | 1.908 | 0.804 | - |
| Low | 2412 | Tip | 0.993 | 0.424 | - |
| Low | 2412 | Bottom | 0.463 | 0.187 | - |

RESULT: No Enhancement Energy Coupling observed.

5. TEST RESULTS

5.1 TEST PROCEDURES

Use the software to control the EUT channel and transmission power. Then record the conducted power before the testing. Place the EUT to the specific test location. After the testing, must writing down the conducted power of the EUT into the report. The SAR value was calculated via the 3D spline interpolation algorithm that has been implemented in the software of DASY4 SAR measurement system manufactured and calibrated by SPEAG. According to the IEEE 1528 standards, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- Power reference measurement
- Verification of the power reference measurement
- Area scan
- Zoom scan
- Power reference measurement

The area scan was performed for the highest spatial SAR location. The zoom scan with 30mm x 30mm x 30mm volume was performed for SAR value averaged over 1g and 10g spatial volumes.

In the zoom scan, the distance between the measurement point at the probe sensor location (geometric center behind the probe tip) and the phantom surface is 4.0mm and maintained at a constant distance of ± 1.0 mm during a zoom scan to determine peak SAR locations. The distance is 4mm between the first measurement point and the bottom surface of the phantom. The secondary measurement point to the bottom surface of the phantom is with 9mm separation distance. The cube size is 7 x 7 x 7 points consist of 343 points and the grid space is 5mm.

The measurement time is 0.5s at each point of the zoom scan. The probe boundary effect compensation shall be applied during the SAR test. Because of the tip of the probe to the Phantom surface separated distances are longer than half a tip probe diameter.

In the area scan, the separation distance is 4mm between the each measurement point and the phantom surface. The scan size shall be included the transmission portion of the EUT. The measurement time is the same as the zoom scan. At last the reference power drift shall be less than $\pm 5\%$.

5.2 MEASURED SAR RESULTS

| ENVIRONMENTAL CONDITION | | Air Temperature : 23.5°C, Liquid Temperature : 22.7°C Humidity : 63%RH | | | | | |
|-------------------------|-------------|---|----------------------|------------|-----------------|---------------------------|------------------------|
| TESTED BY | | Sam Onn | | | DATE | | May 22, 2009 |
| CHAN. | FREQ. (MHz) | TEST MODE | CONDUCTED POWER (mW) | | POWER DRIFT (%) | DEVICE TEST POSITION MODE | MEASURED 1g SAR (W/kg) |
| | | | BEGIN TEST | AFTER TEST | | | |
| LOW | 2412 | DSSS | 39.628 | 39.283 | -0.87 | 1 | 0.743 |
| LOW | 2412 | DSSS | 39.628 | 39.259 | -0.93 | 2 | 0.021 |
| LOW | 2412 | DSSS | 39.628 | 39.212 | -1.05 | 3 | 0.665 |
| LOW | 2412 | DSSS | 39.628 | 39.180 | -1.13 | 4 | 1.070 |
| Mid. | 2438 | DSSS | 34.514 | 34.083 | -1.25 | 4 | 0.907 |
| High | 2464 | DSSS | 29.376 | 28.968 | -1.39 | 4 | 0.769 |
| LOW | 2412 | DSSS | 39.628 | 39.049 | -1.46 | 5 | 0.491 |
| LOW | 2412 | DSSS | 39.628 | 39.010 | -1.56 | 6 | 0.273 |

NOTE:

1. Test configuration of each mode is described in section 4.3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, **1.6 W/kg**, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.

5.3 SAR LIMITS

| HUMAN EXPOSURE | SAR (W/kg) | |
|--|---|--|
| | (GENERAL POPULATION / UNCONTROLLED EXPOSURE ENVIRONMENT) | (OCCUPATIONAL / CONTROLLED EXPOSURE ENVIRONMENT) |
| Spatial Average (whole body) | 0.08 | 0.4 |
| Spatial Peak (averaged over 1 g) | 1.6 | 8.0 |
| Spatial Peak (hands / wrists / feet / ankles averaged over 10 g) | 4.0 | 20.0 |

NOTE:

1. This limits accord to 47 CFR 2.1093 – Safety Limit.
2. The EUT property been complied with the partial body exposure limit under the general population environment.

5.4 RECIPES FOR TISSUE SIMULATING LIQUIDS

For the measurement of the field distribution inside the SAM phantom, the phantom must be filled with 25 liters of tissue simulation liquid.

The following ingredients are used :

- **WATER-** Deionized water (pure H₂O), resistivity $\geq 16 \text{ M}\Omega\cdot\text{cm}$ - as basis for the liquid
- **SUGAR-** Refined sugar in crystals, as available in food shops - to reduce relative permittivity
- **SALT-** Pure NaCl - to increase conductivity
- **CELLULOSE-** Hydroxyethyl-cellulose, medium viscosity (75-125mPa.s, 2% in water, 20°C),
CAS # 54290 - to increase viscosity and to keep sugar in solution
- **PRESERVATIVE-** Preventol D-7 Bayer AG, D-51368 Leverkusen, CAS # 55965-84-9 - to prevent the spread of bacteria and molds
- **DGMBE-** Diethylenglycol-monobuthyl ether (DGMBE), Fluka Chemie GmbH, CAS # 112-34-5 - to reduce relative permittivity

THE RECIPES FOR 2450MHz SIMULATING LIQUID TABLE

| INGREDIENT | HEAD SIMULATING LIQUID 2450MHz (HSL-2450) | MUSCLE SIMULATING LIQUID 2450MHz (MSL-2450) |
|-------------------------------------|--|--|
| Water | 45% | 69.83% |
| DGMBE | 55% | 30.17% |
| Salt | NA | NA |
| Dielectric Parameters at 22°C | f= 2450MHz $\epsilon = 39.2 \pm 5\%$ $\sigma = 1.80 \pm 5\% \text{ S/m}$ | f= 2450MHz $\epsilon = 52.7 \pm 5\%$ $\sigma = 1.95 \pm 5\% \text{ S/m}$ |

Testing the liquids using the Agilent Network Analyzer E5071C and Agilent Dielectric Probe Kit 85070D. The testing procedure is following as

1. Turn Network Analyzer on and allow at least 30min. warm up.
2. Mount dielectric probe kit so that interconnecting cable to Network Analyzer will not be moved during measurements or calibration.
3. Pour de-ionized water and measure water temperature ($\pm 1^\circ$).
4. Set water temperature in Agilent-Software (Calibration Setup).
5. Perform calibration.
6. Validate calibration with dielectric material of known properties (e.g. polished ceramic slab with $>8\text{mm}$ thickness $\epsilon' = 10.0$, $\epsilon'' = 0.0$). If measured parameters do not fit within tolerance, repeat calibration (± 0.2 for ϵ' : ± 0.1 for ϵ'').
7. Conductivity can be calculated from ϵ'' by $\sigma = \omega \epsilon_0 \epsilon'' = \epsilon'' f [\text{GHz}] / 18$.
8. Measure liquid shortly after calibration. Repeat calibration every hour.
9. Stir the liquid to be measured. Take a sample ($\sim 50\text{ml}$) with a syringe from the center of the liquid container.
10. Pour the liquid into a small glass flask. Hold the syringe at the bottom of the flask to avoid air bubbles.
11. Put the dielectric probe in the glass flask. Check that there are no air bubbles in front of the opening in the dielectric probe kit.
12. Perform measurements.
13. Adjust medium parameters in DASY4 for the frequencies necessary for the measurements ('Setup Config', select medium (e.g. Brain 900MHz) and press 'Option'-button.
14. Select the current medium for the frequency of the validation (e.g. Setup Medium Brain 900MHz).



A D T

FOR 2.4GHz BAND SIMULATING LIQUID

| LIQUID TYPE | | MSL-2450 | | |
|--|-------------------------------------|--|-------------------|----------------------|
| SIMULATING LIQUID TEMP. | | 23.5 | | |
| TEST DATE | | May 22, 2009 | | |
| TESTED BY | | Sam Onn | | |
| FREQ. (MHz) | LIQUID PARAMETER | STANDARD VALUE | MEASUREMENT VALUE | ERROR PERCENTAGE (%) |
| 2412.0 | Permittivity (ϵ) | 52.80 | 53.50 | 1.33 |
| 2438.0 | | 52.70 | 53.40 | 1.33 |
| 2450.0 | | 52.70 | 53.30 | 1.14 |
| 2464.0 | | 52.70 | 53.20 | 0.95 |
| 2412.0 | Conductivity (σ) S/m | 1.91 | 1.95 | 2.09 |
| 2438.0 | | 1.94 | 1.99 | 2.58 |
| 2450.0 | | 1.95 | 2.00 | 2.56 |
| 2464.0 | | 1.97 | 2.02 | 2.54 |
| Dielectric Parameters Required at 22°C | | f= 2450MHz ϵ = 52.7 ± 5% σ = 1.95 ± 5% S/m | | |

5.5 TEST EQUIPMENT FOR TISSUE PROPERTY

| ITEM | NAME | BAND | TYPE | SERIES NO. | DATE OF CALIBRATION | DUE DATE OF CALIBRATION |
|------|------------------|---------|--------|------------|---------------------|-------------------------|
| 1 | Network Analyzer | Agilent | E8358A | US41480538 | Nov. 27, 2008 | Nov. 26, 2009 |
| 2 | Dielectric Probe | Agilent | E9327A | US40441181 | Sep. 30, 2008 | Sep. 29, 2009 |

NOTE:

1. Before starting, all test equipment shall be warmed up for 30min.
2. The tolerance ($k=1$) specified by Agilent for general dielectric measurements, deriving from inaccuracies in the calibration data, analyzer drift, and random errors, are usually $\pm 2.5\%$ and $\pm 5\%$ for measured permittivity and conductivity, respectively. However, the tolerances for the conductivity is smaller for material with large loss tangents, i.e., less than $\pm 2.5\%$ ($k=1$). It can be substantially smaller if more accurate methods are applied.

6. SYSTEM VALIDATION

The system validation was performed in the flat phantom with equipment listed in the following table. Since the SAR value is calculated from the measured electric field, dielectric constant and conductivity of the body tissue, and the SAR is proportional to the square of the electric field. So, the SAR value will be also proportional to the RF power input to the system validation dipole under the same test environment. In our system validation test, 250mW RF input power was used.

6.1 TEST EQUIPMENT

| ITEM | NAME | BAND | TYPE | SERIES NO. | DATE OF CALIBRATION | DUE DATE OF CALIBRATION |
|------|-------------------|-------------------|--------------|------------|---------------------|-------------------------|
| 1 | SAM Phantom | S & P | QD000 P40 CA | TP-1150 | NA | NA |
| 2 | Signal Generator | Anritsu | 68247B | 984703 | May 27, 2008 | May 26, 2009 |
| 3 | E-Field Probe | S & P | EX3DV3 | 3504 | Jan. 21, 2009 | Jan. 20, 2010 |
| 4 | DAE | S & P | DAE | 510 | Jan. 21, 2009 | Jan. 20, 2010 |
| 5 | Robot Positioner | Staubli Unimation | NA | NA | NA | NA |
| 6 | Validation Dipole | S & P | D2450V2 | 716 | Mar. 17, 2009 | May 16, 2010 |
| 7 | Power Meter | Agilent | E4416A | GB41291763 | Sep. 30, 2008 | Sep. 29, 2009 |
| 8 | Power Sensor | | E8257C | MY43320668 | Dec. 31, 2008 | Dec. 30, 2009 |

NOTE: Before starting the measurement, all test equipment shall be warmed up for 30min.

6.2 TEST PROCEDURE

Before the system performance check, we need only to tell the system which components (probe, medium, and device) are used for the system performance check; the system will take care of all parameters. The dipole must be placed beneath the flat section of the SAM Twin Phantom with the correct distance holder in place. The distance holder should touch the phantom surface with a light pressure at the reference marking (little cross) and be oriented parallel to the long side of the phantom. Accurate positioning is not necessary, since the system will search for the peak SAR location, except that the dipole arms should be parallel to the surface. The device holder for mobile phones can be left in place but should be rotated away from the dipole.

The "Power Reference Measurement" and "Power Drift Measurement" jobs are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the amplifier output power. If it is too high (above ± 0.1 dB), the system performance check should be repeated; some amplifiers have very high drift during warm-up. A stable amplifier gives drift results in the DASY system below ± 0.02 dB.

The "Surface Check" job tests the optical surface detection system of the DASY system by repeatedly detecting the surface with the optical and mechanical surface detector and comparing the results. The output gives the detecting heights of both systems, the difference between the two systems and the standard deviation of the detection repeatability. Air bubbles or refraction in the liquid due to separation of the sugar-water mixture gives poor repeatability (above ± 0.1 mm). In that case it is better to abort the system performance check and stir the liquid.

The "Area Scan" job measures the SAR above the dipole on a plane parallel to the surface. It is used to locate the approximate location of the peak SAR. The proposed scan uses large grid spacing for faster measurement; due to the symmetric field, the peak detection is reliable. If a finer graphic is desired, the grid spacing can be reduced. Grid spacing and orientation have no influence on the SAR result.

The "Zoom Scan" job measures the field in a volume around the peak SAR value assessed in the previous "Area Scan" job (for more information see the application note on SAR evaluation).

About the validation dipole positioning uncertainty, the constant and low loss dielectric spacer is used to establish the correct distance between the top surface of the dipole and the bottom surface of the phantom, the error component introduced by the uncertainty of the distance between the liquid (i.e., phantom shell) and the validation dipole in the DASY4 system is less than ± 0.1 mm.

$$SAR_{tolerance} [\%] = 100 \times \left(\frac{(a + d)^2}{a^2} - 1 \right)$$

As the closest distance is 10 mm, the resulting tolerance $SAR_{tolerance} [\%]$ is $< 2\%$.

6.3 VALIDATION RESULTS

| SYSTEM VALIDATION TEST OF SIMULATING LIQUID | | | | | |
|---|------------------------|------------------------|------------------|------------------------|--------------|
| FREQUENCY (MHz) | REQUIRED SAR (mW/g) | MEASURED SAR (mW/g) | DEVIATION (%) | SEPARATION DISTANCE | TESTED DATE |
| MSL2450 | 13.30 (1g) | 13.00 | -2.26 | 10mm | May 22, 2009 |
| TESTED BY | Sam Onn | | | | |

NOTE: Please see Appendix for the photo of system validation test.

6.4 SYSTEM VALIDATION UNCERTAINTIES

In the table below, the system validation uncertainty with respect to the analytically assessed SAR value of a dipole source as given in the IEEE 1528 standard is given. This uncertainty is smaller than the expected uncertainty for mobile phone measurements due to the simplified setup and the symmetric field distribution.

| Error Description | Tolerance (±%) | Probability Distribution | Divisor | (C _i) | | Standard Uncertainty (±%) | | (v _i) |
|-----------------------------------|----------------|--------------------------|---------|-------------------|-------|---------------------------|-------|-------------------|
| | | | | (1g) | (10g) | (1g) | (10g) | |
| Measurement System | | | | | | | | |
| Probe Calibration | 5.50 | Normal | 1 | 1 | 1 | 5.50 | 5.50 | ∞ |
| Axial Isotropy | 4.70 | Rectangular | √3 | 0.7 | 0.7 | 1.90 | 1.90 | ∞ |
| Hemispherical Isotropy | 9.60 | Rectangular | √3 | 0.7 | 0.7 | 3.88 | 3.88 | ∞ |
| Boundary effects | 1.00 | Rectangular | √3 | 1 | 1 | 0.58 | 0.58 | ∞ |
| Linearity | 4.70 | Rectangular | √3 | 1 | 1 | 2.71 | 2.71 | ∞ |
| System Detection Limits | 1.00 | Rectangular | √3 | 1 | 1 | 0.58 | 0.58 | ∞ |
| Readout Electronics | 0.30 | Normal | 1 | 1 | 1 | 0.30 | 0.30 | ∞ |
| Response Time | 0.80 | Rectangular | √3 | 1 | 1 | 0.46 | 0.46 | ∞ |
| Integration Time | 2.60 | Rectangular | √3 | 1 | 1 | 1.50 | 1.50 | ∞ |
| RF Ambient Noise | 3.00 | Rectangular | √3 | 1 | 1 | 1.73 | 1.73 | ∞ |
| RF Ambient Reflections | 3.00 | Rectangular | √3 | 1 | 1 | 1.73 | 1.73 | ∞ |
| Probe Positioner | 0.40 | Rectangular | √3 | 1 | 1 | 0.23 | 0.23 | ∞ |
| Probe Positioning | 2.90 | Rectangular | √3 | 1 | 1 | 1.67 | 1.67 | ∞ |
| Max. SAR Eval. | 1.00 | Rectangular | √3 | 1 | 1 | 0.58 | 0.58 | ∞ |
| Dipole Related | | | | | | | | |
| Dipole Axis to Liquid Distance | 2.00 | Rectangular | √3 | 1 | 1 | 1.15 | 1.15 | 145 |
| Input Power Drift | 5.00 | Rectangular | √3 | 1 | 1 | 2.89 | 2.89 | ∞ |
| Phantom and Tissue parameters | | | | | | | | |
| Phantom Uncertainty | 4.00 | Rectangular | √3 | 1 | 1 | 2.31 | 2.31 | ∞ |
| Liquid Conductivity (target) | 5.00 | Rectangular | √3 | 0.64 | 0.43 | 1.85 | 1.24 | ∞ |
| Liquid Conductivity (measurement) | 3.25 | Normal | 1 | 0.64 | 0.43 | 2.08 | 1.40 | ∞ |
| Liquid Permittivity (target) | 5.00 | Rectangular | √3 | 0.6 | 0.49 | 1.73 | 1.41 | ∞ |
| Liquid Permittivity (measurement) | 2.42 | Normal | 1 | 0.6 | 0.49 | 1.45 | 1.19 | ∞ |
| Combined Standard Uncertainty | | | | | | 9.83 | 9.52 | |
| Coverage Factor for 95% | | | | | | Kp=2 | | |
| Expanded Uncertainty (K=2) | | | | | | 19.65 | 19.04 | |

NOTE: About the system validation uncertainty assessment, please reference the section 7.

7. MEASUREMENT SAR PROCEDURE UNCERTAINTIES

The assessment of spatial peak SAR of the hand handheld devices is according to IEEE 1528. All testing situation shall be met below these requirements.

- The system is used by an experienced engineer who follows the manual and the guidelines taught during the training provided by SPEAG.
- The probe has been calibrated within the requested period and the stated uncertainty for the relevant frequency bands does not exceed 4.8% ($k=1$).
- The validation dipole has been calibrated within the requested period and the system performance check has been successful.
- The DAE unit has been calibrated within the within the requested period.
- The minimum distance between the probe sensor and inner phantom shell is selected to be between 4 and 5mm.
- The operational mode of the DUT is CW, CDMA, FDMA or TDMA (GSM, DCS, PCS, IS136 and PDC) and the measurement/integration time per point is >500 ms.
- The dielectric parameters of the liquid have been assessed using Agilent 85070D dielectric probe kit or a more accurate method.
- The dielectric parameters are within 5% of the target values.
- The DUT has been positioned as described in section 3.

7.1. PROBE CALIBRATION UNCERTAINTY

SPEAG conducts the probe calibration in compliance with international and national standards (e.g. IEEE 1528, EN 62209-1, IEC 62209, etc.) under ISO17025. The uncertainties are stated on the calibration certificate. For the most relevant frequency bands, these values do not exceed 4.8% ($k=1$). If evaluations of other bands are performed for which the uncertainty exceeds these values, the uncertainty tables given in the summary have to be revised accordingly.

7.2. ISOTROPY UNCERTAINTY

The axial isotropy tolerance accounts for probe rotation around its axis while the hemispherical isotropy error includes all probe orientations and field polarizations. These parameters are assessed by SPEAG during initial calibration. In 2001, SPEAG further tightened its quality controls and warrants that the maximal deviation from axial isotropy is $\pm 0.20\text{dB}$, while the maximum deviation of hemispherical isotropy is $\pm 0.40\text{dB}$, corresponding to $\pm 4.7\%$ and $\pm 9.6\%$, respectively. A weighting factor of c_p equal to 0.5 can be applied, since the axis of the probe deviates less than 30 degrees from the normal surface orientation.

7.3. BOUNDARY EFFECT UNCERTAINTY

The effect can be estimated according to the following error approximation formula

$$SAR_{tolerance} [\%] = SAR_{be} [\%] \times \frac{(d_{be} + d_{step})^2}{2d_{step}} e^{\frac{d_{be}}{\delta/2}}$$

$$d_{be} + d_{step} < 10\text{mm}$$

The parameter d_{be} is the distance in mm between the surface and the closest measurement point used in the averaging process; d_{step} is the separation distance in mm between the first and second measurement points; δ is the minimum penetration depth in mm within the head tissue equivalent liquids (i.e., $\delta = 13.95\text{mm}$ at 3GHz); SAR_{be} is the deviation between the measured SAR value at the distance d_{be} from the boundary and the wave-guide analytical value SAR_{ref} . DASY4 applies a boundary effect compensation algorithm according to IEEE 1528, which is possible since the axis of the probe never deviates more than 30 degrees from the normal surface orientation. $SAR_{be}[\%]$ is assessed during the calibration process and SPEAG warrants that the uncertainty at distances larger than 4mm is always less than 1%. In summary, the worst case boundary effect SAR tolerance[%] for scanning distances larger than 4mm is $< \pm 0.8\%$.

7.4. PROBE LINEARITY UNCERTAINTY

Field probe linearity uncertainty includes errors from the assessment and compensation of the diode compression effects for CW and pulsed signals with known duty cycles. This error is assessed using the procedure described in IEEE 1528. For SPEAG field probes, the measured difference between CW and pulsed signals, with pulse frequencies between 10Hz and 1kHz and duty cycles between 1 and 100, is $< \pm 0.20\text{dB}$ ($< \pm 4.7\%$).

7.5. READOUT ELECTRONICS UNCERTAINTY

All uncertainties related to the probe readout electronics (DAE unit), including the gain and linearity of the instrumentation amplifier, its loading effect on the probe, and accuracy of the signal conversion algorithm, have been assessed accordingly to IEEE 1528. The combination (root-sum-square RSS method) of these components results in an overall maximum error of $\pm 1.0\%$.

7.6. RESPONSE TIME UNCERTAINTY

The time response of the field probes is assessed by exposing the probe to a well-controlled electric field producing SAR larger than 2.0W/kg at the tissue medium surface. The signal response time is evaluated as the time required by the system to reach 90% of the expected final value after an on/of switch of the power source. Analytically, it can be expressed as:

$$SAR_{\text{tolerance}} [\%] = 100 \times \left(\frac{T_m}{T_m + \tau e^{-T_m/\tau}} - 1 \right)$$

where T_m is 500 ms, i.e., the time between measurement samples, and τ the time constant. The response time τ of SPEAG's probes is $< 5\text{ms}$. In the current implementation, DASY4 waits longer than 100 ms after having reached the grid point before starting a measurement, i.e., the response time uncertainty is negligible.

7.7. INTEGRATION TIME UNCERTAINTY

If the device under test does not emit a CW signal, the integration time applied to measure the electric field at a specific point may introduce additional uncertainties due to the discretization and can be assessed as follows

$$SAR_{tolerance} [\%] = 100 \times \sum_{all\ sub-frames} \frac{t_{frame}}{t_{integration}} \frac{slot_{idle}}{slot_{total}}$$

The tolerances for the different systems are given in Table 7.1, whereby the worst-case $SAR_{tolerance}$ is 2.6%.

| System | $SAR_{tolerance} \%$ |
|-------------|----------------------|
| CW | 0 |
| CDMA* | 0 |
| WCDMA* | 0 |
| FDMA | 0 |
| IS-136 | 2.6 |
| PDC | 2.6 |
| GSM/DCS/PCS | 1.7 |
| DECT | 1.9 |
| Worst-Case | 2.6 |

TABLE 7.1

7.8. PROBE POSITIONER MECHANICAL TOLERANCE

The mechanical tolerance of the field probe positioner can introduce probe positioning uncertainties. The resulting SAR uncertainty is assessed by comparing the SAR obtained according to the specifications of the probe positioner with respect to the actual position defined by the geometric center of the probe sensors. The tolerance is determined as:

$$SAR_{tolerance} [\%] = 100 \times \frac{d_{ph}}{\delta/2}$$

The specified repeatability of the RX robot family used in DASY4 systems is $\pm 25\mu\text{m}$. The absolute accuracy for short distance movements is better than $\pm 0.1\text{mm}$, i.e., the $SAR_{tolerance} [\%]$ is better than 1.5% (rectangular).

7.9. PROBE POSITIONING

The probe positioning procedures affect the tolerance of the separation distance between the probe tip and the phantom surface as:

$$SAR_{tolerance} [\%] = 100 \times \frac{d_{ph}}{\delta/2}$$

where d_{ph} is the maximum deviation of the distance between the probe tip and the phantom surface. The optical surface detection has a precision of better than 0.2mm , resulting in an $SAR_{tolerance} [\%]$ of $< 2.9\%$ (rectangular distribution). Since the mechanical detection provides better accuracy, 2.9% is a worst-case figure for DASY4 system.

7.10. PHANTOM UNCERTAINTY

The SAR measurement uncertainty due to SPEAG phantom shell production tolerances has been evaluated using

$$SAR_{tolerance} [\%] \cong 100 \times \frac{2d}{a}, \quad d \ll a$$

For a maximum deviation d of the inner and outer shell of the phantom from that specified in the CAD file of $\pm 0.2\text{mm}$, and a 10mm spacing a between source and tissue liquid, the calculated phantom uncertainty is $\pm 4.0\%$.

7.11. DASY4 UNCERTAINTY BUDGET

| Error Description | Tolerance (±%) | Probability Distribution | Divisor | (C _i) | | Standard Uncertainty (±%) | | (v _i) |
|--------------------------------------|-------------------|-----------------------------|---------|-------------------|-------|---------------------------------|-------|-------------------|
| | | | | (1g) | (10g) | (1g) | (10g) | |
| Measurement Equipment | | | | | | | | |
| Probe Calibration | 5.50 | Normal | 1 | 1 | 1 | 5.50 | 5.50 | ∞ |
| Axial Isotropy | 4.70 | Rectangular | √3 | 0.7 | 0.7 | 1.90 | 1.90 | ∞ |
| Hemispherical Isotropy | 9.60 | Rectangular | √3 | 0.7 | 0.7 | 3.88 | 3.88 | ∞ |
| Boundary effects | 1.00 | Rectangular | √3 | 1 | 1 | 0.58 | 0.58 | ∞ |
| Linearity | 4.70 | Rectangular | √3 | 1 | 1 | 2.71 | 2.71 | ∞ |
| System Detection Limits | 1.00 | Rectangular | √3 | 1 | 1 | 0.58 | 0.58 | ∞ |
| Readout Electronics | 0.30 | Normal | 1 | 1 | 1 | 0.30 | 0.30 | ∞ |
| Response Time | 0.80 | Rectangular | √3 | 1 | 1 | 0.46 | 0.46 | ∞ |
| Integration Time | 2.60 | Rectangular | √3 | 1 | 1 | 1.50 | 1.50 | ∞ |
| RF Ambient Noise | 3.00 | Rectangular | √3 | 1 | 1 | 1.73 | 1.73 | ∞ |
| RF Ambient Reflections | 3.00 | Rectangular | √3 | 1 | 1 | 1.73 | 1.73 | ∞ |
| Probe Positioner | 0.40 | Rectangular | √3 | 1 | 1 | 0.23 | 0.23 | ∞ |
| Probe Positioning | 2.90 | Rectangular | √3 | 1 | 1 | 1.67 | 1.67 | ∞ |
| Max. SAR Eval. | 1.00 | Rectangular | √3 | 1 | 1 | 0.58 | 0.58 | ∞ |
| Test Sample Related | | | | | | | | |
| Device Positioning | 0.69 | Normal | 1 | 1 | 1 | 0.69 | 0.69 | 10 |
| Device Holder | 3.60 | Normal | 1 | 1 | 1 | 3.60 | 3.60 | 5 |
| Power Drift | 5.00 | Rectangular | √3 | 1 | 1 | 2.89 | 2.89 | ∞ |
| Phantom and Tissue parameters | | | | | | | | |
| Phantom Uncertainty | 4.00 | Rectangular | √3 | 1 | 1 | 2.31 | 2.31 | ∞ |
| Liquid Conductivity (target) | 5.00 | Rectangular | √3 | 0.64 | 0.43 | 1.85 | 1.24 | ∞ |
| Liquid Conductivity (measurement) | 3.25 | Normal | 1 | 0.64 | 0.43 | 2.08 | 1.40 | ∞ |
| Liquid Permittivity (target) | 5.00 | Rectangular | √3 | 0.6 | 0.49 | 1.73 | 1.41 | ∞ |
| Liquid Permittivity (measurement) | 2.42 | Normal | 1 | 0.6 | 0.49 | 1.45 | 1.19 | ∞ |
| Combined Standard Uncertainty | | | | | | 10.42 | 10.13 | |
| Coverage Factor for 95% | | | | | | Kp=2 | | |
| Expanded Uncertainty (K=2) | | | | | | 20.85 | 20.27 | |

TABLE 7.2



The table 7.2: Worst-Case uncertainty budget for DASY4 assessed according to IEEE 1528. The budget is valid for the frequency range 300MHz ~ 3GHz and represents a worst-case analysis. For specific tests and configurations, the uncertainty could be considerable smaller.


8. PHOTOGRAPHS OF THE EUT






















9. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

| | |
|--------------------|----------------------|
| USA | FCC, NVLAP |
| GERMANY | TUV Rheinland |
| JAPAN | VCCI |
| NORWAY | NEMKO |
| CANADA | INDUSTRY CANADA, CSA |
| R.O.C. | TAF, BSMI, NCC |
| NETHERLANDS | Telefication |
| SINGAPORE | GOST-ASIA (MOU) |
| RUSSIA | CERTIS (MOU) |

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3185050

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.

---END---

APPENDIX B: ADT SAR MEASUREMENT SYSTEM



APPENDIX A: TEST DATA

Liquid Level Photo

MSL 2450MHz D=155mm



Date/Time: 2009/5/22 14:08:13

Test Laboratory: Bureau Veritas ADT

M01-DSSS-Low Channel

DUT: Sound Blaster for iTunes ; Type: SB1170

Communication System: DSSS ; Frequency: 2412 MHz ; Duty Cycle: 1:1 ; Modulation type: DBPSK
 Medium: MSL2450 Medium parameters used: $f = 2412$ MHz; $\sigma = 1.95$ mho/m; $\epsilon_r = 53.5$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section ; Separation distance : 5 mm (The bottom side of the EUT to the Phantom)

DASY4 Configuration:

- Probe: EX3DV3 - SN3504 ; ConvF(7.53, 7.53, 7.53) ; Calibrated: 2009/1/21
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn510 ; Calibrated: 2009/1/21
- Phantom: SAM 12 ; Type: SAM V4.0 ; Serial: TP 1202
- Measurement SW: DASY4, V4.7 Build 80 ; Postprocessing SW: SEMCAD, V1.8 Build 186

Low Channel/Area Scan (5x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.827 mW/g


Low Channel/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.2 V/m

Peak SAR (extrapolated) = 1.50 W/kg

SAR(1 g) = 0.743 mW/g; SAR(10 g) = 0.346 mW/g

Maximum value of SAR (measured) = 0.982 mW/g



Date/Time: 2009/5/22 15:44:19

Test Laboratory: Bureau Veritas ADT

M02-DSSS-Low Channel

DUT: Sound Blaster for iTunes ; Type: SB1170

Communication System: DSSS ; Frequency: 2412 MHz ; Duty Cycle: 1:1 ; Modulation type: DBPSK
 Medium: MSL2450 Medium parameters used: $f = 2412$ MHz; $\sigma = 1.95$ mho/m; $\epsilon_r = 53.5$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section ; Separation distance : 5 mm (The edge side of the EUT to the Phantom)

DASY4 Configuration:

- Probe: EX3DV3 - SN3504 ; ConvF(7.53, 7.53, 7.53) ; Calibrated: 2009/1/21
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn510 ; Calibrated: 2009/1/21
- Phantom: SAM 12 ; Type: SAM V4.0 ; Serial: TP 1202
- Measurement SW: DASY4, V4.7 Build 80 ; Postprocessing SW: SEMCAD, V1.8 Build 186

Low Channel/Area Scan (5x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.026 mW/g

Low Channel/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.12 V/m

Peak SAR (extrapolated) = 0.038 W/kg

SAR(1 g) = 0.018 mW/g; SAR(10 g) = 0.014 mW/g

Maximum value of SAR (measured) = 0.032 mW/g


Low Channel/Zoom Scan (7x7x7) (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.12 V/m

Peak SAR (extrapolated) = 0.037 W/kg

SAR(1 g) = 0.021 mW/g; SAR(10 g) = 0.017 mW/g

Maximum value of SAR (measured) = 0.028 mW/g



Date/Time: 2009/5/22 13:08:16

Test Laboratory: Bureau Veritas ADT

M03-Low Channel

DUT: Sound Blaster for iTunes ; Type: SB1170

Communication System: DSSS ; Frequency: 2412 MHz ; Duty Cycle: 1:1 ; Modulation type: DBPSK
 Medium: MSL2450 Medium parameters used: $f = 2412$ MHz; $\sigma = 1.95$ mho/m; $\epsilon_r = 53.5$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section ; Separation distance : 5 mm (The front side of the EUT to the Phantom)

DASY4 Configuration:

- Probe: EX3DV3 - SN3504 ; ConvF(7.53, 7.53, 7.53) ; Calibrated: 2009/1/21
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn510 ; Calibrated: 2009/1/21
- Phantom: SAM 12 ; Type: SAM V4.0 ; Serial: TP 1202
- Measurement SW: DASY4, V4.7 Build 80 ; Postprocessing SW: SEMCAD, V1.8 Build 186

Low Channel/Area Scan (5x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.592 mW/g


Low Channel/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 17.5 V/m

Peak SAR (extrapolated) = 1.38 W/kg

SAR(1 g) = 0.665 mW/g; SAR(10 g) = 0.300 mW/g

Maximum value of SAR (measured) = 0.878 mW/g



Date/Time: 2009/5/22 10:06:24

Test Laboratory: Bureau Veritas ADT

M04-DSSS-Low Channel

DUT: Sound Blaster for iTunes ; Type: SB1170

Communication System: DSSS ; Frequency: 2412 MHz ; Duty Cycle: 1:1 ; Modulation type: DBPSK
Medium: MSL2450 Medium parameters used: $f = 2412$ MHz; $\sigma = 1.95$ mho/m; $\epsilon_r = 53.5$; $\rho = 1000$ kg/m³
Phantom section: Flat Section ; Separation distance : 5 mm (The edge side of the EUT to the Phantom)

DASY4 Configuration:

- Probe: EX3DV3 - SN3504 ; ConvF(7.53, 7.53, 7.53) ; Calibrated: 2009/1/21
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn510 ; Calibrated: 2009/1/21
- Phantom: SAM 12 ; Type: SAM V4.0 ; Serial: TP 1202
- Measurement SW: DASY4, V4.7 Build 80 ; Postprocessing SW: SEMCAD, V1.8 Build 186

Low Channel/Area Scan (5x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.64 mW/g


Low Channel/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 28.0 V/m

Peak SAR (extrapolated) = 2.44 W/kg

SAR(1 g) = 1.07 mW/g; SAR(10 g) = 0.449 mW/g

Maximum value of SAR (measured) = 1.46 mW/g





Date/Time: 2009/5/22 10:26:18

Test Laboratory: Bureau Veritas ADT

M04-DSSS-Mid Channel

DUT: Sound Blaster for iTunes ; Type: SB1170

Communication System: DSSS ; Frequency: 2438 MHz ; Duty Cycle: 1:1 ; Modulation type: DBPSK
 Medium: MSL2450 Medium parameters used: $f = 2438$ MHz; $\sigma = 1.99$ mho/m; $\epsilon_r = 53.4$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section ; Separation distance : 5 mm (The edge side of the EUT to the Phantom)

DASY4 Configuration:

- Probe: EX3DV3 - SN3504 ; ConvF(7.53, 7.53, 7.53) ; Calibrated: 2009/1/21
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn510 ; Calibrated: 2009/1/21
- Phantom: SAM 12 ; Type: SAM V4.0 ; Serial: TP 1202
- Measurement SW: DASY4, V4.7 Build 80 ; Postprocessing SW: SEMCAD, V1.8 Build 186

Mid Channel/Area Scan (5x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.23 mW/g


Mid Channel/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 25.1 V/m

Peak SAR (extrapolated) = 2.10 W/kg

SAR(1 g) = 0.907 mW/g; SAR(10 g) = 0.377 mW/g

Maximum value of SAR (measured) = 1.25 mW/g



Date/Time: 2009/5/22 10:42:31

Test Laboratory: Bureau Veritas ADT

M04-DSSS-High Channel

DUT: Sound Blaster for iTunes ; Type: SB1170

Communication System: DSSS ; Frequency: 2464 MHz ; Duty Cycle: 1:1 ; Modulation type: DBPSK
 Medium: MSL2450 Medium parameters used: $f = 2464 \text{ MHz}$; $\sigma = 2.02 \text{ mho/m}$; $\epsilon_r = 53.2$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Flat Section ; Separation distance : 5 mm (The edge side of the EUT to the Phantom)

DASY4 Configuration:

- Probe: EX3DV3 - SN3504 ; ConvF(7.53, 7.53, 7.53) ; Calibrated: 2009/1/21
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn510 ; Calibrated: 2009/1/21
- Phantom: SAM 12 ; Type: SAM V4.0 ; Serial: TP 1202
- Measurement SW: DASY4, V4.7 Build 80 ; Postprocessing SW: SEMCAD, V1.8 Build 186

High Channel/Area Scan (5x9x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 1.03 mW/g


High Channel/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.0 V/m

Peak SAR (extrapolated) = 1.80 W/kg

SAR(1 g) = 0.769 mW/g; SAR(10 g) = 0.317 mW/g

Maximum value of SAR (measured) = 1.07 mW/g



Date/Time: 2009/5/22 13:28:08

Test Laboratory: Bureau Veritas ADT

M05-DSSS-Low Channel

DUT: Sound Blaster for iTunes ; Type: SB1170

Communication System: DSSS ; Frequency: 2412 MHz ; Duty Cycle: 1:1 ; Modulation type: DBPSK
 Medium: MSL2450 Medium parameters used: $f = 2412$ MHz; $\sigma = 1.95$ mho/m; $\epsilon_r = 53.5$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section ; Separation distance : 0 mm (The tip side of the EUT to the Phantom)

DASY4 Configuration:

- Probe: EX3DV3 - SN3504 ; ConvF(7.53, 7.53, 7.53) ; Calibrated: 2009/1/21
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn510 ; Calibrated: 2009/1/21
- Phantom: SAM 12 ; Type: SAM V4.0 ; Serial: TP 1202
- Measurement SW: DASY4, V4.7 Build 80 ; Postprocessing SW: SEMCAD, V1.8 Build 186

Low Channel/Area Scan (5x8x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.526 mW/g

Low Channel/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.0 V/m

Peak SAR (extrapolated) = 1.00 W/kg

SAR(1 g) = 0.491 mW/g; SAR(10 g) = 0.221 mW/g

Maximum value of SAR (measured) = 0.644 mW/g


Low Channel/Zoom Scan (7x7x7) (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.0 V/m

Peak SAR (extrapolated) = 0.813 W/kg

SAR(1 g) = 0.387 mW/g; SAR(10 g) = 0.173 mW/g

Maximum value of SAR (measured) = 0.516 mW/g



Date/Time: 2009/5/22 14:32:43

Test Laboratory: Bureau Veritas ADT

M06-DSSS-Low Channel / Ant-90

DUT: Sound Blaster for iTunes ; Type: SB1170

Communication System: DSSS ; Frequency: 2412 MHz ; Duty Cycle: 1:1 ; Modulation type: DBPSK
 Medium: MSL2450 Medium parameters used: $f = 2412$ MHz; $\sigma = 1.95$ mho/m; $\epsilon_r = 53.5$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section ; Separation distance : 5 mm (The bottom side of the EUT to the Phantom)

DASY4 Configuration:

- Probe: EX3DV3 - SN3504 ; ConvF(7.53, 7.53, 7.53) ; Calibrated: 2009/1/21
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn510 ; Calibrated: 2009/1/21
- Phantom: SAM 12 ; Type: SAM V4.0 ; Serial: TP 1202
- Measurement SW: DASY4, V4.7 Build 80 ; Postprocessing SW: SEMCAD, V1.8 Build 186

Low Channel/Area Scan (5x7x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.368 mW/g


Low Channel/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.4 V/m

Peak SAR (extrapolated) = 0.505 W/kg

SAR(1 g) = **0.273 mW/g**; SAR(10 g) = 0.152 mW/g

Maximum value of SAR (measured) = 0.334 mW/g



Date/Time: 2009/5/22 10:59:16

Test Laboratory: Bureau Veritas ADT

M07-DSSS-Low Channel / step size set minimum

DUT: Sound Blaster for iTunes ; Type: SB1170

Communication System: DSSS ; Frequency: 2412 MHz ; Duty Cycle: 1:1 ; Modulation type: DBPSK
 Medium: MSL2450 Medium parameters used: $f = 2412$ MHz; $\sigma = 1.95$ mho/m; $\epsilon_r = 53.5$; $\rho = 1000$ kg/m³
 Phantom section: Flat Section ; Separation distance : 5 mm (The edge side of the EUT to the Phantom)

DASY4 Configuration:

- Probe: EX3DV3 - SN3504 ; ConvF(7.53, 7.53, 7.53) ; Calibrated: 2009/1/21
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn510 ; Calibrated: 2009/1/21
- Phantom: SAM 12 ; Type: SAM V4.0 ; Serial: TP 1202
- Measurement SW: DASY4, V4.7 Build 80 ; Postprocessing SW: SEMCAD, V1.8 Build 186

Low Channel/Area Scan (5x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.45 mW/g


Low Channel/Zoom Scan (7x7x7) (13x13x13)/Cube 0: Measurement grid: dx=2.5mm, dy=2.5mm, dz=2.5mm

Reference Value = 27.7 V/m

Peak SAR (extrapolated) = 2.42 W/kg

SAR(1 g) = 1.05 mW/g; SAR(10 g) = 0.444 mW/g

Maximum value of SAR (measured) = 1.73 mW/g



Date/Time: 2009/5/22 09:39:53

Test Laboratory: Bureau Veritas ADT

System Validation Check-MSL 2450MHz

DUT: Dipole 2450 MHz ; Type: D2450V2 ; Serial: 716 ; Test Frequency: 2450 MHz

Communication System: CW ; Frequency: 2450 MHz; Duty Cycle: 1:1; Modulation type: CW
 Medium: MSL2450; Medium parameters used: $f = 2450$ MHz; $\sigma = 2$ mho/m; $\epsilon_r = 53.3$; $\rho = 1000$ kg/m³ ;
 Liquid level : 155 mm
 Phantom section: Flat Section ; Separation distance : 10 mm (The feetpoint of the dipole to the Phantom)
 Air temp. : 23.5 degrees ; Liquid temp. : 22.7 degrees

DASY4 Configuration:

- Probe: EX3DV3 - SN3504 ; ConvF(7.53, 7.53, 7.53) ; Calibrated: 2009/1/21
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn510; Calibrated: 2009/1/21
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP 1202
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

d=10mm, Pin=250mW/Area Scan (5x7x1): Measurement grid: dx=15mm, dy=15mm
 Maximum value of SAR (measured) = 17.2 mW/g


d=10mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 94.4 V/m; Power Drift = -0.086 dB

Peak SAR (extrapolated) = 28.1 W/kg

SAR(1 g) = 13 mW/g; SAR(10 g) = 6.02 mW/g

Maximum value of SAR (measured) = 17.4 mW/g



APPENDIX C: PHOTOGRAPHS OF SYSTEM VALIDATION



APPENDIX D: SYSTEM CERTIFICATE & CALIBRATION

D1: PHANTOM

Schmid & Partner Engineering AG

Zeughausstrasse 43, 8004 Zurich, Switzerland, Phone +41 1 245 97 00, Fax +41 1 245 97 79

Certificate of conformity / First Article Inspection

| | |
|-----------------------|--|
| Item | SAM Twin Phantom V4.0 |
| Type No | QD 000 P40 CA |
| Series No | TP-1150 and higher |
| Manufacturer / Origin | Untersee Composites Hauptstr. 69 CH-8559 Fruthwilen Switzerland |

Tests

The series production process used allows the limitation to test of first articles. Complete tests were made on the pre-series Type No. QD 000 P40 AA, Serial No. TP-1001 and on the series first article Type No. QD 000 P40 BA, Serial No. TP-1006. Certain parameters have been retested using further series units (called samples).

| Test | Requirement | Details | Units tested |
|----------------------|---|--|-----------------------------|
| Shape | Compliance with the geometry according to the CAD model. | IT'IS CAD File (*) | First article, Samples |
| Material thickness | Compliant with the requirements according to the standards | 2mm +/- 0.2mm in specific areas | First article, Samples |
| Material parameters | Dielectric parameters for required frequencies | 200 MHz - 3 GHz Relative permittivity < 5 Loss tangent < 0.05. | Material sample TP 104-5 |
| Material resistivity | The material has been tested to be compatible with the liquids defined in the standards | Liquid type HSL 1800 and others according to the standard. | Pre-series, First article |

Standards

- [1] CENELEC EN 50361
- [2] IEEE P1528-200x draft 6.5
- [3] IEC PT 62209 draft 0.9

(*) The IT'IS CAD file is derived from [2] and is also within the tolerance requirements of the shapes of [1] and [3].

Conformity

Based on the sample tests above, we certify that this item is in compliance with the uncertainty requirements of SAR measurements specified in standard [1] and draft standards [2] and [3].

Date

28.02.2002

Signature / Stamp

F. Bumbult

**Schmid & Partner
Engineering AG**

Zeughausstrasse 43, CH-8004 Zurich
Tel. +41 1 245 97 00, Fax +41 1 245 97 79

Volker Kapp