

**Test Report No. 719165030-EEC-04**  
dated 07 Jan 2010



PSB Singapore

**Note:** This report is issued subject to TÜV SÜD PSB's "Terms and Conditions Governing Technical Services".  
The terms and conditions governing the issue of this report are set out as attached within this report.

**Choose certainty.  
Add value.**

**COMPLIANCE REPORT ON TESTING IN ACCORDANCE WITH  
SAR (SPECIFIC ABSORPTION RATE) REQUIREMENTS**

**Supplement C (Edition 01-01)  
FCC OET Bulletin 65 (Edition 97-01)**

**OF A WIRELESS TRANSCEIVER  
[Model : SB1210]**

**TEST  
FACILITY**

TÜV SÜD PSB Pte Ltd,  
Electrical & Electronics Centre (EEC), Product Services,  
1 Science Park Drive, Singapore 118221

**PREPARED  
FOR**

Creative Technology Ltd.  
31, International Business Park Creative Resource  
S609921

Tel : (+65) 68954252

Fax : (+65) 68954054

**QUOTATION  
NUMBER**

Q09EEC02979

**JOB NUMBER**

719165030

**TEST PERIOD**

28-Dec-2009 – 07-Jan-2010

**PREPARED BY**

Stanley Siah  
Associate Engineer

**APPROVED BY**

Daniel Yeo  
Assistant Vice President



Laboratory:  
TÜV SÜD PSB Pte. Ltd.  
Testing Services  
No.1 Science Park Drive  
Singapore 118221

Phone : +65-6885 1333  
Fax : +65-6776 8670  
E-mail: testing@tuv-sud-psb.sg  
www.tuv-sud-psb.sg  
Co. Reg : 199002667R

Regional Head Office:  
TÜV SÜD Asia Pacific Pte. Ltd.  
3 Science Park Drive, #04-01/05  
The Franklin, Singapore 118223  
**TUV®**



LA-2007-0380-A  
LA-2007-0380-A-1  
LA-2007-0381-F  
LA-2007-0382-B  
LA-2007-0383-G  
LA-2007-0384-G  
LA-2007-0385-E  
LA-2007-0386-C

The results reported herein have been performed in accordance with the laboratory's terms of accreditation under the Singapore Accreditation Council - Singapore Laboratory Accreditation Scheme. Tests/Calibrations marked "Not SAC-SINGLAS Accredited" in this Report are not included in the SAC-SINGLAS Accreditation Schedule for our laboratory.



---

**TABLE OF CONTENTS**

TEST SUMMARY

PRODUCT DESCRIPTION

TEST RESULTS

ANNEX A	- TEST INSTRUMENTATION & GENERAL PROCEDURES
ANNEX B	- EUT PHOTOGRAPHS / DIAGRAMS Test Setup EUT Photographs
ANNEX C	- TISSUE SIMULANT DATA SHEETS
ANNEX D	- SAR VALIDATION RESULTS
ANNEX E	- MEASUREMENT UNCERTAINTY
ANNEX F	- SAR PROBE CALIBRATION CERTIFICATES
ANNEX G	- REFERENCES

## TEST SUMMARY

The product was tested in accordance with the following standards.

### Test Results Summary

Test Standards	Description	Pass / Fail
<ul style="list-style-type: none"><li>Supplement C (Edition 01-01) to FCC OET Bulletin 65 (Edition 97-01)</li><li>ANSI/IEEE Standard C95.1-1993</li></ul>	SAR Measurement (Wi-Fi 2450MHz) Body worn Configuration Only	Pass *


Note:

1. The worst-case SAR value was found to be **0.815W/kg** which is lower than the maximum limit of 1.60 W/kg, over 1g of tissue.

\* Based on spatial peak uncontrolled exposure / general population level:  
Head: 1.60 W/kg, over 1g of tissue.  
Body: 1.60 W/kg, over 1g of tissue.

### Modifications

No modifications were made.





## DEVICE DESCRIPTION

### DEVICE DESCRIPTION

Description	The Equipment Under Test (EUT) is a <b>Wireless transceiver</b> Provides a wireless USB solution, combining X-Fi Technology with our proprietary wireless implantation with all the sleek features. User will be able to do multiple audio wireless streaming simultaneously.
Device Category	Portable Device
Exposure Environment	General Population/Uncontrolled exposure
Test Device Type	Prototype
Brand Name	Creative Sound Blaster Wireless
Serial Numbers	NIL
FCC ID	IBAAVPSB1210

### DEVICE OPERATING CONFIGURATION

Operating Frequencies	<u>Wi-Fi mode</u> Channel 1 (2412Mhz) Channel 2 (2438Mhz) Channel 3 (2464Mhz)
Operating Temperature Tolerance	(10 ~ 40) Degree Celsius
Operating Voltage Tolerance	(3.1 ~ 3.5) Volt DC
Continuous Transmission Tolerance	The EUT shall cause no problem after transmitting for 2 hours.
Rated Output Power(max)	18dBm
Antenna Type	Integrated Chip Antenna
EUT Crest Factor	1.0
Input Power	USB, 5V
Accessories	1) USB docking device 2) Earpiece (earphone and microphone)

### MANUFACTURER

Manufacturer Address	Creative Technology Ltd 31, International business Park Creative Resource S609921
DID	(+65) 68954490
Fax	(+65) 68954953



---

## DEVICE OPERATING CONDITION

### DEVICE OPERATING CONDITION

The EUT has only one single transmit antenna. SAR was evaluated with the radio transmitting data rate for each mode. The EUT was put into exercised by using software control operating at the following frequencies 2.412GHz, 2.438GHz and 2.464GHz (lowest, middle and highest channel).

### TEMPERATURE AND HUMIDITY

(Body)

Ambient Temperature:  $24 \pm 1^{\circ}\text{C}$   
Tissue Temperature:  $24 \pm 1^{\circ}\text{C}$   
Humidity: 54% to 59%





## TEST RESULTS

The measurement results were obtained with the EUT tested in the conditions described in this report (Annex A).

**Table 1 - Body Worn Position SAR Test Results – Front/Rear**

Phantom Configuration	Device Test Positions	Antenna Position	SAR (W/kg), average over 1g Tissue Device Test Channel & Frequency		
			Channel: 1 2412MHz	Channel: 2 2438MHz	Channel: 3 2464MHz
Flat Phantom	EUT <b>Front</b> Touched Phantom	fixed	0.073	0.078	0.030
Flat Phantom	EUT <b>Rear</b> Touched Phantom	fixed	0.189	0.155	0.192
Output Peak Power (dBm) Before Test			17.5	17.4	17.2
Output Peak Power (dBm) After Test			17.2	17.3	17.0

**Table 2 - Body Worn Position SAR Test Results – Right/Left (Worst case)**

Phantom Configuration	Device Test Positions	Antenna Position	SAR (W/kg), average over 1g Tissue Device Test Channel & Frequency		
			Channel: 1 2412MHz	Channel: 2 2438MHz	Channel: 3 2464MHz
Flat Phantom	EUT <b>Top</b> Touched Phantom	fixed	0.815	0.610	0.472
Flat Phantom	EUT <b>Side</b> Touched Phantom	fixed	0.577	0.505	0.445
Output Peak Power (dBm) Before Test			17.8	17.6	17.4
Output Peak Power (dBm) After Test			17.5	17.4	17.1

**Remarks:**

- All modes of operations were investigated and the worst-case SAR levels are reported.
- For **Wi-Fi**, the worst-case SAR value was found to be **0.815W/Kg** (over a 1g tissue) at **Channel 1** which is lower than the maximum limit of 1.60 W/Kg, please refer to the above table.
- For Right and Left only the worst channel is measured.



4. The SAR limit of 1.60W/Kg (Spatial Peak level for Uncontrolled Exposure / General Population) is based on the Test Standards:
- a) Supplement C (Edition 01-01) to FCC OET Bulletin 65 (Edition 97-01)
  - b) ANSI/IEEE Standard C95.1-1993





## FRONT TEST RESULTS

**Ambient Temperature:**  $24 \pm 1^{\circ}\text{C}$   
**Tissue Temperature:**  $24 \pm 1^{\circ}\text{C}$   
**Humidity:** 54% to 59%

Test Laboratory: TUV SUD PSB PTE LTD.

Date/Time: 12/29/2009 10:18:00 AM

File Name: [EUT Front\\_Ch 1\\_2412MHz.da4](#)

Program Name: EUT Front\_Ch 1\_2412MHz\_Data 1.da4

Phantom section: Flat Section

DUT: Sound Blaster WL

Communication System: 2450 Mhz

Frequency: 2412 MHz

Duty Cycle: 1:1

Medium: Body 2450 MHz Medium parameters used:  $f = 2450\text{ MHz}$ ;  $\sigma = 1.97\text{ mho/m}$ ;  $\epsilon_r = 52.1$ ;  $\rho = 1000\text{ kg/m}^3$

### DASY4 Configuration:

Electronics: DAE4 Sn627

Calibrated: 6/14/2007

Phantom: SAM 12

Measurement SW: DASY4, V4.7 Build 80

Probe: EX3DV4 - SN3541

ConvF(7.07, 7.07, 7.07)

Calibrated: 7/13/2007

Post processing SW: SEMCAD, V1.8 Build 186

Sensor-Surface: 4mm (Mechanical Surface Detection)

### EUT Front\_Ch 1\_2412MHz\_Data 1/Area Scan (13x24x1): Measurement grid:

$dx=5\text{mm}$ ,  $dy=5\text{mm}$

Maximum value of SAR (measured) = 0.081 mW/g




### EUT Front\_Ch 1\_2412MHz\_Data 1/Zoom Scan (7x7x7)/Cube 0: Measurement

grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 4.62 V/m; Power Drift = 0.226 dB

Peak SAR (extrapolated) = 0.133 W/kg

**SAR(1 g) = 0.073 mW/g; SAR(10 g) = 0.041 mW/g**





## FRONT TEST RESULTS

**Ambient Temperature:**  $24 \pm 1^{\circ}\text{C}$   
**Tissue Temperature:**  $24 \pm 1^{\circ}\text{C}$   
**Humidity:** 54% to 59%

Test Laboratory: TUV SUD PSB PTE LTD.

Date/Time: 12/29/2009 11:09:32 AM

File Name: [EUT Front\\_Ch 2\\_2438MHz.da4](#)

Program Name: EUT Front\_Ch 2\_2438MHz\_Data 1.da4

Phantom section: Flat Section

DUT: Sound Blaster WL

Communication System: 2450 Mhz

Frequency: 2438 MHz

Duty Cycle: 1:1

Medium: Body 2450 MHz Medium parameters used:  $f = 2450\text{ MHz}$ ;  $\sigma = 1.97\text{ mho/m}$ ;  $\epsilon_r = 52.1$ ;  $\rho = 1000\text{ kg/m}^3$

### DASY4 Configuration:

Electronics: DAE4 Sn627

Calibrated: 6/14/2007

Phantom: SAM 12

Measurement SW: DASY4, V4.7 Build 80

Probe: EX3DV4 - SN3541

ConvF(7.07, 7.07, 7.07)

Calibrated: 7/13/2007

Post processing SW: SEMCAD, V1.8 Build 186

Sensor-Surface: 4mm (Mechanical Surface Detection)

**EUT Front\_Ch 2\_2438MHz\_Data 1/Area Scan (13x24x1):** Measurement grid:

$dx=5\text{mm}$ ,  $dy=5\text{mm}$

Maximum value of SAR (measured) = 0.087 mW/g

**EUT Front\_Ch 2\_2438MHz\_Data 1/Zoom Scan (7x7x7)/Cube 0:** Measurement




grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 3.91 V/m; Power Drift = -0.127 dB

Peak SAR (extrapolated) = 0.138 W/kg

**SAR(1 g) = 0.078 mW/g; SAR(10 g) = 0.043 mW/g**

Maximum value of SAR (measured) = 0.084 mW/g





## FRONT TEST RESULTS

**Ambient Temperature:**  $24 \pm 1^{\circ}\text{C}$   
**Tissue Temperature:**  $24 \pm 1^{\circ}\text{C}$   
**Humidity:** 54% to 59%

Test Laboratory: TUV SUD PSB PTE LTD.

Date/Time: 12/29/2009 12:02:21 PM

File Name: [EUT Front\\_Ch 3\\_2464MHz.da4](#)

Program Name: EUT Front\_Ch 3\_2464MHz\_Data 1.da4

Phantom section: Flat Section

DUT: Sound Blaster WL

Communication System: 2450 Mhz

Frequency: 2464 MHz

Duty Cycle: 1:1

Medium: Body 2450 MHz Medium parameters used:  $f = 2450\text{ MHz}$ ;  $\sigma = 1.97\text{ mho/m}$ ;  $\epsilon_r = 52.1$ ;  $\rho = 1000\text{ kg/m}^3$

### DASY4 Configuration:

Electronics: DAE4 Sn627

Calibrated: 6/14/2007

Phantom: SAM 12

Measurement SW: DASY4, V4.7 Build 80

Probe: EX3DV4 - SN3541

ConvF(7.07, 7.07, 7.07)

Calibrated: 7/13/2007

Post processing SW: SEMCAD, V1.8 Build 186

Sensor-Surface: 4mm (Mechanical Surface Detection)

**EUT Front\_Ch 3\_2464MHz\_Data 1/Area Scan (13x24x1):** Measurement grid:

$dx=5\text{mm}$ ,  $dy=5\text{mm}$

Maximum value of SAR (measured) = 0.034 mW/g

**EUT Front\_Ch 3\_2464MHz\_Data 1/Zoom Scan (7x7x7)/Cube 0:** Measurement



grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 3.04 V/m; Power Drift = -0.357 dB

Peak SAR (extrapolated) = 0.057 W/kg

**SAR(1 g) = 0.030 mW/g; SAR(10 g) = 0.017 mW/g**

Maximum value of SAR (measured) = 0.033 mW/g





## REAR TEST RESULTS

**Ambient Temperature:**  $24 \pm 1^{\circ}\text{C}$   
**Tissue Temperature:**  $24 \pm 1^{\circ}\text{C}$   
**Humidity:** 54% to 59%

Test Laboratory: TUV SUD PSB PTE LTD.

Date/Time: 12/29/2009 4:16:47 PM

File Name: [EUT Rear\\_Ch 1\\_2412MHz.da4](#)

Program Name: EUT Rear\_Ch 1\_2412MHz\_Data 1.da4

Phantom section: Flat Section

DUT: Sound Blaster WL

Communication System: 2450 Mhz

Frequency: 2412 MHz

Duty Cycle: 1:1

Medium: Body 2450 MHz Medium parameters used:  $f = 2450\text{ MHz}$ ;  $\sigma = 1.97\text{ mho/m}$ ;  $\epsilon_r = 52.1$ ;  $\rho = 1000\text{ kg/m}^3$

### DASY4 Configuration:

Electronics: DAE4 Sn627

Calibrated: 6/14/2007

Phantom: SAM 12

Measurement SW: DASY4, V4.7 Build 80

Probe: EX3DV4 - SN3541

ConvF(7.07, 7.07, 7.07)

Calibrated: 7/13/2007

Post processing SW: SEMCAD, V1.8 Build 186

Sensor-Surface: 4mm (Mechanical Surface Detection)

**EUT Rear\_Ch 1\_2412MHz\_Data 1/Area Scan (13x24x1):** Measurement grid:

$dx=5\text{mm}$ ,  $dy=5\text{mm}$

Maximum value of SAR (measured) = 0.197 mW/g



**EUT Rear\_Ch 1\_2412MHz\_Data 1/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 8.15 V/m; Power Drift = 0.016 dB

Peak SAR (extrapolated) = 0.262 W/kg

**SAR(1 g) = 0.189 mW/g; SAR(10 g) = 0.154 mW/g**

Maximum value of SAR (measured) = 0.194 mW/g



## REAR TEST RESULTS

**Ambient Temperature:**  $24 \pm 1^{\circ}\text{C}$   
**Tissue Temperature:**  $24 \pm 1^{\circ}\text{C}$   
**Humidity:** 54% to 59%

Test Laboratory: TUV SUD PSB PTE LTD.

Date/Time: 12/30/2009 3:22:03 PM

File Name: [EUT Rear\\_Ch 2\\_2438MHz.da4](#)

Program Name: EUT Rear\_Ch 2\_2438MHz\_Data 1.da4

Phantom section: Flat Section

DUT: Sound Blaster WL

Communication System: 2450 Mhz

Frequency: 2438 MHz

Duty Cycle: 1:1

Medium: Body 2450 MHz Medium parameters used:  $f = 2450\text{ MHz}$ ;  $\sigma = 1.97\text{ mho/m}$ ;  $\epsilon_r = 52.1$ ;  $\rho = 1000\text{ kg/m}^3$

### DASY4 Configuration:

Electronics: DAE4 Sn627

Calibrated: 6/14/2007

Phantom: SAM 12

Measurement SW: DASY4, V4.7 Build 80

Probe: EX3DV4 - SN3541

ConvF(7.07, 7.07, 7.07)

Calibrated: 7/13/2007

Post processing SW: SEMCAD, V1.8 Build 186

Sensor-Surface: 4mm (Mechanical Surface Detection)

**EUT Rear\_Ch 2\_2438MHz\_Data 1/Area Scan (13x24x1):** Measurement grid:

$dx=5\text{mm}$ ,  $dy=5\text{mm}$

Maximum value of SAR (measured) = 0.159 mW/g

**EUT Rear\_Ch 2\_2438MHz\_Data 1/Zoom Scan (7x7x7)/Cube 0:** Measurement




grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 8.14 V/m; Power Drift = -0.152 dB

Peak SAR (extrapolated) = 0.216 W/kg

**SAR(1 g) = 0.155 mW/g; SAR(10 g) = 0.130 mW/g**

Maximum value of SAR (measured) = 0.157 mW/g





## REAR TEST RESULTS

**Ambient Temperature:**  $24 \pm 1^{\circ}\text{C}$   
**Tissue Temperature:**  $24 \pm 1^{\circ}\text{C}$   
**Humidity:** 54% to 59%

Test Laboratory: TUV SUD PSB PTE LTD.

Date/Time: 12/30/2009 4:27:07 PM

File Name: [EUT Rear Ch 3\\_2464MHz.da4](#)

Program Name: EUT Rear \_Ch 3\_2464MHz\_Data 1.da4

Phantom section: Flat Section

DUT: Sound Blaster WL

Communication System: 2450 Mhz

Frequency: 2464 MHz

Duty Cycle: 1:1

Medium: Body 2450 MHz Medium parameters used:  $f = 2450\text{ MHz}$ ;  $\sigma = 1.97\text{ mho/m}$ ;  $\epsilon_r = 52.1$ ;  $\rho = 1000\text{ kg/m}^3$

### DASY4 Configuration:

Electronics: DAE4 Sn627

Calibrated: 6/14/2007

Phantom: SAM 12

Measurement SW: DASY4, V4.7 Build 80

Probe: EX3DV4 - SN3541

ConvF(7.07, 7.07, 7.07)

Calibrated: 7/13/2007

Post processing SW: SEMCAD, V1.8 Build 186

Sensor-Surface: 4mm (Mechanical Surface Detection)

**EUT Rear\_Ch 3\_2464MHz\_Data 1/Area Scan (13x24x1):** Measurement grid:

$dx=5\text{mm}$ ,  $dy=5\text{mm}$




Maximum value of SAR (measured) = 0.194 mW/g

**EUT Rear\_Ch 3\_2464MHz\_Data 1/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 9.00 V/m; Power Drift = 0.148 dB

Peak SAR (extrapolated) = 0.258 W/kg

**SAR(1 g) = 0.192 mW/g; SAR(10 g) = 0.168 mW/g**





---

TOP TEST RESULTS

---

Ambient Temperature:  $24 \pm 1^{\circ}\text{C}$   
Tissue Temperature:  $24 \pm 1^{\circ}\text{C}$   
Humidity: 54% to 59%

Test Laboratory: TUV SUD PSB PTE LTD.

Date/Time: 12/31/2009 9:30:29 AM

File Name: [EUT Top\\_Ch 1\\_2412MHz.da4](#)

Program Name: EUT Top\_Ch 1\_2412MHz\_Data 1.da4

Phantom section: Flat Section

DUT: Sound Blaster WL

Communication System: 2450 Mhz

Frequency: 2412 MHz

Duty Cycle: 1:1

Medium: Body 2450 MHz Medium parameters used:  $f = 2450\text{ MHz}$ ;  $\sigma = 1.97\text{ mho/m}$ ;  $\epsilon_r = 52.1$ ;  $\rho = 1000\text{ kg/m}^3$

**DASY4 Configuration:**

Electronics: DAE4 Sn627

Calibrated: 6/14/2007

Phantom: SAM 12

Measurement SW: DASY4, V4.7 Build 80

Probe: EX3DV4 - SN3541

ConvF(7.07, 7.07, 7.07)

Calibrated: 7/13/2007

Post processing SW: SEMCAD, V1.8 Build 186

Sensor-Surface: 4mm (Mechanical Surface Detection)

**EUT Top\_Ch 1\_2412MHz\_Data 1/Area Scan (7x21x1):** Measurement grid:

$dx=5\text{mm}$ ,  $dy=5\text{mm}$

Maximum value of SAR (measured) =  $0.921\text{ mW/g}$



**EUT Top\_Ch 1\_2412MHz\_Data 1/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $20.9\text{ V/m}$ ; Power Drift =  $-0.031\text{ dB}$

Peak SAR (extrapolated) =  $2.02\text{ W/kg}$

**SAR(1 g) =  $0.815\text{ mW/g}$ ; SAR(10 g) =  $0.361\text{ mW/g}$**

Maximum value of SAR (measured) =  $0.928\text{ mW/g}$





**TOP TEST RESULTS**

**Ambient Temperature:**  $24 \pm 1^{\circ}\text{C}$   
**Tissue Temperature:**  $24 \pm 1^{\circ}\text{C}$   
**Humidity:** 54% to 59%

Test Laboratory: TUV SUD PSB PTE LTD.

Date/Time: 12/31/2009 10:14:24 AM

File Name: [EUT Top\\_Ch 2\\_2438MHz.da4](#)

Program Name: EUT Top\_Ch 2\_2438MHz\_Data 1.da4

Phantom section: Flat Section

DUT: Sound Blaster WL

Communication System: 2450 Mhz

Frequency: 2438 MHz

Duty Cycle: 1:1

Medium: Body 2450 MHz Medium parameters used:  $f = 2450\text{ MHz}$ ;  $\sigma = 1.97\text{ mho/m}$ ;  $\epsilon_r = 52.1$ ;  $\rho = 1000\text{ kg/m}^3$

**DASY4 Configuration:**

Electronics: DAE4 Sn627

Calibrated: 6/14/2007

Phantom: SAM 12

Measurement SW: DASY4, V4.7 Build 80

Probe: EX3DV4 - SN3541

ConvF(7.07, 7.07, 7.07)

Calibrated: 7/13/2007

Post processing SW: SEMCAD, V1.8 Build 186

Sensor-Surface: 4mm (Mechanical Surface Detection)

**EUT Top\_Ch 2\_2438MHz\_Data 1/Area Scan (7x21x1):** Measurement grid:

$dx=5\text{mm}$ ,  $dy=5\text{mm}$

Maximum value of SAR (measured) = 0.649 mW/g

**EUT Top\_Ch 2\_2438MHz\_Data 1/Zoom Scan (7x7x7)/Cube 0:** Measurement




grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 18.0 V/m; Power Drift = 0.053 dB

Peak SAR (extrapolated) = 1.56 W/kg

**SAR(1 g) = 0.610 mW/g; SAR(10 g) = 0.268 mW/g**

Maximum value of SAR (measured) = 0.705 mW/g





**TOP TEST RESULTS**

**Ambient Temperature:**  $24 \pm 1^{\circ}\text{C}$   
**Tissue Temperature:**  $24 \pm 1^{\circ}\text{C}$   
**Humidity:** 54% to 59%

Test Laboratory: TUV SUD PSB PTE LTD.

Date/Time: 12/31/2009 10:59:24 AM

File Name: [EUT Top\\_Ch 3\\_2464MHz.da4](#)

Program Name: EUT Top\_Ch 3\_2464MHz\_Data 1.da4

Phantom section: Flat Section

DUT: Sound Blaster WL

Communication System: 2450 Mhz

Frequency: 2464 MHz

Duty Cycle: 1:1

Medium: Body 2450 MHz Medium parameters used:  $f = 2450\text{ MHz}$ ;  $\sigma = 1.97\text{ mho/m}$ ;  $\epsilon_r = 52.1$ ;  $\rho = 1000\text{ kg/m}^3$

**DASY4 Configuration:**

Electronics: DAE4 Sn627

Calibrated: 6/14/2007

Phantom: SAM 12

Measurement SW: DASY4, V4.7 Build 80

Probe: EX3DV4 - SN3541

ConvF(7.07, 7.07, 7.07)

Calibrated: 7/13/2007

Post processing SW: SEMCAD, V1.8 Build 186

Sensor-Surface: 4mm (Mechanical Surface Detection)

**EUT Top\_Ch 3\_2464MHz\_Data 1/Area Scan (7x21x1):** Measurement grid:

$dx=5\text{mm}$ ,  $dy=5\text{mm}$

Maximum value of SAR (measured) = 0.545 mW/g




**EUT Top\_Ch 3\_2464MHz\_Data 1/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 15.8 V/m; Power Drift = 0.049 dB

Peak SAR (extrapolated) = 1.29 W/kg

**SAR(1 g) = 0.472 mW/g; SAR(10 g) = 0.201 mW/g**

Maximum value of SAR (measured) = 0.548 mW/g





## SIDE TEST RESULTS

**Ambient Temperature:**  $24 \pm 1^{\circ}\text{C}$   
**Tissue Temperature:**  $24 \pm 1^{\circ}\text{C}$   
**Humidity:** 54% to 59%

Test Laboratory: TUV SUD PSB PTE LTD.

Date/Time: 1/04/2010 9:45:13 AM

File Name: [EUT SIDE\\_Ch 1\\_2412MHz.da4](#)

Program Name: EUT Side\_Ch 1\_2412MHz\_Data 1.da4

Phantom section: Flat Section

DUT: Sound Blaster WL

Communication System: 2450 Mhz

Frequency: 2412 MHz

Duty Cycle: 1:1

Medium: Body 2450 MHz Medium parameters used:  $f = 2450\text{ MHz}$ ;  $\sigma = 1.97\text{ mho/m}$ ;  $\epsilon_r = 52.1$ ;  $\rho = 1000\text{ kg/m}^3$

### DASY4 Configuration:

Electronics: DAE4 Sn627

Calibrated: 6/14/2007

Phantom: SAM 12

Measurement SW: DASY4, V4.7 Build 80

Probe: EX3DV4 - SN3541

ConvF(7.07, 7.07, 7.07)

Calibrated: 7/13/2007

Post processing SW: SEMCAD, V1.8 Build 186

Sensor-Surface: 4mm (Mechanical Surface Detection)

**EUT Side\_Ch 1\_2412MHz\_Data 1/Area Scan (13x24x1):** Measurement grid:

$dx=5\text{mm}$ ,  $dy=5\text{mm}$

Maximum value of SAR (measured) =  $0.627\text{ mW/g}$



**EUT Side\_Ch 1\_2412MHz\_Data 1/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $13.4\text{ V/m}$ ; Power Drift =  $-0.156\text{ dB}$

Peak SAR (extrapolated) =  $0.923\text{ W/kg}$

**SAR(1 g) =  $0.577\text{ mW/g}$ ; SAR(10 g) =  $0.395\text{ mW/g}$**

Maximum value of SAR (measured) =  $0.616\text{ mW/g}$





## SIDE TEST RESULTS

Ambient Temperature:  $24 \pm 1^{\circ}\text{C}$   
Tissue Temperature:  $24 \pm 1^{\circ}\text{C}$   
Humidity: 54% to 59%

Test Laboratory: TUV SUD PSB PTE LTD.

Date/Time: 1/04/2010 10:42:40 AM

File Name: [EUT SIDE\\_Ch 2\\_2438MHz.da4](#)

Program Name: EUT Side \_Ch 2\_2438MHz\_Data 1.da4

Phantom section: Flat Section

DUT: Sound Blaster WL

Communication System: 2450 Mhz

Frequency: 2438 MHz

Duty Cycle: 1:1

Medium: Body 2450 MHz Medium parameters used:  $f = 2450\text{ MHz}$ ;  $\sigma = 1.97\text{ mho/m}$ ;  $\epsilon_r = 52.1$ ;  $\rho = 1000\text{ kg/m}^3$

### DASY4 Configuration:

Electronics: DAE4 Sn627

Calibrated: 6/14/2007

Phantom: SAM 12

Measurement SW: DASY4, V4.7 Build 80

Probe: EX3DV4 - SN3541

ConvF(7.07, 7.07, 7.07)

Calibrated: 7/13/2007

Post processing SW: SEMCAD, V1.8 Build 186

Sensor-Surface: 4mm (Mechanical Surface Detection)

**EUT Side\_Ch 2\_2438MHz\_Data 1/Area Scan (13x24x1):** Measurement grid:

$dx=5\text{mm}$ ,  $dy=5\text{mm}$

Maximum value of SAR (measured) =  $0.528\text{ mW/g}$

**EUT Side\_Ch 2\_2438MHz\_Data 1/Zoom Scan (7x7x7)/Cube 0:** Measurement




grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $12.4\text{ V/m}$ ; Power Drift =  $0.302\text{ dB}$

Peak SAR (extrapolated) =  $0.770\text{ W/kg}$

**SAR(1 g) =  $0.505\text{ mW/g}$ ; SAR(10 g) =  $0.364\text{ mW/g}$**

Maximum value of SAR (measured) =  $0.533\text{ mW/g}$



## SIDE TEST RESULTS

Ambient Temperature:  $24 \pm 1^{\circ}\text{C}$   
Tissue Temperature:  $24 \pm 1^{\circ}\text{C}$   
Humidity: 54% to 59%

Test Laboratory: TUV SUD PSB PTE LTD.

Date/Time: 1/04/2010 14:21:27 AM

File Name: [EUT SIDE\\_Ch 3\\_2464MHz.da4](#)

Program Name: EUT Side \_Ch 3\_2464MHz\_Data 1.da4

Phantom section: Flat Section

DUT: Sound Blaster WL

Communication System: 2450 Mhz

Frequency: 2464 MHz

Duty Cycle: 1:1

Medium: Body 2450 MHz Medium parameters used:  $f = 2450\text{ MHz}$ ;  $\sigma = 1.97\text{ mho/m}$ ;  $\epsilon_r = 52.1$ ;  $\rho = 1000\text{ kg/m}^3$

### DASY4 Configuration:

Electronics: DAE4 Sn627

Calibrated: 6/14/2007

Phantom: SAM 12

Measurement SW: DASY4, V4.7 Build 80

Probe: EX3DV4 - SN3541

ConvF(7.07, 7.07, 7.07)

Calibrated: 7/13/2007

Post processing SW: SEMCAD, V1.8 Build 186

Sensor-Surface: 4mm (Mechanical Surface Detection)

**EUT Side\_Ch 3\_2464MHz\_Data 1/Area Scan (13x24x1):** Measurement grid:

$dx=5\text{mm}$ ,  $dy=5\text{mm}$

Maximum value of SAR (measured) =  $0.462\text{ mW/g}$

**EUT Side\_Ch 3\_2464MHz\_Data 1/Zoom Scan (7x7x7)/Cube 0:** Measurement




grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $12.1\text{ V/m}$ ; Power Drift =  $0.208\text{ dB}$

Peak SAR (extrapolated) =  $0.627\text{ W/kg}$

**SAR(1 g) =  $0.445\text{ mW/g}$ ; SAR(10 g) =  $0.344\text{ mW/g}$**

Maximum value of SAR (measured) =  $0.460\text{ mW/g}$





**Effective Radiated Power (ERP) Measurement:**

Front/Rear

Output Peak Power (dBm) Before Test	17.5	17.4	17.2
Output Peak Power (dBm) After Test	17.2	17.3	17.0

Top/Side

Output Peak Power (dBm) Before Test	17.5	17.4	17.2
Output Peak Power (dBm) After Test	17.2	17.3	17.0





This Report is issued under the following conditions:

1. Results of the testing/calibration in the form of a report will be issued immediately after the service has been completed or terminated.
2. Unless otherwise requested, a report shall contain only technical results. Analysis and interpretation of the results and professional opinion and recommendations expressed thereupon, if required, shall be clearly indicated and additional fee paid for, by the Client.
3. This report applies to the sample of the specific product/equipment given at the time of its testing/calibration. The results are not used to indicate or imply that they are applicable to other similar items. In addition, such results must not be used to indicate or imply that TÜV SÜD PSB approves, recommends or endorses the manufacturer, supplier or user of such product/equipment, or that TÜV SÜD PSB in any way "guarantees" the later performance of the product/equipment.
4. The sample/s mentioned in this report is/are submitted/supplied/manufactured by the Client. TÜV SÜD PSB therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture, consignment or any information supplied.
5. Additional copies of the report are available to the Client at an additional fee. No third party can obtain a copy of this report through TÜV SÜD PSB, unless the Client has authorised TÜV SÜD PSB in writing to do so.
6. TÜV SÜD PSB may at its sole discretion add to or amend the conditions of the report at the time of issue of the report and such report and such additions or amendments shall be binding on the Client.
7. All copyright in the report shall remain with TÜV SÜD PSB and the Client shall, upon payment of TÜV SÜD PSB's fees for the carrying out of the tests/calibrations, be granted a license to use or publish the report to the third parties subject to the terms and conditions herein, provided always that TÜV SÜD PSB may at its absolute discretion be entitled to impose such conditions on the license as it sees fit.
8. Nothing in this report shall be interpreted to mean that TÜV SÜD PSB has verified or ascertained any endorsement or marks from any other testing authority or bodies that may be found on that sample.
9. This report shall not be reproduced wholly or in parts and no reference shall be made by the Client to TÜV SÜD PSB or to the report or results furnished by TÜV SÜD PSB in any advertisements or sales promotion.
10. Unless otherwise stated, the tests are carried out in TÜV SÜD PSB Pte Ltd, No.1 Science Park Drive Singapore 118221.

March 2009



**TEST INSTRUMENTATION & GENERAL PROCEDURES**

**ANNEX A**



## **TEST INSTRUMENTATION & GENERAL PROCEDURES**

## **ANNEX A**

### **A.1 General Test Procedure**

In the SAR measurement, the positioning of the probes must be performed with sufficient accuracy to obtain repeatable measurements in the presence of rapid spatial attenuation phenomena. The accurate positioning of the E-field probe is accomplished by using a high precision robot. The robot can be taught to position the probe sensor following a specific pattern of points. In a first sweep, the sensor is positioned as close as possible to the interface, with the sensor enclosure touching the inside of the fiberglass shell. The SAR is measured on a grid of points, which covers the curved surface of the phantom in an area larger than the size of the EUT. After the initial scan, a high- resolution grid is used to locate the absolute maximum measured energy point. At this location, attenuation versus depth scan will be accomplished by the measurement system to calculate the SAR value.

### **A.2 SAR Test Instrumentation**

#### **SAR Measurement System**

- **Positioning Equipment**

Type: High Precision Industrial Robot, RX90.  
Precision: High precision (repeatability 0.02mm)  
Reliability: High reliability (industrial design)

- **Compaq Computer**

Type: 2.4GHz Pentium  
Memory: 512MB SDRAM  
Operating System: Windows 2000  
Dell Monitor: 17" LCD

- **Dosimetric E-Field Probe**

Type: ET3DV6  
Isotropy Error ( $\varnothing$ ):  $\pm 0.25\text{dB}$   
Dynamic Range: 0.01 – 100 W/kg

- **Phantom & Tissue**

Phantom: "Phantom SAM 12" and "450MHz Phantom" were manufactured by SPEAG.  
Tissue: Simulated Tissue with electrical characteristics similar to those of the human at normal body temperature ( $23 \pm 1^\circ\text{C}$ )  
Shell: Fiberglass shell phantom with 2mm thickness for "Phantom SAM 12".  
Fiberglass shell phantom with 2mm or 6mm thickness for "450MHz Flat Phantom".

## TEST INSTRUMENTATION & GENERAL PROCEDURES

## ANNEX A

### A.3 Test Setup

#### Phantom



The "Phantom SAM 12", manufactured by SPEAG is a fiberglass shell phantom with 2 mm shell thickness. It has three measurement areas:

- Left hand
- Right hand
- Flat phantom

The "450MHz Flat Phantom", manufactured by SPEAG is a fiberglass shell phantom with 2mm or 6mm shell thickness. It has one measurement areas:

- Flat phantom

- 1) The "Phantom SAM 12" table comes in the sizes: A 100x50x85 cm (LxWxH).
- 2) The "450MHz Flat Phantom – 6mm Shell Thickness" table comes in the sizes: A 82x44x18 cm (LxWxH) is used for System Validation Test.
- 3) The "450MHz Flat Phantom – 2mm Shell Thickness" table comes in the sizes: A 82x44x18 cm (LxWxH) is used for SAR Measurement.

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. Only one device holder is necessary if two phantoms are used (e.g., for different solutions).

#### Simulated tissue

**Simulated Tissue: Suggested in a paper by George Hartsgrrove and colleagues in University of Ottawa Ref.: Bioelectromagnetics 8:29-36 (1987)**

This simulated tissue is mainly composed of water, sugar and salt. At higher frequencies, in order to achieve the proper conductivity, the solution does not contain salt. Also, at these frequencies, D.I. water and alcohol is preferred.

Tissue Density : Approximately 1.25 g/cm<sup>3</sup>

#### • **Preparation**

The ingredients (i.e. water, sugar, salt, etc) required to prepare the simulated tissue are carefully weighed and poured into a clean container for mixing. A stirring paddle, that is



**TEST INSTRUMENTATION & GENERAL PROCEDURES**

**ANNEX A**

attached to a hand drill is used to stir the solution for a duration of about 30 minutes or more. When the ingredients are completely dissolved, the solution is left in the container for the air bubbles to disappear.

- **Measurement of Electrical Characteristics of Simulated Tissue**
  - 1) S-PARAMETER Network Analyzer, Agilent 8753ES (30kHz – 6GHz)
  - 2) Agilent 85070D Dielectric Probe Kit



**TEST INSTRUMENTATION & GENERAL PROCEDURES**

**ANNEX A**

**ELECTRICAL CHARACTERISTIC  
MEASUREMENT SETUP**



- **Description of the Agilent 85070D Dielectric Probe Kit**

The 85070D is a dielectric probe that is used to measure the intrinsic electrical properties of materials in the RF and microwave frequency bands. The 85070D software allows you to measure the complex dielectric constant (also called permittivity) of liquids and semi-solids, including the dielectric loss factor of loss tangent.

To obtain data at hundreds of frequencies in seconds, simply immerse the probe into liquids or semi-solids - no special fixtures or containers are required. The 85070D must be used in conjunction with an Agilent network analyzer. The network analyzer provides the high frequency stimulus, and measures the reflected response.


The probe transmits a signal into the material under test (MUT). The measured reflected response from the materials is then related to its dielectric properties. A computer controls the system, and runs software that guides the user through a measurement sequence. An effort is made to keep the results dielectric constant and conductivity within 5 % of published data.

## TEST INSTRUMENTATION & GENERAL PROCEDURES


## ANNEX A

### Tissue Depth

The tissue depth at the “Phantom SAM 12”, “450MHz Flat Phantom – 6mm Shell Thickness” and “450MHz Flat Phantom – 2mm Shell Thickness” is approximately 15cm  $\pm$  0.5cm.




At “Phantom SAM 12”



Tissue – 15.0cm Depth




At “450MHz Flat Phantom – 6mm Shell Thickness”



Tissue – 15.2cm Depth



At “450MHz Flat Phantom – 2mm Shell Thickness”




Tissue – 14.9cm Depth

## TEST INSTRUMENTATION & GENERAL PROCEDURES

## ANNEX A

### Positioning of EUT



The **DASY4 holder** is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of 65°. The intended use position in the CENELEC document is has a rotation angle of 65° and an inclination angle of 80°. The rotation centers for both scales is the ear opening. Thus the device needs no repositioning when changing the angles. The device rotation around the device axis is not changed in the holder. In the CENELEC standard it is always 0°. If the standard changes, a support will be provided with the new angle.

1. **“Cheek/Touch Position”** – the device is brought toward the mouth of the head phantom by pivoting against the “ear reference point” or along the “N-F” line for the SCC-34/SC-2 head phantom. This test position is established:
  - i) When any point on the display, keypad or mouthpiece portions of the handset is in contact with the phantom.
  - ii) (Or) When any portion of a foldout, sliding or similar keypad cover opened to its intended self-adjusting normal use position is in contact with the cheek or mouth of the phantom.

For existing head phantoms – when the handset loses contact with the phantom at the pivoting point, rotation should continue until the device touches the cheek of the phantom or breaks its last contact from the ear spacer.
2. **“Ear/Tilt Position”** – With the handset aligned in the “Cheek/Touch Position”:
  - i) If the earpiece of the handset is not in full contact with the phantom’s ear spacer (in the “Cheek/Touch position”) and the peak SAR location for the “Cheek/Touch” position is located at the ear spacer region or corresponds to the earpiece region of the handset, the device should be returned to the “initial ear position” by rotating it away from the mouth until the earpiece is in full contact with the ear spacer.
  - ii) (Otherwise) The handset should be moved (translated) away from the cheek perpendicular to the line passes through both “ear reference points” (note: one of these ear reference points may not physically exist on a split head model) for approximate 2-3 cm. While it is in this position, the handset is tilted away from the mouth with respect to the “test device reference point” by 15°. After the tilt, it is then moved (translated) back toward the head perpendicular to the line passes through both “ear reference points” until the device touches the phantom or the ear spacer. If the antenna touches the head first, the positioning process should be repeated with a tilt angle less than 15° so that the device and its antenna would touch the phantom simultaneously. This test position may require a device holder or positioner to achieve the translation and tilting with acceptable positioning repeatability.



## **TEST INSTRUMENTATION & GENERAL PROCEDURES**

## **ANNEX A**

### **3. Body Worn Configuration**

All body worn accessories are tested for the FCC RF exposure compliance. The phone is positioned into carrying case (if available) and placed below of the flat phantom. Headset or ear piece (if available) is connected during measurements.

#### **Effective Radiated Power (ERP)**


Set up as shown in Figure1 with EUT was substituted with a transmit antenna that connected to a signal generator. Set the Signal generator to transmit at lower channel of EUT and arbitrarily set the power level so that the received signal by the receiver is a noise-free signal. Rule of Thumb: 0dBm at 3m distance. Record the power level received after maximization. Compute path loss,  $L_{path}$  as follows:

$$\begin{aligned} L_{path} &= \text{transmitted power} - \text{receiver level} \\ &= \text{signal generator level} - \text{cable loss} + \text{antenna gain} - \text{receiver level} \end{aligned}$$


Replace transmitting antenna with EUT that transmits at low channel. Record the power level received after maximization. Compute the ERP as follows:

$$\text{ERP} = \text{receiver level} + \text{pass loss}$$

Repeat the above test procedures when making measurement at EUT middle and high channels.



## ERP Measurement Setup



***Figure 1***

# **TEST INSTRUMENTATION & GENERAL PROCEDURES**

# **ANNEX A**

<u>Instrument</u>	<u>Model</u>	<u>S/No</u>	<u>Cal Due Date</u>	
Boonton RF Power Meter (Dual Channel)	4532	97701	1 April 2010	√
Boonton Power Sensor	51075	51075	1 April 2010	√
Boonton Power Sensor	51075	32002	1 April 2010	√
S-Parameter Network Analyzer (30kHz – 6GHz)	8753ES	MY40001026	31 Mar 2010	√
Agilent 85070D Dielectric Probe Kit	85075D	21356	-	√
Anritsu RF Signal Generator (10MHz – 20GHz)	68347C	04306	-	√
Amplifier Research Power Amplifier (1MHz – 1000MHz)	25W1000B	27225	-	
Amplifier Research Power Amplifier (800MHz – 4.2GHz)	25S1G4A	29346	-	√
Agilent Dual Directional Coupler (0.1~2.0)GHz	HP778D	18289	-	√
AR Directional Coupler (0.8~4.2)GHz	DC7144	29245	-	
2450MHz System Validation Dipole	D2450V2	752	25 Jun 2010	√
Data Acquisition Electronics (DAE4)	DAE4	627	25 Jun 2010	√
Dosimetric E-field Probe	EX3DV4	3541	24 July 2010	√



**TEST SETUP PHOTOGRAPHS**

**ANNEX B**



## TEST SETUP PHOTOGRAPHS

## ANNEX B

### SAR Test Setup Photographs



SAR Test Setup At Flat Phantom



## TEST SETUP PHOTOGRAPHS

## ANNEX B

### SAR Test Setup Photographs



SAR Test Setup At Flat Phantom – Closer View (EUT **Front** Touched Phantom)



SAR Test Setup At Flat Phantom – Closer View (EUT **Rear** Touched Phantom)

## TEST SETUP PHOTOGRAPHS

## ANNEX B

### SAR Test Setup Photographs



SAR Test Setup At Flat Phantom – Closer View (EUT Side Touched Phantom)



SAR Test Setup At Flat Phantom – Closer View (EUT Top Touched Phantom)

**TEST SETUP PHOTOGRAPHS**

**ANNEX B**

**Effective Radiated Power Test Setup Photographs**



Effective Radiated Power Test Setup - front



Effective Radiated Power Test Setup - Rear

**TEST SETUP PHOTOGRAPHS**

**ANNEX B**

**EUT PHOTOGRAPHS**



Front of EUT



Rear of EUT

**TEST SETUP PHOTOGRAPHS**

**ANNEX B**

**EUT PHOTOGRAPHS**




**EUT with Accessories**

SUD



**TISSUE SIMULANT DATA SHEETS**

**ANNEX C**



## SAR VALIDATION

## ANNEX D

Type of Tissue	Body
Target Frequency (MHz)	2450
Target Dielectric Constant	52.7
Target Conductivity (S/m)	1.9
Composition (by weight)	Water 25500 (72.55%) Glycol 9610 (27.34%) Sugar (0%) Salt 38.4 (0.11%) HEC (0%) Preventol D7 (0%)
Measured Dielectric Constant	51.85
Measured Conductivity (S/m)	1.9639

Probe Name	Dosimetric E-field Probe EX3DV4
Probe Serial Number	3541
Sensor Offset (mm)	1.0
Conversion Factor	7.54 ± 11.8 %
Probe Calibration Due Date (DD/MM/YY)	24/06/10



## SAR VALIDATION

## ANNEX D

### Body Tissue at 2450MHz

Frequency	e'	e''	Conductivity
2440000000	54.9456	14.7150	1.9947
2441000000	54.8006	14.6860	1.9915
2442000000	54.6752	14.6697	1.9901
2443000000	54.5313	14.6304	1.9856
2444000000	54.3769	14.6221	1.9853
2445000000	54.2271	14.6032	1.9836
2446000000	54.0869	14.5822	1.9815
2447000000	53.9691	14.5539	1.9785
2448000000	53.8516	14.5757	1.9822
2449000000	53.7201	14.5734	1.9827
<b>2450000000</b>	<b>53.5945</b>	<b>14.5567</b>	<b>1.9813</b>
2451000000	53.4913	14.5452	1.9805
2452000000	53.3798	14.5203	1.9779
2453000000	<b>53.2817</b>	14.5038	1.9765
2454000000	53.1717	14.4912	1.9756
2455000000	53.0747	14.5021	1.9779
2456000000	53.0102	14.4911	1.9772
2457000000	52.9350	14.5165	1.9815
2458000000	52.8455	14.5090	1.9812
2459000000	52.7897	14.5221	1.9838
2460000000	52.7370	14.5210	1.9845
2461000000	52.6863	14.5202	1.9852
2462000000	52.6573	14.5360	1.9882
2463000000	52.6111	14.5202	1.9868
2464000000	52.5934	14.5484	1.9915
2465000000	52.5656	14.5479	1.9922
2466000000	52.5603	14.5821	1.9977
2467000000	52.5705	14.6265	2.0046
2468000000	52.5908	14.6253	2.0052
2469000000	52.5979	14.6565	2.0103
2470000000	52.6129	14.6640	2.0122
2471000000	52.6568	14.6762	2.0147
2472000000	52.6891	14.7001	2.0188
2473000000	52.7418	14.7115	2.0211
2474000000	52.8089	14.7501	2.0273
2475000000	52.8636	14.7706	2.0309
2476000000	52.9443	14.8070	2.0367
2477000000	53.0112	14.8402	2.0421
2478000000	53.1074	14.8701	2.0471
2479000000	53.1974	14.9030	2.0524
2480000000	53.2933	14.9152	2.0549

Tested by: SSW  
Date : 28-Dec-2009  
Frequency: 2450MHz  
Mixture: Body Tissue  
Tissue temp: 24°C

Composition		
Tap Water	0.0g	0.00%
Ultra Pure Water	25000.0g	72.16%
Sugar	0.0g	0.00%
Glyco	9608.0g	27.73%
Salt	40.0g	0.11%
Preventol D7	0.0g	0.00%
Total Weight	34648g	100.0%

Result (FCC)	Dielectric Constant	Conductivity
Measured	53.28	1.9765
Target (FCC)	52.70	1.95
Low Limit	50.065	1.8525
High Limit	55.335	2.0475
% Off Target	1.10	1.36

(e' = Dielectric Constant)  
(e'' = Loss Factor)



**SAR VALIDATION**

**ANNEX D**





## **SAR VALIDATION**

## **ANNEX D**

**Body Tissue at 2450MHz (Dipole forward power = 250mW)**

Test Laboratory: TUV SUD PSB PTE LTD.

Date/Time: 12/28/2009 4:46:28 PM

File Name: [2450MHz\\_System validation 28Dec09.da4](#)

Program Name: 2450MHz\_System validation.da4

Phantom section: Flat Section

DUT: Dipole 2450 MHz

Communication System: CW

Frequency: 2450 MHz

Duty Cycle: 1:1

Medium: Body 2450 MHz Medium parameters used:  $f = 2450 \text{ MHz}$ ;  $\sigma = 1.94 \text{ mho/m}$ ;  $\epsilon_r = 52.1$ ;  $\rho = 1000 \text{ kg/m}^3$

### **DASY4 Configuration:**

Electronics: DAE4 Sn627

Calibrated: 6/14/2007

Phantom: SAM 12

Measurement SW: DASY4, V4.7 Build 80

Probe: EX3DV4 - SN3541

ConvF(7.07, 7.07, 7.07)

Calibrated: 7/13/2007

Post processing SW: SEMCAD, V1.8 Build 186

Sensor-Surface: 4mm (Mechanical Surface Detection)

**2450MHz\_Data 1/Area Scan (7x9x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (measured) = 13.1 mW/g

**2450MHz\_Data 1/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 82.0 V/m; Power Drift = -0.066 dB



Peak SAR (extrapolated) = 25.1 W/kg

**SAR(1 g) = 12 mW/g; SAR(10 g) = 5.48 mW/g**

Maximum value of SAR (measured) = 13.6 mW/g

## SAR VALIDATION

## ANNEX D





**MEASUREMENT UNCERTAINTY**

**ANNEX E**



## MEASUREMENT UNCERTAINTY

## ANNEX E

### Measurement Uncertainty

All test measurement carried out are traceable to national standards. The uncertainty of measurement at a confidence level of 95%, with a coverage of 2, is **±20.6%**.

Error Description	Uncertainty Value ± %	Probability Distribution	Divisor	ci 1g	Standard Unc.(1g)	Vi or Veff
Measurement System						
Probe Calibration	± 4.8	normal	1	1	± 4.8	∞
Axial isotropy	± 4.7	rectangular	√3	(1-cp)^1/2	± 1.9	∞
Hemispherical Isotropy	± 9.6	rectangular	√3	(cp)^1/2	± 3.9	∞
Spatial resolution	± 0.0	rectangular	√3	1	± 0.0	∞
Boundary effects	± 1.0	rectangular	√3	1	± 0.6	∞
Linearity	± 4.7	rectangular	√3	1	± 2.7	∞
System Detection limit	± 1.0	rectangular	√3	1	± 0.6	∞
Readout electronics	± 1.0	normal	1	1	± 1.0	∞
Response time	± 0.8	rectangular	√3	1	± 0.5	∞
Integration time	± 2.6	rectangular	√3	1	± 1.5	∞
RF ambient conditions	± 3.0	rectangular	√3	1	± 1.7	∞
Probe Positioning Mechanical Tolerance	± 0.4	rectangular	√3	1	± 0.2	∞
Probe Positioning with respect to Phantom Shell	± 2.9	rectangular	√3	1	± 1.7	∞
Extrapolation, Interpolation and Integration Algorithms for Max. SAR Evaluation	± 1.0	rectangular	√3	1	± 0.6	∞
Test Sample Related						
Device positioning	± 2.9	normal	1	1	± 2.9	145
Device holder uncertainty	± 3.6	normal	1	1	± 3.6	5
Power drift	± 5.0	rectangular	√3	1	± 2.9	∞
Phantom and Tissue Parameters						
Phantom uncertainty	± 4.0	rectangular	√3	1	± 2.3	∞
Liquid conductivity (target)	± 5.0	rectangular	√3	0.64	± 1.8	∞
Liquid conductivity (meas)	± 2.5	normal	1	0.64	± 1.6	∞
Liquid permittivity (target)	± 5.0	rectangular	√3	0.6	± 1.7	∞
Liquid permittivity (meas)	± 2.5	normal	1	0.6	± 1.5	∞
Combined Standard Uncertainty					± 10.3	330
Coverage Factor for 95%	k=2					
Extended Standard Uncertainty					± 20.6	



**SAR PROBE CALIBRATION CERTIFICATES**

**ANNEX F**

**ANNEX F**  
**SAR PROBE CALIBRATION CERTIFICATES**





**SAR PROBE CALIBRATION CERTIFICATES**

**ANNEX F**

**Calibration Laboratory of**  
**Schmid & Partner**  
**Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Client **TUV SUD PSB Pte Ltd.**

Certificate No: **EX3-3541\_Jun09**

**CALIBRATION CERTIFICATE**

Object **EX3DV4 - SN:3541**

Calibration procedure(s) **QA CAL-01.v6 and QA CAL-23.v3  
Calibration procedure for dosimetric E-field probes**

Calibration date: **June 22, 2009**

Condition of the calibrated item **In Tolerance**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^{\circ}\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	1-Apr-09 (No. 217-01030)	Apr-10
Power sensor E4412A	MY41495277	1-Apr-09 (No. 217-01030)	Apr-10
Power sensor E4412A	MY41499087	1-Apr-09 (No. 217-01030)	Apr-10
Reference 3 dB Attenuator	SN: S5054 (3c)	31-Mar-09 (No. 217-01026)	Mar-10
Reference 20 dB Attenuator	SN: S5086 (20b)	31-Mar-09 (No. 217-01026)	Mar-10
Reference 30 dB Attenuator	SN: S5129 (30b)	31-Mar-09 (No. 217-01027)	Mar-10
Reference Probe ES3DV2	SN: 3013	2-Jan-09 (No. ES3-3013_Jan09)	Jan-10
DAE4	SN: 660	9-Sep-08 (No. DAE4-660_Sep08)	Sep-09

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Oct-07)	In house check: Oct-09
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-08)	In house check: Oct-09

Calibrated by:	Name	Function	Signature
	Marcel Fehr	Laboratory Technician	

Approved by:	Name	Function
	Katja Pokovic	Technical Manager

Issued: June 22, 2009

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



**SAR PROBE CALIBRATION CERTIFICATES**

**ANNEX F**

**Calibration Laboratory of**  
Schmid & Partner  
Engineering AG  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

**Glossary:**

TSL	tissue simulating liquid
NORM <sub>x,y,z</sub>	sensitivity in free space
ConvF	sensitivity in TSL / NORM <sub>x,y,z</sub>
DCP	diode compression point
Polarization $\phi$	$\phi$ rotation around probe axis
Polarization $\vartheta$	$\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis

**Calibration is Performed According to the Following Standards:**

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

**Methods Applied and Interpretation of Parameters:**

- NORM<sub>x,y,z</sub>:** Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not effect the E<sup>2</sup>-field uncertainty inside TSL (see below ConvF).
- NORM(f)<sub>x,y,z</sub> = NORM<sub>x,y,z</sub> \* frequency\_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>:** DCP are numerical linearization parameters assessed based on the data of power sweep (no uncertainty required). DCP does not depend on frequency nor media.
- ConvF and Boundary Effect Parameters:** Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy):** in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset:** The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.



**SAR PROBE CALIBRATION CERTIFICATES**

**ANNEX F**

EX3DV4 SN:3541

June 22, 2009

**Probe EX3DV4**

**SN:3541**

Manufactured:	May 3, 2004
Last calibrated:	June 23, 2008
Recalibrated:	June 22, 2009

Calibrated for DASY Systems

(Note: non-compatible with DASY2 system!)



## SAR PROBE CALIBRATION CERTIFICATES

## ANNEX F

EX3DV4 SN:3541

June 22, 2009

### DASY - Parameters of Probe: EX3DV4 SN:3541

#### Sensitivity in Free Space<sup>A</sup>

#### Diode Compression<sup>B</sup>

NormX	0.49 ± 10.1%	$\mu V/(V/m)^2$	DCP X	91 mV
NormY	0.39 ± 10.1%	$\mu V/(V/m)^2$	DCP Y	92 mV
NormZ	0.45 ± 10.1%	$\mu V/(V/m)^2$	DCP Z	92 mV

#### Sensitivity in Tissue Simulating Liquid (Conversion Factors)

Please see Page 8.

#### Boundary Effect

TSL 900 MHz Typical SAR gradient: 5 % per mm

Sensor Center to Phantom Surface Distance	2.0 mm	3.0 mm
SAR <sub>be</sub> [%] Without Correction Algorithm	9.0	5.0
SAR <sub>be</sub> [%] With Correction Algorithm	0.8	0.4

TSL 1750 MHz Typical SAR gradient: 10 % per mm

Sensor Center to Phantom Surface Distance	2.0 mm	3.0 mm
SAR <sub>be</sub> [%] Without Correction Algorithm	6.9	3.7
SAR <sub>be</sub> [%] With Correction Algorithm	0.8	0.5

#### Sensor Offset

Probe Tip to Sensor Center 1.0 mm

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of NormX,Y,Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Page 8).

<sup>B</sup> Numerical linearization parameter: uncertainty not required.



**SAR PROBE CALIBRATION CERTIFICATES**


**ANNEX F**

EX3DV4 SN:3541

June 22, 2009

**Frequency Response of E-Field**

(TEM-Cell:ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  ( $k=2$ )



**SAR PROBE CALIBRATION CERTIFICATES**

**ANNEX F**

EX3DV4 SN:3541

June 22, 2009

**Receiving Pattern ( $\phi$ ),  $\vartheta = 0^\circ$**



Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  ( $k=2$ )



**SAR PROBE CALIBRATION CERTIFICATES**

**ANNEX F**

EX3DV4 SN:3541

June 22, 2009

**Dynamic Range f(SAR<sub>head</sub>)**  
(Waveguide R22, f = 1800 MHz)



Uncertainty of Linearity Assessment:  $\pm 0.6\%$  (k=2)


## SAR PROBE CALIBRATION CERTIFICATES

## ANNEX F

EX3DV4 SN:3541

June 22, 2009

### Conversion Factor Assessment



f [MHz]	Validity [MHz] <sup>c</sup>	TSL	Permittivity	Conductivity	Alpha	Depth	ConvF Uncertainty
900	± 50 / ± 100	Head	41.5 ± 5%	0.97 ± 5%	0.49	0.74	9.26 ± 11.0% (k=2)
1750	± 50 / ± 100	Head	40.1 ± 5%	1.37 ± 5%	0.51	0.69	8.40 ± 11.0% (k=2)
1900	± 50 / ± 100	Head	40.0 ± 5%	1.40 ± 5%	0.46	0.75	8.11 ± 11.0% (k=2)
2450	± 50 / ± 100	Head	39.2 ± 5%	1.80 ± 5%	0.34	0.82	7.42 ± 11.0% (k=2)
900	± 50 / ± 100	Body	55.0 ± 5%	1.05 ± 5%	0.36	0.83	9.41 ± 11.0% (k=2)
1750	± 50 / ± 100	Body	53.4 ± 5%	1.49 ± 5%	0.48	0.73	8.14 ± 11.0% (k=2)
1900	± 50 / ± 100	Body	53.3 ± 5%	1.52 ± 5%	0.36	0.90	7.79 ± 11.0% (k=2)
2450	± 50 / ± 100	Body	52.7 ± 5%	1.95 ± 5%	0.36	0.88	7.71 ± 11.0% (k=2)

<sup>c</sup> The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.



**SAR PROBE CALIBRATION CERTIFICATES**


**ANNEX F**

EX3DV4 SN:3541

June 22, 2009

**Deviation from Isotropy in HSL**

Error ( $\phi$ ,  $\vartheta$ ),  $f = 900$  MHz



Uncertainty of Spherical Isotropy Assessment:  $\pm 2.6\%$  ( $k=2$ )



**SAR PROBE CALIBRATION CERTIFICATES**

**ANNEX F**

**Calibration Laboratory of**  
**Schmid & Partner**  
**Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **TUV SUD PSB**

Certificate No. **DAE4-627\_Jun09**

**CALIBRATION CERTIFICATE**

Object **DAE4 - SD 000 D04 BJ - SN: 627**

Calibration procedure(s) **QA CAL-06.v12  
Calibration procedure for the data acquisition electronics (DAE)**

Calibration date: **June 24, 2009**

Condition of the calibrated item **In Tolerance**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Fluke Process Calibrator Type 702	SN: 6295803	30-Sep-08 (No: 7673)	Sep-09
Keithley Multimeter Type 2001	SN: 0810278	30-Sep-08 (No: 7670)	Sep-09
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Calibrator Box V1.1	SE UMS 006 AB 1004	05-Jun-09 (in house check)	In house check: Jun-10

Calibrated by:	Name Andrea Guntli	Function Technician	Signature 
Approved by:	Fin Bomholt	R&D Director	

Issued: June 24, 2009

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



**SAR PROBE CALIBRATION CERTIFICATES**

**ANNEX F**

**Calibration Laboratory of**  
**Schmid & Partner**  
**Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

**Glossary**

**DAE** data acquisition electronics  
**Connector angle** information used in DASY system to align probe sensor X to the robot coordinate system.

**Methods Applied and Interpretation of Parameters**

- **DC Voltage Measurement:** Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- **Connector angle:** The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The following parameters as documented in the Appendix contain technical information as a result from the performance test and require no uncertainty.
  - **DC Voltage Measurement Linearity:** Verification of the Linearity at +10% and -10% of the nominal calibration voltage. Influence of offset voltage is included in this measurement.
  - **Common mode sensitivity:** Influence of a positive or negative common mode voltage on the differential measurement.
  - **Channel separation:** Influence of a voltage on the neighbor channels not subject to an input voltage.
  - **AD Converter Values with inputs shorted:** Values on the internal AD converter corresponding to zero input voltage
  - **Input Offset Measurement:** Output voltage and statistical results over a large number of zero voltage measurements.
  - **Input Offset Current:** Typical value for information; Maximum channel input offset current, not considering the input resistance.
  - **Input resistance:** DAE input resistance at the connector, during internal auto-zeroing and during measurement.
  - **Low Battery Alarm Voltage:** Typical value for information. Below this voltage, a battery alarm signal is generated.
  - **Power consumption:** Typical value for information. Supply currents in various operating modes.

## SAR PROBE CALIBRATION CERTIFICATES

## ANNEX F

### Appendix

#### 1. DC Voltage Linearity

High Range	Input ( $\mu\text{V}$ )	Reading ( $\mu\text{V}$ )	Error (%)
Channel X + Input	200000	200000.5	0.00
Channel X + Input	20000	20006.64	0.03
Channel X - Input	20000	-19998.14	-0.01
Channel Y + Input	200000	199999.9	0.00
Channel Y + Input	20000	20002.71	0.01
Channel Y - Input	20000	-20006.38	0.03
Channel Z + Input	200000	199999.5	0.00
Channel Z + Input	20000	20002.83	0.01
Channel Z - Input	20000	-20002.66	0.01

Low Range	Input ( $\mu\text{V}$ )	Reading ( $\mu\text{V}$ )	Error (%)
Channel X + Input	2000	2000.1	0.00
Channel X + Input	200	199.93	-0.03
Channel X - Input	200	-200.33	0.17
Channel Y + Input	2000	2000.1	0.00
Channel Y + Input	200	199.52	-0.24
Channel Y - Input	200	-200.46	0.23
Channel Z + Input	2000	2000	0.00
Channel Z + Input	200	198.83	-0.58
Channel Z - Input	200	-201.40	0.70

#### 2. Common mode sensitivity

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	Common mode Input Voltage (mV)	High Range Average Reading ( $\mu\text{V}$ )	Low Range Average Reading ( $\mu\text{V}$ )
Channel X	200	7.13	6.35
	-200	-6.33	-6.40
Channel Y	200	-3.89	-4.27
	-200	2.79	3.07
Channel Z	200	0.58	0.54
	-200	-2.43	-3.14

#### 3. Channel separation

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	Input Voltage (mV)	Channel X ( $\mu\text{V}$ )	Channel Y ( $\mu\text{V}$ )	Channel Z ( $\mu\text{V}$ )
Channel X	200	-	3.54	-0.13
Channel Y	200	2.29	-	5.42
Channel Z	200	0.12	0.82	-



## SAR PROBE CALIBRATION CERTIFICATES

## ANNEX F

### 4. AD-Converter Values with inputs shorted

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	High Range (LSB)	Low Range (LSB)
Channel X	15820	16014
Channel Y	15474	15871
Channel Z	16121	16858

### 5. Input Offset Measurement

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Input 10M $\Omega$

	Average ( $\mu$ V)	min. Offset ( $\mu$ V)	max. Offset ( $\mu$ V)	Std. Deviation ( $\mu$ V)
Channel X	0.51	-1.09	1.58	0.46
Channel Y	-1.46	-3.36	0.77	0.66
Channel Z	-0.39	-1.58	0.94	0.41

### 6. Input Offset Current

Nominal Input circuitry offset current on all channels: <25fA

### 7. Input Resistance

	Zeroing (MOhm)	Measuring (MOhm)
Channel X	0.2001	199.8
Channel Y	0.2001	200.9
Channel Z	0.2001	196.9

### 8. Low Battery Alarm Voltage (verified during pre test)

Typical values	Alarm Level (VDC)
Supply (+ Vcc)	+7.9
Supply (- Vcc)	-7.6

### 9. Power Consumption (verified during pre test)

Typical values	Switched off (mA)	Stand by (mA)	Transmitting (mA)
Supply (+ Vcc)	+0.0	+6	+14
Supply (- Vcc)	-0.01	-8	-9



**REFERENCES**

**ANNEX G**



## REFERENCES

## ANNEX G

The methods and procedures used for the measurements contained in this report are details in the following reference standards:

Publications	Year	Title
Supplement C (Edition 01-01) to FCC OET Bulletin 65 (Edition 97-01)	2001	"Evaluating Compliance with FCC Guidelines for Human Exposure to radio Frequency Fields"
IEEE Standard 1528-200X	2000	"Product Performance Standards Relative to the safe Use of Electromagnetic Energy"
ANSI/IEEE C95.3	1992	"Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave"
ANSI/IEEE C95.1	1992	"Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3kHz to 300GHz"
ACA, Radio Communications (EMR Human Exposure)	2000 (No.2)	"Radiocommunication (Electromagnetic Radiation – Human Exposure)"
EN50360	2001	Product Standard to demonstrate the compliance of mobile phones with the basic restrictions related to human exposure to electromagnetic fields (300MHz – 3GHz)
EN50361	2001	Basic Standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phone (300MHz – 3GHz)
EN62209-1	2006	Procedure to determine the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (300MHz – 3GHz)