

Report No.: GSM10462185S03

Issue Date: 12-27, 2010

Page 1 of 73

Full SAR Test Report

Applicant Name: Creative Labs Inc

Applicant Address: 1901 McCarthy Blvd., Milpitas California 94035 United States

The following samples were submitted and identified on behalf of the client as:

Sample Description	ZEN Touch 2
SGS Ref	LG048
Model Number	DVP-FL0016
Final Hardware Version Tested	PD6390-512-00.00
Final Software Version Tested	V1.00
FCC ID	IBADVP-FL0016
Date Initial Sample Received	12-24,2010
Testing Start Date	12-25,2010
Testing End Date	12-25,2010

According to:

FCC 47CFR § 2.1093, IEEE Std C95.1-2005

IEEE1528-2003, OET Bulletin 65 Supplement C

Comments/ Conclusion:

The configuration tested complied to the certification requirements specified in this report.

Signed for on behalf of SGS

David Lee

Project Manager

Peter Xue

Technical Manager

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/terms_and_conditions.htm. and, for electronic format documents to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligation under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorised alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only

SHGSM

Table of Contents

Change History	3
1. Report Overview	4
2. Test Lab Declaration or Comments.....	4
3. Applicant Declaration or Comments.....	4
4. Full Test Report	4
5. Partial Test Report.....	4
6. Measurement Uncertainty	4
7. Testing Environment	6
8. Primary Test Laboratory	6
9. Details of Applicant	6
10. Details of Manufacturer.....	6
11. Other testing Locations	6
12. Referenced Documents.....	7
13. Primary Laboratory Accreditation Details	8
14. SGS Shanghai Wireless Telecommunications lab, Personnel	9
15. Test Equipment Information	10
15.1 SPEAG DASY4	10
15.2 The SAR Measurement System	11
15.3 Isotropic E-field Probe ES3DV3.....	13
15.4 SAM Twin Phantom	14
15.5 Device Holder for Transmitters	15
16. Detailed Test Results.....	16
16.1 Summary of Results	16
16.2 Maximum Results	18
16.3 Operation Configurations	18
16.4 Measurement procedure	21
16.5 Detailed Test Results	22
17. Identification of Samples	42
18. Photographs of EUT.....	43
Annex A Photographs of Test Setup	44
Annex B Tissue Simulant Liquid.....	48
Annex C SAR System Validation.....	49
Annex D Description of Test Position	52
Annex E Calibration certificate	55
Annex E.1 Dipole Calibration certification	71

Change History

Version	Change Contents	Author	Date
V1.0	First edition	David Lee	12-27, 2010

1. Report Overview

This report details the results of testing carried out on the samples listed in section 17, the results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this test report is used in any configuration other than that detailed in the test report, the manufacturer must ensure the new configuration complies with all relevant standards and certification requirements. Any mention of SGS Shanghai Wireless Telecommunications lab or testing done by SGS Shanghai Wireless Telecommunications lab made in connection with the distribution or use of the tested product must be approved in writing by SGS Shanghai Wireless Telecommunications lab.

2. Test Lab Declaration or Comments

None

3. Applicant Declaration or Comments

None

4. Full Test Report

A full test report contains, within the results section, all the applicable test cases from the certification requirements of the permanent reference documents of the listed certification bodies.

5. Partial Test Report

A partial test report contains within the results section a sub-set of all the applicable test cases from the certification requirements of the permanent reference documents of the listed certification bodies.

6. Measurement Uncertainty

Measurements and results are all in compliance with the standards listed in section 12 of this report. All measurements and results are recorded and maintained at the laboratory performing the tests and measurement uncertainties are taken into account when comparing measurements to pass/ fail criteria.

A	b1	c	d	e = f(d,k)	g	i = cxg/e	k
Uncertainty Component	Section in P1528	Tol (%)	Prob . Dist.	Div.	Ci (1g)	1g ui (%)	Vi (Veff)
Probe calibration	E.2.1	6.3	N	1	1	6.3	∞
Axial isotropy	E.2.2	0.5	R	$\sqrt{3}$	$(1-c_p)^{1/2}$	0.20	∞
hemispherical isotropy	E.2.2	2.6	R	$\sqrt{3}$	$\sqrt{c_p}$	1.06	∞
Boundary effect	E.2.3	0.8	R	$\sqrt{3}$	1	0.46	∞
Linearity	E.2.4	0.6	R	$\sqrt{3}$	1	0.35	∞
System detection limit	E.2.5	0.25	R	$\sqrt{3}$	1	0.15	∞
Readout electronics	E.2.6	0.3	N	1	1	0.3	∞
Response time	E.2.7	0	R	$\sqrt{3}$	1	0	∞
Integration time	E.2.8	2.6	R	$\sqrt{3}$	1	1.5	∞
RF ambient Condition –Noise	E.6.1	3	R	$\sqrt{3}$	1	1.73	∞
RF ambient Condition - reflections	E.6.1	3	R	$\sqrt{3}$	1	1.73	∞
Probe positioning- mechanical tolerance	E.6.2	1.5	R	$\sqrt{3}$	1	0.87	∞
Probe positioning- with respect to phantom	E.6.3	2.9	R	$\sqrt{3}$	1	1.67	∞
Max. SAR evaluation	E.5.2	1	R	$\sqrt{3}$	1	0.58	∞
Test sample positioning	E.4.2	4	N	1	1	3.7	9
Device holder uncertainty	E.4.1	3.6	N	1	1	3.6	∞
Output power variation –SAR drift measurement	6.62	5	R	$\sqrt{3}$	1	2.89	∞
Phantom uncertainty (shape and thickness tolerances)	E.3.1	4	R	$\sqrt{3}$	1	2.31	∞
Liquid conductivity - deviation from target values	E.3.2	5	R	$\sqrt{3}$	0.64	1.85	∞
Liquid conductivity - measurement uncertainty	E.3.2	4	N	1	0.64	2.56	5
Liquid permittivity - deviation from target values	E.3.3	5	R	$\sqrt{3}$	0.6	1.73	∞
Liquid permittivity - measurement uncertainty	E.3.3	4	N	1	0.6	2.40	5
Combined standard uncertainty				RSS		10.71	430
Expanded uncertainty (95% CONFIDENCE INTERVAL)				K=2		21.43	

7. Testing Environment

Normal Temperature	+20 to +24 °C
Relative Humidity	35 to 60 %

8. Primary Test Laboratory

Name:	Wireless Telecommunications Laboratory SGS-CSTC Standards Technical Services(Shanghai) Co., Ltd
Address:	9F, 3 rd Building, No.889, Yishan Rd, Xuhui District, Shanghai, China 200233
Telephone:	+86 (0) 21 6140 2666
Fax:	+86 (0) 21 5450 0149
Internet:	http://www.cn.sgs.com
Contact:	Mr. Peter Xue
Email:	peter.xue@sgs.com

9. Details of Applicant

Name:	Creative Labs Inc
Address:	1901 McCarthy Blvd., Milpitas California 94035 United States
Telephone:	408-205-6600
Fax:	408-428-6611
Contact:	Thinh Bui
Email:	Tbui@creativelabs.com

10. Details of Manufacturer

Name:	Creative Technology Ltd.
Address:	31, International Business Park, Creative Resource Singapore 609921
Telephone:	+65 6895 4490
Fax:	+65 6895 4483
Contact:	Tan Keng Wah
Email:	Kwtan@ctl.creative.com

11. Other testing Locations

Name:	Not Required
Address:	--
Telephone:	--
Contact:	--
Fax:	--
Email:	--

12. Referenced Documents

The Equipment under Test (EUT) has been tested at SGS's (own or subcontracted) laboratories according to FCC 47CFR § 2.1093, IEEE Std C95.1-2005, IEEE1528-2003, OET Bulletin 65 Supplement C, RSS-102

The following table summarizes the specific reference documents such as harmonized standards or test specifications which were used for testing as SGS's (own or subcontracted) laboratories.

Identity	Document Title	Version
FCC 47CFR § 2.1093	Radiofrequency radiation exposure evaluation: portable devices	2001
IEEE Std C95.1-2005	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.	2005
IEEE1528-2003	IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques	2003
OET Bulletin 65 Supplement C	Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions	2001
KDB 447498 D01	Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies	-
KDB 248227 D01	SAR Measurement Procedures for 802.11a/b/g Transmitters	-
KDB 616217 D03	SAR Evaluation Considerations for Laptop/Notebook/Netbook and Tablet Computers	

Human Exposure	Uncontrolled Environment General Population
Spatial Peak SAR	1.60 W/kg (averaged over a mass of 1g)

Table 12-1 RF Exposure Limits

Notes:

Uncontrolled environments are defined as locations where there is potential exposure of individuals who have no knowledge or control of their potential exposure.

13. Primary Laboratory Accreditation Details



SHGSM

14. SGS Shanghai Wireless Telecommunications lab, Personnel

SGS Wireless Shanghai Project Management Team and list of approved Testers for SGS Wireless Shanghai.

Surname	Forename	Initials
CAI	CAI	CAICAI
Xue	Peter	PETERXUE
Xu	Anyu	ANYA
Ni	Lemon	LEMONNI
Tao	Kevin	KEVINTAO
Wang	Lawrence	LAWRENCE
Zhang	Sean	SEANZH
Ruan	Roger	ROGER
Zhang	Zenger	ZENGER
Tang	Eva	EVATANG
Ho	James	JAMESHO
Tang	Kenny	KENNY
Hailiang	Cai	HAILIANG
Nie	Neo	Neo
Gong	Tina	Tina
Nie	Marina	Marina
Xu	Jesse	Jesse
Wang	Willam	Willam
Lee	David	David
Liu	Magi	Magi

Version 2010-09-20

15. Test Equipment Information

15.1 SPEAG DASY4

Test Platform	SPEAG DASY4 Professional			
Location	SGS SH Lab #8			
Manufacture	SPEAG			
Description	SAR Test System (Frequency range 300MHz-3GHz) 835, 900, 1800, 1900, 2000, 2450 frequency band HAC Extension			
Software Reference	DASY4: V4.7 Build 80 SEMCAD: V1.8 Build 186			
Hardware Reference				
Equipment	Model	Serial Number	Calibration Date	Due date of calibration
Robot	RX90L	F03/5V32A1/A01	n/a	n/a
Phantom	SAM 12	TP-1283	n/a	n/a
DAE	DAE3	569	2010-11-22	2011-11-21
E-Field Probe	ES3DV3	3088	2010-11-23	2011-11-22
Validation Kits	D2450V2	733	2010-11-25	2011-11-24
Agilent Network Analyzer	E5071B	MY42100549	2010-11-24	2011-11-23
RF Bi-Directional Coupler	ZABDC20-252H	n/a	2010-05-21	2011-05-20
Agilent Signal Generator	E4438C	14438CATO-19719	2010-11-01	2011-10-31
Mini-Circuits Preamplifier	ZHL-42	D041905	2010-11-01	2011-10-31
Agilent Power Meter	E4416A	GB41292095	2010-11-01	2011-10-31
Agilent Power Sensor	8481H	MY41091234	2010-11-01	2011-10-31
R&S Power Sensor	NRP-Z92	100025	2010-04-13	2011-04-12
R&S Universal Radio Communication Tester	CMU200	103633	2010-11-01	2011-10-31

15.2 The SAR Measurement System

A photograph of the SAR measurement System is given in Fig. 15-1.

This SAR Measurement System uses a Computer-controlled 3-D stepper motor system (Speag Dasy 4 professional system). A Model ES3DV3 3088 E-field probe is used to determine the internal electric fields. The SAR can be obtained from the equation $SAR = \sigma (|E|^2) / \rho$ where σ and ρ are the conductivity and mass density of the tissue-simulant.

The DASY4 system for performing compliance tests consists of the following items:

A standard high precision 6-axis robot (Stabile RX family) with controller, teach pendant and software. An arm extension is for accommodation the data acquisition electronics (DAE).

A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.

Data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.

The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.




Fig. 15-1 SAR System Configuration

- Ÿ The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- Ÿ A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- Ÿ A computer operating Windows 2000.

SHGSM

- ÿ DASY4 software.
- ÿ Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- ÿ The SAM twin phantom enabling testing left-hand, right-hand and BodyWorn usage.
- ÿ The device holder for handheld mobile phones.
- ÿ Tissue simulating liquid mixed according to the given recipes.
- ÿ Validation dipole kits allowing to validating the proper functioning of the system

15.3 Isotropic E-field Probe ES3DV3




Fig. 15-2 E-field Probe

Construction	Symmetrical design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	Basic Broad Band Calibration in air Conversion Factors (CF) for HSL 900 and HSL 1810 Additional CF for other liquids and frequencies upon request
Frequency	10 MHz to 4 GHz; Linearity: ± 0.2 dB (30 MHz to 4 GHz)
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.3 dB in tissue material (rotation normal to probe axis)
Dynamic Range	5 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB
Dimensions	Overall length: 330 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm
Application	General dosimetry up to 4 GHz Dosimetry in strong gradient fields Compliance tests of mobile phones

15.4 SAM Twin Phantom



Fig. 15-3 SAM Twin Phantom

The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region where shell thickness increases to 6mm). It has three measurement areas:

- Left hand
- Right hand
- Flat phantom

A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. Free space scans of devices on the cover are possible.

On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

Phantom specification:

Description	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528-2003, CENELEC 50361 and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.
Shell Thickness	2±0.2mm, Center ear point: 6±0.2mm
Filling Volume	Approx.25 liters
Dimensions	Length: 1000mm, Width: 500mm, Height: 850mm

15.5 Device Holder for Transmitters



Fig. 15-4 Device Holder for Transmitters

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source in 5mm distance, a positioning uncertainty of $\pm 0.5\text{mm}$ would produce a SAR uncertainty of $\pm 20\%$. An accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions, in which the devices must be measured, are defined by the standards.

The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation centers for both scales are the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.

The DASY device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon_r=3$ and loss tangent $\tan \delta=0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.

16. Detailed Test Results

16.1 Summary of Results

16.1.1 Measurement of RF conducted Power

Unit: dBm

Mode			WLAN
Band	Data rate	Channel	Peak power
802.11b	1Mbps	1	17.52
		6	16.72
		11	16.65
802.11g	6Mbps	1	21.08
		6	21.74
		11	21.70
802.11n	6.5Mbps	1	21.57
		6	21.48
		11	21.34
Mode			WLAN
Band	Data rate	Channel	Average power
802.11b	1Mbps	1	15.85
		6	15.49
		11	15.72
802.11g	6Mbps	1	14.79
		6	15.50
		11	14.22
802.11n	6.5Mbps	1	14.85
		6	15.11
		11	14.62

SHGSM

16.1.2 Measurement of SAR average value


Band	EUT Position	Mode	Test Configuration	Averaged SAR over 1g (W/kg)			SAR limit 1g (W/kg))	Verdict
				CH1	CH6	CH11		
				2412MHz	2437MHz	2462MHz		
WLAN	Body Worn	802.11b	Rear of EUT facing phantom	--	0.528	--	1.6	Passed
			Front of EUT facing phantom	--	0.535	--	1.6	Passed
			Top of EUT facing phantom	--	0.032	--	1.6	Passed
			Bottom of EUT facing phantom	0.594	0.629	0.881	1.6	Passed
			Right of EUT facing phantom	--	0.253	--	1.6	Passed
			Left of EUT facing phantom	--	0.086	--	1.6	Passed
		Worst case of 802.11b for 802.11a	Bottom of EUT facing phantom	--	--	0.866	1.6	Passed
		802.11b	Front of EUT facing phantom with headset	--	--	0.299	1.6	Passed

Band	EUT Position	Mode	Test Configuration	Averaged SAR over 1g (W/kg)			SAR limit 1g (W/kg))	Verdict
				CH1	CH6	CH11		
				2412MHz	2437MHz	2462MHz		
WLAN	Body Worn	802.11n	Rear of EUT facing phantom with headset	--	0.292	--	1.6	Passed
			Front of EUT facing phantom	--	0.263	--	1.6	Passed
			Top of EUT facing phantom	--	0.015	--	1.6	Passed
			Bottom of EUT facing phantom	0.284	0.368	0.380	1.6	Passed
			Right of EUT facing phantom	--	0.141	--	1.6	Passed
			Left of EUT facing phantom	--	0.044	--	1.6	Passed
			Rear of EUT facing phantom with headset	--	--	0.139		

(Note : the worst case of 802.11b and 802.11n are both at the bottom side position, but when we insert the earphone the bottom side of the EUT can not touch the phantom any longer, illuminating in the following pictures .



Without earphone



with earphone

As the pictures show if we check the earphone mode in the bottom side the distance between the EUT and the phantom will be 20mm longer, that would make the SAR value very low, so we pick another side (the front side for 802.11b and the rear side for 802.11g) to check the earphone.)

16.2 Maximum Results

The maximum measured SAR values for Head configuration and BodyWorn configuration are given in section 16.2.1.

16.2.1 BodyWorn Configuration

Frequency Band	EUT Position	Conducted Power (dBm)	SAR, Averaged over 1g (W/kg)	Power Drift (dB)	SAR limit (W/kg)	Verdict
802.11b	Bottom of EUT facing phantom/High	15.72	0.881	-0.037	1.6	Passed
802.11n	Bottom of EUT facing phantom/High	14.62	0.380	0.129	1.6	Passed

16.2.2 Maximum Drift

Maximum Drift during measurement	-0.301
----------------------------------	--------

16.2.3 Measurement Uncertainty

Extended Uncertainty (k=2) 95%	21.43%
--------------------------------	--------

16.3 Operation Configurations

The EUT is measured using chipset based test mode software to ensure the results are consistent and reliable.

The tests are performed in the 802.11b/g/n mode.

1. The 802.11b/n mode is tested at 1,6,11 channels.
2. The 802.11g mode is checked at worst case of 802.11b mode.

SHGSM

3. The EUT is at the lowest data rate during test.


4. Test reduction has been adopted according to conducted output power and produced SAR level:


Low and High channel SAR are optional if SAR value produced in the middle channel is 3dB lower than the applicable SAR limit;

5. The (max. cube) labeling indicates that during the grid scanning an additional peak was found which within 2dB of the highest peak


6. The Bluetooth power of the device is much lower than the reference 60/f(GHz),so the SAR evaluation is not required for Bluetooth.

7. Test positions of EUT (the distance between the EUT and the phantom is 0mm for all the six sides)






Position 5



Position 6



16.4 Measurement procedure

Step 1: Power reference measurement

The SAR measurement was taken at a selected spatial reference point to monitor power variations during testing. This fixed location point was measured and used as a reference value.

Step 2: Area scan

The SAR distribution at the exposed side of the head was measured at a distance of 4mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 15mm*15mm or 10mm*10mm. Based on the area scan data, the area of the maximum absorption was determined by spline interpolation.

Step 3: Zoom scan

Around this point, a volume of 30mm*30mm*30mm (fine resolution volume scan, zoom scan) was assessed by measuring 7*7*7 points. On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure:

The data at the surface was extrapolated, since the center of the dipoles is 2.0mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2mm. (This can be variable. Refer to the probe specification) the extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip. The maximum interpolated value was searched with a straight-forward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10g) were computed using the 3D-Spline interpolation algorithm. The volume was integrated with the trapezoidal algorithm. One thousand points (10*10*10) were interpolated to calculate the average. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

Step 4: Power reference measurement (drift)

The SAR value at the same location as in step 1 was again measured. (If the value changed by more than 5%, the evaluation should be done repeatedly)

16.5 Detailed Test Results

16.5.1 802.11b- BackSide-Middle

Date/Time: 2010-12-25 9:38:39

Test Laboratory: SGS-GSM

LG048 802.11b Back Side Middle

DUT: LG048; Type: WiFi; Serial: LG048AB01

Communication System: WiFi(2450); Frequency: 2437 MHz;Duty Cycle: 1:1

Medium: HSL2450-Body Medium parameters used: $f = 2437$ MHz; $\sigma = 1.95$ mho/m; $\epsilon_r = 52$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3088; ConvF(4.34, 4.34, 4.34); Calibrated: 2010-11-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn569; Calibrated: 2010-11-22
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1283
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mid/Area Scan (51x101x1): **Measurement grid: dx=15mm, dy=15mm**

Maximum value of SAR (interpolated) = 0.613 mW/g


Mid/Zoom Scan (7x7x7)/Cube 0: **Measurement grid: dx=5mm, dy=5mm, dz=5mm**

Reference Value = 7.31 V/m; Power Drift = -0.126 dB

Peak SAR (extrapolated) = 1.39 W/kg

SAR(1 g) = 0.528 mW/g; SAR(10 g) = 0.223 mW/g

Maximum value of SAR (measured) = 0.623 mW/g



0 dB = 0.623mW/g

SHGSM

16.5.2 802.11b-FrontSide-Middle

Date/Time: 2010-12-25 10:04:47

Test Laboratory: SGS-GSM

LG048 802.11b Front Side Middle

DUT: LG048; Type: WiFi; Serial: LG048AB01

Communication System: WiFi(2450); Frequency: 2437 MHz;Duty Cycle: 1:1
Medium: HSL2450-Body Medium parameters used: $f = 2437 \text{ MHz}$; $\sigma = 1.95 \text{ mho/m}$; $\epsilon_r = 52$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section


DASY4 Configuration:

- Probe: ES3DV3 - SN3088; ConvF(4.34, 4.34, 4.34); Calibrated: 2010-11-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn569; Calibrated: 2010-11-22
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1283
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mid/Area Scan (51x101x1): **Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$**
Maximum value of SAR (interpolated) = 0.560 mW/g

Mid/Zoom Scan (7x7x7)/Cube 0: **Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$**
Reference Value = 2.12 V/m; Power Drift = 0.131 dB
Peak SAR (extrapolated) = 1.63 W/kg

SAR(1 g) = 0.535 mW/g; SAR(10 g) = 0.200 mW/g

Maximum value of SAR (measured) = 0.642 mW/g


0 dB = 0.642mW/g

SHGSM

16.5.3 802.11b-TopSide-Middle

Date/Time: 2010-12-25 10:32:04

Test Laboratory: SGS-GSM

LG048 802.11b Top Side Middle

DUT: LG048; Type: WiFi; Serial: LG048AB01

Communication System: WiFi(2450); Frequency: 2437 MHz;Duty Cycle: 1:1
Medium: HSL2450-Body Medium parameters used: $f = 2437 \text{ MHz}$; $\sigma = 1.95 \text{ mho/m}$; $\epsilon_r = 52$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section


DASY4 Configuration:

- Probe: ES3DV3 - SN3088; ConvF(4.2, 4.2, 4.2); Calibrated: 2009-11-19
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn569; Calibrated: 2010-11-22
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1283
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mid/Area Scan (61x71x1): **Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$**
Maximum value of SAR (interpolated) = 0.056 mW/g

Mid/Zoom Scan (7x7x7)/Cube 0: **Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$**
Reference Value = 4.69 V/m; Power Drift = -0.006 dB
Peak SAR (extrapolated) = 0.080 W/kg

SAR(1 g) = 0.032 mW/g; SAR(10 g) = 0.015 mW/g

Maximum value of SAR (measured) = 0.037 mW/g


0 dB = 0.037mW/g

SHGSM

16.5.4 802.11b-BottomSide-Middle

Date/Time: 2010-12-25 10:58:07

Test Laboratory: SGS-GSM

LG048 802.11b Bottom Side Middle

DUT: LG048; Type: WiFi; Serial: LG048AB01


Communication System: WiFi(2450); Frequency: 2437 MHz;Duty Cycle: 1:1
Medium: HSL2450-Body Medium parameters used: $f = 2437 \text{ MHz}$; $\sigma = 1.95 \text{ mho/m}$; $\epsilon_r = 52$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3088; ConvF(4.2, 4.2, 4.2); Calibrated: 2009-11-19
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn569; Calibrated: 2010-11-22
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1283
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mid/Area Scan (61x71x1): **Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$**
Maximum value of SAR (interpolated) = 0.742 mW/g

Mid/Zoom Scan (7x7x7)/Cube 0: **Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$**
Reference Value = 19.2 V/m ; Power Drift = 0.123 dB
Peak SAR (extrapolated) = 1.52 W/kg

SAR(1 g) = 0.629 mW/g ; SAR(10 g) = 0.273 mW/g
Maximum value of SAR (measured) = 0.726 mW/g

0 dB = 0.726mW/g
SHGSM

16.5.5 802.11b-RightSide-Middle

Date/Time: 2010-12-25 11:23:23

Test Laboratory: SGS-GSM

LG048 802.11b Right Side Middle

DUT: LG048; Type: WiFi; Serial: LG048AB01

Communication System: WiFi(2450); Frequency: 2437 MHz;Duty Cycle: 1:1
Medium: HSL2450-Body Medium parameters used: $f = 2437 \text{ MHz}$; $\sigma = 1.95 \text{ mho/m}$; $\epsilon_r = 52$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section


DASY4 Configuration:

- Probe: ES3DV3 - SN3088; ConvF(4.34, 4.34, 4.34); Calibrated: 2010-11-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn569; Calibrated: 2010-11-22
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1283
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mid/Area Scan (51x101x1): **Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$**
Maximum value of SAR (interpolated) = 0.233 mW/g

Mid/Zoom Scan (7x7x7)/Cube 0: **Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$**
Reference Value = 7.60 V/m; Power Drift = 0.052 dB
Peak SAR (extrapolated) = 0.632 W/kg

SAR(1 g) = 0.253 mW/g; SAR(10 g) = 0.099 mW/g

Maximum value of SAR (measured) = 0.298 mW/g


0 dB = 0.298mW/g

SHGSM

16.5.6 802.11b-LeftSide-Middle

Date/Time: 2010-12-25 11:51:45

Test Laboratory: SGS-GSM

LG048 802.11b Left Side Middle

DUT: LG048; Type: WiFi; Serial: LG048AB01

Communication System: WiFi(2450); Frequency: 2437 MHz;Duty Cycle: 1:1
Medium: HSL2450-Body Medium parameters used: $f = 2437 \text{ MHz}$; $\sigma = 1.95 \text{ mho/m}$; $\epsilon_r = 52$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section


DASY4 Configuration:

- Probe: ES3DV3 - SN3088; ConvF(4.34, 4.34, 4.34); Calibrated: 2010-11-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn569; Calibrated: 2010-11-22
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1283
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mid/Area Scan (51x101x1): **Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$**
Maximum value of SAR (interpolated) = 0.094 mW/g

Mid/Zoom Scan (7x7x7)/Cube 0: **Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$**
Reference Value = 4.86 V/m; Power Drift = -0.269 dB
Peak SAR (extrapolated) = 0.174 W/kg

SAR(1 g) = 0.086 mW/g; SAR(10 g) = 0.041 mW/g

Maximum value of SAR (measured) = 0.095 mW/g


0 dB = 0.095mW/g

SHGSM

16.5.7 802.11b-BottomSide-High

Date/Time: 2010-12-25 12:16:28

Test Laboratory: SGS-GSM

LG048 802.11b Bottom Side High

DUT: LG048; Type: WiFi; Serial: LG048AB01

Communication System: WiFi(2450); Frequency: 2462 MHz;Duty Cycle: 1:1
Medium: HSL2450-Body Medium parameters used: $f = 2462 \text{ MHz}$; $\sigma = 2.05 \text{ mho/m}$; $\epsilon_r = 51.9$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section


DASY4 Configuration:

- Probe: ES3DV3 - SN3088; ConvF(4.2, 4.2, 4.2); Calibrated: 2009-11-19
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn569; Calibrated: 2010-11-22
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1283
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186


High/Area Scan (61x71x1): **Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$**
Maximum value of SAR (interpolated) = 1.15 mW/g

High/Zoom Scan (7x7x7)/Cube 0: **Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$**
Reference Value = 21.7 V/m; Power Drift = -0.037 dB
Peak SAR (extrapolated) = 2.20 W/kg

SAR(1 g) = 0.881 mW/g; SAR(10 g) = 0.375 mW/g

Maximum value of SAR (measured) = 1.01 mW/g


SHGSM



16.5.8 802.11b-BottomSide-Low

Date/Time: 2010-12-25 12:42:55

Test Laboratory: SGS-GSM

LG048 802.11b Bottom Side Low

DUT: LG048; Type: WiFi; Serial: LG048AB01

Communication System: WiFi(2450); Frequency: 2412 MHz; Duty Cycle: 1:1

Medium: HSL2450-Body Medium parameters used: $f = 2412 \text{ MHz}$; $\sigma = 1.93 \text{ mho/m}$; $\epsilon_r = 52.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3088; ConvF(4.2, 4.2, 4.2); Calibrated: 2009-11-19
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn569; Calibrated: 2010-11-22
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1283
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Low/Area Scan (61x71x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.719 mW/g


Low/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.6 V/m; Power Drift = -0.258 dB

Peak SAR (extrapolated) = 1.39 W/kg

SAR(1 g) = 0.594 mW/g; SAR(10 g) = 0.263 mW/g

Maximum value of SAR (measured) = 0.687 mW/g



0 dB = 0.687mW/g

SHGSM

16.5.9 802.11g-BottomSide-High

Date/Time: 2010-12-25 13:11:49

Test Laboratory: SGS-GSM

LG048 802.11g Bottom Side High

DUT: LG048; Type: WiFi; Serial: LG048AB01

Communication System: WiFi(2450); Frequency: 2462 MHz;Duty Cycle: 1:1

Medium: HSL2450-Body Medium parameters used: $f = 2462 \text{ MHz}$; $\sigma = 2.04 \text{ mho/m}$; $\epsilon_r = 51.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3088; ConvF(4.34, 4.34, 4.34); Calibrated: 2010-11-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn569; Calibrated: 2010-11-22
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1283
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

High/Area Scan (61x71x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.968 mW/g


High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.6 V/m; Power Drift = 0.038 dB

Peak SAR (extrapolated) = 1.98 W/kg

SAR(1 g) = 0.866 mW/g; SAR(10 g) = 0.374 mW/g

Maximum value of SAR (measured) = 1.01 mW/g



0 dB = 1.01mW/g

SHGSM

16.5.10 802.11b- FrontSide-Middle-with headset

Date/Time: 2010-12-25 13:37:45

Test Laboratory: SGS-GSM

LG048 802.11 b Front Side With Headset Middle

DUT: LG048; Type: WiFi; Serial: LG048AB01


Communication System: WiFi(2450); Frequency: 2437 MHz;Duty Cycle: 1:1
Medium: HSL2450-Body Medium parameters used: $f = 2437 \text{ MHz}$; $\sigma = 1.95 \text{ mho/m}$; $\epsilon_r = 52$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3088; ConvF(4.34, 4.34, 4.34); Calibrated: 2010-11-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn569; Calibrated: 2010-11-22
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1283
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mid/Area Scan (51x101x1): **Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$**
Maximum value of SAR (interpolated) = 0.303 mW/g

Mid/Zoom Scan (7x7x7)/Cube 0: **Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$**
Reference Value = 1.70 V/m ; Power Drift = 0.145 dB
Peak SAR (extrapolated) = 0.923 W/kg

SAR(1 g) = 0.299 mW/g ; SAR(10 g) = 0.112 mW/g
Maximum value of SAR (measured) = 0.360 mW/g

0 dB = 0.360mW/g

SHGSM

16.5.11 802.11n- BackSide-Middle

Date/Time: 2010-12-25 14:03:42

Test Laboratory: SGS-GSM

LG048 802.11n Back Side Middle

DUT: LG048; Type: WiFi; Serial: LG048AB01


Communication System: WiFi(2450); Frequency: 2437 MHz;Duty Cycle: 1:1
Medium: HSL2450-Body Medium parameters used: $f = 2437 \text{ MHz}$; $\sigma = 1.95 \text{ mho/m}$; $\epsilon_r = 52$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3088; ConvF(4.34, 4.34, 4.34); Calibrated: 2010-11-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn569; Calibrated: 2010-11-22
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1283
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mid/Area Scan (51x101x1): **Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$**
Maximum value of SAR (interpolated) = 0.511 mW/g

Mid/Zoom Scan (7x7x7)/Cube 0: **Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$**
Reference Value = 5.51 V/m ; Power Drift = -0.136 dB
Peak SAR (extrapolated) = 0.797 W/kg

SAR(1 g) = 0.292 mW/g ; SAR(10 g) = 0.120 mW/g
Maximum value of SAR (measured) = 0.345 mW/g

0 dB = 0.345mW/g
SHGSM

16.5.12 802.11n-FrontSide-Middle

Date/Time: 2010-12-25 14:28:35

Test Laboratory: SGS-GSM

LG048 802.11n Front Side Middle

DUT: LG048; Type: WiFi; Serial: LG048AB01

Communication System: WiFi(2450); Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: HSL2450-Body Medium parameters used: $f = 2437 \text{ MHz}$; $\sigma = 1.95 \text{ mho/m}$; $\epsilon_r = 52$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3088; ConvF(4.34, 4.34, 4.34); Calibrated: 2010-11-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn569; Calibrated: 2010-11-22
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1283
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mid/Area Scan (51x101x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.328 mW/g


Mid/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 1.64 V/m; Power Drift = 0.173 dB

Peak SAR (extrapolated) = 0.778 W/kg

SAR(1 g) = 0.263 mW/g; SAR(10 g) = 0.103 mW/g

Maximum value of SAR (measured) = 0.296 mW/g



0 dB = 0.296mW/g

SHGSM

16.5.13 802.11n-TopSide-Middle

Date/Time: 2010-12-25 14:56:34

Test Laboratory: SGS-GSM

LG048 802.11n Top Side Middle

DUT: LG048; Type: WiFi; Serial: LG048AB01

Communication System: WiFi(2450); Frequency: 2437 MHz;Duty Cycle: 1:1
Medium: HSL2450-Body Medium parameters used: $f = 2437 \text{ MHz}$; $\sigma = 1.95 \text{ mho/m}$; $\epsilon_r = 52$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section


DASY4 Configuration:

- Probe: ES3DV3 - SN3088; ConvF(4.34, 4.34, 4.34); Calibrated: 2010-11-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn569; Calibrated: 2010-11-22
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1283
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mid/Area Scan (61x71x1): **Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$**
Maximum value of SAR (interpolated) = 0.023 mW/g

Mid/Zoom Scan (7x7x7)/Cube 0: **Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$**
Reference Value = 3.15 V/m; Power Drift = 0.085 dB
Peak SAR (extrapolated) = 0.030 W/kg

SAR(1 g) = 0.015 mW/g; SAR(10 g) = 0.0065 mW/g

Maximum value of SAR (measured) = 0.019 mW/g


0 dB = 0.019mW/g

SHGSM

16.5.14 802.11n-BottomSide-Middle

Date/Time: 2010-12-25 15:24:44

Test Laboratory: SGS-GSM

LG048 802.11n Bottom Side Middle

DUT: LG048; Type: WiFi; Serial: LG048AB01


Communication System: WiFi(2450); Frequency: 2437 MHz;Duty Cycle: 1:1
Medium: HSL2450-Body Medium parameters used: $f = 2437 \text{ MHz}$; $\sigma = 1.95 \text{ mho/m}$; $\epsilon_r = 52$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3088; ConvF(4.34, 4.34, 4.34); Calibrated: 2010-11-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn569; Calibrated: 2010-11-22
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1283
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mid/Area Scan (61x71x1): **Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$**
Maximum value of SAR (interpolated) = 0.451 mW/g

Mid/Zoom Scan (7x7x7)/Cube 0: **Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$**
Reference Value = 15.6 V/m ; Power Drift = -0.278 dB
Peak SAR (extrapolated) = 0.860 W/kg

SAR(1 g) = 0.368 mW/g ; SAR(10 g) = 0.159 mW/g
Maximum value of SAR (measured) = 0.425 mW/g

0 dB = 0.425mW/g
SHGSM

16.5.15 802.11n-RightSide-Middle

Date/Time: 2010-12-25 15:48:43

Test Laboratory: SGS-GSM

LG048 802.11n Right Side Middle

DUT: LG048; Type: WiFi; Serial: LG048AB01

Communication System: WiFi(2450); Frequency: 2437 MHz;Duty Cycle: 1:1
Medium: HSL2450-Body Medium parameters used: $f = 2437 \text{ MHz}$; $\sigma = 1.95 \text{ mho/m}$; $\epsilon_r = 52$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section


DASY4 Configuration:

- Probe: ES3DV3 - SN3088; ConvF(4.34, 4.34, 4.34); Calibrated: 2010-11-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn569; Calibrated: 2010-11-22
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1283
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mid/Area Scan (51x101x1): **Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$**
Maximum value of SAR (interpolated) = 0.156 mW/g

Mid/Zoom Scan (7x7x7)/Cube 0: **Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$**
Reference Value = 5.14 V/m; Power Drift = 0.042 dB
Peak SAR (extrapolated) = 0.362 W/kg

SAR(1 g) = 0.141 mW/g; SAR(10 g) = 0.055 mW/g

Maximum value of SAR (measured) = 0.160 mW/g


0 dB = 0.160mW/g

SHGSM

16.5.16 802.11n-LeftSide-Middle

Date/Time: 2010-12-25 16:14:23

Test Laboratory: SGS-GSM

LG048 802.11n Left Side Middle

DUT: LG048; Type: WiFi; Serial: LG048AB01

Communication System: WiFi(2450); Frequency: 2437 MHz;Duty Cycle: 1:1
Medium: HSL2450-Body Medium parameters used: $f = 2437 \text{ MHz}$; $\sigma = 1.95 \text{ mho/m}$; $\epsilon_r = 52$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section


DASY4 Configuration:

- Probe: ES3DV3 - SN3088; ConvF(4.34, 4.34, 4.34); Calibrated: 2010-11-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn569; Calibrated: 2010-11-22
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1283
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mid/Area Scan (51x101x1): **Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$**
Maximum value of SAR (interpolated) = 0.049 mW/g

Mid/Zoom Scan (7x7x7)/Cube 0: **Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$**
Reference Value = 3.31 V/m; Power Drift = -0.301 dB
Peak SAR (extrapolated) = 0.094 W/kg

SAR(1 g) = 0.044 mW/g; SAR(10 g) = 0.020 mW/g

Maximum value of SAR (measured) = 0.049 mW/g


0 dB = 0.049mW/g

SHGSM

16.5.17 802.11n-BottomSide-High

Date/Time: 2010-12-25 16:41:11

Test Laboratory: SGS-GSM

LG048 802.11n Bottom Side High

DUT: LG048; Type: WiFi; Serial: LG048AB01

Communication System: WiFi(2450); Frequency: 2462 MHz;Duty Cycle: 1:1

Medium: HSL2450-Body Medium parameters used: $f = 2462 \text{ MHz}$; $\sigma = 2.04 \text{ mho/m}$; $\epsilon_r = 51.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3088; ConvF(4.34, 4.34, 4.34); Calibrated: 2010-11-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn569; Calibrated: 2010-11-22
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1283
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

High/Area Scan (61x71x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.455 mW/g


High/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.2 V/m; Power Drift = 0.129 dB

Peak SAR (extrapolated) = 0.868 W/kg

SAR(1 g) = 0.380 mW/g; SAR(10 g) = 0.165 mW/g

Maximum value of SAR (measured) = 0.442 mW/g



0 dB = 0.442mW/g

SHGSM

16.5.18 802.11n-BottomSide-Low

Date/Time: 2010-12-25 17:06:08

Test Laboratory: SGS-GSM

LG048 802.11n Bottom Side Low

DUT: LG048; Type: WiFi; Serial: LG048AB01

Communication System: WiFi(2450); Frequency: 2412 MHz;Duty Cycle: 1:1
Medium: HSL2450-Body Medium parameters used: $f = 2412 \text{ MHz}$; $\sigma = 1.93 \text{ mho/m}$; $\epsilon_r = 52.5$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section


DASY4 Configuration:

- Probe: ES3DV3 - SN3088; ConvF(4.34, 4.34, 4.34); Calibrated: 2010-11-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn569; Calibrated: 2010-11-22
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1283
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Low/Area Scan (61x71x1): **Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$**
Maximum value of SAR (interpolated) = 0.343 mW/g

Low/Zoom Scan (7x7x7)/Cube 0: **Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$**
Reference Value = 13.8 V/m; Power Drift = -0.108 dB
Peak SAR (extrapolated) = 0.655 W/kg

SAR(1 g) = 0.284 mW/g; SAR(10 g) = 0.124 mW/g

Maximum value of SAR (measured) = 0.326 mW/g

SHGSM

16.5.19 802.11n- BackSide-Middle-with headset

Date/Time: 2010-12-25 17:33:33

Test Laboratory: SGS-GSM

LG048 802.11 n Back Side With Headset Middle

DUT: LG048; Type: WiFi; Serial: LG048AB01

Communication System: WiFi(2450); Frequency: 2437 MHz;Duty Cycle: 1:1
Medium: HSL2450-Body Medium parameters used: $f = 2437 \text{ MHz}$; $\sigma = 1.95 \text{ mho/m}$; $\epsilon_r = 52$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section


DASY4 Configuration:

- Probe: ES3DV3 - SN3088; ConvF(4.34, 4.34, 4.34); Calibrated: 2010-11-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn569; Calibrated: 2010-11-22
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1283
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mid/Area Scan (51x101x1): **Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$**
Maximum value of SAR (interpolated) = 0.221 mW/g

Mid/Zoom Scan (7x7x7)/Cube 0: **Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$**
Reference Value = 2.26 V/m; Power Drift = 0.072 dB
Peak SAR (extrapolated) = 0.299 W/kg

SAR(1 g) = 0.139 mW/g; SAR(10 g) = 0.076 mW/g

Maximum value of SAR (measured) = 0.158 mW/g


0 dB = 0.158mW/g

SHGSM

17. Identification of Samples

Product Name	ZEN Touch 2	
Marketing Name	DVP-FL0016	
Final Hardware Version	PD6390-512-00.00	
Final Software Version	V1.00	
Product Definition	Production Unit	
Normal Voltage	3.70V	
High Voltage	4.26V	
Low Voltage	3.15V	
Antenna Type	Inner antenna	
Device Type	Portable	
Limit Type	General Population/Uncontrolled	
WLAN Frequency Bands	802.11b	Tx/Rx: 2.412~2.472GHz
	802.11g	Tx/Rx: 2.412~2.472GHz
	802.11n	Tx/Rx: 2.412~2.472GHz
Reference Number	AB01	
IMEI	--	
Date of receipt	12-24,2010	
Date of Testing Start	12-25,2010	
Date of Testing End	12-25,2010	

18. Photographs of EUT




Fig.18-1 Front View




Fig.18-2 Back View



Fig.18-3 headset View

Annex A Photographs of Test Setup




Fig.A-1 Photograph of the SAR measurement System




Fig.A-2 Photograph of the Tissue Simulant

Liquid depth 15cm for Body Worn

SHGSM



Fig.A-3a Photograph of Back side of the EUT status



Fig.A-3b Photograph of Front side of the EUT status



Fig.A-3c Photograph of Left side of the EUT status




Fig.A-3d Photograph of Right side of the EUT status



Fig.A-3e Photograph of Top side of the EUT status



Fig.A-3f Photograph of Bottom side of the EUT status



Fig.A-3g Photograph of Back side of the EUT status with headset



Fig.A-3h Photograph of Front side of the EUT status with headset

Annex B Tissue Simulant Liquid

Annex B.1 Recipes for Tissue Simulant Liquid

The following tables give the recipes for tissue simulating liquids to be used in different frequency bands.

Frequency (MHz)	835		900		1800-2000		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body
Ingredient (% by weight)								
Water	40.30	50.75	40.30	50.75	55.24	70.17	62.7	73.26
Salt (NaCl)	1.38	0.94	1.38	0.94	0.31	0.39	0.5	0.04
Sucrose	57.90	48.21	57.90	48.21	0	0	0	0
HEC	0.24	0	0.24	0	0	0	0	0
Bactericide	0.18	0.10	0.10	0.10	0	0	0	0
DGBE	0	0	0	0	44.45	29.44	36.8	26.7
Measurement dielectric parameters								
Dielectric Constant	41.9	55.0	41.1	54.5	39.2	53.2	39.8	52.5
Conductivity (S/m)	0.93	0.97	1.04	1.06	1.45	1.59	1.88	1.78
Target values								
Dielectric Constant	41.5	55.2	41.5	55.0	40.0	53.3	39.2	52.7
Conductivity (S/m)	0.90	0.97	0.97	1.05	1.40	1.52	1.80	1.95
Salt: 99 ⁺ % Pure Sodium Chloride					Sucrose: 98 ⁺ % Pure Sucrose			
Water: De-ionized, 16 MΩ ⁺ resistivity					HEC: Hydroxyethyl Cellulose			
DGBE: 99 ⁺ % Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]								

Table B-1 Recipe of Tissue Simulat Liquid

Annex B.2 Measurement for Tissue Simulant Liquid

The dielectric properties for this Tissue Simulant Liquids were measured by using the Agilent Model 85070D Dielectric Probe (rates frequency band 200 MHz to 20 GHz) in conjunction with Agilent E5071B Network Analyzer (300 KHz-8500 MHz). The Conductivity (σ) and Permittivity (ρ) are listed in Table 1. For the SAR measurement given in this report. The temperature variation of the Tissue Simulant Liquids was 22±2°C.

Frequency (MHz)	Tissue Type	Limit/Measured	Permittivity (ρ)	Conductivity (σ)	Temp (°C)
2450	Body	Recommended Limit	52.7±5% (50.07~55.34)	1.95±5% (1.85~2.05)	22±2
		Measured, 12-25,2010	51.9	1.99	21.5

Table B-2 Measurement result of Tissue electric parameters

Annex C SAR System Validation

The microwave circuit arrangement for system verification is sketched in Fig. C-1. The daily system accuracy verification occurs within the flat section of the SAM phantom. A SAR measurement was performed to see if the measured SAR was within $\pm 10\%$ from the target SAR values. These tests were done at 835&1900MHz. The tests were conducted on the same days as the measurement of the EUT. The obtained results from the system accuracy verification are displayed in the table C-1 (A power level of 250mw was input to the dipole antenna). During the tests, the ambient temperature of the laboratory was in the range 22°C, the relative humidity was in the range 60% and the liquid depth above the ear reference points was above 15 cm in all the cases. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values.




Fig. C-1 the microwave circuit arrangement used for SAR system verification

- A. Agilent E4438C Signal Generator
- B. Mini-Circuit ZHL-42 Preamplifier
- C. Mini-Circuit VLF-2500+ Low Pass Filter
- D. Mini-Circuits ZABDC20-252H-N+ Bi-DIR Coupling
- PM1. Power Sensor NRP-Z92
- PM2. Agilent Model E4416A Power Meter
- PM3. Power Sensor NRP-Z92

Validation Kit	Frequency (MHz)	Tissue Type	Limit/Measurement		
			Condition	Recommended/Measured	1g
D2450V2	2450	Body	Nomalized to 1mW(for nominal Head TSL parameters)	Recommended Limit	50.7±10% (45.63-55.77)
			Nomalized to 1W(for nominal Head TSL parameters)	-	52.8
			250mW input power	Measured, 12-25, 2010	13.2

Table C-1 SAR System Validation Result

System Validation for 2450MHz-Body

Date/Time: 2010-12-25 8:52:37

Test Laboratory: SGS-GSM

System Performance Check at 2450MHz

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:733

Communication System: CW; Frequency: 2450 MHz;Duty Cycle: 1:1

Medium: HSL2450-Body Medium parameters used: $f = 2450 \text{ MHz}$; $\sigma = 1.99 \text{ mho/m}$; $\epsilon_r = 51.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3088; ConvF(4.34, 4.34, 4.34); Calibrated: 2010-11-23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn569; Calibrated: 2010-11-22
- Phantom: SAM 12; Type: SAM V4.0; Serial: TP-1283
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

 $d=10\text{mm}$, $P_{in}=250\text{mW}$ /Area Scan (61x101x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 16.4 mW/g


 $d=10\text{mm}$, $P_{in}=250\text{mW}$ /Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 51.4 V/m; Power Drift = -0.003 dB

Peak SAR (extrapolated) = 28.1 W/kg

 $\text{SAR}(1 \text{ g}) = 13.2 \text{ mW/g}$; $\text{SAR}(10 \text{ g}) = 6 \text{ mW/g}$

Maximum value of SAR (measured) = 15.0 mW/g



0 dB = 15.0mW/g

SHGSM

Annex D Description of Test Position

Annex D.1 SAM Phantom Shape




Figure D-1 front, back, and side views of SAM (model for the phantom shell). Full-head model is for illustration purposes only-procedures in this recommended practice are intended primarily for the phantom setup of Figure D-2.
Note: The center strip including the nose region has a different thickness tolerance.




Figure D-2 Sagittally bisected phantom with extended perimeter (shown placed on its side as used for SAR measurements)




Figure D-3 Close-up side view of phantom showing the ear region, N-F and B-M lines, and seven cross-sectional plane locations




Figure D-4 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

Annex D.2 EUT constructions




Figure D-5a Handset vertical and horizontal reference lines-“fixed case”




Figure D-5b Handset vertical and horizontal reference lines-“clam-shell case”

Annex D.3 Definition of the “cheek” position

- Position the device with the vertical centre line of the body of the device and the horizontal line crossing the centre of the ear piece in a plane parallel to the sagittal plane of the phantom ("initial position" see Figure 1-7). While maintaining the device in this plane, align the vertical centre line with the reference plane containing the three ear and mouth reference points (M, RE and LE) and align the centre of the ear piece with the line RE-LE;
- Translate the mobile phone box towards the phantom with the ear piece aligned with the line LE-RE until the phone touches the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the box until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost.

Annex D.4 Definition of the “tilted” position

- Position the device in the “cheek” position described above;
- While maintaining the device in the reference plane described above and pivoting against the ear, move it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost.




Figure D-6 Definition of the reference lines and points, on the phone and on the phantom and initial position




Figure D-7 "Cheek" and "tilt" positions of the mobile phone on the left side

Annex E Calibration certificate

Probe Calibration certificate

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8904 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
S Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Client: SGS-CH (Auden)

Certificate No: ES3-3088_Nov10

CALIBRATION CERTIFICATE

Object: ES3DV3 - SN.3088

Calibration procedure(s): QA CAL-01.v6, QA CAL-23.v3 and QA CAL-25.v2
Calibration procedure for dosimetric E-field probes

Calibration date: November 23, 2010

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&E critical for calibration)

Primary Standards	ID #	Cal. Date (Certificate No.)	Scheduled Calibration
Power meter E4119B	GB41293874	1-Apr-10 (No. 217-01136)	Apr-11
Power sensor E4412A	MY41495277	1-Apr-10 (No. 217-01136)	Apr-11
Power sensor E4412A	MY41496087	1-Apr-10 (No. 217-01136)	Apr-11
Reference 3 dB Attenuator	SN: S5256 (3c)	30-Mar-10 (No. 217-01159)	Mar-11
Reference 20 dB Attenuator	SN: S5266 (20b)	30-Mar-10 (No. 217-01161)	Mar-11
Reference 30 dB Attenuator	SN: S5129 (30b)	30-Mar-10 (No. 217-01160)	Mar-11
Reference Probe ES3DV2	SN: 3013	30-Dec-09 (No. ES3-3013_Dec09)	Dec-10
DAE4	SN: 969	20-Apr-10 (No. DAE4-969_Apr10)	Apr-11
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3542U01780	4-Aug-09 (in house check Oct-09)	In house check: Oct-11
Network Analyzer HP 8753E	US37390585	15-Oct-01 (in house check Oct-10)	In house check: Oct-11
Calibrated by:	Name: Jeton Kastrati	Function: Laboratory Technician	Signature:
Approved by:	Name: Katja Pekovic	Function: Technical Manager	Signature:

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Issued: November 23, 2010

Certificate No: ES3-3088_Nov10

Page 1 of 11

SHGSM

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zughausstrasse 43, 8804 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization β	β rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\beta = 0$ is normal to probe axis

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}: Assessed for E-field polarization $\beta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not effect the E²-field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z} = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; VR_{x,y,z}: A, B, C are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy): in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

Certificate No. ES3-3088_Nov10

Page 2 of 11

SHGSM

ES3DV3 SN:3088

November 23, 2010

Probe ES3DV3

SN:3088

Manufactured:	July 20, 2005
Last calibrated:	November 19, 2009
Recalibrated:	November 23, 2010

Calibrated for DASY/EASY Systems

(Note: non-compatible with DASY2 system)

Certificate No: ES3-3088_Nov10

Page 3 of 11

SHGSM

ES3DV3 SN:3088

November 23, 2010

DASY/EASY - Parameters of Probe: ES3DV3 SN:3088

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm $(\mu V)/(V/m)^2$ ^A	1.32	1.27	1.26	± 10.1%
DCP (mV) ^B	100.0	99.9	100.2	

Modulation Calibration Parameters

UID	Communication System Name	PAR		A dB	B dBuV	C	VR mV	Unc ^E (k=2)
10000	CW	0.00	X	0.00	0.00	1.00	156.3	± 3.4 %
			Y	0.00	0.00	1.00	152.0	
			Z	0.00	0.00	1.00	147.1	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X, Y, Z do not affect the E-field uncertainty inside TSL (see Pages 5 and 6).

^B Numerical investigation parameter, uncertainty not required.

^E Uncertainty is determined using the maximum deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

ES3DV3 SN:3088

November 23, 2010

DASY/EASY - Parameters of Probe: ES3DV3 SN:3088**Calibration Parameter Determined in Head Tissue Simulating Media**

f [MHz]	Validity [MHz] ¹⁾	Permittivity	Conductivity	ConvF X	ConvF Y	ConvF Z	Alpha	Depth Unc (k=2)
835	± 50 / ± 100	41.5 ± 5%	0.90 ± 5%	6.07	6.07	6.07	0.99	1.03 ± 11.0%
900	± 50 / ± 100	41.5 ± 5%	0.97 ± 5%	5.97	5.97	5.97	0.99	1.02 ± 11.0%
1610	± 50 / ± 100	40.0 ± 5%	1.40 ± 5%	5.23	5.23	5.23	0.59	1.38 ± 11.0%
1900	± 50 / ± 100	40.0 ± 5%	1.40 ± 5%	5.14	5.14	5.14	0.51	1.51 ± 11.0%
2000	± 50 / ± 100	40.0 ± 5%	1.40 ± 5%	5.07	5.07	5.07	0.51	1.54 ± 11.0%
2450	± 50 / ± 100	39.2 ± 5%	1.80 ± 5%	4.56	4.56	4.56	0.45	1.70 ± 11.0%

¹⁾ The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

Certificate No: ES3-3088_Nov10

Page 5 of 11

SHGSM

ES3DV3 SN:3088

November 23, 2010

DASY/EASY - Parameters of Probe: ES3DV3 SN:3088

Calibration Parameter Determined in Body Tissue Simulating Media

f [MHz]	Validity [MHz] ^C	Permittivity	Conductivity	ConvF X	ConvF Y	ConvF Z	Alpha	Depth Unc (k=2)
835	± 50 / ± 100	55.2 ± 5%	0.97 ± 5%	5.98	5.98	5.98	0.88	1.13 ± 11.0%
900	± 50 / ± 100	55.0 ± 5%	1.05 ± 5%	5.85	5.85	5.85	0.78	1.19 ± 11.0%
1810	± 50 / ± 100	53.3 ± 5%	1.52 ± 5%	4.92	4.92	4.92	0.26	3.77 ± 11.0%
1900	± 50 / ± 100	53.3 ± 5%	1.52 ± 5%	4.60	4.60	4.60	0.28	2.78 ± 11.0%
2000	± 50 / ± 100	53.3 ± 5%	1.52 ± 5%	4.78	4.76	4.76	0.26	4.52 ± 11.0%
2450	± 50 / ± 100	52.7 ± 5%	1.95 ± 5%	4.34	4.34	4.34	0.44	1.96 ± 11.0%

^C The validity of ± 100 MHz only applies for DASY v4 A and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

Certificate No: ES3-3088_Nov10


Page 6 of 11

SHGSM

ES3DV3 SN:3088

November 23, 2010

Frequency Response of E-Field (TEM-Cell:ifi1110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Certificate No: ES3-3088_Nov'10



Page 7 of 11

SHGSM

ES3DV3 SN:3088

November 23, 2010

Receiving Pattern (ϕ), $\theta = 0^\circ$



Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

Certificate No: ES3-3088_Nov10



Page 8 of 11

SHGSM

ES3DV3 SN:3088

November 23, 2010

Dynamic Range f(SAR_{head}) (TEM cell, f = 900 MHz)



Uncertainty of Linearity Assessment: ± 0.6% (k=2)

Certificate No: ES3-3088_Nov10


Page 9 of 11

SHGSM

ES3DV3 SN:3088


November 23, 2010

Conversion Factor Assessment



Deviation from Isotropy in HSL

Error (ϕ , θ), $f = 900$ MHz



Uncertainty of Spherical Isotropy Assessment: $\pm 2.6\%$ ($k=2$)

Certificate No: ES3-3088_Nov10

Page 10 of 11

SHGSM

ES3DV3 SN:3088

November 23, 2010

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	Not applicable
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm

Certificate No. ES3-3088_Nov10

Page 11 of 11

SHGSM

Annex E.2 DAE Calibration certification

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zaughausstrasse 43, 8004 Zurich, Switzerland

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Client: **SGS-CH (Auden)**




S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accreditation No.: **SCS 108**

Certificate No: **DAE3-569_Nov10**

CALIBRATION CERTIFICATE

Object: **DAE3 - SD 000 D03.AA - SN: 569**

Calibration procedure(s): **QA CAL-06.v22
Calibration procedure for the data acquisition electronics (DAE)**

Calibration date: **November 22, 2010**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (MATE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Keithley Multimeter Type 2001	SN: 0610278	28-Sep-10 (No:10376)	Sep-11

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Calibrator Box V1.1	SE UMS 006 AB 1004	07-Jun-10 (in house check)	In house check: Jun-11

Calibrated by:

Dominique Steffen

Function

Technician

Signature



Approved by:

Fin Bommert

R&D Director



Issued: November 22, 2010

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: DAE3-569_Nov10

Page 1 of 5

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Glossary

DAE data acquisition electronics
Connector angle information used in DASY system to align probe sensor X to the robot coordinate system.

Methods Applied and Interpretation of Parameters

- **DC Voltage Measurement:** Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- **Connector angle:** The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The following parameters as documented in the Appendix contain technical information as a result from the performance test and require no uncertainty.
 - **DC Voltage Measurement Linearity:** Verification of the Linearity at +10% and -10% of the nominal calibration voltage. Influence of offset voltage is included in this measurement.
 - **Common mode sensitivity:** Influence of a positive or negative common mode voltage on the differential measurement.
 - **Channel separation:** Influence of a voltage on the neighbor channels not subject to an input voltage.
 - **AD Converter Values with inputs shorted:** Values on the internal AD converter corresponding to zero input voltage
 - **Input Offset Measurement:** Output voltage and statistical results over a large number of zero voltage measurements.
 - **Input Offset Current:** Typical value for information; Maximum channel input offset current, not considering the input resistance.
 - **Input resistance:** Typical value for information: DAE input resistance at the connector, during internal auto-zeroing and during measurement.
 - **Low Battery Alarm Voltage:** Typical value for information. Below this voltage, a battery alarm signal is generated.
 - **Power consumption:** Typical value for information. Supply currents in various operating modes.

DC Voltage Measurement

A/D - Converter Resolution nominal

High Range: 1LSB = 6.1 μ V, full range = -100...+300 mV

Low Range: 1LSB = 61nV, full range = -1...+3mV

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Calibration Factors	X	Y	Z
High Range	402.938 $\pm$ 0.1% (k=2)	403.345 $\pm$ 0.1% (k=2)	403.529 $\pm$ 0.1% (k=2)
Low Range	3.92800 $\pm$ 0.7% (k=2)	3.95637 $\pm$ 0.7% (k=2)	3.94644 $\pm$ 0.7% (k=2)

Connector Angle

Connector Angle to be used in DASY system	263.0 $^{\circ}$ $\pm$ 1 $^{\circ}$
---	-------------------------------------

Appendix

1. DC Voltage Linearity

High Range	Reading (μV)	Difference (μV)	Error (%)
Channel X + Input	199997.6	0.39	0.00
Channel X + Input	19998.27	-1.73	-0.01
Channel X - Input	-20000.54	-0.84	0.00
Channel Y + Input	199999.9	2.71	0.00
Channel Y + Input	20000.26	0.06	0.00
Channel Y - Input	-19999.11	0.59	-0.00
Channel Z + Input	199999.2	3.34	0.00
Channel Z + Input	19994.29	-5.81	-0.03
Channel Z - Input	-20000.54	-0.74	0.00

Low Range	Reading (μV)	Difference (μV)	Error (%)
Channel X + Input	2000.6	0.76	0.04
Channel X + Input	199.37	-0.23	-0.11
Channel X - Input	-200.61	-0.71	0.35
Channel Y + Input	2000.0	-0.01	-0.00
Channel Y + Input	198.53	-1.37	-0.69
Channel Y - Input	-202.14	-1.84	0.92
Channel Z + Input	2000.6	0.24	0.01
Channel Z + Input	198.39	-1.51	-0.76
Channel Z - Input	-201.69	-1.99	0.99

2. Common mode sensitivity

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	Common mode Input Voltage (mV)	High Range Average Reading (μV)	Low Range Average Reading (μV)
Channel X	200	-0.51	-2.10
	- 200	2.92	2.01
Channel Y	200	4.53	4.19
	- 200	-8.17	-6.12
Channel Z	200	-14.00	-14.37
	- 200	12.62	12.51

3. Channel separation

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	Input Voltage (mV)	Channel X (μV)	Channel Y (μV)	Channel Z (μV)
Channel X	200	-	2.31	-2.14
Channel Y	200	2.21	-	3.30
Channel Z	200	0.63	-0.46	-

4. AD-Converter Values with inputs shorted

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	High Range (LSB)	Low Range (LSB)
Channel X	16227	16350
Channel Y	16586	16231
Channel Z	15827	16157

5. Input Offset Measurement

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Input 10M Ω

	Average (μ V)	min. Offset (μ V)	max. Offset (μ V)	Std. Deviation (μ V)
Channel X	0.17	-1.94	1.87	0.67
Channel Y	-0.86	-2.25	1.36	0.69
Channel Z	-1.20	-2.36	0.46	0.57

6. Input Offset Current

Nominal input circuitry offset current on all channels: <25fA

7. Input Resistance (Typical values for information)

	Zeroing (k Ω m)	Measuring (M Ω m)
Channel X	200	200
Channel Y	200	200
Channel Z	200	200

8. Low Battery Alarm Voltage (Typical values for information)

Typical values	Alarm Level (VDC)
Supply (+ Vcc)	+7.9
Supply (- Vcc)	-7.6

9. Power Consumption (Typical values for information)

Typical values	Switched off (mA)	Stand by (mA)	Transmitting (mA)
Supply (+ Vcc)	+0.01	+6	+14
Supply (- Vcc)	-0.01	-8	-9

Annex E.1 Dipole Calibration certification

D2450V2

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8094 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
S Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Client: SGS-CH (Auden)

Certificate No.: D2450V2-733_Nov10

CALIBRATION CERTIFICATE

Object	D2450V2 - SN: 733																																														
Calibration procedure(s)	QA CAL-05.v7 Calibration procedure for dipole validation kits																																														
Calibration date	November 25, 2010																																														
This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate. All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3) °C and humidity < 70%. Calibration Equipment used (M&TE critical for calibration) <table border="1"> <thead> <tr> <th>Primary Standards</th> <th>ID #</th> <th>Cal Date (Certificate No.)</th> <th>Scheduled Calibration</th> </tr> </thead> <tbody> <tr> <td>Power meter EPM-442A</td> <td>GB37460704</td> <td>06-Oct-10 (No. 217-01266)</td> <td>Oct-11</td> </tr> <tr> <td>Power sensor HP 8481A</td> <td>US37292793</td> <td>06-Oct-10 (No. 217-01266)</td> <td>Oct-11</td> </tr> <tr> <td>Reference 20 dB Attenuator</td> <td>SN: 5086 (20g)</td> <td>30-Mar-10 (No. 217-01158)</td> <td>Mar-11</td> </tr> <tr> <td>Type-N mismatch combination</td> <td>SN: 5047.2 / 06327</td> <td>30-Mar-10 (No. 217-01162)</td> <td>Mar-11</td> </tr> <tr> <td>Reference Probe ES30V3</td> <td>SN: 3205</td> <td>30-Apr-10 (No. ES3-3205_Apr10)</td> <td>Apr-11</td> </tr> <tr> <td>DAE4</td> <td>SN: 601</td> <td>10-Jun-10 (No. DAE4-601_Jun10)</td> <td>Jun-11</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th>Secondary Standards</th> <th>ID #</th> <th>Check Date (in house)</th> <th>Scheduled Check</th> </tr> </thead> <tbody> <tr> <td>Power sensor HP 8481A</td> <td>MY41002317</td> <td>18-Oct-02 (in house check Oct-09)</td> <td>In house check: Oct-11</td> </tr> <tr> <td>RF generator R&S SMT-06</td> <td>100005</td> <td>4-Aug-99 (in house check Oct-06)</td> <td>In house check: Oct-11</td> </tr> <tr> <td>Network Analyzer HP 8753E</td> <td>US37300565 S4206</td> <td>18-Oct-01 (in house check Oct-10)</td> <td>In house check: Oct-11</td> </tr> </tbody> </table>				Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration	Power meter EPM-442A	GB37460704	06-Oct-10 (No. 217-01266)	Oct-11	Power sensor HP 8481A	US37292793	06-Oct-10 (No. 217-01266)	Oct-11	Reference 20 dB Attenuator	SN: 5086 (20g)	30-Mar-10 (No. 217-01158)	Mar-11	Type-N mismatch combination	SN: 5047.2 / 06327	30-Mar-10 (No. 217-01162)	Mar-11	Reference Probe ES30V3	SN: 3205	30-Apr-10 (No. ES3-3205_Apr10)	Apr-11	DAE4	SN: 601	10-Jun-10 (No. DAE4-601_Jun10)	Jun-11	Secondary Standards	ID #	Check Date (in house)	Scheduled Check	Power sensor HP 8481A	MY41002317	18-Oct-02 (in house check Oct-09)	In house check: Oct-11	RF generator R&S SMT-06	100005	4-Aug-99 (in house check Oct-06)	In house check: Oct-11	Network Analyzer HP 8753E	US37300565 S4206	18-Oct-01 (in house check Oct-10)	In house check: Oct-11
Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration																																												
Power meter EPM-442A	GB37460704	06-Oct-10 (No. 217-01266)	Oct-11																																												
Power sensor HP 8481A	US37292793	06-Oct-10 (No. 217-01266)	Oct-11																																												
Reference 20 dB Attenuator	SN: 5086 (20g)	30-Mar-10 (No. 217-01158)	Mar-11																																												
Type-N mismatch combination	SN: 5047.2 / 06327	30-Mar-10 (No. 217-01162)	Mar-11																																												
Reference Probe ES30V3	SN: 3205	30-Apr-10 (No. ES3-3205_Apr10)	Apr-11																																												
DAE4	SN: 601	10-Jun-10 (No. DAE4-601_Jun10)	Jun-11																																												
Secondary Standards	ID #	Check Date (in house)	Scheduled Check																																												
Power sensor HP 8481A	MY41002317	18-Oct-02 (in house check Oct-09)	In house check: Oct-11																																												
RF generator R&S SMT-06	100005	4-Aug-99 (in house check Oct-06)	In house check: Oct-11																																												
Network Analyzer HP 8753E	US37300565 S4206	18-Oct-01 (in house check Oct-10)	In house check: Oct-11																																												
Calibrated by:	Name Dimitre Iliev	Function Laboratory Technician	Signature 																																												
Approved by:	Katja Pokovic	Technical Manager																																													
Issued: November 25, 2010 This calibration certificate shall not be reproduced except in full without written approval of the laboratory.																																															

Certificate No.: D2450V2-733_Nov10

Page 1 of 9

SHGSM

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	52.7	1.95 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	52.3 ± 6 %	1.92 mho/m ± 6 %
Body TSL temperature during test	(21.8 ± 0.2) °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	12.6 mW / g
SAR normalized	normalized to 1W	50.4 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	50.7 mW / g ± 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	5.82 mW / g
SAR normalized	normalized to 1W	23.3 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	23.3 mW / g ± 16.5 % (k=2)

DASY5 Validation Report for Body

Date/Time: 24.11.2010 13:56:51

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:733

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: MSL U12 BB

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.92$ mho/m; $\epsilon_r = 52.3$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.31, 4.31, 4.31); Calibrated: 30.04.2010
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 So601; Calibrated: 10.06.2010
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- Measurement SW: DASY52, V52.2 Build 0, Version 52.2.0 (163)
- Postprocessing SW: SEMCAD X, V14.2 Build 2, Version 14.2.2 (1685)

Pin=250 mW /d=10mm, dist=3.0mm (ES-Probe)/Zoom Scan (7x7x7)/Cube 0: Measurement


grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 93.8 V/m; Power Drift = 0.027 dB

Peak SAR (extrapolated) = 26.7 W/kg

SAR(1 g) = 12.6 mW/g; SAR(10 g) = 5.82 mW/g

Maximum value of SAR (measured) = 16.1 mW/g



Certificate No: D2450V2-733_Nov10

Page 8 of 8

END OF REPORT

SHGSM