

TABLE OF CONTENTS

APPLICANT: Loyal Technology Co., Ltd.

FCC ID: ICK-0022-0021

TEST REPORT CONTAINING:

PAGE 1.....TEST PROCEDURE
PAGE 2.....CIRCUIT DESCRIPTION
PAGE 3.....RADIATION INTERFERENCE TEST DATA
PAGE 4.....OCCUPIED BANDWIDTH

EXHIBIT ATTACHMENTS:

EXHIBIT 1.....POWER OF ATTORNEY LETTER
EXHIBIT 2.....FCC ID LABEL SAMPLE
EXHIBIT 3.....SKETCH OF FCC ID LABEL LOCATION
EXHIBIT 4.....BLOCK DIAGRAM
EXHIBIT 5.....SCHEMATIC
EXHIBIT 6A-6B.....PARTS LIST
EXHIBIT 7.....INSTRUCTION MANUAL
EXHIBIT 8A.....EXTERNAL FRONT PHOTOGRAPH
EXHIBIT 8B.....EXTERNAL REAR PHOTOGRAPH
EXHIBIT 8C.....EXTERNAL WHOLE SET PHOTOGRAPH
EXHIBIT 8D.....INTERNAL CHASSIS PHOTOGRAPH
EXHIBIT 8E.....INTERNAL COMPONENT SIDE PHOTOGRAPH
EXHIBIT 8F.....INTERNAL SOLDER SIDE PHOTOGRAPH

APPLICANT: Loyal Technology Co., Ltd.

FCC ID: ICK-0022-0021

REPORT #: F:\CUS\L\LOYAL\LOY2H9.RPT

PAGE: TABLE OF CONTENTS LIST

APPLICANT: Loyal Technology Co., Ltd.

FCC ID: ICK-0022-0021

TEST EQUIPMENT LIST

1. Spectrum Analyzer: Hewlett Packard 8566B - Opt 462, w/ preselector 85685A, & Quasi-Peak Adapter HP 85650A, & HP 8449B - OPT H02 Cal. 6/26/98
2. Signal Generator, Hewlett Packard 8640B, cal. 10/1/98
3. Eaton Biconical Antenna Model 94455-1
20-200 MHz Serial No. 0997 Cal. 5/15/98
4. Electro-Metric Dipole Kit, 20-1000 MHz, Model TDA-30 10/15/98
5. Electro-Metric Horn 1-18 GHz, Model RGA-180, Cal. 8/15/98
6. Electro-Metric Antennas Model TDA-30/1-4, Cal. 10/15/98
7. Electro-Metric Line Impedance Stabilization Network Model No. EM-7821, Serial No. 101; 100KHz-30MHz 50uH. Cal. 11/19/98
8. Electro-Metric Line Impedance Stabilization Network Model No. EM-7820, Serial No. 2682; 10KHz-30MHz 50uH. Cal. 11/19/98
9. Special low loss cable was used above 1 GHz
10. EMCO Model No. 6512 Passive Loop Antenna Calibrated 10/15/98.
11. Tenney Temperature Chamber

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. In the frequency range 10KHz to 30MHz the RBW was 10KHz and from 30-1000MHz the RBW of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz. The ambient temperature of the UUT was &temp& with a humidity of &humr&.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) METER READING + ACF = FS
33 20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

APPLICANT: Loyal Technology Co., Ltd.

FCC ID: ICK-0022-0021

REPORT #: F:\CUS\L\LOYAL\LOY2H9.RPT

PAGE #: 1

APPLICANT: Loyal Technology Co., Ltd.

FCC ID: ICK-0022-0021

CIRCUIT_DESCRIPTION:

The Loyal Technology Co., Ltd. FCC Identifier ICK-0022-0021 METAL DETECTOR is a 10KHz oscillator. L1 is the main frequency determining element and when it is put in proximatsimity of any metal its inductance changes which in turns changes the frequency slightly. The oscillator is made up of Q3, Q1, Q2, Q4 and IC1. IC2 works as a comparator and triggers a signal when the frequency changes.

ANTENNA_AND_GROUND_CIRCUITRY

This unit makes use of a small plastic case to house the Detector coil which serves as the antenna. This unit is powered from a 9.0V battery.

No ground connection is provided. The unit relies on the ground track of the printed circuit board.

APPLICANT: Loyal Technology Co., Ltd.

FCC ID: ICK-0022-0021

REPORT #: F:\CUS\L\LOYAL\LOY2H9.RPT

PAGE #: 2

APPLICANT: Loyal Technology Co., Ltd.

FCC ID: ICK-0022-0021

NAME OF TEST: RADIATION INTERFERENCE
RULES PART NO.15.109(a) and 15.209

REQUIREMENTS: CARRIER FREQUENCY WILL NOT EXCEED 2400/F(kHz) AT 300 Meters.
OUT-OF-BAND EMISSIONS SHALL NOT EXCEED THE LEVEL OF THE FUNDAMENTAL.

9 to 490 KHz: 2400/F(KHz) uV/m @ 300 METERS
490 to 1705 KHz: 24000/F(KHz) uV/m @ 30 METERS
1705 to 30 MHz: 29.54 dBuV/M @ 30 METERS
30 to 88 MHz: 40.00 dBuV/M @ 3 METERS
88 to 216 MHz: 43.50 dBuV/M
216 to 960 MHz: 46.02 dBuV/M
ABOVE 960 MHz: 54.00 dBuV/M

TEST

CONFIGURATION: The INTENTIONAL RADIATOR was connected to an ignition switch and a harness simulator cable box. The device was tested in both transmitting modes.

TEST DATA:

EMISSION FREQUENCY KHz	METER READING AT 3m dBuV	CORRECT. FACTOR dB	FIELD STRENGTH dBuV/m @ 3m	ANTENNA
10.00	13.6	0.80	14.45	V
20.0	6.4	1.40	7.80	V

Measured at 1.0 meter

At neither 30meters or at 300meters were any emission measurable. the Ambient Noise level was less than 6.0dBuV.

SAMPLE CALCULATION: $FSdBuV/m = MR(dBuV) + ACFdB$.

TEST PROCEDURE: ANSI C63.4-1992 Section 8.2.1. The EUT was placed on a non-conducting table 80CM above the ground plane with the EUT located in the center of the table. With the antenna vertical a preliminary scan was done at 3 meters distance, the EUT was moved to a appropriate distance and the antenna height varied and also placed in a horizontal position. The frequency was scanned from 9.0KHz to 1.0GHz. When an emission was found, the table was rotated to produce the maximum signal strength. The EUT was measured in three(3) orthogonal planes. The unit was measured at TIMCO ENGINEERING, INC. located at 6051 N.W. 19th Lane Gainesville, Florida 32605.

TEST RESULTS: THE UNIT DOES MEET THE FCC REQUIREMENTS.

PERFORMED BY: S. S. SANDERS DATE: 27 JAN. 1999

APPLICANT: Loyal Technology Co., Ltd.
FCC ID: ICK-0022-0021
REPORT #: F:\CUS\L\LOYAL\LOY2H9.RPT
PAGE #: 3