

TABLE OF CONTENTS LIST

APPLICANT: LOYAL TECHNOLOGY CO., LTD.

FCC ID: ICK-0051

TEST REPORT CONTAINING:

PAGE 1-2.....TEST PROCEDURE AND CIRCUIT DESCRIPTION  
PAGE 3.....RADIATION INTERFERENCE TEST DATA  
PAGE 4.....OCCUPIED BANDWIDTH TEST DATA

EXHIBITS CONTAINING:

EXHIBIT 1.....POWER OF ATTORNEY LETTER  
EXHIBIT 2.....BLOCK DIAGRAM  
EXHIBIT 3.....SCHEMATIC  
EXHIBIT 4A-4B.....INSTRUCTION MANUAL  
EXHIBIT 5.....SAMPLE OF FCC ID LABEL  
EXHIBIT 6.....LOCATION OF FCC ID LABEL  
EXHIBIT 7.....EXTERNAL PHOTO - FRONT SIDE  
EXHIBIT 8.....EXTERNAL PHOTO - BACK SIDE  
EXHIBIT 9.....INTERNAL PHOTO - COMPONENT SIDE  
EXHIBIT 10.....INTERNAL PHOTO - COMPONENT CHASSIS VIEW  
EXHIBIT 11.....INTERNAL PHOTO - COPPER SIDE  
EXHIBIT 12.....INTERNAL PHOTO - COPPER CHASSIS VIEW  
EXHIBIT 13.....OCCUPIED BANDWIDTH PLOT - CW  
EXHIBIT 14.....OCCUPIED BANDWIDTH PLOT

APPLICANT: LOYAL TECHNOLOGY CO., LTD.

FCC ID: ICK-0051

REPORT #: T:\CUS\L\LOYAL\LOY466A9\LOY466A9.RPT

PAGE: TABLE OF CONTENTS LIST

APPLICANT: LOYAL TECHNOLOGY CO., LTD.  
FCC ID: ICK-0051

TEST EQUIPMENT LIST

1. Spectrum Analyzer: Hewlett Packard 8566B - Opt 462, w/ preselector 85685A, & Quasi-Peak Adapter HP 85650A, & HP 8449B - OPT H02 Cal. 10/17/99
2. Signal Generator, Hewlett Packard 8640B, cal. 9/23/99
3. Signal Generator, HP 8614A Serial No.2015A07428 cal. 5/27/99
4. EMCO Model No. 6512 Passive Loop 9KHz to 30MHz
5. Eaton Biconnical Antenna Model 94455-1  
20-200 MHz Serial No. 0997 Cal. 9/30/99
6. Electro-Metric Log-Periodic Model No. EM-6950 Ser#632 9/18/99
7. Electro-Metric Dipole Kit, 20-1000 MHz, Model TDA-30 10/31/98
8. Electro-Metric Horn 1-18 GHz, Model RGA-180, Cal. 4/27/99
9. Systron Donner Horn 18-26.3GHz Model DBE-520-20 7/14/99
10. Systron Donner Horn 26.5-40.2GHz Model DBD-520-20 7/14/99
11. ATM Horn 40-60GHz Part #19-443-6R 9/15/99
12. Electro-Metric Antennas Model TDA-30/1-4,Cal. 10/15/98
13. Electro-Metric Line Impedance Stabilization Network Model No. EM-7821, Serial No. 101; 100KHz-30MHz 50uH. Cal.11/19/98
14. Electro-Metric Line Impedance Stabilization Network Model No. EM-7820, Serial No. 2682; 10KHz-30MHz 50uH. Cal. 11/19/98
15. Special low loss cable was used above 1 GHz
16. Tenney Temperature Chamber
17. AC Voltmeter, HP 400FL, Serial No 2213A14499. Cal. 9/21/99
18. Digital Multimeter, Fluke 8010A/12A, Serial No. 4810047. Cal 9/21/99
19. Digital Multimeter, Fluke 77, Serial No. 43850817. Cal 9/21/99
20. Oscilloscope, Tektronix 2230, Serial No. 300572. Cal 9/23/99
21. Frequency Counter, HP 5385A, Serial No. 3242A07460. Cal 10/6/99

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a pre-selector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz. The ambient temperature of the UUT was 80oC with a humidity of 76%.

Example:

Freq (MHz) METER READING + ACF = FS  
33 20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

## TEST PROCEDURES CONTINUED

APPLICANT: LOYAL TECHNOLOGY CO., LTD.  
FCC ID: ICK-0051

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

ANSI STANDARD C63.4-1992 10.1.7 MEASUREMENT PROCEDURES: The unit under test was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

The situation was similar for the conducted measurement except that the table did not rotate. The EUT was setup as described in ANSI C63.4-1992 with the EUT 40 cm from the vertical ground wall.

### CIRCUIT DESCRIPTION:

In the transmit mode the speaker is switched off. The microphone MIC2 is connected to the microphone pre amplifier Q6. The output of Q6 is connected to the input of the audio amplifiers Q3, Q4, & Q5 and the output of Q5 drives the transformer L4. Q5 modulates the voltage of the crystal controlled oscillator, Q1. The crystal controlled oscillator is the transmitter. Q1 is connected to the antenna via the output filter made up of L2, C4, L1, & C1.

### ANTENNA AND GROUND CIRCUITRY

This unit makes use of a external 5" antenna. The antenna is inductively coupled. This unit is powered from a 9.0V battery.

No ground connection is provided. The unit relies on the ground tract of the printed circuit board.

APPLICANT: LOYAL TECHNOLOGY CO., LTD.  
FCC ID: ICK-0051  
REPORT #: T:\CUS\L\LOYAL\LOY466A9\LOY466A9.RPT  
PAGE #: 2

APPLICANT: LOYAL TECHNOLOGY CO., LTD.

FCC ID: ICK-0051

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NO.: 15.235

REQUIREMENTS: CARRIER FREQUENCY WILL NOT EXCEED 80 dBuV/m AT 3M.  
OUT-OF-BAND EMISSIONS SHALL NOT EXCEED:

30 - 88 MHz	40.0 dBuV/M	MEASURED AT 3 METERS
88 - 216 MHz	43.5 dBuV/M	
216 - 960 MHz	46.0 dBuV/M	
ABOVE 960 MHz	54.0 dBuV/M	

TEST DATA:

EMISSION FREQUENCY MHz	METER READING dBuV	COAX LOSS dB	ANTENNA CORRECTION FACTOR	PEAK FIELD STRENGTH dBuV/m@3m			MARGIN dB	ANT. POL.
				10.99	42.54	37.46		
49.86	31.30	0.25						V

NO OTHER EMISSIONS NOTED.

SAMPLE CALCULATION:  $FSdBuV/m = MR(dBuV) + ACFdB$ .

TEST PROCEDURE: The procedure used was ANSI STANDARD C63.4-1992. The spectrum was scanned from 30 MHz to 1000 MHz. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The UUT was tested in 3 orthogonal planes.

TEST RESULTS: THE UNIT DOES MEET THE FCC REQUIREMENTS.

PERFORMED BY: S. S. SANDERS

DATE: NOVEMBER 15, 1999

APPLICANT: LOYAL TECHNOLOGY CO., LTD.  
FCC ID: ICK-0051  
REPORT #: T:\CUS\L\LOYAL\LOY466A9\LOY466A9.RPT  
PAGE #: 3

APPLICANT: LOYAL TECHNOLOGY CO., LTD.

FCC ID: ICK-0051

NAME OF TEST: Occupied Bandwidth

RULES PART NO.: 15.235

REQUIREMENTS: The field strength of any emissions appearing between the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 26 dB below the level of the unmodulated carrier or to the general limits of 15.209, whichever permits the higher emission levels.

THE GRAPHS IN EXHIBITS 13-14 REPRESENT THE EMISSIONS TAKEN FOR THE DEVICE.

METHOD OF MEASUREMENT: A small sample of the transmitter output was fed into the spectrum analyzer and the attached plot was taken. The vertical scale is set to -10 dBm per division. The horizontal scale is set to 5 kHz per division.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: S. S. SANDERS DATE: NOVEMBER 15, 1999

APPLICANT: LOYAL TECHNOLOGY CO., LTD.  
FCC ID: ICK-0051  
REPORT #: T:\CUS\L\LOYAL\LOY466A9\LOY466A9.RPT  
PAGE #: 4