



**FCC 47 CFR PART 15 SUBPART E**

**TEST REPORT**

**For**

**Notebook PC**

**Model: TB120**

**Trade Name: Gateway**

*Issued to*

**Arima Computer Corp  
No. 758, Sec. 4, Bade Road,  
Taipei, Taiwan, R.O.C.**

*Issued by*

**Compliance Certification Services Inc.  
No. 81-1, Lane 210, Bade Rd. 2, Luchu Hsiang,  
Taoyuan Hsien, (338) Taiwan, R.O.C.  
<http://www.ccsemc.com.tw>  
[service@tw.ccsemc.com](mailto:service@tw.ccsemc.com)**



---

*Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.*



# TABLE OF CONTENTS

- 1. TEST RESULT CERTIFICATION..... 3**
- 2. EUT DESCRIPTION ..... 4**
- 3. TEST METHODOLOGY ..... 5**
  - 3.1 EUT CONFIGURATION ..... 5
  - 3.2 EUT EXERCISE ..... 5
  - 3.3 GENERAL TEST PROCEDURES..... 5
  - 3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS..... 6
  - 3.5 DESCRIPTION OF TEST MODES..... 7
- 4. INSTRUMENT CALIBRATION..... 8**
  - 4.1 MEASURING INSTRUMENT CALIBRATION..... 8
  - 4.2 MEASUREMENT EQUIPMENT USED ..... 8
- 5. FACILITIES AND ACCREDITATIONS ..... 9**
  - 5.1 FACILITIES ..... 9
  - 5.2 EQUIPMENT ..... 9
  - 5.3 TABLE OF ACCREDITATIONS AND LISTINGS ..... 10
- 6. SETUP OF EQUIPMENT UNDER TEST ..... 11**
  - 6.1 SETUP CONFIGURATION OF EUT ..... 11
  - 6.2 SUPPORT EQUIPMENT ..... 11
- 7. FCC PART 15 REQUIREMENTS..... 12**
  - 7.1 26 DB EMISSION BANDWIDTH..... 12
  - 7.2 MAXIMUM CONDUCTED OUTPUT POWER ..... 22
  - 7.3 BAND EDGES MEASUREMENT..... 33
  - 7.4 PEAK POWER SPECTRAL DENSITY ..... 46
  - 7.5 PEAK EXCURSION ..... 59
  - 7.6 RADIATED UNDESIRABLE EMISSION ..... 69
  - 7.7 CONDUCTED UNDESIRABLE EMISSION ..... 82
  - 7.8 POWERLINE CONDUCTED EMISSIONS ..... 94
  - 7.9 TRANSMISSION IN ABSENCE OF DATA ..... 97
  - 7.10 FREQUENCY STABILITY ..... 97
  - 7.11 DYNAMIC FREQUENCY SELECTION ..... 98
- APPENDIX I RADIO FREQUENCY EXPOSURE ..... 111**
- APPENDIX 2 PHOTOGRAPHS OF TEST SETUP..... 112**



# 1. TEST RESULT CERTIFICATION

**Applicant:** Arima Computer Corp  
 No. 758, Sec. 4, Bade Road,  
 Taipei, Taiwan, R.O.C.

**Equipment Under Test:** Notebook PC

**Trade Name:** Gateway

**Model:** TB120

**Date of Test:** August 2 ~ September 4, 2007

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart E	No non-compliance noted

### We hereby certify that:

Compliance Certification Services Inc. tested the above equipment. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4: 2003 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.407.

The test results of this report relate only to the tested sample identified in this report.

Approved by:

---

Johnny Liu  
 Section Manager  
 Compliance Certification Services Inc.

Reviewed by:

---

Amanda Wu  
 Section Manager  
 Compliance Certification Services Inc.



## 2. EUT DESCRIPTION

<b>Product</b>	Notebook PC
<b>Trade Name</b>	Gateway
<b>Model Number</b>	TB120
<b>Model Discrepancy</b>	N/A
<b>Power Supply</b>	Gateway / 0335A1965 I/P: AC 100-240V, 1.7A, 50-60Hz O/P: DC 19V, 3.42A
<b>Frequency Range</b>	5.15~5.35 GHz
<b>Transmit Power</b>	IEEE 802.11a mode: 14.63 dBm draft 802.11n Standard-20 MHz Channel mode: 17.94 dBm draft 802.11n Wide-40 MHz Channel mode: 19.23 dBm
<b>Modulation Technique</b>	OFDM (QPSK, BPSK, 16-QAM, 64-QAM)
<b>Transmit Data Rate</b>	IEEE 802.11a mode: 54, 48, 36, 24, 18, 12, 9, 6 Mbps draft 802.11n Standard-20 MHz Channel mode: OFDM (6.5, 7.2, 13, 14.4, 14.44, 19.5, 21.7, 26, 28.89, 28.9, 39, 43.3, 43.33 52, 57.78, 57.8, 58.5, 65.0, 72.2, 78, 86.67, 104, 115.56, 117, 130, 144.44 Mbps) draft 802.11n Wide-40 MHz Channel mode: OFDM (13.5, 15, 27, 30, 40.5, 45, 54, 60, 81, 90, 108, 120, 121.5, 135, 150, 162, 180, 216, 240, 243, 270, 300 Mbps)
<b>Number of Channels</b>	IEEE 802.11a mode: 8 Channels draft 802.11n Standard-20 MHz Channel mode: 8 Channels draft 802.11n Wide-40 MHz Channel mode: 7 Channels
<b>Antenna Specification</b>	Gain: 0.26 dBi
<b>Antenna Designation</b>	PIFA Antenna

### Operation Frequency:

UNLICENSED NATIONAL INFORMATION INFRASTRUCTURE (U-NII)	
CHANNEL	MHz
36	5180
40	5200
44	5220
48	5240
52	5260
56	5280
60	5300
64	5320

### **Remark:**

1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.
2. This submittal(s) (test report) is intended for FCC ID: **ID4TB1204965** filing to comply with Section 15.407 of the FCC Part 15, Subpart E Rules.



### **3. TEST METHODOLOGY**

Both conducted and radiated testing was performed according to the procedures in ANSI C63.4. Radiated testing was performed at an antenna to EUT distance 3 meters.

#### **3.1 EUT CONFIGURATION**

The EUT configuration for testing is installed for RF field strength measurement to meet the Commissions requirement, and is operated in a manner intended to generate the maximum emission in a continuous normal application.

#### **3.2 EUT EXERCISE**

The EUT is operated in the engineering mode to fix the Tx frequency for the purposes of measurement.

According to its specifications, the EUT must comply with the requirements of Section 15.407 under the FCC Rules Part 15 Subpart E.

#### **3.3 GENERAL TEST PROCEDURES**

##### **Conducted Emissions**

The EUT is placed on the turntable, which is positioned at 0.8 m above the ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4, the conducted emission from the EUT is measured in the frequency range between 0.15 MHz and 30MHz, using the CISPR Quasi-Peak detector mode.

##### **Radiated Emissions**

The EUT is placed on the turntable, which is 0.8 m above the ground plane. The turntable is then rotated for 360 degrees to determine the proper orientation for the maximum emission level. The EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission level. And, each emission is to be maximized by changing the horizontal and vertical polarization of the receiving antenna. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4.



### 3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	( <sup>2</sup> )
13.36 - 13.41	322 - 335.4		

<sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup> Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.



### **3.5 DESCRIPTION OF TEST MODES**

The EUT (model: TB120) had been tested under operating condition.

Software used to control the EUT for staying in continuous transmitting mode was programmed.

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz, which worst case was in normal link mode only.

#### **IEEE 802.11a mode:**

Channel Low (5180MHz), Channel Mid (5260MHz) and Channel High (5320MHz) with 6Mbps data rate were chosen for full testing.

#### **draft 802.11n Standard-20 MHz Channel mode:**

Channel Low (5180MHz), Channel Mid (5260MHz) and Channel High (5320MHz) with 6.5Mbps data rate were chosen for full testing.

#### **draft 802.11n Wide-40 MHz Channel mode:**

Channel Low (5190MHz), Channel Mid (5270MHz) and Channel High (5310MHz) with 13.5Mbps data rate were chosen for full testing.

The field strength of spurious emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis) and laptop mode. The worst emission was found in laptop position and the worst case was recorded.



## 4. INSTRUMENT CALIBRATION

### 4.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

### 4.2 MEASUREMENT EQUIPMENT USED

#### Equipment Used for Emissions Measurement

*Remark: Each piece of equipment is scheduled for calibration once a year.*

Conducted Emissions Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY43360131	01/30/2008

3M Semi Anechoic Chamber				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	US42510252	08/01/2008
Test Receiver	Rohde&Schwarz	ESCI	100064	11/13/2007
Switch Controller	TRC	Switch Controller	SC94050010	05/04/2008
4 Port Switch	TRC	4 Port Switch	SC94050020	05/04/2008
Horn-Antenna	TRC	HA-0502	06	06/05/2008
Horn-Antenna	TRC	HA-0801	04	06/20/2008
Horn-Antenna	TRC	HA-1201A	01	07/09/2008
Horn-Antenna	TRC	HA-1301A	01	07/17/2008
Bilog- Antenna	Sunol Sciences	JB3	A030205	03/29/2008
Turn Table	Max-Full	MFT-120S	T120S940302	N.C.R.
Antenna Tower	Max-Full	MFA-430	A440940302	N.C.R.
Controller	Max-Full	MF-CM886	CC-C-1F-13	N.C.R.
Site NSA	CCS	N/A	FCC: 965860 IC: IC 6106	09/25/2008
Test S/W	LABVIEW (V 6.1)			

*Remark: The measurement uncertainty is less than +/-2.0065dB (30MHz ~ 1GHz), +/-3.0958dB (Above 1GHz) which is evaluated as per the NAMAS NIS 81 and CISPR/A/291/CDV.*

Powerline Conducted Emissions Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI TEST RECEIVER 9kHz-30MHz	ROHDE & SCHWARZ	ESHS30	828144/003	10/31/2007
TWO-LINE V-NETWORK 9kHz-30MHz	SCHAFFNER	NNB41	03/10013	06/12/2008
LISN 10kHz-100MHz	EMCO	3825/2	9106-1809	04/01/2008
Test S/W	LABVIEW (V 6.1)			

*Remark: The measurement uncertainty is less than +/- 2.81dB, which is evaluated as per the NAMAS NIS 81 and CISPR/A/291/CDV.*

Dynamic Frequency Selection				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Rohde&Schwarz	FSEK 30	100264	02/19/2008
Signal Generator	Agilent	E8267C	US42340162	12/05/2007





## 5. FACILITIES AND ACCREDITATIONS

### 5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

No. 199, Chunghsen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.

Tel: 886-2-2217-0894 / Fax: 886-2-2217-1029

No. 11, Wugong 6th Rd., Wugu Industrial Park, Taipei Hsien 248, Taiwan

Tel: 886-2-2299-9720 / Fax: 886-2-2298-4045

No.81-1, Lane 210, Bade 2nd Rd., Luchu Hsiang, Taoyuan Hsien 338, Taiwan

Tel: 886-3-324-0332 / Fax: 886-3-324-5235

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

### 5.2 EQUIPMENT








Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

**5.3 TABLE OF ACCREDITATIONS AND LISTINGS**

Country	Agency	Scope of Accreditation	Logo
USA	A2LA	EN 55011, EN 55014-1/2, CISPR 11, CISPR 14-1/2, EN 55022, EN 55015, CISPR 22, CISPR 15, AS/NZS 3548, VCCI V3 (2001), CFR 47, FCC Part 15/18, CNS 13783-1, CNS 13439, CNS 13438, CNS 13803, CNS 14115, EN 55024, IEC 801-2, IEC 801-3, IEC 801-4, IEC/EN 61000-3-2, IEC/EN 61000-3-3, IEC/EN 61000-4-2/3/4/5/6/8/11, EN 50081-1/ EN 61000-6-3, EN 50081-2/EN 61000-6-4, EN 50081-2/EN 61000-6-1: 2001	 ACCREDITED No. 0824-01
USA	FCC	3/10 meter Open Area Test Sites (93105, 90471) / 3M Semi Anechoic Chamber (965860) to perform FCC Part 15/18 measurements	 93105, 90471 965860
Japan	VCCI	3/10 meter Open Area Test Sites to perform conducted/radiated measurements	 R-393/1066/725/879 C-402/747/912
Norway	NEMKO	EN 50081-1/2, EN 50082-1/2, IEC 61000-6-1/2, EN 50091-2, EN 50130-4, EN 55011, EN 55013, EN 55014-1/2, EN 55015, EN 55022, EN 55024, EN 61000-3-2/3, EN 61326-1, IEC 61000-4-2/3/4/5/6/8/11, EN 60601-1-2, EN 300 328, EN 300 422-2, EN 301 419-1, EN 301 489-01/03/07/08/09/17, EN 301 419-2/3, EN 300 454-2, EN 301 357-2	 ELA 124a ELA 124b ELA 124c
Taiwan	TAF	EN 300 328, EN 300 220-1, EN 300 220-2, EN 300 220-3, 47 CFR FCC Part 15 Subpart C, EN 61000-3-2, EN 61000-3-3, CNS 13439, CNS 13783-1, CNS 14115, CNS 13438, AS/NZS CISPR 22, CNS 13022-1, IEC 61000-4-2/3/4/5/6/8/11, CNS 13022-2/3	 Testing Laboratory 0363
Taiwan	BSMI	CNS 13438, CNS 13783-1, CNS 13439, CNS 14115	 SL2-IS-E-0014 SL2-IN-E-0014 SL2-A1-E-0014 SL2-R1-E-0014 SL2-R2-E-0014 SL2-L1-E-0014
Canada	Industry Canada	3/10 meter Open Area Test Sites (IC 2324C-3, IC 2324C-5) / 3M Semi Anechoic Chamber (IC 6106)	 IC 2324C-3 IC 2324C-5 IC 6106

\* No part of this report may be used to claim or imply product endorsement by A2LA or any agency of the US Government.



## 6. SETUP OF EQUIPMENT UNDER TEST

### 6.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix I for the actual connections between EUT and support equipment.

### 6.2 SUPPORT EQUIPMENT

No.	Device Type	Brand	Model	Series No.	FCC ID	Data Cable	Power Cord
1.	Super a/g 108Mbps Wireless Lan Router (Remote)	PLANEX	BLW-04SAG	40DDA0421	SJ9-BLW54SAG	N/A	Unshielded, 1.8m

**Remark:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.




## 7. FCC PART 15 REQUIREMENTS

### 7.126 dB EMISSION BANDWIDTH

#### LIMIT

According to §15.303(c), for purposes of this subpart the emission bandwidth shall be determined by measuring the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, that are 26 dB down relative to the maximum level of the modulated carrier. Compliance with the emissions limits is based on the use of measurement instrumentation employing a peak detector function with an instrument resolutions bandwidth approximately equal to 1.0 percent of the emission bandwidth of the device under measurement.

#### Test Configuration



#### TEST PROCEDURE

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low-loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW > 1%EBW, VBW > RBW, Span >26dB bandwidth, and Sweep = auto.
4. Mark the peak frequency and -26dB (upper and lower) frequency.
5. Repeat until all the rest channels were investigated.

#### TEST RESULTS

*No non-compliance noted*



**Test Data**

**Test mode: IEEE 802.11a mode**

Channel	Frequency (MHz)	Bandwidth (B) (MHz)
Low	5180	20.952
Mid	5260	21.472
High	5320	20.692

**Test mode: draft 802.11n Standard-20 MHz Channel mode / Chain 0**

Channel	Frequency (MHz)	Bandwidth (B) (MHz)
Low	5180	20.883
Mid	5260	21.377
High	5320	22.287

**Test mode: draft 802.11n Standard-20 MHz Channel mode / Chain 1**

Channel	Frequency (MHz)	Bandwidth (B) (MHz)
Low	5180	21.880
Mid	5260	25.412
High	5320	21.828

**Test mode: draft 802.11n Wide-40 MHz Channel mode / Chain 0**

Channel	Frequency (MHz)	Bandwidth (B) (MHz)
Low	5190	39.118
Mid	5270	50.000
High	5310	39.849

**Test mode: draft 802.11n Wide-40 MHz Channel mode / Chain 1**

Channel	Frequency (MHz)	Bandwidth (B) (MHz)
Low	5190	39.488
Mid	5270	49.961
High	5310	39.019



Test Plot

IEEE 802.11a mode:

CH Low


Agilent 17:35:19 Aug 6, 2007

R T

26 dB BW, a Mode Low Ch.

Ref 20 dBm

Atten 20 dB



Center 5.180 00 GHz

Span 50 MHz

#Res BW 150 kHz

#VBW 470 kHz

Sweep 2.12 ms (601 pts)

Occupied Bandwidth

16.5450 MHz

Occ BW % Pwr	99.00 %
x dB	-26.00 dB

Transmit Freq Error	-11.106 kHz
x dB Bandwidth	20.952 MHz

CH Mid


Agilent 18:42:28 Aug 6, 2007

R T

26 dB BW, a Mode Mid Ch.

Ref 20 dBm

Atten 20 dB



Center 5.260 00 GHz

Span 50 MHz

#Res BW 240 kHz

#VBW 680 kHz

Sweep 1 ms (601 pts)

Occupied Bandwidth

16.6540 MHz

Occ BW % Pwr	99.00 %
x dB	-26.00 dB

Transmit Freq Error	-449.374 Hz
x dB Bandwidth	21.472 MHz



### CH High


Agilent 18:49:37 Aug 6, 2007

R T

26 dB BW, a Mode High Ch.

Ref 20 dBm

Atten 20 dB



Center 5.320 00 GHz

Span 50 MHz

#Res BW 160 kHz

#VBW 470 kHz

Sweep 1.88 ms (601 pts)

Occupied Bandwidth  
16.5378 MHz

Occ BW % Pwr 99.00 %  
x dB -26.00 dB

Transmit Freq Error -1.036 kHz  
x dB Bandwidth 20.692 MHz



**draft 802.11n Standard-20 MHz Channel mode / Chain 0**

**CH Low**


Agilent 14:35:52 Aug 7, 2007

R T

26 dB BW, a Mode Low Ch.

Ref 20 dBm

Atten 20 dB



Center 5.180 00 GHz

Span 50 MHz

#Res BW 150 kHz

#VBW 430 kHz

Sweep 2.16 ms (601 pts)

Occupied Bandwidth  
17.7081 MHz

Occ BW % Pwr 99.00 %  
x dB -26.00 dB

Transmit Freq Error 3.324 kHz  
x dB Bandwidth 20.883 MHz

**CH Mid**


Agilent 14:42:40 Aug 7, 2007

R T

26 dB BW, a Mode Mid Ch.

Ref 20 dBm

Atten 20 dB



Center 5.260 00 GHz

Span 50 MHz

#Res BW 200 kHz

#VBW 620 kHz

Sweep 1.2 ms (601 pts)

Occupied Bandwidth  
17.7660 MHz

Occ BW % Pwr 99.00 %  
x dB -26.00 dB

Transmit Freq Error -7.490 kHz  
x dB Bandwidth 21.377 MHz





### CH High


Agilent 14:46:31 Aug 7, 2007

R T

26 dB BW, a Mode High Ch.

Ref 20 dBm

Atten 20 dB



Center 5.320 00 GHz

Span 50 MHz

#Res BW 240 kHz

#VBW 680 kHz

Sweep 1 ms (601 pts)

Occupied Bandwidth  
17.8110 MHz

Occ BW % Pwr 99.00 %  
x dB -26.00 dB

Transmit Freq Error 6.419 kHz  
x dB Bandwidth 22.287 MHz

### draft 802.11n Standard-20 MHz Channel mode / Chain 1

### CH Low


Agilent 19:04:48 Aug 7, 2007

R L

26 dB BW, a Mode Low Ch.

Ref 20 dBm

Atten 20 dB



Center 5.180 00 GHz

Span 50 MHz

#Res BW 240 kHz

#VBW 680 kHz

Sweep 1 ms (601 pts)

Occupied Bandwidth  
16.6350 MHz

Occ BW % Pwr 99.00 %  
x dB -26.00 dB

Transmit Freq Error -243.699 kHz  
x dB Bandwidth 21.880 MHz



### CH Mid


Agilent 19:12:49 Aug 7, 2007

R L

26 dB BW, a Mode Mid Ch.

Ref 20 dBm

Atten 20 dB



Center 5.260 00 GHz

#Res BW 270 kHz

#VBW 820 kHz

Span 50 MHz  
Sweep 1 ms (601 pts)

Occupied Bandwidth  
16.9649 MHz

Occ BW % Pwr 99.00 %  
x dB -26.00 dB

Transmit Freq Error 21.487 kHz  
x dB Bandwidth 25.412 MHz

### CH High


Agilent 19:18:50 Aug 7, 2007

R L

26 dB BW, a Mode High Ch.

Ref 20 dBm

Atten 20 dB



Center 5.320 00 GHz

#Res BW 240 kHz

#VBW 680 kHz

Span 50 MHz  
Sweep 1 ms (601 pts)

Occupied Bandwidth  
16.7828 MHz

Occ BW % Pwr 99.00 %  
x dB -26.00 dB

Transmit Freq Error 9.926 kHz  
x dB Bandwidth 21.828 MHz



**draft 802.11n Wide-40 MHz Channel mode / Chain 0**

**CH Low**


Agilent 17:54:36 Aug 7, 2007

R T

26 dB BW, a Mode Low Ch.

Ref 20 dBm

Atten 20 dB



Center 5.190 00 GHz

Span 50 MHz

#Res BW 300 kHz

#VBW 910 kHz

Sweep 1 ms (601 pts)

Occupied Bandwidth  
35.7705 MHz

Occ BW % Pwr 99.00 %  
x dB -26.00 dB

Transmit Freq Error 9.389 kHz  
x dB Bandwidth 39.118 MHz

**CH Mid**


Agilent 17:57:47 Aug 7, 2007

R T

26 dB BW, a Mode Mid Ch.

Ref 20 dBm

Atten 20 dB



Center 5.270 00 GHz

Span 50 MHz

#Res BW 620 kHz

#VBW 1.8 MHz

Sweep 1 ms (601 pts)

Occupied Bandwidth  
36.2236 MHz

Occ BW % Pwr 99.00 %  
x dB -26.00 dB

Transmit Freq Error 1.776 kHz  
x dB Bandwidth 50.000 MHz



### CH High


Agilent 09:19:11 Aug 8, 2007

R T

26 dB BW, a Mode High Ch.

Ref 20 dBm

Atten 20 dB



Center 5.310 00 GHz

Span 50 MHz

#Res BW 430 kHz

#VBW 1.3 MHz

Sweep 1 ms (601 pts)

Occupied Bandwidth  
35.7678 MHz

Occ BW % Pwr 99.00 %  
x dB -26.00 dB

Transmit Freq Error -12.732 kHz  
x dB Bandwidth 39.849 MHz

### draft 802.11n Wide-40 MHz Channel mode / Chain 1

### CH Low


Agilent 16:24:51 Aug 7, 2007

R T

26 dB BW, a Mode Low Ch.

Ref 20 dBm

Atten 20 dB



Center 5.190 00 GHz

Span 50 MHz

#Res BW 470 kHz

#VBW 1.3 MHz

Sweep 1 ms (601 pts)

Occupied Bandwidth  
35.8435 MHz

Occ BW % Pwr 99.00 %  
x dB -26.00 dB

Transmit Freq Error 15.073 kHz  
x dB Bandwidth 39.488 MHz



### CH Mid


Agilent 16:28:48 Aug 7, 2007

R T

26 dB BW, a Mode Mid Ch.

Ref 20 dBm

Atten 20 dB



Center 5.270 00 GHz

Span 50 MHz

#Res BW 510 kHz

#VBW 1.5 MHz

Sweep 1 ms (601 pts)

Occupied Bandwidth  
36.0002 MHz

Occ BW % Pwr 99.00 %  
x dB -26.00 dB

Transmit Freq Error 14.994 kHz  
x dB Bandwidth 49.961 MHz

### CH High


Agilent 16:32:35 Aug 7, 2007

R T

26 dB BW, a Mode High Ch.

Ref 20 dBm

Atten 20 dB



Center 5.310 00 GHz

Span 50 MHz

#Res BW 300 kHz

#VBW 910 kHz

Sweep 1 ms (601 pts)

Occupied Bandwidth  
35.7756 MHz

Occ BW % Pwr 99.00 %  
x dB -26.00 dB

Transmit Freq Error -55.261 kHz  
x dB Bandwidth 39.019 MHz



## 7.2 MAXIMUM CONDUCTED OUTPUT POWER

### LIMIT

According to §15.407(a),

- (1) For the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 50 mW or  $4 \text{ dBm} + 10 \log B$ , where B is the 26 dB emission bandwidth in MHz.
- (2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log B$ , where B is the 26 dB emission bandwidth in MHz.

*If transmitting antennas of directional gain greater than 6dBi are used, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.*

The peak power shall not exceed the limit as follow:

### Specified Limit of the Peak Power

**Test mode: IEEE 802.11a mode**

Channel	Frequency (MHz)	26 dB Bandwidth (B) (MHz)	10 Log B (dB)	4 + 10 Log B or 11 + 10 Log B (dBm)	Maximum Conducted Output Power Limit (dBm)
Low	5180	20.952	13.21	17.21	17.00
Mid	5260	21.472	13.32	24.32	24.00
High	5320	20.692	13.16	24.16	24.00

**Test mode: draft 802.11n Standard-20 MHz Channel mode**

Channel	Frequency (MHz)	Chain 0 26 dB Bandwidth (B) (MHz)	Chain 1 26 dB Bandwidth (B) (MHz)	Total 26 dB Bandwidth (B) (MHz)	10 Log B (dB)	4 + 10 Log B or 11 + 10 Log B (dBm)	Maximum Conducted Output Power Limit (dBm)
Low	5180	20.883	21.880	24.42	13.88	17.88	17.00
Mid	5260	21.377	25.412	26.86	14.29	25.29	24.00
High	5320	22.287	21.828	25.07	13.99	24.99	24.00


**Test mode: draft 802.11n Wide-40 MHz Channel mode**

Channel	Frequency (MHz)	Chain 0 26 dB Bandwidth (B) (MHz)	Chain 1 26 dB Bandwidth (B) (MHz)	Total 26 dB Bandwidth (B) (MHz)	10 Log B (dB)	4 + 10 Log B or 11 + 10 Log B (dBm)	Maximum Conducted Output Power Limit (dBm)
Low	5190	39.118	39.488	42.32	16.27	20.27	17.00
Mid	5270	50.000	49.961	52.99	17.24	28.24	24.00
High	5310	39.849	39.019	42.46	16.28	27.28	24.00

*(Remark: Maximum antenna gain = 0.26dBi, therefore there is no reduction due to antenna gain.)*

**Test Configuration**

The EUT was connected to a spectrum analyzer through a 50 Ω RF cable.



**TEST PROCEDURE**

Set span to encompass the entire emission bandwidth (EBW) of the signal.

Set RBW = 1 MHz / Set VBW = 3 MHz.

Use sample detector mode if bin width (i.e., span/number of points in spectrum display) < 0.5 RBW. Otherwise use peak detector mode. Use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at full control power for entire sweep of every sweep. If the device transmits continuously, with no off intervals or reduced power intervals, the trigger may be set to “free run”. Trace average 100 traces in power averaging mode. Compute power by integrating the spectrum across the 26 dB EBW of the signal. The integration can be performed using the spectrum analyzer’s band power measurement function with band limits set equal to the EBW band edges or by summing power levels in each 1 MHz band in linear power terms. The 1 MHz band power levels to be summed can be obtained by averaging, in linear power terms, power levels in each frequency bin across the 1 MHz.

**TEST RESULTS**

*No non-compliance noted*

**Test Data**

**Test mode: IEEE 802.11a mode**

Channel	Frequency (MHz)	Maximum Conducted Output Power (dBm)	Limit (dBm)
Low	5180	14.63	17.00
Mid	5260	11.74	24.00
High	5320	11.35	24.00

**Test mode: draft 802.11n Standard-20 MHz Channel mode**

Channel	Frequency (MHz)	Chain 0 Output Power (dBm)	Chain 1 Output Power (dBm)	Total Maximum Conducted Output Power (dBm)	Limit (dBm)
Low	5180	11.11	14.07	15.85	17.00
Mid	5260	9.44	17.28	17.94	24.00
High	5320	9.51	14.10	15.40	24.00



**Test mode: draft 802.11n Wide-40 MHz Channel mode**

<b>Channel</b>	<b>Frequency (MHz)</b>	<b>Chain 0 Output Power (dBm)</b>	<b>Chain 1 Output Power (dBm)</b>	<b>Total Maximum Conducted Output Power (dBm)</b>	<b>Limit (dBm)</b>
Low	5190	6.47	6.79	9.64	17.00
Mid	5270	16.43	16.00	19.23	24.00
High	5310	11.02	8.25	12.86	24.00





**Test Plot**

**Test mode: IEEE 802.11a mode:**

**CH Low**


Agilent 17:36:49 Aug 6, 2007

R T

Peak Transmit Power, a Mode Low Ch.

Ref 30 dBm

Atten 30 dB



Center 5.180 00 GHz

Span 24.99 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

14.63 dBm / 16.6600 MHz

-57.59 dBm/Hz

**CH Mid**


Agilent 18:43:56 Aug 6, 2007

R T

Peak Transmit Power, a Mode Mid Ch.

Ref 30 dBm

Atten 30 dB



Center 5.260 00 GHz

Span 24.9 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

11.74 dBm / 16.6000 MHz

-60.47 dBm/Hz



### CH High


Agilent 18:50:23 Aug 6, 2007

R T

Peak Transmit Power, a Mode High Ch.

Ref 30 dBm

Atten 30 dB



Center 5.320 00 GHz

Span 24.82 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

11.35 dBm / 16.5500 MHz

-60.84 dBm/Hz

### Test mode: draft 802.11n Standard-20 MHz Channel mode / Chain 0:

### CH Low


Agilent 14:37:57 Aug 7, 2007

R T

Peak Transmit Power, a Mode Low Ch.

Ref 30 dBm

Atten 30 dB



Center 5.180 00 GHz

Span 26.7 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

11.11 dBm / 17.8000 MHz

-61.40 dBm/Hz



### CH Mid


Agilent 14:43:48 Aug 7, 2007

R T

Peak Transmit Power, a Mode Mid Ch.

Ref 30 dBm

Atten 30 dB



Center 5.260 00 GHz

Span 26.59 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

9.44 dBm / 17.7300 MHz

-63.04 dBm/Hz

### CH High


Agilent 14:47:19 Aug 7, 2007

R T

Peak Transmit Power, a Mode High Ch.

Ref 30 dBm

Atten 30 dB



Center 5.320 00 GHz

Span 26.62 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

9.51 dBm / 17.7500 MHz

-62.98 dBm/Hz



**Test mode: draft 802.11n Standard-20 MHz Channel mode / Chain 1:**

**CH Low**


Agilent 19:06:32 Aug 7, 2007

R L

Peak Transmit Power, a Mode Low Ch.

Ref 30 dBm

Atten 30 dB



Center 5.180 00 GHz

Span 25.05 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

14.07 dBm / 16.7000 MHz

-58.16 dBm/Hz

**CH Mid**


Agilent 19:15:56 Aug 7, 2007

R L

Peak Transmit Power, a Mode Mid Ch.

Ref 30 dBm

Atten 30 dB



Center 5.260 00 GHz

Span 25.35 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

17.28 dBm / 16.9000 MHz

-54.99 dBm/Hz



### CH High


Agilent 19:19:35 Aug 7, 2007

R L

Peak Transmit Power, a Mode High Ch.

Ref 30 dBm

Atten 30 dB



Center 5.320 00 GHz

Span 25.05 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

14.10 dBm / 16.7000 MHz

-58.13 dBm/Hz

### Test mode: draft 802.11n Wide-40 MHz Channel mode / Chain 0:

### CH Low


Agilent 17:55:05 Aug 7, 2007

R T

Peak Transmit Power, a Mode Low Ch.

Ref 30 dBm

Atten 30 dB



Center 5.190 00 GHz

Span 53.55 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

6.47 dBm / 35.7000 MHz

-69.06 dBm/Hz



### CH Mid


Agilent 17:58:42 Aug 7, 2007

R T

Peak Transmit Power, a Mode Mid Ch.

Ref 30 dBm

Atten 30 dB



Center 5.270 00 GHz

Span 54.3 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

16.43 dBm / 36.2000 MHz

-59.16 dBm/Hz

### CH High


Agilent 09:19:52 Aug 8, 2007

R T

Peak Transmit Power, a Mode High Ch.

Ref 30 dBm

Atten 30 dB



Center 5.310 00 GHz

Span 53.62 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

11.02 dBm / 35.7500 MHz

-64.52 dBm/Hz



**Test mode: draft 802.11n Wide-40 MHz Channel mode / Chain 1:**

**CH Low**


Agilent 16:25:28 Aug 7, 2007

R T

Peak Transmit Power, a Mode Low Ch.

Ref 30 dBm

Atten 30 dB



Center 5.190 00 GHz

Span 53.73 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

6.79 dBm / 35.8200 MHz

-68.75 dBm/Hz

**CH Mid**


Agilent 16:29:44 Aug 7, 2007

R T

Peak Transmit Power, a Mode Mid Ch.

Ref 30 dBm

Atten 30 dB



Center 5.270 00 GHz

Span 54.21 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

16.00 dBm / 36.1400 MHz

-59.58 dBm/Hz



### CH High


Agilent 16:33:43 Aug 7, 2007

R T

Peak Transmit Power, a Mode High Ch.

Ref 30 dBm

Atten 30 dB



Center 5.310 00 GHz

Span 53.74 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

8.25 dBm / 35.8300 MHz

-67.29 dBm/Hz




## 7.3BAND EDGES MEASUREMENT

### LIMIT

According to §15.407(b),

- (1) The provisions of Section 15.205 of this part apply to intentional radiators operating under this section.
- (2) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency block edges as the design of the equipment permits.

### Test Configuration



### TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
  - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
  - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

### TEST RESULTS

Refer to attach spectrum analyzer data chart.




### Band Edges (IEEE 802.11a mode / CH Low)

Detector mode: Peak

Polarity: Vertical

Agilent 18:07:34 Aug 2, 2007

T




Detector mode: Average

Polarity: Vertical

Agilent 18:06:54 Aug 2, 2007

T






Detector mode: Peak

Polarity: Horizontal

Agilent 18:13:45 Aug 2, 2007

T




Detector mode: Average

Polarity: Horizontal

Agilent 18:13:14 Aug 2, 2007

T





### Band Edges (IEEE 802.11a mode / CH High)


Detector mode: Peak

Polarity: Vertical

Agilent 19:27:17 Aug 2, 2007

T

Mkr1 5.350 0 GHz  
67.27 dB $\mu$ V




Detector mode: Average

Polarity: Vertical

Agilent 19:26:50 Aug 2, 2007

T

Mkr1 5.350 0 GHz  
51.44 dB $\mu$ V






Detector mode: Peak

Polarity: Horizontal

Agilent 19:23:58 Aug 2, 2007

T




Detector mode: Average

Polarity: Horizontal

Agilent 19:23:30 Aug 2, 2007

T






**Band Edges (draft 802.11n Standard-20 MHz Channel mode / CH Low)**

**Detector mode: Peak**

**Polarity: Vertical**

Agilent 19:00:39 Aug 2, 2007

T




**Detector mode: Average**

**Polarity: Vertical**

Agilent 18:59:24 Aug 2, 2007

T






Detector mode: Peak

Polarity: Horizontal

Agilent 19:04:15 Aug 2, 2007

T




Detector mode: Average

Polarity: Horizontal

Agilent 19:03:48 Aug 2, 2007

T






### Band Edges (draft 802.11n Standard-20 MHz Channel mode / CH High)

Detector mode: Peak

Polarity: Vertical

Agilent 19:38:48 Aug 2, 2007

T




Detector mode: Average

Polarity: Vertical

Agilent 19:38:26 Aug 2, 2007

T








Detector mode: Peak

Polarity: Horizontal

Agilent 19:34:54 Aug 2, 2007

T




Detector mode: Average

Polarity: Horizontal

Agilent 19:34:32 Aug 2, 2007

T






Band Edges (draft 802.11n Wide-40 MHz Channel mode / CH Low)

Detector mode: Peak

Polarity: Vertical

Agilent 19:16:25 Aug 2, 2007

T




Detector mode: Average

Polarity: Vertical

Agilent 19:15:56 Aug 2, 2007

T






Detector mode: Peak

Polarity: Horizontal

Agilent 19:12:07 Aug 2, 2007

T

Mkr1 5.150 0 GHz  
67.44 dBµV




Detector mode: Average

Polarity: Horizontal

Agilent 19:11:38 Aug 2, 2007

T

Mkr1 5.150 0 GHz  
52.38 dBµV





Band Edges (draft 802.11n Wide-40 MHz Channel mode / CH High)


Detector mode: Peak

Polarity: Vertical

Agilent 19:50:52 Aug 2, 2007

T

Mkr1 5.350 0 GHz  
65.63 dBµV




Detector mode: Average

Polarity: Vertical

Agilent 19:50:30 Aug 2, 2007

T

Mkr1 5.350 0 GHz  
51.52 dBµV






Detector mode: Peak

Polarity: Horizontal

Agilent 19:46:58 Aug 2, 2007

T

Mkr1 5.350 0 GHz  
67.24 dBµV




Detector mode: Average

Polarity: Horizontal

Agilent 19:46:37 Aug 2, 2007

T

Mkr1 5.350 0 GHz  
52.13 dBµV



## 7.4 PEAK POWER SPECTRAL DENSITY


### LIMIT

According to §15.407(a),

- (1) For the band 5.15-5.25 GHz, the peak power spectral density shall not exceed 4dBm in any 1MHz band.
- (2) For the band 5.25-5.35 GHz, the peak power spectral density shall not exceed 11dBm in any 1MHz band.

*If transmitting antennas of directional gain greater than 6dBi are used, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.*

### Test Configuration



### TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.  
Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW = 1MHz, VBW = 3MHz, Span = Sweep= AUTO
3. Record the max. reading.
4. Repeat the above procedure until the measurements for all frequencies are completed

### TEST RESULTS

*No non-compliance noted*

**Test Data****Test mode: IEEE 802.11a mode**

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Margin	Result
Low	5180	3.27	4.00	-0.73	PASS
Mid	5260	2.10	11.00	-8.90	PASS
High	5320	1.11	11.00	-9.89	PASS

**Test mode: draft 802.11n Standard-20 MHz Channel mode**

Channel	Frequency (MHz)	Chain 0 PPSD (dBm)	Chain 1 PPSD (dBm)	PPSD (dBm)	Limit (dBm)	Margin	Result
Low	5180	0.829	0.938	3.89	4.00	-0.11	PASS
Mid	5260	0.873	7.562	8.41	11.00	-2.59	PASS
High	5320	0.845	3.594	5.44	11.00	-5.56	PASS

**Test mode: draft 802.11n Wide-40 MHz Channel mode**

Channel	Frequency (MHz)	Chain 0 PPSD (dBm)	Chain 1 PPSD (dBm)	PPSD (dBm)	Limit (dBm)	Margin	Result
Low	5190	-5.371	-5.539	-2.44	4.00	-6.44	PASS
Mid	5270	5.409	5.154	8.29	11.00	-2.71	PASS
High	5310	0.264	-3.028	1.93	11.00	-9.07	PASS

**Test mode: draft 802.11n Standard-20 MHz Channel mode with combiner**

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Margin	Result
Low	5180	1.704	4.00	-2.296	PASS
Mid	5260	1.293	11.00	-9.707	PASS
High	5320	2.923	11.00	-8.077	PASS

**Test mode: draft 802.11n Wide-40 MHz Channel mode with combiner**

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Margin	Result
Low	5190	-2.418	4.00	-6.418	PASS
Mid	5270	7.281	11.00	-3.719	PASS
High	5310	0.490	11.00	-10.510	PASS

*(Remark: 1. Maximum antenna gain = 0.26dBi, therefore there is no reduction due to antenna gain.*


*2. Total PPSD (dBm) = 10\*LOG(10^(Chain 0 PPSD / 10)+10^(Chain 1 PPSD / 10))*




**Test Plot**

**Test mode: IEEE 802.11a mode:**

**CH Low**



**CH Mid**







### CH High

Agilent 18:50:44 Aug 6, 2007

R T


Peak Power Spectral Density, a Mode High Ch.

Mkr1 5.313 38 GHz

Ref 30 dBm

Atten 30 dB

1.113 dBm



Channel Power

Power Spectral Density

10.98 dBm / 16.5500 MHz

-61.21 dBm/Hz

### Test mode: draft 802.11n Standard-20 MHz Channel mode / Chain 0:

### CH Low

Agilent 14:38:24 Aug 7, 2007

R T


Peak Power Spectral Density, a Mode Low Ch.

Mkr1 5.183 56 GHz

Ref 30 dBm

Atten 30 dB

0.829 dBm



Channel Power

Power Spectral Density

9.73 dBm / 17.8000 MHz

-62.78 dBm/Hz



### CH Mid

Agilent 14:44:01 Aug 7, 2007

R T


Peak Power Spectral Density, a Mode Mid Ch.

Mkr1 5.254 81 GHz

Ref 30 dBm

Atten 30 dB

0.873 dBm



Center 5.260 00 GHz

Span 26.59 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

10.98 dBm / 17.7300 MHz

-61.50 dBm/Hz

### CH High

Agilent 14:47:32 Aug 7, 2007

R T


Peak Power Spectral Density, a Mode High Ch.

Mkr1 5.316 58 GHz

Ref 30 dBm

Atten 30 dB

0.845 dBm



Center 5.320 00 GHz

Span 26.62 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

11.27 dBm / 17.7500 MHz

-61.22 dBm/Hz



**Test mode: draft 802.11n Standard-20 MHz Channel mode / Chain 1:**

**CH Low**

Agilent 19:06:56 Aug 7, 2007

R T


Peak Power Spectral Density, a Mode Low Ch.

Mkr1 5.185 72 GHz

Ref 30 dBm

Atten 30 dB

0.938 dBm



Center 5.180 00 GHz

Span 25.05 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

13.66 dBm / 16.7000 MHz

-58.56 dBm/Hz

**CH Mid**

Agilent 19:16:09 Aug 7, 2007

R L


Peak Power Spectral Density, a Mode Mid Ch.

Mkr1 5.264 86 GHz

Ref 30 dBm

Atten 30 dB

7.562 dBm



Center 5.260 00 GHz

Span 25.35 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

17.44 dBm / 16.9000 MHz

-54.83 dBm/Hz



### CH High

Agilent 19:19:47 Aug 7, 2007

R L


Peak Power Spectral Density, a Mode High Ch.

Mkr1 5.315 95 GHz

Ref 30 dBm

Atten 30 dB

3.594 dBm



Center 5.320 00 GHz

Span 25.05 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

14.27 dBm / 16.7000 MHz

-57.96 dBm/Hz

### Test mode: draft 802.11n Wide-40 MHz Channel mode / Chain 0:

### CH Low

Agilent 17:55:16 Aug 7, 2007

R T


Peak Power Spectral Density, a Mode Low Ch.

Mkr1 5.180 09 GHz

Ref 30 dBm

Atten 30 dB

5.371 dBm



Center 5.190 00 GHz

Span 53.55 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

6.95 dBm / 35.7000 MHz

-68.58 dBm/Hz



### CH Mid

Agilent 20:14:30 Aug 7, 2007

R T


Peak Power Spectral Density, a Mode Mid Ch.

Mkr1 5.275 43 GHz

Ref 30 dBm

Atten 30 dB

5.409 dBm



Center 5.270 00 GHz

Span 54.3 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

15.99 dBm / 36.2000 MHz

-59.59 dBm/Hz

### CH High

Agilent 09:20:07 Aug 8, 2007

R T


Peak Power Spectral Density, a Mode High Ch.

Mkr1 5.317 78 GHz

Ref 30 dBm

Atten 30 dB

0.264 dBm



Center 5.310 00 GHz

Span 53.62 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

11.21 dBm / 35.7500 MHz

-64.33 dBm/Hz



**Test mode: draft 802.11n Wide-40 MHz Channel mode / Chain 1:**

**CH Low**

Agilent 16:25:42 Aug 7, 2007

R T


Peak Power Spectral Density, a Mode Low Ch.

Mkr1 5.206 30 GHz

Ref 30 dBm

Atten 30 dB

-5.539 dBm



Center 5.190 00 GHz

Span 53.73 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

6.17 dBm / 35.8200 MHz

-69.37 dBm/Hz

**CH Mid**

Agilent 16:29:58 Aug 7, 2007

R T


Peak Power Spectral Density, a Mode Mid Ch.

Mkr1 5.279 85 GHz

Ref 30 dBm

Atten 30 dB

5.154 dBm



Center 5.270 00 GHz

Span 54.21 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

16.14 dBm / 36.1400 MHz

-59.44 dBm/Hz



### CH High

Agilent 16:33:54 Aug 7, 2007

R T


Peak Power Spectral Density, a Mode High Ch.

Mkr1 5.321 38 GHz

Ref 30 dBm

Atten 30 dB

-3.028 dBm



Center 5.310 00 GHz

Span 53.74 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

8.48 dBm / 35.8300 MHz

-67.06 dBm/Hz

### Test mode: draft 802.11n Standard-20 MHz Channel mode with combiner:

### CH Low

Agilent 11:00:54 Aug 8, 2007

R T


Peak Power Spectral Density, a Mode Low Ch.

Mkr1 5.178 94 GHz

Ref 30 dBm

Atten 30 dB

1.704 dBm



Center 5.180 00 GHz

Span 26.57 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

12.26 dBm / 17.7100 MHz

-60.22 dBm/Hz



### CH Mid

Agilent 11:06:32 Aug 8, 2007

R T


Peak Power Spectral Density, a Mode Mid Ch.

Mkr1 5.263 59 GHz

Ref 30 dBm

Atten 30 dB

1.293 dBm



Center 5.260 00 GHz

Span 26.57 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

10.44 dBm / 17.7100 MHz

-62.05 dBm/Hz

### CH High

Agilent 11:10:09 Aug 8, 2007

R T


Peak Power Spectral Density, a Mode High Ch.

Mkr1 5.322 25 GHz

Ref 30 dBm

Atten 30 dB

2.923 dBm



Center 5.320 00 GHz

Span 26.52 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

11.84 dBm / 17.6800 MHz

-60.63 dBm/Hz





**Test mode: draft 802.11n Wide-40 MHz Channel mode with combiner:**

**CH Low**

Agilent 10:43:16 Aug 8, 2007

R T


Peak Power Spectral Density, a Mode Low Ch.

Mkr1 5.180 08 GHz

Ref 30 dBm

Atten 30 dB

-2.418 dBm



Center 5.190 00 GHz

Span 53.62 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

8.92 dBm / 35.7500 MHz

-66.62 dBm/Hz

**CH Mid**

Agilent 10:34:56 Aug 8, 2007

R T


Peak Power Spectral Density, a Mode Mid Ch.

Mkr1 5.261 11 GHz

Ref 30 dBm

Atten 30 dB

7.281 dBm



Center 5.270 00 GHz

Span 53.85 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

18.01 dBm / 35.9000 MHz

-57.54 dBm/Hz



### CH High

Agilent 10:39:48 Aug 8, 2007

R T

Peak Power Spectral Density, a Mode High Ch.

Mkr1 5.320 00 GHz

Ref 30 dBm

Atten 30 dB

0.490 dBm

#Samp

Log

10

dB/

Offst

15.4

dB

DI

11.0

dBm

#PAvg

68

V1 S2

Center 5.310 00 GHz

#VBW 3 MHz

Span 53.59 MHz

#Res BW 1 MHz


Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

10.20 dBm / 35.7300 MHz

-65.33 dBm/Hz






## 7.5 PEAK EXCURSION

### LIMIT

According to §15.407(a)(6), the ratio of the peak excursion of the modulation envelope (measured using a peak hold function) to the maximum conducted output power (measured as specified above) shall not exceed 13 dB across any 1 MHz bandwidth or the emission bandwidth whichever is less.

### Test Configuration



### TEST PROCEDURE

The test is performed in accordance with <FCC Public Notice: APPENDIX A Guidelines for Assessing Unlicensed National Information Infrastructure (U-NII) Devices> – Part 15, Subpart E, August 2002.

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to spectrum.
3. Trace A, Set RBW = 1MHz, VBW = 3MHz, Span >26dB bandwidth, Max. hold.
4. Delta Mark trace A Maximum frequency and trace B same frequency.
5. Repeat the above procedure until measurements for all frequencies were complete.

### TEST RESULTS

*No non-compliance noted*



**Test Data**

**Test mode: IEEE 802.11a mode**

Channel	Frequency (MHz)	Peak Excursion (dB)	Limit (dB)	Margin (dB)	Result
Low	5180	10.12	13.00	-2.88	PASS
Mid	5260	8.75	13.00	-4.25	PASS
High	5320	9.69	13.00	-3.31	PASS

**Test mode: draft 802.11n Standard-20 MHz Channel mode / Chain 0**

Channel	Frequency (MHz)	Peak Excursion (dB)	Limit (dB)	Margin (dB)	Result
Low	5180	11.97	13.00	-1.03	PASS
Mid	5260	9.25	13.00	-3.75	PASS
High	5320	12.63	13.00	-0.37	PASS

**Test mode: draft 802.11n Standard-20 MHz Channel mode / Chain 1**

Channel	Frequency (MHz)	Peak Excursion (dB)	Limit (dB)	Margin (dB)	Result
Low	5180	8.39	13.00	-4.61	PASS
Mid	5260	7.77	13.00	-5.23	PASS
High	5320	8.15	13.00	-4.85	PASS

**Test mode: draft 802.11n Wide-40 MHz Channel mode / Chain 0**

Channel	Frequency (MHz)	Peak Excursion (dB)	Limit (dB)	Margin (dB)	Result
Low	5190	11.66	13.00	-1.34	PASS
Mid	5270	12.37	13.00	-0.63	PASS
High	5310	10.12	13.00	-2.88	PASS

**Test mode: draft 802.11n Wide-40 MHz Channel mode / Chain 1**

Channel	Frequency (MHz)	Peak Excursion (dB)	Limit (dB)	Margin (dB)	Result
Low	5190	10.85	13.00	-2.15	PASS
Mid	5270	11.98	13.00	-1.02	PASS
High	5310	10.38	13.00	-2.62	PASS



### Test Plot

**Test mode: IEEE 802.11a mode:**

#### CH Low

Agilent 17:57:56 Aug 6, 2007

R T

Peak Excursion, a Mode Low Ch.

Δ Mkr1 0 Hz

Ref 30 dBm

Atten 30 dB

10.12 dB

#Peak

Log

10

dB/

Offst

11.5

dB

#PAvg

V1 V2

Center 5.180 00 GHz

Span 24.99 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 20 ms (601 pts)

Channel Power

Power Spectral Density

18.95 dBm / 16.6600 MHz

-53.27 dBm/Hz

#### CH Mid

Agilent 18:45:24 Aug 6, 2007

R T

Peak Excursion, a Mode Mid Ch.

Δ Mkr1 0 Hz

Ref 30 dBm

Atten 30 dB

8.75 dB

#Peak

Log

10

dB/

Offst

11.5

dB

#PAvg

V1 V2

Center 5.260 00 GHz

Span 24.9 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 20 ms (601 pts)

Channel Power

Power Spectral Density

17.83 dBm / 16.6000 MHz

-54.38 dBm/Hz



### CH High

Agilent 18:52:23 Aug 6, 2007

R T

Peak Excursion, a Mode High Ch.

Δ Mkr1 0 Hz

Ref 30 dBm

Atten 30 dB

9.69 dB

#Peak

Log

10

dB/

Offst

11.5

dB

#PAvg

V1 V2

Center 5.320 00 GHz

Span 24.82 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 20 ms (601 pts)

Channel Power

Power Spectral Density

17.09 dBm / 16.5500 MHz

-55.09 dBm/Hz

### Test mode: draft 802.11n Standard-20 MHz Channel mode / Chain 0:

### CH Low

Agilent 14:38:48 Aug 7, 2007

R T

Peak Excursion, a Mode Low Ch.

Δ Mkr1 0 Hz

Ref 30 dBm

Atten 30 dB

11.97 dB

#Peak

Log

10

dB/

Offst

11.5

dB

#PAvg

V1 V2

Center 5.180 00 GHz

Span 26.7 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 20 ms (601 pts)

Channel Power

Power Spectral Density

16.68 dBm / 17.8000 MHz

-55.82 dBm/Hz



### CH Mid

Agilent 14:44:27 Aug 7, 2007

R T


Peak Excursion, a Mode Mid Ch.

Δ Mkr1 0 Hz

Ref 30 dBm

Atten 30 dB

9.25 dB



Center 5.260 00 GHz

Span 26.59 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 20 ms (601 pts)

Channel Power

Power Spectral Density

16.79 dBm / 17.7300 MHz

-55.70 dBm/Hz

### CH High

Agilent 14:48:04 Aug 7, 2007

R T


Peak Excursion, a Mode High Ch.

Δ Mkr1 0 Hz

Ref 30 dBm

Atten 30 dB

12.63 dB



Center 5.320 00 GHz

Span 26.62 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 20 ms (601 pts)

Channel Power

Power Spectral Density

16.92 dBm / 17.7500 MHz

-55.57 dBm/Hz



**Test mode: draft 802.11n Standard-20 MHz Channel mode / Chain 1:**

**CH Low**

Agilent 19:07:21 Aug 7, 2007

R L


Peak Excursion, a Mode Low Ch.

Δ Mkr1 0 Hz

Ref 30 dBm

Atten 30 dB

8.39 dB



Center 5.180 00 GHz

Span 25.05 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 20 ms (601 pts)

Channel Power

Power Spectral Density

19.81 dBm / 16.7000 MHz

-52.41 dBm/Hz

**CH Mid**

Agilent 19:16:31 Aug 7, 2007

R L


Peak Excursion, a Mode Mid Ch.

Δ Mkr1 0 Hz

Ref 30 dBm

Atten 30 dB

7.77 dB



Center 5.260 00 GHz

Span 25.35 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 20 ms (601 pts)

Channel Power

Power Spectral Density

23.67 dBm / 16.9000 MHz

-48.61 dBm/Hz





### CH High

Agilent 19:20:10 Aug 7, 2007

R L


Peak Excursion, a Mode High Ch.

Δ Mkr1 0 Hz

Ref 30 dBm

Atten 30 dB

8.15 dB



Center 5.320 00 GHz

Span 25.05 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 20 ms (601 pts)

Channel Power

Power Spectral Density

20.59 dBm / 16.7000 MHz

-51.63 dBm/Hz

### Test mode: draft 802.11n Wide-40 MHz Channel mode / Chain 0:

### CH Low

Agilent 17:55:42 Aug 7, 2007

R T


Peak Excursion, a Mode Low Ch.

Δ Mkr1 0 Hz

Ref 30 dBm

Atten 30 dB

11.66 dB



Center 5.190 00 GHz

Span 53.55 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 20 ms (601 pts)

Channel Power

Power Spectral Density

13.28 dBm / 35.7000 MHz

-62.24 dBm/Hz



### CH Mid

Agilent 20:14:54 Aug 7, 2007

R T


Peak Excursion, a Mode Mid Ch.

Δ Mkr1 0 Hz

Ref 30 dBm

Atten 30 dB

12.37 dB



Center 5.270 00 GHz

Span 54.3 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 20 ms (601 pts)

Channel Power

Power Spectral Density

22.68 dBm / 36.2000 MHz

-52.91 dBm/Hz

### CH High

Agilent 09:20:35 Aug 8, 2007

R T


Peak Excursion, a Mode High Ch.

Δ Mkr1 0 Hz

Ref 30 dBm

Atten 30 dB

10.12 dB



Center 5.310 00 GHz

Span 53.62 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 20 ms (601 pts)

Channel Power

Power Spectral Density

17.55 dBm / 35.7500 MHz

-57.98 dBm/Hz



**Test mode: draft 802.11n Wide-40 MHz Channel mode / Chain 1:**

**CH Low**

Agilent 16:26:05 Aug 7, 2007

R T


Peak Excursion, a Mode Low Ch.

Δ Mkr1 0 Hz

Ref 30 dBm

Atten 30 dB

10.85 dB



Center 5.190 00 GHz

Span 53.73 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 20 ms (601 pts)

Channel Power

Power Spectral Density

13.34 dBm / 35.8200 MHz

-62.20 dBm/Hz

**CH Mid**

Agilent 16:30:21 Aug 7, 2007

R T


Peak Excursion, a Mode Mid Ch.

Δ Mkr1 0 Hz

Ref 30 dBm

Atten 30 dB

11.98 dB



Center 5.270 00 GHz

Span 54.21 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 20 ms (601 pts)

Channel Power

Power Spectral Density

22.42 dBm / 36.1400 MHz

-53.16 dBm/Hz



### CH High

Agilent 16:34:18 Aug 7, 2007

R T

Peak Excursion, a Mode High Ch.

Δ Mkr1 0 Hz

Ref 30 dBm

Atten 30 dB

10.38 dB

#Peak

Log

10

dB/

Offst

11.5

dB

#PAvg

V1 V2

Center 5.310 00 GHz

Span 53.74 MHz

#Res BW 1 MHz

#VBW 3 MHz


Sweep 20 ms (601 pts)

Channel Power

Power Spectral Density

14.96 dBm / 35.8300 MHz

-60.58 dBm/Hz





### 7.6 RADIATED UNDESIRABLE EMISSION

1. According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ( $\mu\text{V/m}$ )	Measurement Distance (m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3


*Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.*

2. In the emission table above, the tighter limit applies at the band edges.


Frequency (MHz)	Field Strength ( $\mu\text{V/m}$ at 3-meter)	Field Strength (dB $\mu\text{V/m}$ at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

### Test Configuration

#### Below 1 GHz



#### Above 1 GHz





## **TEST PROCEDURE**

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:

Below 1GHz:

RBW=100kHz / VBW=300kHz / Sweep=AUTO

Above 1GHz:

(a) PEAK: RBW=VBW=1MHz / Sweep=AUTO

(b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO

7. Repeat above procedures until the measurements for all frequencies are complete.

**TEST RESULTS****Below 1 GHz****Operation Mode:** Normal Link**Test Date:** August 13, 2007**Temperature:** 25°C**Tested by:** Nan Tsai**Humidity:** 55% RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
167.42	V	43.13	-14.59	28.55	43.50	-14.95	Peak
240.17	V	51.64	-14.62	37.02	46.00	-8.98	Peak
264.42	V	48.01	-13.46	34.55	46.00	-11.45	Peak
377.58	V	44.06	-10.16	33.91	46.00	-12.09	Peak
477.82	V	40.21	-7.70	32.52	46.00	-13.48	Peak
678.28	V	33.76	-4.75	29.01	46.00	-16.99	Peak
167.42	H	41.26	-14.59	26.68	43.50	-16.82	Peak
240.17	H	51.21	-14.62	36.59	46.00	-9.41	Peak
264.42	H	49.84	-13.46	36.37	46.00	-9.63	Peak
288.67	H	49.07	-12.69	36.38	46.00	-9.62	Peak
379.20	H	41.73	-10.13	31.60	46.00	-14.40	Peak
532.78	H	34.24	-7.03	27.20	46.00	-18.80	Peak

**Remark:**

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using peak/quasi-peak detector mode.
3. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit or as required by the applicant.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Margin (dB) = Remark result (dBuV/m) – Quasi-peak limit (dBuV/m).





**Above 1 GHz**

**Operation Mode:** Tx / IEEE 802.11a mode / CH Low

**Test Date:** August 3, 2007

**Temperature:** 25°C

**Tested by:** Steven Young

**Humidity:** 55% RH

**Polarity:** Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
10366.67	V	44.76	38.04	14.07	58.82	52.11	74.00	54.00	-1.89	AVG
N/A										
10366.67	H	40.85	33.78	14.07	54.92	47.85	74.00	54.00	-6.15	AVG
N/A										

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: Tx / IEEE 802.11a mode / CH Mid

Test Date: August 3, 2007

Temperature: 25°C

Tested by: Steven Young

Humidity: 55% RH

Polarity: Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
10516.67	V	43.85	37.37	14.74	58.59	52.11	74.00	54.00	-1.89	AVG
N/A										
10516.67	H	40.90	34.38	14.74	55.64	49.12	74.00	54.00	-4.88	AVG
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: Tx / IEEE 802.11a mode / CH High

Test Date: August 3, 2007

Temperature: 25°C

Tested by: Steven Young

Humidity: 55% RH

Polarity: Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
10650.00	V	45.13	37.68	14.93	60.07	52.61	74.00	54.00	-1.39	AVG
N/A										
10633.33	H	39.94	33.74	14.91	54.84	48.65	74.00	54.00	-5.35	AVG
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / draft 802.11n Standard-20 MHz Channel mode / CH Low

Test Date: August 2, 2007

Temperature: 25°C

Tested by: Steven Young

Humidity: 55 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
10366.67	V	45.06	38.21	14.07	59.12	52.28	74.00	54.00	-1.72	AVG
N/A										
10366.67	H	40.26	33.21	14.07	54.33	47.28	74.00	54.00	-6.72	AVG
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / draft 802.11n Standard-20 MHz Channel mode / CH Mid

Test Date: August 2, 2007

Temperature: 25°C

Tested by: Steven Young

Humidity: 55 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
10516.67	V	50.93	38.02	14.74	65.67	52.76	74.00	54.00	-1.24	AVG
N/A										
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / draft 802.11n Standard-20 MHz Channel mode / CH High

Test Date: August 2, 2007

Temperature: 25°C

Tested by: Steven Young

Humidity: 55 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
10650.00	V	48.46	37.56	14.93	63.40	52.49	74.00	54.00	-2.51	AVG
N/A										
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / draft 802.11n Wide-40 MHz Channel mode / CH Low

Test Date: August 2, 2007

Temperature: 25°C

Tested by: Steven Young

Humidity: 55 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
10383.33	V	41.75	34.20	14.15	55.90	48.35	74.00	54.00	-5.65	AVG
N/A										
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / draft 802.11n Wide-40 MHz Channel mode / CH Mid

Test Date: August 2, 2007

Temperature: 25°C

Tested by: Steven Young

Humidity: 55 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
10533.33	V	45.68	36.70	14.76	60.44	51.46	74.00	54.00	-2.54	AVG
N/A										
10533.33	H	41.44	33.80	14.76	56.20	48.56	74.00	54.00	-5.44	AVG
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).





**Operation Mode:** TX / draft 802.11n Wide-40 MHz Channel mode / CH High **Test Date:** August 2, 2007  
**Temperature:** 25°C **Tested by:** Steven Young  
**Humidity:** 55 % RH **Polarity:** Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
10616.67	V	42.62	35.29	14.88	57.51	50.17	74.00	54.00	-3.83	AVG
N/A										
N/A										

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

## 7.7 CONDUCTED UNDESIRABLE EMISSION


### LIMIT

According to 15.407(b),

- (1) For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5.25-5.35 GHz band that generate emissions in the 5.15-5.25 GHz band must meet all applicable technical requirements for operation in the 5.15-5.25 GHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5.15-5.25 GHz band.

The provisions of §15.205 apply to intentional radiators operating under this section.

### Test Configuration



### TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 1 MHz. The video bandwidth is set to 1 MHz. Peak detection measurements are compared to the average EIRP limit, adjusted for the maximum antenna gain. If necessary, additional average detection measurements are made.

Measurements are made over the 30 MHz to 40 GHz range with the transmitter set to the lowest, middle, and highest channels.

### TEST RESULTS

*No non-compliance noted*



**Test Plot**

**Test mode: IEEE 802.11a mode:**

**CH Low**


**30MHz ~ 40GHz**

Agilent 18:38:53 Aug 6, 2007

R T

Conducted Spur., a Mode Low Ch.

Mkr2 10.36 GHz  
-38.49 dBm



**CH Mid**


**30MHz ~ 40GHz**

Agilent 18:55:30 Aug 6, 2007

R T

Conducted Spur., a Mode Mid Ch.

Mkr2 10.52 GHz  
-35.43 dBm





### CH High 30MHz ~ 40GHz

Agilent 18:53:05 Aug 6, 2007

R T


Conducted Spur., a Mode High Ch.

Mkr2 10.64 GHz

Ref 20 dBm

Atten 20 dB

-39.29 dBm



Center 20.02 GHz

Span 39.97 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 199.9 ms (2001 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	5.33 GHz	6.65 dBm
2	(1)	Freq	10.64 GHz	-39.29 dBm

### Test mode: draft 802.11n Standard-20 MHz Channel mode / Chain 0:

### CH Low 30MHz ~ 40GHz

Agilent 14:41:05 Aug 7, 2007

R T


Conducted Spur., a Mode Low Ch.

Mkr2 10.36 GHz

Ref 20 dBm

Atten 20 dB

-38.19 dBm



Center 20.02 GHz

Span 39.97 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 199.9 ms (2001 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	5.19 GHz	6.13 dBm
2	(1)	Freq	10.36 GHz	-38.19 dBm



### CH Mid 30MHz ~ 40GHz

Agilent 14:45:07 Aug 7, 2007


R T

Conducted Spur., a Mode Mid Ch.

Mkr2 10.52 GHz  
-36.08 dBm

Ref 20 dBm

Atten 20 dB



Center 20.02 GHz

Span 39.97 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 199.9 ms (2001 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	5.25 GHz	5.99 dBm
2	(1)	Freq	10.52 GHz	-36.08 dBm

### CH High 30MHz ~ 40GHz

Agilent 14:49:07 Aug 7, 2007


R T

Conducted Spur., a Mode High Ch.

Mkr2 10.64 GHz  
-36.71 dBm

Ref 20 dBm

Atten 20 dB



Center 20.02 GHz

Span 39.97 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 199.9 ms (2001 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	5.33 GHz	6.25 dBm
2	(1)	Freq	10.64 GHz	-36.71 dBm



**Test mode: draft 802.11n Standard-20 MHz Channel mode / Chain 1:**

**CH Low**

**30MHz ~ 40GHz**

Agilent 19:09:29 Aug 7, 2007

R L


Conducted Spur., a Mode Low Ch.

Mkr1 5.19 GHz

Ref 20 dBm

Atten 20 dB

8.67 dBm



Center 20.02 GHz

Span 39.97 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 100 ms (2001 pts)

**CH Mid**

**30MHz ~ 40GHz**

Agilent 19:17:06 Aug 7, 2007

L


Conducted Spur., a Mode Mid Ch.

Mkr1 5.27 GHz

Ref 20 dBm

Atten 20 dB

12.51 dBm



Center 20.02 GHz

Span 39.97 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 100 ms (2001 pts)



### CH High 30MHz ~ 40GHz

Agilent 19:20:44 Aug 7, 2007

R L


Conducted Spur., a Mode High Ch.

Mkr1 5.33 GHz

Ref 20 dBm

Atten 20 dB

9.58 dBm



Center 20.02 GHz

Span 39.97 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 100 ms (2001 pts)

**Test mode: draft 802.11n Wide-40 MHz Channel mode / Chain 0:**

### CH Low 30MHz ~ 40GHz

Agilent 17:56:16 Aug 7, 2007

R T


Conducted Spur., a Mode Low Ch.

Mkr1 5.21 GHz

Ref 20 dBm

Atten 20 dB

0.60 dBm



Center 20.02 GHz

Span 39.97 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 199.9 ms (2001 pts)



### CH Mid

#### 30MHz ~ 40GHz

Agilent 20:15:34 Aug 7, 2007


R T

Conducted Spur., a Mode Mid Ch.

Mkr2 10.54 GHz  
-35.35 dBm

Ref 20 dBm

Atten 20 dB



Center 20.02 GHz

Span 39.97 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 199.9 ms (2001 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	5.29 GHz	10.24 dBm
2	(1)	Freq	10.54 GHz	-35.35 dBm

### CH High

#### 30MHz ~ 40GHz

Agilent 09:21:12 Aug 8, 2007


R T

Conducted Spur., a Mode High Ch.

Mkr2 10.62 GHz  
-37.93 dBm

Ref 20 dBm

Atten 20 dB



Center 20.02 GHz

Span 39.97 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 199.9 ms (2001 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	5.33 GHz	4.74 dBm
2	(1)	Freq	10.62 GHz	-37.93 dBm





**Test mode: draft 802.11n Wide-40 MHz Channel mode / Chain 1:**

**CH Low**

**30MHz ~ 40GHz**

Agilent 16:26:38 Aug 7, 2007

R T


Conducted Spur., a Mode Low Ch.

Mkr1 5.21 GHz

Ref 20 dBm

Atten 20 dB

1.13 dBm



Center 20.02 GHz

Span 39.97 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 199.9 ms (2001 pts)

**CH Mid**

**30MHz ~ 40GHz**

Agilent 16:31:12 Aug 7, 2007

R T


Conducted Spur., a Mode Mid Ch.

Mkr2 10.54 GHz

Ref 20 dBm

Atten 20 dB

-39.30 dBm



Center 20.02 GHz

Span 39.97 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 199.9 ms (2001 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	5.29 GHz	10.22 dBm
2	(1)	Freq	10.54 GHz	-39.30 dBm



### CH High 30MHz ~ 40GHz

Agilent 16:34:58 Aug 7, 2007

R T


Conducted Spur., a Mode High Ch.

Mkr1 5.33 GHz

Ref 20 dBm

Atten 20 dB

3.40 dBm



Center 20.02 GHz

Span 39.97 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 199.9 ms (2001 pts)

### Test mode: draft 802.11n Standard-20 MHz Channel mode with combiner:

### CH Low

### 30MHz ~ 40GHz

Agilent 11:03:15 Aug 8, 2007

R T

Conducted Spur., a Mode Low Ch.

Mkr2 10.34 GHz

Ref 19.4 dBm

#Atten 14 dB

-37.07 dBm



Center 20.02 GHz

Span 39.97 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 199.9 ms (2001 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	5.19 GHz	7.57 dBm
2	(1)	Freq	10.34 GHz	-37.07 dBm

Display

Full Screen

Display Line

-27.00 dBm

On

Off

Limits

Active Fctn

Position

Bottom

Title

Preferences



### CH Mid 30MHz ~ 40GHz

Agilent 11:07:41 Aug 8, 2007

R T


Conducted Spur., a Mode Mid Ch.

Mkr2 10.52 GHz

Ref 19.4 dBm

#Atten 14 dB

-38.61 dBm



Center 20.02 GHz

Span 39.97 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 199.9 ms (2001 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	5.27 GHz	6.68 dBm
2	(1)	Freq	10.52 GHz	-38.61 dBm

### CH High 30MHz ~ 40GHz

Agilent 11:11:20 Aug 8, 2007

R T


Conducted Spur., a Mode High Ch.

Mkr2 10.64 GHz

Ref 17.4 dBm

#Atten 14 dB

-38.29 dBm



Center 20.02 GHz

Span 39.97 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 199.9 ms (2001 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	5.31 GHz	7.46 dBm
2	(1)	Freq	10.64 GHz	-38.29 dBm



**Test mode: draft 802.11n Wide-40 MHz Channel mode with combiner:**

**CH Low**

**30MHz ~ 40GHz**

Agilent 10:44:34 Aug 8, 2007

R T


Conducted Spur., a Mode Low Ch.

Mkr2 10.38 GHz

Ref 19.4 dBm

#Atten 14 dB

-39.44 dBm



Center 20.02 GHz

Span 39.97 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 199.9 ms (2001 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	5.19 GHz	4.09 dBm
2	(1)	Freq	10.38 GHz	-39.44 dBm

**CH Mid**

**30MHz ~ 40GHz**

Agilent 10:37:32 Aug 8, 2007

R T


Conducted Spur., a Mode Mid Ch.

Mkr1 5.25 GHz

Ref 17.4 dBm

#Atten 14 dB

12.67 dBm



Center 20.02 GHz

Span 39.97 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 199.9 ms (2001 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	5.25 GHz	12.67 dBm
2	(1)	Freq	10.54 GHz	-30.85 dBm



### CH High 30MHz ~ 40GHz

Agilent 10:40:57 Aug 8, 2007

R T

Conducted Spur., a Mode High Ch.

Mkr2 10.62 GHz

Ref 19.4 dBm

#Atten 14 dB

-40.31 dBm

#Peak

Log

10

dB/

Offst

15.4

dB

DI

-27.0

dBm

LgAv

V1 S2

Center 20.02 GHz

Span 39.97 GHz

#Res BW 1 MHz

#VBW 1 MHz

Sweep 199.9 ms (2001 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	5.33 GHz	5.32 dBm
2	(1)	Freq	10.62 GHz	-40.31 dBm



## 7.8 POWERLINE CONDUCTED EMISSIONS

### LIMIT

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dB $\mu$ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

\* Decreases with the logarithm of the frequency.

### TEST CONFIGURATION

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

### TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.



**TEST RESULTS**

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

**Test Data**

**Operation Mode:** Normal Link                      **Test Date:** August 13, 2007  
**Temperature:** 25°C                                      **Tested by:** Eddy Chung  
**Humidity:** 55% RH

Freq. (MHz)	QP Reading (dBuV)	AV Reading (dBuV)	Corr. factor (dB)	QP Result (dBuV)	AV Result (dBuV)	QP Limit (dBuV)	AV Limit (dBuV)	QP Margin (dB)	AV Margin (dB)	Note
0.152	49.100	42.380	0.153	49.253	42.533	65.890	55.890	-16.637	-13.357	L1
0.223	40.170	33.580	0.102	40.272	33.682	62.706	52.706	-22.435	-19.025	L1
0.458	33.770	25.580	0.015	33.785	25.595	56.729	46.729	-22.943	-21.133	L1
4.505	30.710	27.630	0.085	30.795	27.715	56.000	46.000	-25.205	-18.285	L1
10.824	34.330	31.490	0.319	34.649	31.809	60.000	50.000	-25.351	-18.191	L1
18.609	37.220	32.630	0.470	37.690	33.100	60.000	50.000	-22.310	-16.900	L1
0.154	46.840	40.410	0.151	46.991	40.561	65.781	55.781	-18.790	-15.220	L2
0.375	37.820	30.460	0.046	37.866	30.506	58.389	48.389	-20.524	-17.884	L2
0.512	36.530	26.590	0.000	36.530	26.590	56.000	46.000	-19.470	-19.410	L2
0.984	34.170	26.930	0.000	34.170	26.930	56.000	46.000	-21.830	-19.070	L2
4.329	32.130	29.070	0.080	32.210	29.150	56.000	46.000	-23.790	-16.850	L2
18.908	37.200	34.420	0.475	37.675	34.895	60.000	50.000	-22.325	-15.105	L2


**Remark:**

1. Measuring frequencies from 0.15 MHz to 30MHz.
2. The emissions measured in frequency range from 0.15 MHz to 30MHz were made with an instrument using Quasi-peak detector and average detector.
3. The IF bandwidth of SPA between 0.15MHz to 30MHz was 10kHz; the IF bandwidth of Test Receiver between 0.15MHz to 30MHz was 9kHz;
4. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)




### Test Plots

#### Conducted emissions (Line 1)



#### Conducted emissions (Line 2)







## **7.9 TRANSMISSION IN ABSENCE OF DATA**

### **LIMIT**

According to §15.319(f), the device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude transmission of control and signaling information or use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

Applicants shall include in their application for equipment authorization a description of how this requirement is met.

### **TEST RESULTS**

*Please refer to the operational description for details.*

**Remark:** *For the details, please refer to the operational description.*

## **7.10 FREQUENCY STABILITY**

### **LIMIT**

According to §15.407(g), manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the operational description.

### **TEST RESULTS**

*Please refer to the operational description for further details.*

**Remark:** *An examination of the band-edge plots shows that the emission will stay within the authorized band over the entire temperature range.*



## 7.11 DYNAMIC FREQUENCY SELECTION

### LIMIT

According to §15.407 (h) and FCC 06-96 appendix “compliance measurement procedures for unlicensed-national information infrastructure devices operating in the 5250-5350 MHz and 5470-5725 MHz bands incorporating dynamic frequency selection”.

**Table 1: Applicability of DFS requirements prior to use of a channel**

Requirement	Operational Mode		
	Master	Client (without radar detection)	Client(with radar detection)
Non-Occupancy Period	Yes	Not required	Yes
DFS Detection Threshold	Yes	Not required	Yes
Channel Availability Check Time	Yes	Not required	Not required
Uniform Spreading	Yes	Not required	Not required

**Table 2: Applicability of DFS requirements during normal operation**

Requirement	Operational Mode		
	Master	Client (without radar detection)	Client(with radar detection)
DFS Detection Threshold	Yes	Not required	Yes
Channel Closing Transmission Time	Yes	Yes	Yes
Channel Move Time	Yes	Yes	Yes

**Table 3: Interference Threshold values, Master or Client incorporating In-Service**

Maximum Transmit Power	Value (see note)
≥200 Milliwatt	-64 dBm
< 200 Milliwatt	-62 dBm

Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna.

Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.



**Table 4: DFS Response requirement values**

Parameter	Value
Non-occupancy period	30 minutes
Channel Availability Check Time	60 seconds
Channel Move Time	10 seconds
Channel Closing Transmission Time	200 milliseconds + approx. 60 milliseconds over remaining 10 second period

The instant that the Channel Move Time and the Channel Closing Transmission Time begins is as follows:

- For the Short pulse radar Test Signals this instant is the end of the Burst.
- For the Frequency Hopping radar Test Signal, this instant is the end of the last radar burst generated.
- For the Long Pulse radar Test Signal this instant is the end of the 12 second period defining the radar transmission.

The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate channel changes (an aggregate of approximately 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

**Table 5 – Short Pulse Radar Test Waveforms**

Radar Type	Pulse Width (Microseconds)	PRI (Microseconds)	Pulses	Minimum Percentage of Successful Detection	Minimum Trials
1	1	1428	18	60%	30
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120

**Table 6 – Long Pulse Radar Test Signal**

Radar Waveform	Bursts	Pulses per Burst	Pulse Width (µsec)	Chirp Width (µsec)	PRI (µsec)	Minimum Percentage of Successful Detection	Minimum Trials
5	8-20	1-3	50-100	5-20	1000-2000	80%	30

**Table 7 – Frequency Hopping Radar Test Signal**

Radar Waveform	Pulse Width (µsec)	PRI (µsec)	Burst Length (ms)	Pulses Per Hop	Hopping Rate (kHz)	Minimum Percentage of Successful Detection	Minimum Trials
6	1	333	300	9	0.33	70%	30



## **DESCRIPTION OF EUT**

### **Overview Of EUT With Respect To §15.407 (H) Requirements**

The firmware installed in the EUT during testing was:

Firmware Rev: 11.1.0.86

The EUT operates over the 5250-5350 MHz range as a Client Device that does not have radar detection capability.

The antenna assembly utilized with the EUT has a gain of 0.26 dBi.

The highest power level is 19.23 dBm EIRP in the 5250-5350 MHz band.

The EUT uses one transmitter connected to two 50-ohm coaxial antenna ports via a diversity switch. Only one antenna port is connected to the test system since the EUT has one antenna only.

The Slave device associated with the EUT during these tests does not have radar detection capability.

WLAN traffic is generated by streaming the video file TestFile.mp2 “6 ½ Magic Hours” from the Master to the Slave in full motion video mode using the media player with the V2.61 Codec package.

TPC is not required since the maximum EIRP is less than 500 mW (27 dBm).

The EUT utilizes the 802.11a architecture, with a nominal channel bandwidth of 20 MHz.

The Master Device is a Cisco Aironet 802.11a/b/g Access Point, FCC ID: LDK102056.

The rated output power of the Master unit is < 23dBm (EIRP). Therefore the required interference threshold level is -62 dBm. After correction for antenna gain and procedural adjustments, the required conducted threshold at the antenna port is  $-62 + 5 = -57$ dBm.

The calibrated conducted DFS Detection Threshold level is set to -62 dBm. The tested level is lower than the required level hence it provides margin to the limit.

### **Manufacturer’s Statement Regarding Uniform Channel Spreading**

The end product implements an automatic channel selection feature at startup such that operation commences on channels distributed across the entire set of allowed 5GHz channels. This feature will ensure uniform spreading is achieved while avoiding non-allowed channels due to prior radar events.

## **TEST AND MEASUREMENT SYSTEM**

### **System Overview**

The measurement system is based on a conducted test method.

The short pulse and long pulse signal generating system utilizes the NTIA software. The Vector Signal Generator has been validated by the NTIA. The hopping signal generating system utilizes the CCS simulated hopping method and system, which has been validated by the DoD, FCC and NTIA. The software selects waveform parameters from within the bounds of the signal type on a random basis using uniform distribution.


The short pulse types 2, 3 and 4, and the long pulse type 5 parameters are randomized at run-time.

The hopping type 6 pulse parameters are fixed while the hopping sequence is based on the August 2005 NTIA Hopping Frequency List. The initial starting point randomized at run-time and each subsequent starting point is incremented by 475. Each frequency in the 100-length segment is compared to the boundaries of the EUT Detection Bandwidth and the software creates a hopping burst pattern in accordance with Section 7.4.1.3 Method #2 Simulated Frequency Hopping Radar Waveform Generating Subsystem of FCC 06-96 APPENDIX. The frequency of the signal generator is incremented in 1 MHz steps from FL to FH for each successive trial. This incremental sequence is repeated as required to generate a minimum of 30 total trials and to maintain a uniform frequency distribution over the entire Detection Bandwidth.

The signal monitoring equipment consists of a spectrum analyzer set to display 8001 bins on the horizontal axis. The time-domain resolution is 2 msec / bin with a 16 second sweep time, meeting the 10 second short pulse reporting criteria. The aggregate ON time is calculated by multiplying the number of bins above a threshold during a particular observation period by the dwell time per bin, with the analyzer set to peak detection and max hold. The time-domain resolution is 3 msec / bin with a 24 second sweep time, meeting the 22 second long pulse reporting criteria and allowing a minimum of 10 seconds after the end of the long pulse waveform.

Should multiple RF ports be utilized for the Master and/or Slave devices (for example, for diversity or MIMO implementations), 50 ohm termination would be removed from the splitter so that connection can be established between splitter and the Master and/or Slave devices.

### **Conducted Method System Block Diagram**





### **System Calibration**

Connect the spectrum analyzer to the test system in place of the master device. Set the signal generator to CW mode. Adjust the amplitude of the signal generator to yield a measured level of  $-62$  dBm on the spectrum analyzer.

Without changing any of the instrument settings, reconnect the spectrum analyzer to the Common port of the Spectrum Analyzer Combiner/Divider and connect a 50 ohm load to the Master Device port of the test system.

Measure the amplitude and calculate the difference from  $-62$  dBm. Adjust the Reference Level Offset of the spectrum analyzer to this difference. Confirm that the signal is displayed at  $-62$  dBm. Readjust the RBW and VBW to 3 MHz, set the span to 10 MHz, and confirm that the signal is still displayed at  $-62$  dBm.

The spectrum analyzer displays the level of the signal generator as received at the antenna ports of the Master Device. The interference detection threshold may be varied from the calibrated value of  $-62$  dBm and the spectrum analyzer will still indicate the level as received by the Master Device.

Set the signal generator to produce a radar waveform, trigger a burst manually and measure the level on the spectrum analyzer. Readjust the amplitude of the signal generator as required so that the peak level of the waveform is at a displayed level equal to the required or desired interference detection threshold. Separate signal generator amplitude settings are determined as required for each radar type.


### **Adjustment Of Displayed Traffic Level**

Establish a link between the Master and Slave, adjusting the Link Step Attenuator as needed to provide a suitable received level at the Master and Slave devices. Stream the video test file to generate WLAN traffic. Confirm that the WLAN traffic level, as displayed on the spectrum analyzer, is at lower amplitude than the radar detection threshold. Confirm that the displayed traffic is from the Master Device. For Master Device testing confirm that the displayed traffic does not include Slave Device traffic. For Slave Device testing confirm that the displayed traffic does not include Master Device traffic.

If a different setting of the Master Step Attenuator is required to meet the above conditions, perform a new System Calibration for the new Master Step Attenuator setting.



**Test Setup**



**TEST RESULTS**


*No non-compliance noted*




**Test Plot**

**PLOTS OF RADAR WAVEFORMS**

**Sample of Short Pulse Radar Type 1**




**Sample of Short Pulse Radar Type 2**








### Sample of Short Pulse Radar Type 3




### Sample of Short Pulse Radar Type 4






### Sample of Long Pulse Radar Type 5



### Sample of Frequency Hopping Radar Type 6





## **TEST CHANNEL AND METHOD**

All tests were performed at a channel center frequency of 5300 MHz utilizing a conducted test method.

## **CHANNEL MOVE TIME AND CHANNEL CLOSING TRANSMISSION TIME**

### **GENERAL REPORTING NOTES**

The reference marker is set at the end of last radar pulse.

The delta marker is set at the end of the last WLAN transmission following the radar pulse. This delta is the channel move time.

The aggregate channel closing transmission time is calculated as follows:

Aggregate Transmission Time =

(Number of analyzer bins showing transmission) \* (dwell time per bin)

The observation period over which the aggregate time is calculated

Begins at (Reference Marker + 200 msec) and


Ends no earlier than (Reference Marker + 10 sec).



### Type 1 Channel Move Time Results

No non-compliance noted.

Channel Move Time (s)	Limit (s)
0.428	10







### Type 1 Channel Closing Transmission Time Results

No non-compliance noted.


Aggregate Transmission Time (ms)	Limit (ms)	Margin (ms)
8	60	-52





### Type 5 Channel Move Time Results

No non-compliance noted: The traffic ceases prior to the end of the radar waveform, therefore it also ceases prior to 10 seconds after the end of the radar waveform.





## APPENDIX I RADIO FREQUENCY EXPOSURE

### LIMIT

According to §15.407(f), U-NII devices are subject to the radio frequency radiation exposure requirements specified in §§ 1.1307(b), 2.1091 and 2.1093 of this chapter, as appropriate. All equipment shall be considered to operate in a "general population/uncontrolled" environment. Applications for equipment authorization of devices operating under this section must contain a statement confirming compliance with these requirements for both fundamental emissions and unwanted emissions. Technical information showing the basis for this statement must be submitted to the Commission upon request.

### EUT Specification

<b>EUT</b>	Notebook PC
<b>Frequency band (Operating)</b>	<input type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input checked="" type="checkbox"/> WLAN: 5.15GHz ~ 5.35GHz <input type="checkbox"/> WLAN: 5.725GHz ~ 5.850GHz <input type="checkbox"/> Bluetooth: 2.402 GHz ~ 2.482 GHz <input type="checkbox"/> Others: _____
<b>Device category</b>	<input checked="" type="checkbox"/> Portable (<20cm separation) <input type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others: _____
<b>Exposure classification</b>	General Population/Uncontrolled exposure ( $S=1mW/cm^2$ )
<b>Antenna diversity</b>	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input checked="" type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	IEEE 802.11a mode: 14.63 dBm (29.04mW) draft 802.11n Standard-20 MHz Channel mode: 17.94 dBm (62.23mW) draft 802.11n Wide-40 MHz Channel mode: 19.23 dBm (83.75mW)
<b>Antenna gain (Max)</b>	0.26 dBi (Numeric gain: 1.06)
<b>Evaluation applied</b>	<input type="checkbox"/> MPE Evaluation <input checked="" type="checkbox"/> SAR Evaluation* <input type="checkbox"/> N/A
<b>Remark:</b>	
<ol style="list-style-type: none"> <li>The maximum output power is <u>19.23dBm (83.75mW) at 5270MHz (with 1.06 numeric antenna gain.)</u></li> <li>For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is <math>1.0 mW/cm^2</math> even if the calculation indicates that the power density would be larger.</li> </ol>	

### TEST RESULTS

No non-compliance noted.

**Remark:** Please refer to the separated SAR report.