



**CONFORMANCE TEST REPORT
FOR
FCC 47 CFR, Part 15 Subpart C**

Report No.: ET93S-09-208-04

Client: Fellowes Inc.
 Product: Earglove Bluetooth Adapter
 Model: Earglove BT Adapter
 FCC ID: IDHBTHS02
 Manufacturer/supplier: Antonio Precise Products Manufactory Ltd.

Date test item received: 2004/09/02

Date test campaign completed: 2004/09/22

Date of issue: 2004/11/02

The test result only corresponds to the tested sample. It is not permitted to copy this report, in part or in full, without the permission of the test laboratory.

Total number of pages of this test report: 71 pages

Total number of pages of photos: External photos 1 pages

Internal photos 7 pages

Setup photos 2 pages

Test Engineer	Checked By	Approved By
<i>Mark</i> Mark	<i>Joe Hsieh</i> Joe Hsieh	<i>Tsung-ching Lin</i> Tsung-Ching Lin

ELECTRONICS TESTING CENTER, TAIWAN
 NO.8, LANE 29, WEN-MING RD.,
 LO-SHAN TSUN, KUI-SHAN HSIANG,
 TAOYUAN HSIEN 333
 TAIWAN, R.O.C.

TEL: (03) 3276170~4
 INT: +886-3-3276170~4
 FAX: (03) 3276188
 INT: +886-3-3276188



TEST REPORT CERTIFICATION

Client : Fellowes Inc.
Address : 1789 Norwood Avenue, Itasca, Illinois 60143-1095, USA
Manufacturer : Antonio Precise Products Manufactory Ltd.
Address : 3/F, Photonics Centre, No. 2 Science Park East Avenue, Hong Kong Science Park, Shatin, N.T. Hong Kong
EUT : Earglove Bluetooth Adapter
Trade name : Earglove Bluetooth Adapter
Model No. : Earglove BT Adapter
Power Source : Adapter Model No.: SA106A-0512-6
: Input: 100-240Vac, 50-60Hz, 250mA
Output: DC 5.5Vdc, 0.5A, 2.75W
Regulations applied : FCC 47 CFR, Part 15 Subpart C (2003)

The testing described in this report has been carried out to the best of our knowledge and ability, and our responsibility is limited to the exercise of reasonable care. This certification is not intended to relieve the sellers from their legal and/or contractual obligations.

The compliance test is only certified for the test equipment and the results of the testing report relate only to the item tested. The compliance test of this report was conducted in accordance with the appropriate standards. It's not intention to assure the quality and performance of the product. This report shall not be reproduced except in full, without the approval of ETC. This report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

Laboratory Introduction: Electronics Testing Center, Taiwan is recognized, filed and mutual recognition arrangement as following:

- ① ISO9001: TÜV Product Service
- ② ISO/IEC 17025: BSMI, CNLA, DGT, NVLAP, CCIBLAC, UL, Compliance
- ③ Filing: FCC, Industry Canada, VCCI
- ④ MRA: Australia, Hong Kong, New Zealand, Singapore, USA, Japan, Korea, China, APLAC through CNLA



NVLAP Lab Code 200133-0

Table of Contents	Page
1 GENERAL INFORMATION	5
1.1 Product Description.....	5
1.2 Characteristics of Device	5
1.3 Test Methodology	5
1.4 Modifiction List of EUT	5
1.5 Test Facility.....	5
2 PROVISIONS APPLICABLE	6
2.1 Definition	6
2.2 Requirement for Compliance	7
2.3 Restricted Bands of Operation	9
2.4 Labeling Requirement	9
2.5 User Information	10
3. SYSTEM TEST CONFIGURATION	11
3.1 Justification	11
3.2 Devices for Tested System.....	11
4 RADIATED EMISSION MEASUREMENT	12
4.1 Applicable Standard	12
4.2 Measurement Procedure.....	12
4.3 Measuring Instrument	14
4.4 Radiated Emission Data	15
4.4.1 RF Portion.....	15
4.4.2 Other Emission	18
4.4.3 Radiated Measurement at Bandedge with Fundamental Frequencies.....	25
4.5 Field Strength Calculation.....	25
5 CONDUCTED EMISSION MEASUREMENT	26
5.1 Standard Applicable	26
5.2 Measurement Procedure.....	26
5.3 Conducted Emission Data	27
5.4 Result Data Calculation.....	34
5.5 Conducted Measurement Equipment	34
6 ANTENNA REQUIREMENT	35
6.1 Standard Applicable	35
6.2 Antenna Construction and Directional Gain	35
7 20dB EMISSION BANDWIDTH MEASUREMENT	36

7.1 Standard Applicable	36
7.2 Measurement Procedure	36
7.3 Measurement Equipment	36
7.4 Measurement Data.....	37
8 OUTPUT POWER MEASUREMENT	41
8.1 Standard Applicable	41
8.2 Measurement Procedure.....	41
8.3 Measurement Equipment	41
8.4 Measurement Data.....	42
9 OUT-OF-BAND RF CONDUCTED SPURIOUS EMISSION MEASUREMENT.....	46
9.1 Standard Applicable	46
9.2 Measurement Procedure.....	46
9.3 Measurement Equipment	46
9.4 Measurement Data.....	47
10 NUMBER OF HOPPING CHANNELS	53
10.1 Standard Applicable	53
10.2 Measurement Procedure.....	53
10.3 Measurement Equipment	53
10.4 Measurement Data.....	53
11 HOPPING CHANNEL CARRIER FREQUENCY SEPARATED	55
11.1 Standard Applicable	55
11.2 Measurement Procedure.....	55
11.3 Measurement Equipment	55
11.4 Measurement Data.....	56
12 POWER SPECTRAL DENSITY.....	60
12.1 Standard Applicable	60
12.2 Measurement Procedure.....	60
12.3 Measurement Equipment	60
12.4 Measurement Data.....	61
13 DWELL TIME.....	65
13.1 Standard Applicable	65
13.2 Measurement Procedure.....	65
13.3 Measurement Equipment	65
13.4 Measurement Data.....	65

1 GENERAL INFORMATION

1.1 Product Description

- a) Type of EUT : Earglove Bluetooth Adapter
- b) Trade Name : Earglove Bluetooth Adapter
- c) Model No. : Earglove BT Adapter
- d) Power Supply : Adapter Model No.: SA106A-0512B-6
 - Input: 100-240Vac, 50-60Hz, 250mA
 - Output: DC 5.5Vdc, 0.5A, 2.75W

1.2 Characteristics of Device

The EUT is a Bluetooth Telephony Base based on the Bluetooth technology. Bluetooth is a short-range radio link intended to be a cable replacement between portable or fixed electronic devices. Bluetooth operates in the unlicensed ISM Band at 2.4GHz. In this band, 79 RF channels spaced 1MHz apart are defined. The rated output power is -3.5 dBm (0.45 mW).

1.3 Test Methodology

All testing were performed according to the procedures in ANSI C63.4 an FCC CFR 47 Part 2 and Part 15.

1.4 Modification List of EUT

N/A

1.5 Test Facility

The semi-anechoic chamber and conducted measurement facility used to collect the radiated and conducted data are located inside the Building at No.8, Lane 29, Wen-ming Road, Lo-shan Tsun, Kweishan Hsiang, Taoyuan, Taiwan, R.O.C.

This site has been accreditation as a FCC filing site.

2 PROVISIONS APPLICABLE

2.1 Definition

Unintentional radiator:

A device that intentionally generates and radio frequency energy for use within the device, or that sends radio frequency signals by conduction to associated equipment via connecting wiring, but which is not intended to emit RF energy by radiation or induction.

Class A Digital Device:

A digital device which is marketed for use in commercial or business environment; exclusive of a device which is market for use by the general public, or which is intended to be used in the home.

Class B Digital Device :

A digital device which is marketed for use in a residential environment notwithstanding use in a commercial, business or industrial environment. Example of such devices that are marketed for the general public.

Note : A manufacturer may also qualify a device intended to be marketed in a commercial, business, or industrial environment as a Class B digital device, and in fact is encouraged to do so, provided the device complies with the technical specifications for a Class B Digital Device. In the event that a particular type of device has been found to repeatedly cause harmful interference to radio communications, the Commission may classify such a digital device as a Class B Digital Device, Regardless of its intended use.

Intentional radiator:

A device that intentionally generates and emits radio frequency energy by radiation or induction.

2.2 Requirement for Compliance

(1) Conducted Emission Requirement

For unintentional device, according to §15.107(a) Line Conducted Emission Limits is as following:

Frequency MHz	Quasi Peak dB μ V	Average dB μ V
0.15 - 0.5	66-56*	56-46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

*Decreases with the logarithm of the frequency.

For intentional device, according to §15.207(a) Line Conducted Emission Limits is same as above table.

(2) Radiated Emission Requirement

For unintentional device, according to §15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency MHz	Distance Meters	Radiated dB μ V/m	Radiated μ V/m
30 - 88	3	40.0	100
88 - 216	3	43.5	150
216 - 960	3	46.0	200
above 960	3	54.0	500

For intentional device, according to §15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

(3) Antenna Requirement

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

(4) 20dB Bandwidth Requirement

For frequency hopping systems, according to 15.247(a)(1), hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of hopping channel, whichever is greater.

(5) Output Power Requirement

For frequency hopping systems, according to 15.247(1), operating in the 2400-2483.5MHz band employing at least 75 hopping channels. The maximum peak output power of the transmitter shall not exceed 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(6) 100 kHz Bandwidth of Frequency Band Edges Requirement

According to 15.247(c), if any 100 kHz bandwidth outside these frequency bands, the radio frequency power that is produced by the modulation products of the spreading sequence, the information sequence and the carrier frequency shall be either at least 20 dB below that in any 100 kHz bandwidth within the band that contains the highest level of the desired power or shall not exceed the general levels specified in §15.209(a), whichever results in the lesser attenuation.

(7) Number of Hopping Channels

According to 15.247(b)(1), for frequency hopping systems, operating in the 2400-2483.5MHz band employing at least 75 hopping channels.

(8) Channel Carrier Frequencies Separation

According to 15.247(a)(1)(iii), the frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25kHz or the 20dB bandwidth of hopping channel, whichever is greater.

(9) Dwell Time

According to 15.247(a)(1)(iii), frequency hopping system in the 2400-2483.5MHz band employing at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 second multiplied by the number of hopping channels employed.

(10) Power Spectral Density

According to 15.247(d), for bluetooth device, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

2.3 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42-16.423	399.9-410	4.5-5.25
0.495 - 0.505 **	16.69475 - 16.69525	608-614	5.35-5.46
2.1735 - 2.1905	16.80425 - 16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475 - 156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2.4 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device :

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

2.5 User Information

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual.

The Federal Communications Commission Radio Frequency Interference Statement includes the following paragraph.

This equipment has been tested and found to comply with the limits for a Class B Digital Device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction may cause harmful interference to radio communication. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio / TV technician for help.

3. SYSTEM TEST CONFIGURATION


3.1 Justification

For the purposes of this test report ancillary equipment is defined as equipment which is used in conjunction with the EUT to provide operational and control features to the EUT during the test. Notebook PC was used to control the RF channel under the highest, middle and lowest frequency and transmit the maximum RF power. Customer would not use it. But nevertheless ancillary equipment can influence the test results..

3.2 Devices for Tested System

Device	Manufacture	Model	Cable Description
*Earglove Bluetooth Adapter	Antonio Precise Products Manufactory Ltd.	Earglove BT Adapter	1.8m, Unshielded Line
Notebook PC	ASUS	L7245	3.3m, Unshielded Power Line (Adaptor) 1.8m, Unshielded Signal Line
Power Supply	GW	GPC-6030D	1.2m, Unshielded Line
Test Jig	----	----	0.2m, Unshielded Signal Line

Remark “*” means equipment under test.



4 RADIATED EMISSION MEASUREMENT

4.1 Applicable Standard

For unintentional radiator, the radiated emission shall comply with §15.109(a).

For intentional radiators, according to §15.247 (a), operation under this provision is limited to frequency hopping and digitally modulated, and the out band emission shall be comply with §15.247 (c)

4.2 Measurement Procedure

A. Preliminary Measurement For Portable Devices.

For portable devices, the following procedure was performed to determine the maximum emission axis of EUT (X,Y and Z axis):

1. With the receiving antenna is H polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
2. With the receiving antenna is V polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
3. Compare the results derived from above two steps. The axis of maximum emission from EUT was determined and the configuration was used to perform the final measurement.
4. The position in which the maximum noise occurred was “Y axis”. (Please see the test setup photos)

B. Final Measurement

1. Setup the configuration per figure 1 and 2 for frequencies measured below and above 1 GHz respectively. Turn on EUT and make sure that it is in continuous operating function.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a semi-anechoic chamber to determine the accurate frequencies of higher emissions and then each selected frequency is precisely measured. As the same purpose, for emission measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission measured below and above 1 GHz, set the spectrum analyzer on a 120 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.

Figure 1 : Frequencies measured below 1 GHz configuration





Figure 2 : Frequencies measured above 1 GHz configuration



4.3 Measuring Instrument

The following instrument are used for radiated emissions measurement :

Equipment	Manufacturer	Model No.	Next Cal. Due
EMI Test Receiver	Hewlett-Packard	8546A	08/27/2005
Horn Antenna	EMCO	3115	06/05/2005
LogBicone Antenna	Schwarzbeck	9160	10/28/2005
Horn Antenna	EMCO	3116	06/28/2005
Preamplifier	Hewlett-Packard	8449B	09/04/2005
Spectrum Analyzer	Hewlett-Packard	8564EC	09/10/2005

Measuring instrument setup in measured frequency band when specified detector function is used :

Frequency Band (MHz)	Instrument	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	RF Test Receiver	Quasi-Peak	120 kHz	N/A
	Spectrum Analyzer	Peak	100 kHz	100 kHz
Above 1000	Spectrum Analyzer	Peak	1 MHz	1 MHz
	Spectrum Analyzer	Average	1 MHz	10 Hz

Measuring instrument setup in measured frequency band when specified detector function is used :

Frequency Band (MHz)	Instrument	Function	Resolution bandwidth	Video Bandwidth
2390 & 2483.5	Spectrum Analyzer	Peak	1 MHz	1 MHz
	Spectrum Analyzer	Average	1 MHz	10 Hz

4.4 Radiated Emission Data

4.4.1 RF Portion

a) Channel 0

Operation Mode : Transmitting

Fundamental Frequency : 2402 MHz

Test Date : Sep. 18, 2004 Temperature : 24°C Humidity : 71%

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave	(H/V Max.)		
1201.000	48.2	---	51.2	---	-13.9	37.3	---	74.0	54.0	-16.7	73	1.0
4804.000	---	---	51.9	---	-4.6	47.3	---	74.0	54.0	-6.7	182	1.0
12010.000	---	---	---	---	2.9	---	---	74.0	54.0	---	---	---
16216.000	---	---	---	---	3.8	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. Item “Margin” referred to Average limit while there is only peak result.
4. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

b) Channel 39

Operation Mode : Transmitting

Fundamental Frequency : 2441 MHz

Test Date : Sep. 18, 2004

Temperature : 24°C

Humidity : 71%

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave	(H/V Max.)		
1220.500	51.7	---	53.3	---	-13.9	39.4	---	74.0	54.0	-14.6	89	1.0
4882.000	---	---	50.1	---	-4.6	45.5	---	74.0	54.0	-8.5	132	1.0
7323.000	---	---	---	---	-1.0	---	---	74.0	54.0	---	---	---
12205.000	---	---	---	---	2.9	---	---	74.0	54.0	---	---	---
19528.000	---	---	---	---	4.5	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. Item “Margin” referred to Average limit while there is only peak result.
4. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

c) Channel 78

Operation Mode : Transmitting

Fundamental Frequency : 2480 MHz

Test Date : Sep. 18, 2004

Temperature : 24°C

Humidity : 71%

Frequency (MHz)	Reading (dBuV)					Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V		Peak		Peak	Ave	Peak	Ave			
1240.00	49.5	---	53.1	---	-	-13.9	39.2	---	74.0	54.0	-14.8	173	1.0
4960.000	48.1	---	48.5	---	-	-4.6	43.9	---	74.0	54.0	-10.1	243	1.0
7440.000	---	---	---	---	-	-1.0	---	---	74.0	54.0	---	---	---
12400.000	---	---	---	---	-	2.9	---	---	74.0	54.0	---	---	---
19840.000	---	---	---	---	-	4.5	---	---	74.0	54.0	---	---	---
22320.000	---	---	---	---	-	1.3	---	---	74.0	54.0	---	---	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. Item “Margin” referred to Average limit while there is only peak result.
4. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

4.4.2 Other Emission

Operation Mode: 2402MHz

Test Date : Sep. 18, 2004

Temperature : 24°C

Humidity : 71%

Emission Frequency (MHz)	Meter Reading (dBuV)		CORR'd Factor (dB)	Results (dBuV/m)		Limit (3m) (dBuV/m)	Margins (dB)	Table Degree (deg)		Ant. High (m)	
	HOR.	VERT.		HOR.	VERT.			HOR.	VERT.	HOR.	VERT.
143.490	19.2	***	15.1	34.3	***	43.5	-9.2	32	***	1.0	***
145.430	***	22.1	15.1	***	37.2	43.5	-6.3	***	78	***	1.0
150.210	21.7	***	15.1	36.8	***	43.5	-6.7	123	***	1.0	***
245.210	22.1	***	14.6	36.7	***	46.0	-9.3	242	***	1.5	***
245.340	***	20.5	14.6	***	35.1	46.0	-10.9	***	192	***	1.0
261.830	24.6	22.5	14.6	39.2	37.1	46.0	-6.8	173	310	1.5	1.5
269.590	24.0	***	15.7	39.7	***	46.0	-6.3	87	***	1.0	***
284.140	***	21.5	15.7	***	37.2	46.0	-8.8	***	228	***	1.5
446.130	***	16.7	20.7	***	37.4	46.0	-8.6	***	273	***	1.5
701.240	13.0	***	26.1	39.1	***	46.0	-6.9	123	***	1.5	***
708.030	***	11.7	26.1	***	37.8	46.0	-8.2	***	192	***	1.0
900.090	11.7	***	29.0	40.7	***	46.0	-5.3	169	***	1.5	***
902.030	***	11.2	29.0	***	40.2	46.0	-5.8	***	172	***	1.0

Note :


1. Remark “***” means that the emissions level is too low to be measured.
2. Remark “#” means the noise was low, so record the peak value.
3. Item “Margin” referred to Q.P. limit while there is only peak result.
4. Please refer to page 19 to page 24 for chart

Horizontal



ETC TEST LABORTORY

Data#: 5660 File#: C:\Program Files\e3\MARK1.emi




Site : MOO SITE
Condition : FCC PART15 B 3m HORIZONTAL
EUT :
MODEL :
memo : TX_CHO

Vertical



ETC TEST LABORTORY

Data#: 5657 File#: C:\Program Files\e3\MARK1.emi




Site : MOO SITE
Condition : FCC PART15 B 3m VERTICAL
EUT :
MODEL :
memo : TX_CHO

Horizontal



ETC TEST LABORTORY

Data#: 5655 File#: C:\Program Files\e3\MARK1.emi




Site : MOO SITE
Condition : FCC PART15 B 3m HORIZONTAL
EUT :
MODEL :
memo : TX_CH39

Vertical



ETC TEST LABORTORY

Data#: 5658 File#: C:\Program Files\e3\MARK1.emi




Site : MOO SITE
Condition : FCC PART15 B 3m VERTICAL
EUT :
MODEL :
memo : TX_CH39

Horizontal



ETC TEST LABORTORY

Data#: 5656 File#: C:\Program Files\e3\MARK1.emi




Site : MOO SITE
Condition : FCC PART15 B 3m HORIZONTAL
EUT :
MODEL :
memo : TX_CH78

Vertical



ETC TEST LABORTORY

Data#: 5659 File#: C:\Program Files\e3\MARK1.emi



Site : MOO SITE
Condition : FCC PART15 B 3m VERTICAL
EUT :
MODEL :
memo : TX_CH78

4.4.3 Radiated Measurement at Bandedge with Fundamental Frequencies

(A)

Channel 0

Operation Mode : Transmitting

Fundamental Frequency : 2402 MHz

Test Date : Sep. 18, 2004

Temperature : 24°C

Humidity : 71%

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave	(H/V Max.)		
2390.000	30.8	21.0	30.7	20.9	28.3	59.1	49.3	74.0	54.0	-14.9	312	1.0

Note:

The result is the highest value of radiated emission from restrict band of 2310 ~2390 MHz.

(B)

Channel 78

Operation Mode : Transmitting

Fundamental Frequency : 2402 MHz

Test Date : Sep. 18, 2004

Temperature : 24°C

Humidity : 71%

Frequency (MHz)	Reading (dBuV)				Factor (dB) Corr.	Result @3m (dBuV/m)		Limit @3m (dBuV/m)		Margin (dB)	Table Deg. (Deg.)	Ant. High (m)
	H		V			Peak	Ave	Peak	Ave	(H/V Max.)		
2483.500	31.2	21.2	31.3	21.4	28.3	59.6	49.7	74.0	54.0	-14.4	128	1.0

Note:

The result is the highest value of radiated emission from restrict band of 2483.5 ~2500 MHz.

4.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor, High Pass Filter Loss(if used) and Cable Loss, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

where

$$\text{Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

5 CONDUCTED EMISSION MEASUREMENT


5.1 Standard Applicable

For unintentional and intentional device, Line Conducted Emission Limits are in accordance to § 15.107(a) and §15.207(a) respectively. Both Limits are identical specification.

5.2 Measurement Procedure

1. Setup the configuration per figure 3.
2. A preliminary scan with a spectrum monitor is performed to identify the frequency of emission that has the highest amplitude relative to the limit by operating the EUT in selected modes of operation, typical cable positions, and with a typical system configuration.
3. Record the 6 highest emissions relative to the limit.
4. Measure each frequency obtained from step 3 by a test receiver set on quasi peak detector function, and then record the accuracy frequency and emission level. If all emissions measured in the specified band are attenuated more than 20 dB from the limit, this step would be ignored, and the peak detector function would be used.
5. Confirm the highest three emissions with variation of the EUT cable configuration and record the final data.
6. Repeat all above procedures on measuring each operation mode of EUT.

Figure 3 : Conducted emissions measurement configuration



5.3 Conducted Emission Data

Operation Mode: 2402MHz

Test Date : Sep. 22, 2004

Temperature : 24°C

Humidity : 69%

Freq. (MHz)	Meter Reading (dBuV)				Factor (dB)	Result (dBuV)				Limit (dBuV)		Margins (dB) Q.P. or AVG.		
	Q.P Value		AVG. Value			Q.P Value		AVG. Value		Q.P Value	AVG. Value			
	L1	L2	L1	L2		L1	L2	L1	L2					
0.154	***	30.1	----	----	0.2	***	30.3	----	----	65.8	55.8	-35.5		
0.197	***	30.2	----	----	0.2	***	30.4	----	----	63.7	53.7	-33.3		
0.275	29.1	***	----	----	0.2	29.3	***	----	----	61.0	51.0	-31.7		
0.310	***	31.8	----	----	0.2	***	32.0	----	----	60.0	50.0	-28.0		
0.404	45.2	***	37.2	----	0.2	45.4	***	37.4	----	57.8	47.8	-10.4		
0.407	***	48.9	----	38.1	0.2	***	49.1	----	38.3	57.7	47.7	-8.6		
0.466	***	42.8	----	----	0.2	***	43.0	----	----	56.6	46.6	-13.6		
0.482	45.9	***	37.1	----	0.2	46.1	***	37.3	----	56.3	46.3	-9.0		
0.507	***	39.1	----	----	0.2	***	39.3	----	----	56.0	46.0	-16.7		
0.516	37.2	***	----	----	0.2	37.4	***	----	----	56.0	46.0	-18.6		
2.684	30.1	***	----	----	0.2	30.3	***	----	----	56.0	46.0	-25.7		
6.512	30.2	***	----	----	0.2	30.4	***	----	----	60.0	50.0	-29.6		

Note:


1. “***” means the value was too low to be measured.
2. If the data table appeared symbol of “----” means the Q.P. value is under the limit of AVG. so, the AVG. value doesn't need to be measured.
3. “#” means the noise was too low, so record the peak value.
4. The estimated measurement uncertainty of the result measurement is ± 2.5 dB.
5. Please refer to page 28 to page 33 for chart

CONDUCTED EMISSION TEST

PEAK VALUE

EUT:
Manuf:
Op Cond: TX_CH0
Operator: MARK
Test Spec: FCC PART15B
Comment: L1

Prescan Measurement: Detector: X PK
 Meas Time: see scan settings
 Peaks: 8
 Acc Margin: 6 dB




CONDUCTED EMISSION TEST

PEAK VALUE

EUT:
Manuf:
Op Cond: TX_CH0
Operator: MARK
Test Spec: FCC PART15B
Comment: L2

Prescan Measurement: Detector: X PK
 Meas Time: see scan settings
 Peaks: 8
 Acc Margin: 6 dB




CONDUCTED EMISSION TEST

PEAK VALUE

EUT:
Manuf:
Op Cond: TX_CH39
Operator: MARK
Test Spec: FCC PART15B
Comment: L1

Prescan Measurement: Detector: X PK
 Meas Time: see scan settings
 Peaks: 8
 Acc Margin: 6 dB




CONDUCTED EMISSION TEST

PEAK VALUE

EUT:
Manuf:
Op Cond: TX_CH39
Operator: MARK
Test Spec: FCC PART15B
Comment: L2

Prescan Measurement: Detector: X PK
 Meas Time: see scan settings
 Peaks: 8
 Acc Margin: 6 dB



CONDUCTED EMISSION TEST

PEAK VALUE

EUT:

Manuf:


Op Cond: TX_CH78

Operator: MARK

Test Spec: FCC PART15B

Comment: L1

Prescan Measurement: Detector: X PK
 Meas Time: see scan settings
 Peaks: 8
 Acc Margin: 6 dB




CONDUCTED EMISSION TEST

PEAK VALUE

EUT:
Manuf:
Op Cond: TX_CH78
Operator: MARK
Test Spec: FCC PART15B
Comment: L2

Prescan Measurement: Detector: X PK
 Meas Time: see scan settings
 Peaks: 8
 Acc Margin: 6 dB



5.4 Result Data Calculation

The result data is calculated by adding the LISN Factor to the measured reading. The basic equation with a sample calculation is as follows:

$$\text{RESULT} = \text{READING} + \text{LISN FACTOR (Included Cable Loss)}$$

Assume a receiver reading of 22.5 dB μ V is obtained, and LISN Factor is 0.1 dB, then the total of disturbance voltage is 22.6 dB μ V.

$$\text{RESULT} = 22.5 + 0.1 = 22.6 \text{ dB } \mu \text{ V}$$

$$\begin{aligned} \text{Level in } \mu \text{ V} &= \text{Common Antilogarithm}[(22.6 \text{ dB } \mu \text{ V})/20] \\ &= 13.48 \text{ } \mu \text{ V} \end{aligned}$$

5.5 Conducted Measurement Equipment

The following test equipment are used during the conducted test.

Equipment	Manufacturer	Model No.	Next Cal. Due
RF Test Receiver	Rohde and Schwarz	ESCS30	09/18/2005
Line Impedance Stabilization network	EMCO	3825	11/01/2004
Line Impedance Stabilization network	Rolf Heine	NNB-2/16Z	04/04/2005

6 ANTENNA REQUIREMENT

6.1 Standard Applicable

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to §15.247 (b), if Receiving antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

6.2 Antenna Construction and Directional Gain

Highly efficient chip antennas fix on the PCB. The peak gain of antenna used is 3.0 dBi.