

FCC RF Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT2211-1, XT2211-2, XT2211DL
FCC ID : IHDT56AA2
STANDARD : 47 CFR Part 2, 90(R)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S) : Oct. 12, 2021 ~ Oct. 20, 2021

We, Sporton International (ShenZhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (ShenZhen) Inc., the test report shall not be reproduced except in full.



Reviewed by: Derreck Chen / Supervisor



Approved by: Eric Shih / Manager



Sporton International (ShenZhen) Inc.

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055
People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY... 3
SUMMARY OF TEST RESULT ... 4
1 GENERAL DESCRIPTION ... 5
1.1 Applicant ... 5
1.2 Manufacturer ... 5
1.3 Feature of Equipment Under Test ... 5
1.4 Maximum ERP Power, and Emission Designator ... 6
1.5 Testing Site ... 6
1.6 Test Software ... 7
1.7 Applied Standards ... 7
1.8 Specification of Accessory ... 7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST ... 8
2.1 Test Mode ... 8
2.2 Connection Diagram of Test System ... 9
2.3 Support Unit used in test configuration and system ... 9
2.4 Measurement Results Explanation Example ... 10
3 CONDUCTED TEST ITEMS ... 11
3.1 Measuring Instruments ... 11
3.2 Conducted Output Power and ERP ... 12
3.3 Peak-to-Average Ratio ... 13
3.4 Occupied Bandwidth ... 14
3.5 Conducted Band Edge Measurement ... 15
3.6 Emission Mask ... 16
3.7 Conducted Spurious Emission Measurement ... 17
3.8 Frequency Stability Measurement ... 18
4 RADIATED TEST ITEMS ... 19
4.1 Measuring Instruments ... 19
4.2 Test Setup ... 19
4.3 Test Result of Radiated Test ... 20
4.4 Radiated Spurious Emission Measurement ... 21
5 LIST OF MEASURING EQUIPMENT ... 22
6 UNCERTAINTY OF EVALUATION ... 23
APPENDIX A. TEST RESULTS OF CONDUCTED TEST
APPENDIX B. TEST RESULTS OF RADIATED TEST
APPENDIX C. TEST SETUP PHOTOGRAPHS



REVISION HISTORY

| REPORT NO. | VERSION | DESCRIPTION | ISSUED DATE |
|------------|---------|-------------------------|---------------|
| FG181714D | Rev. 01 | Initial issue of report | Nov. 02, 2021 |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

SUMMARY OF TEST RESULT

| Report Section | FCC Rule | Description | Limit | Result | Remark |
|----------------|--|--|-------------------------------------|----------------|---|
| 3.2 | §2.1046 | Conducted Output Power | — | Reporting only | - |
| | §90.542 (a)(7) | Effective Radiated Power | ERP < 3Watt | PASS | - |
| 3.3 | - | Peak-to-Average Ratio | — | Reporting only | - |
| 3.4 | §2.1049 | Occupied Bandwidth | — | Reporting only | - |
| 3.5 | §2.1053 §90.543 (e)(2)(3) | Conducted Band Edge Measurement | Refer standard | PASS | - |
| 3.6 | §2.1051 §90.210(n) | Emission Mask | Mask B | PASS | - |
| 3.7 | §2.1053 §90.543 (e)(3) | Conducted Spurious Emission | < 43+10log ₁₀ (P[Watts]) | PASS | - |
| 3.8 | §2.1055 §90.539 (e) | Frequency Stability Temperature & Voltage | < ±1.25 ppm | PASS | - |
| 4.4 | §2.1053 §90.543 (e)(3) §90.543 (f) | Radiated Spurious Emission | < 43+10log ₁₀ (P[Watts]) | PASS | Under limit 18.98 dB at 1577.000 MHz |

| |
|--|
| Declaration of Conformity: |
| The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers. |
| Comments and Explanations: |
| The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification. |



1 General Description

1.1 Applicant

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Feature of Equipment Under Test

| Product Feature | |
|---------------------------------|---|
| Equipment | Mobile Cellular Phone |
| Brand Name | Motorola |
| Model Name | XT2211-1, XT2211-2, XT2211DL |
| FCC ID | IHDT56AA2 |
| Tx Frequency | LTE Band 14: 788 MHz ~ 798 MHz |
| Rx Frequency | LTE Band 14: 758 MHz ~ 768 MHz |
| Bandwidth | 5MHz / 10MHz |
| Maximum Output Power to Antenna | <Ant. 1> 22.64 dBm <Ant. 3> 22.05 dBm |
| Antenna Gain | -5.11 dBi |
| Type of Modulation | QPSK / 16QAM / 64QAM |
| IMEI Code | Conducted: 358116610011738 Radiation: 35811661001461 |
| HW Version | DVT2 |
| SW Version | RRDE31.Q3-37 |
| EUT Stage | Identical Prototype |

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Maximum ERP Power, and Emission Designator

| LTE Band 14 | | QPSK | | 16QAM/64QAM | |
|-------------|-----------------------|----------------|------------------------------|----------------|------------------------------|
| BW (MHz) | Frequency Range (MHz) | Maximum ERP(W) | Emission Designator (99%OBW) | Maximum ERP(W) | Emission Designator (99%OBW) |
| 5 | 790.5~795.5 | 0.0342 | 4M51G7D | 0.0291 | 4M52W7D |
| 10 | 793 | 0.0345 | 9M11G7D | 0.0291 | 9M07W7D |

1.5 Testing Site

<FCC>-SZ

Sporton International (Shenzhen) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

| | | | |
|---------------------------|---|----------------------------|---------------------------------------|
| Test Firm | Sporton International (Shenzhen) Inc. | | |
| Test Site Location | 1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595 | | |
| Test Site No. | Sporton Site No. | FCC Designation No. | FCC Test Firm Registration No. |
| | TH01-SZ | CN1256 | 421272 |

| | | | |
|---------------------------|---|----------------------------|---------------------------------------|
| Test Firm | Sporton International (Shenzhen) Inc. | | |
| Test Site Location | 101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City Guangdong Province China 518103 TEL: +86-755-33202398 | | |
| Test Site No. | Sporton Site No. | FCC Designation No. | FCC Test Firm Registration No. |
| | 03CH02-SZ | CN1256 | 421272 |

1.6 Test Software

| Item | Site | Manufacturer | Name | Version |
|------|-----------|--------------|------|--------------|
| 1. | 03CH02-SZ | AUDIX | E3 | 6.2009-8-24a |

1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, Part 90(R)
- ♦ ANSI C63.26
- ♦ KDB 971168 D01 Power Meas License Digital Systems v03r01
- ♦ KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

1.8 Specification of Accessory

| Specification of Accessory | | | | |
|----------------------------|------------|---------------------|------------|-----------------|
| AC Adapter 1 | Brand Name | Motorola(Salcomp) | Model Name | MC-101 |
| AC Adapter 2 | Brand Name | Motorola(AOHAI) | Model Name | MC-101 |
| AC Adapter 3 | Brand Name | Motorola(Chenyang) | Model Name | MC-101 |
| Battery | Brand Name | Motorola(ATL) | Model Name | MD50 |
| USB Cable 1 | Brand Name | Motorola(Saibao) | Model Name | SC18D22297 |
| USB Cable 2 | Brand Name | Motorola(Cabletech) | Model Name | SC18D22298 |
| USB Cable 3 | Brand Name | Motorola(Luxshare) | Model Name | SC18D22299 |
| Earphone | Brand Name | Motorola (NLD) | Model Name | NLD-EM313A-05SF |



2 Test Configuration of Equipment Under Test


2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

| Conducted Test Cases | Band | Bandwidth (MHz) | | | | | | Modulation | | | RB # | | | Test Channel | | |
|-----------------------------|---|-----------------|---|---|----|----|----|------------|-------|-------|------|------|------|--------------|---|---|
| | | 1.4 | 3 | 5 | 10 | 15 | 20 | QPSK | 16QAM | 64QAM | 1 | Half | Full | L | M | H |
| Max. Output Power | 14 | - | - | V | - | - | - | V | V | V | V | V | V | V | V | V |
| Peak-to-Average Ratio | 14 | - | - | | V | - | - | V | V | V | V | | V | | V | |
| 26dB and 99% Bandwidth | 14 | - | - | V | | - | - | V | V | V | | | V | V | V | V |
| Conducted Band Edge | 14 | - | - | | V | - | - | V | V | V | V | | V | | V | |
| Emission Mask | 14 | - | - | V | | - | - | V | V | V | V | | V | V | V | V |
| | 14 | - | - | | V | - | - | V | V | V | V | | V | | V | |
| Conducted Spurious Emission | 14 | - | - | | V | - | - | V | V | V | V | | | | V | |
| Frequency Stability | 14 | - | - | | V | - | - | V | | | | | V | | V | |
| E.R.P | 14 | - | - | V | | - | - | V | V | V | V | | | V | V | V |
| | 14 | - | - | | V | - | - | V | V | V | V | | | | V | |
| Radiated Spurious Emission | 14 | - | - | V | V | - | - | V | | | | V | | | | V |
| Note | <ol style="list-style-type: none"> The mark "v " means that this configuration is chosen for testing The mark "- " means that this bandwidth is not supported. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. | | | | | | | | | | | | | | | |

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

| Item | Equipment | Trade Name | Model No. | FCC ID | Data Cable | Power Cord |
|------|------------------|------------|-----------|--------|------------|-------------------|
| 1. | LTE Base Station | Anritsu | MT8820C | N/A | N/A | Unshielded, 1.8 m |
| 2. | DC Power Supply | GW INSTEK | GPS-3030D | N/A | N/A | Unshielded, 1.8 m |

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.0 dB and a 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.0 + 10 = 14.0 \text{ (dB)} \end{aligned}$$

3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.1.1 Test Setup


3.1.2 Conducted Output Power



3.1.3 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge, Emission Mask, and Conducted Spurious Emission



3.1.4 Frequency Stability



3.1.5 Test Result of Conducted Test

Please refer to Appendix A.

3.2 Conducted Output Power and ERP

3.2.1 Description of the Conducted Output Power Measurement and ERP

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 3 Watts for LTE Band 14.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.2.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.3 Peak-to-Average Ratio

3.3.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.3.2 Test Procedures

1. The EUT was connected to spectrum and system simulator via a power divider.
2. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
3. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.

3.4 Occupied Bandwidth

3.4.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.5 Conducted Band Edge Measurement

3.5.1 Description of Conducted Band Edge Measurement

For operations in the 758-768 MHz and the 788-798 MHz bands

(1) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than $76 + 10 \log$ (P) dB in a 6.25 kHz band segment, for base and fixed stations.

(2) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than $65 + 10 \log$ (P) dB in a 6.25 kHz band segment, for mobile and portable stations.

(3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least $43 + 10 \log$ (P) dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set spectrum analyzer with RMS detector.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. Checked that all the results comply with the emission limit line.

Example:

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)} = -13\text{dBm.}$$

3.6 Emission Mask

3.6.1 Description of Emission Mask

<Emission Mask B>.

For transmitters that are equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as follows:

- (1) On any frequency removed from the assigned frequency by more than 50 percent, but not more than 100 percent of the authorized bandwidth: At least 25 dB.
- (2) On any frequency removed from the assigned frequency by more than 100 percent, but not more than 250 percent of the authorized bandwidth: At least 35 dB.
- (3) On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least $43 + 10 \log (P)$ dB.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
5. Set spectrum analyzer with RMS detector.
6. Taking the record of maximum spurious emission.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= $P(W) - [43 + 10\log(P)]$ (dB)
= $[30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
= -13dBm.

3.7 Conducted Spurious Emission Measurement

3.7.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30MHz up to a frequency including its 10th harmonic.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and base station via power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's, for under 1GHz RBW = 100kHz, VBW = 300kHz and for above 1GHz RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. Set spectrum analyzer with RMS detector.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= P(W)- [43 + 10log(P)] (dB)
= [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
= -13dBm.

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ± 1.25 ppm of the center frequency.

3.8.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5.
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

4.4 Radiated Spurious Emission Measurement

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559–1610 MHz shall be limited to -70 dBW/MHz(-40 dBm/MHz) equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10. $EIRP (dBm) = S.G. Power - Tx Cable Loss + Tx Antenna Gain$
11. $ERP (dBm) = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= $P(W) - [43 + 10\log(P)] (dB)$
= $[30 + 10\log(P)] (dBm) - [43 + 10\log(P)] (dB)$
= -13dBm.



5 List of Measuring Equipment

| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Test Date | Due Date | Remark |
|---------------------------|------------------------------|-------------------|--------------------|-----------------|------------------|---------------------------------|---------------|-----------------------|
| Spectrum Analyzer | R&S | FSV40 | 101078 | 10Hz~40GHz | Apr. 08, 2021 | Oct. 12, 2021~ Oct. 20, 2021 | Apr. 07, 2022 | Conducted (TH01-SZ) |
| DC Power Supply | TTI | PL330P | 290070 | Max 32V , 3A | Oct. 15, 2020 | Oct. 12, 2021~ Oct. 20, 2021 | Oct. 14, 2021 | Conducted (TH01-SZ) |
| DC Power Supply | TTI | PL330P | 290070 | Max 32V , 3A | Oct. 14, 2021 | | Oct. 13, 2022 | Conducted (TH01-SZ) |
| Power Divider | TOJOIN | PS-2SM-04 265 | 60.06.020.007 7 | 0.4GHz~26.5GHz | Dec. 26, 2020 | Oct. 12, 2021~ Oct. 20, 2021 | Dec. 25, 2021 | Conducted (TH01-SZ) |
| Thermal Chamber | Ten Billion Hongzhangroup | LP-150U | H2014081803 | -40~+150°C | Jul. 14, 2021 | Oct. 12, 2021~ Oct. 20, 2021 | Jul. 13, 2022 | Conducted (TH01-SZ) |
| EXA Spectrum Analyzer | KEYSIGHT | N9010A | MY55150213 | 10Hz~44GHz | Jul. 13, 2021 | Oct. 13, 2021 | Jul. 13, 2022 | Radiation (03CH02-SZ) |
| Loop Antenna | R&S | HFH2-Z2 | 100354 | 9kHz~30MHz | Jun. 22, 2020 | Oct. 13, 2021 | Jun. 21, 2022 | Radiation (03CH02-SZ) |
| Bilog Antenna | TeseQ | CBL6112D | 35407 | 30MHz-2GHz | Jul. 15, 2021 | Oct. 13, 2021 | Jul. 14, 2022 | Radiation (03CH02-SZ) |
| Double Ridge Horn Antenna | ETS-Lindgren | 3117 | 00119436 | 1GHz~18GHz | Jul. 25, 2021 | Oct. 13, 2021 | Jul. 24, 2022 | Radiation (03CH02-SZ) |
| SHF-EHF Horn | com-power | AH-840 | 101071 | 18Ghz-40GHz | Apr. 11, 2021 | Oct. 13, 2021 | Apr. 10, 2022 | Radiation (03CH02-SZ) |
| LF Amplifier | Bur35407geon | BPA-530 | 102211 | 0.01~3000Mhz | Jul. 13, 2021 | Oct. 13, 2021 | Jul. 13, 2022 | Radiation (03CH02-SZ) |
| HF Amplifier | KEYSIGHT | 83017A | MY53270105 | 0.5GHz~26.5Ghz | Oct. 16, 2020 | Oct. 13, 2021 | Oct. 15, 2021 | Radiation (03CH02-SZ) |
| HF Amplifier | MITEQ | TTA1840-35 -HG | 1871923 | 18GHz~40GHz | Jul. 13, 2021 | Oct. 13, 2021 | Jul. 13, 2022 | Radiation (03CH02-SZ) |
| AC Power Source | Chroma | 61601 | 61601000247 0 | N/A | NCR | Oct. 13, 2021 | NCR | Radiation (03CH02-SZ) |
| Turn Table | Chaintek | T-200 | N/A | 0~360 degree | NCR | Oct. 13, 2021 | NCR | Radiation (03CH02-SZ) |
| Antenna Mast | Chaintek | MBS-400 | N/A | 1 m~4 m | NCR | Oct. 13, 2021 | NCR | Radiation (03CH02-SZ) |

NCR: No Calibration Required

6 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

| | |
|---|--------|
| Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$) | 2.47dB |
|---|--------|

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

| | |
|---|--------|
| Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$) | 3.31dB |
|---|--------|

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

| | |
|---|--------|
| Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$) | 3.72dB |
|---|--------|

----- THE END -----



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

| LTE Band 14 Maximum Average Power [dBm] | | | | | | |
|---|---------|-----------|--------|--------|--------|---------|
| BW [MHz] | RB Size | RB Offset | Mod | Lowest | Middle | Highest |
| 5 | 1 | 0 | QPSK | 22.51 | 22.54 | 22.49 |
| 5 | 1 | 12 | | 22.58 | 22.59 | 22.60 |
| 5 | 1 | 24 | | 22.27 | 22.26 | 22.32 |
| 5 | 12 | 0 | | 21.50 | 21.50 | 21.48 |
| 5 | 12 | 7 | | 21.58 | 21.55 | 21.52 |
| 5 | 12 | 13 | | 21.51 | 21.50 | 21.47 |
| 5 | 25 | 0 | | 21.51 | 21.52 | 21.48 |
| 5 | 1 | 0 | 16-QAM | 21.62 | 21.59 | 21.57 |
| 5 | 1 | 12 | | 21.90 | 21.89 | 21.88 |
| 5 | 1 | 24 | | 21.59 | 21.60 | 21.60 |
| 5 | 12 | 0 | | 20.49 | 20.46 | 20.42 |
| 5 | 12 | 7 | | 20.56 | 20.49 | 20.48 |
| 5 | 12 | 13 | | 20.50 | 20.47 | 20.47 |
| 5 | 25 | 0 | | 20.49 | 20.47 | 20.45 |
| 5 | 1 | 0 | 64QAM | 20.51 | 20.53 | 20.48 |
| 5 | 1 | 12 | | 20.80 | 20.76 | 20.71 |
| 5 | 1 | 24 | | 20.50 | 20.47 | 20.46 |
| 5 | 12 | 0 | | 19.47 | 19.46 | 19.37 |
| 5 | 12 | 7 | | 19.54 | 19.44 | 19.45 |
| 5 | 12 | 13 | | 19.47 | 19.38 | 19.43 |
| 5 | 25 | 0 | | 19.48 | 19.51 | 19.42 |



| LTE Band 14 Maximum Average Power [dBm] | | | | | | |
|---|---------|-----------|--------|--------|--------|---------|
| BW [MHz] | RB Size | RB Offset | Mod | Lowest | Middle | Highest |
| 10 | 1 | 0 | QPSK | | 22.64 | |
| 10 | 1 | 25 | | | 22.53 | |
| 10 | 1 | 49 | | | 22.47 | |
| 10 | 25 | 0 | | | 21.67 | |
| 10 | 25 | 12 | | | 21.62 | |
| 10 | 25 | 25 | | | 21.65 | |
| 10 | 50 | 0 | | | 21.66 | |
| 10 | 1 | 0 | 16-QAM | | 21.78 | |
| 10 | 1 | 25 | | | 21.90 | |
| 10 | 1 | 49 | | | 21.77 | |
| 10 | 25 | 0 | | | 20.61 | |
| 10 | 25 | 12 | | | 20.57 | |
| 10 | 25 | 25 | | | 20.64 | |
| 10 | 50 | 0 | | | 20.63 | |
| 10 | 1 | 0 | 64QAM | | 20.69 | |
| 10 | 1 | 25 | | | 20.79 | |
| 10 | 1 | 49 | | | 20.62 | |
| 10 | 25 | 0 | | | 19.63 | |
| 10 | 25 | 12 | | | 19.57 | |
| 10 | 25 | 25 | | | 19.64 | |
| 10 | 50 | 0 | | | 19.61 | |

ERP

| LTE Band 14 ($G_T - L_C = -5.11$ dBi) QPSK | | | | | | |
|---|--------|--------|--------|-----|--------|--|
| Bandwidth | 5M | | | 10M | | |
| Channel | 23305 | 23330 | 23355 | | 23330 | |
| | (Low) | (Mid) | (High) | | (Mid) | |
| Frequency | 790.5 | 793 | 795.5 | | 793 | |
| (MHz) | | | | | | |
| Conducted Power (dBm) | 22.58 | 22.59 | 22.60 | | 22.64 | |
| Conducted Power (Watts) | 0.1811 | 0.1816 | 0.1820 | | 0.1837 | |
| ERP(dBm) | 15.32 | 15.33 | 15.34 | | 15.38 | |
| ERP(Watts) | 0.0340 | 0.0341 | 0.0342 | | 0.0345 | |

| LTE Band 14 ($G_T - L_C = -5.11$ dBi) 16QAM | | | | | | |
|--|--------|--------|--------|-----|--------|--|
| Bandwidth | 5M | | | 10M | | |
| Channel | 23305 | 23330 | 23355 | | 23330 | |
| | (Low) | (Mid) | (High) | | (Mid) | |
| Frequency | 790.5 | 793 | 795.5 | | 793 | |
| (MHz) | | | | | | |
| Conducted Power (dBm) | 21.90 | 21.89 | 21.88 | | 21.90 | |
| Conducted Power (Watts) | 0.1549 | 0.1545 | 0.1542 | | 0.1549 | |
| ERP(dBm) | 14.64 | 14.63 | 14.62 | | 14.64 | |
| ERP(Watts) | 0.0291 | 0.0290 | 0.0290 | | 0.0291 | |



| LTE Band 14 ($G_T - L_C = -5.11$ dBi) 64QAM | | | | | | |
|--|--------|--------|--------|-----|--------|--|
| Bandwidth | 5M | | | 10M | | |
| Channel | 23305 | 23330 | 23355 | | 23330 | |
| | (Low) | (Mid) | (High) | | (Mid) | |
| Frequency | 790.5 | 793 | 795.5 | | 793 | |
| (MHz) | | | | | | |
| Conducted Power (dBm) | 20.80 | 20.76 | 20.71 | | 20.79 | |
| Conducted Power (Watts) | 0.1202 | 0.1191 | 0.1178 | | 0.1199 | |
| ERP(dBm) | 13.54 | 13.50 | 13.45 | | 13.53 | |
| ERP(Watts) | 0.0226 | 0.0224 | 0.0221 | | 0.0225 | |


LTE Band 14

Peak-to-Average Ratio


| Mode | LTE Band 14 / 10MHz | | | | |
|------------|---------------------|---------|-------|---------|-------------|
| Mod. | QPSK | | 16QAM | | Limit: 13dB |
| RB Size | 1RB | Full RB | 1RB | Full RB | Result |
| Lowest CH | - | - | - | - | PASS |
| Middle CH | 4.46 | 5.04 | 5.65 | 5.97 | |
| Highest CH | - | - | - | - | |
| Mode | LTE Band 14 / 10MHz | | | | |
| Mod. | 64QAM | | | | Limit: 13dB |
| RB Size | 1RB | Full RB | | | Result |
| Lowest CH | - | - | - | - | PASS |
| Middle CH | 5.59 | 6.29 | - | - | |
| Highest CH | - | - | - | - | |

LTE Band 14 / 10MHz / QPSK

Middle Channel/ 1RB




Middle Channel / Full RB




LTE Band 14 / 10MHz / 16QAM

Middle Channel/ 1RB




Middle Channel / Full RB




LTE Band 14 / 10MHz / 64QAM

Middle Channel/ 1RB



Middle Channel / Full RB






26dB Bandwidth

| Mode | LTE Band 14 : 26dB BW(MHz) | | | | | | | | | | | |
|------------|----------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| BW | 1.4MHz | | 3MHz | | 5MHz | | 10MHz | | 15MHz | | 20MHz | |
| Mod. | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM |
| Lowest CH | - | - | - | - | 4.97 | 4.93 | - | - | - | - | - | - |
| Middle CH | - | - | - | - | 5.09 | 5.04 | 9.85 | 9.67 | - | - | - | - |
| Highest CH | - | - | - | - | 5.07 | 4.94 | - | - | - | - | - | - |
| Mode | LTE Band 14 : 26dB BW(MHz) | | | | | | | | | | | |
| BW | 1.4MHz | | 3MHz | | 5MHz | | 10MHz | | 15MHz | | 20MHz | |
| Mod. | 64QAM | | 64QAM | | 64QAM | | 64QAM | | 64QAM | | 64QAM | |
| Lowest CH | - | - | - | - | 5.18 | - | - | - | - | - | - | - |
| Middle CH | - | - | - | - | 5.05 | - | 9.85 | - | - | - | - | - |
| Highest CH | - | - | - | - | 4.99 | - | - | - | - | - | - | - |




LTE Band 14

Lowest Channel / 5MHz / QPSK




Date: 12.OCT.2021 22:48:00

Lowest Channel / 5MHz / 16QAM




Date: 12.OCT.2021 22:47:49

Middle Channel / 5MHz / QPSK




Date: 12.OCT.2021 23:59:57

Middle Channel / 5MHz / 16QAM




Date: 12.OCT.2021 23:51:08

Highest Channel / 5MHz / QPSK




Date: 12.OCT.2021 23:52:15

Highest Channel / 5MHz / 16QAM




Date: 12.OCT.2021 23:52:04






LTE Band 14

Lowest Channel / 5MHz / 64QAM




Date: 13.OCT.2021 00:03:32

Middle Channel / 5MHz / 64QAM




Date: 13.OCT.2021 00:19:59

Middle Channel / 10MHz / 64QAM



Date: 13.OCT.2021 00:36:14

Highest Channel / 5MHz / 64QAM



Date: 13.OCT.2021 00:11:33




Occupied Bandwidth

| Mode | LTE Band 14 : 99%OBW(MHz) | | | | | | | | | | | |
|------------|---------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| BW | 1.4MHz | | 3MHz | | 5MHz | | 10MHz | | 15MHz | | 20MHz | |
| Mod. | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM | QPSK | 16QAM |
| Lowest CH | - | - | - | - | 4.50 | 4.51 | - | - | - | - | - | - |
| Middle CH | - | - | - | - | 4.51 | 4.52 | 9.11 | 8.97 | - | - | - | - |
| Highest CH | - | - | - | - | 4.49 | 4.49 | - | - | - | - | - | - |
| Mode | LTE Band 14 : 99%OBW(MHz) | | | | | | | | | | | |
| BW | 1.4MHz | | 3MHz | | 5MHz | | 10MHz | | 15MHz | | 20MHz | |
| Mod. | 64QAM | | 64QAM | | 64QAM | | 64QAM | | 64QAM | | 64QAM | |
| Lowest CH | - | - | - | - | 4.52 | - | - | - | - | - | - | - |
| Middle CH | - | - | - | - | 4.52 | - | 9.07 | - | - | - | - | - |
| Highest CH | - | - | - | - | 4.51 | - | - | - | - | - | - | - |




LTE Band 14

Lowest Channel / 5MHz / QPSK




Date: 12.OCT.2021 22:47:37

Lowest Channel / 5MHz / 16QAM




Date: 12.OCT.2021 22:47:38

Middle Channel / 5MHz / QPSK




Date: 12.OCT.2021 23:51:30

Middle Channel / 5MHz / 16QAM




Date: 12.OCT.2021 23:51:39

Highest Channel / 5MHz / QPSK



Date: 12.OCT.2021 23:51:41

Highest Channel / 5MHz / 16QAM




Date: 12.OCT.2021 23:51:53



LTE Band 14


Middle Channel / 10MHz / QPSK

Middle Channel / 10MHz / 16QAM



| Type | Ref | Trc | X-value | Y-value | Function | Function Result |
|------|-----|-----|--------------|-----------|----------|-----------------|
| M1 | 1 | | 796.437 MHz | 15.80 dBm | | |
| T1 | 1 | | 788.4446 MHz | 10.55 dBm | Occ BW | 9.110889111 MHz |
| T2 | 1 | | 797.5554 MHz | 11.39 dBm | | |

Date: 13.OCT.2021 00:17:12




| Type | Ref | Trc | X-value | Y-value | Function | Function Result |
|------|-----|-----|--------------|-----------|----------|-----------------|
| M1 | 1 | | 796.397 MHz | 16.20 dBm | | |
| T1 | 1 | | 788.5245 MHz | 9.52 dBm | Occ BW | 8.971028971 MHz |
| T2 | 1 | | 797.4955 MHz | 9.70 dBm | | |

Date: 13.OCT.2021 00:17:23


LTE Band 14

Lowest Channel / 5MHz / 64QAM




Date: 13.OCT.2021 00:03:21

Middle Channel / 5MHz / 64QAM




Date: 13.OCT.2021 00:11:11

Middle Channel / 10MHz / 64QAM



Date: 13.OCT.2021 00:16:03

Highest Channel / 5MHz / 64QAM




Date: 13.OCT.2021 00:11:22



Conducted Band Edge


LTE Band 14 / 5MHz / QPSK

Lowest Band Edge / 1 RB




Date: 12.OCT.2021 23:43:29

Highest Band Edge / 1 RB




Date: 12.OCT.2021 23:59:31

Lowest Band Edge / Full RB



Date: 12.OCT.2021 23:38:02

Highest Band Edge / Full RB




Date: 12.OCT.2021 23:54:04




LTE Band 14 / 5MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 12.OCT.2021 23:41:40

Highest Band Edge / 1 RB




Date: 12.OCT.2021 23:57:42

Lowest Band Edge / Full RB



Date: 12.OCT.2021 23:39:51

Highest Band Edge / Full RB




Date: 12.OCT.2021 23:55:53



LTE Band 14 / 5MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 13.OCT.2021 00:07:10

Highest Band Edge / 1 RB




Date: 14.OCT.2021 12:57:57

Lowest Band Edge / Full RB



Date: 13.OCT.2021 00:05:21

Highest Band Edge / Full RB




Date: 13.OCT.2021 00:13:22




LTE Band 14 / 10MHz / QPSK

Lowest Band Edge / 1 RB

Highest Band Edge / 1 RB




Date: 13.OCT.2021 00:28:36



Date: 13.OCT.2021 00:30:25

Band Edge / Full RB





Date: 13.OCT.2021 00:19:34



LTE Band 14 / 10MHz / 16QAM

Lowest Band Edge / 1 RB


Highest Band Edge / 1 RB



Date: 14.OCT.2021 01:38:17

Date: 14.OCT.2021 01:40:15

Band Edge / Full RB




Date: 13.OCT.2021 00:21:23




LTE Band 14 / 10MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 13.OCT.2021 00:39:53

Highest Band Edge / 1 RB



Date: 13.OCT.2021 00:41:42


Band Edge / Full RB





Date: 13.OCT.2021 00:38:04



Conducted Spurious Emission









LTE Band 14 / 5MHz

Lowest Channel / 64QAM

Middle Channel / 64QAM




Date: 13.OCT.2021 00:08:59



Date: 13.OCT.2021 00:10:49

Highest Channel / 64QAM




Date: 13.OCT.2021 00:17:01



LTE Band 14 / 10MHz


Middle Channel / 64QAM




Mask

LTE Band 14 / 5MHz / QPSK

Lowest Channel / 1RB




Date: 20.OCT.2021 13:26:16



Date: 20.OCT.2021 13:26:56


Lowest Channel / Full RB




Date: 20.OCT.2021 13:22:56

LTE Band 14 / 5MHz / 16QAM

Lowest Channel / 1RB




Date: 20.OCT.2021 13:21:33



Date: 20.OCT.2021 13:27:35


Lowest Channel / Full RB




Date: 20.OCT.2021 13:23:36

LTE Band 14 / 5MHz / 64QAM

Lowest Channel / 1RB




Date: 20.OCT.2021 13:124:56



Date: 20.OCT.2021 13:128:15


Lowest Channel / Full RB




Date: 20.OCT.2021 13:124:16

LTE Band 14 / 5MHz / QPSK

Middle Channel / 1RB




Date: 20.OCT.2021 13:30:53



Date: 20.OCT.2021 13:30:14


Middle Channel / Full RB




Date: 20.OCT.2021 13:34:10

LTE Band 14 / 5MHz / 16QAM

Middle Channel / 1RB




Date: 20.OCT.2021 13:12:13



Date: 20.OCT.2021 13:12:14


Middle Channel / Full RB




Date: 20.OCT.2021 13:13:31

LTE Band 14 / 5MHz / 64QAM

Middle Channel / 1RB




Date: 20.OCT.2021 13:13:12



Date: 20.OCT.2021 13:28:55


Middle Channel / Full RB




Date: 20.OCT.2021 13:13:12

LTE Band 14 / 5MHz / QPSK

Highest Channel / 1RB




Date: 20.OCT.2021 13:13:09



Date: 20.OCT.2021 13:13:50



Highest Channel / Full RB




Date: 20.OCT.2021 13:14:50

LTE Band 14 / 5MHz / 16QAM

Highest Channel / 1RB




Highest Channel / Full RB




LTE Band 14 / 5MHz / 64QAM

Highest Channel / 1RB




Date: 20.OCT.2021 13:136:49



Date: 20.OCT.2021 13:140:10


Highest Channel / Full RB




Date: 20.OCT.2021 13:136:09

LTE Band 14 / 10MHz / QPSK

Middle Channel / 1RB




Date: 20.OCT.2021 13:42:48



Date: 20.OCT.2021 13:42:09


Middle Channel / Full RB




Date: 20.OCT.2021 13:46:05

LTE Band 14 / 10MHz / 16QAM

Middle Channel / 1RB




Date: 20.OCT.2021 13:43:26



Date: 20.OCT.2021 13:41:29


Middle Channel / Full RB




Date: 20.OCT.2021 13:45:26

LTE Band 14 / 10MHz / 64QAM

Middle Channel / 1RB




Date: 20.OCT.2021 13:14:07



Date: 20.OCT.2021 13:14:10

Middle Channel / Full RB



Date: 20.OCT.2021 13:14:47

Frequency Stability

| Test Conditions | | LTE Band 14 (QPSK) / Middle Channel | Limit |
|------------------|-------------------|-------------------------------------|---------|
| Temperature (°C) | Voltage (Volt) | BW 10MHz | Note 2. |
| | | Deviation (ppm) | Result |
| 50 | Normal Voltage | 0.0018 | PASS |
| 40 | Normal Voltage | 0.0019 | |
| 30 | Normal Voltage | 0.0011 | |
| 20(Ref.) | Normal Voltage | 0.0000 | |
| 10 | Normal Voltage | 0.0023 | |
| 0 | Normal Voltage | 0.0020 | |
| -10 | Normal Voltage | 0.0024 | |
| -20 | Normal Voltage | 0.0025 | |
| -30 | Normal Voltage | 0.0011 | |
| 20 | Maximum Voltage | 0.0016 | |
| 20 | Normal Voltage | 0.0000 | |
| 20 | Battery End Point | 0.0028 | |

Note:

1. Normal Voltage =3.87 V. ; Battery End Point (BEP) =3.5 V. ; Maximum Voltage =4.43 V.
2. Note: The frequency fundamental emissions stay within the authorized frequency block.



Appendix B. Test Results of Radiated Test

Field Strength of Spurious Radiated

| LTE Band 14 / QPSK / RB Size 1 Offset 0 | | | | | | | | | |
|--|-------------------|-------------|---------------|-------------------|-------------------|--------------------|----------------------|-----------------------|--------------------|
| Bandwidth | Frequency (MHz) | ERP (dBm) | Limit (dBm) | Over Limit (dB) | SPA Reading (dBm) | S.G. Power (dBm) | TX Cable loss (dB) | TX Antenna Gain (dBi) | Polarization (H/V) |
| 10MHz | 1577 | -61.70 | -42.15 | -19.55 | -70.35 | -64.95 | 4.00 | 9.40 | H |
| | 2365.5 | -62.89 | -13 | -49.89 | -76.13 | -66.46 | 4.88 | 10.60 | H |
| | 3154 | -60.84 | -13 | -47.84 | -76.46 | -65.77 | 5.52 | 12.60 | H |
| | 1577 | -61.13 | -42.15 | -18.98 | -69.91 | -64.38 | 4.00 | 9.40 | V |
| | 2365.5 | -62.83 | -13 | -49.83 | -76.06 | -66.40 | 4.88 | 10.60 | V |
| | 3154 | -61.24 | -13 | -48.24 | -76.86 | -66.17 | 5.52 | 12.60 | V |
| Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line. | | | | | | | | | |
| Test Result | | | | | PASS | | | | |