



# FCC RF TEST REPORT

**APPLICANT** : Motorola Mobility LLC  
**EQUIPMENT** : Mobile Cellular Phone  
**BRAND NAME** : Motorola  
**MODEL NAME** : XT2175-1  
**FCC ID** : IHDT56AC1  
**Standard** : FCC Part 15 Subpart E §15.407  
**CLASSIFICATION** : 15E 6 GHz Low Power Indoor Client (6XD)  
**TEST DATE(S)** : Sep. 13, 2021 ~ Nov. 09, 2021

We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

*Jason Jia*

Reviewed by: Jason Jia / Supervisor

*Alex Wang*

Approved by: Alex Wang / Manager



**Sporton International (Kunshan) Inc.**

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300  
People's Republic of China**



# Table of Contents

**History of this test report..... 3**

**Summary of Test Result..... 4**

**1 General Description ..... 5**

    1.1 Applicant ..... 5

    1.2 Manufacturer..... 5

    1.3 Product Feature of Equipment Under Test..... 5

    1.4 Product Specification of Equipment Under Test..... 6

    1.5 Modification of EUT ..... 6

    1.6 Specification of Accessory..... 7

    1.7 Testing Location ..... 8

    1.8 Test Software..... 8

    1.9 Applicable Standards..... 8

**2 Test Configuration of Equipment Under Test ..... 9**

    2.1 Carrier Frequency and Channel ..... 9

    2.2 Test Mode..... 11

    2.3 Connection Diagram of Test System..... 13

    2.4 Support Unit used in test configuration and system ..... 14

    2.5 EUT Operation Test Setup ..... 14

    2.6 Measurement Results Explanation Example..... 14

**3 Test Result ..... 15**

    3.1 26dB & 99% Occupied Bandwidth Measurement ..... 15

    3.2 Maximum conducted Output Power and Fundamental Maximum EIRP Measurement..... 20

    3.3 Fundamental Power Spectral Density Measurement ..... 21

    3.4 In-Band Emissions (Channel Mask) ..... 23

    3.5 Contention Based Protocol..... 53

    3.6 Unwanted Emissions Measurement..... 58

    3.7 AC Conducted Emission Measurement..... 62

    3.8 Antenna Requirements..... 64

**4 List of Measuring Equipment..... 65**

**5 Uncertainty of Evaluation ..... 66**

**Appendix A. Conducted Test Results**

**Appendix B. AC Conducted Emission Test Result**

**Appendix C. Radiated Spurious Emission**

**Appendix D. Duty Cycle Plots**

**Appendix E. Setup Photographs**





### Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.403(i) 15.407(a)(10)	26dB Emission Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.407(a)(8)	Maximum Conducted Output Power	Reporting only	-
3.2	15.407(a)(8)	Fundamental Maximum EIRP	Pass	-
3.3	15.407(a)(8)	Fundamental Power Spectral Density	Pass	-
3.4	15.407(b)(6)	In-Band Emissions (Channel Mask)	Pass	-
3.5	15.407(d)(6)	Contention Based Protocol	Pass	
3.6	15.407(b)	Unwanted Emissions	Pass	Under limit 3.04 dB at 43.580 MHz
3.7	15.207	AC Conducted Emission	Pass	Under limit 7.23 dB at 0.206 MHz
3.8	15.203 15.407(a)	Antenna Requirement	Pass	-

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



# 1 General Description

## 1.1 Applicant

Motorola Mobility LLC  
222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

## 1.2 Manufacturer

Motorola Mobility LLC  
222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2175-1
FCC ID	IHDT56AC1
IMEI Code	Conducted: 350506880020187/350506880020195 Conduction: 350506880020864/350506880020872 Radiation: 350506880021441/350506880021458 CBP: 350506880019247/350506880019254
HW Version	DVT2
SW Version	RRX31.Q3-38
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

### 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification							
<b>Tx/Rx Frequency Range</b>	U-NII-5: 5925 MHz ~ 6425 MHz U-NII-6: 6425 MHz ~ 6525 MHz U-NII-7: 6525 MHz ~ 6875 MHz U-NII-8: 6875 MHz ~ 7125 MHz						
<b>Maximum Output Power to Antenna</b>	<b>&lt;5925 MHz ~ 7125 MHz &gt;</b> 802.11a : 12.87 dBm / 0.0194 W 802.11ax HE20 : 13.76 dBm / 0.0238 W 802.11ax HE40 : 17.55 dBm / 0.0569 W 802.11ax HE80 : 17.01 dBm / 0.0502 W 802.11ax HE160 : 17.24 dBm / 0.0530 W						
<b>99% Occupied Bandwidth</b>	802.11a : 16.98 MHz 802.11ax HE20 : 19.08 MHz 802.11ax HE40 : 38.16 MHz 802.11ax HE80 : 77.56 MHz 802.11ax HE160 : 156.80 MHz						
<b>Antenna Type / Gain</b>	<b>&lt;5925 MHz ~ 6425 MHz &gt;</b> <Ant. 1> : IFA Antenna with gain -6.2 dBi <Ant. 2> : IFA Antenna with gain -6.2 dBi <b>&lt;6425 MHz ~ 6525 MHz &gt;</b> <Ant. 1> : IFA Antenna with gain -6.2 dBi <Ant. 2> : IFA Antenna with gain -6.6 dBi <b>&lt;6525 MHz ~ 6875 MHz &gt;</b> <Ant. 1> : IFA Antenna with gain -6.2 dBi <Ant. 2> : IFA Antenna with gain -6.6 dBi <b>&lt;6875 MHz ~ 7125 MHz &gt;</b> <Ant. 1> : IFA Antenna with gain -6.6 dBi <Ant. 2> : IFA Antenna with gain -7.0 dBi						
<b>Type of Modulation</b>	802.11a : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ax : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM)						
<b>Antenna Function Description</b>	<table border="1"> <thead> <tr> <th></th> <th>Ant. 1</th> <th>Ant. 2</th> </tr> </thead> <tbody> <tr> <td>802.11a/ax MIMO</td> <td>V</td> <td>V</td> </tr> </tbody> </table>		Ant. 1	Ant. 2	802.11a/ax MIMO	V	V
	Ant. 1	Ant. 2					
802.11a/ax MIMO	V	V					

**Remark:**

1. The above EUT's information was declared by manufacturer. Please refer to Comments and Explanations in report summary.
2. WLAN 5G Ant. 1 / Ant. 2 corresponding to EUT Photo Ant. 7 / Ant. 6
3. 802.11ax support OFDMA full RU tone and partial RU tone, both full RU and partial RU-left (for low CH) and partial RU-right (for high CH) are tested, only the worse data were reported.

### 1.5 Modification of EUT

No modifications are made to the EUT during all test items.



## 1.6 Specification of Accessory

Specification of Accessory				
AC Adapter 1(US)	Brand Name	Motorola(Salcomp)	Model Name	MC-331
AC Adapter 1(EU)	Brand Name	Motorola(Salcomp)	Model Name	MC-332
AC Adapter 1(UK)	Brand Name	Motorola(Salcomp)	Model Name	MC-333
AC Adapter 1(AR)	Brand Name	Motorola(Salcomp)	Model Name	MC-336
AC Adapter 1(BR)	Brand Name	Motorola(Salcomp)	Model Name	MC-337
AC Adapter 1(PRC)	Brand Name	Motorola(Salcomp)	Model Name	MC-338
AC Adapter 1(CHILE)	Brand Name	Motorola(Salcomp)	Model Name	MC-339
AC Adapter 2(US)	Brand Name	Motorola(Chenyang)	Model Name	MC-331
AC Adapter 2(EU)	Brand Name	Motorola(Chenyang)	Model Name	MC-332
AC Adapter 2(AR)	Brand Name	Motorola(Chenyang)	Model Name	MC-336
AC Adapter 2(BR)	Brand Name	Motorola(Chenyang)	Model Name	MC-337
AC Adapter 3(US)	Brand Name	Motorola(Acbel)	Model Name	MC-331
AC Adapter 3(EU)	Brand Name	Motorola(Acbel)	Model Name	MC-332
AC Adapter 3(UK)	Brand Name	Motorola(Acbel)	Model Name	MC-333
Battery	Brand Name	Motorola(ATL)	Model Name	MB50
Earphone 1	Brand Name	Motorola(Lyand)	Model Name	MH191(SH38C81577)
Earphone 2	Brand Name	Motorola(LCHSE)	Model Name	MH191(SH38C81576)
Type C to Audio Cable	Brand Name	Motorola(Luxshare)	Model Name	SC18C27844
Type C to HDMI Cable	Brand Name	Motorola(Linxee)	Model Name	SC18D02146
USB Cable 1	Brand Name	Motorola(Saibao)	Model Name	SC18D22297
USB Cable 2	Brand Name	Motorola(Cabletech)	Model Name	SC18D22298
USB Cable 3	Brand Name	Motorola(Luxshare)	Model Name	SC18D22299



### 1.7 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

<b>Test Firm</b>	Sporton International (Kunshan) Inc.		
<b>Test Site Location</b>	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	CO01-KS 03CH05-KS TH01-KS	CN1257	314309

### 1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH05-KS	AUDIX	E3	6.2009-8-24al
2.	CO01-KS	AUDIX	E3	6.2009-8-24

### 1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 987594 D02 U-NII 6 GHz EMC Measurement v01
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.





## 2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

### 2.1 Carrier Frequency and Channel

<U-NII-5, 6, 7, 8>

BW 20M	Channel	1	5	9	13	17	21	25	29
	Freq. (MHz)	5955	5975	5995	6015	6035	6055	6075	6095
BW 40M	Channel	3		11		19		27	
	Freq. (MHz)	5965		6005		6045		6085	
BW 80M	Channel	7				23			
	Freq. (MHz)	5985				6065			
BW 160M	Channel	15							
	Freq. (MHz)	6025							
BW 20M	Channel	33	37	41	45	49	53	57	61
	Freq. (MHz)	6115	6135	6155	6175	6195	6215	6235	6255
BW 40M	Channel	35		43		51		59	
	Freq. (MHz)	6125		6165		6205		6245	
BW 80M	Channel	39				55			
	Freq. (MHz)	6145				6225			
BW 160M	Channel	47							
	Freq. (MHz)	6185							
BW 20M	Channel	65	69	73	77	81	85	89	93
	Freq. (MHz)	6275	6295	6315	6335	6355	6375	6395	6415
BW 40M	Channel	67		75		83		91	
	Freq. (MHz)	6285		6325		6365		6405	
BW 80M	Channel	71				87			
	Freq. (MHz)	6305				6385			
BW 160M	Channel	79							
	Freq. (MHz)	6345							



BW 20M	Channel	97	101	105	109	113	117	121	125
	Freq. (MHz)	6435	6455	6475	6495	6515	6535	6555	6575
BW 40M	Channel	99		107		115		123	
	Freq. (MHz)	6445		6485		6525		6565	
BW 80M	Channel	103				119			
	Freq. (MHz)	6465				6545			
BW 160M	Channel	111							
	Freq. (MHz)	6505							

BW 20M	Channel	129	133	137	141	145	149	153	157
	Freq. (MHz)	6595	6615	6635	6655	6675	6695	6715	6735
BW 40M	Channel	131		139		147		155	
	Freq. (MHz)	6605		6645		6685		6725	
BW 80M	Channel	135				151			
	Freq. (MHz)	6625				6705			
BW 160M	Channel	143							
	Freq. (MHz)	6665							

BW 20M	Channel	161	165	169	173	177	181	185	189
	Freq. (MHz)	6755	6775	6795	6815	6835	6855	6875	6895
BW 40M	Channel	163		171		179		187	
	Freq. (MHz)	6765		6805		6845		6885	
BW 80M	Channel	167				183			
	Freq. (MHz)	6785				6865			
BW 160M	Channel	175							
	Freq. (MHz)	6825							

BW 20M	Channel	193	197	201	205	209	213	217	221
	Freq. (MHz)	6915	6935	6955	6975	6995	7015	7035	7055
BW 40M	Channel	195		203		211		219	
	Freq. (MHz)	6925		6965		7005		7045	
BW 80M	Channel	199				215			
	Freq. (MHz)	6945				7025			
BW 160M	Channel	207							
	Freq. (MHz)	6985							

BW 20M	Channel	225		229		-			
	Freq. (MHz)	7075		7095		-			
BW 40M	Channel	227							
	Freq. (MHz)	7085							



## 2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11a	6 Mbps
802.11ax HE20	MCS0
802.11ax HE40	MCS0
802.11ax HE80	MCS0
802.11ax HE160	MCS0

Co-location
802.11ax HE40 CH227 + BLE (2Mbps) CH39
802.11ax HE40 CH227 + 802.11ax HE20 CH01

Test Cases	
AC Conducted Emission	Mode 1 : GSM850 Idle + Bluetooth Link + WLAN Link(6G) + USB Cable 1(Charging from Adapter 1)
<b>Remark:</b> For Radiated Test Cases, the tests were performed with Adapter 1 and USB Cable 1.	

Ch. #		5925-7125 MHz	5925-7125 MHz	5925-7125 MHz	5925-7125 MHz
		UNII-5	UNII-6	UNII-7	UNII-8
		802.11a	802.11a	802.11a	802.11a
L	Low	001	097	117	189
M	Middle	045	105	149	209
H	High	093	113	181	229
Straddle		-	-	-	185

Ch. #		5925-7125 MHz	5925-7125 MHz	5925-7125 MHz	5925-7125 MHz
		UNII-5	UNII-6	UNII-7	UNII-8
		802.11ax HE20	802.11ax HE20	802.11ax HE20	802.11ax HE20
L	Low	001	097	117	189
M	Middle	045	105	149	209
H	High	093	113	181	229
Straddle		-	-	-	185

Ch. #		5925-7125 MHz	5925-7125 MHz	5925-7125 MHz	5925-7125 MHz
		UNII-5	UNII-6	UNII-7	UNII-8
		802.11ax HE40	802.11ax HE40	802.11ax HE40	802.11ax HE40
L	Low	003	099	123	195
M	Middle	043	-	147	203
H	High	091	107	179	227
Straddle		-	115	-	187




Ch. #		5925-7125 MHz UNII-5	5925-7125 MHz UNII-6	5925-7125 MHz UNII-7	5925-7125 MHz UNII-8
		802.11ax HE80	802.11ax HE80	802.11ax HE80	802.11ax HE80
L	Low	007	103	135	199
M	Middle	039		151	-
H	High	087		167	215
Straddle		-	119	183	-

Ch. #		5925-7125 MHz UNII-5	5925-7125 MHz UNII-6	5925-7125 MHz UNII-7	5925-7125 MHz UNII-8
		802.11ax HE160	802.11ax HE160	802.11ax HE160	802.11ax HE160
L	Low	015	-	143	207
M	Middle	047			
H	High	079			
Straddle		-	111	175	-


Remark: For radiation spurious emission, the final modulation and the worst data rate was reference the max RF conducted power.

## 2.3 Connection Diagram of Test System

For Radiated Emission



For Conducted Emission





## 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	ASUS	GT-AXE11000	MSQ-RTAXIC00	N/A	Unshielded,1.8m
3.	Notebook	Dell	P78G	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A

## 2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss.

*Offset = RF cable loss.*

Following shows an offset computation example with cable loss 7.7 dB.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)}. \\ &= 7.7 \text{ (dB)} \end{aligned}$$

### 3 Test Result

#### 3.1 26dB & 99% Occupied Bandwidth Measurement

##### 3.1.1 Limit of 26dB & 99% Occupied Bandwidth

<FCC 14-30 CFR 15.407>

(a)(10) The maximum transmitter channel bandwidth for U-NII devices in the 5.925-7.125 GHz band is 320 megahertz.


##### 3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

##### 3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section C) Emission bandwidth
2. Set RBW = approximately 1% of the emission bandwidth.
3. Set the VBW > RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
7. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW)  $\geq 3 * RBW$ .
8. Measure and record the results in the test report.

##### 3.1.4 Test Setup





##### 3.1.5 Test Result of 26dB & 99% Occupied Bandwidth

Please refer to Appendix A.

Only the maximum 26dB & 99% OB plots of each bandwidth shown in the report.





For 20MHz:









For 40MHz:







For 80MHz:





For 160MHz:



**Note:** The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

## 3.2 Maximum conducted Output Power and Fundamental Maximum EIRP Measurement

### 3.2.1 Limit of Fundamental Maximum EIRP

<FCC 14-30 CFR 15.407>

(a)(8) For client devices operating under the control of an indoor access point in the 5.925-7.125 GHz bands, the maximum e.i.r.p. over the frequency band of operation must not exceed 24 dBm.

### 3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.2.3 Test Procedures


The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor,  $10 \log(1/x)$ , where  $x$  is the duty cycle.
4. For MIMO mode, the measure-and-sum technique should be used for measuring the in-band transmit power of a device.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits, a single measurement over the entire emission bandwidth can be performed to show compliance.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Fundamental Maximum EIRP

Please refer to Appendix A.



### 3.3 Fundamental Power Spectral Density Measurement

#### 3.3.1 Limit of Fundamental Power Spectral Density

##### <FCC 14-30 CFR 15.407>

(a)(8) For client devices operating under the control of an indoor access point in the 5.925-7.125 GHz bands, the maximum EIRP power spectral density must not exceed  $-1$  dBm in any 1-megahertz band.

#### 3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Section F) Maximum power spectral density.

##### # Method SA-2 #


(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
  - Set span to encompass the entire emission bandwidth (EBW) of the signal.
  - Set RBW = 1 MHz.
  - Set VBW  $\geq$  3 MHz.
  - Number of points in sweep  $\geq$  2 Span / RBW.
  - Sweep time = auto.
  - Detector = RMS
  - Trace average at least 100 traces in power averaging mode.
  - Add  $10 \log(1/x)$ , where  $x$  is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add  $10 \log(1/0.25) = 6$  dB if the duty cycle is 25 percent.
1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
  2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.
  3. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

Method (a): Measure and sum the spectra across the outputs.


The total final Power Spectral Density is from a device with 2 transmitter outputs. The spectrum measurements of the individual outputs are all performed with the same span and number of points, the spectrum value in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 to obtain the value for the first frequency bin of the summed spectrum.

### 3.3.4 Test Setup



### 3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



Note: EIRP Power Density = maximum power spectral density + Gain



## 3.4 In-Band Emissions (Channel Mask)

### 3.4.1 Limit of Unwanted Emissions

#### <FCC 14-30 CFR 15.407>

(b)(6) For transmitters operating within the 5.925-7.125 GHz bands: Power spectral density must be suppressed by 20 dB at 1 MHz outside of channel edge, by 28 dB at one channel bandwidth from the channel center, and by 40 dB at one- and one-half times the channel bandwidth away from channel center. At frequencies between one megahertz outside an unlicensed device's channel edge and one channel bandwidth from the center of the channel, the limits must be linearly interpolated between 20 dB and 28 dB suppression, and at frequencies between one and one- and one-half times an unlicensed device's channel bandwidth, the limits must be linearly interpolated between 28 dB and 40 dB suppression. Emissions removed from the channel center by more than one- and one-half times the channel bandwidth must be suppressed by at least 40 dB.

### 3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.4.3 Test Procedures


The testing follows FCC KDB 987594 D02 U-NII 6GHz EMC Measurement v01.

Section J) In-Band Emissions.

1. Take nominal bandwidth as reference channel bandwidth provided that 26 dB emission bandwidth is always larger than nominal bandwidth
2. Measure the power spectral density (which will be used for emissions mask reference) using the following procedure:
  - a) Set the span to encompass the entire 26 dB EBW of the signal.
  - b) Set RBW = same RBW used for 26 dB EBW measurement.
  - c) Set VBW  $\geq 3 \times$  RBW
  - d) Number of points in sweep  $\geq [2 \times \text{span} / \text{RBW}]$ .
  - e) Sweep time = auto.
  - f) Detector = RMS (i.e., power averaging)
  - g) Trace average at least 100 traces in power averaging (rms) mode.
  - h) Use the peak search function on the instrument to find the peak of the spectrum.

3. Using the measuring equipment limit line function, develop the emissions mask based on the following requirements. The emissions power spectral density must be reduced below the peak power spectral density (in dB) as follows:
  - a. Suppressed by 20 dB at 1 MHz outside of the channel edge.
  - b. Suppressed by 28 dB at one channel bandwidth from the channel center.
  - c. Suppressed by 40 dB at one- and one-half times the channel bandwidth from the channel center.
4. Adjust the span to encompass the entire mask as necessary.
5. Clear trace.
6. Trace average at least 100 traces in power averaging (rms) mode.
7. Adjust the reference level as necessary so that the crest of the channel touches the top of the emission mask.

#### **3.4.4 Test Setup**








### 3.4.5 Test Result

MIMO <Ant. 1+2(1)>


EUT Mode : 802.11a

Plot on Channel 5955MHz




Date: 9.NOV.2021 13:39:23

Plot on Channel 6175MHz




Date: 9.NOV.2021 13:43:34

Plot on Channel 6415MHz



Date: 9.NOV.2021 13:44:51


Plot on Channel 6435MHz



Date: 9.NOV.2021 13:48:11




Plot on Channel 6475MHz




Date: 9.NOV.2021 13:50:00

Plot on Channel 6515MHz




Date: 9.NOV.2021 13:53:20

Plot on Channel 6535MHz



Date: 9.NOV.2021 13:54:58


Plot on Channel 6695MHz



Date: 9.NOV.2021 13:59:23




Plot on Channel 6855MHz




Date: 9.NOV.2021 14:00:47

Plot on Channel 6875MHz




Date: 9.NOV.2021 14:05:16

Plot on Channel 6895MHz




Date: 9.NOV.2021 14:07:28

Plot on Channel 6995MHz



Date: 9.NOV.2021 14:13:20

Plot on Channel 7095MHz




Date: 9.NOV.2021 14:17:01




EUT Mode : 802.11ax HE20

Plot on Channel 5955MHz




Date: 9.NOV.2021 14:26:28

Plot on Channel 6175MHz




Date: 9.NOV.2021 14:31:24

Plot on Channel 6415MHz



Date: 9.NOV.2021 14:32:42


Plot on Channel 6435MHz



Date: 9.NOV.2021 14:38:40




Plot on Channel 6475MHz




Date: 9.NOV.2021 14:40:26

Plot on Channel 6515MHz




Date: 9.NOV.2021 14:44:36

Plot on Channel 6535MHz



Date: 9.NOV.2021 14:46:37


Plot on Channel 6695MHz



Date: 9.NOV.2021 14:50:52




Plot on Channel 6855MHz




Date: 9.NOV.2021 14:53:00

Plot on Channel 6875MHz




Date: 9.NOV.2021 14:57:35

Plot on Channel 6895MHz




Date: 9.NOV.2021 14:59:29

Plot on Channel 6995MHz



Date: 9.NOV.2021 15:04:06

Plot on Channel 7095MHz




Date: 9.NOV.2021 15:05:40




EUT Mode : 802.11ax HE40

Plot on Channel 5965MHz




Date: 9.NOV.2021 15:19:40

Plot on Channel 6165MHz




Date: 9.NOV.2021 15:41:02

Plot on Channel 6405MHz



Date: 9.NOV.2021 15:45:07


Plot on Channel 6445MHz



Date: 9.NOV.2021 15:46:14




Plot on Channel 6485MHz




Date: 9.NOV.2021 15:49:30

Plot on Channel 6525MHz




Date: 9.NOV.2021 15:50:39

Plot on Channel 6565MHz




Date: 9.NOV.2021 15:59:42

Plot on Channel 6685MHz




Date: 9.NOV.2021 16:00:44

Plot on Channel 6845MHz



Date: 9.NOV.2021 16:04:46

Plot on Channel 6885MHz




Date: 9.NOV.2021 16:38:58






Plot on Channel 6925MHz




Date: 9.NOV.2021 16:19:22

Plot on Channel 6965MHz



Date: 9.NOV.2021 16:24:30

Plot on Channel 7085MHz




Date: 9.NOV.2021 16:36:34




EUT Mode : 802.11ax HE80

Plot on Channel 5985MHz




Date: 14 SEP. 2021 22:27:28

Plot on Channel 6145MHz




Date: 14 SEP. 2021 22:59:44

Plot on Channel 6385MHz



Date: 14 SEP. 2021 23:01:39


Plot on Channel 6465MHz



Date: 14 SEP. 2021 23:02:35




Plot on Channel 6545MHz




Date: 14 SEP. 2021 23:04:28

Plot on Channel 6625MHz




Date: 14 SEP. 2021 23:05:00

Plot on Channel 6705MHz




Date: 14 SEP. 2021 23:06:41

Plot on Channel 6785MHz




Date: 14 SEP. 2021 23:07:27

Plot on Channel 6865MHz



Date: 14 SEP. 2021 23:09:37


Plot on Channel 6945MHz



Date: 14 SEP. 2021 23:12:19



**Plot on Channel 7025MHz**




Date: 14 SEP. 2021 23:14:25




EUT Mode : 802.11ax HE160

Plot on Channel 6025MHz




Date: 19.OCT.2021 13:15:38

Plot on Channel 6185MHz




Date: 19.OCT.2021 13:24:39

Plot on Channel 6345MHz



Date: 19.OCT.2021 13:25:57


Plot on Channel 6505MHz



Date: 19.OCT.2021 14:44:59




Plot on Channel 6665MHz




Date: 19.OCT.2021 14:50:56

Plot on Channel 6825MHz



Date: 19.OCT.2021 14:53:03

Plot on Channel 6985MHz




Date: 19.OCT.2021 15:02:04



MIMO <Ant. 1+2(2)>


EUT Mode : 802.11a

Plot on Channel 5955MHz




Date: 9.NOV.2021 13:40:37

Plot on Channel 6175MHz




Date: 9.NOV.2021 13:42:40

Plot on Channel 6415MHz



Date: 9.NOV.2021 13:45:49


Plot on Channel 6435MHz



Date: 9.NOV.2021 13:47:11




Plot on Channel 6475MHz




Date: 9.NOV.2021 13:50:51

Plot on Channel 6515MHz




Date: 9.NOV.2021 13:52:03

Plot on Channel 6535MHz




Date: 9.NOV.2021 13:56:26

Plot on Channel 6695MHz




Date: 9.NOV.2021 13:57:51

Plot on Channel 6855MHz



Date: 9.NOV.2021 14:01:59

Plot on Channel 6875MHz




Date: 9.NOV.2021 14:03:55






Plot on Channel 6895MHz




Date: 9.NOV.2021 14:09:06

Plot on Channel 6995MHz



Date: 9.NOV.2021 14:11:32

Plot on Channel 7095MHz



Date: 9.NOV.2021 14:15:58