


FCC SAR Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT2231-1, XT2231-5
FCC ID : IHDT56AC2
STANDARD : FCC 47 CFR Part 2 (2.1093)

We, Sporton International Inc. (Shenzhen), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Shenzhen), the test report shall not be reproduced except in full.



Reviewed by: Hank Huang / Supervisor



Approved by: Johnny Chen / Manager



Sporton International Inc. (Shenzhen)

**1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055
People's Republic of China**



Table of Contents

1. Statement of Compliance 4
2. Administration Data 5
3. Guidance Applied 5
4. Equipment Under Test (EUT) Information 6
4.1 General Information 6
4.2 General LTE SAR Test and Reporting Considerations 8
5. Proximity Sensor Triggering Test 10
6. RF Exposure Limits 12
6.1 Uncontrolled Environment 12
6.2 Controlled Environment 12
7. Specific Absorption Rate (SAR) 13
7.1 Introduction 13
7.2 SAR Definition 13
8. System Description and Setup 14
8.1 E-Field Probe 15
8.2 Data Acquisition Electronics (DAE) 15
8.3 Phantom 16
8.4 Device Holder 17
9. Measurement Procedures 18
9.1 Spatial Peak SAR Evaluation 18
9.2 Power Reference Measurement 19
9.3 Area Scan 19
9.4 Zoom Scan 20
9.5 Volume Scan Procedures 20
9.6 Power Drift Monitoring 20
10. Test Equipment List 21
11. System Verification 22
11.1 Tissue Simulating Liquids 22
11.2 Tissue Verification 23
11.3 System Performance Check Results 24
12. RF Exposure Positions 26
12.1 Ear and handset reference point 26
12.2 Definition of the cheek position 27
12.3 Definition of the tilt position 28
12.4 Body Worn Accessory 29
12.5 Product Specific 10g SAR Exposure 30
12.6 Wireless Router 30
13. Conducted RF Output Power (Unit: dBm) 31
14. Antenna Location 41
15. SAR Test Results 42
15.1 Head SAR 44
15.2 Hotspot SAR 48
15.3 Body Worn Accessory SAR 53
15.4 Product Specific SAR 57
15.5 Repeated SAR Measurement 61
16. Simultaneous Transmission Analysis 62
16.1 Head Exposure Conditions 63
16.2 Hotspot Exposure Conditions 64
16.3 Body-Worn Accessory Exposure Conditions 66
16.4 Product Specific Exposure Conditions 67
16.5 SPLSR Evaluation and Analysis 69
17. Uncertainty Assessment 77
18. References 78
Appendix A. Plots of System Performance Check
Appendix B. Plots of High SAR Measurement
Appendix C. DASy Calibration Certificate
Appendix D. Test Setup Photos
Appendix E. Conducted RF Output Power Table



1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for **Motorola Mobility LLC, Mobile Cellular Phone, XT2231-1, XT2231-5**, are as follows.

Highest 1g SAR Summary						
Equipment Class	Frequency Band		Head (Separation 0mm)	Hotspot (Separation 5mm)	Body-worn (Separation 5mm)	Highest Simultaneous Transmission 1g SAR (W/kg)
			1g SAR (W/kg)			
Licensed	GSM	GSM850	0.54	1.23	1.23	1.59
		GSM1900	0.35	1.42	1.42	
	WCDMA	Band V	0.42	1.19	1.19	
		Band IV	0.25	1.40	1.40	
		Band II	0.53	1.44	1.44	
	LTE	Band 13	0.27	1.01	1.01	
		Band 26/Band 5	0.46	1.20	1.20	
		Band 66/ Band 4	0.24	1.36	1.31	
		Band 2	0.37	1.42	1.42	
		Band 7	0.18	1.34	1.33	
		Band 38	<0.10	1.44	1.44	
DTS	WLAN	2.4GHz WLAN	1.03	1.16	1.16	1.42
NII		5GHz WLAN	1.05	1.18	1.19	1.49
DSS	Bluetooth	2.4GHz Bluetooth	<0.10	0.28	0.28	1.59

Highest 10g SAR Summary				
Equipment Class	Frequency Band		Product Specific 10g SAR (W/kg) (Separation 0mm)	Highest Simultaneous Transmission 10g SAR (W/kg)
License	GSM	GSM850	2.97	3.42
		GSM1900	3.12	
	WCDMA	Band V	2.82	
		Band IV	3.35	
		Band II	3.23	
	LTE	Band 26/Band 5	2.46	
		Band 66/ Band 4	3.13	
		Band 2	3.15	
		Band 7	2.79	
		Band 38	2.61	
DTS	WLAN	2.4GHz WLAN	1.66	3.35
NII		5GHz WLAN	3.17	3.42

Date of Testing: 2021/12/5 ~ 2022/1/11

Remark: This device supports both LTE B4/5 and B66/26. Since the supported frequency span for LTE B4/5 falls completely within the supports frequency span for LTE B66/26, both LTE bands have the same target power, and both LTE bands share the same transmission path; therefore, SAR was only assessed for LTE B66/26.

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for Partial-Body 1g SAR, 4.0 W/kg for Product Specific 10g SAR) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.



2. Administration Data

Sporton International Inc. (Shenzhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Testing Laboratory			
Test Firm	Sporton International Inc. (Shenzhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	SAR01-SZ	CN1256	421272

Applicant	
Company Name	Motorola Mobility LLC
Address	222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

Manufacturer	
Company Name	Motorola Mobility LLC
Address	222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

3. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r03
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 616217 D04 SAR for laptop and tablets v01r02
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05
- FCC KDB 941225 D06 Hotspot Mode SAR v02r01



4. Equipment Under Test (EUT) Information

4.1 General Information

Product Feature & Specification	
Equipment Name	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2231-1, XT2231-5
FCC ID	IHDT56AC2
IMEI Code	Sample 1: IMEI 1: 359986690042897 IMEI 2: 359986690045411 Sample 2: IMEI 1: 359986690032161 IMEI 2: 359986690037640 Sample 3: IMEI 1: 359986690053530 IMEI 2: 359986690055378 Sample 4: IMEI 1: 359986690042921 IMEI 2: 359986690045445
Wireless Technology and Frequency Range	GSM850: 824 MHz ~ 849 MHz GSM1900: 1850 MHz ~ 1910 MHz WCDMA Band II: 1850 MHz ~ 1910 MHz WCDMA Band IV: 1710 MHz ~ 1755 MHz WCDMA Band V: 824 MHz ~ 849 MHz LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 7: 2500 MHz ~ 2570 MHz LTE Band 13: 777 MHz ~ 787 MHz LTE Band 26: 814 MHz ~ 849 MHz LTE Band 38: 2570 MHz ~ 2620 MHz LTE Band 66: 1710 MHz ~ 1780 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5720 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Mode	GSM/GPRS/EGPRS RMC/AMR 12.2Kbps HSDPA/HSUPA DC-HSDPA HSPA+ (16QAM uplink is not supported) LTE: QPSK, 16QAM, 64QAM WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
HW Version	PVT2
SW Version	STA32.48
GSM / (E)GPRS Transfer mode	Class B – EUT cannot support Packet Switched and Circuit Switched Network simultaneously but can automatically switch between Packet and Circuit Switched Network.
EUT Stage	Identical Prototype
Remark: 1. 802.11n-HT40 is not supported in 2.4GHz WLAN. 2. This device supports VoIP in GPRS, EGPRS, WCDMA and LTE (e.g. for 3rd-party VoIP), LTE supports VoLTE operation.	



3. This device 2.4GHz WLAN support hotspot operation and Bluetooth support tethering applications.
4. This device 5.2GHz WLAN/5.8GHz WLAN support hotspot operation, and 5.2GHz WLAN/5.8GHz WLAN supports WiFi Direct (GC/GO), and 5.3GHz / 5.5GHz supports WiFi Direct (GC only).
5. This device does not support DTM operation and supports GPRS/EGPRS mode up to multi-slot class 12.
6. The device implements the power management and proximity sensor /receiver detection/hotspot mode for SAR compliance at different exposure conditions (head, body-worn, hotspot, extremity) and the details about the power management decision and sensor detection are provided in the operational description. And the device will invoke corresponding work scenarios power level base on frequency bands/antennas, which can refer to power table at appendix E.
7. There are two different types of EUT. They are single SIM card mobile and dual SIM card mobile. The others are the same including circuit design, PCB board, structure and all components. It is special to declare. After pre-scan two types of EUT, we found test result of the sample that dual SIM was the worst, so we chose dual SIM card mobile to perform all tests.
8. For dual SIM card mobile has two SIM slots and supports dual SIM dual standby. The WWAN radio transmission will be enabled by either one SIM at a time (single active). After pre-scan two SIM cards power, we found test result of the SIM1 was the worse, so we chose SIM1 slot to perform all tests.
9. For some WWAN bands, sensor on reduced power level is higher than hotspot reduced power level, so front/back sensor on SAR can represent hotspot conservatively.
10. There are four samples. The difference between them could be referred to the XT2231-1, XT2231-5_Operational Description of Product Equality Declaration which is exhibited separately. According to the difference, we choose sample 1 for full testing and sample 2/3/4 for worst case verification.
11. The device has three headsets. For three headsets only suppliers are different. So we chose headset 1 to perform full SAR testing only.
12. This device has two batteries. For battery 1 was in sample 1/2, and battery 2 was in sample 3/4. They were all evaluated for SAR testing conservatively.



4.2 General LTE SAR Test and Reporting Considerations

Summarized necessary items addressed in KDB 941225 D05 v02r05																																																															
FCC ID	IHDT56AC2																																																														
Equipment Name	Mobile Cellular Phone																																																														
Operating Frequency Range of each LTE transmission band	LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 7: 2500 MHz ~ 2570 MHz LTE Band 13: 777 MHz ~ 787 MHz LTE Band 26: 814 MHz ~ 849 MHz LTE Band 38: 2570 MHz ~ 2620 MHz LTE Band 66: 1710 MHz ~ 1780 MHz																																																														
Channel Bandwidth	LTE Band 2: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 4: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 5: 1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 7: 5MHz, 10MHz, 15MHz, 20MHz LTE Band 13: 5MHz, 10MHz LTE Band 26: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz LTE Band 38: 5MHz, 10MHz, 15MHz, 20MHz LTE Band 66: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz																																																														
uplink modulations used	QPSK / 16QAM / 64QAM																																																														
LTE Voice / Data requirements	Voice and Data																																																														
LTE Release Version	R11, Cat4																																																														
CA Support	Not Supported																																																														
LTE MPR permanently built-in by design	<p>Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3</p> <table border="1"> <thead> <tr> <th rowspan="2">Modulation</th> <th colspan="6">Channel bandwidth / Transmission bandwidth (N_{RB})</th> <th rowspan="2">MPR (dB)</th> </tr> <tr> <th>1.4 MHz</th> <th>3.0 MHz</th> <th>5 MHz</th> <th>10 MHz</th> <th>15 MHz</th> <th>20 MHz</th> </tr> </thead> <tbody> <tr> <td>QPSK</td> <td>> 5</td> <td>> 4</td> <td>> 8</td> <td>> 12</td> <td>> 16</td> <td>> 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>≤ 5</td> <td>≤ 4</td> <td>≤ 8</td> <td>≤ 12</td> <td>≤ 16</td> <td>≤ 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>> 5</td> <td>> 4</td> <td>> 8</td> <td>> 12</td> <td>> 16</td> <td>> 18</td> <td>≤ 2</td> </tr> <tr> <td>64 QAM</td> <td>≤ 5</td> <td>≤ 4</td> <td>≤ 8</td> <td>≤ 12</td> <td>≤ 16</td> <td>≤ 18</td> <td>≤ 2</td> </tr> <tr> <td>64 QAM</td> <td>> 5</td> <td>> 4</td> <td>> 8</td> <td>> 12</td> <td>> 16</td> <td>> 18</td> <td>≤ 3</td> </tr> <tr> <td>256 QAM</td> <td colspan="6">≥ 1</td> <td>≤ 5</td> </tr> </tbody> </table>	Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1	16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2	64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2	64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3	256 QAM	≥ 1						≤ 5
Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)																																																								
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz																																																									
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1																																																								
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1																																																								
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2																																																								
64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2																																																								
64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3																																																								
256 QAM	≥ 1						≤ 5																																																								
LTE A-MPR	In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)																																																														
Spectrum plots for RB configuration	A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.																																																														
Power reduction applied to satisfy SAR compliance	Yes, when operating in Proximity sensors/receiver/hotspot detect mechanism, head/body-worn/hotspot/extremity will trigger reduced power for some WWAN bands applied to satisfy SAR compliance,the detail please referred to section 13.																																																														




Transmission (H, M, L) channel numbers and frequencies in each LTE band												
LTE Band 2												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	18607	1850.7	18615	1851.5	18625	1852.5	18650	1855	18675	1857.5	18700	1860
M	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880
H	19193	1909.3	19185	1908.5	19175	1907.5	19150	1905	19125	1902.5	19100	1900
LTE Band 4												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	19957	1710.7	19965	1711.5	19975	1712.5	20000	1715	20025	1717.5	20050	1720
M	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5
H	20393	1754.3	20385	1753.5	20375	1752.5	20350	1750	20325	1747.5	20300	1745
LTE Band 5												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20407	824.7	20415	825.5	20425	826.5	20450	829	20450	829	20450	829
M	20525	836.5	20525	836.5	20525	836.5	20525	836.5	20525	836.5	20525	836.5
H	20643	848.3	20635	847.5	20625	846.5	20600	844	20600	844	20600	844
LTE Band 7												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20775	2502.5	20800	2505	20825	2507.5	20850	2510	20850	2510	20850	2510
M	21100	2535	21100	2535	21100	2535	21100	2535	21100	2535	21100	2535
H	21425	2567.5	21400	2565	21375	2562.5	21350	2560	21350	2560	21350	2560
LTE Band 13												
	Bandwidth 5 MHz				Bandwidth 10 MHz				Bandwidth 10 MHz			
	Channel #		Freq.(MHz)		Channel #		Freq.(MHz)		Channel #		Freq.(MHz)	
L	23205		779.5		23230		782		23230		782	
M	23230		782		23230		782		23230		782	
H	23255		784.5		23230		782		23230		782	

LTE Band 26												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	26697	814.7	26705	815.5	26715	816.5	26740	819	26765	821.5	26765	821.5
M	26865	831.5	26865	831.5	26865	831.5	26865	831.5	26865	831.5	26865	831.5
H	27033	848.3	27025	847.5	27015	846.5	26990	844	26965	841.5	26965	841.5
LTE Band 38												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	37775	2572.5	37800	2575	37825	2577.5	37850	2580	37850	2580	37850	2580
M	38000	2595	38000	2595	38000	2595	38000	2595	38000	2595	38000	2595
H	38225	2617.5	38200	2615	38175	2612.5	38150	2610	38150	2610	38150	2610
LTE Band 66												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	131979	1710.7	131987	1711.5	131997	1712.5	132022	1715	132047	1717.5	132072	1720
M	132322	1745	132322	1745	132322	1745	132322	1745	132322	1745	132322	1745
H	132665	1779.3	132657	1778.5	132647	1777.5	132622	1775	132597	1772.5	132572	1770

5. Proximity Sensor Triggering Test

<Proximity Sensor Triggering Distance>:

1. Proximity sensor triggering distance testing was performed according to the procedures outlined in KDB 616217 D04 section 6.2, and EUT moving further away from the flat phantom and EUT moving toward the flat phantom were both assessed and the tissue-equivalent medium for highest frequency (5850MHz) and lowest (835MHz) frequency was used for proximity sensor triggering testing.
2. Capacitive proximity sensors placed coincident with antenna elements at the top and bottom ends of the phone are utilized to determine when the device comes in proximity of the user's body at the front or back of the device. The output power will reduce to body worn power level when top and bottom sensor pad be detected.
3. The sensors used to detect the proximity of the user's body at the front or back surface of the device use a detection threshold distance. The data shown in the sections below shows the distance(s). When front or back body worn condition is detected reduced power will be active.
4. The device employs proximity sensors also can detect the presence of the user's a finger or hand when handheld state at the front/back /bottom side of the device. When front/back /bottom side of handheld condition is detected reduced power will be active.
5. For verification of compliance of power reduction scheme, additional SAR testing with EUT transmitting at full RF power at a conservative trigger distance -1mm was performed:



<P-Sensor>

Proximity Sensor Triggering Distance (mm)				
Position	Front		Back	
	Moving towards	Moving away	Moving towards	Moving away
Minimum	15	15	19	19

<Handheld for ANT1>

Proximity Sensor Triggering Distance (mm)						
Position	Front		Back		Bottom Side	
	Moving towards	Moving away	Moving towards	Moving away	Moving towards	Moving away
Minimum	5	5	8	8	14	14

6. RF Exposure Limits

6.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

6.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

7. Specific Absorption Rate (SAR)

7.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

7.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$\text{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

8. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:




- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

8.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG).The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – >6 GHz Linearity: ±0.2 dB (30 MHz – 6 GHz)	
Directivity	±0.3 dB in TSL (rotation around probe axis) ±0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 µW/g – >100 mW/g Linearity: ±0.2 dB (noise: typically <1 µW/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

8.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.


The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Photo of DAE


8.3 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

8.4 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

9. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

9.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

9.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

9.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0 is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{Area}, \Delta y_{Area}$	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be \leq the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

9.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

		≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}		≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$	≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$
Minimum zoom scan volume	x, y, z	≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details. * When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.			

9.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

9.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.



10. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	750MHz System Validation Kit	D750V3	1087	2019/3/27	2022/3/24
SPEAG	835MHz System Validation Kit	D835V2	4d258	2020/5/7	2023/5/6
SPEAG	1750MHz System Validation Kit	D1750V2	1090	2019/3/27	2022/3/25
SPEAG	1900MHz System Validation Kit	D1900V2	5d170	2019/3/26	2022/3/24
SPEAG	2450MHz System Validation Kit	D2450V2	924	2020/9/2	2023/9/1
SPEAG	2600MHz System Validation Kit	D2600V2	1061	2020/11/26	2023/11/25
SPEAG	5000MHz System Validation Kit	D5GHzV2	1113	2019/9/24	2022/9/22
SPEAG	Data Acquisition Electronics	DAE4	1210	2021/8/25	2022/8/24
SPEAG	Dosimetric E-Field Probe	EX3DV4	3975	2021/6/7	2022/6/6
SPEAG	SAM Twin Phantom	QD 000 P40 CD	1671	NCR	NCR
Anritsu	Radio communication analyzer	MT8820C	6201300653	2021/7/14	2022/7/13
Anritsu	Radio communication analyzer	MT8821C	6262314715	2021/6/29	2022/6/28
Agilent	Wireless Communication Test Set	E5515C	MY50267224	2021/7/14	2022/7/13
Agilent	Network Analyzer	E5071C	MY46523671	2021/10/25	2022/10/24
Speag	Dielectric Assessment KIT	DAK-3.5	1138	2021/6/9	2022/6/8
Agilent	Signal Generator	N5181A	MY50145381	2021/12/28	2022/12/27
Agilent	Vector Signal Generator	MG3710A	6201682672	2021/1/7	2022/1/6
Anritsu	Power Sensor	MA2411B	1306099	2021/9/29	2022/9/28
Anritsu	Power Meter	ML2495A	1349001	2021/9/29	2022/9/28
R&S	Power Sensor	NRP50S	101254	2021/4/9	2022/4/8
R&S	Power Sensor	NRP8S	109228	2021/4/9	2022/4/8
R&S	CBT BLUETOOTH TESTER	CBT	101246	2021/4/12	2022/4/11
R&S	Spectrum Analyzer	FSP7	100818	2021/7/14	2022/7/13
TES	Hygrometer	1310	200505600	2021/7/17	2022/7/16
Anymetre	Thermo-Hygrometer	JR593	2015030904	2021/7/17	2022/7/16
SPEAG	Device Holder	N/A	N/A	N/A	N/A
AR	Amplifier	5S1G4	0333096	Note 1	
mini-circuits	Amplifier	ZVE-3W-83+	599201528	Note 1	
ARRA	Power Divider	A3200-2	N/A	Note 1	
ET Industries	Dual Directional Coupler	C-058-10	N/A	Note 1	
Weinschel	Attenuator 1	3M-10	N/A	Note 1	
Weinschel	Attenuator 2	3M-20	N/A	Note 1	

Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check
2. Referring to KDB 865664 D01v01r04, the dipole calibration interval can be extended to 3 years with justification. The dipoles are also not physically damaged, or repaired during the interval.
3. The justification data of dipole can be found in appendix C. The return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration.

11. System Verification

11.1 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 11.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 11.2.




Fig 11.1 Photo of Liquid Height for Head SAR



Fig 11.2 Photo of Liquid Height for Body SAR

11.2 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
For Head								
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
1800, 1900	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0

Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
750	Head	22.7	0.881	40.783	0.89	41.90	-1.01	-2.67	±5	2021/12/11
835	Head	22.8	0.916	42.677	0.90	41.50	1.78	2.84	±5	2021/12/12
1750	Head	22.5	1.378	40.204	1.37	40.10	0.58	0.26	±5	2021/12/10
1900	Head	22.9	1.440	40.038	1.40	40.00	2.86	0.09	±5	2021/12/8
2450	Head	22.2	1.823	37.953	1.80	39.20	1.28	-3.18	±5	2022/1/7
2600	Head	22.6	1.992	40.445	1.96	39.00	1.63	3.71	±5	2021/12/5
5250	Head	22.5	4.748	36.881	4.71	35.95	0.81	2.59	±5	2022/1/3
5250	Head	22.8	4.757	36.931	4.71	35.95	1.00	2.73	±5	2022/1/8
5600	Head	22.6	5.189	36.130	5.07	35.50	2.35	1.77	±5	2022/1/4
5600	Head	22.6	5.048	36.534	5.07	35.50	-0.43	2.91	±5	2022/1/9
5750	Head	22.7	5.364	35.845	5.22	35.35	2.76	1.40	±5	2022/1/8
5750	Head	22.7	4.989	35.458	5.22	35.35	-4.43	0.31	±5	2022/1/11



11.3 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

<1g SAR>

Table with 11 columns: Date, Frequency (MHz), Tissue Type, Input Power (mW), Dipole S/N, Probe S/N, DAE S/N, Measured 1g SAR (W/kg), Targeted 1g SAR (W/kg), Normalized 1g SAR (W/kg), Deviation (%). Rows include test data from 2021/12/11 to 2022/1/11.

<10g SAR>

Table with 11 columns: Date, Frequency (MHz), Tissue Type, Input Power (mW), Dipole S/N, Probe S/N, DAE S/N, Measured 10g SAR (W/kg), Targeted 10g SAR (W/kg), Normalized 10g SAR (W/kg), Deviation (%). Rows include test data from 2021/12/11 to 2022/1/11.




Fig 11.3.1 System Performance Check Setup



Fig 11.3.2 Setup Photo

12. RF Exposure Positions

12.1 Ear and handset reference point

Figure 12.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M,” the left ear reference point (ERP) is marked “LE,” and the right ERP is marked “RE.” Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 12.1.2 The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 12.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 12.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.




Fig 12.1.1 Front, back, and side views of SAM twin phantom




Fig 12.1.2 Close-up side view of phantom showing the ear region.




Fig 12.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

12.2 Definition of the cheek position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 12.2.1 and Figure 12.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 12.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 12.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 12.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 12.2.3. The actual rotation angles should be documented in the test report.




Fig 12.2.1 Handset vertical and horizontal reference lines—“fixed case”




Fig 12.2.2 Handset vertical and horizontal reference lines—“clam-shell case”




Fig 12.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

12.3 Definition of the tilt position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°.
3. Rotate the handset around the horizontal line by 15°.
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 12.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




Fig 12.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.

12.4 Body Worn Accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 12.4). Per KDB648474 D04v01r03, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Fig 12.4 Body Worn Position

12.5 Product Specific 10g SAR Exposure

For smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, According to KDB648474 D04v01r03, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance

1. The normally required head and body-worn accessory SAR test procedures for handsets, including hotspot mode, must be applied.
2. The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions.6 The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.

12.6 Wireless Router

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v02r01 where SAR test considerations for handsets ($L \times W \geq 9$ cm x 5 cm) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

13. Conducted RF Output Power (Unit: dBm)

The detailed conducted power table can refer to Appendix E.

<GSM Conducted Power>

1. Per KDB 447498 D01v06, the maximum output power channel is used for SAR testing and for further SAR test reduction.
2. Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the GPRS 2Tx slots for GSM850 and GSM1900 are considered as the primary mode.
3. Other configurations of GSM / GPRS / EDGE are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode, SAR measurement is not required for the secondary mode.

<WCDMA Conducted Power>

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01v03r01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.
3. For DC-HSDPA, the device was configured according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1, with the primary and the secondary serving HS-DSCH Cell enabled during the power measurement.

A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2Kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{HS} = 24/15 * \beta_c$.

Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{HS}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.

Setup Configuration

HSUPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - iii. Set Cell Power = -86 dBm
 - iv. Set Channel Type = 12.2k + HSPA
 - v. Set UE Target Power
 - vi. Power Ctrl Mode= Alternating bits
 - vii. Set and observe the E-TFCI
 - viii. Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- d. The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note1)	β_{ec}	β_{ed} (Note 4) (Note 5)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2) (Note 6)	AG Index (Note 5)	E-TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1} : 47/15 β_{ed2} : 47/15	4 4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15	0	-	-	5/15	5/15	47/15	4	1	1.0	0.0	12	67

Note 1: For sub-test 1 to 4, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. For sub-test 5, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 5/15$ with $\beta_{hs} = 5/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS- DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF0) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 5: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Note 6: For subtests 2, 3 and 4, UE may perform E-DPDCH power scaling at max power which could results in slightly smaller MPR values.

Setup Configuration

DC-HSDPA 3GPP release 8 Setup Configuration:

- a. The EUT was connected to Base Station referred to the Setup Configuration below
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set RMC 12.2Kbps + HSDPA mode.
 - ii. Set Cell Power = -25 dBm
 - iii. Set HS-DSCH Configuration Type to FRC (H-set 12, QPSK)
 - iv. Select HSDPA Uplink Parameters
 - v. Set Gain Factors (β_c and β_d) and parameters were set according to each Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - a). Subtest 1: $\beta_c/\beta_d=2/15$
 - b). Subtest 2: $\beta_c/\beta_d=12/15$
 - c). Subtest 3: $\beta_c/\beta_d=15/8$
 - d). Subtest 4: $\beta_c/\beta_d=15/4$
 - vi. Set Delta ACK, Delta NACK and Delta CQI = 8
 - vii. Set Ack-Nack Repetition Factor to 3
 - viii. Set CQI Feedback Cycle (k) to 4 ms
 - ix. Set CQI Repetition Factor to 2
 - x. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification. A summary of these settings are illustrated below:

C.8.1.12 Fixed Reference Channel Definition H-Set 12

Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table. Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		




Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)

Setup Configuration



<WCDMA Conducted Power>

General Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSDPA / HSUPA / DC-HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA


<LTE Conducted Power>

General Note:

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r05, for QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r05, 16QAM/64QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM/64QAM SAR testing is not required.
7. Per KDB 941225 D05v02r05, smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
8. For LTE B4 / B5 / B26 / B38 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
9. LTE B4/B5 SAR test was covered by B66/B26; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. the maximum output power, including tolerance, for the smaller band is \leq the larger band to qualify for the SAR test exclusion
 - b. the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band
10. According to 2017 TCB workshop, for 64 QAM and 16 QAM should be verified by checking the signal constellation with a call box to avoid incorrect maximum power levels due to MPR and other requirements associated with signal modulation, and the following figure is taken from the "Fundamental Measurement >> Modulation Analysis >> constellation" mode of the device connect to the MT8821C base station, therefore, the device 64QAM and 16QAM signal modulation are correct.



64QAM



16QAM

<TDD LTE SAR Measurement>

TDD LTE configuration setup for SAR measurement

SAR was tested with a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by 3GPP.

- a. 3GPP TS 36.211 section 4.2 for Type 2 Frame Structure and Table 4.2-2 for uplink-downlink configurations
- b. "special subframe S" contains both uplink and downlink transmissions, it has been taken into consideration to determine the transmission duty factor according to the worst case uplink and downlink cyclic prefix requirements for UpPTS
- c. Establishing connections with base station simulators ensure a consistent means for testing SAR and recommended for evaluating SAR. The Anritsu MT8820C (firmware: #22.52#004) was used for LTE output power measurements and SAR testing.




Figure 4.2-1: Frame structure type 2 (for 5 ms switch-point periodicity).

Table 4.2-2: Uplink-downlink configurations.

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS).

Special subframe configuration	Normal cyclic prefix in downlink			Extended cyclic prefix in downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	6592 · Ts	2192 · Ts	2560 · Ts	7680 · Ts	2192 · Ts	2560 · Ts
1	19760 · Ts			20480 · Ts		
2	21952 · Ts			23040 · Ts		
3	24144 · Ts			25600 · Ts		
4	26336 · Ts	4384 · Ts	5120 · Ts	7680 · Ts	4384 · Ts	5120 · Ts
5	6592 · Ts			20480 · Ts		
6	19760 · Ts			23040 · Ts		
7	21952 · Ts			12800 · Ts		
8	24144 · Ts	-	-	-	-	-
9	13168 · Ts	-	-	-	-	-

Special subframe (30720·T _s): Normal cyclic prefix in downlink (UpPTS)			
	Special subframe configuration	Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
Uplink duty factor in one special subframe	0~4	7.13%	8.33%
	5~9	14.3%	16.7%

Special subframe(30720·T _s): Extended cyclic prefix in downlink (UpPTS)			
	Special subframe configuration	Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
Uplink duty factor in one special subframe	0~3	7.13%	8.33%
	4~7	14.3%	16.7%

The highest duty factor is resulted from:

For LTE Band 41 Power class 3

- i. Uplink-downlink configuration: 0. In a half-frame consisted of 5 subframes, uplink operation is in 3 uplink subframes and 1 special subframe.
- ii. special subframe configuration: 5-9 for normal cyclic prefix in downlink, 4-7 for extended cyclic prefix in downlink
- iii. for special subframe with extended cyclic prefix in uplink, the total uplink duty factor in one half-frame is: $(3+0.167)/5 = 63.3\%$
- iv. for special subframe with normal cyclic prefix in uplink, the total uplink duty factor in one half-frame is: $(3+0.143)/5 = 62.9\%$
- v. For TDD LTE SAR measurement, the duty cycle 1:1.59 (62.9 %) was used perform testing and considering the theoretical duty cycle of 63.3% for extended cyclic prefix in the uplink, and the theoretical duty cycle of 62.9% for normal cyclic prefix in uplink, a scaling factor of extended cyclic prefix $63.3\%/62.9\% = 1.006$ is applied to scale-up the measured SAR result. The scaled TDD LTE SAR = measured SAR (W/kg)* Tune-up Scaling Factor* scaling factor for extended cyclic prefix.

<WLAN Conducted Power>

General Note:


1. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
2. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
3. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
4. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures.18 The initial test position procedure is described in the following:
 - a. When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
 - b. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
 - c. For all positions/configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.



<2.4GHz Bluetooth>

General Note:

1. For 2.4GHz Bluetooth SAR testing was selected 1Mbps, due to its highest average power.
2. The Bluetooth duty cycle is 76.91 % as following figure, according to 2016 Oct. TCB workshop for Bluetooth SAR scaling need further consideration and the maximum duty cycle is 100%, therefore the actual duty cycle will be scaled up to100% for Bluetooth reported SAR calculation





14. Antenna Location

The detailed antenna location information can refer to SAR Test Setup Photos.

15. SAR Test Results

General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of BT/WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - c. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
 - d. For BT/WLAN: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
 - e. For TDD LTE SAR measurement of power class 3, the duty cycle 1:1.59 (62.9 %) was used perform testing and considering the theoretical duty cycle of 63.3% for extended cyclic prefix in the uplink, and the theoretical duty cycle of 62.9% for normal cyclic prefix in uplink, a scaling factor of extended cyclic prefix $63.3\%/62.9\% = 1.006$ is applied to scale-up the measured SAR result. The Reported TDD LTE SAR = measured SAR (W/kg)* Tune-up Scaling Factor* scaling factor for extended cyclic prefix.
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required when the measured SAR is ≥ 0.8 W/kg. Per KDB 865664 D01v01r04, if the extremity repeated SAR is necessary, the same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.
4. The device implements the power management and proximity sensor /receiver detection/hotspot mode for SAR compliance at different exposure conditions (head, body-worn, hotspot, extremity) and the details about the power management decision and sensor detection are provided in the operational description. And the device will invoke corresponding work scenarios power level base on frequency bands/antennas, which can refer to power table at appendix E.
5. For some WWAN bands, sensor on reduced power level is higher than hotspot reduced power level, so front/back sensor on SAR can represent hotspot conservatively.
6. For dual SIM card mobile has two SIM slots and supports dual SIM dual standby. The WWAN radio transmission will be enabled by either one SIM at a time (single active). After pre-scan two SIM cards power, we found test result of the SIM1 was the worse, so we chose SIM1 slot to perform all tests.
7. There are four samples. The difference between them could be referred to the XT2231-1, XT2231-5_Operational Description of Product Equality Declaration which is exhibited separately. According to the difference, we choose sample 1 for full testing and sample 2/3/4 for worst case verification.
8. The device has three headsets. For three headsets only suppliers are different. So we chose headset 1 to perform full SAR testing only.
9. This device has two batteries. For battery 1 was in sample 1/2, and battery 2 was in sample 3/4. They were all evaluated for SAR testing conservatively.
10. Per KDB648474 D04v01r03, for smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm, when hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg, however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold.
 - a. For this device SAR for WWAN/WLAN transmitter scaled to maximum output power mode for product specific 10g SAR is higher than 1.2W/kg of GSM850/1900, WCDMA Band II/IV/V, LTE Band2/4/5/7/26/66/38, WLAN 2.4GHz/5.2GHz/5.8GHz, therefore product specific 10g SAR is necessary.
 - b. WLAN 5.3/5.5GHz tested the product specific 10g SAR since it has no hotspot mode.
 - c. When 10-g product specific 10g SAR is considered, SAR thresholds is specified in the procedures for SAR test reduction and exclusion should be multiplied by 2.5.
11. For distance SAR and non-distance SAR in body-worn, always chose higher SAR to do co-located analysis.
12. For WLAN 5G distance SAR test at Front 4mm and Back 7mm is only for simultaneous transmission analysis with WWAN.

GSM Note:

1. Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the GPRS 2Tx slots for GSM850 and GSM1900 are considered as the primary mode.
2. Other configurations of GSM / GPRS / EDGE are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode, SAR measurement is not required for the secondary mode.

WCDMA Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSDPA / HSUPA / DC-HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

LTE Note:

1. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
2. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
3. Per KDB 941225 D05v02r05, for QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
4. Per KDB 941225 D05v02r05, 16QAM/64QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM/64QAM SAR testing is not required.
5. Per KDB 941225 D05v02r05, smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
6. For LTE B4 / B5 / B26 / B38 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
7. LTE B4/B5 SAR test was covered by B66/B26; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. the maximum output power, including tolerance, for the smaller band is \leq the larger band to qualify for the SAR test exclusion
 - b. the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band

WLAN Note:

1. Per KDB 248227 D01v02r02, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
2. Per KDB 248227 D01v02r02, U-NII-1 SAR testing is not required when the U-NII-2A band highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band.
3. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
4. For all positions / configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
5. During SAR testing the WLAN transmission was verified using a spectrum analyzer.



15.1 Head SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
01	GSM850	GPRS 2 Tx slots	Right Cheek	0mm	Full	251	848.8	1	30.96	32.00	1.271	0.1	0.422	0.536
	GSM850	GPRS 2 Tx slots	Right Cheek	0mm	Full	251	848.8	2	30.96	32.00	1.271	-0.03	0.378	0.480
	GSM850	GPRS 2 Tx slots	Right Cheek	0mm	Full	251	848.8	3	30.96	32.00	1.271	-0.07	0.417	0.530
	GSM850	GPRS 2 Tx slots	Right Cheek	0mm	Full	251	848.8	4	30.96	32.00	1.271	0.02	0.406	0.516
	GSM850	GPRS 2 Tx slots	Right Tilted	0mm	Full	251	848.8	1	30.96	32.00	1.271	0.06	0.211	0.268
	GSM850	GPRS 2 Tx slots	Left Cheek	0mm	Full	251	848.8	1	30.96	32.00	1.271	0.08	0.307	0.390
	GSM850	GPRS 2 Tx slots	Left Tilted	0mm	Full	251	848.8	1	30.96	32.00	1.271	-0.05	0.186	0.236
02	GSM1900	GPRS 2 Tx slots	Right Cheek	0mm	Full	661	1880	1	27.94	29.50	1.432	0.14	0.247	0.354
	GSM1900	GPRS 2 Tx slots	Right Tilted	0mm	Full	661	1880	1	27.94	29.50	1.432	0.06	0.092	0.132
	GSM1900	GPRS 2 Tx slots	Left Cheek	0mm	Full	661	1880	1	27.94	29.50	1.432	0.07	0.125	0.179
	GSM1900	GPRS 2 Tx slots	Left Tilted	0mm	Full	661	1880	1	27.94	29.50	1.432	0.11	0.140	0.201

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
03	WCDMA V	RMC 12.2Kbps	Right Cheek	0mm	Full	4182	836.4	1	22.82	24.00	1.312	-0.17	0.320	0.420
	WCDMA V	RMC 12.2Kbps	Right Tilted	0mm	Full	4182	836.4	1	22.82	24.00	1.312	-0.08	0.207	0.272
	WCDMA V	RMC 12.2Kbps	Left Cheek	0mm	Full	4182	836.4	1	22.82	24.00	1.312	-0.09	0.283	0.371
	WCDMA V	RMC 12.2Kbps	Left Tilted	0mm	Full	4182	836.4	1	22.82	24.00	1.312	0.01	0.150	0.197
04	WCDMA IV	RMC 12.2Kbps	Right Cheek	0mm	Full	1413	1732.6	1	23.02	24.00	1.253	0.07	0.202	0.253
	WCDMA IV	RMC 12.2Kbps	Right Tilted	0mm	Full	1413	1732.6	1	23.02	24.00	1.253	0.03	0.070	0.088
	WCDMA IV	RMC 12.2Kbps	Left Cheek	0mm	Full	1413	1732.6	1	23.02	24.00	1.253	0.05	0.090	0.113
	WCDMA IV	RMC 12.2Kbps	Left Tilted	0mm	Full	1413	1732.6	1	23.02	24.00	1.253	0.18	0.078	0.098
05	WCDMA II	RMC 12.2Kbps	Right Cheek	0mm	Full	9400	1880	1	22.80	24.00	1.318	0.17	0.398	0.525
	WCDMA II	RMC 12.2Kbps	Right Cheek	0mm	Full	9400	1880	2	22.80	24.00	1.318	-0.08	0.357	0.471
	WCDMA II	RMC 12.2Kbps	Right Cheek	0mm	Full	9400	1880	3	22.80	24.00	1.318	-0.07	0.374	0.493
	WCDMA II	RMC 12.2Kbps	Right Cheek	0mm	Full	9400	1880	4	22.80	24.00	1.318	0.1	0.322	0.424
	WCDMA II	RMC 12.2Kbps	Right Tilted	0mm	Full	9400	1880	1	22.80	24.00	1.318	-0.13	0.170	0.224
	WCDMA II	RMC 12.2Kbps	Left Cheek	0mm	Full	9400	1880	1	22.80	24.00	1.318	0.05	0.219	0.289
	WCDMA II	RMC 12.2Kbps	Left Tilted	0mm	Full	9400	1880	1	22.80	24.00	1.318	-0.03	0.245	0.323



<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
06	LTE Band 13	10M	QPSK	1	25	Right Cheek	0mm	Full	23230	782	1	23.10	24.00	1.230	0.12	0.223	0.274
	LTE Band 13	10M	QPSK	1	25	Right Tilted	0mm	Full	23230	782	1	23.10	24.00	1.230	-0.05	0.139	0.171
	LTE Band 13	10M	QPSK	1	25	Left Cheek	0mm	Full	23230	782	1	23.10	24.00	1.230	-0.06	0.222	0.273
	LTE Band 13	10M	QPSK	1	25	Left Tilted	0mm	Full	23230	782	1	23.10	24.00	1.230	0.01	0.155	0.191
	LTE Band 13	10M	QPSK	25	0	Right Cheek	0mm	Full	23230	782	1	21.98	23.00	1.265	0.13	0.199	0.252
	LTE Band 13	10M	QPSK	25	0	Right Tilted	0mm	Full	23230	782	1	21.98	23.00	1.265	0.02	0.125	0.158
	LTE Band 13	10M	QPSK	25	0	Left Cheek	0mm	Full	23230	782	1	21.98	23.00	1.265	0.06	0.199	0.252
	LTE Band 13	10M	QPSK	25	0	Left Tilted	0mm	Full	23230	782	1	21.98	23.00	1.265	-0.03	0.129	0.163
07	LTE Band 26	15M	QPSK	1	37	Right Cheek	0mm	Full	26865	831.5	1	23.00	24.00	1.259	0.14	0.365	0.460
	LTE Band 26	15M	QPSK	1	37	Right Tilted	0mm	Full	26865	831.5	1	23.00	24.00	1.259	-0.02	0.187	0.235
	LTE Band 26	15M	QPSK	1	37	Left Cheek	0mm	Full	26865	831.5	1	23.00	24.00	1.259	0.05	0.288	0.363
	LTE Band 26	15M	QPSK	1	37	Left Tilted	0mm	Full	26865	831.5	1	23.00	24.00	1.259	0.08	0.182	0.229
	LTE Band 26	15M	QPSK	36	0	Right Cheek	0mm	Full	26865	831.5	1	21.96	23.00	1.271	-0.02	0.232	0.295
	LTE Band 26	15M	QPSK	36	0	Right Tilted	0mm	Full	26865	831.5	1	21.96	23.00	1.271	0.04	0.140	0.178
	LTE Band 26	15M	QPSK	36	0	Left Cheek	0mm	Full	26865	831.5	1	21.96	23.00	1.271	0.06	0.219	0.278
	LTE Band 26	15M	QPSK	36	0	Left Tilted	0mm	Full	26865	831.5	1	21.96	23.00	1.271	0.11	0.140	0.178
08	LTE Band 66	20M	QPSK	1	49	Right Cheek	0mm	Full	132322	1745	1	23.33	24.00	1.167	-0.03	0.201	0.235
	LTE Band 66	20M	QPSK	1	49	Right Tilted	0mm	Full	132322	1745	1	23.33	24.00	1.167	0.06	0.103	0.120
	LTE Band 66	20M	QPSK	1	49	Left Cheek	0mm	Full	132322	1745	1	23.33	24.00	1.167	-0.02	0.117	0.137
	LTE Band 66	20M	QPSK	1	49	Left Tilted	0mm	Full	132322	1745	1	23.33	24.00	1.167	0.01	0.110	0.128
	LTE Band 66	20M	QPSK	50	0	Right Cheek	0mm	Full	132322	1745	1	22.27	23.00	1.183	0.14	0.115	0.136
	LTE Band 66	20M	QPSK	50	0	Right Tilted	0mm	Full	132322	1745	1	22.27	23.00	1.183	0.02	0.084	0.099
	LTE Band 66	20M	QPSK	50	0	Left Cheek	0mm	Full	132322	1745	1	22.27	23.00	1.183	0.09	0.095	0.113
	LTE Band 66	20M	QPSK	50	0	Left Tilted	0mm	Full	132322	1745	1	22.27	23.00	1.183	-0.05	0.088	0.104
09	LTE Band 2	20M	QPSK	1	49	Right Cheek	0mm	Full	18900	1880	1	22.92	24.00	1.282	0.19	0.288	0.369
	LTE Band 2	20M	QPSK	1	49	Right Tilted	0mm	Full	18900	1880	1	22.92	24.00	1.282	-0.03	0.190	0.244
	LTE Band 2	20M	QPSK	1	49	Left Cheek	0mm	Full	18900	1880	1	22.92	24.00	1.282	0.02	0.231	0.296
	LTE Band 2	20M	QPSK	1	49	Left Tilted	0mm	Full	18900	1880	1	22.92	24.00	1.282	0.04	0.273	0.350
	LTE Band 2	20M	QPSK	50	0	Right Cheek	0mm	Full	18900	1880	1	21.90	23.00	1.288	0.09	0.285	0.367
	LTE Band 2	20M	QPSK	50	0	Right Tilted	0mm	Full	18900	1880	1	21.90	23.00	1.288	-0.04	0.162	0.209
	LTE Band 2	20M	QPSK	50	0	Left Cheek	0mm	Full	18900	1880	1	21.90	23.00	1.288	0.02	0.229	0.295
	LTE Band 2	20M	QPSK	50	0	Left Tilted	0mm	Full	18900	1880	1	21.90	23.00	1.288	0.06	0.260	0.335
10	LTE Band 7	20M	QPSK	1	49	Right Cheek	0mm	Full	21100	2535	1	22.69	24.00	1.352	0.01	0.135	0.183
	LTE Band 7	20M	QPSK	1	49	Right Tilted	0mm	Full	21100	2535	1	22.69	24.00	1.352	-0.03	0.026	0.035
	LTE Band 7	20M	QPSK	1	49	Left Cheek	0mm	Full	21100	2535	1	22.69	24.00	1.352	0.05	0.075	0.101
	LTE Band 7	20M	QPSK	1	49	Left Tilted	0mm	Full	21100	2535	1	22.69	24.00	1.352	-0.02	0.050	0.068
	LTE Band 7	20M	QPSK	50	0	Right Cheek	0mm	Full	21100	2535	1	21.46	23.00	1.426	0.09	0.075	0.107
	LTE Band 7	20M	QPSK	50	0	Right Tilted	0mm	Full	21100	2535	1	21.46	23.00	1.426	0.04	0.024	0.034
	LTE Band 7	20M	QPSK	50	0	Left Cheek	0mm	Full	21100	2535	1	21.46	23.00	1.426	0.02	0.066	0.094
	LTE Band 7	20M	QPSK	50	0	Left Tilted	0mm	Full	21100	2535	1	21.46	23.00	1.426	0.01	0.035	0.050



<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
11	LTE Band 38	20M	QPSK	1	49	Right Cheek	0mm	Full	38000	2595	1	23.26	24.00	1.186	62.9	1.006	0.05	0.055	0.066
	LTE Band 38	20M	QPSK	1	49	Right Tilted	0mm	Full	38000	2595	1	23.26	24.00	1.186	62.9	1.006	-0.02	0.022	0.026
	LTE Band 38	20M	QPSK	1	49	Left Cheek	0mm	Full	38000	2595	1	23.26	24.00	1.186	62.9	1.006	0.04	0.043	0.051
	LTE Band 38	20M	QPSK	1	49	Left Tilted	0mm	Full	38000	2595	1	23.26	24.00	1.186	62.9	1.006	0.02	0.042	0.050
	LTE Band 38	20M	QPSK	50	0	Right Cheek	0mm	Full	38000	2595	1	22.20	23.00	1.202	62.9	1.006	-0.08	0.053	0.064
	LTE Band 38	20M	QPSK	50	0	Right Tilted	0mm	Full	38000	2595	1	22.20	23.00	1.202	62.9	1.006	0.02	0.017	0.021
	LTE Band 38	20M	QPSK	50	0	Left Cheek	0mm	Full	38000	2595	1	22.20	23.00	1.202	62.9	1.006	0.01	0.033	0.040
	LTE Band 38	20M	QPSK	50	0	Left Tilted	0mm	Full	38000	2595	1	22.20	23.00	1.202	62.9	1.006	0.03	0.031	0.037

<WLAN2.4G SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	Full	6	2437	1	19.10	20.00	1.230	99.27	1.007	0.08	0.441	0.546
	WLAN2.4GHz	802.11b 1Mbps	Right Tilted	0mm	Full	6	2437	1	19.10	20.00	1.230	99.27	1.007	0.03	0.536	0.664
	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	Full	6	2437	1	19.10	20.00	1.230	99.27	1.007	0.04	0.774	0.959
	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	Full	11	2462	1	18.90	20.00	1.288	99.27	1.007	0.01	0.780	1.012
	WLAN2.4GHz	802.11b 1Mbps	Left Tilted	0mm	Full	6	2437	1	19.10	20.00	1.230	99.27	1.007	0.02	0.782	0.969
12	WLAN2.4GHz	802.11b 1Mbps	Left Tilted	0mm	Full	11	2462	1	18.90	20.00	1.288	99.27	1.007	-0.08	0.796	1.033

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	DH5 1Mbps	Right Cheek	0mm	Full	78	2480	1	10.50	12.00	1.413	76.91	1.300	0.02	0.013	0.024
	Bluetooth	DH5 1Mbps	Right Tilted	0mm	Full	78	2480	1	10.50	12.00	1.413	76.91	1.300	0.04	0.010	0.018
13	Bluetooth	DH5 1Mbps	Left Cheek	0mm	Full	78	2480	1	10.50	12.00	1.413	76.91	1.300	0.16	0.022	0.040
	Bluetooth	DH5 1Mbps	Left Tilted	0mm	Full	78	2480	1	10.50	12.00	1.413	76.91	1.300	0.06	0.019	0.035



<WLAN5G SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN5.3GHz	802.11ac-VHT80 MCS0	Right Cheek	0mm	Reduced	58	5290	1	11.00	12.00	1.259	87.77	1.139	0.08	0.285	0.409
	WLAN5.3GHz	802.11ac-VHT80 MCS0	Right Tilted	0mm	Reduced	58	5290	1	11.00	12.00	1.259	87.77	1.139	-0.05	0.340	0.488
	WLAN5.3GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	Reduced	58	5290	1	11.00	12.00	1.259	87.77	1.139	0.04	0.458	0.657
14	WLAN5.3GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Reduced	58	5290	1	11.00	12.00	1.259	87.77	1.139	-0.12	0.707	1.014
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Right Cheek	0mm	Reduced	122	5610	1	11.41	12.00	1.146	87.77	1.139	0.02	0.278	0.363
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Right Tilted	0mm	Reduced	122	5610	1	11.41	12.00	1.146	87.77	1.139	0.06	0.349	0.455
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	Reduced	122	5610	1	11.41	12.00	1.146	87.77	1.139	0.02	0.468	0.611
15	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Reduced	122	5610	1	11.41	12.00	1.146	87.77	1.139	0.03	0.806	1.052
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Reduced	122	5610	2	11.41	12.00	1.146	87.77	1.139	-0.12	0.627	0.818
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Reduced	122	5610	3	11.41	12.00	1.146	87.77	1.139	0.08	0.588	0.767
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Reduced	122	5610	4	11.41	12.00	1.146	87.77	1.139	0.11	0.438	0.571
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Reduced	138	5690	1	11.37	12.00	1.156	87.77	1.139	0.02	0.530	0.698
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Right Cheek	0mm	Reduced	155	5775	1	10.70	11.50	1.202	87.77	1.139	0.07	0.267	0.366
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Right Tilted	0mm	Reduced	155	5775	1	10.70	11.50	1.202	87.77	1.139	-0.03	0.320	0.438
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	Reduced	155	5775	1	10.70	11.50	1.202	87.77	1.139	0.09	0.360	0.493
16	WLAN5.8GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Reduced	155	5775	1	10.70	11.50	1.202	87.77	1.139	0.02	0.758	1.038



15.2 Hotspot SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS 2 Tx slots	Front	5mm	Reduced	251	848.8	1	28.95	30.00	1.274	0.08	0.460	0.586
17	GSM850	GPRS 2 Tx slots	Back	5mm	Reduced	251	848.8	1	28.95	30.00	1.274	0.09	0.968	1.233
	GSM850	GPRS 2 Tx slots	Back	5mm	Reduced	251	848.8	2	28.95	30.00	1.274	0.06	0.939	1.196
	GSM850	GPRS 2 Tx slots	Back	5mm	Reduced	251	848.8	3	28.95	30.00	1.274	0.05	0.959	1.221
	GSM850	GPRS 2 Tx slots	Back	5mm	Reduced	251	848.8	4	28.95	30.00	1.274	0.02	0.895	1.140
	GSM850	GPRS 2 Tx slots	Left Side	5mm	Reduced	251	848.8	1	28.95	30.00	1.274	-0.09	0.331	0.422
	GSM850	GPRS 2 Tx slots	Right Side	5mm	Reduced	251	848.8	1	28.95	30.00	1.274	0.02	0.432	0.550
	GSM850	GPRS 2 Tx slots	Bottom Side	5mm	Reduced	251	848.8	1	28.95	30.00	1.274	0.07	0.310	0.395
	GSM850	GPRS 2 Tx slots	Back	5mm	Reduced	128	824.2	1	28.88	30.00	1.294	0.11	0.721	0.933
	GSM850	GPRS 2 Tx slots	Back	5mm	Reduced	189	836.4	1	28.86	30.00	1.300	0.06	0.795	1.034
	GSM1900	GPRS 2 Tx slots	Front	5mm	Reduced	661	1880	1	24.08	25.50	1.387	-0.02	0.476	0.660
	GSM1900	GPRS 2 Tx slots	Back	5mm	Reduced	661	1880	1	24.08	25.50	1.387	0.04	0.884	1.226
	GSM1900	GPRS 2 Tx slots	Left Side	5mm	Reduced	661	1880	1	22.61	24.00	1.377	0.05	0.168	0.231
	GSM1900	GPRS 2 Tx slots	Right Side	5mm	Reduced	661	1880	1	22.61	24.00	1.377	0.09	0.065	0.089
	GSM1900	GPRS 2 Tx slots	Bottom Side	5mm	Reduced	661	1880	1	22.61	24.00	1.377	0.11	0.905	1.246
	GSM1900	GPRS 2 Tx slots	Bottom Side	5mm	Reduced	512	1850.2	1	22.33	24.00	1.469	0.01	0.810	1.190
	GSM1900	GPRS 2 Tx slots	Bottom Side	5mm	Reduced	810	1909.8	1	22.54	24.00	1.400	0.05	0.737	1.031
18	GSM1900	GPRS 2 Tx slots	Back	5mm	Reduced	512	1850.2	1	23.85	25.50	1.462	0.01	0.968	1.415
	GSM1900	GPRS 2 Tx slots	Back	5mm	Reduced	810	1909.8	1	23.99	25.50	1.416	-0.03	0.934	1.322



<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA V	RMC 12.2Kbps	Front	5mm	Reduced	4182	836.4	1	22.01	23.00	1.256	0.09	0.468	0.588
	WCDMA V	RMC 12.2Kbps	Back	5mm	Reduced	4182	836.4	1	22.01	23.00	1.256	0.08	0.890	1.118
	WCDMA V	RMC 12.2Kbps	Left Side	5mm	Reduced	4182	836.4	1	22.01	23.00	1.256	-0.04	0.449	0.564
	WCDMA V	RMC 12.2Kbps	Right Side	5mm	Reduced	4182	836.4	1	22.01	23.00	1.256	0.05	0.540	0.678
	WCDMA V	RMC 12.2Kbps	Bottom Side	5mm	Reduced	4182	836.4	1	22.01	23.00	1.256	0.13	0.267	0.335
	WCDMA V	RMC 12.2Kbps	Back	5mm	Reduced	4132	826.4	1	21.88	23.00	1.294	0.02	0.785	1.016
19	WCDMA V	RMC 12.2Kbps	Back	5mm	Reduced	4233	846.6	1	22.00	23.00	1.259	0.03	0.945	1.190
	WCDMA IV	RMC 12.2Kbps	Front	5mm	Reduced	1413	1732.6	1	16.62	17.50	1.225	0.04	0.278	0.340
	WCDMA IV	RMC 12.2Kbps	Back	5mm	Reduced	1413	1732.6	1	16.62	17.50	1.225	0.02	0.978	1.198
	WCDMA IV	RMC 12.2Kbps	Left Side	5mm	Reduced	1413	1732.6	1	15.65	16.50	1.216	0.05	0.008	0.010
	WCDMA IV	RMC 12.2Kbps	Right Side	5mm	Reduced	1413	1732.6	1	15.65	16.50	1.216	0.11	0.043	0.052
	WCDMA IV	RMC 12.2Kbps	Bottom Side	5mm	Reduced	1413	1732.6	1	15.65	16.50	1.216	0.09	0.963	1.171
	WCDMA IV	RMC 12.2Kbps	Bottom Side	5mm	Reduced	1312	1712.4	1	15.44	16.50	1.276	-0.05	1.080	1.379
	WCDMA IV	RMC 12.2Kbps	Bottom Side	5mm	Reduced	1513	1752.6	1	15.64	16.50	1.219	0.02	0.884	1.078
20	WCDMA IV	RMC 12.2Kbps	Back	5mm	Reduced	1312	1712.4	1	16.53	17.50	1.250	-0.04	1.120	1.400
	WCDMA IV	RMC 12.2Kbps	Back	5mm	Reduced	1513	1752.6	1	16.58	17.50	1.236	0.11	0.877	1.084
	WCDMA II	RMC 12.2Kbps	Front	5mm	Reduced	9400	1880	1	17.36	18.50	1.300	-0.02	0.355	0.462
	WCDMA II	RMC 12.2Kbps	Back	5mm	Reduced	9400	1880	1	17.36	18.50	1.300	-0.08	0.931	1.210
	WCDMA II	RMC 12.2Kbps	Left Side	5mm	Reduced	9400	1880	1	15.80	17.00	1.318	0.04	0.165	0.218
	WCDMA II	RMC 12.2Kbps	Right Side	5mm	Reduced	9400	1880	1	15.80	17.00	1.318	0.03	0.092	0.121
	WCDMA II	RMC 12.2Kbps	Bottom Side	5mm	Reduced	9400	1880	1	15.80	17.00	1.318	0.08	0.880	1.160
	WCDMA II	RMC 12.2Kbps	Bottom Side	5mm	Reduced	9262	1852.4	1	15.79	17.00	1.321	0.01	0.902	1.192
	WCDMA II	RMC 12.2Kbps	Bottom Side	5mm	Reduced	9538	1907.6	1	15.61	17.00	1.377	0.09	1.010	1.391
	WCDMA II	RMC 12.2Kbps	Back	5mm	Reduced	9262	1852.4	1	17.30	18.50	1.318	-0.05	0.920	1.213
21	WCDMA II	RMC 12.2Kbps	Back	5mm	Reduced	9538	1907.6	1	17.20	18.50	1.349	-0.01	1.070	1.443
	WCDMA II	RMC 12.2Kbps	Back	5mm	Reduced	9538	1907.6	2	17.20	18.50	1.349	-0.08	1.020	1.376
	WCDMA II	RMC 12.2Kbps	Back	5mm	Reduced	9538	1907.6	3	17.20	18.50	1.349	0.07	0.889	1.199
	WCDMA II	RMC 12.2Kbps	Back	5mm	Reduced	9538	1907.6	4	17.20	18.50	1.349	-0.04	0.906	1.222



<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
22	LTE Band 13	10M	QPSK	1	25	Front	5mm	Full	23230	782	1	23.10	24.00	1.230	0.11	0.372	0.458
	LTE Band 13	10M	QPSK	1	25	Back	5mm	Full	23230	782	1	23.10	24.00	1.230	0.13	0.820	1.009
	LTE Band 13	10M	QPSK	1	25	Left Side	5mm	Full	23230	782	1	23.10	24.00	1.230	0.05	0.346	0.426
	LTE Band 13	10M	QPSK	1	25	Right Side	5mm	Full	23230	782	1	23.10	24.00	1.230	-0.05	0.415	0.511
	LTE Band 13	10M	QPSK	1	25	Bottom Side	5mm	Full	23230	782	1	23.10	24.00	1.230	0.01	0.173	0.213
	LTE Band 13	10M	QPSK	25	0	Front	5mm	Full	23230	782	1	21.98	23.00	1.265	0.03	0.297	0.376
	LTE Band 13	10M	QPSK	25	0	Back	5mm	Full	23230	782	1	21.98	23.00	1.265	-0.06	0.613	0.775
	LTE Band 13	10M	QPSK	25	0	Left Side	5mm	Full	23230	782	1	21.98	23.00	1.265	0.13	0.280	0.354
	LTE Band 13	10M	QPSK	25	0	Right Side	5mm	Full	23230	782	1	21.98	23.00	1.265	0.05	0.331	0.419
	LTE Band 13	10M	QPSK	25	0	Bottom Side	5mm	Full	23230	782	1	21.98	23.00	1.265	0.04	0.131	0.166
	LTE Band 13	10M	QPSK	50	0	Back	5mm	Full	23230	782	1	21.95	23.00	1.274	0.06	0.565	0.720
23	LTE Band 26	15M	QPSK	1	37	Front	5mm	Reduced	26865	831.5	1	22.11	23.00	1.227	0.07	0.445	0.546
	LTE Band 26	15M	QPSK	1	37	Back	5mm	Reduced	26865	831.5	1	22.11	23.00	1.227	-0.07	0.974	1.196
	LTE Band 26	15M	QPSK	1	37	Left Side	5mm	Reduced	26865	831.5	1	22.11	23.00	1.227	-0.06	0.368	0.452
	LTE Band 26	15M	QPSK	1	37	Right Side	5mm	Reduced	26865	831.5	1	22.11	23.00	1.227	0.02	0.433	0.531
	LTE Band 26	15M	QPSK	1	37	Bottom Side	5mm	Reduced	26865	831.5	1	22.11	23.00	1.227	0.08	0.327	0.401
	LTE Band 26	15M	QPSK	36	0	Front	5mm	Reduced	26865	831.5	1	21.06	22.00	1.242	0.06	0.425	0.528
	LTE Band 26	15M	QPSK	36	0	Back	5mm	Reduced	26865	831.5	1	21.06	22.00	1.242	0.07	0.856	1.063
	LTE Band 26	15M	QPSK	36	0	Left Side	5mm	Reduced	26865	831.5	1	21.06	22.00	1.242	0.01	0.408	0.507
	LTE Band 26	15M	QPSK	36	0	Right Side	5mm	Reduced	26865	831.5	1	21.06	22.00	1.242	0.04	0.449	0.558
	LTE Band 26	15M	QPSK	36	0	Bottom Side	5mm	Reduced	26865	831.5	1	21.06	22.00	1.242	0.13	0.269	0.334
	LTE Band 26	15M	QPSK	75	0	Back	5mm	Reduced	26865	831.5	1	20.98	22.00	1.265	0.06	0.839	1.061
24	LTE Band 66	20M	QPSK	1	49	Front	5mm	Reduced	132322	1745	1	16.70	17.50	1.202	0.06	0.368	0.442
	LTE Band 66	20M	QPSK	1	49	Back	5mm	Reduced	132322	1745	1	16.70	17.50	1.202	0.08	0.921	1.107
	LTE Band 66	20M	QPSK	1	49	Left Side	5mm	Reduced	132322	1745	1	15.73	16.50	1.194	-0.01	0.006	0.007
	LTE Band 66	20M	QPSK	1	49	Right Side	5mm	Reduced	132322	1745	1	15.73	16.50	1.194	0.06	0.051	0.061
	LTE Band 66	20M	QPSK	1	49	Bottom Side	5mm	Reduced	132322	1745	1	15.73	16.50	1.194	-0.05	1.010	1.206
	LTE Band 66	20M	QPSK	1	49	Bottom Side	5mm	Reduced	132072	1720	1	15.61	16.50	1.227	-0.14	1.110	1.362
	LTE Band 66	20M	QPSK	1	49	Bottom Side	5mm	Reduced	132572	1770	1	15.52	16.50	1.253	0.06	0.989	1.239
	LTE Band 66	20M	QPSK	1	49	Back	5mm	Reduced	132072	1720	1	16.58	17.50	1.236	-0.09	1.060	1.310
	LTE Band 66	20M	QPSK	1	49	Back	5mm	Reduced	132572	1770	1	16.48	17.50	1.265	-0.02	0.890	1.126
	LTE Band 66	20M	QPSK	50	0	Front	5mm	Reduced	132322	1745	1	15.74	16.50	1.191	0.06	0.334	0.398
	LTE Band 66	20M	QPSK	50	0	Back	5mm	Reduced	132322	1745	1	15.74	16.50	1.191	-0.02	0.822	0.979
	LTE Band 66	20M	QPSK	50	0	Left Side	5mm	Reduced	132322	1745	1	14.69	15.50	1.205	0.04	0.003	0.004
	LTE Band 66	20M	QPSK	50	0	Right Side	5mm	Reduced	132322	1745	1	14.69	15.50	1.205	-0.05	0.041	0.049
	LTE Band 66	20M	QPSK	50	0	Bottom Side	5mm	Reduced	132322	1745	1	14.69	15.50	1.205	-0.13	0.843	1.016
	LTE Band 66	20M	QPSK	50	0	Bottom Side	5mm	Reduced	132072	1720	1	14.28	15.50	1.324	0.02	0.896	1.187
	LTE Band 66	20M	QPSK	50	0	Bottom Side	5mm	Reduced	132572	1770	1	14.53	15.50	1.250	0.08	0.726	0.908
	LTE Band 66	20M	QPSK	50	0	Back	5mm	Reduced	132072	1720	1	15.38	16.50	1.294	0.19	0.771	0.998
	LTE Band 66	20M	QPSK	50	0	Back	5mm	Reduced	132572	1770	1	15.53	16.50	1.250	0.06	0.736	0.920
	LTE Band 66	20M	QPSK	100	0	Back	5mm	Reduced	132322	1745	1	15.57	16.50	1.239	0.01	0.765	0.948
	LTE Band 66	20M	QPSK	100	0	Bottom Side	5mm	Reduced	132322	1745	1	14.56	15.50	1.242	0.13	0.772	0.959
25	LTE Band 2	20M	QPSK	1	49	Front	5mm	Reduced	18900	1880	1	17.10	18.50	1.380	0.05	0.555	0.766
	LTE Band 2	20M	QPSK	1	49	Back	5mm	Reduced	18900	1880	1	17.10	18.50	1.380	0.14	1.030	1.422
	LTE Band 2	20M	QPSK	1	49	Left Side	5mm	Reduced	18900	1880	1	15.98	17.00	1.265	-0.04	0.166	0.210
	LTE Band 2	20M	QPSK	1	49	Right Side	5mm	Reduced	18900	1880	1	15.98	17.00	1.265	0.09	0.088	0.111
	LTE Band 2	20M	QPSK	1	49	Bottom Side	5mm	Reduced	18900	1880	1	15.98	17.00	1.265	-0.03	0.894	1.131
	LTE Band 2	20M	QPSK	1	49	Bottom Side	5mm	Reduced	18700	1860	1	15.88	17.00	1.294	-0.12	0.912	1.180
	LTE Band 2	20M	QPSK	1	49	Bottom Side	5mm	Reduced	19100	1900	1	15.76	17.00	1.330	0.06	1.000	1.330
	LTE Band 2	20M	QPSK	1	49	Back	5mm	Reduced	18700	1860	1	17.04	18.50	1.400	0.01	0.898	1.257
	LTE Band 2	20M	QPSK	1	49	Back	5mm	Reduced	19100	1900	1	17.08	18.50	1.387	0.09	0.922	1.279



	LTE Band 2	20M	QPSK	50	0	Front	5mm	Reduced	18900	1880	1	16.07	17.50	1.390	-0.12	0.467	0.649
	LTE Band 2	20M	QPSK	50	0	Back	5mm	Reduced	18900	1880	1	16.07	17.50	1.390	0.15	0.810	1.126
	LTE Band 2	20M	QPSK	50	0	Left Side	5mm	Reduced	18900	1880	1	14.98	16.00	1.265	0.02	0.125	0.158
	LTE Band 2	20M	QPSK	50	0	Right Side	5mm	Reduced	18900	1880	1	14.98	16.00	1.265	0.08	0.069	0.087
	LTE Band 2	20M	QPSK	50	0	Bottom Side	5mm	Reduced	18900	1880	1	14.98	16.00	1.265	0.06	0.730	0.923
	LTE Band 2	20M	QPSK	50	0	Bottom Side	5mm	Reduced	18700	1860	1	14.96	16.00	1.271	0.09	0.702	0.892
	LTE Band 2	20M	QPSK	50	0	Bottom Side	5mm	Reduced	19100	1900	1	14.87	16.00	1.297	-0.04	0.752	0.975
	LTE Band 2	20M	QPSK	50	0	Back	5mm	Reduced	18700	1860	1	16.05	17.50	1.396	0.05	0.737	1.029
	LTE Band 2	20M	QPSK	50	0	Back	5mm	Reduced	19100	1900	1	16.02	17.50	1.406	0.11	0.796	1.119
	LTE Band 2	20M	QPSK	100	0	Back	5mm	Reduced	18900	1880	1	16.04	17.50	1.400	0.13	0.800	1.120
	LTE Band 2	20M	QPSK	100	0	Bottom Side	5mm	Reduced	18900	1880	1	14.93	16.00	1.279	0.02	0.680	0.870
	LTE Band 7	20M	QPSK	1	49	Front	5mm	Reduced	21100	2535	1	13.74	15.00	1.337	0.02	0.387	0.517
	LTE Band 7	20M	QPSK	1	49	Back	5mm	Reduced	21100	2535	1	13.74	15.00	1.337	0.04	0.854	1.141
	LTE Band 7	20M	QPSK	1	49	Left Side	5mm	Reduced	21100	2535	1	12.61	14.00	1.377	-0.05	0.040	0.055
	LTE Band 7	20M	QPSK	1	49	Right Side	5mm	Reduced	21100	2535	1	12.61	14.00	1.377	0.06	0.008	0.011
	LTE Band 7	20M	QPSK	1	49	Bottom Side	5mm	Reduced	21100	2535	1	12.61	14.00	1.377	0.04	0.907	1.249
	LTE Band 7	20M	QPSK	1	49	Bottom Side	5mm	Reduced	20850	2510	1	12.41	14.00	1.442	0.05	0.856	1.234
26	LTE Band 7	20M	QPSK	1	49	Bottom Side	5mm	Reduced	21350	2560	1	12.60	14.00	1.380	-0.02	0.970	1.339
	LTE Band 7	20M	QPSK	1	49	Back	5mm	Reduced	20850	2510	1	13.46	15.00	1.426	0.02	0.726	1.035
	LTE Band 7	20M	QPSK	1	49	Back	5mm	Reduced	21350	2560	1	13.73	15.00	1.340	-0.04	0.995	1.333
	LTE Band 7	20M	QPSK	50	0	Front	5mm	Reduced	21100	2535	1	12.76	14.00	1.330	-0.02	0.302	0.402
	LTE Band 7	20M	QPSK	50	0	Back	5mm	Reduced	21100	2535	1	12.76	14.00	1.330	0.05	0.689	0.917
	LTE Band 7	20M	QPSK	50	0	Left Side	5mm	Reduced	21100	2535	1	11.72	13.00	1.343	0.05	0.032	0.043
	LTE Band 7	20M	QPSK	50	0	Right Side	5mm	Reduced	21100	2535	1	11.72	13.00	1.343	0.09	0.005	0.007
	LTE Band 7	20M	QPSK	50	0	Bottom Side	5mm	Reduced	21100	2535	1	11.72	13.00	1.343	-0.05	0.526	0.706
	LTE Band 7	20M	QPSK	50	0	Bottom Side	5mm	Reduced	20850	2510	1	11.32	13.00	1.472	0.02	0.571	0.841
	LTE Band 7	20M	QPSK	50	0	Bottom Side	5mm	Reduced	21350	2560	1	11.71	13.00	1.346	0.07	0.800	1.077
	LTE Band 7	20M	QPSK	50	0	Back	5mm	Reduced	20850	2510	1	12.73	14.00	1.340	0.01	0.685	0.918
	LTE Band 7	20M	QPSK	50	0	Back	5mm	Reduced	21350	2560	1	12.75	14.00	1.334	-0.11	0.747	0.996
	LTE Band 7	20M	QPSK	100	0	Back	5mm	Reduced	21100	2535	1	12.75	14.00	1.334	0.08	0.611	0.815
	LTE Band 7	20M	QPSK	100	0	Bottom Side	5mm	Reduced	21100	2535	1	11.63	13.00	1.371	0.04	0.706	0.968

<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 38	20M	QPSK	1	49	Front	5mm	Reduced	38000	2595	1	15.89	17.00	1.291	62.9	1.006	0.07	0.453	0.588
27	LTE Band 38	20M	QPSK	1	49	Back	5mm	Reduced	38000	2595	1	15.89	17.00	1.291	62.9	1.006	-0.03	1.110	1.442
	LTE Band 38	20M	QPSK	1	49	Back	5mm	Reduced	38000	2595	2	15.89	17.00	1.291	62.9	1.006	0.05	1.020	1.325
	LTE Band 38	20M	QPSK	1	49	Back	5mm	Reduced	38000	2595	3	15.89	17.00	1.291	62.9	1.006	0.02	1.030	1.338
	LTE Band 38	20M	QPSK	1	49	Back	5mm	Reduced	38000	2595	4	15.89	17.00	1.291	62.9	1.006	0.05	1.100	1.429
	LTE Band 38	20M	QPSK	1	49	Left Side	5mm	Reduced	38000	2595	1	15.06	16.00	1.242	62.9	1.006	0.06	0.008	0.010
	LTE Band 38	20M	QPSK	1	49	Right Side	5mm	Reduced	38000	2595	1	15.06	16.00	1.242	62.9	1.006	0.03	0.005	0.006
	LTE Band 38	20M	QPSK	1	49	Bottom Side	5mm	Reduced	38000	2595	1	15.06	16.00	1.242	62.9	1.006	0.11	1.080	1.349
	LTE Band 38	20M	QPSK	50	0	Front	5mm	Reduced	38000	2595	1	14.66	16.00	1.361	62.9	1.006	-0.05	0.380	0.520
	LTE Band 38	20M	QPSK	50	0	Back	5mm	Reduced	38000	2595	1	14.66	16.00	1.361	62.9	1.006	0.06	0.785	1.075
	LTE Band 38	20M	QPSK	50	0	Left Side	5mm	Reduced	38000	2595	1	14.02	15.00	1.253	62.9	1.006	0.08	0.006	0.008
	LTE Band 38	20M	QPSK	50	0	Right Side	5mm	Reduced	38000	2595	1	14.02	15.00	1.253	62.9	1.006	0.03	0.003	0.004
	LTE Band 38	20M	QPSK	50	0	Bottom Side	5mm	Reduced	38000	2595	1	14.02	15.00	1.253	62.9	1.006	0.08	0.719	0.906
	LTE Band 38	20M	QPSK	100	0	Back	5mm	Reduced	38000	2595	1	14.65	16.00	1.365	62.9	1.006	0.07	0.786	1.079
	LTE Band 38	20M	QPSK	100	0	Bottom Side	5mm	Reduced	38000	2595	1	13.71	15.00	1.346	62.9	1.006	0.06	0.721	0.976



<WLAN2.4 SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	5mm	Reduced	6	2437	1	17.00	18.00	1.259	99.27	1.007	0.02	0.267	0.338
	WLAN2.4GHz	802.11b 1Mbps	Back	5mm	Reduced	6	2437	1	17.00	18.00	1.259	99.27	1.007	-0.03	0.819	1.038
	WLAN2.4GHz	802.11b 1Mbps	Right Side	5mm	Reduced	6	2437	1	17.00	18.00	1.259	99.27	1.007	0.11	0.225	0.285
	WLAN2.4GHz	802.11b 1Mbps	Top Side	5mm	Reduced	6	2437	1	17.00	18.00	1.259	99.27	1.007	0.15	0.338	0.428
28	WLAN2.4GHz	802.11b 1Mbps	Back	5mm	Reduced	11	2462	1	16.80	18.00	1.318	99.27	1.007	0.08	0.876	1.163

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	DH5 1Mbps	Front	5mm	Full	78	2480	1	10.50	12.00	1.413	76.91	1.300	0.06	0.053	0.097
29	Bluetooth	DH5 1Mbps	Back	5mm	Full	78	2480	1	10.50	12.00	1.413	76.91	1.300	0.01	0.151	0.277
	Bluetooth	DH5 1Mbps	Right Side	5mm	Full	78	2480	1	10.50	12.00	1.413	76.91	1.300	0.01	0.003	0.006
	Bluetooth	DH5 1Mbps	Top Side	5mm	Full	78	2480	1	10.50	12.00	1.413	76.91	1.300	0.02	0.052	0.095

<WLAN5G SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN5.2GHz	802.11ac-VHT80 MCS0	Front	5mm	Reduced	42	5210	1	9.70	11.00	1.349	87.77	1.139	0.13	0.234	0.360
	WLAN5.2GHz	802.11ac-VHT80 MCS0	Back	5mm	Reduced	42	5210	1	9.70	11.00	1.349	87.77	1.139	-0.02	0.584	0.897
	WLAN5.2GHz	802.11ac-VHT80 MCS0	Right Side	5mm	Reduced	42	5210	1	9.70	11.00	1.349	87.77	1.139	0.05	0.147	0.226
30	WLAN5.2GHz	802.11ac-VHT80 MCS0	Top Side	5mm	Reduced	42	5210	1	9.70	11.00	1.349	87.77	1.139	0.01	0.762	1.171
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Front	5mm	Reduced	155	5775	1	9.90	11.00	1.288	87.77	1.139	-0.06	0.204	0.299
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Back	5mm	Reduced	155	5775	1	9.90	11.00	1.288	87.77	1.139	0.04	0.557	0.817
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Right Side	5mm	Reduced	155	5775	1	9.90	11.00	1.288	87.77	1.139	0.05	0.112	0.164
31	WLAN5.8GHz	802.11ac-VHT80 MCS0	Top Side	5mm	Reduced	155	5775	1	9.90	11.00	1.288	87.77	1.139	0.02	0.805	1.181
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Top Side	5mm	Reduced	155	5775	2	9.90	11.00	1.288	87.77	1.139	0.08	0.620	0.910
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Top Side	5mm	Reduced	155	5775	3	9.90	11.00	1.288	87.77	1.139	0.13	0.560	0.822
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Top Side	5mm	Reduced	155	5775	4	9.90	11.00	1.288	87.77	1.139	0.04	0.465	0.682



15.3 Body Worn Accessory SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Headset	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS 2 Tx slots	Front	5mm	-	Reduced	251	848.8	1	28.95	30.00	1.274	0.08	0.460	0.586
32	GSM850	GPRS 2 Tx slots	Back	5mm	-	Reduced	251	848.8	1	28.95	30.00	1.274	0.09	0.968	1.233
	GSM850	GPRS 2 Tx slots	Back	5mm	-	Reduced	251	848.8	2	28.95	30.00	1.274	0.06	0.939	1.196
	GSM850	GPRS 2 Tx slots	Back	5mm	-	Reduced	251	848.8	3	28.95	30.00	1.274	0.05	0.959	1.221
	GSM850	GPRS 2 Tx slots	Back	5mm	-	Reduced	251	848.8	4	28.95	30.00	1.274	0.02	0.895	1.140
	GSM850	GPRS 2 Tx slots	Back	5mm	-	Reduced	128	824.2	1	28.88	30.00	1.294	0.11	0.721	0.933
	GSM850	GPRS 2 Tx slots	Back	5mm	-	Reduced	189	836.4	1	28.86	30.00	1.300	0.06	0.795	1.034
	GSM850	GPRS 2 Tx slots	Back	5mm	Headset	Reduced	251	848.8	1	28.95	30.00	1.274	0.02	0.818	1.042
	GSM850	GPRS 2 Tx slots	Front	14mm	-	Full	251	848.8	1	30.96	32.00	1.271	0.08	0.367	0.466
	GSM850	GPRS 2 Tx slots	Back	18mm	-	Full	251	848.8	1	30.96	32.00	1.271	0.02	0.446	0.567
	GSM1900	GPRS 2 Tx slots	Front	5mm	-	Reduced	661	1880	1	24.08	25.50	1.387	-0.02	0.476	0.660
	GSM1900	GPRS 2 Tx slots	Back	5mm	-	Reduced	661	1880	1	24.08	25.50	1.387	0.04	0.884	1.226
33	GSM1900	GPRS 2 Tx slots	Back	5mm	-	Reduced	512	1850.2	1	23.85	25.50	1.462	0.01	0.968	1.415
	GSM1900	GPRS 2 Tx slots	Back	5mm	-	Reduced	810	1909.8	1	23.99	25.50	1.416	-0.03	0.934	1.322
	GSM1900	GPRS 2 Tx slots	Back	5mm	Headset	Reduced	512	1850.2	1	23.85	25.50	1.462	0.04	0.835	1.221
	GSM1900	GPRS 2 Tx slots	Front	14mm	-	Full	661	1880	1	27.94	29.50	1.432	-0.04	0.420	0.602
	GSM1900	GPRS 2 Tx slots	Back	18mm	-	Full	512	1850.2	1	27.83	29.50	1.469	0.02	0.416	0.611

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Headset	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA V	RMC 12.2Kbps	Front	5mm	-	Reduced	4182	836.4	1	22.01	23.00	1.256	0.09	0.468	0.588
	WCDMA V	RMC 12.2Kbps	Back	5mm	-	Reduced	4182	836.4	1	22.01	23.00	1.256	0.08	0.890	1.118
	WCDMA V	RMC 12.2Kbps	Back	5mm	-	Reduced	4132	826.4	1	21.88	23.00	1.294	0.02	0.785	1.016
34	WCDMA V	RMC 12.2Kbps	Back	5mm	-	Reduced	4233	846.6	1	22.00	23.00	1.259	0.03	0.945	1.190
	WCDMA V	RMC 12.2Kbps	Front	14mm	-	Full	4182	836.4	1	22.82	24.00	1.312	0.08	0.363	0.476
	WCDMA V	RMC 12.2Kbps	Back	18mm	-	Full	4233	846.6	1	22.67	24.00	1.358	0.06	0.430	0.584
	WCDMA IV	RMC 12.2Kbps	Front	5mm	-	Reduced	1413	1732.6	1	16.62	17.50	1.225	0.04	0.278	0.340
	WCDMA IV	RMC 12.2Kbps	Back	5mm	-	Reduced	1413	1732.6	1	16.62	17.50	1.225	0.02	0.978	1.198
35	WCDMA IV	RMC 12.2Kbps	Back	5mm	-	Reduced	1312	1712.4	1	16.53	17.50	1.250	-0.04	1.120	1.400
	WCDMA IV	RMC 12.2Kbps	Back	5mm	-	Reduced	1513	1752.6	1	16.58	17.50	1.236	0.11	0.877	1.084
	WCDMA IV	RMC 12.2Kbps	Back	5mm	Headset	Reduced	1312	1712.4	1	16.53	17.50	1.250	0.03	0.882	1.103
	WCDMA IV	RMC 12.2Kbps	Front	14mm	-	Full	1413	1732.6	1	23.02	24.00	1.253	0.07	0.468	0.586
	WCDMA IV	RMC 12.2Kbps	Back	18mm	-	Full	1312	1712.4	1	22.91	24.00	1.285	0.02	0.716	0.920
	WCDMA II	RMC 12.2Kbps	Front	5mm	-	Reduced	9400	1880	1	17.36	18.50	1.300	-0.02	0.355	0.462
	WCDMA II	RMC 12.2Kbps	Back	5mm	-	Reduced	9400	1880	1	17.36	18.50	1.300	-0.08	0.931	1.210
	WCDMA II	RMC 12.2Kbps	Back	5mm	-	Reduced	9262	1852.4	1	17.30	18.50	1.318	-0.05	0.920	1.213
36	WCDMA II	RMC 12.2Kbps	Back	5mm	-	Reduced	9538	1907.6	1	17.20	18.50	1.349	-0.01	1.070	1.443
	WCDMA II	RMC 12.2Kbps	Back	5mm	-	Reduced	9538	1907.6	2	17.20	18.50	1.349	-0.08	1.020	1.376
	WCDMA II	RMC 12.2Kbps	Back	5mm	-	Reduced	9538	1907.6	3	17.20	18.50	1.349	0.07	0.889	1.199
	WCDMA II	RMC 12.2Kbps	Back	5mm	-	Reduced	9538	1907.6	4	17.20	18.50	1.349	-0.04	0.906	1.222
	WCDMA II	RMC 12.2Kbps	Back	5mm	Headset	Reduced	9538	1907.6	1	17.20	18.50	1.349	-0.05	1.050	1.416
	WCDMA II	RMC 12.2Kbps	Front	14mm	-	Full	9400	1880	1	22.80	24.00	1.318	0.08	0.583	0.769
	WCDMA II	RMC 12.2Kbps	Back	18mm	-	Full	9538	1907.6	1	22.63	24.00	1.371	0.06	0.827	1.134



<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Headset	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
37	LTE Band 13	10M	QPSK	1	25	Front	5mm	-	Full	23230	782	1	23.10	24.00	1.230	0.11	0.372	0.458
	LTE Band 13	10M	QPSK	1	25	Back	5mm	-	Full	23230	782	1	23.10	24.00	1.230	0.13	0.820	1.009
	LTE Band 13	10M	QPSK	25	0	Front	5mm	-	Full	23230	782	1	21.98	23.00	1.265	0.03	0.297	0.376
	LTE Band 13	10M	QPSK	25	0	Back	5mm	-	Full	23230	782	1	21.98	23.00	1.265	-0.06	0.613	0.775
	LTE Band 13	10M	QPSK	50	0	Back	5mm	-	Full	23230	782	1	21.95	23.00	1.274	0.06	0.565	0.720
38	LTE Band 26	15M	QPSK	1	37	Front	5mm	-	Reduced	26865	831.5	1	22.11	23.00	1.227	0.07	0.445	0.546
	LTE Band 26	15M	QPSK	1	37	Back	5mm	-	Reduced	26865	831.5	1	22.11	23.00	1.227	-0.07	0.974	1.196
	LTE Band 26	15M	QPSK	1	37	Front	14mm	-	Full	26865	831.5	1	23.00	24.00	1.259	0.12	0.232	0.292
	LTE Band 26	15M	QPSK	1	37	Back	18mm	-	Full	26865	831.5	1	23.00	24.00	1.259	0.14	0.375	0.472
	LTE Band 26	15M	QPSK	36	0	Front	5mm	-	Reduced	26865	831.5	1	21.06	22.00	1.242	0.06	0.425	0.528
	LTE Band 26	15M	QPSK	36	0	Back	5mm	-	Reduced	26865	831.5	1	21.06	22.00	1.242	0.07	0.856	1.063
	LTE Band 26	15M	QPSK	75	0	Back	5mm	-	Reduced	26865	831.5	1	20.98	22.00	1.265	0.06	0.839	1.061
39	LTE Band 66	20M	QPSK	1	49	Front	5mm	-	Reduced	132322	1745	1	16.70	17.50	1.202	0.06	0.368	0.442
	LTE Band 66	20M	QPSK	1	49	Back	5mm	-	Reduced	132322	1745	1	16.70	17.50	1.202	0.08	0.921	1.107
	LTE Band 66	20M	QPSK	1	49	Back	5mm	-	Reduced	132072	1720	1	16.58	17.50	1.236	-0.09	1.060	1.310
	LTE Band 66	20M	QPSK	1	49	Back	5mm	-	Reduced	132572	1770	1	16.48	17.50	1.265	-0.02	0.890	1.126
	LTE Band 66	20M	QPSK	1	49	Back	5mm	Headset	Reduced	132072	1720	1	16.58	17.50	1.236	0.13	1.040	1.285
	LTE Band 66	20M	QPSK	1	49	Front	14mm	-	Full	132322	1745	1	23.33	24.00	1.167	0.07	0.481	0.561
	LTE Band 66	20M	QPSK	1	49	Back	18mm	-	Full	132072	1720	1	23.24	24.00	1.191	0.02	0.596	0.710
	LTE Band 66	20M	QPSK	50	0	Front	5mm	-	Reduced	132322	1745	1	15.74	16.50	1.191	0.06	0.334	0.398
	LTE Band 66	20M	QPSK	50	0	Back	5mm	-	Reduced	132322	1745	1	15.74	16.50	1.191	-0.02	0.822	0.979
	LTE Band 66	20M	QPSK	50	0	Back	5mm	-	Reduced	132072	1720	1	15.38	16.50	1.294	0.19	0.771	0.998
	LTE Band 66	20M	QPSK	50	0	Back	5mm	-	Reduced	132572	1770	1	15.53	16.50	1.250	0.06	0.736	0.920
	LTE Band 66	20M	QPSK	100	0	Back	5mm	-	Reduced	132322	1745	1	15.57	16.50	1.239	0.01	0.765	0.948
40	LTE Band 2	20M	QPSK	1	49	Front	5mm	-	Reduced	18900	1880	1	17.10	18.50	1.380	0.05	0.555	0.766
	LTE Band 2	20M	QPSK	1	49	Back	5mm	-	Reduced	18900	1880	1	17.10	18.50	1.380	0.14	1.030	1.422
	LTE Band 2	20M	QPSK	1	49	Back	5mm	-	Reduced	18700	1860	1	17.04	18.50	1.400	0.01	0.898	1.257
	LTE Band 2	20M	QPSK	1	49	Back	5mm	-	Reduced	19100	1900	1	17.08	18.50	1.387	0.09	0.922	1.279
	LTE Band 2	20M	QPSK	1	49	Back	5mm	Headset	Reduced	18900	1880	1	17.10	18.50	1.380	0.08	0.953	1.316
	LTE Band 2	20M	QPSK	1	49	Front	14mm	-	Full	18900	1880	1	22.92	24.00	1.282	0.05	0.618	0.792
	LTE Band 2	20M	QPSK	1	49	Back	18mm	-	Full	18900	1880	1	22.92	24.00	1.282	-0.03	0.656	0.841
	LTE Band 2	20M	QPSK	50	0	Front	5mm	-	Reduced	18900	1880	1	16.07	17.50	1.390	-0.12	0.467	0.649
	LTE Band 2	20M	QPSK	50	0	Back	5mm	-	Reduced	18900	1880	1	16.07	17.50	1.390	0.15	0.810	1.126
	LTE Band 2	20M	QPSK	50	0	Back	5mm	-	Reduced	18700	1860	1	16.05	17.50	1.396	0.05	0.737	1.029
	LTE Band 2	20M	QPSK	50	0	Back	5mm	-	Reduced	19100	1900	1	16.02	17.50	1.406	0.11	0.796	1.119
	LTE Band 2	20M	QPSK	100	0	Back	5mm	-	Reduced	18900	1880	1	16.04	17.50	1.400	0.13	0.800	1.120
41	LTE Band 7	20M	QPSK	1	49	Front	5mm	-	Reduced	21100	2535	1	13.74	15.00	1.337	0.02	0.387	0.517
	LTE Band 7	20M	QPSK	1	49	Back	5mm	-	Reduced	21100	2535	1	13.74	15.00	1.337	0.04	0.854	1.141
	LTE Band 7	20M	QPSK	1	49	Back	5mm	-	Reduced	20850	2510	1	13.46	15.00	1.426	0.02	0.726	1.035
	LTE Band 7	20M	QPSK	1	49	Back	5mm	-	Reduced	21350	2560	1	13.73	15.00	1.340	-0.04	0.995	1.333
	LTE Band 7	20M	QPSK	1	49	Back	5mm	Headset	Reduced	21350	2560	1	13.73	15.00	1.340	0.08	0.833	1.116
	LTE Band 7	20M	QPSK	1	49	Front	14mm	-	Full	21100	2535	1	22.69	24.00	1.352	0.06	0.772	1.044
	LTE Band 7	20M	QPSK	1	49	Front	14mm	-	Full	20850	2510	1	22.50	24.00	1.413	0.03	0.731	1.033
	LTE Band 7	20M	QPSK	1	49	Front	14mm	-	Full	21350	2560	1	22.65	24.00	1.365	0.08	0.746	1.018
	LTE Band 7	20M	QPSK	1	49	Back	18mm	-	Full	21350	2560	1	22.65	24.00	1.365	-0.02	0.964	1.315
	LTE Band 7	20M	QPSK	50	0	Front	5mm	-	Reduced	21100	2535	1	12.76	14.00	1.330	-0.02	0.302	0.402
	LTE Band 7	20M	QPSK	50	0	Back	5mm	-	Reduced	21100	2535	1	12.76	14.00	1.330	0.05	0.689	0.917
	LTE Band 7	20M	QPSK	50	0	Back	5mm	-	Reduced	20850	2510	1	12.73	14.00	1.340	0.01	0.685	0.918
	LTE Band 7	20M	QPSK	50	0	Back	5mm	-	Reduced	21350	2560	1	12.75	14.00	1.334	-0.11	0.747	0.996
	LTE Band 7	20M	QPSK	100	0	Back	5mm	-	Reduced	21100	2535	1	12.75	14.00	1.334	0.08	0.611	0.815



<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Headset	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 38	20M	QPSK	1	49	Front	5mm	-	Reduced	38000	2595	1	15.89	17.00	1.291	62.9	1.006	0.07	0.453	0.588
42	LTE Band 38	20M	QPSK	1	49	Back	5mm	-	Reduced	38000	2595	1	15.89	17.00	1.291	62.9	1.006	-0.03	1.110	1.442
	LTE Band 38	20M	QPSK	1	49	Back	5mm	-	Reduced	38000	2595	2	15.89	17.00	1.291	62.9	1.006	0.05	1.020	1.325
	LTE Band 38	20M	QPSK	1	49	Back	5mm	-	Reduced	38000	2595	3	15.89	17.00	1.291	62.9	1.006	0.02	1.030	1.338
	LTE Band 38	20M	QPSK	1	49	Back	5mm	-	Reduced	38000	2595	4	15.89	17.00	1.291	62.9	1.006	0.05	1.100	1.429
	LTE Band 38	20M	QPSK	1	49	Back	5mm	Headset	Reduced	38000	2595	1	15.89	17.00	1.291	62.9	1.006	0.04	0.993	1.290
	LTE Band 38	20M	QPSK	1	49	Front	14mm	-	Full	38000	2595	1	23.26	24.00	1.186	62.9	1.006	0.05	0.557	0.664
	LTE Band 38	20M	QPSK	1	49	Back	18mm	-	Full	38000	2595	1	23.26	24.00	1.186	62.9	1.006	0.01	0.536	0.639
	LTE Band 38	20M	QPSK	50	0	Front	5mm	-	Reduced	38000	2595	1	14.66	16.00	1.361	62.9	1.006	-0.05	0.380	0.520
	LTE Band 38	20M	QPSK	50	0	Back	5mm	-	Reduced	38000	2595	1	14.66	16.00	1.361	62.9	1.006	0.06	0.785	1.075
	LTE Band 38	20M	QPSK	100	0	Back	5mm	-	Reduced	38000	2595	1	14.65	16.00	1.365	62.9	1.006	0.07	0.786	1.079



<WLAN2.4G SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Headset	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	5mm	-	Reduced	6	2437	1	17.00	18.00	1.259	99.27	1.007	0.02	0.267	0.338
	WLAN2.4GHz	802.11b 1Mbps	Back	5mm	-	Reduced	6	2437	1	17.00	18.00	1.259	99.27	1.007	-0.03	0.819	1.038
43	WLAN2.4GHz	802.11b 1Mbps	Back	5mm	-	Reduced	11	2462	1	16.80	18.00	1.318	99.27	1.007	0.08	0.876	1.163
	WLAN2.4GHz	802.11b 1Mbps	Front	14mm	-	Full	6	2437	1	19.10	20.00	1.230	99.27	1.007	0.03	0.109	0.135
	WLAN2.4GHz	802.11b 1Mbps	Back	18mm	-	Full	11	2412	1	18.90	20.00	1.288	99.27	1.007	-0.01	0.148	0.192

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Headset	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	DH5 1Mbps	Front	5mm	-	Full	78	2480	1	10.50	12.00	1.413	76.91	1.300	0.06	0.053	0.097
44	Bluetooth	DH5 1Mbps	Back	5mm	-	Full	78	2480	1	10.50	12.00	1.413	76.91	1.300	0.01	0.151	0.277

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Headset	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN5.3GHz	802.11ac-VHT80 MCS0	Front	5mm	-	Reduced	58	5290	1	11.00	12.00	1.259	87.77	1.139	0.08	0.312	0.447
45	WLAN5.3GHz	802.11ac-VHT80 MCS0	Back	5mm	-	Reduced	58	5290	1	11.00	12.00	1.259	87.77	1.139	0.04	0.827	1.186
	WLAN5.3GHz	802.11ac-VHT80 MCS0	Back	5mm	-	Reduced	58	5290	2	11.00	12.00	1.259	87.77	1.139	0.04	0.329	0.472
	WLAN5.3GHz	802.11ac-VHT80 MCS0	Back	5mm	-	Reduced	58	5290	3	11.00	12.00	1.259	87.77	1.139	0.04	0.222	0.318
	WLAN5.3GHz	802.11ac-VHT80 MCS0	Back	5mm	-	Reduced	58	5290	4	11.00	12.00	1.259	87.77	1.139	0.04	0.248	0.356
	WLAN5.3GHz	802.11a 6Mbps	Front	14mm	-	Full	56	5280	1	17.48	18.00	1.127	96.97	1.031	0.07	0.321	0.373
	WLAN5.3GHz	802.11a 6Mbps	Back	18mm	-	Full	56	5280	1	17.48	18.00	1.127	96.97	1.031	0.02	0.503	0.585
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Front	5mm	-	Reduced	122	5610	1	11.41	12.00	1.146	87.77	1.139	0.13	0.303	0.395
46	WLAN5.5GHz	802.11ac-VHT80 MCS0	Back	5mm	-	Reduced	122	5610	1	11.41	12.00	1.146	87.77	1.139	0.03	0.869	1.134
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Back	5mm	-	Reduced	138	5690	1	11.37	12.00	1.156	87.77	1.139	0.03	0.854	1.125
	WLAN5.5GHz	802.11a 6Mbps	Front	14mm	-	Full	100	5500	1	16.98	17.50	1.126	96.97	1.031	-0.04	0.278	0.323
	WLAN5.5GHz	802.11a 6Mbps	Back	18mm	-	Full	100	5500	1	16.98	17.50	1.126	96.97	1.031	0.03	0.488	0.567
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Front	5mm	-	Reduced	155	5775	1	11.50	12.50	1.259	87.77	1.139	0.09	0.308	0.442
47	WLAN5.8GHz	802.11ac-VHT80 MCS0	Back	5mm	-	Reduced	155	5775	1	11.50	12.50	1.259	87.77	1.139	0.11	0.825	1.183
	WLAN5.8GHz	802.11a 6Mbps	Front	14mm	-	Full	149	5745	1	16.81	17.50	1.171	96.97	1.031	-0.05	0.275	0.332
	WLAN5.8GHz	802.11a 6Mbps	Back	18mm	-	Full	149	5745	1	16.81	17.50	1.171	96.97	1.031	0.03	0.484	0.584



15.4 Product Specific SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	GSM850	GPRS 2 Tx slots	Back	0mm	Reduced	251	848.8	1	29.93	31.00	1.279	0.06	1.810	2.316
48	GSM850	GPRS 2 Tx slots	Back	0mm	Reduced	128	824.2	1	29.85	31.00	1.303	0.17	2.280	2.971
	GSM850	GPRS 2 Tx slots	Back	0mm	Reduced	128	824.2	2	29.85	31.00	1.303	-0.02	2.160	2.815
	GSM850	GPRS 2 Tx slots	Back	0mm	Reduced	128	824.2	3	29.85	31.00	1.303	-0.05	2.150	2.802
	GSM850	GPRS 2 Tx slots	Back	0mm	Reduced	128	824.2	4	29.85	31.00	1.303	0.02	2.040	2.658
	GSM850	GPRS 2 Tx slots	Back	0mm	Reduced	189	836.4	1	29.83	31.00	1.309	0.08	1.790	2.343
	GSM850	GPRS 2 Tx slots	Back	7mm	Full	128	824.2	1	30.93	32.00	1.279	0.13	0.560	0.716
	GSM1900	GPRS 2 Tx slots	Front	0mm	Reduced	661	1880	1	27.11	28.50	1.377	0.05	1.240	1.708
	GSM1900	GPRS 2 Tx slots	Back	0mm	Reduced	661	1880	1	27.11	28.50	1.377	0.06	1.560	2.148
	GSM1900	GPRS 2 Tx slots	Back	0mm	Reduced	512	1850.2	1	26.92	28.50	1.439	0.06	1.510	2.173
	GSM1900	GPRS 2 Tx slots	Back	0mm	Reduced	810	1909.8	1	27.05	28.50	1.396	0.06	1.710	2.388
	GSM1900	GPRS 2 Tx slots	Bottom Side	0mm	Reduced	661	1880	1	27.11	28.50	1.377	0.03	2.110	2.906
49	GSM1900	GPRS 2 Tx slots	Bottom Side	0mm	Reduced	512	1850.2	1	26.92	28.50	1.439	0.06	2.170	3.122
	GSM1900	GPRS 2 Tx slots	Bottom Side	0mm	Reduced	810	1909.8	1	27.05	28.50	1.396	0.07	1.860	2.597
	GSM1900	GPRS 2 Tx slots	Front	4mm	Full	661	1880	1	27.94	29.50	1.432	0.05	0.872	1.249
	GSM1900	GPRS 2 Tx slots	Back	7mm	Full	810	1909.8	1	27.91	29.50	1.442	0.13	1.030	1.485
	GSM1900	GPRS 2 Tx slots	Bottom Side	13mm	Full	512	1850.2	1	27.83	29.50	1.469	0.02	0.562	0.826

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WCDMA V	RMC 12.2Kbps	Back	0mm	Full	4182	836.4	1	22.82	24.00	1.312	0.05	1.990	2.611
50	WCDMA V	RMC 12.2Kbps	Back	0mm	Full	4132	826.4	1	22.72	24.00	1.343	-0.06	2.100	2.820
	WCDMA V	RMC 12.2Kbps	Back	0mm	Full	4233	846.6	1	22.67	24.00	1.358	0.02	1.870	2.540
	WCDMA IV	RMC 12.2Kbps	Front	0mm	Reduced	1413	1732.6	1	19.43	20.50	1.279	0.06	0.868	1.111
	WCDMA IV	RMC 12.2Kbps	Back	0mm	Reduced	1413	1732.6	1	19.43	20.50	1.279	-0.05	1.600	2.047
	WCDMA IV	RMC 12.2Kbps	Back	0mm	Reduced	1312	1712.4	1	19.28	20.50	1.324	0.03	1.800	2.384
	WCDMA IV	RMC 12.2Kbps	Back	0mm	Reduced	1513	1752.6	1	19.40	20.50	1.288	0.01	1.680	2.164
	WCDMA IV	RMC 12.2Kbps	Bottom Side	0mm	Reduced	1413	1732.6	1	19.43	20.50	1.279	0.07	2.300	2.943
51	WCDMA IV	RMC 12.2Kbps	Bottom Side	0mm	Reduced	1312	1712.4	1	19.28	20.50	1.324	0.03	2.530	3.351
	WCDMA IV	RMC 12.2Kbps	Bottom Side	0mm	Reduced	1312	1712.4	2	19.28	20.50	1.324	0.05	2.260	2.993
	WCDMA IV	RMC 12.2Kbps	Bottom Side	0mm	Reduced	1312	1712.4	3	19.28	20.50	1.324	-0.08	2.370	3.139
	WCDMA IV	RMC 12.2Kbps	Bottom Side	0mm	Reduced	1312	1712.4	4	19.28	20.50	1.324	0.02	2.390	3.165
	WCDMA IV	RMC 12.2Kbps	Bottom Side	0mm	Reduced	1513	1752.6	1	19.40	20.50	1.288	-0.05	2.190	2.821
	WCDMA IV	RMC 12.2Kbps	Front	4mm	Full	1413	1732.6	1	23.02	24.00	1.253	0.05	0.874	1.095
	WCDMA IV	RMC 12.2Kbps	Back	7mm	Full	1312	1712.4	1	22.91	24.00	1.285	-0.02	1.570	2.018
	WCDMA IV	RMC 12.2Kbps	Bottom Side	13mm	Full	1312	1712.4	1	22.91	24.00	1.285	-0.1	0.910	1.170
	WCDMA II	RMC 12.2Kbps	Front	0mm	Reduced	9400	1880	1	19.57	21.00	1.390	0.06	1.190	1.654
	WCDMA II	RMC 12.2Kbps	Back	0mm	Reduced	9400	1880	1	19.57	21.00	1.390	0.02	1.900	2.641
	WCDMA II	RMC 12.2Kbps	Back	0mm	Reduced	9262	1852.4	1	19.56	21.00	1.393	-0.03	1.910	2.661
	WCDMA II	RMC 12.2Kbps	Back	0mm	Reduced	9538	1907.6	1	19.32	21.00	1.472	0.09	1.620	2.385
52	WCDMA II	RMC 12.2Kbps	Bottom Side	0mm	Reduced	9400	1880	1	19.57	21.00	1.390	0.12	2.320	3.225
	WCDMA II	RMC 12.2Kbps	Bottom Side	0mm	Reduced	9262	1852.4	1	19.56	21.00	1.393	0.02	2.160	3.009
	WCDMA II	RMC 12.2Kbps	Bottom Side	0mm	Reduced	9538	1907.6	1	19.32	21.00	1.472	0.04	1.940	2.856
	WCDMA II	RMC 12.2Kbps	Front	4mm	Full	9400	1880	1	22.80	24.00	1.318	0.06	1.170	1.542
	WCDMA II	RMC 12.2Kbps	Back	7mm	Full	9262	1852.4	1	22.74	24.00	1.337	-0.01	1.130	1.510
	WCDMA II	RMC 12.2Kbps	Bottom Side	13mm	Full	9400	1880	1	22.80	24.00	1.318	-0.05	0.708	0.933



<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
53	LTE Band 26	15M	QPSK	1	37	Back	0mm	Full	26865	831.5	1	23.00	24.00	1.259	-0.06	1.950	2.455
	LTE Band 26	15M	QPSK	36	0	Back	0mm	Full	26865	831.5	1	21.96	23.00	1.271	0.02	1.100	1.398
	LTE Band 26	15M	QPSK	75	0	Back	0mm	Full	26865	831.5	1	21.85	23.00	1.303	0.01	1.060	1.381
	LTE Band 66	20M	QPSK	1	49	Front	0mm	Reduced	132322	1745	1	19.03	20.00	1.250	-0.05	0.759	0.949
	LTE Band 66	20M	QPSK	1	49	Back	0mm	Reduced	132322	1745	1	19.03	20.00	1.250	0.08	1.620	2.025
	LTE Band 66	20M	QPSK	1	49	Back	0mm	Reduced	132072	1720	1	18.68	20.00	1.355	0.09	1.780	2.412
	LTE Band 66	20M	QPSK	1	49	Back	0mm	Reduced	132572	1770	1	18.73	20.00	1.340	-0.02	1.420	1.902
	LTE Band 66	20M	QPSK	1	49	Bottom Side	0mm	Reduced	132322	1745	1	19.03	20.00	1.250	0.13	2.120	2.651
54	LTE Band 66	20M	QPSK	1	49	Bottom Side	0mm	Reduced	132072	1720	1	18.68	20.00	1.355	0.08	2.310	3.130
	LTE Band 66	20M	QPSK	1	49	Bottom Side	0mm	Reduced	132572	1770	1	18.73	20.00	1.340	0.05	1.970	2.639
	LTE Band 66	20M	QPSK	1	49	Front	4mm	Full	132322	1745	1	23.33	24.00	1.167	0.04	1.040	1.213
	LTE Band 66	20M	QPSK	1	49	Back	7mm	Full	132072	1720	1	23.24	24.00	1.191	-0.02	1.470	1.751
	LTE Band 66	20M	QPSK	1	49	Bottom Side	13mm	Full	132072	1720	1	23.24	24.00	1.191	0.01	0.840	1.001
	LTE Band 66	20M	QPSK	50	0	Front	0mm	Reduced	132322	1745	1	17.99	19.00	1.262	0.03	0.602	0.760
	LTE Band 66	20M	QPSK	50	0	Back	0mm	Reduced	132322	1745	1	17.99	19.00	1.262	0.02	1.270	1.603
	LTE Band 66	20M	QPSK	50	0	Bottom Side	0mm	Reduced	132322	1745	1	17.99	19.00	1.262	-0.05	1.690	2.132
	LTE Band 66	20M	QPSK	50	0	Bottom Side	0mm	Reduced	132072	1720	1	17.70	19.00	1.349	0.06	1.830	2.469
	LTE Band 66	20M	QPSK	50	0	Bottom Side	0mm	Reduced	132572	1770	1	17.82	19.00	1.312	0.08	1.620	2.126
	LTE Band 66	20M	QPSK	100	0	Back	0mm	Reduced	132322	1745	1	17.94	19.00	1.276	-0.07	1.270	1.621
	LTE Band 66	20M	QPSK	100	0	Bottom Side	0mm	Reduced	132322	1745	1	17.94	19.00	1.276	0.02	1.660	2.119
	LTE Band 2	20M	QPSK	1	49	Front	0mm	Reduced	18900	1880	1	19.72	21.00	1.343	0.06	1.120	1.504
	LTE Band 2	20M	QPSK	1	49	Back	0mm	Reduced	18900	1880	1	19.72	21.00	1.343	-0.08	1.990	2.672
	LTE Band 2	20M	QPSK	1	49	Back	0mm	Reduced	18700	1860	1	19.71	21.00	1.346	0.09	1.880	2.530
	LTE Band 2	20M	QPSK	1	49	Back	0mm	Reduced	19100	1900	1	19.67	21.00	1.358	-0.04	1.920	2.608
	LTE Band 2	20M	QPSK	1	49	Bottom Side	0mm	Reduced	18900	1880	1	19.72	21.00	1.343	0.13	2.070	2.780
55	LTE Band 2	20M	QPSK	1	49	Bottom Side	0mm	Reduced	18700	1860	1	19.71	21.00	1.346	0.02	2.340	3.149
	LTE Band 2	20M	QPSK	1	49	Bottom Side	0mm	Reduced	19100	1900	1	19.67	21.00	1.358	0.02	1.980	2.689
	LTE Band 2	20M	QPSK	1	49	Front	4mm	Full	18900	1880	1	22.92	24.00	1.282	0.08	1.350	1.731
	LTE Band 2	20M	QPSK	1	49	Back	7mm	Full	18900	1880	1	22.92	24.00	1.282	-0.05	1.510	1.936
	LTE Band 2	20M	QPSK	1	49	Bottom Side	13mm	Full	18700	1860	1	22.85	24.00	1.303	-0.15	0.695	0.906
	LTE Band 2	20M	QPSK	50	0	Front	0mm	Reduced	18900	1880	1	18.77	20.00	1.327	-0.04	0.855	1.135
	LTE Band 2	20M	QPSK	50	0	Back	0mm	Reduced	18900	1880	1	18.77	20.00	1.327	0.02	1.600	2.124
	LTE Band 2	20M	QPSK	50	0	Back	0mm	Reduced	18700	1860	1	18.62	20.00	1.374	0.11	1.530	2.102
	LTE Band 2	20M	QPSK	50	0	Back	0mm	Reduced	19100	1900	1	18.76	20.00	1.330	0.09	1.510	2.009
	LTE Band 2	20M	QPSK	50	0	Bottom Side	0mm	Reduced	18900	1880	1	18.77	20.00	1.327	-0.05	1.820	2.416
	LTE Band 2	20M	QPSK	50	0	Bottom Side	0mm	Reduced	18700	1860	1	18.62	20.00	1.374	0.02	1.770	2.432
	LTE Band 2	20M	QPSK	50	0	Bottom Side	0mm	Reduced	19100	1900	1	18.76	20.00	1.330	0.09	1.610	2.142
	LTE Band 2	20M	QPSK	100	0	Back	0mm	Reduced	18900	1880	1	18.68	20.00	1.355	-0.04	1.540	2.087
	LTE Band 2	20M	QPSK	100	0	Bottom Side	0mm	Reduced	18900	1880	1	18.68	20.00	1.355	0.02	1.710	2.317
	LTE Band 7	20M	QPSK	1	49	Front	0mm	Reduced	21100	2535	1	16.74	18.00	1.337	0.02	1.090	1.457
	LTE Band 7	20M	QPSK	1	49	Back	0mm	Reduced	21100	2535	1	16.74	18.00	1.337	0.08	1.830	2.446
	LTE Band 7	20M	QPSK	1	49	Back	0mm	Reduced	20850	2510	1	16.45	18.00	1.429	0.11	1.670	2.386
56	LTE Band 7	20M	QPSK	1	49	Back	0mm	Reduced	21350	2560	1	16.68	18.00	1.355	-0.02	2.060	2.792
	LTE Band 7	20M	QPSK	1	49	Bottom Side	0mm	Reduced	21100	2535	1	16.74	18.00	1.337	0.19	1.300	1.738
	LTE Band 7	20M	QPSK	1	49	Front	4mm	Full	21100	2535	1	22.69	24.00	1.352	0.02	2.010	2.718
	LTE Band 7	20M	QPSK	1	49	Front	4mm	Full	20850	2510	1	22.50	24.00	1.413	0.08	1.920	2.712
	LTE Band 7	20M	QPSK	1	49	Front	4mm	Full	21350	2560	1	22.65	24.00	1.365	-0.06	1.950	2.661
	LTE Band 7	20M	QPSK	1	49	Back	7mm	Full	21350	2560	1	22.65	24.00	1.365	-0.02	2.040	2.784
	LTE Band 7	20M	QPSK	1	49	Bottom Side	13mm	Full	21100	2535	1	22.69	24.00	1.352	0.04	1.030	1.393
	LTE Band 7	20M	QPSK	50	0	Front	0mm	Reduced	21100	2535	1	15.64	17.00	1.368	0.05	0.847	1.158
	LTE Band 7	20M	QPSK	50	0	Back	0mm	Reduced	21100	2535	1	15.64	17.00	1.368	0.18	1.460	1.997



	LTE Band 7	20M	QPSK	50	0	Bottom Side	0mm	Reduced	21100	2535	1	15.64	17.00	1.368	0.02	1.150	1.573
	LTE Band 7	20M	QPSK	100	0	Back	0mm	Reduced	21100	2535	1	15.63	17.00	1.371	0.04	1.600	2.193

<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	LTE Band 38	20M	QPSK	1	49	Front	0mm	Reduced	38000	2595	1	19.64	20.50	1.219	62.9	1.006	0.07	0.812	0.996
57	LTE Band 38	20M	QPSK	1	49	Back	0mm	Reduced	38000	2595	1	19.64	20.50	1.219	62.9	1.006	-0.06	2.130	2.612
	LTE Band 38	20M	QPSK	1	49	Back	0mm	Reduced	38000	2595	2	19.64	20.50	1.219	62.9	1.006	0.08	2.070	2.538
	LTE Band 38	20M	QPSK	1	49	Back	0mm	Reduced	38000	2595	3	19.64	20.50	1.219	62.9	1.006	0.04	2.060	2.526
	LTE Band 38	20M	QPSK	1	49	Back	0mm	Reduced	38000	2595	4	19.64	20.50	1.219	62.9	1.006	0.02	2.040	2.502
	LTE Band 38	20M	QPSK	1	49	Bottom Side	0mm	Reduced	38000	2595	1	19.64	20.50	1.219	62.9	1.006	0.08	0.885	1.085
	LTE Band 38	20M	QPSK	1	49	Front	4mm	Full	38000	2595	1	23.26	24.00	1.186	62.9	1.006	0.06	1.430	1.706
	LTE Band 38	20M	QPSK	1	49	Back	7mm	Full	38000	2595	1	23.26	24.00	1.186	62.9	1.006	-0.05	1.490	1.777
	LTE Band 38	20M	QPSK	1	49	Bottom Side	13mm	Full	38000	2595	1	23.26	24.00	1.186	62.9	1.006	-0.04	0.809	0.965
	LTE Band 38	20M	QPSK	50	0	Front	0mm	Reduced	38000	2595	1	18.68	19.50	1.208	62.9	1.006	0.09	0.713	0.866
	LTE Band 38	20M	QPSK	50	0	Back	0mm	Reduced	38000	2595	1	18.68	19.50	1.208	62.9	1.006	0.01	1.840	2.236
	LTE Band 38	20M	QPSK	50	0	Bottom Side	0mm	Reduced	38000	2595	1	18.68	19.50	1.208	62.9	1.006	0.09	0.824	1.001
	LTE Band 38	20M	QPSK	100	0	Back	0mm	Reduced	38000	2595	1	18.66	19.50	1.213	62.9	1.006	0.08	1.830	2.234



<WLAN2.4G SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
58	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Full	6	2437	1	19.10	20.00	1.230	99.27	1.007	0.06	1.340	1.660
	WLAN2.4GHz	802.11b 1Mbps	Back	7mm	Full	6	2437	1	19.10	20.00	1.230	99.27	1.007	0.01	0.390	0.483

<WLAN5G SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WLAN5.2GHz	802.11a 6Mbps	Front	0mm	Full	40	5200	1	15.89	17.50	1.449	96.97	1.031	0.04	0.521	0.778
	WLAN5.2GHz	802.11a 6Mbps	Back	0mm	Full	40	5200	1	15.89	17.50	1.449	96.97	1.031	0.08	0.555	0.829
59	WLAN5.2GHz	802.11a 6Mbps	Top Side	0mm	Full	40	5200	1	15.89	17.50	1.449	96.97	1.031	0.06	2.070	3.092
	WLAN5.2GHz	802.11a 6Mbps	Top Side	0mm	Full	48	5240	1	14.65	15.50	1.215	96.97	1.031	0.1	1.430	1.792
	WLAN5.2GHz	802.11a 6Mbps	Front	4mm	Full	40	5200	1	15.89	17.50	1.449	96.97	1.031	0.09	0.228	0.341
	WLAN5.2GHz	802.11a 6Mbps	Back	7mm	Full	40	5200	1	15.89	17.50	1.449	96.97	1.031	-0.13	0.184	0.275
	WLAN5.3GHz	802.11a 6Mbps	Front	0mm	Full	56	5280	1	17.48	18.00	1.127	96.97	1.031	0.05	1.100	1.278
	WLAN5.3GHz	802.11a 6Mbps	Back	0mm	Full	56	5280	1	17.48	18.00	1.127	96.97	1.031	0.11	2.110	2.452
	WLAN5.3GHz	802.11a 6Mbps	Back	0mm	Full	52	5260	1	17.38	18.00	1.153	96.97	1.031	0.16	2.140	2.545
	WLAN5.3GHz	802.11a 6Mbps	Right Side	0mm	Full	56	5280	1	17.48	18.00	1.127	96.97	1.031	0.02	0.580	0.674
60	WLAN5.3GHz	802.11a 6Mbps	Top Side	0mm	Full	56	5280	1	17.48	18.00	1.127	96.97	1.031	-0.16	2.730	3.173
	WLAN5.3GHz	802.11a 6Mbps	Top Side	0mm	Full	56	5280	2	17.48	18.00	1.127	96.97	1.031	-0.1	2.320	2.696
	WLAN5.3GHz	802.11a 6Mbps	Top Side	0mm	Full	56	5280	3	17.48	18.00	1.127	96.97	1.031	0.07	1.650	1.918
	WLAN5.3GHz	802.11a 6Mbps	Top Side	0mm	Full	56	5280	4	17.48	18.00	1.127	96.97	1.031	0.05	1.990	2.313
	WLAN5.3GHz	802.11a 6Mbps	Top Side	0mm	Full	52	5260	1	17.38	18.00	1.153	96.97	1.031	-0.12	2.510	2.985
	WLAN5.3GHz	802.11a 6Mbps	Front	4mm	Full	56	5280	1	17.48	18.00	1.127	96.97	1.031	0.06	0.372	0.432
	WLAN5.3GHz	802.11a 6Mbps	Back	7mm	Full	56	5280	1	17.48	18.00	1.127	96.97	1.031	-0.04	0.546	0.635
	WLAN5.5GHz	802.11a 6Mbps	Front	0mm	Full	100	5500	1	16.98	17.50	1.126	96.97	1.031	0.05	0.782	0.908
	WLAN5.5GHz	802.11a 6Mbps	Back	0mm	Full	100	5500	1	16.98	17.50	1.126	96.97	1.031	0.13	1.050	1.219
	WLAN5.5GHz	802.11a 6Mbps	Right Side	0mm	Full	100	5500	1	16.98	17.50	1.126	96.97	1.031	0.02	0.471	0.547
	WLAN5.5GHz	802.11a 6Mbps	Top Side	0mm	Full	100	5500	1	16.98	17.50	1.126	96.97	1.031	0.07	2.190	2.543
61	WLAN5.5GHz	802.11a 6Mbps	Top Side	0mm	Full	124	5620	1	16.98	17.50	1.127	96.97	1.031	-0.06	2.560	2.975
	WLAN5.5GHz	802.11a 6Mbps	Front	4mm	Full	100	5500	1	16.98	17.50	1.126	96.97	1.031	0.01	0.371	0.431
	WLAN5.5GHz	802.11a 6Mbps	Back	7mm	Full	100	5500	1	16.98	17.50	1.126	96.97	1.031	0.04	0.482	0.560
	WLAN5.8GHz	802.11a 6Mbps	Front	0mm	Full	149	5745	1	16.81	17.50	1.171	96.97	1.031	0.05	0.978	1.181
	WLAN5.8GHz	802.11a 6Mbps	Back	0mm	Full	149	5745	1	16.81	17.50	1.171	96.97	1.031	0.04	1.010	1.220
	WLAN5.8GHz	802.11a 6Mbps	Top Side	0mm	Full	149	5745	1	16.81	17.50	1.171	96.97	1.031	0.03	2.300	2.777
62	WLAN5.8GHz	802.11a 6Mbps	Top Side	0mm	Full	157	5785	1	16.57	17.50	1.238	96.97	1.031	0.05	2.330	2.973
	WLAN5.8GHz	802.11a 6Mbps	Front	4mm	Full	149	5745	1	16.81	17.50	1.171	96.97	1.031	0.03	0.353	0.426
	WLAN5.8GHz	802.11a 6Mbps	Back	7mm	Full	149	5745	1	16.81	17.50	1.171	96.97	1.031	0.07	0.393	0.475



15.5 Repeated SAR Measurement

<1g>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Ratio	Reported 1g SAR (W/kg)
1st	WCDMA IV	-	-	-	-	RMC 12.2Kbps	Back	5mm	Reduced	1312	1712.4	16.53	17.50	1.250	-	-	-0.04	1.120	1	1.400
2nd	WCDMA IV	-	-	-	-	RMC 12.2Kbps	Back	5mm	Reduced	1312	1712.4	16.53	17.50	1.250	-	-	-0.01	1.060	1.057	1.325
1st	WCDMA II	-	-	-	-	RMC 12.2Kbps	Back	5mm	Reduced	9538	1907.6	17.20	18.50	1.349	-	-	-0.01	1.070	1	1.443
2nd	WCDMA II	-	-	-	-	RMC 12.2Kbps	Back	5mm	Reduced	9538	1907.6	17.20	18.50	1.349	-	-	-0.15	1.060	1.009	1.430
1st	LTE Band 13	10M	QPSK	1	25	-	Back	5mm	Full	23230	782	23.10	24.00	1.230	-	-	0.13	0.820	1	1.009
2nd	LTE Band 13	10M	QPSK	1	25	-	Back	5mm	Full	23230	782	23.10	24.00	1.230	-	-	0.1	0.805	1.019	0.990
1st	LTE Band 26	15M	QPSK	1	37	-	Back	5mm	Reduced	26865	831.5	22.11	23.00	1.227	-	-	-0.07	0.974	1	1.196
2nd	LTE Band 26	15M	QPSK	1	37	-	Back	5mm	Reduced	26865	831.5	22.11	23.00	1.227	-	-	-0.03	0.970	1.004	1.191
1st	LTE Band 38	20M	QPSK	1	49	-	Back	5mm	Reduced	38000	2595	15.89	17.00	1.291	62.9	1.006	-0.03	1.110	1	1.442
2nd	LTE Band 38	20M	QPSK	1	49	-	Back	5mm	Reduced	38000	2595	15.89	17.00	1.291	62.9	1.006	-0.01	1.050	1.057	1.364
1st	WLAN2.4GHz	-	-	-	-	802.11b 1Mbps	Back	5mm	Reduced	11	2462	16.80	18.00	1.318	99.27	1.007	0.08	0.876	1	1.163
2nd	WLAN2.4GHz	-	-	-	-	802.11b 1Mbps	Back	5mm	Reduced	11	2462	16.80	18.00	1.318	99.27	1.007	0.04	0.850	1.031	1.128
1st	WLAN5GHz	-	-	-	-	802.11ac-VHT80 MCS0	Back	5mm	Reduced	58	5290	11.00	12.00	1.259	87.77	1.139	0.04	0.827	1	1.186
2nd	WLAN5GHz	-	-	-	-	802.11ac-VHT80 MCS0	Back	5mm	Reduced	58	5290	11.00	12.00	1.259	87.77	1.139	0.04	0.819	1.010	1.174
1st	WLAN5GHz	-	-	-	-	802.11ac-VHT80 MCS0	Back	5mm	Reduced	122	5610	11.41	12.00	1.146	87.77	1.139	0.03	0.869	1	1.134
2nd	WLAN5GHz	-	-	-	-	802.11ac-VHT80 MCS0	Back	5mm	Reduced	122	5610	11.41	12.00	1.146	87.77	1.139	0.08	0.857	1.014	1.118
1st	WLAN5GHz	-	-	-	-	802.11ac-VHT80 MCS0	Back	5mm	Reduced	155	5775	11.50	12.50	1.259	87.77	1.139	0.11	0.825	1	1.183
2nd	WLAN5GHz	-	-	-	-	802.11ac-VHT80 MCS0	Back	5mm	Reduced	155	5775	11.50	12.50	1.259	87.77	1.139	-0.05	0.816	1.011	1.170

<10g>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Ratio	Reported 10g SAR (W/kg)
1st	GSM850	-	-	-	-	GPRS 2 Tx slots	Back	0mm	Reduced	128	824.2	29.85	31.00	1.303	-	-	0.17	2.280	1	2.971
2nd	GSM850	-	-	-	-	GPRS 2 Tx slots	Back	0mm	Reduced	128	824.2	29.85	31.00	1.303	-	-	0.04	2.250	1.013	2.932
1st	WCDMA IV	-	-	-	-	RMC 12.2Kbps	Bottom Side	0mm	Reduced	1312	1712.4	19.28	20.50	1.324	-	-	0.03	2.530	1	3.351
2nd	WCDMA IV	-	-	-	-	RMC 12.2Kbps	Bottom Side	0mm	Reduced	1312	1712.4	19.28	20.50	1.324	-	-	0.13	2.510	1.008	3.324
1st	LTE Band 2	20M	QPSK	1	49	-	Bottom Side	0mm	Reduced	18700	1860	19.71	21.00	1.346	-	-	0.02	2.340	1	3.149
2nd	LTE Band 2	20M	QPSK	1	49	-	Bottom Side	0mm	Reduced	18700	1860	19.71	21.00	1.346	-	-	0.08	2.300	1.017	3.095
1st	LTE Band 38	20M	QPSK	1	49	-	Back	0mm	Reduced	38000	2595	19.64	20.50	1.219	62.9	1.006	-0.06	2.130	1	2.612
2nd	LTE Band 38	20M	QPSK	1	49	-	Back	0mm	Reduced	38000	2595	19.64	20.50	1.219	62.9	1.006	-0.05	2.090	1.019	2.563
1st	WLAN5GHz	-	-	-	-	802.11a 6Mbps	Top Side	0mm	Full	56	5280	17.48	18.00	1.127	96.97	1.031	-0.16	2.730	1	3.173
2nd	WLAN5GHz	-	-	-	-	802.11a 6Mbps	Top Side	0mm	Full	56	5280	17.48	18.00	1.127	96.97	1.031	-0.06	2.710	1.007	3.149
1st	WLAN5GHz	-	-	-	-	802.11a 6Mbps	Top Side	0mm	Full	124	5620	16.98	17.50	1.127	96.97	1.031	-0.06	2.560	1	2.975
2nd	WLAN5GHz	-	-	-	-	802.11a 6Mbps	Top Side	0mm	Full	124	5620	16.98	17.50	1.127	96.97	1.031	0.02	2.490	1.028	2.894
1st	WLAN5GHz	-	-	-	-	802.11a 6Mbps	Top Side	0mm	Full	157	5785	16.57	17.50	1.238	96.97	1.031	0.05	2.330	1	2.973
2nd	WLAN5GHz	-	-	-	-	802.11a 6Mbps	Top Side	0mm	Full	157	5785	16.57	17.50	1.238	96.97	1.031	0.02	2.280	1.022	2.910

General Note:

- Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is $\geq 0.8W/kg$.
- Per KDB 865664 D01v01r04, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR $< 1.45W/kg$, only one repeated measurement is required.
- Per KDB 865664 D01v01r04, if the extremity repeated SAR is necessary, the same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.
- The ratio is the difference in percentage between original and repeated *measured SAR*.
- All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

16. Simultaneous Transmission Analysis

No.	Simultaneous Transmission Configurations	Portable Handset			
		Head	Body-worn	Hotspot	Product specific 10g SAR
1.	WWAN + WLAN2.4GHz	Yes	Yes	Yes	Yes
2.	WWAN + WLAN5GHz	Yes	Yes	Yes	Yes
3.	WWAN + Bluetooth	Yes	Yes	Yes	Yes

General Note:

1. This device supports VoIP in GPRS, EGPRS, WCDMA and LTE (e.g. for 3rd-party VoIP), LTE supports VoLTE operation.
2. EUT will choose each GSM, WCDMA and LTE according to the network signal condition; therefore, they will not operate simultaneously at any moment.
3. This device 2.4GHz WLAN support hotspot operation and Bluetooth support tethering applications.
4. This device 5.2GHz WLAN/5.8GHz WLAN support hotspot operation, and 5.2GHz WLAN/5.8GHz WLAN supports WLAN Direct (GC/GO), and 5.3GHz / 5.5GHz supports WLAN Direct (GC only).
5. WIFI 5.3/5.5GHz has no hotspot function.
6. The worst case 5 GHz WLAN SAR for each configuration was used for SAR summation.
7. WLAN 2.4GHz and Bluetooth share the same antenna so can't transmit simultaneously.
8. According to the EUT characteristic, WLAN 5GHz and Bluetooth can't transmit simultaneously.
9. The maximum SAR summation is calculated based on the same configuration and test position.
10. Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - i) 1g Scalar SAR summation < 1.6W/kg and 10g Scalar SAR summation < 4.0W/kg.
 - ii) $SPLSR = (SAR1 + SAR2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - iii) If $SPLSR \leq 0.04$ for 1g SAR and $SPLSR \leq 0.10$ for 10g SAR, simultaneously transmission SAR measurement is not necessary.
 - iv) Simultaneously transmission SAR measurement, and the reported multi-band 1g SAR < 1.6W/kg and 10g SAR < 4.0W/kg.
 - v) The SPLSR calculated results please refer to section 16.5.



16.1 Head Exposure Conditions

WWAN Band		Exposure Position	1	3	6	9	1+3	1+6	1+9
			WWAN 1g SAR (W/kg)	2.4GHz WLAN 1g SAR (W/kg)	5GHz WLAN 1g SAR (W/kg)	Bluetooth 1g SAR (W/kg)	Summed 1g SAR (W/kg)	Summed 1g SAR (W/kg)	Summed 1g SAR (W/kg)
GSM	GSM850	Right Cheek	0.536	0.546	0.409	0.024	1.08	0.95	0.56
		Right Tilted	0.268	0.664	0.488	0.018	0.93	0.76	0.29
		Left Cheek	0.390	1.012	0.657	0.040	1.40	1.05	0.43
		Left Tilted	0.236	1.033	1.052	0.035	1.27	1.29	0.27
	GSM1900	Right Cheek	0.354	0.546	0.409	0.024	0.90	0.76	0.38
		Right Tilted	0.132	0.664	0.488	0.018	0.80	0.62	0.15
		Left Cheek	0.179	1.012	0.657	0.040	1.19	0.84	0.22
		Left Tilted	0.201	1.033	1.052	0.035	1.23	1.25	0.24
WCDMA	WCDMA V	Right Cheek	0.420	0.546	0.409	0.024	0.97	0.83	0.44
		Right Tilted	0.272	0.664	0.488	0.018	0.94	0.76	0.29
		Left Cheek	0.371	1.012	0.657	0.040	1.38	1.03	0.41
		Left Tilted	0.197	1.033	1.052	0.035	1.23	1.25	0.23
	WCDMA IV	Right Cheek	0.253	0.546	0.409	0.024	0.80	0.66	0.28
		Right Tilted	0.088	0.664	0.488	0.018	0.75	0.58	0.11
		Left Cheek	0.113	1.012	0.657	0.040	1.13	0.77	0.15
		Left Tilted	0.098	1.033	1.052	0.035	1.13	1.15	0.13
	WCDMA II	Right Cheek	0.525	0.546	0.409	0.024	1.07	0.93	0.55
		Right Tilted	0.224	0.664	0.488	0.018	0.89	0.71	0.24
		Left Cheek	0.289	1.012	0.657	0.040	1.30	0.95	0.33
		Left Tilted	0.323	1.033	1.052	0.035	1.36	1.38	0.36
LTE	LTE Band 13	Right Cheek	0.274	0.546	0.409	0.024	0.82	0.68	0.30
		Right Tilted	0.171	0.664	0.488	0.018	0.84	0.66	0.19
		Left Cheek	0.273	1.012	0.657	0.040	1.29	0.93	0.31
		Left Tilted	0.191	1.033	1.052	0.035	1.22	1.24	0.23
	LTE Band 26	Right Cheek	0.460	0.546	0.409	0.024	1.01	0.87	0.48
		Right Tilted	0.235	0.664	0.488	0.018	0.90	0.72	0.25
		Left Cheek	0.363	1.012	0.657	0.040	1.38	1.02	0.40
		Left Tilted	0.229	1.033	1.052	0.035	1.26	1.28	0.26
	LTE Band 66	Right Cheek	0.235	0.546	0.409	0.024	0.78	0.64	0.26
		Right Tilted	0.120	0.664	0.488	0.018	0.78	0.61	0.14
		Left Cheek	0.137	1.012	0.657	0.040	1.15	0.79	0.18
		Left Tilted	0.128	1.033	1.052	0.035	1.16	1.18	0.16
	LTE Band 2	Right Cheek	0.369	0.546	0.409	0.024	0.92	0.78	0.39
		Right Tilted	0.244	0.664	0.488	0.018	0.91	0.73	0.26
		Left Cheek	0.296	1.012	0.657	0.040	1.31	0.95	0.34
		Left Tilted	0.350	1.033	1.052	0.035	1.38	1.40	0.39
	LTE Band 7	Right Cheek	0.183	0.546	0.409	0.024	0.73	0.59	0.21
		Right Tilted	0.035	0.664	0.488	0.018	0.70	0.52	0.05
		Left Cheek	0.101	1.012	0.657	0.040	1.11	0.76	0.14
		Left Tilted	0.068	1.033	1.052	0.035	1.10	1.12	0.10
	LTE Band 38	Right Cheek	0.066	0.546	0.409	0.024	0.61	0.48	0.09
		Right Tilted	0.026	0.664	0.488	0.018	0.69	0.51	0.04
		Left Cheek	0.051	1.012	0.657	0.040	1.06	0.71	0.09
		Left Tilted	0.050	1.033	1.052	0.035	1.08	1.10	0.09



16.2 Hotspot Exposure Conditions

WWAN Band	Exposure Position	1	3	6	9	1+3	1+6	1+9	Case No	
		WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth	Summed	Summed	Summed		
		1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)		
GSM	GSM850	Front	0.586	0.338	0.360	0.097	0.92	0.95	0.68	
		Back	1.233	1.163	0.897	0.277	2.40	2.13	1.51	Case 1/23
		Left side	0.422				0.42	0.42	0.42	
		Right side	0.550	0.285	0.226	0.006	0.84	0.78	0.56	
		Top side		0.428	1.181	0.095	0.43	1.18	0.10	
	Bottom side	0.395				0.40	0.40	0.40		
	GSM1900	Front	0.660	0.338	0.360	0.097	1.00	1.02	0.76	
		Back	1.415	1.163	0.897	0.277	2.58	2.31	1.69	Case 2/24/43
		Left side	0.231				0.23	0.23	0.23	
		Right side	0.089	0.285	0.226	0.006	0.37	0.32	0.10	
Top side			0.428	1.181	0.095	0.43	1.18	0.10		
Bottom side	1.246				1.25	1.25	1.25			
WCDMA	WCDMA V	Front	0.588	0.338	0.360	0.097	0.93	0.95	0.69	
		Back	1.190	1.163	0.897	0.277	2.35	2.09	1.47	Case 3/25
		Left side	0.564				0.56	0.56	0.56	
		Right side	0.678	0.285	0.226	0.006	0.96	0.90	0.68	
		Top side		0.428	1.181	0.095	0.43	1.18	0.10	
	Bottom side	0.335				0.34	0.34	0.34		
	WCDMA IV	Front	0.340	0.338	0.360	0.097	0.68	0.70	0.44	
		Back	1.400	1.163	0.897	0.277	2.56	2.30	1.68	Case 4/26/44
		Left side	0.010				0.01	0.01	0.01	
		Right side	0.052	0.285	0.226	0.006	0.34	0.28	0.06	
		Top side		0.428	1.181	0.095	0.43	1.18	0.10	
	Bottom side	1.379				1.38	1.38	1.38		
	WCDMA II	Front	0.462	0.338	0.360	0.097	0.80	0.82	0.56	
		Back	1.443	1.163	0.897	0.277	2.61	2.34	1.72	Case 5/27/45
		Left side	0.218				0.22	0.22	0.22	
Right side		0.121	0.285	0.226	0.006	0.41	0.35	0.13		
Top side			0.428	1.181	0.095	0.43	1.18	0.10		
Bottom side	1.391				1.39	1.39	1.39			
LTE	LTE Band 13	Front	0.458	0.338	0.360	0.097	0.80	0.82	0.56	
		Back	1.009	1.163	0.897	0.277	2.17	1.91	1.29	Case 6/28
		Left side	0.426				0.43	0.43	0.43	
		Right side	0.511	0.285	0.226	0.006	0.80	0.74	0.52	
		Top side		0.428	1.181	0.095	0.43	1.18	0.10	
		Bottom side	0.213				0.21	0.21	0.21	
	LTE Band 26	Front	0.546	0.338	0.360	0.097	0.88	0.91	0.64	
		Back	1.196	1.163	0.897	0.277	2.36	2.09	1.47	Case 7/29
		Left side	0.507				0.51	0.51	0.51	
		Right side	0.558	0.285	0.226	0.006	0.84	0.78	0.56	
		Top side		0.428	1.181	0.095	0.43	1.18	0.10	
		Bottom side	0.401				0.40	0.40	0.40	
	LTE Band 66	Front	0.442	0.338	0.360	0.097	0.78	0.80	0.54	
		Back	1.310	1.163	0.897	0.277	2.47	2.21	1.59	Case 8/30
		Left side	0.007				0.01	0.01	0.01	
		Right side	0.061	0.285	0.226	0.006	0.35	0.29	0.07	
		Top side		0.428	1.181	0.095	0.43	1.18	0.10	
		Bottom side	1.362				1.36	1.36	1.36	
LTE Band 2	Front	0.766	0.338	0.360	0.097	1.10	1.13	0.86		
	Back	1.422	1.163	0.897	0.277	2.59	2.32	1.70	Case 9/31/46	



FCC SAR Test Report

Report No. : FA1N1011

		Left side	0.210				0.21	0.21	0.21	
		Right side	0.111	0.285	0.226	0.006	0.40	0.34	0.12	
		Top side		0.428	1.181	0.095	0.43	1.18	0.10	
		Bottom side	1.330				1.33	1.33	1.33	
	LTE Band 7	Front	0.517	0.338	0.360	0.097	0.86	0.88	0.61	
		Back	1.333	1.163	0.897	0.277	2.50	2.23	1.61	Case 10/32/47
		Left side	0.055				0.06	0.06	0.06	
		Right side	0.011	0.285	0.226	0.006	0.30	0.24	0.02	
		Top side		0.428	1.181	0.095	0.43	1.18	0.10	
	Bottom side	1.339				1.34	1.34	1.34		
	LTE Band 38	Front	0.588	0.338	0.360	0.097	0.93	0.95	0.69	
		Back	1.442	1.163	0.897	0.277	2.61	2.34	1.72	Case 11/33/48
		Left side	0.010				0.01	0.01	0.01	
		Right side	0.006	0.285	0.226	0.006	0.29	0.23	0.01	
		Top side		0.428	1.181	0.095	0.43	1.18	0.10	
Bottom side	1.349				1.35	1.35	1.35			



16.3 Body-Worn Accessory Exposure Conditions

WWAN Band		Exposure Position	1	3	6	9	1+3	1+6	1+9	Case No
			WWAN 1g SAR (W/kg)	2.4GHz WLAN 1g SAR (W/kg)	5GHz WLAN 1g SAR (W/kg)	Bluetooth 1g SAR (W/kg)	Summed 1g SAR (W/kg)	Summed 1g SAR (W/kg)	Summed 1g SAR (W/kg)	
GSM	GSM850	Front	0.586	0.338	0.447	0.097	0.92	1.03	0.68	
		Back	1.233	1.163	1.186	0.277	2.40	2.42	1.51	Case 1/12
		Back with Headset	1.042				1.04	1.04	1.04	
	GSM1900	Front	0.660	0.338	0.447	0.097	1.00	1.11	0.76	
		Back	1.415	1.163	1.186	0.277	2.58	2.60	1.69	Case 2/13/43
		Back with Headset	1.221				1.22	1.22	1.22	
WCDMA	WCDMA V	Front	0.588	0.338	0.447	0.097	0.93	1.04	0.69	
		Back	1.190	1.163	1.186	0.277	2.35	2.38	1.47	Case 3/14
		Back with Headset					0.00	0.00	0.00	
	WCDMA IV	Front	0.586	0.338	0.447	0.097	0.92	1.03	0.68	
		Back	1.400	1.163	1.186	0.277	2.56	2.59	1.68	Case 4/15/44
		Back with Headset	1.103				1.10	1.10	1.10	
	WCDMA II	Front	0.769	0.338	0.447	0.097	1.11	1.22	0.87	
		Back	1.443	1.163	1.186	0.277	2.61	2.63	1.72	Case 5/16/45
		Back with Headset	1.416				1.42	1.42	1.42	
LTE	LTE Band 13	Front	0.458	0.338	0.447	0.097	0.80	0.91	0.56	
		Back	1.009	1.163	1.186	0.277	2.17	2.20	1.29	Case 6/17
		Back with Headset					0.00	0.00	0.00	
	LTE Band 26	Front	0.546	0.338	0.447	0.097	0.88	0.99	0.64	
		Back	1.196	1.163	1.186	0.277	2.36	2.38	1.47	Case 7/18
		Back with Headset					0.00	0.00	0.00	
	LTE Band 66	Front	0.561	0.338	0.447	0.097	0.90	1.01	0.66	
		Back	1.310	1.163	1.186	0.277	2.47	2.50	1.59	Case 8/19
		Back with Headset	1.285				1.29	1.29	1.29	
	LTE Band 2	Front	0.792	0.338	0.447	0.097	1.13	1.24	0.89	
		Back	1.422	1.163	1.186	0.277	2.59	2.61	1.70	Case 9/20/46
		Back with Headset	1.316				1.32	1.32	1.32	
	LTE Band 7	Front	1.044	0.338	0.447	0.097	1.38	1.49	1.14	
		Back	1.333	1.163	1.186	0.277	2.50	2.52	1.61	Case 10/21/47
		Back with Headset	1.116				1.12	1.12	1.12	
LTE Band 38	Front	0.664	0.338	0.447	0.097	1.00	1.11	0.76		
	Back	1.442	1.163	1.186	0.277	2.61	2.63	1.72	Case 11/22/48	
	Back with Headset	1.290				1.29	1.29	1.29		