

FCC SAR Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT2229-3
FCC ID : IHDT56AC7
STANDARD : FCC 47 CFR Part 2 (2.1093)

We, Sporton International Inc. (Shenzhen), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Shenzhen), the test report shall not be reproduced except in full.

Hank Huang

Reviewed by: Hank Huang / Supervisor

Johnny Chen

Approved by: Johnny Chen / Manager



Sporton International Inc. (Shenzhen)
1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055
People's Republic of China



Table of Contents

1. Statement of Compliance 4
2. Administration Data 5
3. Guidance Applied 5
4. Equipment Under Test (EUT) Information 6
4.1 General Information 6
4.2 General LTE SAR Test and Reporting Considerations 8
5. RF Exposure Limits 10
5.1 Uncontrolled Environment 10
5.2 Controlled Environment 10
6. Specific Absorption Rate (SAR) 11
6.1 Introduction 11
6.2 SAR Definition 11
7. System Description and Setup 12
7.1 E-Field Probe 13
7.2 Data Acquisition Electronics (DAE) 13
7.3 Phantom 14
7.4 Device Holder 15
8. Measurement Procedures 16
8.1 Spatial Peak SAR Evaluation 16
8.2 Power Reference Measurement 17
8.3 Area Scan 17
8.4 Zoom Scan 18
8.5 Volume Scan Procedures 18
8.6 Power Drift Monitoring 18
9. Test Equipment List 19
10. System Verification 20
10.1 Tissue Simulating Liquids 20
10.2 Tissue Verification 21
10.3 System Performance Check Results 22
11. RF Exposure Positions 24
11.1 Ear and handset reference point 24
11.2 Definition of the cheek position 25
11.3 Definition of the tilt position 26
11.4 Body Worn Accessory 27
11.5 Product Specific 10g SAR Exposure 28
11.6 Wireless Router 28
12. Conducted RF Output Power (Unit: dBm) 29
13. Antenna Location 35
14. SAR Test Results 36
14.1 Head SAR 37
14.2 Hotspot SAR 39
14.3 Body Worn Accessory SAR 43
14.4 Product Specific SAR 45
14.5 Repeated SAR Measurement 46
15. Simultaneous Transmission Analysis 47
15.1 Head Exposure Conditions 48
15.2 Hotspot Exposure Conditions 49
15.3 Body-Worn Accessory Exposure Conditions 50
15.4 Product Specific Exposure Conditions 51
15.5 SPLSR Evaluation and Analysis 52
16. Uncertainty Assessment 57
17. References 58
Appendix A. Plots of System Performance Check
Appendix B. Plots of High SAR Measurement
Appendix C. DASy Calibration Certificate
Appendix D. Test Setup Photos
Appendix E. Conducted RF Output Power Table



1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for **Motorola Mobility LLC, Mobile Cellular Phone, XT2229-3**, are as follows.

Highest 1g SAR Summary						
Equipment Class	Frequency Band		Head (Separation 0mm)	Hotspot (Separation 5mm)	Body-worn (Separation 5mm)	Highest Simultaneous Transmission 1g SAR (W/kg)
			1g SAR (W/kg)			
Licensed	GSM	GSM850	0.55	1.29	1.29	1.50
		GSM1900	0.32	1.14	1.43	
	WCDMA	Band II	0.38	1.30	1.33	
		Band V	0.46	1.31	1.31	
	LTE	Band 2	0.48	1.28	1.33	
		Band 7	0.13	1.29	1.21	
		Band 26/Band 5	0.47	1.27	1.27	
DTS	WLAN	2.4GHz WLAN	0.83	1.10	1.10	1.41
NII		5GHz WLAN	1.15	1.13	1.18	1.50
DSS	Bluetooth	2.4GHz Bluetooth	<0.10	<0.10	<0.10	1.46
Highest 10g SAR Summary						
Equipment Class	Frequency Band		Product Specific 10g SAR (W/kg) (Separation 0mm)		Highest Simultaneous Transmission 10g SAR (W/kg)	
License	GSM	GSM850	1.89		2.67	
		GSM1900	1.58			
	WCDMA	Band II	1.83			
		Band V	2.02			
	LTE	Band 2	1.87			
		Band 7	1.33			
		Band 26/Band 5	1.96			
NII	WLAN	5GHz WLAN	2.45		2.67	
Date of Testing:			2022/2/14 ~ 2022/2/27			
Remark: This device supports both LTE B5/38 and B26/41. Since the supported frequency span for LTE B5/38 falls completely within the supports frequency span for LTE B26/41, both LTE bands have the same target power, and both LTE bands share the same transmission path; therefore, SAR was only assessed for LTE B26/41.						

Declaration of Conformity:
 The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:
 The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.
 This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for Partial-Body 1g SAR, 4.0 W/kg for Product Specific 10g SAR) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.



2. Administration Data

Sporton International Inc. (Shenzhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Testing Laboratory			
Test Firm	Sporton International Inc. (Shenzhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	SAR02-SZ	CN1256	421272

Applicant	
Company Name	Motorola Mobility LLC
Address	222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

Manufacturer	
Company Name	Motorola Mobility LLC
Address	222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

3. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r03
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 616217 D04 SAR for laptop and tablets v01r02
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05
- FCC KDB 941225 D06 Hotspot Mode SAR v02r01



4. Equipment Under Test (EUT) Information

4.1 General Information

Product Feature & Specification	
Equipment Name	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2229-3
FCC ID	IHDT56AC7
IMEI Code	Sample 1: IMEI 1: 350634170005658 IMEI 2: 350634170006516 Sample 2: IMEI 1: 350634170006961 IMEI 2: 350634170007449
Wireless Technology and Frequency Range	GSM850: 824 MHz ~ 849 MHz GSM1900: 1850 MHz ~ 1910 MHz WCDMA Band II: 1850 MHz ~ 1910 MHz WCDMA Band V: 824 MHz ~ 849 MHz LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 7: 2500 MHz ~ 2570 MHz LTE Band 26: 814 MHz ~ 849 MHz LTE Band 38: 2570 MHz ~ 2620 MHz LTE Band 41: 2496 MHz ~ 2690 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5720 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Mode	GSM/GPRS/EGPRS RMC/AMR 12.2Kbps HSDPA/HSUPA DC-HSDPA HSPA+ (16QAM uplink is not supported) LTE: QPSK, 16QAM, 64QAM WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
HW Version	DVT2
SW Version	STA32.48
GSM / (E)GPRS Transfer mode	Class B – EUT cannot support Packet Switched and Circuit Switched Network simultaneously but can automatically switch between Packet and Circuit Switched Network.
EUT Stage	Identical Prototype
Remark: 1. 802.11n-HT40 is not supported in 2.4GHz WLAN. 2. This device supports VoIP in GPRS, EGPRS, WCDMA and LTE (e.g. for 3rd-party VoIP), LTE supports VoLTE operation. 3. This device 2.4GHz WLAN support hotspot operation and Bluetooth support tethering applications. 4. This device 5.2GHz WLAN/5.8GHz WLAN support hotspot operation, and 5.2GHz WLAN/5.8GHz WLAN supports WiFi Direct (GC/GO), and 5.3GHz / 5.5GHz supports WiFi Direct (GC only). 5. This device does not support DTM operation and supports GPRS/EGPRS mode up to multi-slot class 12. 6. The device implements the power management and receiver detection/hotspot mode for SAR compliance at different exposure conditions (head, body-worn, hotspot, extremity) and the details about the power management decision and sensor detection are provided in the operational description. And the device will invoke corresponding work scenarios power level base on frequency bands/antennas, which can refer to power table at appendix E. 7. There are two different types of EUT. They are single SIM card mobile and dual SIM card mobile. The others are the	



same including circuit design, PCB board, structure and all components. It is special to declare. After pre-scan two types of EUT, we found test result of the sample that dual SIM was the worst, so we chose dual SIM card mobile to perform all tests.

8. For dual SIM card mobile has two SIM slots and supports dual SIM dual standby. The WWAN radio transmission will be enabled by either one SIM at a time (single active). After pre-scan two SIM cards power, we found test result of the SIM1 was the worse, so we chose SIM1 slot to perform all tests.
9. There are two samples. The difference between them could be referred to the XT2229-3_Operational Description of Product Equality Declaration which is exhibited separately. According to the difference, we choose sample 1 for full testing and sample 2 for worst case verification.
10. The device has three headsets. For three headsets only suppliers are different. So we chose headset 1 to perform full SAR testing only.
11. This device has two batteries. For battery 1 was in sample 1, and battery 2 was in sample 2. They were all evaluated for SAR testing conservatively.



4.2 General LTE SAR Test and Reporting Considerations

Summarized necessary items addressed in KDB 941225 D05 v02r05																																																															
FCC ID	IHDT56AC7																																																														
Equipment Name	Mobile Cellular Phone																																																														
Operating Frequency Range of each LTE transmission band	LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 7: 2500 MHz ~ 2570 MHz LTE Band 26: 814 MHz ~ 849 MHz LTE Band 38: 2570 MHz ~ 2620 MHz LTE Band 41: 2496 MHz ~ 2690 MHz																																																														
Channel Bandwidth	LTE Band 2: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 5: 1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 7: 5MHz, 10MHz, 15MHz, 20MHz LTE Band 26: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz LTE Band 38: 5MHz, 10MHz, 15MHz, 20MHz LTE Band 41: 5MHz, 10MHz, 15MHz, 20MHz																																																														
uplink modulations used	QPSK / 16QAM / 64QAM																																																														
LTE Voice / Data requirements	Voice and Data																																																														
LTE Release Version	R11, Cat4																																																														
CA Support	Not Supported																																																														
LTE MPR permanently built-in by design	<p>Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3</p> <table border="1"> <thead> <tr> <th rowspan="2">Modulation</th> <th colspan="6">Channel bandwidth / Transmission bandwidth (N_{RB})</th> <th rowspan="2">MPR (dB)</th> </tr> <tr> <th>1.4 MHz</th> <th>3.0 MHz</th> <th>5 MHz</th> <th>10 MHz</th> <th>15 MHz</th> <th>20 MHz</th> </tr> </thead> <tbody> <tr> <td>QPSK</td> <td>> 5</td> <td>> 4</td> <td>> 8</td> <td>> 12</td> <td>> 16</td> <td>> 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>≤ 5</td> <td>≤ 4</td> <td>≤ 8</td> <td>≤ 12</td> <td>≤ 16</td> <td>≤ 18</td> <td>≤ 1</td> </tr> <tr> <td>16 QAM</td> <td>> 5</td> <td>> 4</td> <td>> 8</td> <td>> 12</td> <td>> 16</td> <td>> 18</td> <td>≤ 2</td> </tr> <tr> <td>64 QAM</td> <td>≤ 5</td> <td>≤ 4</td> <td>≤ 8</td> <td>≤ 12</td> <td>≤ 16</td> <td>≤ 18</td> <td>≤ 2</td> </tr> <tr> <td>64 QAM</td> <td>> 5</td> <td>> 4</td> <td>> 8</td> <td>> 12</td> <td>> 16</td> <td>> 18</td> <td>≤ 3</td> </tr> <tr> <td>256 QAM</td> <td colspan="6">≥ 1</td> <td>≤ 5</td> </tr> </tbody> </table>	Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1	16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2	64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2	64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3	256 QAM	≥ 1						≤ 5
Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)																																																								
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz																																																									
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1																																																								
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1																																																								
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2																																																								
64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2																																																								
64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3																																																								
256 QAM	≥ 1						≤ 5																																																								
LTE A-MPR	In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)																																																														
Spectrum plots for RB configuration	A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.																																																														
Power reduction applied to satisfy SAR compliance	Yes, when operating in receiver/hotspot detect mechanism, head/body-worn/hotspot/extremity will trigger reduced power for some WWAN bands applied to satisfy SAR compliance, the detail please referred to section 12.																																																														

Transmission (H, M, L) channel numbers and frequencies in each LTE band												
LTE Band 2												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	18607	1850.7	18615	1851.5	18625	1852.5	18650	1855	18675	1857.5	18700	1860
M	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880
H	19193	1909.3	19185	1908.5	19175	1907.5	19150	1905	19125	1902.5	19100	1900
LTE Band 5												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20407	824.7	20415	825.5	20425	826.5	20450	829				
M	20525	836.5	20525	836.5	20525	836.5	20525	836.5	20525	836.5	20525	836.5
H	20643	848.3	20635	847.5	20625	846.5	20600	844				
LTE Band 7												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20775	2502.5	20800	2505	20825	2507.5	20850	2510				
M	21100	2535	21100	2535	21100	2535	21100	2535	21100	2535	21100	2535
H	21425	2567.5	21400	2565	21375	2562.5	21350	2560				

LTE Band 26										
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	26697	814.7	26705	815.5	26715	816.5	26740	819	26765	821.5
M	26865	831.5	26865	831.5	26865	831.5	26865	831.5	26865	831.5
H	27033	848.3	27025	847.5	27015	846.5	26990	844	26965	841.5
LTE Band 38										
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz			
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	37775	2572.5	37800	2575	37825	2577.5	37850	2580		
M	38000	2595	38000	2595	38000	2595	38000	2595	38000	2595
H	38225	2617.5	38200	2615	38175	2612.5	38150	2610		

LTE Band 41								
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	39675	2498.5	39700	2501	39725	2503.5	39750	2506
LM	40148	2545.8	40160	2547	40173	2548.3	40185	2549.5
M	40620	2593	40620	2593	40620	2593	40620	2593
HM	41093	2640.3	41080	2639	41068	2637.8	41055	2636.5
H	41565	2687.5	41540	2685	41515	2682.5	41490	2680

5. RF Exposure Limits

5.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

5.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

6. Specific Absorption Rate (SAR)

6.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

6.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$\text{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

7. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:




- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

7.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG).The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – >6 GHz Linearity: ±0.2 dB (30 MHz – 6 GHz)	
Directivity	±0.3 dB in TSL (rotation around probe axis) ±0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 µW/g – >100 mW/g Linearity: ±0.2 dB (noise: typically <1 µW/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

7.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.


The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Photo of DAE


7.3 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

7.4 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

8. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

8.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

8.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

8.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0 is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: $\Delta x_{Area}, \Delta y_{Area}$	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

8.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z	≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm	
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details. * When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

8.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

8.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASYS measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.



9. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	835MHz System Validation Kit	D835V2	4d258	May 07, 2020	May 06, 2023
SPEAG	1900MHz System Validation Kit	D1900V2	5d170	Mar. 26, 2019	Mar. 24, 2022
SPEAG	2450MHz System Validation Kit	D2450V2	924	Sep. 02, 2020	Sep. 01, 2023
SPEAG	2600MHz System Validation Kit	D2600V2	1061	Nov. 26, 2020	Nov. 25, 2023
SPEAG	5000MHz System Validation Kit	D5GHzV2	1113	Sep. 24, 2019	Sep. 22, 2022
SPEAG	Data Acquisition Electronics	DAE4	1664	Mar. 01, 2021	Feb. 28, 2022
SPEAG	Dosimetric E-Field Probe	EX3DV4	7641	Mar. 15, 2021	Mar. 14, 2022
SPEAG	SAM Twin Phantom	QD 000 P40 CD	1670	NCR	NCR
SPEAG	Phone Positioner	N/A	N/A	NCR	NCR
Anritsu	Radio communication analyzer	MT8820C	6201563813	Dec. 28, 2021	Dec. 27, 2022
Anritsu	Radio communication analyzer	MT8821C	6201588577	Apr. 08, 2021	Apr. 07, 2022
Agilent	Wireless Communication Test Set	E5515C	MY50267224	Jul. 14, 2021	Jul. 13, 2022
Keysight	Network Analyzer	E5071C	MY46523671	Oct. 25, 2021	Oct. 24, 2022
Speag	Dielectric Assessment KIT	DAK-3.5	1138	Jun. 09, 2021	Jun. 08, 2022
Agilent	Signal Generator	N5181A	MY50145381	Dec. 28, 2021	Dec. 27, 2022
Anritsu	Power Sensor	MA2411B	1306099	Sep. 29, 2021	Sep. 28, 2022
Anritsu	Power Meter	ML2495A	1349001	Sep. 29, 2021	Sep. 28, 2022
Anritsu	Power Sensor	MA2411B	1542004	Dec. 28, 2021	Dec. 27, 2022
Anritsu	Power Meter	ML2495A	1339473	Dec. 28, 2021	Dec. 27, 2022
R&S	CBT BLUETOOTH TESTER	CBT	100963	Dec. 28, 2021	Dec. 27, 2022
R&S	Spectrum Analyzer	FSP7	100818	Jul. 14, 2021	Jul. 13, 2022
TES	Hygrometer	1310	200505600	Jul. 17, 2021	Jul. 16, 2022
Anymetre	Thermo-Hygrometer	JR593	2015030903	Dec. 30, 2021	Dec. 29, 2022
SPEAG	Device Holder	N/A	N/A	N/A	N/A
AR	Amplifier	5S1G4	0333096	Note 1	
mini-circuits	Amplifier	ZVE-3W-83+	599201528	Note 1	
ARRA	Power Divider	A3200-2	N/A	Note 1	
ET Industries	Dual Directional Coupler	C-058-10	N/A	Note 1	
Weinschel	Attenuator 1	3M-10	N/A	Note 1	
Weinschel	Attenuator 2	3M-20	N/A	Note 1	

Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check
2. Referring to KDB 865664 D01v01r04, the dipole calibration interval can be extended to 3 years with justification. The dipoles are also not physically damaged, or repaired during the interval.
3. The justification data of dipole can be found in appendix C. The return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration.

10. System Verification

10.1 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 11.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 11.2.




Fig 11.1 Photo of Liquid Height for Head SAR




Fig 11.2 Photo of Liquid Height for Body SAR



10.2 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ε _r)
For Head								
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
1800, 1900	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0

Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ε _r)	Conductivity Target (σ)	Permittivity Target (ε _r)	Delta (σ) (%)	Delta (ε _r) (%)	Limit (%)	Date
835	Head	22.1	0.901	40.721	0.90	41.50	0.11	-1.88	±5	2022/2/14
835	Head	22.5	0.927	42.674	0.90	41.50	3.00	2.83	±5	2022/2/17
1900	Head	22.3	1.430	38.742	1.40	40.00	2.14	-3.15	±5	2022/2/15
1900	Head	22.1	1.460	39.123	1.40	40.00	4.29	-2.19	±5	2022/2/18
2450	Head	22.4	1.829	40.081	1.80	39.20	1.61	2.25	±5	2022/2/20
2450	Head	22.8	1.861	39.575	1.80	39.20	3.39	0.96	±5	2022/2/24
2600	Head	22.6	1.974	38.204	1.96	39.00	0.71	-2.04	±5	2022/2/16
2600	Head	22.9	1.922	39.818	1.96	39.00	-1.94	2.10	±5	2022/2/19
5250	Head	22.1	4.764	36.965	4.71	35.95	1.15	2.82	±5	2022/2/21
5250	Head	22.2	4.699	36.046	4.71	35.95	-0.23	0.27	±5	2022/2/22
5600	Head	22.3	5.004	36.093	5.07	35.50	-1.30	1.67	±5	2022/2/25
5600	Head	22.4	5.221	37.021	5.07	35.50	2.98	4.28	±5	2022/2/26
5750	Head	22.1	5.298	35.158	5.22	35.35	1.49	-0.54	±5	2022/2/23
5750	Head	22.2	5.173	35.826	5.22	35.35	-0.90	1.35	±5	2022/2/27

10.3 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

<1g SAR>

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2022/2/14	835	Head	250	4d258	7641	1664	2.300	9.44	9.2	-2.54
2022/2/17	835	Head	250	4d258	7641	1664	2.320	9.44	9.28	-1.69
2022/2/15	1900	Head	250	5d170	7641	1664	9.420	39.00	37.68	-3.38
2022/2/18	1900	Head	250	5d170	7641	1664	9.630	39.00	38.52	-1.23
2022/2/20	2450	Head	250	924	7641	1664	13.100	51.40	52.4	1.95
2022/2/24	2450	Head	250	924	7641	1664	13.300	51.40	53.2	3.50
2022/2/16	2600	Head	250	1061	7641	1664	14.100	56.60	56.4	-0.35
2022/2/19	2600	Head	250	1061	7641	1664	13.800	56.60	55.2	-2.47
2022/2/21	5250	Head	100	1113	7641	1664	7.610	80.50	76.1	-5.47
2022/2/25	5250	Head	100	1113	7641	1664	7.330	80.50	73.3	-8.94
2022/2/22	5600	Head	100	1113	7641	1664	7.880	83.40	78.8	-5.52
2022/2/26	5600	Head	100	1113	7641	1664	7.560	83.40	75.6	-9.35
2022/2/23	5750	Head	100	1113	7641	1664	7.860	80.00	78.6	-1.75
2022/2/27	5750	Head	100	1113	7641	1664	7.700	80.00	77	-3.75

<10g SAR>

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 10g SAR (W/kg)	Targeted 10g SAR (W/kg)	Normalized 10g SAR (W/kg)	Deviation (%)
2022/2/14	835	Head	250	4d258	7641	1664	1.600	6.13	6.4	4.40
2022/2/17	835	Head	250	4d258	7641	1664	1.650	6.13	6.6	7.67
2022/2/15	1900	Head	250	5d170	7641	1664	5.330	20.30	21.32	5.02
2022/2/18	1900	Head	250	5d170	7641	1664	5.550	20.30	22.2	9.36
2022/2/20	2450	Head	250	924	7641	1664	6.060	24.00	24.24	1.00
2022/2/24	2450	Head	250	924	7641	1664	5.700	24.00	22.8	-5.00
2022/2/16	2600	Head	250	1061	7641	1664	6.310	25.10	25.24	0.56
2022/2/19	2600	Head	250	1061	7641	1664	6.140	25.10	24.56	-2.15
2022/2/21	5250	Head	100	1113	7641	1664	2.360	23.10	23.6	2.16
2022/2/25	5250	Head	100	1113	7641	1664	2.250	23.10	22.5	-2.60
2022/2/22	5600	Head	100	1113	7641	1664	2.160	23.80	21.6	-9.24
2022/2/26	5600	Head	100	1113	7641	1664	2.280	23.80	22.8	-4.20
2022/2/23	5750	Head	100	1113	7641	1664	2.160	22.80	21.6	-5.26
2022/2/27	5750	Head	100	1113	7641	1664	2.390	22.80	23.9	4.82




Fig 11.3.1 System Performance Check Setup



Fig 11.3.2 Setup Photo

11. RF Exposure Positions

11.1 Ear and handset reference point

Figure 12.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M,” the left ear reference point (ERP) is marked “LE,” and the right ERP is marked “RE.” Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 12.1.2 The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 12.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 12.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.




Fig 12.1.1 Front, back, and side views of SAM twin phantom




Fig 12.1.2 Close-up side view of phantom showing the ear region.




Fig 12.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

11.2 Definition of the cheek position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 12.2.1 and Figure 12.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 12.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 12.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 12.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 12.2.3. The actual rotation angles should be documented in the test report.




Fig 12.2.1 Handset vertical and horizontal reference lines—“fixed case”




Fig 12.2.2 Handset vertical and horizontal reference lines—“clam-shell case”




Fig 12.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

11.3 Definition of the tilt position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°.
3. Rotate the handset around the horizontal line by 15°.
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 12.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




Fig 12.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.

11.4 Body Worn Accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 12.4). Per KDB648474 D04v01r03, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Fig 12.4 Body Worn Position



11.5 Product Specific 10g SAR Exposure

For smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, According to KDB648474 D04v01r03, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance

1. The normally required head and body-worn accessory SAR test procedures for handsets, including hotspot mode, must be applied.
2. The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions.6 The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.

11.6 Wireless Router

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v02r01 where SAR test considerations for handsets ($L \times W \geq 9$ cm x 5 cm) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.


12. Conducted RF Output Power (Unit: dBm)

The detailed conducted power table can refer to Appendix E.


<LTE Conducted Power>

General Note:

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r05, for QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r05, 16QAM/64QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM/64QAM SAR testing is not required.
7. Per KDB 941225 D05v02r05, smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
8. For LTE B5 / B26 / B38 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
9. LTE B5/38 SAR test was covered by B26/41; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. the maximum output power, including tolerance, for the smaller band is \leq the larger band to qualify for the SAR test exclusion
 - b. the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band
10. According to 2017 TCB workshop, for 64 QAM and 16 QAM should be verified by checking the signal constellation with a call box to avoid incorrect maximum power levels due to MPR and other requirements associated with signal modulation, and the following figure is taken from the "Fundamental Measurement >> Modulation Analysis >> constellation" mode of the device connect to the MT8821C base station, therefore, the device 64QAM and 16QAM signal modulation are correct.



64QAM



16QAM

<TDD LTE SAR Measurement>

TDD LTE configuration setup for SAR measurement

SAR was tested with a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by 3GPP.

- a. 3GPP TS 36.211 section 4.2 for Type 2 Frame Structure and Table 4.2-2 for uplink-downlink configurations
- b. "special subframe S" contains both uplink and downlink transmissions, it has been taken into consideration to determine the transmission duty factor according to the worst case uplink and downlink cyclic prefix requirements for UpPTS
- c. Establishing connections with base station simulators ensure a consistent means for testing SAR and recommended for evaluating SAR. The Anritsu MT8820C (firmware: #22.52#004) was used for LTE output power measurements and SAR testing.




Figure 4.2-1: Frame structure type 2 (for 5 ms switch-point periodicity).

Table 4.2-2: Uplink-downlink configurations.

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS).

Special subframe configuration	Normal cyclic prefix in downlink			Extended cyclic prefix in downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	$6592 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$	$7680 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$
1	$19760 \cdot T_s$			$20480 \cdot T_s$		
2	$21952 \cdot T_s$			$23040 \cdot T_s$		
3	$24144 \cdot T_s$			$25600 \cdot T_s$		
4	$26336 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$	$7680 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$
5	$6592 \cdot T_s$			$20480 \cdot T_s$		
6	$19760 \cdot T_s$			$23040 \cdot T_s$		
7	$21952 \cdot T_s$			$12800 \cdot T_s$		
8	$24144 \cdot T_s$			-		
9	$13168 \cdot T_s$	-	-	-	-	-

Special subframe (30720·T _s): Normal cyclic prefix in downlink (UpPTS)			
	Special subframe configuration	Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
Uplink duty factor in one special subframe	0~4	7.13%	8.33%
	5~9	14.3%	16.7%

Special subframe(30720·T _s): Extended cyclic prefix in downlink (UpPTS)			
	Special subframe configuration	Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
Uplink duty factor in one special subframe	0~3	7.13%	8.33%
	4~7	14.3%	16.7%

The highest duty factor is resulted from:

For LTE Band 41 Power class 3

- i. Uplink-downlink configuration: 0. In a half-frame consisted of 5 subframes, uplink operation is in 3 uplink subframes and 1 special subframe.
- ii. special subframe configuration: 5-9 for normal cyclic prefix in downlink, 4-7 for extended cyclic prefix in downlink
- iii. for special subframe with extended cyclic prefix in uplink, the total uplink duty factor in one half-frame is: $(3+0.167)/5 = 63.3\%$
- iv. for special subframe with normal cyclic prefix in uplink, the total uplink duty factor in one half-frame is: $(3+0.143)/5 = 62.9\%$
- v. For TDD LTE SAR measurement, the duty cycle 1:1.59 (62.9 %) was used perform testing and considering the theoretical duty cycle of 63.3% for extended cyclic prefix in the uplink, and the theoretical duty cycle of 62.9% for normal cyclic prefix in uplink, a scaling factor of extended cyclic prefix $63.3\%/62.9\% = 1.006$ is applied to scale-up the measured SAR result. The scaled TDD LTE SAR = measured SAR (W/kg)* Tune-up Scaling Factor* scaling factor for extended cyclic prefix.

<WLAN Conducted Power>

General Note:


1. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
2. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
3. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
4. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures.18 The initial test position procedure is described in the following:
 - a. When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
 - b. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
 - c. For all positions/configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.



<2.4GHz Bluetooth>

General Note:

1. For 2.4GHz Bluetooth SAR testing was selected 1Mbps, due to its highest average power.
2. The Bluetooth duty cycle is 76.91 % as following figure, according to 2016 Oct. TCB workshop for Bluetooth SAR scaling need further consideration and the maximum duty cycle is 100%, therefore the actual duty cycle will be scaled up to100% for Bluetooth reported SAR calculation





13. Antenna Location

The detailed antenna location information can refer to SAR Test Setup Photos.

14. SAR Test Results

General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of BT/WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - c. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
 - d. For BT/WLAN: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
 - e. For TDD LTE SAR measurement of power class 3, the duty cycle 1:1.59 (62.9 %) was used perform testing and considering the theoretical duty cycle of 63.3% for extended cyclic prefix in the uplink, and the theoretical duty cycle of 62.9% for normal cyclic prefix in uplink, a scaling factor of extended cyclic prefix $63.3\%/62.9\% = 1.006$ is applied to scale-up the measured SAR result. The Reported TDD LTE SAR = measured SAR (W/kg)* Tune-up Scaling Factor* scaling factor for extended cyclic prefix.
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required when the measured SAR is ≥ 0.8 W/kg. Per KDB 865664 D01v01r04, if the extremity repeated SAR is necessary, the same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.
4. The device implements the power management and receiver detection/hotspot mode for SAR compliance at different exposure conditions (head, body-worn, hotspot, extremity) and the details about the power management decision and sensor detection are provided in the operational description. And the device will invoke corresponding work scenarios power level base on frequency bands/antennas, which can refer to power table at appendix E.
5. For dual SIM card mobile has two SIM slots and supports dual SIM dual standby. The WWAN radio transmission will be enabled by either one SIM at a time (single active). After pre-scan two SIM cards power, we found test result of the SIM1 was the worse, so we chose SIM1 slot to perform all tests.
6. There are two samples. The difference between them could be referred to the XT2229-3_Operational Description of Product Equality Declaration which is exhibited separately. According to the difference, we choose sample 1 for full testing and sample 2 for worst case verification.
7. The device has three headsets. For three headsets only suppliers are different. So we chose headset 1 to perform full SAR testing only.
8. This device has two batteries. For battery 1 was in sample 1, and battery 2 was in sample 2. They were all evaluated for SAR testing conservatively.
9. The following table "n/a" means the measured SAR is too small to find the 1g cube SAR.



14.1 Head SAR

Table with columns: Plot No., Band, BW (MHz), Modulation, RB Size, RB offset, Mode, Test Position, Gap (mm), Antenna, Power Reduction, Ch., Freq. (MHz), Sample, Average Power (dBm), Tune-Up Limit (dBm), Tune-up Scaling Factor, Power Drift (dB), Measured 1g SAR (W/kg), Reported 1g SAR (W/kg). Rows are grouped by frequency bands: 835MHz, 1900MHz, and 1900MHz.



Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Antenna	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
2600MHz																				
07	LTE Band 7	20M	QPSK	1	49	Right Cheek	0mm	Ant 1	Full	21100	2535	1	23.29	24.00	1.178	-	-	0.03	0.112	0.132
	LTE Band 7	20M	QPSK	1	49	Right Tilted	0mm	Ant 1	Full	21100	2535	1	23.29	24.00	1.178	-	-	-	n/a	n/a
	LTE Band 7	20M	QPSK	1	49	Left Cheek	0mm	Ant 1	Full	21100	2535	1	23.29	24.00	1.178	-	-	0.02	0.055	0.065
	LTE Band 7	20M	QPSK	1	49	Left Tilted	0mm	Ant 1	Full	21100	2535	1	23.29	24.00	1.178	-	-	-	n/a	n/a
	LTE Band 7	20M	QPSK	50	0	Right Cheek	0mm	Ant 1	Full	21100	2535	1	22.06	23.00	1.242	-	-	0.05	0.099	0.123
	LTE Band 7	20M	QPSK	50	0	Right Tilted	0mm	Ant 1	Full	21100	2535	1	22.06	23.00	1.242	-	-	-	n/a	n/a
	LTE Band 7	20M	QPSK	50	0	Left Cheek	0mm	Ant 1	Full	21100	2535	1	22.06	23.00	1.242	-	-	0.01	0.044	0.055
	LTE Band 7	20M	QPSK	50	0	Left Tilted	0mm	Ant 1	Full	21100	2535	1	22.06	23.00	1.242	-	-	-	n/a	n/a
08	LTE Band 41	20M	QPSK	1	49	Right Cheek	0mm	Ant 1	Full	40185	2549.5	1	23.28	24.00	1.180	62.9	1.006	-0.05	0.060	0.071
	LTE Band 41	20M	QPSK	1	49	Right Tilted	0mm	Ant 1	Full	40185	2549.5	1	23.28	24.00	1.180	62.9	1.006	-	n/a	n/a
	LTE Band 41	20M	QPSK	1	49	Left Cheek	0mm	Ant 1	Full	40185	2549.5	1	23.28	24.00	1.180	62.9	1.006	-0.02	0.038	0.045
	LTE Band 41	20M	QPSK	1	49	Left Tilted	0mm	Ant 1	Full	40185	2549.5	1	23.28	24.00	1.180	62.9	1.006	-	n/a	n/a
	LTE Band 41	20M	QPSK	50	0	Right Cheek	0mm	Ant 1	Full	40185	2549.5	1	22.21	23.00	1.199	62.9	1.006	0.06	0.048	0.058
	LTE Band 41	20M	QPSK	50	0	Right Tilted	0mm	Ant 1	Full	40185	2549.5	1	22.21	23.00	1.199	62.9	1.006	-	n/a	n/a
	LTE Band 41	20M	QPSK	50	0	Left Cheek	0mm	Ant 1	Full	40185	2549.5	1	22.21	23.00	1.199	62.9	1.006	-	n/a	n/a
	LTE Band 41	20M	QPSK	50	0	Left Tilted	0mm	Ant 1	Full	40185	2549.5	1	22.21	23.00	1.199	62.9	1.006	-	n/a	n/a

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	
2450MHz																		
	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	Ant 3	Reduced	6	2437	1	16.50	17.50	1.259	99.27	1.007	-0.15	0.298	0.378	
	WLAN2.4GHz	802.11b 1Mbps	Right Tilted	0mm	Ant 3	Reduced	6	2437	1	16.50	17.50	1.259	99.27	1.007	0.18	0.283	0.359	
09	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	Ant 3	Reduced	6	2437	1	16.50	17.50	1.259	99.27	1.007	0.16	0.651	0.825	
	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	Ant 3	Reduced	6	2437	2	16.50	17.50	1.259	99.27	1.007	0.11	0.551	0.699	
	WLAN2.4GHz	802.11b 1Mbps	Left Tilted	0mm	Ant 3	Reduced	6	2437	1	16.50	17.50	1.259	99.27	1.007	-0.17	0.604	0.766	
	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	Ant 3	Reduced	1	2412	1	16.40	17.50	1.288	99.27	1.007	0.06	0.609	0.790	
	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	Ant 3	Reduced	11	2462	1	16.30	17.50	1.318	99.27	1.007	0.05	0.532	0.706	
	Bluetooth	DH5 1Mbps	Right Cheek	0mm	Ant 3	Full	78	2480	1	9.40	10.50	1.288	76.91	1.300	-	n/a	n/a	
	Bluetooth	DH5 1Mbps	Right Tilted	0mm	Ant 3	Full	78	2480	1	9.40	10.50	1.288	76.91	1.300	-	n/a	n/a	
10	Bluetooth	DH5 1Mbps	Left Cheek	0mm	Ant 3	Full	78	2480	1	9.40	10.50	1.288	76.91	1.300	0.08	0.015	0.025	
	Bluetooth	DH5 1Mbps	Left Tilted	0mm	Ant 3	Full	78	2480	1	9.40	10.50	1.288	76.91	1.300	-0.18	0.008	0.013	
5000MHz																		
	WLAN5.3GHz	802.11ac-VHT80 MCS0	Right Cheek	0mm	Ant 3	Reduced	58	5290	1	11.90	13.50	1.445	87.77	1.139	-0.18	0.215	0.354	
	WLAN5.3GHz	802.11ac-VHT80 MCS0	Right Tilted	0mm	Ant 3	Reduced	58	5290	1	11.90	13.50	1.445	87.77	1.139	-0.07	0.262	0.431	
	WLAN5.3GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	Ant 3	Reduced	58	5290	1	11.90	13.50	1.445	87.77	1.139	0.05	0.329	0.542	
11	WLAN5.3GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Ant 3	Reduced	58	5290	1	11.90	13.50	1.445	87.77	1.139	0.15	0.691	1.138	
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Right Cheek	0mm	Ant 3	Reduced	138	5690	1	10.82	12.50	1.472	87.77	1.139	0.01	0.236	0.396	
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Right Tilted	0mm	Ant 3	Reduced	138	5690	1	10.82	12.50	1.472	87.77	1.139	0.11	0.297	0.498	
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	Ant 3	Reduced	138	5690	1	10.82	12.50	1.472	87.77	1.139	-0.01	0.321	0.538	
12	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Ant 3	Reduced	138	5690	1	10.82	12.50	1.472	87.77	1.139	0.03	0.495	0.830	
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Ant 3	Reduced	106	5530	1	10.56	12.50	1.563	87.77	1.139	0.02	0.382	0.680	
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Ant 3	Reduced	122	5610	1	10.57	12.50	1.560	87.77	1.139	0.04	0.377	0.670	
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Right Cheek	0mm	Ant 3	Reduced	155	5775	1	11.96	13.00	1.271	87.77	1.139	0.14	0.330	0.478	
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Right Tilted	0mm	Ant 3	Reduced	155	5775	1	11.96	13.00	1.271	87.77	1.139	-0.14	0.408	0.590	
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	Ant 3	Reduced	155	5775	1	11.96	13.00	1.271	87.77	1.139	-0.1	0.440	0.637	
13	WLAN5.8GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Ant 3	Reduced	155	5775	1	11.96	13.00	1.271	87.77	1.139	0.16	0.796	1.152	
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Ant 3	Reduced	155	5775	2	11.96	13.00	1.271	87.77	1.139	0.03	0.624	0.903	



14.2 Hotspot SAR

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Mode	Test Position	Gap (mm)	Antenna	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
835MHz																			
	GSM850	-	-	-	-	GPRS 2 Tx slots	Front	5mm	Ant 1	Reduced	251	848.8	1	30.15	31.00	1.216	0.04	0.528	0.642
	GSM850	-	-	-	-	GPRS 2 Tx slots	Back	5mm	Ant 1	Reduced	251	848.8	1	30.15	31.00	1.216	-0.15	0.961	1.169
	GSM850	-	-	-	-	GPRS 2 Tx slots	Left Side	5mm	Ant 1	Reduced	251	848.8	1	30.15	31.00	1.216	-0.07	0.368	0.448
	GSM850	-	-	-	-	GPRS 2 Tx slots	Right Side	5mm	Ant 1	Reduced	251	848.8	1	30.15	31.00	1.216	-0.03	0.503	0.612
	GSM850	-	-	-	-	GPRS 2 Tx slots	Bottom Side	5mm	Ant 1	Reduced	251	848.8	1	30.15	31.00	1.216	0.17	0.543	0.660
	GSM850	-	-	-	-	GPRS 2 Tx slots	Back	5mm	Ant 1	Reduced	128	824.2	1	30.10	31.00	1.230	-0.16	0.952	1.171
14	GSM850	-	-	-	-	GPRS 2 Tx slots	Back	5mm	Ant 1	Reduced	189	836.4	1	30.08	31.00	1.236	-0.05	1.040	1.285
	WCDMA V	-	-	-	-	RMC 12.2Kbps	Front	5mm	Ant 1	Full	4182	836.4	1	22.82	24.00	1.312	0.05	0.560	0.735
15	WCDMA V	-	-	-	-	RMC 12.2Kbps	Back	5mm	Ant 1	Full	4182	836.4	1	22.82	24.00	1.312	0.02	1.000	1.312
	WCDMA V	-	-	-	-	RMC 12.2Kbps	Back	5mm	Ant 1	Full	4182	836.4	2	22.82	24.00	1.312	0.1	0.883	1.159
	WCDMA V	-	-	-	-	RMC 12.2Kbps	Left Side	5mm	Ant 1	Full	4182	836.4	1	22.82	24.00	1.312	0.15	0.429	0.563
	WCDMA V	-	-	-	-	RMC 12.2Kbps	Right Side	5mm	Ant 1	Full	4182	836.4	1	22.82	24.00	1.312	0.1	0.476	0.625
	WCDMA V	-	-	-	-	RMC 12.2Kbps	Bottom Side	5mm	Ant 1	Full	4182	836.4	1	22.82	24.00	1.312	-0.06	0.546	0.716
	WCDMA V	-	-	-	-	RMC 12.2Kbps	Back	5mm	Ant 1	Full	4132	826.4	1	22.72	24.00	1.343	0.18	0.921	1.237
	WCDMA V	-	-	-	-	RMC 12.2Kbps	Back	5mm	Ant 1	Full	4233	846.6	1	22.67	24.00	1.358	0.03	0.890	1.209
	LTE Band 26	15M	QPSK	1	37	-	Front	5mm	Ant 1	Full	26865	831.5	1	23.00	24.00	1.259	0.03	0.571	0.719
16	LTE Band 26	15M	QPSK	1	37	-	Back	5mm	Ant 1	Full	26865	831.5	1	23.00	24.00	1.259	-0.01	1.010	1.272
	LTE Band 26	15M	QPSK	1	37	-	Left Side	5mm	Ant 1	Full	26865	831.5	1	23.00	24.00	1.259	0.19	0.297	0.374
	LTE Band 26	15M	QPSK	1	37	-	Right Side	5mm	Ant 1	Full	26865	831.5	1	23.00	24.00	1.259	-0.05	0.381	0.480
	LTE Band 26	15M	QPSK	1	37	-	Bottom Side	5mm	Ant 1	Full	26865	831.5	1	23.00	24.00	1.259	-0.04	0.583	0.734
	LTE Band 26	15M	QPSK	36	0	-	Front	5mm	Ant 1	Full	26865	831.5	1	21.96	23.00	1.271	-0.14	0.432	0.549
	LTE Band 26	15M	QPSK	36	0	-	Back	5mm	Ant 1	Full	26865	831.5	1	21.96	23.00	1.271	-0.09	0.645	0.820
	LTE Band 26	15M	QPSK	36	0	-	Left Side	5mm	Ant 1	Full	26865	831.5	1	21.96	23.00	1.271	-0.02	0.256	0.325
	LTE Band 26	15M	QPSK	36	0	-	Right Side	5mm	Ant 1	Full	26865	831.5	1	21.96	23.00	1.271	0.03	0.331	0.421
	LTE Band 26	15M	QPSK	36	0	-	Bottom Side	5mm	Ant 1	Full	26865	831.5	1	21.96	23.00	1.271	0.09	0.514	0.653
	LTE Band 26	15M	QPSK	75	0	-	Back	5mm	Ant 1	Full	26865	831.5	1	21.85	23.00	1.303	0.05	0.764	0.996



Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Mode	Test Position	Gap (mm)	Antenna	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
1900MHz																			
	GSM1900	-	-	-	-	GPRS 2 Tx slots	Front	5mm	Ant 1	Reduced	661	1880	1	22.75	24.00	1.334	-0.18	0.295	0.393
	GSM1900	-	-	-	-	GPRS 2 Tx slots	Back	5mm	Ant 1	Reduced	661	1880	1	22.75	24.00	1.334	0.02	0.452	0.603
	GSM1900	-	-	-	-	GPRS 2 Tx slots	Left Side	5mm	Ant 1	Reduced	661	1880	1	22.75	24.00	1.334	-0.13	0.144	0.192
	GSM1900	-	-	-	-	GPRS 2 Tx slots	Right Side	5mm	Ant 1	Reduced	661	1880	1	22.75	24.00	1.334	0.05	0.081	0.108
	GSM1900	-	-	-	-	GPRS 2 Tx slots	Bottom Side	5mm	Ant 1	Reduced	661	1880	1	22.75	24.00	1.334	0.09	0.636	0.848
17	GSM1900	-	-	-	-	GPRS 2 Tx slots	Bottom Side	5mm	Ant 1	Reduced	512	1850.2	1	22.65	24.00	1.365	0.04	0.832	1.135
	GSM1900	-	-	-	-	GPRS 2 Tx slots	Bottom Side	5mm	Ant 1	Reduced	810	1909.8	1	22.71	24.00	1.346	0.07	0.553	0.744
	WCDMA II	-	-	-	-	RMC 12.2Kbps	Front	5mm	Ant 1	Reduced	9400	1880	1	15.95	17.00	1.274	0.19	0.395	0.503
	WCDMA II	-	-	-	-	RMC 12.2Kbps	Back	5mm	Ant 1	Reduced	9400	1880	1	15.95	17.00	1.274	-0.14	0.601	0.765
	WCDMA II	-	-	-	-	RMC 12.2Kbps	Left Side	5mm	Ant 1	Reduced	9400	1880	1	15.95	17.00	1.274	0.12	0.179	0.228
	WCDMA II	-	-	-	-	RMC 12.2Kbps	Right Side	5mm	Ant 1	Reduced	9400	1880	1	15.95	17.00	1.274	0.07	0.091	0.116
	WCDMA II	-	-	-	-	RMC 12.2Kbps	Bottom Side	5mm	Ant 1	Reduced	9400	1880	1	15.95	17.00	1.274	0.14	0.834	1.062
18	WCDMA II	-	-	-	-	RMC 12.2Kbps	Bottom Side	5mm	Ant 1	Reduced	9262	1852.4	1	15.91	17.00	1.285	-0.16	1.010	1.298
	WCDMA II	-	-	-	-	RMC 12.2Kbps	Bottom Side	5mm	Ant 1	Reduced	9262	1852.4	2	15.91	17.00	1.285	0.03	0.985	1.266
	WCDMA II	-	-	-	-	RMC 12.2Kbps	Bottom Side	5mm	Ant 1	Reduced	9538	1907.6	1	15.87	17.00	1.297	0.1	0.769	0.998
	LTE Band 2	20M	QPSK	1	49	-	Front	5mm	Ant 1	Reduced	18900	1880	1	16.13	17.00	1.222	0.07	0.322	0.393
	LTE Band 2	20M	QPSK	1	49	-	Back	5mm	Ant 1	Reduced	18900	1880	1	16.13	17.00	1.222	-0.01	0.501	0.612
	LTE Band 2	20M	QPSK	1	49	-	Left Side	5mm	Ant 1	Reduced	18900	1880	1	16.13	17.00	1.222	-0.15	0.182	0.222
	LTE Band 2	20M	QPSK	1	49	-	Right Side	5mm	Ant 1	Reduced	18900	1880	1	16.13	17.00	1.222	-0.14	0.091	0.111
	LTE Band 2	20M	QPSK	1	49	-	Bottom Side	5mm	Ant 1	Reduced	18900	1880	1	16.13	17.00	1.222	-0.14	0.838	1.024
19	LTE Band 2	20M	QPSK	1	49	-	Bottom Side	5mm	Ant 1	Reduced	18700	1860	1	15.98	17.00	1.265	0.16	1.010	1.277
	LTE Band 2	20M	QPSK	1	49	-	Bottom Side	5mm	Ant 1	Reduced	19100	1900	1	15.90	17.00	1.288	-0.17	0.786	1.013
	LTE Band 2	20M	QPSK	50	0	-	Front	5mm	Ant 1	Reduced	18900	1880	1	15.12	16.00	1.225	-0.07	0.301	0.369
	LTE Band 2	20M	QPSK	50	0	-	Back	5mm	Ant 1	Reduced	18900	1880	1	15.12	16.00	1.225	0.08	0.455	0.557
	LTE Band 2	20M	QPSK	50	0	-	Left Side	5mm	Ant 1	Reduced	18900	1880	1	15.12	16.00	1.225	-0.09	0.148	0.181
	LTE Band 2	20M	QPSK	50	0	-	Right Side	5mm	Ant 1	Reduced	18900	1880	1	15.12	16.00	1.225	-0.17	0.074	0.091
	LTE Band 2	20M	QPSK	50	0	-	Bottom Side	5mm	Ant 1	Reduced	18900	1880	1	15.12	16.00	1.225	-0.08	0.674	0.825
	LTE Band 2	20M	QPSK	50	0	-	Bottom Side	5mm	Ant 1	Reduced	18700	1860	1	15.10	16.00	1.230	0.02	0.686	0.844
	LTE Band 2	20M	QPSK	50	0	-	Bottom Side	5mm	Ant 1	Reduced	19100	1900	1	14.98	16.00	1.265	-0.08	0.632	0.799
	LTE Band 2	20M	QPSK	100	0	-	Bottom Side	5mm	Ant 1	Reduced	18900	1880	1	15.04	16.00	1.247	-0.08	0.668	0.833



Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Antenna	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
2600MHz																				
	LTE Band 7	20M	QPSK	1	49	Front	5mm	Ant 1	Reduced	21100	2535	1	13.35	14.00	1.161	-	-	0.01	0.441	0.512
	LTE Band 7	20M	QPSK	1	49	Back	5mm	Ant 1	Reduced	21100	2535	1	13.35	14.00	1.161	-	-	0.02	0.825	0.958
	LTE Band 7	20M	QPSK	1	49	Left Side	5mm	Ant 1	Reduced	21100	2535	1	13.35	14.00	1.161	-	-	-	n/a	n/a
	LTE Band 7	20M	QPSK	1	49	Right Side	5mm	Ant 1	Reduced	21100	2535	1	13.35	14.00	1.161	-	-	-	n/a	n/a
20	LTE Band 7	20M	QPSK	1	49	Bottom Side	5mm	Ant 1	Reduced	21100	2535	1	13.35	14.00	1.161	-	-	0.05	1.110	1.289
	LTE Band 7	20M	QPSK	1	49	Bottom Side	5mm	Ant 1	Reduced	20850	2510	1	13.29	14.00	1.178	-	-	-0.02	0.880	1.036
	LTE Band 7	20M	QPSK	1	49	Bottom Side	5mm	Ant 1	Reduced	21350	2560	1	13.30	14.00	1.175	-	-	-0.03	0.956	1.123
	LTE Band 7	20M	QPSK	1	49	Back	5mm	Ant 1	Reduced	20850	2510	1	13.29	14.00	1.178	-	-	-0.17	0.665	0.783
	LTE Band 7	20M	QPSK	1	49	Back	5mm	Ant 1	Reduced	21350	2560	1	13.30	14.00	1.175	-	-	0.13	0.802	0.942
	LTE Band 7	20M	QPSK	50	0	Front	5mm	Ant 1	Reduced	21100	2535	1	12.35	13.00	1.161	-	-	0.05	0.338	0.393
	LTE Band 7	20M	QPSK	50	0	Back	5mm	Ant 1	Reduced	21100	2535	1	12.35	13.00	1.161	-	-	0.03	0.641	0.744
	LTE Band 7	20M	QPSK	50	0	Left Side	5mm	Ant 1	Reduced	21100	2535	1	12.35	13.00	1.161	-	-	-	n/a	n/a
	LTE Band 7	20M	QPSK	50	0	Right Side	5mm	Ant 1	Reduced	21100	2535	1	12.35	13.00	1.161	-	-	-	n/a	n/a
	LTE Band 7	20M	QPSK	50	0	Bottom Side	5mm	Ant 1	Reduced	21100	2535	1	12.35	13.00	1.161	-	-	-0.03	0.795	0.923
	LTE Band 7	20M	QPSK	50	0	Bottom Side	5mm	Ant 1	Reduced	20850	2510	1	12.22	13.00	1.197	-	-	0.02	0.658	0.787
	LTE Band 7	20M	QPSK	50	0	Bottom Side	5mm	Ant 1	Reduced	21350	2560	1	12.33	13.00	1.167	-	-	-0.12	0.770	0.898
	LTE Band 7	20M	QPSK	100	0	Back	5mm	Ant 1	Reduced	21100	2535	1	12.31	13.00	1.172	-	-	0.12	0.601	0.704
	LTE Band 7	20M	QPSK	100	0	Bottom Side	5mm	Ant 1	Reduced	21100	2535	1	12.31	13.00	1.172	-	-	0.01	0.795	0.932
	LTE Band 41	20M	QPSK	1	49	Front	5mm	Ant 1	Reduced	401852549.5		1	14.50	15.50	1.259	62.9	1.006	0.18	0.385	0.488
	LTE Band 41	20M	QPSK	1	49	Back	5mm	Ant 1	Reduced	401852549.5		1	14.50	15.50	1.259	62.9	1.006	0.14	0.732	0.927
	LTE Band 41	20M	QPSK	1	49	Left Side	5mm	Ant 1	Reduced	401852549.5		1	14.50	15.50	1.259	62.9	1.006	-	n/a	n/a
	LTE Band 41	20M	QPSK	1	49	Right Side	5mm	Ant 1	Reduced	401852549.5		1	14.50	15.50	1.259	62.9	1.006	-	n/a	n/a
21	LTE Band 41	20M	QPSK	1	49	Bottom Side	5mm	Ant 1	Reduced	401852549.5		1	14.50	15.50	1.259	62.9	1.006	-0.08	1.110	1.406
	LTE Band 41	20M	QPSK	1	49	Bottom Side	5mm	Ant 1	Reduced	401852549.5		2	14.50	15.50	1.259	62.9	1.006	0.05	0.802	1.016
	LTE Band 41	20M	QPSK	1	49	Bottom Side	5mm	Ant 1	Reduced	39750	2506	1	14.44	15.50	1.276	62.9	1.006	0.09	0.899	1.154
	LTE Band 41	20M	QPSK	1	49	Bottom Side	5mm	Ant 1	Reduced	40620	2593	1	14.41	15.50	1.285	62.9	1.006	0.13	0.750	0.970
	LTE Band 41	20M	QPSK	1	49	Bottom Side	5mm	Ant 1	Reduced	410552636.5		1	14.15	15.50	1.365	62.9	1.006	-0.03	0.446	0.612
	LTE Band 41	20M	QPSK	1	49	Bottom Side	5mm	Ant 1	Reduced	41490	2680	1	14.15	15.50	1.365	62.9	1.006	-0.16	0.288	0.395
	LTE Band 41	20M	QPSK	1	49	Back	5mm	Ant 1	Reduced	39750	2506	1	14.44	15.50	1.276	62.9	1.006	-0.16	0.561	0.720
	LTE Band 41	20M	QPSK	1	49	Back	5mm	Ant 1	Reduced	40620	2593	1	14.41	15.50	1.285	62.9	1.006	0.05	0.553	0.715
	LTE Band 41	20M	QPSK	1	49	Back	5mm	Ant 1	Reduced	410552636.5		1	14.15	15.50	1.365	62.9	1.006	0.18	0.301	0.413
	LTE Band 41	20M	QPSK	1	49	Back	5mm	Ant 1	Reduced	41490	2680	1	14.15	15.50	1.365	62.9	1.006	0.05	0.201	0.276
	LTE Band 41	20M	QPSK	50	0	Front	5mm	Ant 1	Reduced	401852549.5		1	13.41	14.50	1.285	62.9	1.006	0.03	0.301	0.389
	LTE Band 41	20M	QPSK	50	0	Back	5mm	Ant 1	Reduced	401852549.5		1	13.41	14.50	1.285	62.9	1.006	0.02	0.562	0.727
	LTE Band 41	20M	QPSK	50	0	Left Side	5mm	Ant 1	Reduced	401852549.5		1	13.41	14.50	1.285	62.9	1.006	-	n/a	n/a
	LTE Band 41	20M	QPSK	50	0	Right Side	5mm	Ant 1	Reduced	401852549.5		1	13.41	14.50	1.285	62.9	1.006	-	n/a	n/a
	LTE Band 41	20M	QPSK	50	0	Bottom Side	5mm	Ant 1	Reduced	401852549.5		1	13.41	14.50	1.285	62.9	1.006	-0.01	0.798	1.032
	LTE Band 41	20M	QPSK	50	0	Bottom Side	5mm	Ant 1	Reduced	39750	2506	1	13.28	14.50	1.324	62.9	1.006	-0.12	0.702	0.935
	LTE Band 41	20M	QPSK	50	0	Bottom Side	5mm	Ant 1	Reduced	40620	2593	1	13.19	14.50	1.352	62.9	1.006	0.03	0.623	0.847
	LTE Band 41	20M	QPSK	50	0	Bottom Side	5mm	Ant 1	Reduced	410552636.5		1	13.12	14.50	1.374	62.9	1.006	-0.09	0.363	0.502
	LTE Band 41	20M	QPSK	50	0	Bottom Side	5mm	Ant 1	Reduced	41490	2680	1	12.98	14.50	1.419	62.9	1.006	-0.09	0.238	0.340
	LTE Band 41	20M	QPSK	100	0	Back	5mm	Ant 1	Reduced	401852549.5		1	13.38	14.50	1.294	62.9	1.006	0.03	0.589	0.767
	LTE Band 41	20M	QPSK	100	0	Bottom Side	5mm	Ant 1	Reduced	401852549.5		1	13.38	14.50	1.294	62.9	1.006	0.06	0.783	1.019



Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
2450MHz																	
	WLAN2.4GHz	802.11b 1Mbps	Front	5mm	Ant 3	Reduced	6	2437	1	15.40	16.50	1.288	99.27	1.007	0.17	0.226	0.293
22	WLAN2.4GHz	802.11b 1Mbps	Back	5mm	Ant 3	Reduced	6	2437	1	15.40	16.50	1.288	99.27	1.007	-0.06	0.847	1.099
	WLAN2.4GHz	802.11b 1Mbps	Right Side	5mm	Ant 3	Reduced	6	2437	1	15.40	16.50	1.288	99.27	1.007	0.03	0.181	0.235
	WLAN2.4GHz	802.11b 1Mbps	Top Side	5mm	Ant 3	Reduced	6	2437	1	15.40	16.50	1.288	99.27	1.007	0.03	0.560	0.726
	WLAN2.4GHz	802.11b 1Mbps	Back	5mm	Ant 3	Reduced	1	2412	1	15.30	16.50	1.318	99.27	1.007	-0.16	0.648	0.860
	WLAN2.4GHz	802.11b 1Mbps	Back	5mm	Ant 3	Reduced	11	2462	1	15.10	16.50	1.380	99.27	1.007	0.02	0.731	1.016
	Bluetooth	DH5 1Mbps	Front	5mm	Ant 3	Full	78	2480	1	9.40	10.50	1.288	76.91	1.300	-0.19	0.010	0.017
23	Bluetooth	DH5 1Mbps	Back	5mm	Ant 3	Full	78	2480	1	9.40	10.50	1.288	76.91	1.300	0.06	0.019	0.031
	Bluetooth	DH5 1Mbps	Right Side	5mm	Ant 3	Full	78	2480	1	9.40	10.50	1.288	76.91	1.300	-	0.000	0.000
	Bluetooth	DH5 1Mbps	Top Side	5mm	Ant 3	Full	78	2480	1	9.40	10.50	1.288	76.91	1.300	-0.14	0.013	0.022
5000MHz																	
	WLAN5.2GHz	802.11ac-VHT80 MCS0	Front	5mm	Ant 3	Reduced	42	5210	1	12.00	13.50	1.413	87.77	1.139	-0.05	0.144	0.232
	WLAN5.2GHz	802.11ac-VHT80 MCS0	Back	5mm	Ant 3	Reduced	42	5210	1	12.00	13.50	1.413	87.77	1.139	-0.13	0.245	0.394
	WLAN5.2GHz	802.11ac-VHT80 MCS0	Right Side	5mm	Ant 3	Reduced	42	5210	1	12.00	13.50	1.413	87.77	1.139	0.13	0.096	0.154
24	WLAN5.2GHz	802.11ac-VHT80 MCS0	Top Side	5mm	Ant 3	Reduced	42	5210	2	12.00	13.50	1.413	87.77	1.139	0.04	0.702	1.129
	WLAN5.2GHz	802.11ac-VHT80 MCS0	Top Side	5mm	Ant 3	Reduced	42	5210	1	12.00	13.50	1.413	87.77	1.139	-0.17	0.630	1.014
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Front	5mm	Ant 3	Reduced	155	5775	1	11.96	13.00	1.271	87.77	1.139	0.19	0.252	0.365
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Back	5mm	Ant 3	Reduced	155	5775	1	11.96	13.00	1.271	87.77	1.139	0.1	0.615	0.890
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Right Side	5mm	Ant 3	Reduced	155	5775	1	11.96	13.00	1.271	87.77	1.139	-0.1	0.164	0.237
25	WLAN5.8GHz	802.11ac-VHT80 MCS0	Top Side	5mm	Ant 3	Reduced	155	5775	1	11.96	13.00	1.271	87.77	1.139	-0.05	0.688	0.996



14.3 Body Worn Accessory SAR

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Mode	Test Position	Gap (mm)	Antenna	Headset	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
835MHz																				
	GSM850	-	-	-	-	GPRS 2 Tx slots	Front	5mm	Ant 1	-	Reduced	251	848.8	1	30.15	31.00	1.216	0.04	0.528	0.642
	GSM850	-	-	-	-	GPRS 2 Tx slots	Back	5mm	Ant 1	-	Reduced	251	848.8	1	30.15	31.00	1.216	-0.15	0.961	1.169
	GSM850	-	-	-	-	GPRS 2 Tx slots	Back	5mm	Ant 1	-	Reduced	128	824.2	1	30.10	31.00	1.230	-0.16	0.952	1.171
26	GSM850	-	-	-	-	GPRS 2 Tx slots	Back	5mm	Ant 1	-	Reduced	189	836.4	1	30.08	31.00	1.236	-0.05	1.040	1.285
	GSM850	-	-	-	-	GPRS 2 Tx slots	Back	5mm	Ant 1	Headset	Reduced	189	836.4	1	30.08	31.00	1.236	0.02	0.980	1.211
	WCDMA V	-	-	-	-	RMC 12.2Kbps	Front	5mm	Ant 1	-	Full	4182	836.4	1	22.82	24.00	1.312	0.05	0.560	0.735
27	WCDMA V	-	-	-	-	RMC 12.2Kbps	Back	5mm	Ant 1	-	Full	4182	836.4	1	22.82	24.00	1.312	0.02	1.000	1.312
	WCDMA V	-	-	-	-	RMC 12.2Kbps	Back	5mm	Ant 1	-	Full	4182	836.4	2	22.82	24.00	1.312	0.1	0.883	1.159
	WCDMA V	-	-	-	-	RMC 12.2Kbps	Back	5mm	Ant 1	-	Full	4132	826.4	1	22.72	24.00	1.343	0.18	0.921	1.237
	WCDMA V	-	-	-	-	RMC 12.2Kbps	Back	5mm	Ant 1	-	Full	4233	846.6	1	22.67	24.00	1.358	0.03	0.890	1.209
	WCDMA V	-	-	-	-	RMC 12.2Kbps	Back	5mm	Ant 1	Headset	Full	4182	836.4	1	22.82	24.00	1.312	0.05	0.939	1.232
	LTE Band 26	15M	QPSK	1	37	-	Front	5mm	Ant 1	-	Full	26865	831.5	1	23.00	24.00	1.259	0.03	0.571	0.719
28	LTE Band 26	15M	QPSK	1	37	-	Back	5mm	Ant 1	-	Full	26865	831.5	1	23.00	24.00	1.259	-0.01	1.010	1.272
	LTE Band 26	15M	QPSK	1	37	-	Back	5mm	Ant 1	Headset	Full	26865	831.5	1	23.00	24.00	1.259	0.03	0.887	1.117
	LTE Band 26	15M	QPSK	36	0	-	Front	5mm	Ant 1	-	Full	26865	831.5	1	21.96	23.00	1.271	-0.14	0.432	0.549
	LTE Band 26	15M	QPSK	36	0	-	Back	5mm	Ant 1	-	Full	26865	831.5	1	21.96	23.00	1.271	-0.09	0.645	0.820
	LTE Band 26	15M	QPSK	75	0	-	Back	5mm	Ant 1	-	Full	26865	831.5	1	21.85	23.00	1.303	0.05	0.764	0.996
1900MHz																				
	GSM1900	-	-	-	-	GPRS 2 Tx slots	Front	5mm	Ant 1	-	Reduced	661	1880	1	25.78	27.00	1.324	-0.18	0.594	0.787
	GSM1900	-	-	-	-	GPRS 2 Tx slots	Back	5mm	Ant 1	-	Reduced	661	1880	1	25.78	27.00	1.324	0.02	0.883	1.169
29	GSM1900	-	-	-	-	GPRS 2 Tx slots	Back	5mm	Ant 1	-	Reduced	512	1850.2	1	25.62	27.00	1.374	0.18	1.040	1.429
	GSM1900	-	-	-	-	GPRS 2 Tx slots	Back	5mm	Ant 1	-	Reduced	512	1850.2	2	25.62	27.00	1.374	-0.11	0.956	1.314
	GSM1900	-	-	-	-	GPRS 2 Tx slots	Back	5mm	Ant 1	-	Reduced	810	1909.8	1	25.71	27.00	1.346	0.08	0.756	1.017
	GSM1900	-	-	-	-	GPRS 2 Tx slots	Back	5mm	Ant 1	Headset	Reduced	512	1850.2	1	25.62	27.00	1.374	0.18	1.010	1.388
	WCDMA II	-	-	-	-	RMC 12.2Kbps	Front	5mm	Ant 1	-	Reduced	9400	1880	1	17.94	19.00	1.276	0.19	0.625	0.798
	WCDMA II	-	-	-	-	RMC 12.2Kbps	Back	5mm	Ant 1	-	Reduced	9400	1880	1	17.94	19.00	1.276	-0.14	0.946	1.208
30	WCDMA II	-	-	-	-	RMC 12.2Kbps	Back	5mm	Ant 1	-	Reduced	9262	1852.4	1	17.90	19.00	1.288	-0.04	1.030	1.327
	WCDMA II	-	-	-	-	RMC 12.2Kbps	Back	5mm	Ant 1	-	Reduced	9538	1907.6	1	17.80	19.00	1.318	0.06	0.839	1.106
	WCDMA II	-	-	-	-	RMC 12.2Kbps	Back	5mm	Ant 1	Headset	Reduced	9262	1852.4	1	17.90	19.00	1.288	0.03	0.861	1.109
	LTE Band 2	20M	QPSK	1	49	-	Front	5mm	Ant 1	-	Reduced	18900	1880	1	19.25	20.00	1.189	0.07	0.663	0.788
	LTE Band 2	20M	QPSK	1	49	-	Back	5mm	Ant 1	-	Reduced	18900	1880	1	19.25	20.00	1.189	-0.01	1.020	1.212
31	LTE Band 2	20M	QPSK	1	49	-	Back	5mm	Ant 1	-	Reduced	18700	1860	1	19.19	20.00	1.205	-0.19	1.100	1.326
	LTE Band 2	20M	QPSK	1	49	-	Back	5mm	Ant 1	-	Reduced	19100	1900	1	19.11	20.00	1.227	0.06	1.050	1.289
	LTE Band 2	20M	QPSK	1	49	-	Back	5mm	Ant 1	Headset	Reduced	18700	1860	1	19.19	20.00	1.205	0.02	1.010	1.217
	LTE Band 2	20M	QPSK	50	0	-	Front	5mm	Ant 1	-	Reduced	18900	1880	1	18.20	19.00	1.202	-0.07	0.646	0.777
	LTE Band 2	20M	QPSK	50	0	-	Back	5mm	Ant 1	-	Reduced	18900	1880	1	18.20	19.00	1.202	0.08	0.829	0.997
	LTE Band 2	20M	QPSK	50	0	-	Back	5mm	Ant 1	-	Reduced	18700	1860	1	18.15	19.00	1.216	0.06	0.881	1.071
	LTE Band 2	20M	QPSK	50	0	-	Back	5mm	Ant 1	-	Reduced	19100	1900	1	18.02	19.00	1.253	0.12	0.806	1.010
	LTE Band 2	20M	QPSK	100	0	-	Back	5mm	Ant 1	-	Reduced	18900	1880	1	18.21	19.00	1.199	0.13	0.847	1.016



FCC SAR Test Report

Report No. : FA1N1011-04

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Antenna	Headset	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	
2600MHz																						
32	LTE Band 7	20M	QPSK	1	49	Front	5mm	Ant 1	-	Reduced	21100	2535	1	14.23	15.00	1.194	-	-	0.01	0.538	0.642	
	LTE Band 7	20M	QPSK	1	49	Back	5mm	Ant 1	-	Reduced	21100	2535	1	14.23	15.00	1.194	-	-	0.02	1.010	1.206	
	LTE Band 7	20M	QPSK	1	49	Back	5mm	Ant 1	-	Reduced	20850	2510	1	14.15	15.00	1.216	-	-	-0.17	0.802	0.975	
	LTE Band 7	20M	QPSK	1	49	Back	5mm	Ant 1	-	Reduced	21350	2560	1	14.21	15.00	1.199	-	-	0.13	0.998	1.197	
	LTE Band 7	20M	QPSK	1	49	Back	5mm	Ant 1	Headset	Reduced	21100	2535	1	14.23	15.00	1.194	-	-	0.03	0.983	1.174	
	LTE Band 7	20M	QPSK	50	0	Front	5mm	Ant 1	-	Reduced	21100	2535	1	13.35	14.00	1.161	-	-	0.05	0.432	0.502	
	LTE Band 7	20M	QPSK	50	0	Back	5mm	Ant 1	-	Reduced	21100	2535	1	13.35	14.00	1.161	-	-	0.03	0.791	0.919	
	LTE Band 7	20M	QPSK	50	0	Back	5mm	Ant 1	-	Reduced	20850	2510	1	13.21	14.00	1.199	-	-	0.19	0.603	0.723	
	LTE Band 7	20M	QPSK	50	0	Back	5mm	Ant 1	-	Reduced	21350	2560	1	13.32	14.00	1.169	-	-	0.02	0.746	0.872	
33	LTE Band 7	20M	QPSK	100	0	Back	5mm	Ant 1	-	Reduced	21100	2535	1	13.28	14.00	1.180	-	-	0.12	0.752	0.888	
	40185-2549.5MHz																					
	LTE Band 41	20M	QPSK	1	49	Front	5mm	Ant 1	-	Reduced	40185	2549.5	1	16.18	17.00	1.208	62.9	1.006	0.18	0.567	0.689	
	LTE Band 41	20M	QPSK	1	49	Back	5mm	Ant 1	-	Reduced	40185	2549.5	1	16.18	17.00	1.208	62.9	1.006	0.14	1.080	1.312	
	LTE Band 41	20M	QPSK	1	49	Back	5mm	Ant 1	-	Reduced	40185	2549.5	2	16.18	17.00	1.208	62.9	1.006	0.08	0.955	1.160	
	LTE Band 41	20M	QPSK	1	49	Front	5mm	Ant 1	-	Reduced	39750	2506	1	16.12	17.00	1.225	62.9	1.006	0.15	0.472	0.581	
	LTE Band 41	20M	QPSK	1	49	Front	5mm	Ant 1	-	Reduced	40620	2593	1	16.06	17.00	1.242	62.9	1.006	-0.16	0.381	0.476	
	LTE Band 41	20M	QPSK	1	49	Front	5mm	Ant 1	-	Reduced	41055	2636.5	1	15.90	17.00	1.288	62.9	1.006	-0.15	0.212	0.275	
	LTE Band 41	20M	QPSK	1	49	Front	5mm	Ant 1	-	Reduced	41490	2680	1	15.85	17.00	1.303	62.9	1.006	0.17	0.136	0.178	
	LTE Band 41	20M	QPSK	1	49	Back	5mm	Ant 1	-	Reduced	39750	2506	1	16.12	17.00	1.225	62.9	1.006	-0.16	0.826	1.018	
	LTE Band 41	20M	QPSK	1	49	Back	5mm	Ant 1	-	Reduced	40620	2593	1	16.06	17.00	1.242	62.9	1.006	0.05	0.813	1.016	
	LTE Band 41	20M	QPSK	1	49	Back	5mm	Ant 1	-	Reduced	41055	2636.5	1	15.90	17.00	1.288	62.9	1.006	0.18	0.457	0.592	
	LTE Band 41	20M	QPSK	1	49	Back	5mm	Ant 1	-	Reduced	41490	2680	1	15.85	17.00	1.303	62.9	1.006	0.05	0.293	0.384	
	LTE Band 41	20M	QPSK	1	49	Back	5mm	Ant 1	Headset	Reduced	40185	2549.5	1	16.18	17.00	1.208	62.9	1.006	0.11	1.010	1.227	
	LTE Band 41	20M	QPSK	50	0	Front	5mm	Ant 1	-	Reduced	40185	2549.5	1	15.02	16.00	1.253	62.9	1.006	0.03	0.430	0.542	
	LTE Band 41	20M	QPSK	50	0	Back	5mm	Ant 1	-	Reduced	40185	2549.5	1	15.02	16.00	1.253	62.9	1.006	0.02	0.806	1.016	
	LTE Band 41	20M	QPSK	50	0	Back	5mm	Ant 1	-	Reduced	39750	2506	1	15.00	16.00	1.259	62.9	1.006	-0.07	0.635	0.804	
	LTE Band 41	20M	QPSK	50	0	Back	5mm	Ant 1	-	Reduced	40620	2593	1	14.86	16.00	1.300	62.9	1.006	-0.17	0.601	0.786	
	LTE Band 41	20M	QPSK	50	0	Back	5mm	Ant 1	-	Reduced	41055	2636.5	1	14.81	16.00	1.315	62.9	1.006	0.14	0.321	0.425	
	LTE Band 41	20M	QPSK	50	0	Back	5mm	Ant 1	-	Reduced	41490	2680	1	14.72	16.00	1.343	62.9	1.006	0.12	0.253	0.342	
	LTE Band 41	20M	QPSK	100	0	Back	5mm	Ant 1	-	Reduced	40185	2549.5	1	14.88	16.00	1.294	62.9	1.006	0.03	0.834	1.086	

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Headset	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	
2450MHz																			
34	WLAN2.4GHz	802.11b 1Mbps	Front	5mm	Ant 3	-	Reduced	6	2437	1	15.40	16.50	1.288	99.27	1.007	0.17	0.226	0.293	
	WLAN2.4GHz	802.11b 1Mbps	Back	5mm	Ant 3	-	Reduced	6	2437	1	15.40	16.50	1.288	99.27	1.007	-0.06	0.847	1.099	
	WLAN2.4GHz	802.11b 1Mbps	Back	5mm	Ant 3	-	Reduced	1	2412	1	15.30	16.50	1.318	99.27	1.007	-0.16	0.648	0.860	
	WLAN2.4GHz	802.11b 1Mbps	Back	5mm	Ant 3	-	Reduced	11	2462	1	15.10	16.50	1.380	99.27	1.007	0.02	0.731	1.016	
	Bluetooth	DH5 1Mbps	Front	5mm	Ant 3	-	Full	78	2480	1	9.40	10.50	1.288	76.91	1.300	-0.19	0.010	0.017	
35	Bluetooth	DH5 1Mbps	Back	5mm	Ant 3	-	Full	78	2480	1	9.40	10.50	1.288	76.91	1.300	0.06	0.019	0.031	
5000MHz																			
36	WLAN5.3GHz	802.11n-HT40 MCS0	Front	5mm	Ant 3	-	Reduced	54	5270	1	15.72	17.00	1.343	93.3	1.072	-0.1	0.386	0.556	
	WLAN5.3GHz	802.11n-HT40 MCS0	Back	5mm	Ant 3	-	Reduced	54	5270	1	15.72	17.00	1.343	93.3	1.072	0.06	0.820	1.180	
	WLAN5.3GHz	802.11n-HT40 MCS0	Back	5mm	Ant 3	-	Reduced	54	5270	2	15.72	17.00	1.343	93.3	1.072	-0.18	0.749	1.078	
	WLAN5.3GHz	802.11n-HT40 MCS0	Back	5mm	Ant 3	-	Reduced	62	5310	1	13.80	15.50	1.479	93.3	1.072	0.07	0.430	0.682	
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Front	5mm	Ant 3	-	Reduced	138	5690	1	11.86	13.50	1.459	87.77	1.139	-0.08	0.234	0.389	
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Back	5mm	Ant 3	-	Reduced	138	5690	1	11.86	13.50	1.459	87.77	1.139	-0.1	0.634	1.053	
37	WLAN5.5GHz	802.11ac-VHT80 MCS0	Back	5mm	Ant 3	-	Reduced	106	5530	1	11.65	13.50	1.531	87.77	1.139	0.15	0.402	0.701	
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Back	5mm	Ant 3	-	Reduced	122	5610	1	11.65	13.50	1.531	87.77	1.139	-0.13	0.394	0.687	
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Front	5mm	Ant 3	-	Reduced	155	5775	1	12.50	13.50	1.259	87.77	1.139	0.19	0.252	0.361	
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Back	5mm	Ant 3	-	Reduced	155	5775	1	12.50	13.50	1.259	87.77	1.139	0.1	0.688	0.987	

Sporton International Inc. (Shenzhen)

TEL : +86-755-86379589 / FAX : +86-755-86379595

FCC ID : IHDT56AC7

Issued Date : Mar. 15, 2022

Form version. : 200414



14.4 Product Specific SAR

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Mode	Test Position	Gap (mm)	Antenna	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
835MHz																					
39	GSM850	-	-	-	-	GPRS 2 Tx slots	Back	0mm	Ant 1	Reduced	251	848.8	1	30.15	31.00	1.216	-	-	0.04	1.550	1.885
40	WCDMA V	-	-	-	-	RMC 12.2Kbps	Back	0mm	Ant 1	Full	4182	836.4	1	22.82	24.00	1.312	-	-	-0.11	1.540	2.021
	WCDMA V	-	-	-	-	RMC 12.2Kbps	Back	0mm	Ant 1	Full	4182	836.4	2	22.82	24.00	1.312	-	-	0.18	1.430	1.876
	WCDMA V	-	-	-	-	RMC 12.2Kbps	Back	0mm	Ant 1	Full	4132	826.4	1	22.72	24.00	1.343	-	-	-0.15	1.230	1.652
	WCDMA V	-	-	-	-	RMC 12.2Kbps	Back	0mm	Ant 1	Full	4233	846.6	1	22.67	24.00	1.358	-	-	0.02	1.320	1.793
41	LTE Band 26	15M	QPSK	1	37	-	Back	0mm	Ant 1	Full	26865	831.5	1	23.00	24.00	1.259	-	-	0.06	1.560	1.964
	LTE Band 26	15M	QPSK	36	0	-	Back	0mm	Ant 1	Full	26865	831.5	1	21.96	23.00	1.271	-	-	0.03	1.130	1.436
1900MHz																					
	GSM1900	-	-	-	-	GPRS 2 Tx slots	Back	0mm	Ant 1	Reduced	661	1880	1	25.78	27.00	1.324	-	-	0.08	0.966	1.279
42	GSM1900	-	-	-	-	GPRS 2 Tx slots	Bottom Side	0mm	Ant 1	Reduced	661	1880	1	25.78	27.00	1.324	-	-	0.07	1.190	1.576
	WCDMA II	-	-	-	-	RMC 12.2Kbps	Back	0mm	Ant 1	Reduced	9400	1880	1	17.94	19.00	1.276	-	-	0.03	0.652	0.832
43	WCDMA II	-	-	-	-	RMC 12.2Kbps	Bottom Side	0mm	Ant 1	Reduced	9400	1880	1	17.94	19.00	1.276	-	-	0.01	1.430	1.825
	LTE Band 2	20M	QPSK	1	49	-	Back	0mm	Ant 1	Reduced	18900	1880	1	19.25	20.00	1.189	-	-	-0.11	1.490	1.771
44	LTE Band 2	20M	QPSK	1	49	-	Bottom Side	0mm	Ant 1	Reduced	18900	1880	1	19.25	20.00	1.189	-	-	0.02	1.570	1.866
	LTE Band 2	20M	QPSK	1	49	-	Bottom Side	0mm	Ant 1	Reduced	18900	1880	2	19.25	20.00	1.189	-	-	0.05	1.450	1.723
	LTE Band 2	20M	QPSK	50	0	-	Back	0mm	Ant 1	Reduced	18900	1880	1	18.20	19.00	1.202	-	-	0.08	1.130	1.359
	LTE Band 2	20M	QPSK	50	0	-	Bottom Side	0mm	Ant 1	Reduced	18900	1880	1	18.20	19.00	1.202	-	-	-0.08	1.200	1.443
2600MHz																					
45	LTE Band 7	20M	QPSK	1	49	-	Back	0mm	Ant 1	Reduced	21100	2535	1	14.23	15.00	1.194	-	-	0.06	1.110	1.325
	LTE Band 7	20M	QPSK	1	49	-	Bottom Side	0mm	Ant 1	Reduced	21100	2535	1	14.23	15.00	1.194	-	-	0.03	0.619	0.739
	LTE Band 7	20M	QPSK	50	0	-	Back	0mm	Ant 1	Reduced	21100	2535	1	13.35	14.00	1.161	-	-	0.06	0.890	1.034
	LTE Band 7	20M	QPSK	50	0	-	Bottom Side	0mm	Ant 1	Reduced	21100	2535	1	13.35	14.00	1.161	-	-	0.03	0.420	0.488
46	LTE Band 41	20M	QPSK	1	49	-	Back	0mm	Ant 1	Reduced	40185	2549.5	1	16.18	17.00	1.208	62.9	1.006	0.03	1.110	1.349
	LTE Band 41	20M	QPSK	1	49	-	Back	0mm	Ant 1	Reduced	40185	2549.5	2	16.18	17.00	1.208	62.9	1.006	0.01	1.030	1.252
	LTE Band 41	20M	QPSK	1	49	-	Bottom Side	0mm	Ant 1	Reduced	40185	2549.5	1	16.18	17.00	1.208	62.9	1.006	0.14	0.626	0.761
	LTE Band 41	20M	QPSK	50	0	-	Back	0mm	Ant 1	Reduced	40185	2549.5	1	15.02	16.00	1.253	62.9	1.006	0.02	0.860	1.084
	LTE Band 41	20M	QPSK	50	0	-	Bottom Side	0mm	Ant 1	Reduced	40185	2549.5	1	15.02	16.00	1.253	62.9	1.006	-0.01	0.420	0.529

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)	
5000MHz																		
47	WLAN5.2GHz	802.11n-HT40 MCS0	Top Side	0mm	Ant 3	Reduced	46	5230	1	16.40	17.00	1.148	93.3	1.072	0.05	1.500	1.846	
	WLAN5.3GHz	802.11n-HT40 MCS0	Front	0mm	Ant 3	Reduced	54	5270	1	15.72	17.00	1.343	93.3	1.072	0.1	0.354	0.510	
	WLAN5.3GHz	802.11n-HT40 MCS0	Back	0mm	Ant 3	Reduced	54	5270	1	15.72	17.00	1.343	93.3	1.072	0.08	0.453	0.652	
	WLAN5.3GHz	802.11n-HT40 MCS0	Right Side	0mm	Ant 3	Reduced	54	5270	1	15.72	17.00	1.343	93.3	1.072	-0.09	0.203	0.292	
48	WLAN5.3GHz	802.11n-HT40 MCS0	Top Side	0mm	Ant 3	Reduced	54	5270	1	15.72	17.00	1.343	93.3	1.072	0.02	1.700	2.447	
	WLAN5.3GHz	802.11n-HT40 MCS0	Top Side	0mm	Ant 3	Reduced	54	5270	2	15.72	17.00	1.343	93.3	1.072	0.04	1.680	2.418	
	WLAN5.3GHz	802.11n-HT40 MCS0	Top Side	0mm	Ant 3	Reduced	62	5310	1	13.80	15.50	1.479	93.3	1.072	0.1	0.930	1.475	
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Front	0mm	Ant 3	Reduced	138	5690	1	11.86	13.50	1.459	87.77	1.139	-0.13	0.244	0.405	
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Back	0mm	Ant 3	Reduced	138	5690	1	11.86	13.50	1.459	87.77	1.139	0.06	0.378	0.628	
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Right Side	0mm	Ant 3	Reduced	138	5690	1	11.86	13.50	1.459	87.77	1.139	-0.16	0.176	0.292	
49	WLAN5.5GHz	802.11ac-VHT80 MCS0	Top Side	0mm	Ant 3	Reduced	138	5690	1	11.86	13.50	1.459	87.77	1.139	-0.08	0.904	1.502	



14.5 Repeated SAR Measurement

<1g>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Mode	Test Position	Gap (mm)	Antenna	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Ratio	Reported 1g SAR (W/kg)
1st	GSM850	-	-	-	-	GPRS 2 Tx slots	Back	5mm	Ant 1	Reduced	189	836.4	1	30.08	31.00	1.236	-	-	-0.05	1.040	1	1.285
2nd	GSM850	-	-	-	-	GPRS 2 Tx slots	Back	5mm	Ant 1	Reduced	189	836.4	1	30.08	31.00	1.236	-	-	0.03	1.000	1.040	1.236
1st	LTE Band 41	20M	QPSK	1	49	-	Bottom Side	5mm	Ant 1	Reduced	40185	2549.5	1	14.50	15.50	1.259	62.9	1.006	-0.08	1.110	1	1.406
2nd	LTE Band 41	20M	QPSK	1	49	-	Bottom Side	5mm	Ant 1	Reduced	40185	2549.5	1	14.50	15.50	1.259	62.9	1.006	0.03	1.030	1.078	1.304
1st	LTE Band 2	20M	QPSK	1	49	-	Back	5mm	Ant 1	Reduced	18700	1860	1	19.19	20.00	1.205	-	-	-0.19	1.100	1	1.326
2nd	LTE Band 2	20M	QPSK	1	49	-	Back	5mm	Ant 1	Reduced	18700	1860	1	19.19	20.00	1.205	-	-	0.12	1.060	1.038	1.277
1st	WLAN5.3GHz	-	-	-	-	802.11n-HT40 MCS0	Back	5mm	Ant 3	Reduced	54	5270	1	15.72	17.00	1.343	93.3	1.072	0.06	0.820	1	1.180
2nd	WLAN5.3GHz	-	-	-	-	802.11n-HT40 MCS0	Back	5mm	Ant 3	Reduced	54	5270	1	15.72	17.00	1.343	93.3	1.072	-0.12	0.730	1.123	1.051

General Note:

- Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is $\geq 0.8W/kg$.
- Per KDB 865664 D01v01r04, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR $< 1.45W/kg$, only one repeated measurement is required.
- Per KDB 865664 D01v01r04, if the extremity repeated SAR is necessary, the same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.
- The ratio is the difference in percentage between original and repeated *measured SAR*.
- All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

15. Simultaneous Transmission Analysis

No.	Simultaneous Transmission Configurations	Portable Handset			
		Head	Body-worn	Hotspot	Product specific 10g SAR
1.	WWAN + WLAN2.4GHz	Yes	Yes	Yes	Yes
2.	WWAN + WLAN5GHz	Yes	Yes	Yes	Yes
3.	WWAN + Bluetooth	Yes	Yes	Yes	Yes

General Note:

1. This device supports VoIP in GPRS, EGPRS, WCDMA and LTE (e.g. for 3rd-party VoIP), LTE supports VoLTE operation.
2. EUT will choose each GSM, WCDMA and LTE according to the network signal condition; therefore, they will not operate simultaneously at any moment.
3. This device 2.4GHz WLAN support hotspot operation and Bluetooth support tethering applications.
4. This device 5.2GHz WLAN/5.8GHz WLAN support hotspot operation, and 5.2GHz WLAN/5.8GHz WLAN supports WLAN Direct (GC/GO), and 5.3GHz / 5.5GHz supports WLAN Direct (GC only).
5. WIFI 5.3/5.5GHz has no hotspot function.
6. The worst case 5 GHz WLAN SAR for each configuration was used for SAR summation.
7. WLAN 2.4GHz and Bluetooth share the same antenna so can't transmit simultaneously.
8. According to the EUT characteristic, WLAN 5GHz and Bluetooth can't transmit simultaneously.
9. The maximum SAR summation is calculated based on the same configuration and test position.
10. Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - i) 1g Scalar SAR summation < 1.6W/kg and 10g Scalar SAR summation < 4.0W/kg.
 - ii) $SPLSR = (SAR1 + SAR2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - iii) If $SPLSR \leq 0.04$ for 1g SAR and $SPLSR \leq 0.10$ for 10g SAR, simultaneously transmission SAR measurement is not necessary.
 - iv) Simultaneously transmission SAR measurement, and the reported multi-band 1g SAR < 1.6W/kg and 10g SAR < 4.0W/kg.
 - v) The SPLSR calculated results please refer to section 15.5.



15.1 Head Exposure Conditions

WWAN Band		Exposure Position	1	2	3	4	1+2	1+3	1+4
			WWAN 1g SAR (W/kg)	WLAN2.4GHz 1g SAR (W/kg)	WLAN5GHz 1g SAR (W/kg)	Bluetooth 1g SAR (W/kg)	Summed 1g SAR (W/kg)	Summed 1g SAR (W/kg)	Summed 1g SAR (W/kg)
GSM	GSM850	Right Cheek	0.551	0.378	0.478		0.93	1.03	0.55
		Right Tilted	0.281	0.359	0.590		0.64	0.87	0.28
		Left Cheek	0.449	0.825	0.637	0.025	1.27	1.09	0.47
		Left Tilted	0.260	0.766	1.152	0.013	1.03	1.41	0.27
	GSM1900	Right Cheek	0.317	0.378	0.478		0.70	0.80	0.32
		Right Tilted	0.188	0.359	0.590		0.55	0.78	0.19
		Left Cheek	0.232	0.825	0.637	0.025	1.06	0.87	0.26
		Left Tilted	0.241	0.766	1.152	0.013	1.01	1.39	0.25
WCDMA	WCDMA II	Right Cheek	0.377	0.378	0.478		0.76	0.86	0.38
		Right Tilted	0.283	0.359	0.590		0.64	0.87	0.28
		Left Cheek	0.326	0.825	0.637	0.025	1.15	0.96	0.35
		Left Tilted	0.331	0.766	1.152	0.013	1.10	1.48	0.34
	WCDMA V	Right Cheek	0.463	0.378	0.478		0.84	0.94	0.46
		Right Tilted	0.256	0.359	0.590		0.62	0.85	0.26
		Left Cheek	0.400	0.825	0.637	0.025	1.23	1.04	0.43
		Left Tilted	0.224	0.766	1.152	0.013	0.99	1.38	0.24
LTE	LTE Band 26	Right Cheek	0.468	0.378	0.478		0.85	0.95	0.47
		Right Tilted	0.217	0.359	0.590		0.58	0.81	0.22
		Left Cheek	0.386	0.825	0.637	0.025	1.21	1.02	0.41
		Left Tilted	0.183	0.766	1.152	0.013	0.95	1.34	0.20
	LTE Band 2	Right Cheek	0.476	0.378	0.478		0.85	0.95	0.48
		Right Tilted	0.264	0.359	0.590		0.62	0.85	0.26
		Left Cheek	0.315	0.825	0.637	0.025	1.14	0.95	0.34
		Left Tilted	0.324	0.766	1.152	0.013	1.09	1.48	0.34
	LTE Band 7	Right Cheek	0.132	0.378	0.478		0.51	0.61	0.13
		Right Tilted		0.359	0.590		0.36	0.59	0.00
		Left Cheek	0.065	0.825	0.637	0.025	0.89	0.70	0.09
		Left Tilted		0.766	1.152	0.013	0.77	1.15	0.01
	LTE Band 41	Right Cheek	0.071	0.378	0.478		0.45	0.55	0.07
		Right Tilted		0.359	0.590		0.36	0.59	0.00
		Left Cheek	0.045	0.825	0.637	0.025	0.87	0.68	0.07
		Left Tilted		0.766	1.152	0.013	0.77	1.15	0.01



15.2 Hotspot Exposure Conditions

WWAN Band		Exposure Position	1	2	3	4	1+2	1+3	1+4	Case No
			WWAN 1g SAR (W/kg)	WLAN2.4GHz 1g SAR (W/kg)	WLAN5GHz 1g SAR (W/kg)	Bluetooth 1g SAR (W/kg)	Summed 1g SAR (W/kg)	Summed 1g SAR (W/kg)	Summed 1g SAR (W/kg)	
GSM	GSM850	Front	0.642	0.293	0.365	0.017	0.94	1.01	0.66	
		Back	1.285	1.099	0.890	0.031	2.38	2.18	1.32	Case 1/9
		Left side	0.448				0.45	0.45	0.45	
		Right side	0.612	0.235	0.237		0.85	0.85	0.61	
		Top side		0.726	1.129	0.022	0.73	1.13	0.02	
		Bottom side	0.660				0.66	0.66	0.66	
	GSM1900	Front	0.393	0.293	0.365	0.017	0.69	0.76	0.41	
		Back	0.603	1.099	0.890	0.031	1.70	1.49	0.63	Case 2
		Left side	0.192				0.19	0.19	0.19	
		Right side	0.108	0.235	0.237		0.34	0.35	0.11	
		Top side		0.726	1.129	0.022	0.73	1.13	0.02	
		Bottom side	1.135				1.14	1.14	1.14	
WCDMA	WCDMA V	Front	0.735	0.293	0.365	0.017	1.03	1.10	0.75	
		Back	1.312	1.099	0.890	0.031	2.41	2.20	1.34	Case 3/11
		Left side	0.563				0.56	0.56	0.56	
		Right side	0.625	0.235	0.237		0.86	0.86	0.63	
		Top side		0.726	1.129	0.022	0.73	1.13	0.02	
		Bottom side	0.716				0.72	0.72	0.72	
	WCDMA II	Front	0.503	0.293	0.365	0.017	0.80	0.87	0.52	
		Back	0.765	1.099	0.890	0.031	1.86	1.66	0.80	Case 4/12
		Left side	0.228				0.23	0.23	0.23	
		Right side	0.116	0.235	0.237		0.35	0.35	0.12	
		Top side		0.726	1.129	0.022	0.73	1.13	0.02	
		Bottom side	1.298				1.30	1.30	1.30	
LTE	LTE Band 26	Front	0.719	0.293	0.365	0.017	1.01	1.08	0.74	
		Back	1.272	1.099	0.890	0.031	2.37	2.16	1.30	Case 5/13
		Left side	0.374				0.37	0.37	0.37	
		Right side	0.480	0.235	0.237		0.72	0.72	0.48	
		Top side		0.726	1.129	0.022	0.73	1.13	0.02	
		Bottom side	0.734				0.73	0.73	0.73	
	LTE Band 2	Front	0.393	0.293	0.365	0.017	0.69	0.76	0.41	
		Back	0.612	1.099	0.890	0.031	1.71	1.50	0.64	Case 6
		Left side	0.222				0.22	0.22	0.22	
		Right side	0.111	0.235	0.237		0.35	0.35	0.11	
		Top side		0.726	1.129	0.022	0.73	1.13	0.02	
		Bottom side	1.277				1.28	1.28	1.28	
	LTE Band 7	Front	0.512	0.293	0.365	0.017	0.81	0.88	0.53	
		Back	0.958	1.099	0.890	0.031	2.06	1.85	0.99	Case 7/15
		Left side					0.00	0.00	0.00	
		Right side		0.235	0.237		0.24	0.24	0.00	
		Top side		0.726	1.129	0.022	0.73	1.13	0.02	
		Bottom side	1.289				1.29	1.29	1.29	
	LTE Band 41	Front	0.488	0.293	0.365	0.017	0.78	0.85	0.51	
		Back	0.927	1.099	0.890	0.031	2.03	1.82	0.96	Case 8/16
		Left side					0.00	0.00	0.00	
		Right side		0.235	0.237		0.24	0.24	0.00	
		Top side		0.726	1.129	0.022	0.73	1.13	0.02	
		Bottom side	1.406				1.41	1.41	1.41	



15.3 Body-Worn Accessory Exposure Conditions

WWAN Band		Exposure Position	1	2	3	4	1+2	1+3	1+4	Case No
			WWAN	WLAN2.4GHz	WLAN5GHz	Bluetooth	Summed	Summed	Summed	
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	
GSM	GSM850	Front	0.642	0.293	0.556	0.017	0.94	1.20	0.66	
		Back	1.285	1.099	1.180	0.031	2.38	2.47	1.32	Case 1/22
		Front with Headset					0.00	0.00	0.00	
		Back with Headset	1.211				1.21	1.21	1.21	
	GSM1900	Front	0.787	0.293	0.556	0.017	1.08	1.34	0.80	
		Back	1.429	1.099	1.180	0.031	2.53	2.61	1.46	Case 17/23
		Front with Headset					0.00	0.00	0.00	
		Back with Headset	1.388				1.39	1.39	1.39	
WCDMA	WCDMA V	Front	0.735	0.293	0.556	0.017	1.03	1.29	0.75	
		Back	1.312	1.099	1.180	0.031	2.41	2.49	1.34	Case 3/24
		Front with Headset					0.00	0.00	0.00	
		Back with Headset	1.232				1.23	1.23	1.23	
	WCDMA II	Front	0.798	0.293	0.556	0.017	1.09	1.35	0.82	
		Back	1.327	1.099	1.180	0.031	2.43	2.51	1.36	Case 18/25
		Front with Headset					0.00	0.00	0.00	
		Back with Headset	1.109				1.11	1.11	1.11	
LTE	LTE Band 26	Front	0.719	0.293	0.556	0.017	1.01	1.28	0.74	
		Back	1.272	1.099	1.180	0.031	2.37	2.45	1.30	Case 5/26
		Front with Headset					0.00	0.00	0.00	
		Back with Headset	1.117				1.12	1.12	1.12	
	LTE Band 2	Front	0.788	0.293	0.556	0.017	1.08	1.34	0.81	
		Back	1.326	1.099	1.180	0.031	2.43	2.51	1.36	Case 19/27
		Front with Headset					0.00	0.00	0.00	
		Back with Headset	1.217				1.22	1.22	1.22	
	LTE Band 7	Front	0.642	0.293	0.556	0.017	0.94	1.20	0.66	
		Back	1.206	1.099	1.180	0.031	2.31	2.39	1.24	Case 20/28
		Front with Headset					0.00	0.00	0.00	
		Back with Headset	1.174				1.17	1.17	1.17	
	LTE Band 41	Front	0.689	0.293	0.556	0.017	0.98	1.25	0.71	
		Back	1.312	1.099	1.180	0.031	2.41	2.49	1.34	Case 21/29
		Front with Headset					0.00	0.00	0.00	
		Back with Headset	1.227				1.23	1.23	1.23	



15.4 Product Specific Exposure Conditions


Note: For Bluetooth Product specific 10g stand-alone SAR is not required for a transmitter or antenna, due to 1g hotspot SAR is <1.2W/kg.

WWAN Band	Exposure Position	1	3	1+3
		WWAN 10g SAR (W/kg)	WLAN5GHz Ant 3 10g SAR (W/kg)	Summed 10g SAR (W/kg)
GSM850	Front		0.510	0.51
	Back	1.885	0.652	2.54
	Left side			0.00
	Right side		0.292	0.29
	Top side		2.447	2.45
	Bottom side			0.00
GSM1900	Front		0.510	0.51
	Back	1.279	0.652	1.93
	Left side			0.00
	Right side		0.292	0.29
	Top side		2.447	2.45
	Bottom side	1.576		1.58
WCDMA V	Front		0.510	0.51
	Back	2.021	0.652	2.67
	Left side			0.00
	Right side		0.292	0.29
	Top side		2.447	2.45
	Bottom side			0.00
WCDMA II	Front		0.510	0.51
	Back	0.832	0.652	1.48
	Left side			0.00
	Right side		0.292	0.29
	Top side		2.447	2.45
	Bottom side	1.825		1.83
LTE Band 26	Front		0.510	0.51
	Back	1.964	0.652	2.62
	Left side			0.00
	Right side		0.292	0.29
	Top side		2.447	2.45
	Bottom side			0.00
LTE Band 2	Front		0.510	0.51
	Back	1.771	0.652	2.42
	Left side			0.00
	Right side		0.292	0.29
	Top side		2.447	2.45
	Bottom side	1.866		1.87
LTE Band 7	Front		0.510	0.51
	Back	1.325	0.652	1.98
	Left side			0.00
	Right side		0.292	0.29
	Top side		2.447	2.45
	Bottom side	0.739		0.74
LTE Band 41	Front		0.510	0.51
	Back	1.349	0.652	2.00
	Left side			0.00
	Right side		0.292	0.29
	Top side		2.447	2.45
	Bottom side	0.761		0.76

15.5 SPLSR Evaluation and Analysis

General Note:

1. When standalone SAR is measured for both antennas in the pair, the peak location separation distance is computed by the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where $(x1, y1, z1)$ and $(x2, y2, z2)$ are the coordinates in the area scans or extrapolated peak SAR locations in the zoom scans, as appropriate.
2. $SPLSR = (SAR1 + SAR2)1.5 / (\text{min. separation distance, mm})$. If $SPLSR \leq 0.04$ for 1g SAR, simultaneously transmission SAR measurement is not necessary.



WWAN+WLAN2.4GHz/WLAN5GHz _Back 5mm



Hotspot:

Case	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
Case 1	GSM850	Back	1.285	5	-0.0205	-0.0815	-0.207	158.4	2.38	0.02	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0736	-0.209				
	GSM850	Back	1.285	5	-0.0205	-0.0815	-0.207	163.3	2.38	0.02	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0786	-0.209				
Case 2	GSM1900 Cube0	Back	0.603	5	-0.0165	-0.0815	-0.209	159.2	1.70	0.01	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0736	-0.209				
	GSM1900 Cube1	Back	0.603	5	-0.0385	-0.0825	-0.209	156.7	1.70	0.01	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0736	-0.209				
	GSM1900 Cube0	Back	0.603	5	-0.0165	-0.0815	-0.209	164.1	1.70	0.01	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0786	-0.209				
	GSM1900 Cube1	Back	0.603	5	-0.0385	-0.0825	-0.209	161.7	1.70	0.01	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0786	-0.209				
Case 3	WCDMA V	Back	1.312	5	-0.0315	-0.0815	-0.209	156.5	2.41	0.02	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0736	-0.209				
	WCDMA V	Back	1.312	5	-0.0315	-0.0815	-0.209	161.5	2.41	0.02	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0786	-0.209				
Case 4	WCDMA II	Back	0.765	5	-0.038	-0.0855	-0.209	159.8	1.86	0.02	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0736	-0.209				
	WCDMA II	Back	0.765	5	-0.038	-0.0855	-0.209	164.7	1.86	0.02	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0786	-0.209				
Case 5	LTE B26	Back	1.272	5	-0.03	-0.0815	-0.209	156.7	2.37	0.02	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0736	-0.209				
	LTE B26	Back	1.272	5	-0.03	-0.0815	-0.209	161.7	2.37	0.02	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0786	-0.209				
Case 6	LTE B2 Cube0	Back	0.612	5	-0.035	-0.087	-0.209	161.6	1.71	0.01	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0736	-0.209				
	LTE B2 Cube1	Back	0.612	5	-0.0415	-0.0885	-0.209	162.5	1.71	0.01	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0736	-0.209				
	LTE B2 Cube0	Back	0.612	5	-0.035	-0.087	-0.209	166.5	1.71	0.01	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0786	-0.209				
	LTE B2 Cube1	Back	0.612	5	-0.0415	-0.0885	-0.209	167.5	1.71	0.01	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0786	-0.209				
Case 7	LTE B7	Back	0.958	5	-0.0106	-0.082	-0.209	161.2	2.06	0.02	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0736	-0.209				
	LTE B7	Back	0.958	5	-0.0106	-0.082	-0.209	166.0	2.06	0.02	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0786	-0.209				
Case 8	LTE B41	Back	0.927	5	-0.0106	-0.082	-0.209	161.2	2.03	0.02	Not required



Case	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
Case 9	WLAN 2.4G	Back	1.099	5	-0.0526	0.0736	-0.209	166.0	2.03	0.02	Not required
	LTE B41		0.927	5	-0.0106	-0.082	-0.209				
	WLAN 2.4G		1.099	5	-0.0526	0.0786	-0.209				
Case 11	WCDMA V	Back	1.312	5	-0.0315	-0.0815	-0.209	157.9	2.20	0.02	Not required
	WLAN5GHz		0.89	5	-0.059	0.074	-0.209				
	WLAN5GHz		0.89	5	-0.059	0.074	-0.209				
Case 12	WCDMA II	Back	0.765	5	-0.038	-0.0855	-0.209	160.9	1.66	0.01	Not required
	WLAN5GHz		0.89	5	-0.059	0.074	-0.209				
	WLAN5GHz		0.89	5	-0.059	0.074	-0.209				
Case 13	LTE B26	Back	1.272	5	-0.03	-0.0815	-0.209	158.2	2.16	0.02	Not required
	WLAN5GHz		0.89	5	-0.059	0.074	-0.209				
	WLAN5GHz		0.89	5	-0.059	0.074	-0.209				
Case 15	LTE B7	Back	0.958	5	-0.0106	-0.082	-0.209	163.3	1.85	0.02	Not required
	WLAN5GHz		0.89	5	-0.059	0.074	-0.209				
	WLAN5GHz		0.89	5	-0.059	0.074	-0.209				
Case 16	LTE B41	Back	0.927	5	-0.0106	-0.082	-0.209	163.3	1.82	0.01	Not required
	WLAN5GHz		0.89	5	-0.059	0.074	-0.209				
	WLAN5GHz		0.89	5	-0.059	0.074	-0.209				

Body Worn:

Case	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
Case 1	GSM850	Back	1.285	5	-0.0205	-0.0815	-0.207	158.4	2.38	0.02	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0736	-0.209				
	GSM850	Back	1.285	5	-0.0205	-0.0815	-0.207	163.3	2.38	0.02	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0786	-0.209				
Case 17	GSM1900 Cube0	Back	1.429	5	-0.0165	-0.0815	-0.209	159.2	2.53	0.03	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0736	-0.209				
	GSM1900 Cube1	Back	1.429	5	-0.0385	-0.0825	-0.209	156.7	2.53	0.03	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0736	-0.209				
	GSM1900 Cube0	Back	1.429	5	-0.0165	-0.0815	-0.209	164.1	2.53	0.02	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0786	-0.209				
GSM1900 Cube1	Back	1.429	5	-0.0385	-0.0825	-0.209	161.7	2.53	0.02	Not required	
WLAN 2.4G		1.099	5	-0.0526	0.0786	-0.209					
Case 3	WCDMA V	Back	1.312	5	-0.0315	-0.0815	-0.209	156.5	2.41	0.02	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0736	-0.209				
	WCDMA V	Back	1.312	5	-0.0315	-0.0815	-0.209	161.5	2.41	0.02	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0786	-0.209				
Case 18	WCDMA II	Back	1.327	5	-0.038	-0.0855	-0.209	159.8	2.43	0.02	Not required
	WCDMA II		1.327	5	-0.038	-0.0855	-0.209				



FCC SAR Test Report

Report No. : FA1N1011-04

Case	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
Case 4	WLAN 2.4G	Back	1.099	5	-0.0526	0.0736	-0.209	164.7	2.43	0.02	Not required
	WCDMA II		1.327	5	-0.038	-0.0855	-0.209				
	WLAN 2.4G		1.099	5	-0.0526	0.0786	-0.209				
Case 5	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE B26	Back	1.272	5	-0.03	-0.0815	-0.209				
	WLAN 2.4G		1.099	5	-0.0526	0.0736	-0.209	156.7	2.37	0.02	Not required
	LTE B26	Back	1.272	5	-0.03	-0.0815	-0.209	161.7	2.37	0.02	Not required
WLAN 2.4G	1.099		5	-0.0526	0.0786	-0.209					
Case 19	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE B2 Cube0	Back	1.326	5	-0.035	-0.087	-0.209				
	WLAN 2.4G		1.099	5	-0.0526	0.0736	-0.209	161.6	2.43	0.02	Not required
	LTE B2 Cube1	Back	1.326	5	-0.0415	-0.0885	-0.209	162.5	2.43	0.02	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0736	-0.209				
	LTE B2 Cube0	Back	1.326	5	-0.035	-0.087	-0.209	166.5	2.43	0.02	Not required
	WLAN 2.4G		1.099	5	-0.0526	0.0786	-0.209				
LTE B2 Cube1	Back	1.326	5	-0.0415	-0.0885	-0.209	167.5	2.43	0.02	Not required	
WLAN 2.4G		1.099	5	-0.0526	0.0786	-0.209					
Case 20	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE B7	Back	1.206	5	-0.0106	-0.082	-0.209				
	WLAN 2.4G		1.099	5	-0.0526	0.0736	-0.209	161.2	2.31	0.02	Not required
	LTE B7	Back	1.206	5	-0.0106	-0.082	-0.209	166.0	2.31	0.02	Not required
WLAN 2.4G	1.099		5	-0.0526	0.0786	-0.209					
Case 21	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE B41	Back	1.312	5	-0.0106	-0.082	-0.209				
	WLAN 2.4G		1.099	5	-0.0526	0.0736	-0.209	161.2	2.41	0.02	Not required
	LTE B41	Back	1.312	5	-0.0106	-0.082	-0.209	166.0	2.41	0.02	Not required
WLAN 2.4G	1.099		5	-0.0526	0.0786	-0.209					
Case 22	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	GSM850	Back	1.285	5	-0.0205	-0.0815	-0.207				
	WLAN5GHz		1.18	5	-0.06	0.074	-0.209	160.5	2.47	0.02	Not required
Case 23	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	GSM1900 Cube0	Back	1.429	5	-0.0165	-0.0815	-0.209				
	WLAN5GHz		1.18	5	-0.06	0.074	-0.209	161.5	2.61	0.03	Not required
	GSM1900 Cube1	Back	1.429	5	-0.0385	-0.0825	-0.209	158.0	2.61	0.03	Not required
WLAN5GHz	1.18		5	-0.06	0.074	-0.209					
Case 24	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	WCDMA V	Back	1.312	5	-0.0315	-0.0815	-0.209				
	WLAN5GHz		1.18	5	-0.06	0.074	-0.209	158.1	2.49	0.02	Not required
Case 25	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	WCDMA II	Back	1.327	5	-0.038	-0.0855	-0.209				
	WLAN5GHz		1.18	5	-0.06	0.074	-0.209	161.0	2.51	0.02	Not required
Case 26	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE B26	Back	1.272	5	-0.03	-0.0815	-0.209				
	WLAN5GHz		1.18	5	-0.06	0.074	-0.209	158.4	2.45	0.02	Not required
Case 27	Band	Position	SAR (W/kg)	Gap	SAR peak location (m)			3D	Summed	SPLSR	Simultaneous

Sporton International Inc. (Shenzhen)

TEL : +86-755-86379589 / FAX : +86-755-86379595

FCC ID : IHDT56AC7

Issued Date : Mar. 15, 2022

Form version. : 200414



				(mm)	X	Y	Z	distance (mm)	SAR (W/kg)		
	LTE B2 Cube0	Back	1.326	5	-0.035	-0.087	-0.209	162.9	2.51	0.02	Not required
	WLAN5GHz		1.18	5	-0.06	0.074	-0.209				
	LTE B2 Cube1	Back	1.326	5	-0.0415	-0.0885	-0.209	163.5	2.51	0.02	Not required
	WLAN5GHz		1.18	5	-0.06	0.074	-0.209				
Case 28	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE B7	Back	1.206	5	-0.0106	-0.082	-0.209	163.6	2.39	0.02	Not required
	WLAN5GHz		1.18	5	-0.06	0.074	-0.209				
Case 29	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (m)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	LTE B41	Back	1.312	5	-0.0106	-0.082	-0.209	163.6	2.49	0.02	Not required
	WLAN5GHz		1.18	5	-0.06	0.074	-0.209				

Test Engineer : Kevin Xu, David Dai, Bin He



16. Uncertainty Assessment

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg and highest measured 10-g SAR is less 3.75W/kg. Therefore, the measurement uncertainty table is not required in this report.

17. References

- [1] FCC 47 CFR Part 2 “Frequency Allocations and Radio Treaty Matters; General Rules and Regulations”
- [2] ANSI/IEEE Std. C95.1-1992, “IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz”, September 1992
- [3] IEEE Std. 1528-2013, “IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques”, Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [6] FCC KDB 865664 D02 v01r02, “RF Exposure Compliance Reporting and Documentation Considerations” Oct 2015.
- [7] FCC KDB 447498 D01 v06, “Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies”, Oct 2015
- [8] FCC KDB 648474 D04 v01r03, “SAR Evaluation Considerations for Wireless Handsets”, Oct 2015.
- [9] FCC KDB 248227 D01 v02r02, “SAR Guidance for IEEE 802.11 (WiFi) Transmitters”, Oct 2015.
- [10] FCC KDB 616217 D04 v01r02, “SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers”, Oct 2015
- [11] FCC KDB 941225 D01 v03r01, “3G SAR MEAUREMENT PROCEDURES”, Oct 2015
- [12] FCC KDB 941225 D05 v02r05, “SAR Evaluation Considerations for LTE Devices”, Dec 2015
- [13] FCC KDB 941225 D06 v02r01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", Oct 2015.

-----THE END-----



Appendix A. Plots of System Performance Check

The plots are shown as follows.

System Check_835MHz

DUT: D835V2-SN:4d258


Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1
Medium: HSL_835_220214 Medium parameters used: $f = 835$ MHz; $\sigma = 0.901$ S/m; $\epsilon_r = 40.721$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.4 °C; Liquid Temperature : 22.1 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7641; ConvF(10.9, 10.9, 10.9); Calibrated: 2021/3/15
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1664; Calibrated: 2021/3/1
- Phantom: Twin-SAM1(P1aP2a20); Type: QD 000 P40 CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.13 (7474)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 2.53 W/kg

Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 53.64 V/m; Power Drift = 0.06 dB
Peak SAR (extrapolated) = 2.88 W/kg
SAR(1 g) = 2.3 W/kg; SAR(10 g) = 1.6 W/kg
Maximum value of SAR (measured) = 2.55 W/kg



System Check_835MHz

DUT: D835V2-SN:4d258


Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1
Medium: HSL_835_220217 Medium parameters used: $f = 835$ MHz; $\sigma = 0.927$ S/m; $\epsilon_r = 42.674$;
 $\rho = 1000$ kg/m³
Ambient Temperature : 23.6 °C; Liquid Temperature : 22.5 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7641; ConvF(10.9, 10.9, 10.9); Calibrated: 2021/3/15
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1664; Calibrated: 2021/3/1
- Phantom: Twin-SAM1(P1aP2a20); Type: QD 000 P40 CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.13 (7474)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 2.47 W/kg

Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 49.73 V/m; Power Drift = 0.04 dB
Peak SAR (extrapolated) = 2.84 W/kg
SAR(1 g) = 2.32 W/kg; SAR(10 g) = 1.65 W/kg
Maximum value of SAR (measured) = 2.51 W/kg



0 dB = 2.51 W/kg

System Check_1900MHz

DUT: D1900V2-SN:5d170


Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1
Medium: HSL_1900_220215 Medium parameters used: $f = 1900 \text{ MHz}$; $\sigma = 1.43 \text{ S/m}$; $\epsilon_r = 38.742$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : 23.4 °C; Liquid Temperature : 22.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7641; ConvF(9.05, 9.05, 9.05); Calibrated: 2021/3/15
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1664; Calibrated: 2021/3/1
- Phantom: Twin-SAM1(P1aP2a20); Type: QD 000 P40 CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.13 (7474)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$
Maximum value of SAR (interpolated) = 13.0 W/kg

Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$
Reference Value = 90.17 V/m; Power Drift = 0.11 dB
Peak SAR (extrapolated) = 15.4 W/kg
SAR(1 g) = 9.42 W/kg; SAR(10 g) = 5.33 W/kg
Maximum value of SAR (measured) = 12.9 W/kg



0 dB = 12.9 W/kg

System Check_1900MHz

DUT: D1900V2-SN:5d170


Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1
Medium: HSL_1900_220218 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.46$ S/m; $\epsilon_r = 39.123$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.1 °C; Liquid Temperature : 22.1 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7641; ConvF(9.05, 9.05, 9.05); Calibrated: 2021/3/15
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1664; Calibrated: 2021/3/1
- Phantom: Twin-SAM1(P1aP2a20); Type: QD 000 P40 CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.13 (7474)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 12.4 W/kg

Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 86.69 V/m; Power Drift = 0.09 dB
Peak SAR (extrapolated) = 15.1 W/kg
SAR(1 g) = 9.63 W/kg; SAR(10 g) = 5.55 W/kg
Maximum value of SAR (measured) = 12.7 W/kg



0 dB = 12.7 W/kg

System Check_2450MHz

DUT: D2450V2-SN:924


Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1
Medium: HSL_2450_220220 Medium parameters used: $f = 2450$ MHz; $\sigma = 1.829$ S/m; $\epsilon_r = 40.081$;
 $\rho = 1000$ kg/m³
Ambient Temperature : 23.2 °C; Liquid Temperature : 22.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7641; ConvF(8.29, 8.29, 8.29); Calibrated: 2021/3/15
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1664; Calibrated: 2021/3/1
- Phantom: Twin-SAM1(P1aP2a20); Type: QD 000 P40 CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.13 (7474)

Pin=250mW/Area Scan (71x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 22.8 W/kg

Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 106.6 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 27.6 W/kg
SAR(1 g) = 13.1 W/kg; SAR(10 g) = 6.06 W/kg
Maximum value of SAR (measured) = 21.8 W/kg



0 dB = 21.8 W/kg

System Check_2450MHz

DUT: D2450V2-SN:924


Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1
Medium: HSL_2450_220224 Medium parameters used: $f = 2450$ MHz; $\sigma = 1.861$ S/m; $\epsilon_r = 39.575$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.6 °C; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7641; ConvF(8.29, 8.29, 8.29); Calibrated: 2021/3/15
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1664; Calibrated: 2021/3/1
- Phantom: Twin-SAM1(P1aP2a20); Type: QD 000 P40 CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.13 (7474)

Pin=250mW/Area Scan (81x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 9.35 W/kg

Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 57.76 V/m; Power Drift = 0.18 dB
Peak SAR (extrapolated) = 13.3 W/kg
SAR(1 g) = 13.3 W/kg; SAR(10 g) = 5.7 W/kg
Maximum value of SAR (measured) = 9.49 W/kg



0 dB = 9.49 W/kg

System Check_2600MHz

DUT: D2600V2-SN:1061


Communication System: UID 0, CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1
Medium: HSL_2600_220216 Medium parameters used: $f = 2600$ MHz; $\sigma = 1.974$ S/m; $\epsilon_r = 38.204$;
 $\rho = 1000$ kg/m³
Ambient Temperature : 23.4 °C; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7641; ConvF(7.94, 7.94, 7.94); Calibrated: 2021/3/15
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1664; Calibrated: 2021/3/1
- Phantom: Twin-SAM1(P1aP2a20); Type: QD 000 P40 CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.13 (7474)

Pin=250mW/Area Scan (71x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 25.5 W/kg

Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 108.7 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 30.7 W/kg
SAR(1 g) = 14.1 W/kg; SAR(10 g) = 6.31 W/kg
Maximum value of SAR (measured) = 24.4 W/kg



0 dB = 24.4 W/kg

System Check_2600MHz

DUT: D2600V2-SN:1061


Communication System: UID 0, CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1
Medium: HSL_2600_220219 Medium parameters used: $f = 2600$ MHz; $\sigma = 1.922$ S/m; $\epsilon_r = 39.818$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.6 °C; Liquid Temperature : 22.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7641; ConvF(7.94, 7.94, 7.94); Calibrated: 2021/3/15
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1664; Calibrated: 2021/3/1
- Phantom: Twin-SAM1(P1aP2a20); Type: QD 000 P40 CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.13 (7474)

Pin=250mW/Area Scan (71x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 24.8 W/kg

Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 108.7 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 29.9 W/kg
SAR(1 g) = 13.8 W/kg; SAR(10 g) = 6.14 W/kg
Maximum value of SAR (measured) = 23.8 W/kg



0 dB = 23.8 W/kg

System Check_5250MHz

DUT: D5GHzV2-SN:1113


Communication System: UID 0, CW (0); Frequency: 5250 MHz; Duty Cycle: 1:1
Medium: HSL_5250_220221 Medium parameters used: $f = 5250$ MHz; $\sigma = 4.764$ S/m; $\epsilon_r = 36.965$;
 $\rho = 1000$ kg/m³
Ambient Temperature : 23.2 °C; Liquid Temperature : 22.1 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7641; ConvF(5.68, 5.68, 5.68); Calibrated: 2021/3/15
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1664; Calibrated: 2021/3/1
- Phantom: Twin-SAM1(P1aP2a20); Type: QD 000 P40 CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.13 (7474)

Pin=100mW/Area Scan (71x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 18.0 W/kg

Pin=100mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 64.19 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 29.0 W/kg
SAR(1 g) = 7.61 W/kg; SAR(10 g) = 2.36 W/kg
Maximum value of SAR (measured) = 17.1 W/kg



0 dB = 17.1 W/kg

System Check_5250MHz

DUT: D5GHzV2-SN:1113


Communication System: UID 0, CW (0); Frequency: 5250 MHz; Duty Cycle: 1:1
Medium: HSL_5250_220225 Medium parameters used: $f = 5250$ MHz; $\sigma = 4.699$ S/m; $\epsilon_r = 36.046$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.1 °C; Liquid Temperature : 22.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7641; ConvF(5.68, 5.68, 5.68); Calibrated: 2021/3/15
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1664; Calibrated: 2021/3/1
- Phantom: Twin-SAM1(P1aP2a20); Type: QD 000 P40 CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.13 (7474)

Pin=100mW/Area Scan (71x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 16.4 W/kg

Pin=100mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 55.99 V/m; Power Drift = 0.05 dB
Peak SAR (extrapolated) = 27.3 W/kg
SAR(1 g) = 7.33 W/kg; SAR(10 g) = 2.25 W/kg
Maximum value of SAR (measured) = 16.5 W/kg



0 dB = 16.5 W/kg

System Check_5600MHz

DUT: D5GHzV2-SN:1113


Communication System: UID 0, CW (0); Frequency: 5600 MHz; Duty Cycle: 1:1
Medium: HSL_5600_220222 Medium parameters used: $f = 5600$ MHz; $\sigma = 5.004$ S/m; $\epsilon_r = 36.093$;
 $\rho = 1000$ kg/m³
Ambient Temperature : 23.2 °C; Liquid Temperature : 22.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7641; ConvF(5.03, 5.03, 5.03); Calibrated: 2021/3/15
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1664; Calibrated: 2021/3/1
- Phantom: Twin-SAM1(P1aP2a20); Type: QD 000 P40 CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.10 (3); SEMCAD X Version 14.6.13 (7474)

Pin=100mW/Area Scan (71x71x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm
Maximum value of SAR (interpolated) = 19.8 W/kg

Pin=100mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
Reference Value = 59.22 V/m; Power Drift = -0.16 dB
Peak SAR (extrapolated) = 32.7 W/kg
SAR(1 g) = 7.88 W/kg; SAR(10 g) = 2.16 W/kg
Maximum value of SAR (measured) = 18.6 W/kg



0 dB = 18.6 W/kg