



# FCC RF Test Report

APPLICANT : Motorola Mobility LLC  
EQUIPMENT : Mobile Cellular Phone  
BRAND NAME : Motorola  
MODEL NAME : XT2203-1  
FCC ID : IHDT56AE6  
STANDARD : FCC Part 15 Subpart C §15.247  
CLASSIFICATION : (DSS) Spread Spectrum Transmitter  
TEST DATE(S) : Jan. 13, 2022 ~ Feb. 24, 2022

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

*Jason Jia*

Reviewed by: Jason Jia / Supervisor

*Alex Wang*

Approved by: Alex Wang / Manager



**Sporton International Inc. (Kunshan)**

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300  
People's Republic of China**



# TABLE OF CONTENTS

**REVISION HISTORY..... 3**

**SUMMARY OF TEST RESULT ..... 4**

**1 GENERAL DESCRIPTION..... 5**

    1.1 Applicant ..... 5

    1.2 Manufacturer ..... 5

    1.3 Product Feature of Equipment Under Test..... 5

    1.4 Product Specification of Equipment Under Test..... 6

    1.5 Modification of EUT ..... 7

    1.6 Specification of Accessory ..... 7

    1.7 Testing Location ..... 8

    1.8 Test Software ..... 8

    1.9 Applicable Standards ..... 8

**2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST..... 9**

    2.1 Carrier Frequency Channel ..... 9

    2.2 Test Mode ..... 10

    2.3 Connection Diagram of Test System ..... 11

    2.4 Support Unit used in test configuration and system ..... 12

    2.5 EUT Operation Test Setup ..... 12

    2.6 Measurement Results Explanation Example ..... 12

**3 TEST RESULT ..... 13**

    3.1 Number of Channel Measurement ..... 13

    3.2 Hopping Channel Separation Measurement ..... 16

    3.3 Dwell Time Measurement ..... 27

    3.4 20dB and 99% Bandwidth Measurement ..... 30

    3.5 Output Power Measurement ..... 51

    3.6 Conducted Band Edges Measurement ..... 52

    3.7 Conducted Spurious Emission Measurement ..... 65

    3.8 Radiated Band Edges and Spurious Emission Measurement ..... 84

    3.9 AC Conducted Emission Measurement ..... 88

    3.10 Antenna Requirements ..... 90

**4 LIST OF MEASURING EQUIPMENT ..... 91**

**5 UNCERTAINTY OF EVALUATION..... 92**

**APPENDIX A. CONDUCTED TEST RESULTS**

**APPENDIX B. AC CONDUCTED EMISSION TEST RESULT**

**APPENDIX C. RADIATED SPURIOUS EMISSION**

**APPENDIX D. DUTY CYCLE PLOTS**

**APPENDIX E. SETUP PHOTOGRAPHS**



### REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR1D2901A	Rev. 01	Initial issue of report	Mar. 01, 2022



## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	Number of Channels	≥ 15Chs	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	≥ 2/3 of 20dB BW	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	≤ 0.4sec in 31.6sec period	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	-	Report only	-
3.4	-	99% Bandwidth	-	Report only	-
3.5	15.247(b)(1)	Peak Output Power	≤ 125 mW	Pass	-
3.6	15.247(d)	Conducted Band Edges	≤ 20dBc	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	≤ 20dBc	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 5.67 dB at 48.430 MHz
3.9	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 6.07 dB at 0.227 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



# 1 General Description

## 1.1 Applicant

Motorola Mobility LLC  
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

## 1.2 Manufacturer

Motorola Mobility LLC  
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2203-1
IMEI Code	Conducted: 354596750030032/354596750030040 Conduction: 354596750032137/354596750032145 Radiation: 354596750032137/354596750032145
FCC ID	IHDT56AE6
HW Version	DVT2
SW Version	S1RD32.41
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



### 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx/Rx Frequency Range</b>	2402 MHz ~ 2480 MHz
<b>Number of Channels</b>	79
<b>Carrier Frequency of Each Channel</b>	2402+n*1 MHz; n=0~78
<b>Maximum Output Power to Antenna</b>	For Ant 1: Bluetooth BR(1Mbps) : 11.02 dBm (0.0126 W) Bluetooth EDR (2Mbps) : 9.95 dBm (0.0099 W) Bluetooth EDR (3Mbps) : 9.89 dBm (0.0097 W) For Ant 2: Bluetooth BR(1Mbps) : 12.82 dBm (0.0191 W) Bluetooth EDR (2Mbps) : 11.65 dBm (0.0146 W) Bluetooth EDR (3Mbps) : 12.06 dBm (0.0161 W)
<b>99% Occupied Bandwidth</b>	For Ant 1: Bluetooth BR(1Mbps) : 0.842MHz Bluetooth EDR (2Mbps) : 1.166MHz Bluetooth EDR (3Mbps) : 1.149MHz For Ant 2: Bluetooth BR(1Mbps) : 0.836MHz Bluetooth EDR (2Mbps) : 1.166MHz Bluetooth EDR (3Mbps) : 1.152MHz
<b>Antenna Type / Gain</b>	For Ant 1: PIFA Antenna type with gain -7.0 dBi For Ant 2: PIFA Antenna type with gain -8.0 dBi
<b>Type of Modulation</b>	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

Note: Ant.1 corresponding to EUT photo Antenna 3, Ant.2 corresponding to EUT photo Antenna 5.



### 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

### 1.6 Specification of Accessory

Specification of Accessory				
AC Adapter 1(US)	Brand Name	Motorola (Salcomp)	Model Name	MC-331
AC Adapter 1(EU)	Brand Name	Motorola (Salcomp)	Model Name	MC-332
AC Adapter 1(UK)	Brand Name	Motorola (Salcomp)	Model Name	MC-333
AC Adapter 1(IN)	Brand Name	Motorola (Salcomp)	Model Name	MC-334
AC Adapter 1(AU)	Brand Name	Motorola (Salcomp)	Model Name	MC-335
AC Adapter 1(AR)	Brand Name	Motorola (Salcomp)	Model Name	MC-336
AC Adapter 1(BR)	Brand Name	Motorola (Salcomp)	Model Name	MC-337
AC Adapter 1(CHILE)	Brand Name	Motorola (Salcomp)	Model Name	MC-339
AC Adapter 2(US)	Brand Name	Motorola (Acbel)	Model Name	MC-331
AC Adapter 2(EU)	Brand Name	Motorola (Acbel)	Model Name	MC-332
AC Adapter 2(UK)	Brand Name	Motorola (Acbel)	Model Name	MC-333
AC Adapter 3(US)	Brand Name	Motorola (AOHAI)	Model Name	MC-331
AC Adapter 3(EU)	Brand Name	Motorola (AOHAI)	Model Name	MC-332
AC Adapter 3(UK)	Brand Name	Motorola (AOHAI)	Model Name	MC-333
Battery 1	Brand Name	Motorola (ATL)	Model Name	ND40
Battery 2	Brand Name	Motorola (SCUD)	Model Name	ND40
Earphone	Brand Name	Motorola (Lyand)	Model Name	MI181C
USB Cable 1	Brand Name	Motorola (Saibao)	Model Name	SC18D22297
USB Cable 2	Brand Name	Motorola (Cabletech)	Model Name	SC18D22298
USB Cable 3	Brand Name	Motorola (Luxshare)	Model Name	SC18D22299



### 1.7 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

<b>Test Firm</b>	Sporton International Inc. (Kunshan)		
<b>Test Site Location</b>	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People’s Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	CO01-KS 03CH02-KS TH01-KS	CN1257	314309

### 1.8 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH02-KS	AUDIX	E3	6.2009-8-24a
2.	CO01-KS	AUDIX	E3	6.2009-8-24

### 1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ANSI C63.10-2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.





## 2 Test Configuration of Equipment Under Test

### 2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-



## 2.2 Test Mode


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report, and the worst mode of radiated spurious emissions is Bluetooth 1Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps π/4-DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted Test Cases	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	Mode 4: CH00_2402 MHz Mode 5: CH39_2441 MHz Mode 6: CH78_2480 MHz	Mode 7: CH00_2402 MHz Mode 8: CH39_2441 MHz Mode 9: CH78_2480 MHz
Radiated Test Cases	<b>Bluetooth BR 1Mbps GFSK</b> Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz <b>Mode 3: CH78_2480 MHz</b>		
AC Conducted Emission	Mode 1 : GSM 850 Idle + Bluetooth Link + WLAN Link (2.4G) + USB Cable 1(Charging from Adapter1)		
<b>Remark:</b> 1. For radiated test cases, the worst mode data rate 1Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission. 2. All test modes of the Radiated Spurious Emission (RSE) were tested; only the worse data for Ant.1 in bold were reported. 3. For Radiated Test Cases, The tests were performed with Adapter 1 and USB Cable 1.			

## 2.3 Connection Diagram of Test System

For Radiated Emission



For Conducted Emission



## 2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Base Station	Anritus	MT8821C	N/A	N/A	Unshielded,1.8m
2.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
3.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
5.	Bluetooth base station	R&S	CBT	N/A	N/A	Unshielded,1.8m

## 2.5 EUT Operation Test Setup

For Bluetooth function, the engineering test program was provided and enabled to make EUT connect with Bluetooth base station to continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss*

Following shows an offset computation example with cable loss 6.0 dB.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)}. \\ &= 6.0 \text{ (dB)} \end{aligned}$$

### 3 Test Result

#### 3.1 Number of Channel Measurement

##### 3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW = 300kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

##### 3.1.4 Test Setup






### 3.1.5 Test Result of Number of Hopping Frequency

Please refer to Appendix A.


For Ant 1:

#### Number of Hopping Channel Plot on Channel 00 - 78



Date: 27.JAN.2022 03:05:43

#### Number of Hopping Channel Plot on Channel 00 - 78




Date: 27.JAN.2022 03:06:33




For Ant 2:

Number of Hopping Channel Plot on Channel 00 - 78



Date: 27.JAN.2022 02:02:06

Number of Hopping Channel Plot on Channel 00 - 78



Date: 27.JAN.2022 02:03:00

## 3.2 Hopping Channel Separation Measurement

### 3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels;  
RBW = 300kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

### 3.2.4 Test Setup








### 3.2.5 Test Result of Hopping Channel Separation

Please refer to Appendix A.

For Ant 1:


<1Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 27.JAN.2022 03:09:10


Channel Separation Plot on Channel 39 - 40



Date: 27.JAN.2022 03:15:10




Channel Separation Plot on Channel 77 - 78



Date: 27.JAN.2022 03:22:10

<2Mbps>


Channel Separation Plot on Channel 00 - 01



Date: 27.JAN.2022 03:42:08




Channel Separation Plot on Channel 39 - 40



Date: 27.JAN.2022 03:33:52

Channel Separation Plot on Channel 77 - 78




Date: 27.JAN.2022 03:32:55




<3Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 27.JAN.2022 03:47:37


Channel Separation Plot on Channel 39 - 40



Date: 27.JAN.2022 03:51:37



Channel Separation Plot on Channel 77 - 78




Date: 27.JAN.2022 03:58:18



For Ant 2:


<1Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 27.JAN.2022 01:48:06


Channel Separation Plot on Channel 39 - 40



Date: 27.JAN.2022 01:53:27




Channel Separation Plot on Channel 77 - 78



Date: 27.JAN.2022 01:58:16

<2Mbps>


Channel Separation Plot on Channel 00 - 01



Date: 27.JAN.2022 02:19:12




Channel Separation Plot on Channel 39 - 40



Date: 27.JAN.2022 02:16:42

Channel Separation Plot on Channel 77 - 78




Date: 27.JAN.2022 02:12:39






<3Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 27.JAN.2022 02:40:20


Channel Separation Plot on Channel 39 - 40



Date: 27.JAN.2022 02:45:32



Channel Separation Plot on Channel 77 - 78



Date: 27.JAN.2022 02:57:35

### 3.3 Dwell Time Measurement

#### 3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW  $\geq$  RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

#### 3.3.4 Test Setup






### 3.3.5 Test Result of Dwell Time

Please refer to Appendix A.

For Ant 1:


#### Package Transfer Time Plot



Date: 13.JAN.2022 17:03:25

For Ant 2:

#### Package Transfer Time Plot



Date: 13.JAN.2022 18:58:46



**Remark:**

1. In normal mode, hopping rate is 1600 hops/s with 6 slots (5 Transmit and 1 Receive slot) in 79 hopping channels.  
With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),  
Hops Over Occupancy Time comes to  $(1600 / 6 / 79) \times (0.4 \times 79) = 106.67$  hops.
2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels.  
With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s),  
Hops Over Occupancy Time comes to  $(800 / 6 / 20) \times (0.4 \times 20) = 53.33$  hops.
3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

## 3.4 20dB and 99% Bandwidth Measurement

### 3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only

### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.  
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;  
The RBW is set to 1% to 5% of the 99% OBW, the VBW is set to 3 times the RBW;  
Sweep = auto; Detector function = peak;  
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.  
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;  
The RBW is set to 1% to 5% of the 99% OBW, the VBW is set to 3 times the RBW;  
Sweep = auto; Detector function = sample;  
Trace = max hold.
6. Measure and record the results in the test report.

### 3.4.4 Test Setup






### 3.4.5 Test Result of 20dB Bandwidth

Please refer to Appendix A.

For Ant 1:


<1Mbps>

#### 20 dB Bandwidth Plot on Channel 00



Date: 27.JAN.2022 03:10:09


#### 20 dB Bandwidth Plot on Channel 39



Date: 27.JAN.2022 03:16:10




20 dB Bandwidth Plot on Channel 78



Date: 27.JAN.2022 03:23:13

<2Mbps>

20 dB Bandwidth Plot on Channel 00




Date: 27.JAN.2022 03:44:12






20 dB Bandwidth Plot on Channel 39



Date: 27.JAN.2022 03:34:51

20 dB Bandwidth Plot on Channel 78




Date: 27.JAN.2022 03:28:08




<3Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 27.JAN.2022 03:48:38


20 dB Bandwidth Plot on Channel 39



Date: 27.JAN.2022 03:52:38



20 dB Bandwidth Plot on Channel 78




Date: 27.JAN.2022 03:59:14



For Ant 2:


<1Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 27.JAN.2022 01:42:17


20 dB Bandwidth Plot on Channel 39



Date: 27.JAN.2022 01:49:58




20 dB Bandwidth Plot on Channel 78



Date: 27.JAN.2022 01:55:19

<2Mbps>


20 dB Bandwidth Plot on Channel 00



Date: 27.JAN.2022 02:20:20




20 dB Bandwidth Plot on Channel 39



Date: 27.JAN.2022 02:13:55

20 dB Bandwidth Plot on Channel 78




Date: 27.JAN.2022 02:05:42




<3Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 27.JAN.2022 02:41:54


20 dB Bandwidth Plot on Channel 39



Date: 27.JAN.2022 02:46:34



20 dB Bandwidth Plot on Channel 78



Date: 27.JAN.2022 02:52:47





### 3.4.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

For Ant 1:


<1Mbps>

#### 99% Occupied Bandwidth Plot on Channel 00



Date: 27.JAN.2022 03:11:50


#### 99% Occupied Bandwidth Plot on Channel 39



Date: 27.JAN.2022 03:16:53




99% Occupied Bandwidth Plot on Channel 78



Date: 27.JAN.2022 03:24:07

<2Mbps>


99% Occupied Bandwidth Plot on Channel 00



Date: 27.JAN.2022 03:45:05



99% Occupied Bandwidth Plot on Channel 39



Date: 27.JAN.2022 03:35:30

99% Occupied Bandwidth Plot on Channel 78




Date: 27.JAN.2022 03:29:04




<3Mbps>

99% Occupied Bandwidth Plot on Channel 00



Date: 27.JAN.2022 03:49:34


99% Occupied Bandwidth Plot on Channel 39



Date: 27.JAN.2022 03:53:16



99% Occupied Bandwidth Plot on Channel 78



Date: 27.JAN.2022 04:00:12



For Ant 2:

<1Mbps>

99% Occupied Bandwidth Plot on Channel 00



Date: 27.JAN.2022 01:43:21


99% Occupied Bandwidth Plot on Channel 39



Date: 27.JAN.2022 01:50:39




99% Occupied Bandwidth Plot on Channel 78



Date: 27.JAN.2022 01:56:20

<2Mbps>


99% Occupied Bandwidth Plot on Channel 00



Date: 27.JAN.2022 02:21:17



99% Occupied Bandwidth Plot on Channel 39



Date: 27.JAN.2022 02:14:39

99% Occupied Bandwidth Plot on Channel 78




Date: 27.JAN.2022 02:06:44






<3Mbps>

99% Occupied Bandwidth Plot on Channel 00



Date: 27.JAN.2022 02:42:57


99% Occupied Bandwidth Plot on Channel 39



Date: 27.JAN.2022 02:47:16



99% Occupied Bandwidth Plot on Channel 78



Date: 27.JAN.2022 02:53:46

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

## 3.5 Output Power Measurement

### 3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:

- (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.


### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

### 3.5.4 Test Setup



### 3.5.5 Test Result of Peak Output Power

Please refer to Appendix A.

## 3.6 Conducted Band Edges Measurement

### 3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


### 3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

### 3.6.4 Test Setup






### 3.6.5 Test Result of Conducted Band Edges

For Ant 1:


<1Mbps>

#### Low Band Edge Plot on Channel 00



Date: 27.JAN.2022 03:10:35

#### High Band Edge Plot on Channel 78




Date: 27.JAN.2022 03:24:29




<2Mbps>

Low Band Edge Plot on Channel 00



Date: 27.JAN.2022 03:44:30

High Band Edge Plot on Channel 78




Date: 27.JAN.2022 03:28:26




<3Mbps>

Low Band Edge Plot on Channel 00



Date: 27.JAN.2022 03:48:59

High Band Edge Plot on Channel 78




Date: 27.JAN.2022 03:59:38



For Ant 2:


<1Mbps>

Low Band Edge Plot on Channel 00



Date: 27.JAN.2022 01:42:44

High Band Edge Plot on Channel 78




Date: 27.JAN.2022 01:55:42






<2Mbps>

Low Band Edge Plot on Channel 00



Date: 27.JAN.2022 02:20:39

High Band Edge Plot on Channel 78




Date: 27.JAN.2022 02:06:06




<3Mbps>

Low Band Edge Plot on Channel 00



Date: 27.JAN.2022 02:42:21

High Band Edge Plot on Channel 78



Date: 27.JAN.2022 02:53:10