



FCC RF Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT2237-1
FCC ID : IHDT56AJ1
STANDARD : FCC Part 15 Subpart E §15.407
CLASSIFICATION : (NII) Unlicensed National Information Infrastructure
TEST DATE(S) : Oct. 24, 2021 ~ Nov. 05, 2022

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

This report contains data that were produced under subcontract by Sporton International Inc. (Shenzhen)

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia



Approved by: Jason Jia

Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant 5

 1.2 Manufacturer..... 5

 1.3 Product Feature of Equipment Under Test..... 5

 1.4 Product Specification of Equipment Under Test..... 6

 1.5 Modification of EUT 7

 1.6 Specification of Accessory..... 7

 1.7 Testing Location 8

 1.8 Test Software..... 8

 1.9 Applicable Standards..... 9

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST..... 10

 2.1 Carrier Frequency and Channel 10

 2.2 Test Mode..... 11

 2.3 Connection Diagram of Test System..... 13

 2.4 Support Unit used in test configuration and system 13

 2.5 EUT Operation Test Setup 14

 2.6 Measurement Results Explanation Example..... 14

3 TEST RESULT..... 15

 3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement 15

 3.2 Maximum Conducted Output Power Measurement 17

 3.3 Power Spectral Density Measurement 19

 3.4 Unwanted Emissions Measurement..... 22

 3.5 AC Conducted Emission Measurement..... 27

 3.6 Antenna Requirements..... 29

4 LIST OF MEASURING EQUIPMENT 30

5 UNCERTAINTY OF EVALUATION..... 31

APPENDIX A. CONDUCTED TEST RESULTS

APPENDIX B. AC CONDUCTED EMISSION TEST RESULT

APPENDIX C. RADIATED SPURIOUS EMISSION

APPENDIX D. DUTY CYCLE PLOTS

APPENDIX E. SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR200909E	Rev. 01	Initial issue of report	Nov. 23, 2022



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit for U-NII-1/2A/2C	Limit for U-NII-3	Result	Remark
3.1	2.1049 & 15.403(i)	6dB, 26dB & 99% Bandwidth	-	6dB Bandwidth > 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 24 dBm	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 11 dBm/MHz	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b) & 15.209(a)	15.407(b)(4)(i) & 15.209(a)	Pass	Under limit 3.08 dB at 5350.08 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	15.207(a)	Pass	Under limit 8.51 dB at 0.17 MHz
3.6	15.203 & 15.407(a)	Antenna Requirement	15.203 & 15.407(a)	15.203 & 15.407(a)	Pass	-

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1 General Description

1.1 Applicant

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2237-1
FCC ID	IHDT56AJ1
IMEI Code	Conducted: 352182740031539/352182740031547 Conduction: 352182740026810/352182740026828 Radiation: 352182740025952/352182740025960
HW Version	DVT2
SW Version	TTN33.40
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	5180 MHz ~ 5240 MHz 5260 MHz ~ 5320 MHz 5500 MHz ~ 5720 MHz 5745 MHz ~ 5825 MHz
Maximum Output Power to Antenna	<p><5180 MHz ~ 5240 MHz> 802.11a : 17.29 dBm / 0.0536 W 802.11n HT20 : 17.01 dBm / 0.0502 W 802.11n HT40 : 17.32 dBm / 0.0540 W 802.11ac VHT20: 14.92 dBm / 0.0310 W 802.11ac VHT40: 15.30 dBm / 0.0339 W 802.11ac VHT80: 10.64 dBm / 0.0116 W</p> <p><5260 MHz ~ 5320 MHz> 802.11a : 17.57 dBm / 0.0571 W 802.11n HT20 : 17.32 dBm / 0.0540 W 802.11n HT40 : 17.46 dBm / 0.0557 W 802.11ac VHT20: 15.29 dBm / 0.0338 W 802.11ac VHT40: 15.42 dBm / 0.0348 W 802.11ac VHT80: 10.93 dBm / 0.0124 W</p> <p><5500 MHz ~ 5720 MHz > 802.11a : 17.58 dBm / 0.0573 W 802.11n HT20 : 17.41 dBm / 0.0551 W 802.11n HT40 : 17.50 dBm / 0.0562 W 802.11ac VHT20: 15.48 dBm / 0.0353 W 802.11ac VHT40: 15.46 dBm / 0.0352 W 802.11ac VHT80: 15.58 dBm / 0.0361 W</p> <p><5745 MHz ~ 5825 MHz> 802.11a : 16.84 dBm / 0.0483 W 802.11n HT20 : 16.64 dBm / 0.0461 W 802.11n HT40 : 16.78 dBm / 0.0476 W 802.11ac VHT20: 14.69 dBm / 0.0294 W 802.11ac VHT40: 14.81 dBm / 0.0303 W 802.11ac VHT80: 14.83 dBm / 0.0304 W</p>
99% Occupied Bandwidth	<p><5180 MHz ~ 5240 MHz> 802.11a : 17.782 MHz 802.11n HT20 : 18.781 MHz 802.11n HT40 : 37.483 MHz 802.11ac VHT80 : 75.764 MHz</p> <p><5260 MHz ~ 5320 MHz> 802.11a : 17.742 MHz 802.11n HT20 : 18.661 MHz 802.11n HT40 : 37.483 MHz 802.11ac VHT80 : 75.924 MHz</p> <p><5500 MHz ~ 5720 MHz> 802.11a : 18.302 MHz 802.11n HT20 : 18.941 MHz 802.11n HT40 : 37.642 MHz 802.11ac VHT80 : 76.404 MHz</p> <p><5745 MHz ~ 5825 MHz> 802.11a : 18.182 MHz 802.11n HT20 : 18.901 MHz 802.11n HT40 : 37.483 MHz 802.11ac VHT80 : 75.924 MHz</p>



Antenna Type / Gain	<p><5180 MHz ~ 5240 MHz> PIFA Antenna with gain -6.40 dBi</p> <p><5260 MHz ~ 5320 MHz> PIFA Antenna with gain -6.80 dBi</p> <p><5500 MHz ~ 5720 MHz> PIFA Antenna with gain -6.70 dBi</p> <p><5745 MHz ~ 5825 MHz> PIFA Antenna with gain -7.80 dBi</p>
Type of Modulation	<p>802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)</p> <p>802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)</p>

Note: For 802.11n HT20 / ac VHT20 and 802.11n HT40 / ac VHT40 mode, the whole testing has assessed only 802.11n HT20/ HT40 by referring to their higher conducted power.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Specification of Accessory

Accessories Information				
AC Adapter 1 (US)	Brand Name	Motorola(Salom)	Model Name	MC-301
AC Adapter 1 (EU)	Brand Name	Motorola(Salom)	Model Name	MC-302
AC Adapter 1 (UK)	Brand Name	Motorola(Salom)	Model Name	MC-303
AC Adapter 1 (AU)	Brand Name	Motorola(Salom)	Model Name	MC-305
AC Adapter 1 (AR)	Brand Name	Motorola(Salom)	Model Name	MC-306
AC Adapter 1 (BR)	Brand Name	Motorola(Salom)	Model Name	MC-307
AC Adapter 2 (IN)	Brand Name	Motorola(Acbel)	Model Name	MC-304
Battery 1	Brand Name	Motorola(Sunwoda)	Model Name	PV50
Battery 2	Brand Name	Motorola(SCUD)	Model Name	PV50
Earphone	Brand Name	Motorola(Juwei)	Model Name	MH202
USB Cable 1	Brand Name	Motorola(Saibao)	Model Name	SC18D13215
USB Cable 2	Brand Name	Motorola(Cabletech)	Model Name	SC18D13216
USB Cable 3	Brand Name	Motorola(Luxshare)	Model Name	SC18D13217



1.7 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	TH01-KS	CN1257	314309

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-SZ DFS01-SZ	CN1256	421272

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City Guangdong Province China 518103 TEL: +86-755-33202398		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH01-SZ	CN1256	421272

1.8 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH01-SZ	AUDIX	E3	6.2009-8-24
2.	CO01-SZ	AUDIX	E3	6.120613b



1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5180-5240 MHz U-NII-1	36	5180	44	5220
	38*	5190	46*	5230
	40	5200	48	5240
	42 [#]	5210		

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5260-5320 MHz U-NII-2A	52	5260	60	5300
	54*	5270	62*	5310
	56	5280	64	5320
	58 [#]	5290		

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5500-5720MHz U-NII-2C	100	5500	112	5560
	102*	5510	116	5580
	104	5520	132	5660
	106 [#]	5530	134*	5670
	108	5540	136	5680
	110*	5550	140	5700

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5745-5825 MHz U-NII-3	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155 [#]	5775	165	5825



Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
TDWR Channel	118*	5590	124	5620
	120	5600	126*	5630
	122 [#]	5610	128	5640

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
Straddle Channel	138 [#]	5690	144	5720
	142*	5710		

Note:

1. The above Frequency and Channel in "*" were 802.11n HT40 and 802.11ac VHT40.
2. The above Frequency and Channel in "[#]" were 802.11ac VHT80.

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0

AC Conducted Emission	Mode 1 : GSM850 Idle + Bluetooth Link + WLAN(5G)Link + USB Cable 3(Charging from Adapter 1) +Earphone
------------------------------	---

Simultaneous transmission
802.11a CH64(5320MHz)+ LTE Band 13 Link

Remark:

1. For Radiated Test Cases, The tests were performance with Adapter 2, Earphone and USB Cable 3.
2. The Co-location mode is assessed from the worst of WLAN TX + WWAN Link mode.




Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		5180-5240 MHz	5260-5320 MHz	5500-5720MHz	5745-5825 MHz
		802.11a	802.11a	802.11a	802.11a
L	Low	36	52	100	149
M	Middle	44	60	116	157
H	High	48	64	140	165
Straddle		-	-	144	-

Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		5180-5240 MHz	5260-5320 MHz	5500-5720MHz	5745-5825 MHz
		802.11n HT20	802.11n HT20	802.11n HT20	802.11n HT20
L	Low	36	52	100	149
M	Middle	44	60	116	157
H	High	48	64	140	165
Straddle		-	-	144	-

Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		5180-5240 MHz	5260-5320 MHz	5500-5720MHz	5745-5825 MHz
		802.11n HT40	802.11n HT40	802.11n HT40	802.11n HT40
L	Low	38	54	102	151
M	Middle	-	-	110	-
H	High	46	62	134	159
Straddle		-	-	142	-

Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		5180-5240 MHz	5260-5320 MHz	5500-5720MHz	5745-5825 MHz
		802.11ac VHT80	802.11ac VHT80	802.11ac VHT80	802.11ac VHT80
L	Low	-	-	106	-
M	Middle	42	58	122	155
H	High	-	-	-	-
Straddle		-	-	138	-

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Base Station(LTE)	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	WLAN AP	Dlink	DIR-820L	KA2IR820LA1	N/A	Unshielded,1.8m
3.	Bluetooth Earphone	Samsung	EO-MG900	PYAHS-107W	N/A	N/A



2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 6.75 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 6.75 + 10 = 16.75 \text{ (dB)} \end{aligned}$$



3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.

3.1.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

- The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

<input checked="" type="checkbox"/>	Section C) Bandwidth Measurement 1. Emission Bandwidth (EBW) and 99% OBW
	<ol style="list-style-type: none"> Set RBW = approximately 1% of the emission bandwidth. Set the VBW > RBW. Detector = Peak. Trace mode = max hold Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set to 1%~5% of the OBW and set the Video bandwidth (VBW) ≥ 3 * RBW. Measure and record the results in the test report.
<input checked="" type="checkbox"/>	Section C) Bandwidth Measurement 2. Minimum Emission Bandwidth for the band 5.725 - 5.85 GHz
	<ol style="list-style-type: none"> Set RBW = 100kHz. Set the VBW ≥ 3 x RBW. Detector = Peak. Trace mode = max hold Measure the maximum width of the emission that is 6 dB down from the peak of the emission. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.



3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW.

For the 5.25–5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz.

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note that U-NII-2 band, devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures


The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band.

For the 5.25–5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.



3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04.
Section F) Maximum power spectral density.

For devices operating in the bands 5.15 - 5.25 GHz, 5.25 - 5.35 GHz, and 5.47 - 5.725 GHz

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz.
- Set VBW \geq 3 MHz.
- Number of points in sweep \geq 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.


For devices operating in the band 5.725 - 5.85 GHz

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
 - Set span to encompass the entire emission bandwidth (EBW) of the signal.
 - Set RBW = 500KHz
 - Set VBW \geq 2MHz.
 - Number of points in sweep \geq 2 Span / RBW.
 - Sweep time = auto.
 - Detector = RMS
 - Trace average at least 100 traces in power averaging mode.
 - Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.
1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
 2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Unwanted Emissions Measurement

This section as specified in FCC Part 15.407(b) is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement. The unwanted emissions shall comply with 15.407(b)(1) to (6), and restricted bands per FCC Part 15.205.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27dBm/MHz .

For transmitters operating in the 5250-5350 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27 dBm/MHz . Devices operating in the 5250-5350 MHz band that generate emissions in the 5150-5250 MHz band must meet all applicable technical requirements for operation in the 5150-5250 MHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5150-5250 MHz band.

For transmitters operating in the 5470-5600 MHz and 5650-5725MHz band: all emissions outside of the 5470-5600 MHz and 5650-5725MHz band shall not exceed an EIRP of -27 dBm/MHz .

- (2) For transmitters operating in the 5.725-5.85 GHz band:
15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(3) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

(4) EIRP (dBm)	Field Strength at 3m (dBµV/m)
- 27	68.2

Note: The following formula is used to convert the EIRP to field strength.

$$EIRP = E_{Meas} + 20\log (d_{Meas}) - 104.7$$

where

EIRP is the equivalent isotropically radiated power, in dBm

E_{Meas} is the field strength of the emission at the measurement distance, in dBµV/m

d_{Meas} is the measurement distance, in m

(4) ANSI C63.10-2013 clause 12.7.3 note 97

As specified by regulatory requirements, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit. However, an out-of-band emission that complies with both the average and peak general regulatory limits is not required to satisfy the peak emission limit.

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.4.3 Test Procedures


1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04. Section G) Unwanted emissions measurement.
 - (1) Procedure for Unwanted Emissions Measurements Below 1000MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold
 - (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW \geq 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold
 - (3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW \geq 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in Peak mode also complies with the average limit), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.4.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.4.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix C.



3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBµV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.6 Antenna Requirements

3.6.1 Standard Applicable

According to FCC 47 CFR Section 15.407(a)(1)(2), if transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.6.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 12, 2022	Oct. 24, 2022~ Nov. 01, 2022	Oct. 11, 2023	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 05, 2022	Oct. 24, 2022~ Nov. 01, 2022	Jan. 04, 2023	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 05, 2022	Oct. 24, 2022~ Nov. 01, 2022	Jan. 04, 2023	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 15, 2022	Oct. 24, 2022~ Nov. 01, 2022	Jul. 14, 2023	Conducted (TH01-KS)
EMI Test Receiver&SA	Agilent	N9038A	MY52260185	20Hz~26.5GHz	Dec. 27, 2021	Nov. 05, 2022	Dec. 26, 2022	Radiation (03CH01-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 07, 2022	Nov. 05, 2022	Jul. 06, 2023	Radiation (03CH01-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	Jul. 28, 2022	Nov. 05, 2022	Jun. 27, 2024	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz~2GHz	Sep. 28, 2021	Nov. 05, 2022	Sep. 27, 2023	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Jul. 07, 2022	Nov. 05, 2022	Jul. 06, 2023	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Apr. 10, 2022	Nov. 05, 2022	Apr. 09, 2023	Radiation (03CH01-SZ)
LF Amplifier	Burgeon	BPA-530	102209	0.01~3000Mhz	Apr. 06, 2022	Nov. 05, 2022	Apr. 05, 2023	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	AMF-7D-0010 1800-30-10P-R	1943528	1GHz~18GHz	Oct. 19, 2022	Nov. 05, 2022	Oct. 18, 2023	Radiation (03CH01-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270105	0.5GHz~26.5GHz	Oct. 19, 2022	Nov. 05, 2022	Oct. 18, 2023	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 06, 2022	Nov. 05, 2022	Jul. 05, 2023	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	Nov. 09, 2021	Nov. 05, 2022	Nov. 08, 2022	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Nov. 05, 2022	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Nov. 05, 2022	NCR	Radiation (03CH01-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Jul. 07, 2022	Nov. 04, 2022	Jul. 06, 2023	Conduction (CO01-SZ)
AC LISN	R&S	ENV216	100063	9kHz~30MHz	Sep. 15, 2022	Nov. 04, 2022	Sep. 14, 2023	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	EMCO	3816/2SH	00103892	9kHz~30MHz	Oct. 17, 2022	Nov. 04, 2022	Oct. 16, 2023	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 07, 2022	Nov. 04, 2022	Jul. 06, 2023	Conduction (CO01-SZ)

NCR: No Calibration Required



5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Power	±0.46 dB
Conducted Emissions	±0.48 dB
Occupied Channel Bandwidth	±0.1 %
Conducted Power Spectral Density	±0.40 dB

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.2dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.2dB
---	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.3dB
---	-------



Appendix A. Conducted Test Results

Report Number : FR2O0909E

Test Engineer:	Long Wu	Temperature:	21~25	°C
Test Date:	2022/10/24~2022/11/01	Relative Humidity:	51~54	%

TEST RESULTS DATA
Average Power Table

U-NII-1										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)		Pass/Fail
11a	6Mbps	1	36	5180	0.11	15.86	24.00	-6.40		Pass
11a	6Mbps	1	44	5220	0.11	17.29	24.00	-6.40		Pass
11a	6Mbps	1	48	5240	0.11	17.24	24.00	-6.40		Pass
HT20	MCS0	1	36	5180	0.12	15.37	24.00	-6.40		Pass
HT20	MCS0	1	44	5220	0.12	16.94	24.00	-6.40		Pass
HT20	MCS0	1	48	5240	0.12	17.01	24.00	-6.40		Pass
HT40	MCS0	1	38	5190	0.24	12.61	24.00	-6.40		Pass
HT40	MCS0	1	46	5230	0.24	17.32	24.00	-6.40		Pass
VHT20	MCS0	1	36	5180	0.12	14.80	24.00	-6.40		Pass
VHT20	MCS0	1	44	5220	0.12	14.90	24.00	-6.40		Pass
VHT20	MCS0	1	48	5240	0.12	14.92	24.00	-6.40		Pass
VHT40	MCS0	1	38	5190	0.24	12.55	24.00	-6.40		Pass
VHT40	MCS0	1	46	5230	0.24	15.30	24.00	-6.40		Pass
VHT80	MCS0	1	42	5210	0.46	10.64	24.00	-6.40		Pass

TEST RESULTS DATA
Average Power Table

FCC U-NII-2A										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail
11a	6M bps	1	52	5260	0.11	17.50	23.98	-6.80	26.99	Pass
11a	6M bps	1	60	5300	0.11	17.57	23.98	-6.80	26.99	Pass
11a	6M bps	1	64	5320	0.11	16.18	23.98	-6.80	26.99	Pass
HT20	MCS 0	1	52	5260	0.12	17.21	23.98	-6.80	26.99	Pass
HT20	MCS 0	1	60	5300	0.12	17.32	23.98	-6.80	26.99	Pass
HT20	MCS 0	1	64	5320	0.12	15.85	23.98	-6.80	26.99	Pass
HT40	MCS 0	1	54	5270	0.24	17.46	23.98	-6.80	26.99	Pass
HT40	MCS 0	1	62	5310	0.24	13.10	23.98	-6.80	26.99	Pass
VHT20	MCS 0	1	52	5260	0.12	15.29	23.98	-6.80	26.99	Pass
VHT20	MCS 0	1	60	5300	0.12	15.28	23.98	-6.80	26.99	Pass
VHT20	MCS 0	1	64	5320	0.12	15.28	23.98	-6.80	26.99	Pass
VHT40	MCS 0	1	54	5270	0.24	15.42	23.98	-6.80	26.99	Pass
VHT40	MCS 0	1	62	5310	0.24	12.98	23.98	-6.80	26.99	Pass
VHT80	MCS 0	1	58	5290	0.46	10.93	23.98	-6.80	26.99	Pass

TEST RESULTS DATA
Average Power Table

FCC U-NII-2C										
Mod.	Data Rate	Ntx	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail
11a	6M bps	1	100	5500	0.11	15.84	23.98	-6.70	26.99	Pass
11a	6M bps	1	116	5580	0.11	17.40	23.98	-6.70	26.99	Pass
11a	6M bps	1	140	5700	0.11	15.48	23.98	-6.70	26.99	Pass
11a	6Mbps	1	144	5720	0.11	17.58	23.98	-6.70	26.99	Pass
HT20	MCS 0	1	100	5500	0.12	14.15	23.98	-6.70	26.99	Pass
HT20	MCS0	1	104	5520	0.12	17.24	23.98	-6.70	26.99	Pass
HT20	MCS0	1	116	5580	0.12	17.41	23.98	-6.70	26.99	Pass
HT20	MCS 0	1	136	5680	0.12	17.16	23.98	-6.70	26.99	Pass
HT20	MCS 0	1	140	5700	0.12	13.74	23.98	-6.70	26.99	Pass
HT20	MCS0	1	144	5720	0.12	17.24	23.98	-6.70	26.99	Pass
HT40	MCS 0	1	102	5510	0.24	12.09	23.98	-6.70	26.99	Pass
HT40	MCS 0	1	110	5550	0.24	17.42	23.98	-6.70	26.99	Pass
HT40	MCS 0	1	126	5630	0.24	17.50	23.98	-6.70	26.99	Pass
HT40	MCS 0	1	134	5670	0.24	14.43	23.98	-6.70	26.99	Pass
HT40	MCS0	1	142	5710	0.24	17.39	23.98	-6.70	26.99	Pass
VHT20	MCS 0	1	100	5500	0.12	14.07	23.98	-6.70	26.99	Pass
VHT20	MCS 0	1	116	5580	0.12	15.48	23.98	-6.70	26.99	Pass
VHT20	MCS 0	1	140	5700	0.12	13.68	23.98	-6.70	26.99	Pass
VHT20	MCS0	1	144	5720	0.12	15.24	23.98	-6.70	26.99	Pass
VHT40	MCS 0	1	102	5510	0.24	12.03	23.98	-6.70	26.99	Pass
VHT40	MCS 0	1	110	5550	0.24	15.43	23.98	-6.70	26.99	Pass
VHT40	MCS 0	1	134	5670	0.24	14.37	23.98	-6.70	26.99	Pass
VHT40	MCS0	1	142	5710	0.24	15.46	23.98	-6.70	26.99	Pass
VHT80	MCS 0	1	106	5530	0.46	10.60	23.98	-6.70	26.99	Pass
VHT80	MCS 0	1	122	5610	0.46	14.97	23.98	-6.70	26.99	Pass
VHT80	MCS0	1	138	5690	0.46	15.58	23.98	-6.70	26.99	Pass

TEST RESULTS DATA
Average Power Table

U-NII-3										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)		Pass/Fail
11a	6M bps	1	149	5745	0.11	16.84	30.00	-7.80		Pass
11a	6Mbps	1	157	5785	0.11	16.83	30.00	-7.80		Pass
11a	6Mbps	1	165	5825	0.11	16.66	30.00	-7.80		Pass
HT20	MCS 0	1	149	5745	0.12	16.64	30.00	-7.80		Pass
HT20	MCS 0	1	157	5785	0.12	16.60	30.00	-7.80		Pass
HT20	MCS 0	1	165	5825	0.12	16.60	30.00	-7.80		Pass
HT40	MCS 0	1	151	5755	0.24	16.78	30.00	-7.80		Pass
HT40	MCS 0	1	159	5795	0.24	16.74	30.00	-7.80		Pass
VHT20	MCS 0	1	149	5745	0.12	14.63	30.00	-7.80		Pass
VHT20	MCS 0	1	157	5785	0.12	14.65	30.00	-7.80		Pass
VHT20	MCS 0	1	165	5825	0.12	14.69	30.00	-7.80		Pass
VHT40	MCS 0	1	151	5755	0.24	14.75	30.00	-7.80		Pass
VHT40	MCS 0	1	159	5795	0.24	14.81	30.00	-7.80		Pass
VHT80	MCS 0	1	155	5775	0.46	14.83	30.00	-7.80		Pass



Ambient Condition: 25 °C, 45 %RH

According Standard: Part15E

Test Date: 2022.10.24~2022.11.01

Test Engineer: Long Wu

Emission Bandwidth

Test Result


TestMode	Antenna	Freq(MHz)	26dB EBW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11A	Ant1	5180	24.32	5168.28	5192.60	---	---
		5220	26.96	5206.80	5233.76	---	---
		5240	24.84	5228.88	5253.72	---	---
		5260	26.88	5245.60	5272.48	---	---
		5300	23.80	5288.36	5312.16	---	---
		5320	23.92	5308.68	5332.60	---	---
		5500	25.00	5487.76	5512.76	---	---
		5580	25.68	5567.40	5593.08	---	---
		5700	27.56	5686.28	5713.84	---	---
		5720	28.80	5705.88	5734.68	---	---
		5745	27.64	5731.88	5759.52	---	---
		5785	28.96	5771.48	5800.44	---	---
		5825	27.80	5810.44	5838.24	---	---
11N20SISO	Ant1	5180	27.12	5165.88	5193.00	---	---
		5220	26.04	5207.28	5233.32	---	---
		5240	25.04	5227.44	5252.48	---	---
		5260	25.72	5247.12	5272.84	---	---
		5300	25.48	5288.28	5313.76	---	---
		5320	25.88	5308.00	5333.88	---	---
		5500	25.00	5487.40	5512.40	---	---
		5520	25.08	5507.44	5532.52	---	---
		5580	25.92	5566.84	5592.76	---	---
		5680	26.92	5666.28	5693.20	---	---
		5700	28.32	5685.60	5713.92	---	---
		5720	27.84	5706.56	5734.40	---	---
		5745	25.60	5732.24	5757.84	---	---
		5785	27.36	5771.24	5798.60	---	---
5825	27.88	5811.20	5839.08	---	---		



11N40SISO	Ant1	5190	70.16	5153.76	5223.92	---	---
		5230	72.00	5192.88	5264.88	---	---
		5270	66.64	5237.52	5304.16	---	---
		5310	67.36	5277.04	5344.40	---	---
		5510	67.84	5477.60	5545.44	---	---
		5550	68.64	5517.76	5586.40	---	---
		5630	70.80	5596.00	5666.80	---	---
		5670	73.20	5634.08	5707.28	---	---
		5710	69.60	5674.64	5744.24	---	---
		5755	69.04	5719.40	5788.44	---	---
		5795	70.08	5758.44	5828.52	---	---
11AC80SISO	Ant1	5210	87.20	5169.84	5257.04	---	---
		5290	109.12	5235.60	5344.72	---	---
		5530	112.00	5481.20	5593.20	---	---
		5610	104.00	5562.80	5666.80	---	---
		5690	132.16	5626.96	5759.12	---	---
		5775	121.76	5708.92	5830.68	---	---




Test Graphs







11A_Ant1_5240




11A_Ant1_5260








11A_Ant1_5500




Date: 24.OCT.2022 23:56:00

11A_Ant1_5580




Date: 24.OCT.2022 23:57:00



11A_Ant1_5720





11A_Ant1_5745



11A_Ant1_5785





11N20SISO_Ant1_5180






11N20SISO_Ant1_5260




Date: 25.OCT.2022 00:10:04

11N20SISO_Ant1_5300




Date: 25.OCT.2022 00:11:04






11N20SISO_Ant1_5520




11N20SISO_Ant1_5580








11N20SISO_Ant1_5680




11N20SISO_Ant1_5700















11N40SISO_Ant1_5270





11N40SISO_Ant1_5310
















11AC80SISO_Ant1_5210




11AC80SISO_Ant1_5290








11AC80SISO_Ant1_5690



11AC80SISO_Ant1_5775





Occupied channel bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11A	Ant1	5180	17.742	5171.1688	5188.9111	---	---
		5220	17.782	5211.0889	5228.8711	---	---
		5240	17.742	5231.2088	5248.9510	---	---
		5260	17.702	5251.1289	5268.8312	---	---
		5300	17.702	5291.1688	5308.8711	---	---
		5320	17.742	5311.2088	5328.9510	---	---
		5500	17.782	5491.0889	5508.8711	---	---
		5580	17.782	5571.1688	5588.9510	---	---
		5700	18.302	5690.8492	5709.1508	---	---
		5720	18.102	5710.9690	5729.0709	---	---
		5745	17.902	5736.0889	5753.9910	---	---
		5785	18.142	5775.8891	5794.0310	---	---
		5825	18.182	5815.8492	5834.0310	---	---
		11N20SISO	Ant1	5180	18.781	5170.6094	5189.3906
5220	18.701			5210.6094	5229.3107	---	---
5240	18.621			5230.7293	5249.3506	---	---
5260	18.661			5250.6094	5269.2707	---	---
5300	18.621			5290.6893	5309.3107	---	---
5320	18.661			5310.6893	5329.3506	---	---
5500	18.661			5490.6094	5509.2707	---	---
5520	18.701			5510.6494	5529.3506	---	---
5580	18.661			5570.6893	5589.3506	---	---
5680	18.901			5670.4895	5689.3906	---	---
5700	18.941			5690.5295	5709.4705	---	---
5720	18.861			5710.5295	5729.3906	---	---
5745	18.701			5735.6494	5754.3506	---	---
5785	18.901			5775.4496	5794.3506	---	---
5825	18.901	5815.4496	5834.3506	---	---		



11N40SISO	Ant1	5190	37.243	5171.4585	5208.7013	---	---
		5230	37.483	5211.2987	5248.7812	---	---
		5270	37.483	5251.2188	5288.7013	---	---
		5310	37.403	5291.3786	5328.7812	---	---
		5510	37.003	5491.5385	5528.5415	---	---
		5550	37.083	5531.6184	5568.7013	---	---
		5630	37.483	5611.2987	5648.7812	---	---
		5670	37.562	5651.2188	5688.7812	---	---
		5710	37.642	5691.2188	5728.8611	---	---
		5755	37.323	5736.2987	5773.6214	---	---
		5795	37.483	5776.0589	5813.5415	---	---
11AC80SISO	Ant1	5210	75.764	5172.2777	5248.0420	---	---
		5290	75.924	5252.1179	5328.0420	---	---
		5530	75.924	5492.1179	5568.0420	---	---
		5610	75.924	5572.1179	5648.0420	---	---
		5690	76.404	5651.7982	5728.2018	---	---
		5775	75.924	5736.7982	5812.7223	---	---



Test Graphs

