



FCC RF Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT2323-1
FCC ID : IHDT56AL8
STANDARD : 47 CFR Part 2, 22(H), 24(E), 27(L)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S) : Apr. 23, 2023 ~ May 06, 2023

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant..... 5

 1.2 Manufacturer 5

 1.3 Product Feature of Equipment Under Test 5

 1.4 Product Specification of Equipment Under Test 6

 1.5 Modification of EUT 7

 1.6 Maximum ERP/EIRP Power, and Emission Designator 7

 1.7 Testing Location 8

 1.8 Test Software 8

 1.9 Applicable Standards 8

 1.10 Specification of Accessory 9

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 10

 2.1 Test Mode..... 10

 2.2 Connection Diagram of Test System 11

 2.3 Support Unit used in test configuration 11

 2.4 Measurement Results Explanation Example 11

 2.5 Frequency List of Low/Middle/High Channels..... 12

3 CONDUCTED TEST RESULT..... 13

 3.1 Measuring Instruments..... 13

 3.2 Test Setup 13

 3.3 Test Result of Conducted Test..... 13

 3.4 Conducted Output Power and ERP/EIRP 14

 3.5 Peak-to-Average Ratio 15

 3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement..... 16

 3.7 Conducted Band Edge 17

 3.8 Conducted Spurious Emission 18

 3.9 Frequency Stability..... 19

4 RADIATED TEST ITEMS 20

 4.1 Measuring Instruments..... 20

 4.2 Test Setup 20

 4.3 Test Result of Radiated Test..... 21

 4.4 Field Strength of Spurious Radiation Measurement 22

5 LIST OF MEASURING EQUIPMENT 23

6 MEASUREMENT UNCERTAINTY 24

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. TEST SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG340401A	Rev. 01	Initial issue of report	May 31, 2023



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	-	Report Only	-
	§22.913(a)(5)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§2.1053 §22.917(a) §24.238(a) §27.53(h)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 25.86 dB at 5640.00 MHz

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Motorola Mobility LLC
222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC
222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2323-1
FCC ID	IHDT56AL8
IMEI Code	Conducted: 350492020025032/350492020025040 Radiation: 350492020024498/350492020024506
HW Version	DVT2
SW Version	T2TV33.16
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	<p>GSM/GPRS/EDGE: 850: 824 MHz ~ 849 MHz 1900: 1850MHz ~ 1910MHz</p> <p>WCDMA: Band V: 824 MHz ~ 849 MHz Band II: 1850 MHz ~ 1910 MHz Band IV: 1710 MHz ~ 1755 MHz</p>
Rx Frequency	<p>GSM/GPRS/EDGE: 850: 869 MHz ~ 894 MHz 1900: 1930 MHz ~ 1990 MHz</p> <p>WCDMA: Band V: 869 MHz ~ 894 MHz Band II: 1930 MHz ~ 1990 MHz Band IV: 2110 MHz ~ 2155 MHz</p>
Maximum Output Power to Antenna	<p>Ant 0: GSM 850: 32.85 dBm GSM 1900: 29.66 dBm WCDMA Band V: 24.23 dBm WCDMA Band II: 22.79 dBm WCDMA Band IV: 22.75 dBm</p> <p>Ant 1: GSM 850: 33.04 dBm GSM 1900: 29.39 dBm WCDMA Band V: 24.27 dBm WCDMA Band II: 22.41 dBm WCDMA Band IV: 22.38 dBm</p> <p>Ant 2: GSM 1900: 30.30 dBm WCDMA Band II: 23.13 dBm WCDMA Band IV: 22.97 dBm</p> <p>Ant 3: GSM 1900: 31.28 dBm WCDMA Band II: 23.95 dBm WCDMA Band IV: 23.83 dBm</p>
Antenna Type	<p>Ant 0: Monopole Antenna Ant 1/2/3: IFA Antenna</p>
Antenna Gain	<p>Ant 0: Cellular Band: -4.34 dBi PCS Band: -4.5 dBi AWS Band: -3.2 dBi</p> <p>Ant 1: Cellular Band: -3.3 dBi PCS Band: -3.3 dBi AWS Band: -3.1 dBi</p>



	Ant 2: PCS Band: -2.5 dBi AWS Band: -2.8 dBi Ant 3: PCS Band: -1.0 dBi AWS Band: -1.0 dBi
Type of Modulation	GSM/GPRS: GMSK EDGE: GMSK / 8PSK WCDMA : BPSK HSPA : QPSK HSPA+ : 16QAM (16QAM uplink is not supported) DC-HSDPA : 64QAM

Note:

1. The WWAN Antenna 0/1/2/3 only support Antenna switch function, not support MIMO.
2. The maximum ERP/EIRP is calculated from max output power and max antenna gain, only the maximum ERP/EIRP of Ant.1 for GSM850/WCDMA Band V, and Ant.3 for GSM1900/WCDMA Band IV/Band II are shown in the report.
3. The EUT has two working states, flip open state and flip close state, RSE pretest the two states and choose the worst flip open state to perform full test.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, and Emission Designator

FCC Rule	Frequency Band	Frequency Range (MHz)	Type of Modulation	Maximum ERP/EIRP (W)	Emission Designator
Part 22	GSM850 (GPRS)	824.2 ~ 848.8	GMSK	0.5741	241KGXW
Part 22	GSM850 (EDGE)	824.2 ~ 848.8	8PSK	0.0975	241KG7W
Part 22	WCDMA Band V	826.4 ~ 846.6	BPSK	0.0762	4M14F9W
Part 24	GSM1900 (GPRS)	1850.2 ~ 1909.8	GMSK	1.0666	244KGXW
Part 24	GSM1900 (EDGE)	1850.2 ~ 1909.8	8PSK	0.3715	246KG7W
Part 24	WCDMA Band II	1852.4 ~ 1907.6	BPSK	0.1972	4M15F9W
Part 27	WCDMA Band IV	1712.4 ~ 1752.6	BPSK	0.1919	4M15F9W



1.7 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH04-KS TH01-KS	CN1257	314309

1.8 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH04-KS	AUDIX	E3	6.2009-8-24al

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E), 27(L)
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



1.10 Specification of Accessory

Specification of Accessory				
AC Adapter 1(US)	Brand Name	Motorola(Acbel)	Model Name	MC-331
AC Adapter 1(EU)	Brand Name	Motorola(Acbel)	Model Name	MC-332
AC Adapter 1(UK)	Brand Name	Motorola(Acbel)	Model Name	MC-333
AC Adapter 2(US)	Brand Name	Motorola(Chenyang)	Model Name	MC-331
AC Adapter 2(EU)	Brand Name	Motorola(Chenyang)	Model Name	MC-332
AC Adapter 2(AU)	Brand Name	Motorola(Chenyang)	Model Name	MC-335
AC Adapter 2(AR)	Brand Name	Motorola(Chenyang)	Model Name	MC-336
AC Adapter 2(BR)	Brand Name	Motorola(Chenyang)	Model Name	MC-337
AC Adapter 3(US)	Brand Name	Motorola(Salcomp)	Model Name	MC-331
AC Adapter 3(EU)	Brand Name	Motorola(Salcomp)	Model Name	MC-332
AC Adapter 3(UK)	Brand Name	Motorola(Salcomp)	Model Name	MC-333
AC Adapter 3(IN)	Brand Name	Motorola(Salcomp)	Model Name	MC-334
AC Adapter 3(AU)	Brand Name	Motorola(Salcomp)	Model Name	MC-335
AC Adapter 3(AR)	Brand Name	Motorola(Salcomp)	Model Name	MC-336
AC Adapter 3(BR)	Brand Name	Motorola(Salcomp)	Model Name	MC-337
AC Adapter 3(CHILE)	Brand Name	Motorola(Salcomp)	Model Name	MC-339
AC Adapter 3(KR)	Brand Name	Motorola(Salcomp)	Model Name	MC-330
AC Adapter 4(BR)	Brand Name	Motorola(Cliptech)	Model Name	MC-337
Base Battery	Brand Name	Motorola (ATL)	Model Name	PM29
Flip Battery	Brand Name	Motorola (ATL)	Model Name	PV11
USB Cable 1	Brand Name	Motorola(Saibao)	Model Name	SC18D22297
USB Cable 2	Brand Name	Motorola(Cabletech)	Model Name	SC18D22298
USB Cable 3	Brand Name	Motorola(Luxshare)	Model Name	SC18D22299



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:


1. 30 MHz to 10th harmonic for GSM850 and WCDMA Band V.
2. 30 MHz to 10th harmonic for WCDMA Band IV.
3. 30 MHz to 10th harmonic for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	<ul style="list-style-type: none"> ■ GPRS 1 Tx slots Link ■ EDGE 1 Tx slots Link 	<ul style="list-style-type: none"> ■ GPRS 1 Tx slots Link ■ EDGE 1 Tx slots Link
GSM 1900	<ul style="list-style-type: none"> ■ GPRS 1 Tx slots Link ■ EDGE 1 Tx slots Link 	<ul style="list-style-type: none"> ■ GPRS 1 Tx slots Link ■ EDGE 1 Tx slots Link
WCDMA Band V	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link
WCDMA Band II	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link
WCDMA Band IV	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link

2.2 Connection Diagram of Test System



The EUT has been configuration operated in a manner tended to maximize its emission characteristics in a typical application.

2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	Base Station	Anritsu	MT8820/8821	Fcc DoC	N/A	Shielded, 1.5m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

$$\text{Offset} = \text{RF cable loss} + \text{attenuator factor}.$$

The following shows an offset computation example with RF cable loss 4.8 dB and a 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.8 + 10 = 14.8 \text{ (dB)} \end{aligned}$$



2.5 Frequency List of Low/Middle/High Channels

Frequency List				
Band	Channel/Frequency(MHz)	Lowest	Middle	Highest
GSM850	Channel	128	189	251
	Frequency	824.2	836.4	848.8
WCDMA Band V	Channel	4132	4182	4233
	Frequency	826.4	836.4	846.6
GSM1900	Channel	512	661	810
	Frequency	1850.2	1880.0	1909.8
WCDMA Band II	Channel	9262	9400	9538
	Frequency	1852.4	1880.0	1907.6
WCDMA Band IV	Channel	1312	1413	1513
	Frequency	1712.4	1732.6	1752.6

3 Conducted Test Result

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.



3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850 and WCDMA Band V.

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900 and WCDMA Band II.

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.



3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.



4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12. $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 12, 2022	Apr. 23, 2023~ Apr. 25, 2023	Oct. 11, 2023	Conducted (TH01-KS)
Power divider	STI	STI08-0055	-	0.5~40GHz	Aug. 26, 2022	Apr. 23, 2023~ Apr. 25, 2023	Aug. 25, 2023	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 15, 2022	Apr. 23, 2023~ Apr. 25, 2023	Jul. 14, 2023	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY57471079	10Hz-44G,MAX 30dB	Oct. 12, 2022	May 06, 2023	Oct. 11, 2023	Radiation (03CH04-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 16, 2022	May 06, 2023	Oct. 15, 2023	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz-1GHz	May 24, 2022	May 06, 2023	May 23, 2023	Radiation (03CH04-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	1284	1GHz~18GHz	Oct. 16, 2022	May 06, 2023	Oct. 15, 2023	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 08, 2023	May 06, 2023	Jan. 07, 2024	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	May 24, 2022	May 06, 2023	May 23, 2023	Radiation (03CH04-KS)
Amplifier	MITEQ	EM18G40G GA	060728	18~40GHz	Jan. 05, 2023	May 06, 2023	Jan. 04, 2024	Radiation (03CH04-KS)
high gain Amplifier	EM	EM01G18G A	060840	1Ghz-18Ghz	Oct. 12, 2022	May 06, 2023	Oct. 11, 2023	Radiation (03CH04-KS)
Amplifier	Agilent	8449B	3008A02370	1Ghz-18Ghz	Oct. 12, 2022	May 06, 2023	Oct. 11, 2023	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	May 06, 2023	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	May 06, 2023	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	May 06, 2023	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required



6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Power	±0.46 dB
Conducted Emissions	±0.48 dB
Occupied Channel Bandwidth	±0.1 %

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.82dB
---	--------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.56dB
---	--------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.54dB
---	--------

----- THE END -----



Appendix A. Test Results of Conducted Test

Test Engineer :	Simle Wang	Temperature :	22~23°C
		Relative Humidity :	40~42%

Conducted Output Power(Average power) and ERP/EIRP

GSM850-Ant 1 TX Channel	Burst Average Power (dBm)			ERP(W)		
	128	189	251	L	M	H
Frequency (MHz)	824.2	836.4	848.8			
GSM 1 Tx slot	32.93	32.97	32.89	0.5598	0.5649	0.5546
GPRS 1 Tx slot	32.96	33.04	32.91	0.5636	0.5741	0.5572
GPRS 2 Tx slots	29.45	29.51	29.39	0.2512	0.2547	0.2477
GPRS 3 Tx slots	27.75	27.78	27.69	0.1698	0.1710	0.1675
GPRS 4 Tx slots	26.12	26.29	26.13	0.1167	0.1213	0.1169
EDGE 1 Tx slot	25.21	25.34	25.33	0.0946	0.0975	0.0973
EDGE 2 Tx slots	23.59	23.68	23.62	0.0652	0.0665	0.0656
EDGE 3 Tx slots	22.40	22.47	22.37	0.0495	0.0504	0.0492
EDGE 4 Tx slots	20.19	20.34	20.24	0.0298	0.0308	0.0301

GSM1900-Ant 3 TX Channel	Burst Average Power (dBm)			EIRP(W)		
	512	661	810	L	M	H
Frequency (MHz)	1850.2	1880	1909.8			
GSM 1 Tx slot	31.20	31.21	31.04	1.0471	1.0495	1.0093
GPRS 1 Tx slot	31.23	31.28	31.09	1.0544	1.0666	1.0209
GPRS 2 Tx slots	28.85	28.94	28.93	0.6095	0.6223	0.6209
GPRS 3 Tx slots	27.36	27.47	27.30	0.4325	0.4436	0.4266
GPRS 4 Tx slots	24.88	25.02	24.98	0.2443	0.2523	0.2500
EDGE 1 Tx slot	26.66	26.70	26.53	0.3681	0.3715	0.3573
EDGE 2 Tx slots	24.74	24.81	24.79	0.2366	0.2404	0.2393
EDGE 3 Tx slots	23.43	23.53	23.47	0.1750	0.1791	0.1766
EDGE 4 Tx slots	21.55	21.61	21.42	0.1135	0.1151	0.1102



Band		WCDMA V-Ant 1			ERP(W)		
TX Channel		4132	4182	4233			
Rx Channel		4357	4407	4458			
Frequency (MHz)		826.4	836.4	846.6	L	M	H
3GPP Rel 99	AMR 12.2Kbps	24.10	24.16	24.05	0.0733	0.0743	0.0724
3GPP Rel 99	RMC 12.2Kbps	24.22	24.27	24.18	0.0753	0.0762	0.0746
3GPP Rel 6	HSDPA Subtest-1	23.19	23.25	22.98	0.0594	0.0603	0.0566
3GPP Rel 6	HSDPA Subtest-2	23.05	23.17	23.26	0.0575	0.0592	0.0604
3GPP Rel 6	HSDPA Subtest-3	22.82	22.69	22.67	0.0546	0.0530	0.0527
3GPP Rel 6	HSDPA Subtest-4	22.59	22.65	22.61	0.0518	0.0525	0.0520
3GPP Rel 8	DC-HSDPA Subtest-1	23.14	23.31	23.08	0.0587	0.0611	0.0579
3GPP Rel 8	DC-HSDPA Subtest-2	23.11	23.31	23.19	0.0583	0.0611	0.0594
3GPP Rel 8	DC-HSDPA Subtest-3	22.61	22.71	22.65	0.0520	0.0532	0.0525
3GPP Rel 8	DC-HSDPA Subtest-4	22.65	22.69	22.59	0.0525	0.0530	0.0518
3GPP Rel 6	HSUPA Subtest-1	23.08	23.10	23.23	0.0579	0.0582	0.0600
3GPP Rel 6	HSUPA Subtest-2	21.21	21.16	21.27	0.0377	0.0372	0.0382
3GPP Rel 6	HSUPA Subtest-3	22.15	22.09	22.11	0.0468	0.0461	0.0463
3GPP Rel 6	HSUPA Subtest-4	21.15	21.22	21.06	0.0372	0.0378	0.0364
3GPP Rel 6	HSUPA Subtest-5	22.95	23.20	23.04	0.0562	0.0596	0.0574

Band		WCDMA IV-Ant 3			EIRP(W)		
TX Channel		1312	1413	1513			
Rx Channel		1537	1638	1738			
Frequency (MHz)		1712.4	1732.6	1752.6	L	M	H
3GPP Rel 99	AMR 12.2Kbps	23.76	23.81	23.76	0.1888	0.1910	0.1888
3GPP Rel 99	RMC 12.2Kbps	23.68	23.83	23.71	0.1854	0.1919	0.1866
3GPP Rel 6	HSDPA Subtest-1	22.90	22.96	22.93	0.1549	0.1570	0.1560
3GPP Rel 6	HSDPA Subtest-2	22.97	23.31	23.09	0.1574	0.1702	0.1618
3GPP Rel 6	HSDPA Subtest-3	22.82	22.84	22.71	0.1521	0.1528	0.1483
3GPP Rel 6	HSDPA Subtest-4	22.77	22.75	22.54	0.1503	0.1496	0.1426
3GPP Rel 8	DC-HSDPA Subtest-1	22.99	23.22	22.84	0.1581	0.1667	0.1528
3GPP Rel 8	DC-HSDPA Subtest-2	23.09	23.37	23.02	0.1618	0.1726	0.1592
3GPP Rel 8	DC-HSDPA Subtest-3	22.30	22.64	22.53	0.1349	0.1459	0.1422
3GPP Rel 8	DC-HSDPA Subtest-4	22.71	22.49	22.61	0.1483	0.1409	0.1449
3GPP Rel 6	HSUPA Subtest-1	22.84	23.23	22.97	0.1528	0.1671	0.1574
3GPP Rel 6	HSUPA Subtest-2	20.99	21.15	21.21	0.0998	0.1035	0.1050
3GPP Rel 6	HSUPA Subtest-3	22.18	22.27	21.91	0.1312	0.1340	0.1233
3GPP Rel 6	HSUPA Subtest-4	20.95	21.22	20.97	0.0989	0.1052	0.0993
3GPP Rel 6	HSUPA Subtest-5	23.08	22.96	22.85	0.1614	0.1570	0.1531



Band		WCDMA II-Ant 3			EIRP(W)		
TX Channel		9262	9400	9538			
Rx Channel		9662	9800	9938			
Frequency (MHz)		1852.4	1880	1907.6	L	M	H
3GPP Rel 99	AMR 12.2Kbps	23.84	23.90	23.83	0.1923	0.1950	0.1919
3GPP Rel 99	RMC 12.2Kbps	23.87	23.95	23.81	0.1936	0.1972	0.1910
3GPP Rel 6	HSDPA Subtest-1	23.01	23.02	23.01	0.1589	0.1592	0.1589
3GPP Rel 6	HSDPA Subtest-2	23.03	23.13	22.93	0.1596	0.1633	0.1560
3GPP Rel 6	HSDPA Subtest-3	22.63	22.89	22.63	0.1455	0.1545	0.1455
3GPP Rel 6	HSDPA Subtest-4	22.57	22.81	22.45	0.1435	0.1517	0.1396
3GPP Rel 8	DC-HSDPA Subtest-1	23.11	23.30	22.90	0.1626	0.1698	0.1549
3GPP Rel 8	DC-HSDPA Subtest-2	23.19	23.24	23.12	0.1656	0.1675	0.1629
3GPP Rel 8	DC-HSDPA Subtest-3	22.39	22.69	22.57	0.1377	0.1476	0.1435
3GPP Rel 8	DC-HSDPA Subtest-4	22.63	22.51	22.47	0.1455	0.1416	0.1403
3GPP Rel 6	HSUPA Subtest-1	22.84	23.30	23.14	0.1528	0.1698	0.1637
3GPP Rel 6	HSUPA Subtest-2	20.92	21.07	21.11	0.0982	0.1016	0.1026
3GPP Rel 6	HSUPA Subtest-3	22.09	22.09	21.95	0.1285	0.1285	0.1245
3GPP Rel 6	HSUPA Subtest-4	20.88	21.23	20.97	0.0973	0.1054	0.0993
3GPP Rel 6	HSUPA Subtest-5	23.05	22.97	22.98	0.1603	0.1574	0.1578



A1. GSM

Peak-to-Average Ratio


Mode	GSM850		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.12	3.42	PASS
Middle CH	0.14	3.30	
Highest CH	0.12	3.71	

Mode	GSM1900		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.14	3.48	PASS
Middle CH	0.17	3.36	
Highest CH	0.20	3.83	



GSM850 (GSM)


Lowest Channel



Date: 25.APR.2023 03:04:28


GSM850 (EDGE class 8)

Lowest Channel




Date: 25.APR.2023 18:48:37

Middle Channel




Date: 25.APR.2023 03:04:56

Middle Channel



Date: 25.APR.2023 18:48:54

Highest Channel




Date: 25.APR.2023 03:05:20

Highest Channel



Date: 25.APR.2023 18:49:09





26dB Bandwidth


Mode	GSM850 (MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.312	0.311
Middle CH	0.314	0.305
Highest CH	0.312	0.315

Mode	GSM1900 (MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.313	0.310
Middle CH	0.312	0.313
Highest CH	0.314	0.314



GSM850 (GSM)


Lowest Channel



Date: 25-APR-2023 02:46:29


GSM850 (EDGE class 8)

Lowest Channel




Date: 25-APR-2023 18:29:23

Middle Channel




Date: 25-APR-2023 02:46:53

Middle Channel




Date: 25-APR-2023 18:29:58

Highest Channel



Date: 25-APR-2023 02:47:19

Highest Channel




Date: 25-APR-2023 18:30:21



GSM1900 (GSM)


Lowest Channel



Date: 25-APR-2023 03:27:15


GSM1900 (EDGE class 8)

Lowest Channel




Date: 25-APR-2023 05:10:22

Middle Channel




Date: 25-APR-2023 03:27:37

Middle Channel




Date: 25-APR-2023 05:10:45

Highest Channel



Date: 25-APR-2023 03:28:00

Highest Channel



Date: 25-APR-2023 05:10:210



Occupied Bandwidth

Mode	GSM850 (MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.241	0.239
Middle CH	0.240	0.241
Highest CH	0.241	0.238

Mode	GSM1900 (MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.242	0.246
Middle CH	0.244	0.242
Highest CH	0.240	0.241



GSM850 (GSM)


Lowest Channel



Date: 25-APR-2023 02:39:28


GSM850 (EDGE class 8)

Lowest Channel




Date: 25-APR-2023 18:30:57

Middle Channel




Date: 25-APR-2023 02:40:05

Middle Channel




Date: 25-APR-2023 18:31:27

Highest Channel



Date: 25-APR-2023 02:40:34

Highest Channel




Date: 25-APR-2023 18:31:56



GSM1900 (GSM)


Lowest Channel



Date: 25.APR.2023 03:25:42


GSM1900 (EDGE class 8)

Lowest Channel




Date: 25.APR.2023 04:55:28

Middle Channel




Date: 25.APR.2023 03:26:08

Middle Channel




Date: 25.APR.2023 04:56:27

Highest Channel



Date: 25.APR.2023 03:26:31



Highest Channel



Date: 25.APR.2023 04:56:51



Conducted Band Edge







GSM1900 (GSM)

Lowest Band Edge

Highest Band Edge





Date: 25.APR.2023 03:29:55

Date: 25.APR.2023 03:31:55

GSM1900 (EDGE class 8)

Lowest Band Edge

Highest Band Edge




Date: 25.APR.2023 05:04:57

Date: 25.APR.2023 05:06:59




Conducted Spurious Emission





GSM1900 (GSM)


Lowest Channel



Date: 25.APR.2023 03:35:16


GSM1900 (EDGE class 8)

Lowest Channel




Date: 25.APR.2023 05:08:07

Middle Channel




Date: 25.APR.2023 03:36:58

Middle Channel




Date: 25.APR.2023 05:10:16

Highest Channel



Date: 25.APR.2023 03:38:43

Highest Channel



Date: 25.APR.2023 05:10:00



Frequency Stability

Test Conditions	Middle Channel	GSM850 (GSM)	GSM850 (EDGE class 8)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0049	0.0025	PASS
40	Normal Voltage	0.0512	0.0121	
30	Normal Voltage	0.0094	0.0535	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0545	0.0364	
0	Normal Voltage	0.0112	0.0578	
-10	Normal Voltage	0.0055	0.0425	
-20	Normal Voltage	0.0127	0.0177	
-30	Normal Voltage	0.0181	0.0469	
20	Maximum Voltage	0.0256	0.0624	
20	Normal Voltage	0.0351	0.0152	
20	Battery End Point	0.0378	0.0234	

Note:

1. Normal Voltage = 3.91V ; Battery End Point (BEP) =3.4V. ; Maximum Voltage =4.5V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



Test Conditions	Middle Channel	GSM1900 (GSM)	GSM1900 (EDGE class 8)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0021	0.0009	PASS
40	Normal Voltage	0.0055	0.0032	
30	Normal Voltage	0.0066	0.0076	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0178	0.0236	
0	Normal Voltage	0.0216	0.0165	
-10	Normal Voltage	0.0348	0.0039	
-20	Normal Voltage	0.0298	0.0034	
-30	Normal Voltage	0.0009	0.0254	
20	Maximum Voltage	0.0024	0.0182	
20	Normal Voltage	0.0026	0.0325	
20	Battery End Point	0.0166	0.0248	

Note:


1. Normal Voltage = 3.91V ; Battery End Point (BEP) =3.4V. ; Maximum Voltage =4.5V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.




A2. WCDMA

Peak-to-Average Ratio

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	2.93	2.87	2.90	PASS
Middle CH	3.16	2.87	2.75	
Highest CH	3.04	2.96	2.70	







26dB Bandwidth

Mode	WCDMA Band V (MHz)	WCDMA Band II (MHz)	WCDMA Band IV (MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.72	4.73	4.72
Middle CH	4.72	4.73	4.75
Highest CH	4.72	4.72	4.72