



FCC RF Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT2305-1
FCC ID : IHDT56AL5
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System
TEST DATE(S) : Mar. 13, 2023 ~ Apr. 06, 2023

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia



Approved by: Jason Jia

Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant 5

 1.2 Manufacturer 5

 1.3 Product Feature of Equipment Under Test..... 5

 1.4 Product Specification of Equipment Under Test..... 5

 1.5 Modification of EUT 6

 1.6 Specification of Accessory..... 6

 1.7 Testing Location 7

 1.8 Test Software..... 7

 1.9 Applicable Standards..... 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

 2.1 Carrier Frequency and Channel 8

 2.2 Test Mode 9

 2.3 Connection Diagram of Test System..... 9

 2.4 Support Unit used in test configuration and system 10

 2.5 EUT Operation Test Setup 10

 2.6 Measurement Results Explanation Example..... 11

3 TEST RESULT 12

 3.1 6dB and 99% Bandwidth Measurement 12

 3.2 Output Power Measurement..... 13

 3.3 Power Spectral Density Measurement 14

 3.4 Conducted Band Edges and Spurious Emission Measurement 16

 3.5 Radiated Band Edges and Spurious Emission Measurement 17

 3.6 AC Conducted Emission Measurement..... 21

 3.7 Antenna Requirements 23

4 LIST OF MEASURING EQUIPMENT 24

5 UNCERTAINTY OF EVALUATION 25

APPENDIX A. CONDUCTED TEST RESULTS

APPENDIX B. AC CONDUCTED EMISSION TEST RESULT

APPENDIX C. RADIATED SPURIOUS EMISSION

APPENDIX D. DUTY CYCLE PLOTS

APPENDIX E. SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR322305C	Rev. 01	Initial issue of report	Apr. 21, 2023



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.1	-	99% Bandwidth	-	Report Only	-
3.2	15.247(b)	Power Output Measurement	≤ 30dBm	Pass	-
3.3	15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4	15.247(d)	Conducted Band Edges	≤ 20dBc	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.04 dB at 2484.63 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 8.60 dB at 0.150 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1 General Description

1.1 Applicant

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2305-1
FCC ID	IHDT56AL5
IMEI Code	Conducted: 351048560017737/351048560017745 Conduction: 351048560019972/351048560019980 Radiation: 351048560021275
HW Version	DVT2
SW Version	TTT33.46
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to antenna	<MIMO Ant. 3+8> 802.11b : 26.04 dBm (0.4018 W) 802.11g : 28.69 dBm (0.7396 W) 802.11n HT20 : 28.77 dBm (0.7534 W) 802.11n HT40 : 28.42 dBm (0.6950 W) 802.11ac VHT20 : 28.86 dBm (0.7691 W) 802.11ac VHT40 : 28.45 dBm (0.6998 W) 802.11ax HE20 : 28.89 dBm (0.7745 W) 802.11ax HE40 : 28.57 dBm (0.7194 W)
99% Occupied Bandwidth	802.11b : 13.506MHz 802.11g : 17.542MHz 802.11ax HE20 : 19.461MHz 802.11ax HE40 : 38.122MHz
Antenna Type / Gain	<Ant3>:IFA Antenna type with gain -5.50 dBi <Ant8>:Loop Antenna type with gain -6.50 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK)



	802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM) 802.11ax : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM)
--	--

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to Comments and Explanations in report summary.
2. For WLAN SISO & MIMO (STBC) mode, the whole testing has assessed only MIMO mode by referring to the higher normal conducted power.
3. WIFI MIMO only support STBC by manufacturer declared.
4. For 802.11n/ac & 802.11ax mode, the whole testing have assessed only 802.11ax HE20/40 by referring to the higher output power.
5. 802.11ax support full RU tone and partial RU tone, both full RU and partial RU-left (for low CH) and partial RU-right (for high CH) are tested for conducted power/PSD/RSE, the full RU power > partial RU, therefore the full RU perform full test and Partial RU verified power/PSD/RSE.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Specification of Accessory

Specification of Accessory				
AC Adapter 1	Brand Name	Motorola (Chenyang)	Model Name	MC-681N
AC Adapter 2	Brand Name	Motorola (Acbel)	Model Name	MC-681N
Battery	Brand Name	Motorola(Amperex)	Model Name	PG44
USB Cable 1	Brand Name	Motorola(Saibao)	Model Name	SC18D86731
USB Cable 2	Brand Name	Motorola(Saibao)	Model Name	SC18D71644



1.7 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People’s Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH07-KS TH01-KS	CN1257	314309

1.8 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH07-KS	AUDIX	E3	6.2009-8-24al
2.	CO01-KS	AUDIX	E3	6.2009-8-24

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

MIMO Antenna


Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11ax HE20	MCS0
802.11ax HE40	MCS0

Test Cases	
AC Conducted Emission	Mode 1 :Bluetooth Link+ WLAN Link(2.4G)+ USB Cable(Charging From Adapter1)


Simultaneous transmission
802.11ax HE20 CH11(2462MHz)+ SA-N48 802.11ax HE20 CH11(2462MHz)+Bluetooth LE(2Mbps)CH39(2480MHz)+ SA-N48

2.3 Connection Diagram of Test System

AC Conducted Emission:



Radiated Emission:



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
2.	Notebook	Lenovo	V130-15IKB005	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
3.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
4.	Earphone	N/A	N/A	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 2.95 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

=2.95 + 10 = 12.95 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1%~5% of OBW and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

Method (b): Measure and sum spectral maxima across the outputs.

The measurement on each individual output were performed with the same span and number on each individual output. The maximum value (peak) of each spectrum is determined. These maximum values are then summed mathematically in linear power units across the outputs.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.11
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Please refer to Appendix A.



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.5.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C.



3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBµV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

<STBC Modes>

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

Basic methodology with NANT transmit antennas, each with the same directional gain GANT dBi, being driven by NANT transmitter outputs of equal power, and If antenna gains are not equal and each transmit antenna can be driven by more than one spatial stream, directional gain may be calculated by either of the following two formulas:

Directional gain = GANT MAX.

<STBC Modes>						
	Ant. 3 (dBi)	Ant. 8 (dBi)	DG for Power (dBi)	DG for PSD (dBi)	Power Limit Reduction (dB)	PSD Limit Reduction (dB)
2.4 GHz	-5.50	-6.50	-5.50	-5.50	0.00	0.00

$Power\ Limit\ Reduction = DG(Power) - 6dBi, (min = 0)$

$PSD\ Limit\ Reduction = DG(PSD) - 6dBi, (min = 0)$



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 12, 2022	Mar. 13, 2023~ Mar. 29, 2023	Oct. 11, 2023	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 05, 2023	Mar. 13, 2023~ Mar. 29, 2023	Jan. 04, 2024	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 05, 2023	Mar. 13, 2023~ Mar. 29, 2023	Jan. 04, 2024	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Max 30dBm	Oct. 12, 2022	Apr. 06, 2023	Oct. 11, 2023	Radiation (03CH07-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55370528	10Hz-44G,MAX 30dB	Oct. 12, 2022	Apr. 06, 2023	Oct. 11, 2023	Radiation (03CH07-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 16, 2022	Apr. 06, 2023	Oct. 15, 2023	Radiation (03CH07-KS)
Bilog Antenna	TeseQ	CBL6111D	59913	30MHz-1GHz	Aug. 26, 2022	Apr. 06, 2023	Aug. 25, 2023	Radiation (03CH07-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218652	1GHz~18GHz	Apr. 05, 2023	Apr. 06, 2023	Apr. 04, 2024	Radiation (03CH07-KS)
high gain Amplifier	EM	EM01G18GA	060840	1Ghz-18Ghz	Oct. 12, 2022	Apr. 06, 2023	Oct. 11, 2023	Radiation (03CH07-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Oct. 17, 2022	Apr. 06, 2023	Oct. 16, 2023	Radiation (03CH07-KS)
Amplifier	SONOMA	310N	413740	9KHz-1GHz	Jan. 05, 2023	Apr. 06, 2023	Jan. 04, 2024	Radiation (03CH07-KS)
Amplifier	EM	EM01G18GA	060834	1Ghz-18Ghz	Oct. 12, 2022	Apr. 06, 2023	Oct. 11, 2023	Radiation (03CH07-KS)
Amplifier	EM	EM18G40GG A	060851	18~40GHz	Jan. 05, 2023	Apr. 06, 2023	Jan. 04, 2024	Radiation (03CH07-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Apr. 06, 2023	NCR	Radiation (03CH07-KS)
Turn Table	EM	EM 1000-T	N/A	0~360 degree	NCR	Apr. 06, 2023	NCR	Radiation (03CH07-KS)
Antenna Mast	EM	EM 1000-A	N/A	1 m~4 m	NCR	Apr. 06, 2023	NCR	Radiation (03CH07-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	May 24, 2022	Mar. 29, 2023	May 23, 2023	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2022	Mar. 29, 2023	Oct. 12, 2023	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	May 24, 2022	Mar. 29, 2023	May 23, 2023	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000811	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2022	Mar. 29, 2023	Oct. 11, 2023	Conduction (CO01-KS)

NCR: No Calibration Required



5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Power	±0.46 dB
Conducted Emissions	±0.48 dB
Occupied Channel Bandwidth	±0.1 %
Conducted Power Spectral Density	±0.40 dB

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.78dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0dB
---	-------

----- THE END -----



Appendix A. Conducted Test Results

Report Number : FR322305C

Test Engineer:	Jiang Jun	Temperature:	21~25	°C
Test Date:	2023.3.13~2023.3.29	Relative Humidity:	51~54	%

TEST RESULTS DATA
Peak Output Power

2.4GHz Band MIMO																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant3	Ant8	SUM	Ant3	Ant8	Ant3	Ant8	Ant3	Ant8	Ant3	Ant8	
11b	1Mbps	2	1	2412	22.53	22.73	25.64	30.00		-5.50		20.14		36.00	Pass	
11b	1Mbps	2	6	2437	22.46	23.54	26.04	30.00		-5.50		20.54		36.00	Pass	
11b	1Mbps	2	11	2462	23.02	22.39	25.73	30.00		-5.50		20.23		36.00	Pass	
11g	6Mbps	2	1	2412	25.57	25.49	28.54	30.00		-5.50		23.04		36.00	Pass	
11g	6Mbps	2	6	2437	25.63	25.70	28.68	30.00		-5.50		23.18		36.00	Pass	
11g	6Mbps	2	10	2457	26.12	25.18	28.69	30.00		-5.50		23.19		36.00	Pass	
11g	6Mbps	2	11	2462	24.39	24.26	27.34	30.00		-5.50		21.84		36.00	Pass	
HT20	MCS0	2	1	2412	25.22	24.69	27.97	30.00		-5.50		22.47		36.00	Pass	
HT20	MCS0	2	6	2437	25.52	25.52	28.53	30.00		-5.50		23.03		36.00	Pass	
HT20	MCS0	2	9	2452	26.21	25.26	28.77	30.00		-5.50		23.27		36.00	Pass	
HT20	MCS0	2	10	2457	24.58	23.03	26.88	30.00		-5.50		21.38		36.00	Pass	
HT20	MCS0	2	11	2462	23.81	22.73	26.31	30.00		-5.50		20.81		36.00	Pass	
HT40	MCS0	2	3	2422	24.61	24.64	27.64	30.00		-5.50		22.14		36.00	Pass	
HT40	MCS0	2	6	2437	25.62	25.18	28.42	30.00		-5.50		22.92		36.00	Pass	
HT40	MCS0	2	7	2442	24.95	23.71	27.38	30.00		-5.50		21.88		36.00	Pass	
HT40	MCS0	2	8	2447	24.19	22.98	26.64	30.00		-5.50		21.14		36.00	Pass	
HT40	MCS0	2	9	2452	22.42	21.81	25.14	30.00		-5.50		19.64		36.00	Pass	
VHT20	MCS0	2	1	2412	25.25	24.75	28.02	30.00		-5.50		22.52		36.00	Pass	
VHT20	MCS0	2	6	2437	25.55	25.57	28.57	30.00		-5.50		23.07		36.00	Pass	
VHT20	MCS0	2	9	2452	26.29	25.36	28.86	30.00		-5.50		23.36		36.00	Pass	
VHT20	MCS0	2	10	2457	24.67	23.11	26.97	30.00		-5.50		21.47		36.00	Pass	
VHT20	MCS0	2	11	2462	23.86	22.81	26.38	30.00		-5.50		20.88		36.00	Pass	
VHT40	MCS0	2	3	2422	24.67	24.66	27.68	30.00		-5.50		22.18		36.00	Pass	
VHT40	MCS0	2	6	2437	25.65	25.22	28.45	30.00		-5.50		22.95		36.00	Pass	
VHT40	MCS0	2	7	2442	25.04	23.77	27.46	30.00		-5.50		21.96		36.00	Pass	
VHT40	MCS0	2	8	2447	24.28	23.08	26.73	30.00		-5.50		21.23		36.00	Pass	
VHT40	MCS0	2	9	2452	22.45	21.85	25.17	30.00		-5.50		19.67		36.00	Pass	

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
Peak Output Power

2.4GHz Band MIMO																	
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Peak Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
						Ant3	Ant8	SUM	Ant3	Ant8	Ant3	Ant8	Ant3	Ant8	Ant3	Ant8	
HE20	MCS0	2	1	2412	Full	25.32	24.85	28.10	30.00		-5.50		22.60		36.00	Pass	
HE20	MCS0	2	1	2412	26/0	19.54	16.96	21.45	30.00		-5.50		15.95		36.00	Pass	
HE20	MCS0	2	1	2412	52/37	22.62	20.01	24.52	30.00		-5.50		19.02		36.00	Pass	
HE20	MCS0	2	1	2412	106/53	24.78	22.87	26.94	30.00		-5.50		21.44		36.00	Pass	
HE20	MCS0	2	6	2437	Full	25.57	25.65	28.62	30.00		-5.50		23.12		36.00	Pass	
HE20	MCS0	2	6	2437	26/0	20.47	19.84	23.18	30.00		-5.50		17.68		36.00	Pass	
HE20	MCS0	2	6	2437	52/37	23.26	23.23	26.26	30.00		-5.50		20.76		36.00	Pass	
HE20	MCS0	2	6	2437	106/53	25.03	24.87	27.96	30.00		-5.50		22.46		36.00	Pass	
HE20	MCS0	2	9	2452	Full	26.31	25.41	28.89	30.00		-5.50		23.39		36.00	Pass	
HE20	MCS0	2	10	2457	Full	24.74	23.20	27.05	30.00		-5.50		21.55		36.00	Pass	
HE20	MCS0	2	11	2462	Full	23.96	22.88	26.46	30.00		-5.50		20.96		36.00	Pass	
HE20	MCS0	2	11	2462	26/8	15.12	14.11	17.65	30.00		-5.50		12.15		36.00	Pass	
HE20	MCS0	2	11	2462	52/40	18.25	17.62	20.96	30.00		-5.50		15.46		36.00	Pass	
HE20	MCS0	2	11	2462	106/54	20.97	19.95	23.50	30.00		-5.50		18.00		36.00	Pass	
HE40	MCS0	2	3	2422	Full	24.73	24.74	27.75	30.00		-5.50		22.25		36.00	Pass	
HE40	MCS0	2	6	2437	Full	25.82	25.29	28.57	30.00		-5.50		23.07		36.00	Pass	
HE40	MCS0	2	7	2442	Full	25.11	23.85	27.54	30.00		-5.50		22.04		36.00	Pass	
HE40	MCS0	2	8	2447	Full	24.36	23.19	26.82	30.00		-5.50		21.32		36.00	Pass	
HE40	MCS0	2	9	2452	Full	22.52	21.93	25.25	30.00		-5.50		19.75		36.00	Pass	

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
Average Output Power

2.4GHz Band MIMO																		
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power with duty factor (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant 1	Ant 2	Ant3	Ant8	SUM	Ant3	Ant8	Ant3	Ant8	Ant3	Ant8	Ant3	Ant8	
11b	1Mbps	2	1	2412	0.04	0.03	19.93	20.22	23.09	30.00		-5.50		17.59		36.00		Pass
11b	1Mbps	2	6	2437	0.04	0.03	19.87	20.44	23.17	30.00		-5.50		17.67		36.00		Pass
11b	1Mbps	2	11	2462	0.04	0.03	20.49	20.06	23.29	30.00		-5.50		17.79		36.00		Pass
11g	6Mbps	2	1	2412	0.13	0.13	18.91	19.11	22.02	30.00		-5.50		16.52		36.00		Pass
11g	6Mbps	2	6	2437	0.13	0.13	19.20	19.37	22.30	30.00		-5.50		16.80		36.00		Pass
11g	6Mbps	2	10	2457	0.13	0.13	18.89	18.18	21.56	30.00		-5.50		16.06		36.00		Pass
11g	6Mbps	2	11	2462	0.13	0.13	15.30	14.46	17.91	30.00		-5.50		12.41		36.00		Pass
HT20	MCS0	2	1	2412	0.14	0.14	16.21	16.35	19.29	30.00		-5.50		13.79		36.00		Pass
HT20	MCS0	2	6	2437	0.14	0.14	18.22	18.27	21.26	30.00		-5.50		15.76		36.00		Pass
HT20	MCS0	2	9	2452	0.14	0.14	19.15	17.81	21.54	30.00		-5.50		16.04		36.00		Pass
HT20	MCS0	2	10	2457	0.14	0.14	14.70	13.62	17.20	30.00		-5.50		11.70		36.00		Pass
HT20	MCS0	2	11	2462	0.14	0.14	13.99	13.10	16.58	30.00		-5.50		11.08		36.00		Pass
HT40	MCS0	2	3	2422	0.28	0.28	15.13	15.72	18.45	30.00		-5.50		12.95		36.00		Pass
HT40	MCS0	2	4	2427	0.28	0.28	11.08	11.08	14.09	30.00		-5.50		8.59		36.00		Pass
HT40	MCS0	2	5	2432	0.28	0.28	11.08	11.08	14.09	30.00		-5.50		8.59		36.00		Pass
HT40	MCS0	2	6	2437	0.28	0.28	16.82	15.90	19.39	30.00		-5.50		13.89		36.00		Pass
HT40	MCS0	2	7	2442	0.28	0.28	15.04	14.09	17.60	30.00		-5.50		12.10		36.00		Pass
HT40	MCS0	2	8	2447	0.28	0.28	14.15	13.30	16.76	30.00		-5.50		11.26		36.00		Pass
HT40	MCS0	2	9	2452	0.28	0.28	12.40	11.36	14.92	30.00		-5.50		9.42		36.00		Pass
VHT20	MCS0	2	1	2412	0.17	0.13	16.30	16.39	19.36	30.00		-5.50		13.86		36.00		Pass
VHT20	MCS0	2	6	2437	0.17	0.13	18.28	18.29	21.30	30.00		-5.50		15.80		36.00		Pass
VHT20	MCS0	2	9	2452	0.17	0.13	19.26	17.88	21.63	30.00		-5.50		16.13		36.00		Pass
VHT20	MCS0	2	10	2457	0.17	0.13	14.80	13.69	17.29	30.00		-5.50		11.79		36.00		Pass
VHT20	MCS0	2	11	2462	0.17	0.13	14.09	13.14	16.65	30.00		-5.50		11.15		36.00		Pass
VHT40	MCS0	2	3	2422	0.28	0.28	15.19	15.77	18.50	30.00		-5.50		13.00		36.00		Pass
VHT40	MCS0	2	6	2437	0.28	0.28	16.97	16.01	19.53	30.00		-5.50		14.03		36.00		Pass
VHT40	MCS0	2	7	2442	0.28	0.28	15.15	14.15	17.69	30.00		-5.50		12.19		36.00		Pass
VHT40	MCS0	2	8	2447	0.28	0.28	14.26	13.37	16.85	30.00		-5.50		11.35		36.00		Pass
VHT40	MCS0	2	9	2452	0.28	0.28	12.46	11.40	14.97	30.00		-5.50		9.47		36.00		Pass

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
Average Output Power

2.4GHz Band MIMO																			
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Duty Factor (dB)		Average Conducted Power with duty factor (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
						Ant3	Ant8	Ant3	Ant8	SUM	Ant3	Ant8	Ant3	Ant8	Ant3	Ant8	Ant3	Ant8	
HE20	MCS0	2	1	2412	Full	0.18	0.18	16.41	16.50	19.47	30.00		-5.50	13.97	36.00	Pass			
HE20	MCS0	2	1	2412	26/0	0.04	0.04	9.92	6.47	11.54	30.00		-5.50	6.04	36.00	Pass			
HE20	MCS0	2	1	2412	52/37	0.05	0.05	12.29	9.22	14.03	30.00		-5.50	8.53	36.00	Pass			
HE20	MCS0	2	1	2412	106/53	0.08	0.08	14.90	12.93	17.04	30.00		-5.50	11.54	36.00	Pass			
HE20	MCS0	2	6	2437	Full	0.18	0.18	18.40	18.46	21.44	30.00		-5.50	15.94	36.00	Pass			
HE20	MCS0	2	6	2437	26/0	0.04	0.04	10.71	9.48	13.15	30.00		-5.50	7.65	36.00	Pass			
HE20	MCS0	2	6	2437	52/37	0.05	0.05	13.86	12.97	16.45	30.00		-5.50	10.95	36.00	Pass			
HE20	MCS0	2	6	2437	106/53	0.08	0.08	15.90	15.23	18.59	30.00		-5.50	13.09	36.00	Pass			
HE20	MCS0	2	9	2452	Full	0.18	0.18	19.39	18.01	21.76	30.00		-5.50	16.26	36.00	Pass			
HE20	MCS0	2	10	2457	Full	0.18	0.18	14.96	13.87	17.46	30.00		-5.50	11.96	36.00	Pass			
HE20	MCS0	2	11	2462	Full	0.18	0.18	14.16	13.23	16.73	30.00		-5.50	11.23	36.00	Pass			
HE20	MCS0	2	11	2462	26/8	0.04	0.04	5.33	4.27	7.84	30.00		-5.50	2.34	36.00	Pass			
HE20	MCS0	2	11	2462	52/40	0.05	0.05	7.89	6.87	10.42	30.00		-5.50	4.92	36.00	Pass			
HE20	MCS0	2	11	2462	106/54	0.08	0.08	10.34	9.26	12.84	30.00		-5.50	7.34	36.00	Pass			
HE40	MCS0	2	3	2422	Full	0.34	0.34	15.31	15.88	18.61	30.00		-5.50	13.11	36.00	Pass			
HE40	MCS0	2	6	2437	Full	0.34	0.34	17.12	16.16	19.68	30.00		-5.50	14.18	36.00	Pass			
HE40	MCS0	2	7	2442	Full	0.34	0.34	15.30	14.31	17.84	30.00		-5.50	12.34	36.00	Pass			
HE40	MCS0	2	8	2447	Full	0.34	0.34	14.43	13.52	17.01	30.00		-5.50	11.51	36.00	Pass			
HE40	MCS0	2	9	2452	Full	0.34	0.34	12.59	11.53	15.10	30.00		-5.50	9.60	36.00	Pass			

Note: Measured power (dBm) has offset with cable loss.



Ambient Condition: 25 °C, 45 %RH	
According Standard: ■Part15C	
Test Date: 2023.3.13~2023.3.29	Test Engineer: Jiang Jun


DTS Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B-MIMO	Ant3	2412	8.04	2408.00	2416.04	0.5	PASS
	Ant8	2412	7.08	2408.48	2415.56	0.5	PASS
	Ant3	2437	8.04	2433.00	2441.04	0.5	PASS
	Ant8	2437	7.56	2433.48	2441.04	0.5	PASS
	Ant3	2462	7.56	2458.00	2465.56	0.5	PASS
	Ant8	2462	8.56	2457.48	2466.04	0.5	PASS
11G-MIMO	Ant3	2412	15.76	2404.12	2419.88	0.5	PASS
	Ant8	2412	15.92	2404.24	2420.16	0.5	PASS
	Ant3	2437	15.68	2429.48	2445.16	0.5	PASS
	Ant8	2437	16.36	2428.84	2445.20	0.5	PASS
	Ant3	2457	15.00	2448.88	2463.88	0.5	PASS
	Ant8	2457	15.68	2448.84	2464.52	0.5	PASS
11AX20MIMO	Ant3	2412	17.00	2403.52	2420.52	0.5	PASS
	Ant8	2412	17.52	2403.72	2421.24	0.5	PASS
	Ant3	2437	16.80	2429.32	2446.12	0.5	PASS
	Ant8	2437	18.80	2427.72	2446.52	0.5	PASS
	Ant3	2452	17.84	2442.68	2460.52	0.5	PASS
	Ant8	2452	16.40	2443.12	2459.52	0.5	PASS
	Ant3	2457	17.72	2447.84	2465.56	0.5	PASS
	Ant8	2457	17.08	2447.48	2464.56	0.5	PASS
11AX40MIMO	Ant3	2422	36.88	2403.76	2440.64	0.5	PASS
	Ant8	2422	35.28	2404.32	2439.60	0.5	PASS
	Ant3	2437	38.00	2418.04	2456.04	0.5	PASS
	Ant8	2437	37.60	2418.28	2455.88	0.5	PASS
	Ant3	2442	37.44	2423.20	2460.64	0.5	PASS
	Ant8	2442	35.12	2424.48	2459.60	0.5	PASS
	Ant3	2447	37.28	2428.36	2465.64	0.5	PASS
	Ant8	2447	35.04	2429.48	2464.52	0.5	PASS
	Ant3	2452	37.36	2433.28	2470.64	0.5	PASS
	Ant8	2452	35.12	2434.48	2469.60	0.5	PASS




Test Graphs






11B-MIMO_Ant3_2437



Date: 13.MAR.2023 15:23:41


11B-MIMO_Ant8_2437




Date: 13.MAR.2023 15:25:12



11B-MIMO_Ant3_2462




11B-MIMO_Ant8_2462






11G-MIMO_Ant3_2412



Date: 13.MAR.2023 15:32:31


11G-MIMO_Ant8_2412



Date: 13.MAR.2023 15:34:27




11G-MIMO_Ant3_2437



Date: 13.MAR.2023 15:36:42


11G-MIMO_Ant8_2437




Date: 13.MAR.2023 15:38:16




11G-MIMO_Ant3_2457




11G-MIMO_Ant8_2457









11AX20MIMO_Ant3_2412




11AX20MIMO_Ant8_2412








11AX20MIMO_Ant3_2452




Date: 29.MAR.2023 12:11:56

11AX20MIMO_Ant8_2452




Date: 29.MAR.2023 12:13:49






11AX20MIMO_Ant3_2462




11AX20MIMO_Ant8_2462







11AX40MIMO_Ant3_2422




11AX40MIMO_Ant8_2422








11AX40MIMO_Ant3_2442




11AX40MIMO_Ant8_2442






11AX40MIMO_Ant3_2447




11AX40MIMO_Ant8_2447






11AX40MIMO_Ant3_2452



11AX40MIMO_Ant8_2452






Occupied Channel Bandwidth


Test Result

TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B-MIMO	Ant3	2412	11.908	2405.9660	2417.8741	---	---
	Ant8	2412	12.747	2405.6464	2418.3936	---	---
	Ant3	2437	12.667	2430.7263	2443.3936	---	---
	Ant8	2437	13.147	2430.4865	2443.6334	---	---
	Ant3	2462	12.907	2455.4865	2468.3936	---	---
	Ant8	2462	13.506	2455.0869	2468.5934	---	---
11G-MIMO	Ant3	2412	17.143	2403.4486	2420.5914	---	---
	Ant8	2412	17.183	2403.5285	2420.7113	---	---
	Ant3	2437	17.542	2428.2887	2445.8312	---	---
	Ant8	2437	17.143	2428.4885	2445.6314	---	---
	Ant3	2457	17.103	2448.4086	2465.5115	---	---
	Ant8	2457	17.143	2448.1688	2465.3117	---	---
	Ant3	2462	17.423	2453.2488	2470.6713	---	---
	Ant8	2462	17.463	2453.1289	2470.5914	---	---
11AX20MIMO	Ant3	2412	19.061	2402.4895	2421.5504	---	---
	Ant8	2412	19.221	2402.4496	2421.6703	---	---
	Ant3	2437	19.181	2427.4496	2446.6304	---	---
	Ant8	2437	19.341	2427.3696	2446.7103	---	---
	Ant3	2452	19.101	2442.4496	2461.5504	---	---
	Ant8	2452	18.981	2442.4096	2461.3906	---	---
	Ant3	2457	19.101	2447.4496	2466.5504	---	---
	Ant8	2457	19.181	2447.2897	2466.4705	---	---
	Ant3	2462	19.181	2452.4096	2471.5904	---	---
	Ant8	2462	19.461	2452.2098	2471.6703	---	---
11AX40MIMO	Ant3	2422	37.962	2403.0589	2441.0210	---	---
	Ant8	2422	37.962	2403.0589	2441.0210	---	---
	Ant3	2437	38.122	2417.9790	2456.1009	---	---
	Ant8	2437	38.042	2417.9790	2456.0210	---	---
	Ant3	2442	37.802	2423.0589	2460.8611	---	---
	Ant8	2442	37.562	2423.1389	2460.7013	---	---
	Ant3	2447	37.722	2428.1389	2465.8611	---	---
	Ant8	2447	37.403	2428.2987	2465.7013	---	---
	Ant3	2452	37.882	2433.0589	2470.9411	---	---
	Ant8	2452	37.802	2433.1389	2470.9411	---	---




Test Graphs








11B-MIMO_Ant3_2462



Date: 13.MAR.2023 15:28:06


11B-MIMO_Ant8_2462



Date: 13.MAR.2023 15:29:59




11G-MIMO_Ant3_2412




Date: 13.MAR.2023 15:32:46

11G-MIMO_Ant8_2412




Date: 13.MAR.2023 15:34:39






11G-MIMO_Ant3_2457



Date: 29.MAR.2023 12:06:18


11G-MIMO_Ant8_2457



Date: 29.MAR.2023 12:08:11




11G-MIMO_Ant3_2462



Date: 13.MAR.2023 15:40:23


11G-MIMO_Ant8_2462



Date: 13.MAR.2023 15:42:13




11AX20MIMO_Ant3_2412



Date: 13.MAR.2023 15:45:54


11AX20MIMO_Ant8_2412



Date: 13.MAR.2023 15:47:53




11AX20MIMO_Ant3_2437



Date: 13.MAR.2023 15:50:01


11AX20MIMO_Ant8_2437



Date: 13.MAR.2023 15:51:34




11AX20MIMO_Ant3_2452




Date: 29.MAR.2023 12:12:11

11AX20MIMO_Ant8_2452




Date: 29.MAR.2023 12:14:04






11AX20MIMO_Ant3_2462




Date: 13.MAR.2023 15:58:22

11AX20MIMO_Ant8_2462




Date: 13.MAR.2023 16:00:18






11AX40MIMO_Ant3_2437



Date: 13.MAR.2023 16:07:18


11AX40MIMO_Ant8_2437



Date: 13.MAR.2023 16:08:48




11AX40MIMO_Ant3_2442



Date: 29.MAR.2023 12:35:40


11AX40MIMO_Ant8_2442



Date: 29.MAR.2023 12:37:26




11AX40MIMO_Ant3_2447



Date: 29.MAR.2023 12:39:46

11AX40MIMO_Ant8_2447



Date: 29.MAR.2023 12:41:38