



FCC RF Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT2415-1, XT2415-3, XT2415-5, XT2415V
FCC ID : IHDT56AN5
STANDARD : FCC Part 15 Subpart E §15.407
CLASSIFICATION : (NII) Unlicensed National Information Infrastructure
TEST DATE(S) : Sep. 19, 2023 ~ Oct. 12, 2023

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

1.1 Applicant 5

1.2 Manufacturer 5

1.3 Product Feature of Equipment Under Test 5

1.4 Product Specification of Equipment Under Test 5

1.5 Modification of EUT 6

1.6 Specification of Accessory 7

1.7 Testing Location 7

1.8 Test Software 7

1.9 Applicable Standards 8

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 9

2.1 Carrier Frequency and Channel 9

2.2 Test Mode 11

2.3 Connection Diagram of Test System 13

2.4 Support Unit used in test configuration and system 13

2.5 EUT Operation Test Setup 14

2.6 Measurement Results Explanation Example 14

3 TEST RESULT 15

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement 15

3.2 Maximum Conducted Output Power Measurement 17

3.3 Power Spectral Density Measurement 19

3.4 Unwanted Emissions Measurement 22

3.5 AC Conducted Emission Measurement 27

3.6 Antenna Requirements 29

4 LIST OF MEASURING EQUIPMENT 30

5 MEASUREMENT UNCERTAINTY 31

APPENDIX A. CONDUCTED TEST RESULTS

APPENDIX B. AC CONDUCTED EMISSION TEST RESULT

APPENDIX C. RADIATED SPURIOUS EMISSION

APPENDIX D. DUTY CYCLE PLOTS

APPENDIX E. SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR391202E	Rev. 01	Initial issue of report	Oct. 25, 2023



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit for U-NII-1/2A/2C	Limit for U-NII-3	Result	Remark
3.1	2.1049 & 15.403(i)	6dB, 26dB & 99% Bandwidth	-	6dB Bandwidth > 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 24 dBm	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 11 dBm/MHz	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b) & 15.209(a)	15.407(b)(4)(i) & 15.209(a)	Pass	Under limit 3.09 dB at 5354.250 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	15.207(a)	Pass	Under limit 13.62 dB at 18.328 MHz
3.6	15.203 & 15.407(a)	Antenna Requirement	15.203 & 15.407(a)	15.203 & 15.407(a)	Pass	-

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2415-1, XT2415-3, XT2415-5, XT2415V
FCC ID	IHDT56AN5
IMEI Code	Conducted: 357534480029799/357534480029807 Conduction: 357534480029658/357534480029666 Radiation: 357534480029716/3575344800724
HW Version	DVT2
SW Version	UUD34.38
EUT Stage	Identical Prototype

Remark: The four model names are only for market segment purpose, there is no other difference.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	5180 MHz ~ 5240 MHz 5260 MHz ~ 5320 MHz 5500 MHz ~ 5720 MHz 5745 MHz ~ 5825 MHz
Maximum Output Power to Antenna	<5180 MHz ~ 5240 MHz> 802.11a : 19.87 dBm / 0.0971 W 802.11n HT20 : 19.72 dBm / 0.0938 W 802.11n HT40 : 15.66 dBm / 0.0368 W 802.11ac VHT20: 19.74 dBm / 0.0942 W 802.11ac VHT40: 17.72 dBm / 0.0592 W 802.11ac VHT80: 15.08 dBm / 0.0322 W <5260 MHz ~ 5320 MHz> 802.11a : 19.95 dBm / 0.0989 W 802.11n HT20 : 19.67 dBm / 0.0927 W 802.11n HT40 : 15.66 dBm / 0.0368 W 802.11ac VHT20: 19.76 dBm / 0.0946 W 802.11ac VHT40: 17.75 dBm / 0.0596 W



	802.11ac VHT80: 15.69 dBm / 0.0371 W <5500 MHz ~ 5720 MHz > 802.11a : 19.55 dBm / 0.0902 W 802.11n HT20 : 18.63 dBm / 0.0729 W 802.11n HT40 : 15.28 dBm / 0.0337 W 802.11ac VHT20: 18.69 dBm / 0.0740 W 802.11ac VHT40: 17.08 dBm / 0.0511 W 802.11ac VHT80: 17.27 dBm / 0.0533 W <5745 MHz ~ 5825 MHz > 802.11a : 19.54 dBm / 0.0899 W 802.11n HT20 : 19.46 dBm / 0.0883 W 802.11n HT40 : 15.07 dBm / 0.0321 W 802.11ac VHT20: 19.53 dBm / 0.0897 W 802.11ac VHT40: 17.12 dBm / 0.0515 W 802.11ac VHT80: 17.23 dBm / 0.0528 W
99% Occupied Bandwidth	<5180 MHz ~ 5240 MHz > 802.11a : 20.979 MHz 802.11ac VHT20 : 20.979 MHz 802.11ac VHT40 : 36.763 MHz 802.11ac VHT80 : 76.084 MHz <5260 MHz ~ 5320 MHz > 802.11a : 19.700 MHz 802.11ac VHT20 : 20.180 MHz 802.11ac VHT40 : 36.763 MHz 802.11ac VHT80 : 75.924 MHz <5500 MHz ~ 5720 MHz > 802.11a : 17.862 MHz 802.11ac VHT20 : 18.501 MHz 802.11ac VHT40 : 36.364 MHz 802.11ac VHT80 : 75.604 MHz <5745 MHz ~ 5825 MHz > 802.11a : 18.182 MHz 802.11ac VHT20 : 18.821 MHz 802.11ac VHT40 : 36.444 MHz 802.11ac VHT80 : 75.764 MHz
Antenna Type / Gain	<5180 MHz ~ 5240 MHz > IFA Antenna with gain -5.00 dBi <5260 MHz ~ 5320 MHz > IFA Antenna with gain -5.00 dBi <5500 MHz ~ 5720 MHz > IFA Antenna with gain -5.00 dBi <5745 MHz ~ 5825 MHz > IFA Antenna with gain -5.00 dBi
Type of Modulation	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)

Note: For 802.11n HT20 / ac VHT20 and 802.11n HT40 / ac VHT40 mode, the whole testing has assessed only 802.11ac VHT20/ VHT40 by referring to their higher conducted power.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Specification of Accessory

Accessories Information				
AC Adapter 1	Brand Name	Motorola(Salcomp)	Model Name	MC-101
AC Adapter 2	Brand Name	Motorola(Chenyang)	Model Name	MC-101
AC Adapter 3	Brand Name	Motorola(AOHAI)	Model Name	MC-101
Battery 1	Brand Name	Motorola (ATL)	Model Name	QA50
USB Cable 1	Brand Name	WASHIN	Model Name	S928D98335
USB Cable 2	Brand Name	Saibao	Model Name	S928D98333
USB Cable 3	Brand Name	Saibao	Model Name	S928D98334

1.7 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH08-KS TH01-KS	CN1257	314309

1.8 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH08-KS	AUDIX	E3	210616
3.	CO01-KS	AUDIX	E3	6.2009-8-24



1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5180-5240 MHz U-NII-1	36	5180	44	5220
	38*	5190	46*	5230
	40	5200	48	5240
	42 [#]	5210	-	-

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5260-5320 MHz U-NII-2A	52	5260	60	5300
	54*	5270	62*	5310
	56	5280	64	5320
	58 [#]	5290	-	-

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5500-5720MHz U-NII-2C	100	5500	112	5560
	102*	5510	116	5580
	104	5520	132	5660
	106 [#]	5530	134*	5670
	108	5540	136	5680
	110*	5550	140	5700

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5745-5825 MHz U-NII-3	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155 [#]	5775	165	5825



Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
TDWR Channel	118*	5590	124	5620
	120	5600	126*	5630
	122 [#]	5610	128	5640

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
Straddle Channel	138 [#]	5690	144	5720
	142*	5710	-	-

Note:

1. The above Frequency and Channel in "*" were 802.11n HT40 and 802.11ac VHT40.
2. The above Frequency and Channel in "[#]" were 802.11ac VHT80.



2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11a	6 Mbps
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0
802.11ac VHT80	MCS0

AC Conducted Emission	Mode 1 : GSM 850 Idle + Bluetooth Link + WLAN Link(5G) + USB Cable 3(Charging from Adapter 2) + Earphone
Remark: For Radiated Test Cases, The tests were performance with Adapter 2, Earphone, USB Cable 3.	

Simultaneous transmission
Wifi 5G 802.11ac VHT80 CH58_TX + LTE_Band 13 Link




Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		802.11a	802.11a	802.11a	802.11a
L	Low	36	52	100	149
M	Middle	44	60	116	157
H	High	48	64	140	165
Straddle		-	-	144	-

Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		802.11ac VHT20	802.11ac VHT20	802.11ac VHT20	802.11ac VHT20
L	Low	36	52	100	149
M	Middle	44	60	116	157
H	High	48	64	140	165
Straddle		-	-	144	-

Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		802.11ac VHT40	802.11ac VHT40	802.11ac VHT40	802.11ac VHT40
L	Low	38	54	102	151
M	Middle	-	-	110	-
H	High	46	62	134	159
Straddle		-	-	142	-

Ch. #		U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
		802.11ac VHT80	802.11ac VHT80	802.11ac VHT80	802.11ac VHT80
L	Low	-	-	106	-
M	Middle	42	58	122	155
H	High	-	-	-	-
Straddle		-	-	138	-

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritus	MT8820C	N/A	N/A	Unshielded,1.8m
2.	LTE Base Station	Anritus	MT8821C	N/A	N/A	Unshielded,1.8m
	5GNR Base Station	Anritus	MT8000A	N/A	N/A	Unshielded,1.8m
3.	WLAN AP	TP-Link	TL-WDR5600	N/A	N/A	Unshielded,1.8m
4.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
5.	Bluetooth Earphone	Xiaomi	LYEJ02LM	N/A	N/A	N/A
6.	Bluetooth Earphone	Lenovo	thinkplus-BH3	N/A	N/A	N/A
7.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	shielded cable DC O/P 1.8m Unshielded AC I/P
8.	Notebook	Lenovo	S730-13IWL	N/A	N/A	shielded cable DC O/P 1.8m Unshielded AC I/P
9.	Notebook	Lenovo	V130-14IKB001	N/A	N/A	shielded cable DC O/P 1.8m Unshielded AC I/P
10.	Hard Disk	Lenovo	F310	DoC	N/A	Shielded, 1.2m
11.	Vector Signal Generator	R&S	SMBV100A	258305	N/A	N/A
12.	SD Card	Kingston	8GB	N/A	N/A	N/A



2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5.8 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 5.8 + 10 = 15.8 \text{ (dB)} \end{aligned}$$



3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.

3.1.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

- 1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

<input checked="" type="checkbox"/>	Section C) Bandwidth Measurement 1. Emission Bandwidth (EBW) and 99% OBW
	<ol style="list-style-type: none"> 1. Set RBW = approximately 1% of the emission bandwidth. 2. Set the VBW > RBW. 3. Detector = Peak. 4. Trace mode = max hold 5. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%. 6. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set to 1%~5% of the OBW and set the Video bandwidth (VBW) ≥ 3 * RBW. 7. Measure and record the results in the test report.
<input checked="" type="checkbox"/>	Section C) Bandwidth Measurement 2. Minimum Emission Bandwidth for the band 5.725 - 5.85 GHz
	<ol style="list-style-type: none"> 1. Set RBW = 100kHz. 2. Set the VBW ≥ 3 x RBW. 3. Detector = Peak. 4. Trace mode = max hold 5. Measure the maximum width of the emission that is 6 dB down from the peak of the emission. 6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.



3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW.

For the 5.25–5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz.

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note that U-NII-2 band, devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.


Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty

factor, $10 \log(1/x)$, where x is the duty cycle.

4. For MIMO mode, the measure-and-sum technique should be used for measuring the in-band transmit power of a device.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band.

For the 5.25–5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.



3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04. Section F) Maximum power spectral density.

For devices operating in the bands 5.15 - 5.25 GHz, 5.25 - 5.35 GHz, and 5.47 - 5.725 GHz

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz.
- Set VBW \geq 3 MHz.
- Number of points in sweep \geq 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.


For devices operating in the band 5.725 - 5.85 GHz

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
 - Set span to encompass the entire emission bandwidth (EBW) of the signal.
 - Set RBW = 500KHz (or 300 kHz if the SA can't set RBW=500KHz).
 - Set VBW \geq 1 MHz.
 - Number of points in sweep \geq 2 Span / RBW.
 - Sweep time = auto.
 - Detector = RMS
 - Trace average at least 100 traces in power averaging mode.
 - If the SA can't set RBW=500KHz, then add $10 \log(500\text{kHz}/\text{RBW})$ to the test result.
 - Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.
1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
 2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Unwanted Emissions Measurement

This section as specified in FCC Part 15.407(b) is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement. The unwanted emissions shall comply with 15.407(b)(1) to (6), and restricted bands per FCC Part 15.205.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27dBm/MHz .

For transmitters operating in the 5250-5350 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27 dBm/MHz . Devices operating in the 5250-5350 MHz band that generate emissions in the 5150-5250 MHz band must meet all applicable technical requirements for operation in the 5150-5250 MHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5150-5250 MHz band.

For transmitters operating in the 5470-5600 MHz and 5650-5725MHz band: all emissions outside of the 5470-5600 MHz and 5650-5725MHz band shall not exceed an EIRP of -27 dBm/MHz .

- (2) For transmitters operating in the 5.725-5.85 GHz band:
15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.



(3) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

(4) EIRP (dBm)	Field Strength at 3m (dBµV/m)
- 27	68.2

Note: The following formula is used to convert the EIRP to field strength.

$$EIRP = E_{Meas} + 20\log (d_{Meas}) - 104.7$$

where

EIRP is the equivalent isotropically radiated power, in dBm

E_{Meas} is the field strength of the emission at the measurement distance, in dBµV/m

d_{Meas} is the measurement distance, in m

(4) ANSI C63.10-2013 clause 12.7.3 note 97

As specified by regulatory requirements, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit. However, an out-of-band emission that complies with both the average and peak general regulatory limits is not required to satisfy the peak emission limit.

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.4.3 Test Procedures


1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04. Section G) Unwanted emissions measurement.
 - (1) Procedure for Unwanted Emissions Measurements Below 1000MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold
 - (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW \geq 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold
 - (3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW \geq 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.4.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.4.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix C.



3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBµV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.6 Antenna Requirements

3.6.1 Standard Applicable

According to FCC 47 CFR Section 15.407(a)(1)(2), if transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.6.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV30	101338	10Hz~30GHz	May 16, 2023	Sep. 22, 2023 ~Oct. 11, 2023	May 15, 2024	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 05, 2023	Sep. 22, 2023 ~Oct. 11, 2023	Jan. 04, 2024	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 05, 2023	Sep. 22, 2023 ~Oct. 11, 2023	Jan. 04, 2024	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY56400023	3Hz~8.5GHz;Max x 30dBm	Jan. 05, 2023	Sep. 19, 2023 ~Oct. 12, 2023	Jan. 04, 2024	Radiation (03CH08-KS)
Spectrum Analyzer	R&S	FSV40	101932	10kHz~40GHz; Max 30dBm	Oct. 10, 2023	Sep. 19, 2023 ~Oct. 12, 2023	Oct. 09, 2024	Radiation (03CH08-KS)
Loop Antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Oct. 10, 2023	Sep. 19, 2023 ~Oct. 12, 2023	Oct. 09, 2024	Radiation (03CH08-KS)
Bilog Antenna	TESEQ& VGT	CBL 61110	59915	30MHz-1GHz	Aug. 12, 2023	Sep. 19, 2023 ~Oct. 12, 2023	Aug. 11, 2024	Radiation (03CH08-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Mar. 18, 2023	Sep. 19, 2023 ~Oct. 12, 2023	Mar. 17, 2024	Radiation (03CH08-KS)
high gain Amplifier	EM	EM01G18GA	060845	1Ghz-18Ghz	Jan. 05, 2023	Sep. 19, 2023 ~Oct. 12, 2023	Jan. 04, 2024	Radiation (03CH08-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 08, 2023	Sep. 19, 2023 ~Oct. 12, 2023	Jan. 07, 2024	Radiation (03CH08-KS)
Amplifier	SONOMA	310N	413741	9KHz-1GHz	Jan. 05, 2023	Sep. 19, 2023 ~Oct. 12, 2023	Jan. 04, 2024	Radiation (03CH08-KS)
Amplifier	EM	EM01G18GA	060834	1Ghz-18Ghz	Oct. 10, 2023	Sep. 19, 2023 ~Oct. 12, 2023	Oct. 09, 2024	Radiation (03CH08-KS)
Amplifier	MITEQ	EM18G40GGA	060728	18~40GHz	Jan. 05, 2023	Sep. 19, 2023 ~Oct. 12, 2023	Jan. 04, 2024	Radiation (03CH08-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Sep. 19, 2023 ~Oct. 12, 2023	NCR	Radiation (03CH08-KS)
Turn Table	EM	EM 1000-T	N/A	0~360 degree	NCR	Sep. 19, 2023 ~Oct. 12, 2023	NCR	Radiation (03CH08-KS)
Antenna Mast	EM	EM 1000-A	N/A	1 m~4 m	NCR	Sep. 19, 2023 ~Oct. 12, 2023	NCR	Radiation (03CH08-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	May 16, 2023	Sep. 20, 2023 ~Sep. 21, 2023	May 15, 2024	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2022	Sep. 20, 2023 ~Sep. 21, 2023	Oct. 12, 2023	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	May 16, 2023	Sep. 20, 2023 ~Sep. 21, 2023	May 15, 2024	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2022	Sep. 20, 2023 ~Sep. 21, 2023	Oct. 11, 2023	Conduction (CO01-KS)

NCR: No Calibration Required



5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Power	±0.46 dB
Conducted Emissions	±0.48 dB
Occupied Channel Bandwidth	±0.1 %
Conducted Power Spectral Density	±0.40 dB

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.94dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.28dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.90dB
---	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.26dB
---	--------



Appendix A. Conducted Test Results

A1. Conducted Test Results

Test Engineer:	Gene Wang	Temperature:	21~25	°C
Test Date:	2023.9.22~2023.10.11	Relative Humidity:	51~54	%

TEST RESULTS DATA
Average Power Table

FCC U-NII-1 single antenna											
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power with duty factor (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)		Pass/Fail	Power Setting
					Ant 6	Ant 6	Ant 6	Ant 6			
11a	6Mbps	1	36	5180	0.13	19.36	24.00	-5.00		Pass	39
11a	6Mbps	1	44	5220	0.13	19.84	24.00	-5.00		Pass	40
11a	6Mbps	1	48	5240	0.13	19.87	24.00	-5.00		Pass	40
HT20	MCS0	1	36	5180	0.14	19.15	24.00	-5.00		Pass	39
HT20	MCS0	1	44	5220	0.14	19.72	24.00	-5.00		Pass	40
HT20	MCS0	1	48	5240	0.14	19.68	24.00	-5.00		Pass	40
HT40	MCS0	1	38	5190	0.28	15.54	24.00	-5.00		Pass	32
HT40	MCS0	1	46	5230	0.28	15.66	24.00	-5.00		Pass	32
VHT20	MCS0	1	36	5180	0.14	19.21	24.00	-5.00		Pass	39
VHT20	MCS0	1	44	5220	0.14	19.74	24.00	-5.00		Pass	40
VHT20	MCS0	1	48	5240	0.14	19.73	24.00	-5.00		Pass	40
VHT40	MCS0	1	38	5190	0.28	16.22	24.00	-5.00		Pass	33
VHT40	MCS0	1	46	5230	0.28	17.72	24.00	-5.00		Pass	36
VHT80	MCS0	1	42	5210	0.55	15.08	24.00	-5.00		Pass	31

TEST RESULTS DATA
Average Power Table

FCC U-NII-2A single antenna										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power with duty factor (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail	Power Setting
					Ant 6	Ant 6	Ant 6			
11a	6Mbps	1	52	5260	19.86	23.98	-5.00	26.99	Pass	40
11a	6Mbps	1	60	5300	19.95	23.98	-5.00	26.99	Pass	40
11a	6Mbps	1	64	5320	19.01	23.98	-5.00	26.99	Pass	38
HT20	MCS0	1	52	5260	19.59	23.98	-5.00	26.99	Pass	40
HT20	MCS0	1	60	5300	19.67	23.98	-5.00	26.99	Pass	40
HT20	MCS0	1	64	5320	18.82	23.98	-5.00	26.99	Pass	38
HT40	MCS0	1	54	5270	15.66	23.98	-5.00	26.99	Pass	32
HT40	MCS0	1	62	5310	15.59	23.98	-5.00	26.99	Pass	32
VHT20	MCS0	1	52	5260	19.69	23.98	-5.00	26.99	Pass	40
VHT20	MCS0	1	60	5300	19.76	23.98	-5.00	26.99	Pass	40
VHT20	MCS0	1	64	5320	18.91	23.98	-5.00	26.99	Pass	38
VHT40	MCS0	1	54	5270	17.75	23.98	-5.00	26.99	Pass	36
VHT40	MCS0	1	62	5310	16.16	23.98	-5.00	26.99	Pass	33
VHT80	MCS0	1	58	5290	15.69	23.98	-5.00	26.99	Pass	32

TEST RESULTS DATA
Average Power Table

FCC U-NII-2C single antenna										Power Setting
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power with duty factor (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail	
					Ant 6	Ant 6	Ant 6			
11a	6Mbps	1	100	5500	18.39	23.98	-5.00	26.99	Pass	Ant 6
11a	6Mbps	1	116	5580	19.55	23.98	-5.00	26.99	Pass	37
11a	6Mbps	1	140	5700	18.15	23.98	-5.00	26.99	Pass	40
HT20	MCS0	1	100	5500	18.63	23.98	-5.00	26.99	Pass	38
HT20	MCS0	1	116	5580	16.61	23.98	-5.00	26.99	Pass	38
HT20	MCS0	1	140	5700	18.16	23.98	-5.00	26.99	Pass	35
HT40	MCS0	1	102	5510	15.28	23.98	-5.00	26.99	Pass	38
HT40	MCS0	1	110	5550	15.17	23.98	-5.00	26.99	Pass	32
HT40	MCS0	1	134	5670	14.69	23.98	-5.00	26.99	Pass	32
VHT20	MCS0	1	100	5500	18.69	23.98	-5.00	26.99	Pass	32
VHT20	MCS0	1	116	5580	16.70	23.98	-5.00	26.99	Pass	38
VHT20	MCS0	1	140	5700	18.23	23.98	-5.00	26.99	Pass	35
VHT40	MCS0	1	102	5510	16.86	23.98	-5.00	26.99	Pass	38
VHT40	MCS0	1	110	5550	17.08	23.98	-5.00	26.99	Pass	35
VHT40	MCS0	1	134	5670	16.76	23.98	-5.00	26.99	Pass	36
VHT80	MCS0	1	106	5530	15.64	23.98	-5.00	26.99	Pass	36
VHT80	MCS0	1	122	5610	17.27	23.98	-5.00	26.99	Pass	32
										36

FCC U-NII-2C straddle channel single antenna										Power Setting
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power with duty factor (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail	
					Ant 6	Ant 6	Ant 6			
11a	6Mbps	1	144	5720	18.12	23.98	-5.00	26.99	Pass	Ant 6
HT20	MCS0	1	144	5720	18.50	23.98	-5.00	26.99	Pass	38
HT40	MCS0	1	142	5710	14.55	23.98	-5.00	26.99	Pass	39
VHT20	MCS0	1	144	5720	18.57	23.98	-5.00	26.99	Pass	32
VHT40	MCS0	1	142	5710	16.62	23.98	-5.00	26.99	Pass	39
VHT80	MCS0	1	138	5690	17.08	23.98	-5.00	26.99	Pass	36

TEST RESULTS DATA
Average Power Table

U-NII-3 single antenna										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power with duty factor (dBm)		Conducted Power Limit (dBm)		DG (dBi)	Pass/Fail
					Ant 6	SUM	Ant 6	Ant 6		
11a	6Mbps	1	149	5745	17.10		30.00	-5.00	Pass	
11a	6Mbps	1	157	5785	19.54		30.00	-5.00	Pass	
11a	6Mbps	1	165	5825	19.07		30.00	-5.00	Pass	
HT20	MCS0	1	149	5745	18.59		30.00	-5.00	Pass	
HT20	MCS0	1	157	5785	19.46		30.00	-5.00	Pass	
HT20	MCS0	1	165	5825	19.01		30.00	-5.00	Pass	
HT40	MCS0	1	151	5755	15.07		30.00	-5.00	Pass	
HT40	MCS0	1	159	5795	15.03		30.00	-5.00	Pass	
VHT20	MCS0	1	149	5745	18.69		30.00	-5.00	Pass	
VHT20	MCS0	1	157	5785	19.53		30.00	-5.00	Pass	
VHT20	MCS0	1	165	5825	19.05		30.00	-5.00	Pass	
VHT40	MCS0	1	151	5755	17.12		30.00	-5.00	Pass	
VHT40	MCS0	1	159	5795	17.07		30.00	-5.00	Pass	
VHT80	MCS0	1	155	5775	17.23		30.00	-5.00	Pass	

Power Setting	
Ant 6	
35	
40	
40	
38	
40	
40	
32	
32	
38	
40	
40	
36	
36	
36	



Ambient Condition: <u>25</u> °C, <u>45</u> %RH
Test Date: <u>2023.9.22~2023.10.11</u> Test Engineer: <u>Gene Wang</u>

Emission Bandwidth

Test Result



TestMode	Freq(MHz)	26dB EBW [MHz]	FL[MHz]	FH[MHz]
11A	5180	33.50	5164.00	5197.50
	5220	32.60	5204.10	5236.70
	5240	31.00	5225.00	5256.00
	5260	31.60	5243.60	5275.20
	5300	30.40	5285.30	5315.70
	5320	30.90	5304.20	5335.10
	5500	29.00	5486.40	5515.40
	5580	25.30	5567.00	5592.30
	5700	26.40	5686.80	5713.20
	5720	26.40	5707.20	5733.60
	5745	30.60	5729.10	5759.70
	5785	29.00	5770.60	5799.60
	5825	25.90	5811.40	5837.30
11AC20 SISO	5180	32.20	5164.50	5196.70
	5220	35.60	5201.10	5236.70
	5240	31.50	5225.30	5256.80
	5260	32.40	5243.70	5276.10
	5300	32.50	5282.60	5315.10
	5320	35.10	5302.90	5338.00
	5500	26.80	5486.90	5513.70
	5580	26.00	5566.20	5592.20
	5700	26.00	5686.80	5712.80
	5720	27.80	5707.50	5735.30
	5745	27.70	5730.90	5758.60
	5785	31.10	5768.40	5799.50
	5825	25.40	5812.20	5837.60
11AC40 SISO	5190	41.20	5169.40	5210.60
	5230	51.20	5204.60	5255.80
	5270	54.60	5241.00	5295.60
	5310	53.00	5285.60	5338.60
	5510	40.80	5489.80	5530.60





	5550	40.80	5529.60	5570.40
	5670	40.60	5649.80	5690.40
	5710	40.40	5690.00	5730.40
	5755	40.60	5734.80	5775.40
	5795	40.60	5774.80	5815.40
11AC80 SISO	5210	102.80	5159.60	5262.40
	5290	106.80	5231.20	5338.00
	5530	80.80	5490.00	5570.80
	5610	80.80	5570.00	5650.80
	5690	80.40	5650.00	5730.40
	5775	82.80	5733.40	5816.20





Test Graphs









11A_5320
























11AC20SISO_5720




11AC20SISO_5745






11AC20SISO_5785




11AC20SISO_5825






11AC40SISO_5190




11AC40SISO_5230






11AC40SISO_5270




11AC40SISO_5310






11AC40SISO_5510




11AC40SISO_5550








11AC40SISO_5670




11AC40SISO_5710













11AC80SISO_5690



11AC80SISO_5775





Occupied channel bandwidth

Test Result


TestMode	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]
11A	5180	19.74	5170.2897	5190.0300
	5220	20.979	5209.3706	5230.3497
	5240	19.82	5230.4895	5250.3097
	5260	19.7	5250.0100	5269.7103
	5300	19.381	5290.2498	5309.6304
	5320	19.54	5310.0899	5329.6304
	5500	17.862	5491.0889	5508.9510
	5580	17.582	5571.2088	5588.7912
	5700	17.702	5691.1688	5708.8711
	5720	17.662	5711.2088	5728.8711
	5745	18.102	5735.9291	5754.0310
	5785	18.182	5775.8891	5794.0709
	5825	17.782	5816.0490	5833.8312
11AC20 SISO	5180	20.22	5170.0100	5190.2298
	5220	20.979	5209.3706	5230.3497
	5240	20.26	5230.2897	5250.5495
	5260	19.98	5249.8501	5269.8302
	5300	19.78	5290.0500	5309.8302
	5320	20.18	5309.7702	5329.9500
	5500	18.501	5490.7692	5509.2707
	5580	18.382	5570.8092	5589.1908
	5700	18.462	5690.8092	5709.2707
	5720	18.422	5710.8092	5729.2308
	5745	18.821	5735.5694	5754.3906
	5785	18.701	5775.6094	5794.3107
	5825	18.581	5815.6494	5834.2308
11AC40 SISO	5190	36.523	5171.6983	5208.2218
	5230	36.763	5211.6184	5248.3816
	5270	36.763	5251.6184	5288.3816
	5310	36.523	5291.6983	5328.2218
	5510	36.284	5491.8581	5528.1419
	5550	36.204	5531.8581	5568.0619
	5670	36.364	5651.7782	5688.1419
	5710	36.364	5691.8581	5728.2218





	5755	36.444	5736.7782	5773.2218
	5795	36.444	5776.7782	5813.2218
11AC80 SISO	5210	76.084	5171.9580	5248.0420
	5290	75.924	5251.9580	5327.8821
	5530	75.604	5492.2777	5567.8821
	5610	75.445	5572.2777	5647.7223
	5690	75.604	5652.2777	5727.8821
	5775	75.764	5737.1179	5812.8821



Test Graphs











11A_5500





Date: 21.SEP.2023 21:15:41

11A_5580




Date: 21.SEP.2023 21:16:35





11A_5785



11A_5825




11AC20SISO_5180







11AC20SISO_5220




11AC20SISO_5240








11AC20SISO_5320





Date: 21.SEP.2023 21:28:34


11AC20SISO_5500




Date: 21.SEP.2023 21:29:33














11AC40SISO_5270




11AC40SISO_5310








11AC40SISO_5670



Date: 21.SEP.2023 22:05:27

11AC40SISO_5710



Date: 21.SEP.2023 22:06:18