



FCC RF Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT2419-1, XT2419-2, XT2419-3, XT2419V
FCC ID : IHDT56AQ4
STANDARD : 47 CFR Part 2, and 90(S)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S) : Dec. 19, 2023 ~ Jan. 25, 2024

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Jason Jia



Approved by: Jason Jia

Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant..... 5

 1.2 Manufacturer 5

 1.3 Feature of Equipment Under Test..... 5

 1.4 Product Specification of Equipment Under Test 5

 1.5 Modification of EUT 5

 1.6 Maximum Conducted Power and Emission Designator 6

 1.7 Testing Site..... 6

 1.8 Test Software 7

 1.9 Applied Standards 7

 1.10 Specification of Accessory 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

 2.1 Test Mode..... 8

 2.2 Connection Diagram of Test System 9

 2.3 Support Unit used in test configuration and system..... 9

 2.4 Measurement Results Explanation Example 9

 2.5 Frequency List of Low/Middle/High Channels..... 10

3 TEST RESULT..... 11

 3.1 Conducted Output Power Measurement..... 11

 3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement..... 12

 3.3 Emissions Mask Measurement 13

 3.4 Emissions Mask – Out Of Band Emissions Measurement..... 15

 3.5 Field Strength of Spurious Radiation Measurement 16

 3.6 Frequency Stability Measurement..... 19

4 LIST OF MEASURING EQUIPMENT 21

5 MEASUREMENT UNCERTAINTY 22

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. TEST SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG3D0836E	Rev. 01	Initial issue of report	Feb. 07, 2024



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	—	Report only	-
3.2	§2.1049 §90.209	Occupied Bandwidth and 26dB Bandwidth	—	Report only	-
3.3	§2.1051 §90.691	Emission masks – In-band emissions	$< 50+10\log_{10}(P[\text{Watts}])$	PASS	-
3.4	§2.1051 §90.691	Emission masks – Out of band emissions	$< 43+10\log_{10}(P[\text{Watts}])$	PASS	-
3.5	§2.1053 §90.691	Field Strength of Spurious Radiation	$< 43+10\log_{10}(P[\text{Watts}])$	PASS	Under limit -48.49 dB at 3267.00 MHz
3.6	§2.1055 §90.213	Frequency Stability for Temperature & Voltage	$< 2.5 \text{ ppm}$	PASS	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2419-1, XT2419-2, XT2419-3, XT2419V
FCC ID	IHDT56AQ4
IMEI Code	Conducted: 355199400022373/355199400022381 Radiation: 355199400020955/355199400020963
HW Version	DVT2
SW Version	U2UB34.18
EUT Stage	Identical Prototype

Remark: The four model names are only for market segment, no other difference.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx Frequency	814 ~ 824 MHz
Rx Frequency	859 ~ 869 MHz
Bandwidth	1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz
Maximum Output Power to Antenna	<Ant.0>: 22.79 dBm <Ant.1>: 22.62 dBm
Antenna Gain	<Ant.0>: -5.0 dBi <Ant.1>: -4.8 dBi
Type of Modulation	QPSK / 16QAM / 64QAM / 256QAM

Note: Only maximum conducted Power of Ant.0 is shown in the report.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Maximum Conducted Power and Emission Designator

LTE Band 26		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum Conducted power (W)	Emission Designator (99%OBW)	Maximum Conducted power (W)	Emission Designator (99%OBW)
1.4	814.7 ~ 823.3	0.1832	1M09G7D	0.1820	1M10W7D
3	815.5 ~ 822.5	0.1879	2M73G7D	0.1845	2M72W7D
5	816.5 ~ 821.5	0.1901	4M53G7D	0.1824	4M48W7D
10	819.0	0.1816	9M11G7D	0.1799	9M01W7D
15	824	0.1832	13M5G7D	0.1832	13M5W7D

Note: All modulations have been tested, and only the worst test results are shown in the report.

1.7 Testing Site

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People’s Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	TH01-SZ	CN1256	421272

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People’s Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH04-SZ	CN1256	421272



1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH04-SZ	AUDIX	E3	6.2009-8-24

1.9 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 90(S)
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 971168 D02 Misc Rev Approv License Devices v02r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

1.10 Specification of Accessory

Accessories Information				
Battery 1	Brand Name	Motorola (ATL)	Model Name	QS50
Battery 2	Brand Name	Motorola (Jiade)	Model Name	QS50
USB Cable 1	Brand Name	Motorola(Saibao)	Model Name	SC18D86732
USB Cable 2	Brand Name	Motorola(Cabletech)	Model Name	SC18E05246



2 Test Configuration of Equipment Under Test


2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is 30 MHz to 9000 MHz.

Test Items	Band	Bandwidth (MHz)						Modulation				RB #			Test Channel			
		1.4	3	5	10	15	20	QPSK	16 QAM	64 QAM	256 QAM	1	Half	Full	L	M	H	
Max. Output Power	26	v	v	v	v	v	-	v	v	v	v	v	v	v	v	v	v	v
Peak-to-Average Ratio	26				v			v	v	v				v		v		
26dB and 99% Bandwidth	26	v	v	v	v		-	v	v					v		v		
						v		v	v									v
Emission masks In-band emissions	26	v	v	v	v	v	-	v	v	v		v		v	v		v	
Emission masks – Out of band emissions	26	v	v	v	v	v	-	v				v			v	v	v	
Frequency Stability	26				v		-	v						v		v		
Radiated Spurious Emission	26				v		-	v				v				v		
Note	<ol style="list-style-type: none"> The mark “v” means that this configuration is chosen for testing The mark “-” means that this bandwidth is not supported. LTE Band26 transmit frequency for part22 rule is 824MHz-849MHz, for part90 rule is 814MHz-824MHz. ERP over 15MHz bandwidth complies the ERP limit line of part22 rule, therefore ERP of the partial frequency spectrum which falls within part 22 also complies. For QAM modulation mode, the whole testing has assessed 16QAM&64QAM mode by referring to the higher conducted power. 																	

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.0 dB and a 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.0 + 10 = 14.0 \text{ (dB)} \end{aligned}$$



2.5 Frequency List of Low/Middle/High Channels

LTE Band 26 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	-	26740	-
	Frequency	-	819	-
5	Channel	26715	26740	26765
	Frequency	816.5	819	821.5
3	Channel	26705	26740	26775
	Frequency	815.5	819	822.5
1.4	Channel	26697	26740	26783
	Frequency	814.7	819	823.3

LTE Band 26 Cross-rule Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	-	Middle	-
15	Channel	-	26790	-
	Frequency	-	824	-
10	Channel	-	26790	-
	Frequency	-	824	-
5	Channel	-	26790	-
	Frequency	-	824	-
3	Channel	-	26790	-
	Frequency	-	824	-
1.4	Channel	-	26790	-
	Frequency	-	824	-

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Please refer to Appendix A.

3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.2.1 Description of (Occupied) Bandwidth Limitations Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The 26dB and 99% occupied bandwidth (BW) of the middle channel for the highest RF power with full RB sizes were measured.

3.2.4 Test Setup



3.2.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth

Please refer to Appendix A.



3.3 Emissions Mask Measurement

3.3.1 Description of Emissions Mask Measurement

Equipment used in this licensed to EA or non-EA systems shall comply with the emission mask provisions of FCC Part 90.691.(a):

(a) Out-of-band emission requirement shall apply only to the “outer” channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \text{ Log}_{10}(f/6.1)$ decibels or $50 + 10 \text{ Log}_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \text{ Log}_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The emissions mask of low and high channels for the highest RF powers were measured.
3. The measured RBW and the VBW set 3 times of RBW are then set in spectrum analyzer, and the RBW correction factor $10 \text{ log } (1\% \text{ of OBW/measured RBW})(\text{dB})$ was compensated, if required.
4. The test results were shown below plots with a correction offset factor including cable loss, insertion loss of power divider.

3.3.4 Test Setup



3.3.5 Test Result (Plots) of Conducted Emissions Mask

Please refer to Appendix A.

3.4 Emissions Mask – Out Of Band Emissions Measurement

3.4.1 Description of Conducted Emissions Out of band emissions measurement

The power of any emission FCC Part 90.691 (a)(2) on any frequency removed from the assigned frequency by out of the authorized bandwidth at least $43 + 10 \log (P)$ dB. It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

3.4.4 Test Setup



3.4.5 Test Result (Plots) of Conducted Emission

Please refer to Appendix A.



3.5 Field Strength of Spurious Radiation Measurement

3.5.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI/TIA-603-E. The power of any emission FCC Part 90.691 on any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth at least $43 + 10 \log(P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log_{10}(P[\text{Watts}])$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. $\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$
11. $\text{ERP (dBm)} = \text{EIRP} - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
13. The limit line is derived from $43 + 10 \log(P)$ dB below the transmitter power P(Watts)

3.5.4 Test Setup

For radiated test from 30MHz



For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



3.5.5 Test Result of Field Strength of Spurious Radiated

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

3.6 Frequency Stability Measurement

3.6.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency according to FCC Part 90.213.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.6.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
3. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
4. The variation in frequency was measured for the worst case.

3.6.5 Test Setup



3.6.6 Test Result of Temperature Variation

Please refer to Appendix A.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 06, 2023	Dec.19,2023~ Dec.20,2023	Apr. 05, 2024	Conducted (TH01-SZ)
DC Power Supply	TTI	PL330P	290070	Max 32V , 3A	Oct. 16, 2023	Dec.19,2023~ Dec.20,2023	Oct. 15, 2024	Conducted (TH01-SZ)
Power Divider	TOJOIN	PS-2SM-04 265	60.06.020.007 7	0.4GHz~26.5GHz	Dec. 25, 2022	Dec.19,2023~ Dec.20,2023	Dec. 24, 2023	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Jul. 05, 2023	Dec.19,2023~ Dec.20,2023	Jul. 04, 2024	Conducted (TH01-SZ)
EMI Test Receiver	R&S	ESR7	101404	9kHz~7GHz	Oct. 18, 2023	Jan. 25,2024	Oct. 17, 2024	Radiation (03CH04-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 07, 2023	Jan. 25,2024	Jul. 06, 2024	Radiation (03CH04-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	Jun. 28, 2022	Jan. 25,2024	Jun. 27, 2024	Radiation (03CH04-SZ)
Bilog Antenna	TeseQ	CBL6111D	41909	30MHz~1GHz	May. 14, 2023	Jan. 25,2024	May. 13, 2024	Radiation (03CH04-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1474	1GHz~18GHz	Jul. 07, 2023	Jan. 25,2024	Jul. 06, 2024	Radiation (03CH04-SZ)
Horn Antenna	SCHWARZBECK	BBHA9170	9170#679	15GHz~40GHz	Jul. 08, 2023	Jan. 25,2024	Jul. 07, 2024	Radiation (03CH04-SZ)
Amplifier	Burgeon	BPA-530	102211	0.01Hz ~3000MHz	Oct. 18, 2023	Jan. 25,2024	Oct. 17, 2024	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	AMF-7D-00 101800-30-1	1943528	1GHz~18GHz	Oct. 18, 2023	Jan. 25,2024	Oct. 17, 2024	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	TTA1840-35 -HG	1871923	18GHz~40GHz	Jul. 07, 2023	Jan. 25,2024	Jul. 06, 2024	Radiation (03CH04-SZ)
Amplifier	Agilent Technologies	83017A	MY57280136	500MHz~26.5GHz	Aug. 21, 2023	Jan. 25,2024	Aug. 20, 2024	Radiation (03CH04-SZ)
AC Power Source	APC	AFV-S-600B	F119050019	N/A	Oct. 18, 2023	Jan. 25,2024	Oct. 17, 2024	Radiation (03CH04-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jan. 25,2024	NCR	Radiation (03CH04-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jan. 25,2024	NCR	Radiation (03CH04-SZ)

NCR: No Calibration Required



5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	±1.34 dB
Occupied Channel Bandwidth	±0.012 MHz
Conducted Power	±1.34 dB
Peak to Average Ratio	±1.34 dB
Frequency Stability	±1.3 Hz

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.80
---	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.10
---	------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.90
---	------

----- THE END -----



Appendix A. Test Results of Conducted Test

Test Engineer :	Hank Lin	Temperature :	24~26°C
		Relative Humidity :	50~53%

Conducted Output Power (Average power)

LTE Band 26_ANT.0

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.
Channel				26790	-	-
Frequency (MHz)				824	-	-
15	QPSK	1	0	22.41	-	-
15	QPSK	1	37	22.63	-	-
15	QPSK	1	74	22.51	-	-
15	QPSK	36	0	22.39	-	-
15	QPSK	36	20	22.53	-	-
15	QPSK	36	39	22.54	-	-
15	QPSK	75	0	22.62	-	-
15	16QAM	1	0	22.21	-	-
15	16QAM	1	37	22.21	-	-
15	16QAM	1	74	22.29	-	-
15	16QAM	36	0	22.15	-	-
15	16QAM	36	20	22.18	-	-
15	16QAM	36	39	22.26	-	-
15	16QAM	75	0	22.24	-	-
15	16QAM	1	0	22.46	-	-
15	16QAM	1	37	22.28	-	-
15	16QAM	1	74	22.63	-	-
15	16QAM	36	0	21.15	-	-
15	16QAM	36	20	21.15	-	-
15	16QAM	36	39	21.10	-	-
15	16QAM	75	0	21.13	-	-
15	16QAM	1	0	19.26	-	-
15	16QAM	1	37	19.29	-	-
15	16QAM	1	74	19.26	-	-
15	16QAM	36	0	19.27	-	-
15	16QAM	36	20	19.21	-	-
15	16QAM	36	39	19.13	-	-
15	16QAM	75	0	19.13	-	-
Channel				-	26740	-
Frequency (MHz)				-	819	-
10	QPSK	1	0	-	22.32	-
10	QPSK	1	25	-	22.57	-



10	QPSK	1	49	-	22.35	-
10	QPSK	25	0	-	22.29	-
10	QPSK	25	12	-	22.59	-
10	QPSK	25	25	-	22.42	-
10	QPSK	50	0	-	22.45	-
10	16QAM	1	0	-	22.11	-
10	16QAM	1	25	-	22.37	-
10	16QAM	1	49	-	22.36	-
10	16QAM	25	0	-	22.03	-
10	16QAM	25	12	-	22.15	-
10	16QAM	25	25	-	22.15	-
10	16QAM	50	0	-	22.39	-
10	16QAM	1	0	-	22.30	-
10	16QAM	1	25	-	22.20	-
10	16QAM	1	49	-	22.55	-
10	16QAM	25	0	-	21.01	-
10	16QAM	25	12	-	21.20	-
10	16QAM	25	25	-	21.24	-
10	16QAM	50	0	-	21.31	-
10	16QAM	1	0	-	19.09	-
10	16QAM	1	25	-	19.04	-
10	16QAM	1	49	-	19.09	-
10	16QAM	25	0	-	18.99	-
10	16QAM	25	12	-	19.18	-
10	16QAM	25	25	-	19.12	-
10	16QAM	50	0	-	19.07	-
Channel				26715	26740	26765
Frequency (MHz)				816.5	819	821.5
5	QPSK	1	0	22.37	22.30	22.37
5	QPSK	1	12	22.31	22.67	22.59
5	QPSK	1	24	22.39	22.39	22.47
5	QPSK	12	0	22.29	22.36	22.45
5	QPSK	12	7	22.51	22.62	22.79
5	QPSK	12	13	22.24	22.60	22.61
5	QPSK	25	0	22.41	22.55	22.64
5	16QAM	1	0	22.10	22.16	22.61
5	16QAM	1	12	22.02	22.36	22.44
5	16QAM	1	24	22.14	22.38	22.39
5	16QAM	12	0	22.08	22.06	22.41
5	16QAM	12	7	21.87	22.12	22.26
5	16QAM	12	13	22.13	22.19	22.30
5	16QAM	25	0	22.07	22.26	22.24
5	16QAM	1	0	22.31	22.28	22.56
5	16QAM	1	12	22.20	22.30	22.44
5	16QAM	1	24	22.46	22.51	22.48



5	16QAM	12	0	20.96	21.05	21.21
5	16QAM	12	7	20.90	21.15	21.27
5	16QAM	12	13	21.04	21.36	21.42
5	16QAM	25	0	21.15	21.35	21.33
5	16QAM	1	0	19.12	19.12	19.37
5	16QAM	1	12	19.16	19.12	19.24
5	16QAM	1	24	19.09	18.99	19.12
5	16QAM	12	0	19.05	19.14	19.20
5	16QAM	12	7	19.13	19.06	19.07
5	16QAM	12	13	18.90	19.05	19.23
5	16QAM	25	0	19.02	18.99	19.19
Channel				26705	26740	26775
Frequency (MHz)				815.5	819	822.5
3	QPSK	1	0	22.38	22.36	22.47
3	QPSK	1	8	22.41	22.58	22.74
3	QPSK	1	14	22.27	22.38	22.40
3	QPSK	8	0	22.29	22.32	22.53
3	QPSK	8	4	22.33	22.50	22.59
3	QPSK	8	7	22.32	22.51	22.59
3	QPSK	15	0	22.54	22.47	22.49
3	16QAM	1	0	22.15	22.14	22.53
3	16QAM	1	8	22.13	22.33	22.47
3	16QAM	1	14	22.21	22.30	22.25
3	16QAM	8	0	22.05	21.87	22.41
3	16QAM	8	4	22.05	22.17	22.32
3	16QAM	8	7	22.00	22.34	22.34
3	16QAM	15	0	22.08	22.33	22.32
3	16QAM	1	0	22.28	22.23	22.62
3	16QAM	1	8	22.25	22.28	22.51
3	16QAM	1	14	22.30	22.66	22.43
3	16QAM	8	0	20.86	21.02	21.08
3	16QAM	8	4	21.03	21.23	21.25
3	16QAM	8	7	21.07	21.36	21.36
3	16QAM	15	0	21.04	21.30	21.38
3	16QAM	1	0	19.13	19.03	19.28
3	16QAM	1	8	19.05	19.05	19.24
3	16QAM	1	14	19.02	19.03	19.34
3	16QAM	8	0	19.06	19.08	19.25
3	16QAM	8	4	19.15	19.15	19.09
3	16QAM	8	7	18.93	18.98	19.27
3	16QAM	15	0	19.02	19.12	19.14
Channel				26697	26740	26783
Frequency (MHz)				814.7	819	823.3
1.4	QPSK	1	0	22.36	22.37	22.50
1.4	QPSK	1	3	22.44	22.59	22.63




1.4	QPSK	1	5	22.33	22.44	22.56
1.4	QPSK	3	0	22.35	22.39	22.37
1.4	QPSK	3	1	22.44	22.49	22.59
1.4	QPSK	3	3	22.35	22.30	22.44
1.4	QPSK	6	0	22.43	22.39	22.62
1.4	16QAM	1	0	22.08	22.16	22.47
1.4	16QAM	1	3	22.09	22.28	22.49
1.4	16QAM	1	5	22.17	22.34	22.27
1.4	16QAM	3	0	22.04	22.25	22.56
1.4	16QAM	3	1	22.06	22.42	22.43
1.4	16QAM	3	3	22.10	22.32	22.25
1.4	16QAM	6	0	22.10	22.33	22.27
1.4	16QAM	1	0	22.39	22.31	22.59
1.4	16QAM	1	3	22.17	22.13	22.52
1.4	16QAM	1	5	22.44	22.48	22.44
1.4	16QAM	3	0	22.34	22.27	22.60
1.4	16QAM	3	1	22.21	22.03	22.36
1.4	16QAM	3	3	22.34	22.41	22.45
1.4	16QAM	6	0	21.00	21.21	21.32
1.4	16QAM	1	0	19.09	19.19	19.32
1.4	16QAM	1	3	19.09	19.00	19.28
1.4	16QAM	1	5	19.02	19.07	19.30
1.4	16QAM	3	0	19.09	19.16	19.33
1.4	16QAM	3	1	19.03	19.20	19.19
1.4	16QAM	3	3	19.04	18.98	19.30
1.4	16QAM	6	0	19.12	19.02	19.26



LTE Band 26_Part 90S

Peak-to-Average Ratio


Mode	LTE Band 26 / 10MHz			
Mod.	QPSK	16QAM	64QAM	Limit: 13dB
RB Size	Full RB	Full RB	Full RB	Result
Middle CH	5.19	5.91	6.41	PASS






26dB Bandwidth

Mode	LTE Band 26 : 26dB BW(MHz)									
	1.4MHz		3MHz		5MHz		10MHz		15MHz (cross-rule)	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	1.33	1.32	3.06	3.15	4.85	5.09	9.95	9.89	14.33	14.39






Middle Channel / 5MHz / QPSK



Date: 19, DEC, 2023 17:01:14


Middle Channel / 5MHz / 16QAM



Date: 19, DEC, 2023 17:01:55


LTE Band 26

Middle Channel / 10MHz / QPSK




Date: 20, DEC, 2023 19:54:46

Middle Channel / 10MHz / 16QAM




Date: 20, DEC, 2023 19:55:27

High Channel / 15MHz / QPSK



Date: 20, DEC, 2023 20:09:29

High Channel / 15MHz / 16QAM




Date: 20, DEC, 2023 20:09:56




Occupied Bandwidth

Mode	LTE Band 26 : 99%OBW(MHz)									
	1.4MHz		3MHz		5MHz		10MHz		15MHz (cross-rule)	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Middle CH	1.09	1.10	2.73	2.72	4.53	4.48	9.11	9.01	13.49	13.52






Middle Channel / 5MHz / QPSK



Date: 19, DEC, 2023 17:01:00


Middle Channel / 5MHz / 16QAM



Date: 19, DEC, 2023 17:01:41


LTE Band 26

Middle Channel / 10MHz / QPSK




Date: 20, DEC, 2023 19:54:32

Middle Channel / 10MHz / 16QAM




Date: 20, DEC, 2023 19:55:13

High Channel / 15MHz / QPSK



Date: 20, DEC, 2023 20:09:15


High Channel / 15MHz / 16QAM





Date: 20, DEC, 2023 20:10:10



Emission masks – In-band emissions










LTE Band 26 / 1.4MHz / 64QAM


Lowest Band Edge / 1 RB



Spectrum Emission Mask		Standard: None		Tx Power 23.30 dBm		Tx Bandwidth 1.400 MHz		RBW 30.000 kHz	
Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit			
-3.000 MHz	-737.500 kHz	100.000 kHz	813.95982 MHz	-15.25 dBm	-38.55 dB	-2.25 dB			
-737.500 kHz	-700.000 kHz	300.000 kHz	813.99625 MHz	-36.58 dBm	-59.88 dB	-16.58 dB			
700.000 kHz	737.500 kHz	300.000 kHz	815.40804 MHz	-70.92 dBm	-94.21 dB	-50.92 dB			
737.500 kHz	3.000 MHz	100.000 kHz	815.62122 MHz	-44.86 dBm	-68.16 dB	-31.86 dB			

Date: 19.DEC.2023 15:51:40

Highest Band Edge / 1 RB




Spectrum Emission Mask		Standard: None		Tx Power 23.21 dBm		Tx Bandwidth 1.400 MHz		RBW 30.000 kHz	
Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit			
-3.000 MHz	-737.500 kHz	100.000 kHz	822.34985 MHz	-44.71 dBm	-67.92 dB	-31.71 dB			
-737.500 kHz	-700.000 kHz	300.000 kHz	822.56518 MHz	-70.59 dBm	-93.80 dB	-50.59 dB			
700.000 kHz	737.500 kHz	300.000 kHz	824.00696 MHz	-36.33 dBm	-59.54 dB	-16.33 dB			
737.500 kHz	3.000 MHz	100.000 kHz	824.05089 MHz	-13.55 dBm	-36.76 dB	-0.55 dB			

Date: 19.DEC.2023 16:05:11

Lowest Band Edge / 1 RB-CHP


NA

Highest Band Edge / 1 RB-CHP



Channel Power		Standard: None		Tx Power 23.21 dBm		Tx Bandwidth 1.400 MHz		RBW 30.000 kHz	
Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit			
-3.000 MHz	-737.500 kHz	100.000 kHz	822.34985 MHz	-44.71 dBm	-67.92 dB	-31.71 dB			
-737.500 kHz	-700.000 kHz	300.000 kHz	822.56518 MHz	-70.59 dBm	-93.80 dB	-50.59 dB			
700.000 kHz	737.500 kHz	300.000 kHz	824.00696 MHz	-36.33 dBm	-59.54 dB	-16.33 dB			
737.500 kHz	3.000 MHz	100.000 kHz	824.05089 MHz	-13.55 dBm	-36.76 dB	-0.55 dB			


Date: 19.DEC.2023 16:44:31






LTE Band 26 / 3MHz / QPSK

Lowest Band Edge / 1RB




Date: 19.DEC.2023 17:25:42

Highest Band Edge / 1RB




Date: 19.DEC.2023 16:22:52

Lowest Band Edge / Full RB



Date: 19.DEC.2023 16:18:30

Highest Band Edge / Full RB




Date: 19.DEC.2023 16:29:14




LTE Band 26 / 3MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 19.DEC.2023 16:13:24

Highest Band Edge / 1 RB




Date: 19.DEC.2023 16:24:08

Lowest Band Edge / Full RB



Date: 19.DEC.2023 16:17:13

Highest Band Edge / Full RB




Date: 19.DEC.2023 16:27:57




LTE Band 26 / 3MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 19.DEC.2023 16:14:40

Highest Band Edge / 1 RB




Date: 19.DEC.2023 16:25:25

Lowest Band Edge / Full RB



Date: 19.DEC.2023 16:15:57

Highest Band Edge / Full RB




Date: 19.DEC.2023 16:26:41




LTE Band 26 / 5MHz / QPSK

Lowest Band Edge / 1RB

Highest Band Edge / 1RB




Date: 19.DEC.2023 16:53:16




Date: 19.DEC.2023 17:03:01

Lowest Band Edge / Full RB

Highest Band Edge / Full RB



Date: 19.DEC.2023 16:58:48




Date: 19.DEC.2023 17:08:38




LTE Band 26 / 5MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 19.DEC.2023 16:54:22

Highest Band Edge / 1 RB




Date: 19.DEC.2023 17:04:07

Lowest Band Edge / Full RB



Date: 19.DEC.2023 16:57:42

Highest Band Edge / Full RB




Date: 19.DEC.2023 17:07:31




LTE Band 26 / 5MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 19.DEC.2023 16:55:29

Highest Band Edge / 1 RB




Date: 19.DEC.2023 17:05:13

Lowest Band Edge / Full RB



Date: 19.DEC.2023 16:56:35

Highest Band Edge / Full RB




Date: 19.DEC.2023 17:06:20



LTE Band 26 / 10MHz / QPSK


Lowest Band Edge / 1RB



Spectrum Emission Mask		Standard: None		Tx Power 22.44 dBm		Tx Bandwidth 10.000 MHz		RBW 100.000 kHz		Power Abs		Power Rel		ΔLimit	
Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit	Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit	Range Low	Range Up
-10.000 MHz	-5.038 MHz	100.000 kHz	813.9929 MHz	-32.27 dBm	-54.72 dB	-19.27 dB	-10.000 MHz	-5.038 MHz	100.000 kHz	810.67024 MHz	-54.45 dBm	-76.77 dB	-41.45 dB	-10.000 MHz	-5.038 MHz
-5.038 MHz	-5.000 MHz	300.000 Hz	813.99813 MHz	-56.47 dBm	-78.92 dB	-36.47 dB	-5.038 MHz	-5.000 MHz	300.000 Hz	813.97188 MHz	-80.67 dBm	-102.99 dB	-60.67 dB	-5.038 MHz	-5.000 MHz
5.000 MHz	5.038 MHz	300.000 Hz	824.00188 MHz	-80.51 dBm	-102.96 dB	-60.51 dB	5.000 MHz	5.038 MHz	300.000 Hz	824.00563 MHz	-56.44 dBm	-78.77 dB	-36.44 dB	5.038 MHz	10.000 MHz
5.038 MHz	10.000 MHz	100.000 kHz	828.90890 MHz	-54.36 dBm	-76.80 dB	-41.36 dB									

Date: 20.DEC.2023 19:46:39


Lowest Band Edge / 1RB



Spectrum Emission Mask		Standard: None		Tx Power 22.33 dBm		Tx Bandwidth 10.000 MHz		RBW 100.000 kHz		Power Abs		Power Rel		ΔLimit	
Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit	Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit	Range Low	Range Up
-10.000 MHz	-5.038 MHz	100.000 kHz	810.67024 MHz	-54.45 dBm	-76.77 dB	-41.45 dB	-10.000 MHz	-5.038 MHz	100.000 kHz	813.97188 MHz	-80.67 dBm	-102.99 dB	-60.67 dB	-10.000 MHz	-5.038 MHz
-5.038 MHz	-5.000 MHz	300.000 Hz	813.97188 MHz	-80.67 dBm	-102.99 dB	-60.67 dB	-5.038 MHz	-5.000 MHz	300.000 Hz	824.00563 MHz	-56.44 dBm	-78.77 dB	-36.44 dB	-5.038 MHz	-5.000 MHz
5.000 MHz	5.038 MHz	300.000 Hz	824.00563 MHz	-56.44 dBm	-78.77 dB	-36.44 dB	5.038 MHz	10.000 MHz	100.000 kHz	824.05000 MHz	-32.06 dBm	-54.39 dB	-19.06 dB	5.038 MHz	10.000 MHz

Date: 20.DEC.2023 19:51:17

Lowest Band Edge / Full RB




Spectrum Emission Mask		Standard: None		Tx Power 23.00 dBm		Tx Bandwidth 10.000 MHz		RBW 100.000 kHz		Power Abs		Power Rel		ΔLimit	
Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit	Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit	Range Low	Range Up
-10.000 MHz	-5.038 MHz	100.000 kHz	813.94642 MHz	-30.62 dBm	-53.62 dB	-17.62 dB	-10.000 MHz	-5.038 MHz	100.000 kHz	813.99813 MHz	-55.57 dBm	-78.57 dB	-35.57 dB	-10.000 MHz	-5.038 MHz
-5.038 MHz	-5.000 MHz	300.000 Hz	813.99813 MHz	-55.57 dBm	-78.57 dB	-35.57 dB	-5.038 MHz	-5.000 MHz	300.000 Hz	824.00188 MHz	-54.60 dBm	-77.60 dB	-34.60 dB	-5.038 MHz	-5.000 MHz
5.000 MHz	5.038 MHz	300.000 Hz	824.00188 MHz	-54.60 dBm	-77.60 dB	-34.60 dB	5.038 MHz	10.000 MHz	100.000 kHz	824.03929 MHz	-30.44 dBm	-53.44 dB	-17.44 dB	5.038 MHz	10.000 MHz

Date: 20.DEC.2023 19:52:13




LTE Band 26 / 10MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 20.DEC.2023 19:47:35

Lowest Band Edge / 1 RB



Date: 20.DEC.2023 19:50:21

Lowest Band Edge / Full RB




Date: 20.DEC.2023 19:53:09




LTE Band 26 / 10MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 20.DEC.2023 19:48:30

Lowest Band Edge / 1 RB



Date: 20.DEC.2023 19:49:26

Lowest Band Edge / Full RB





Date: 20.DEC.2023 19:54:05



LTE Band 26 / 15MHz

Highest Band Edge / 1RB QPSK

Highest Band Edge / Full RB QPSK





Date: 20. DEC. 2023 20:00:21

Date: 20. DEC. 2023 20:04:58

Highest Band Edge / 1 RB 16QAM

Highest Band Edge / Full RB 16QAM



Date: 20. DEC. 2023 20:01:17


Date: 20. DEC. 2023 20:04:02




LTE Band 26 / 15MHz

Highest Band Edge / 1 RB 64QAM

Highest Band Edge / Full RB 64QAM



Date: 20.DEC.2023 20:02:12



Date: 20.DEC.2023 20:03:07





Emission masks – Out of band emissions


LTE Band 26 / 1.4MHz

Lowest Channel / QPSK

Middle Channel / QPSK




Highest Channel / QPSK






LTE Band 26 / 3MHz

Lowest Channel / QPSK




Date: 19.DEC.2023 16:19:22

Middle Channel / QPSK



Date: 19.DEC.2023 16:20:14

Highest Channel / QPSK





Date: 19.DEC.2023 16:30:07




LTE Band 26 / 5MHz

Lowest Channel / QPSK

Middle Channel / QPSK




Highest Channel / QPSK





LTE Band 26 / 10MHz


Middle Channel / QPSK



Date: 20.DEC.2023 19:58:02

LTE Band 26 / 15MHz

Highest Channel / QPSK



Date: 20.DEC.2023 20:06:10



Frequency Stability

Test Conditions		LTE Band 26 (QPSK) / Middle Channel	Limit
Temperature (°C)	Voltage (Volt)	BW 10MHz	Note 2.
		Deviation (ppm)	Result
50	Normal Voltage	0.0000	PASS
40	Normal Voltage	0.0002	
30	Normal Voltage	0.0010	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0014	
0	Normal Voltage	0.0010	
-10	Normal Voltage	0.0011	
-20	Normal Voltage	0.0000	
-30	Normal Voltage	0.0013	
20	Maximum Voltage	0.0005	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0015	

Note:

1. Normal Voltage = 3.91 V. ; Battery End Point (BEP) = 3.4 V. ; Maximum Voltage = 4.5 V.
2. The frequency fundamental emissions stay within the authorized frequency block.



Appendix B. Test Results of Radiated Test

Radiated Spurious Emission

Test Engineer :	Shiwei Wen	Temperature :	22~25°C
		Relative Humidity :	48~52%

RSE Pre-scanned harmonic for the different antennas, we choose the worst antenna mode to perform final test and record in the report.

LTE Band 26 / 10MHz / QPSK / Ant. 0									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1633.5	-66.32	-13	-53.32	-74.71	-69.57	4.00	9.40	H
	2450.25	-64.14	-13	-51.14	-76.28	-67.71	4.88	10.60	H
	3267	-61.49	-13	-48.49	-76.80	-66.42	5.52	12.60	H
	1633.5	-66.25	-13	-53.25	-74.59	-69.50	4.00	9.40	V
	2450.25	-64.07	-13	-51.07	-76.19	-67.64	4.88	10.60	V
	3267	-62.01	-13	-49.01	-77.18	-66.94	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.