



Partial Spot Check Evaluation

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT2429-2
FCC ID : IHDT56AR5
STANDARD : 47 CFR Part 2, 22(H), 24(E), 27(H), 27(M), 27(O), 27(Q), 90(S)
47 CFR Part 15 Subpart C §15.209
47 CFR Part 15 Subpart C §15.225
47 CFR Part 15 Subpart C §15.247
47 CFR Part 15 Subpart E §15.407
TEST DATE(S) : Feb. 04, 2024 ~ Mar. 06, 2024

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY..... 3

1 GENERAL DESCRIPTION..... 4

1.1 Applicant 4

1.2 Manufacturer..... 4

1.3 Product Feature of Equipment Under Test..... 4

1.4 Modification of EUT 4

1.5 Testing Site..... 4

1.6 Test Software..... 5

1.7 Applicable Standards..... 5

1.8 Specification of Accessory..... 6

2 RE-USE OF MEASURED DATA..... 7

2.1 Introduction Section 7

2.2 Model Difference Information 7

2.3 Reference detail Section: 8

2.4 Spot Check Verification Data Section..... 9

3 LIST OF MEASURING EQUIPMENT..... 12

4 MEASUREMENT UNCERTAINTY 14

APPENDIX A. SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
411904-01	Rev. 01	Initial issue of report	Mar. 18, 2024
411904-01	Rev. 02	Update Conducted Power on Page 10 for WWAN bands	Mar. 26, 2024

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/maker who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Motorola Mobility LLC
222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC
222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2429-2
FCC ID	IHDT56AR5
IMEI Code	Conducted/Radiation: 353380310013395 NFC: 353380310013296/353380310013304
HW Version	DVT2
SW Version	U2UU34.8
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Testing Site

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH02-KS 03CH05-KS 03CH04-KS TH01-KS	CN1257	314309



1.6 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	SPORTON	FCC 15C-15E Test Tools Ver10.0_210607	10.0
2.	TH01-KS	SPORTON	FCC BT2.0 Ver3.0_For_CHINA_190111	3.0
3.	TH01-KS	SPORTON	FCC LTE_Ver2.0 Auto_china_210503	2.0
4.	03CH02-KS	AUDIX	E3	6.2009-8-24a
5.	03CH04-KS	AUDIX	E3	210616
6.	03CH05-KS	AUDIX	E3	6.2009-8-24aI

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC KDB 484596 D01 Referencing Test Data v02r02
- ♦ 47 CFR Part 2, 22(H), 24(E), 27(H), 27(M), 27(O), 27(Q), 90(S)
- ♦ 47 CFR Part 15 Subpart C §15.209
- ♦ 47 CFR Part 15 Subpart C §15.225
- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ 47 CFR Part 15 Subpart E §15.407
- ♦ ANSI C63.10-2013
- ♦ ANSI C63.26-2015



1.8 Specification of Accessory

Specification of Accessory				
AC Adapter 1(US)	Brand Name	Motorola(Chenyang)	Model Name	MC-681N
AC Adapter 1(EU)	Brand Name	Motorola(Chenyang)	Model Name	MC-682N
AC Adapter 1(UK)	Brand Name	Motorola(Chenyang)	Model Name	MC-683N
AC Adapter 1(AU)	Brand Name	Motorola(Chenyang)	Model Name	MC-685N
AC Adapter 1(AR)	Brand Name	Motorola(Chenyang)	Model Name	MC-686N
AC Adapter 1(BR)	Brand Name	Motorola(Chenyang)	Model Name	MC-687N
AC Adapter 1(CHILE)	Brand Name	Motorola(Chenyang)	Model Name	MC-689N
AC Adapter 2(US)	Brand Name	Motorola(Acbel)	Model Name	MC-681N
AC Adapter 2(EU)	Brand Name	Motorola(Acbel)	Model Name	MC-682N
AC Adapter 2(UK)	Brand Name	Motorola(Acbel)	Model Name	MC-683N
AC Adapter 2(AU)	Brand Name	Motorola(Acbel)	Model Name	MC-685N
AC Adapter 2(AR)	Brand Name	Motorola(Acbel)	Model Name	MC-686N
AC Adapter 2(BR)	Brand Name	Motorola(Acbel)	Model Name	MC-687N
AC Adapter 2(IN)	Brand Name	Motorola(Acbel)	Model Name	MC-684N
Battery 1	Brand Name	Motorola(ATL)	Model Name	QC50
Battery 2	Brand Name	Motorola(SCUD)	Model Name	QC50
USB Cable 1	Brand Name	Motorola(Saibao)	Model Name	SLQ-A248A
USB Cable 2	Brand Name	Motorola(Juwei)	Model Name	S928E13829
USB Cable 3	Brand Name	Motorola(Saibao)	Model Name	SLQ-A248A



2 Re-use of Measured Data

2.1 Introduction Section

This application re-uses data collected on a similar device. The subject device of this application (Model: XT2429-2, FCC ID: IHDT56AR5) is electrically identical to the reference device (Model: XT2429-1, FCC ID: IHDT56AR4) for the portions of the circuitry corresponding to the data being re-used. Based on their similarity, the FCC Part 15C (equipment class: DTS, DSS, DXX) and FCC Part 15E (equipment class: NII) and FCC Part 22, 24, 27, 90 (equipment class: PCE) referencing the original model's result and do spot-check, following the FCC KDB 484596 D01 Referencing Test Data v02r02.

The applicant takes full responsibility that the test data as referenced in this report represent compliance for this FCC ID: IHDT56AR5 .

2.2 Model Difference Information

The **main** difference between FCC ID: IHDT56AR4 and FCC ID: IHDT56AR5 is as below:

- Remove WCDMA Band IV, LTE B4/12/13/17/25/66 and 5G NR n2/n66.
- Add LTE B18/19/20/32/71 and 5G NR n8/n20/n71/n77.

Other differences and all the details of similarity and difference can be found in the confidential documents (XT2429-2_Operational Description of Product Equality Declaration).



2.3 Reference detail Section:

Rule Part	Equipment Class	Frequency Band (MHz)	Reference FCC ID (Parent)	Type Grant/Permissive Change	Reference Title	FCC ID Filling (Variant)	Report Title/Section
15C	DSS (BR/EDR)	2400~2483.5	IHDT56AR4	Original Grant	FR411904A	IHDT56AR5	All sections applicable
	DTS (BLE)	2400~2483.5	IHDT56AR4	Original Grant	FR411904B	IHDT56AR5	All sections applicable
	DTS (WLAN)	2400~2483.5	IHDT56AR4	Original Grant	FR411904C	IHDT56AR5	All sections applicable
	DXX (NFC)	13.56	IHDT56AR4	Original Grant	FR411904D	IHDT56AR5	All sections applicable
15E	U-NII	5180~5240	IHDT56AR4	Original Grant	FR411904E	IHDT56AR5	All sections applicable
		5260~5320	IHDT56AR4	Original Grant	FR411904E FZ411904	IHDT56AR5	All sections applicable
		5500~5720	IHDT56AR4	Original Grant	FR411904E FZ411904	IHDT56AR5	All sections applicable
		5745~5825	IHDT56AR4	Original Grant	FR411904E	IHDT56AR5	All sections applicable
22, 24, 27, 90,	PCE (GSM)	GSM 850/1900	IHDT56AR4	Original Grant	FG411904A	IHDT56AR5	All sections applicable
	PCE (WCDMA)	Band II, V	IHDT56AR4	Original Grant	FG411904A	IHDT56AR5	All sections applicable
	PCE (LTE)	B2/5/7/26/38 ULCA 7C	IHDT56AR4	Original Grant	FG411904B FG411904C	IHDT56AR5	All sections applicable
	PCE (LTE)	B26 (90S)	IHDT56AR4	Original Grant	FG411904D	IHDT56AR5	All sections applicable
	PCE (LTE)	B42 (27Q)	IHDT56AR4	Original Grant	FG411904E	IHDT56AR5	All sections applicable
	PCE (NR)	n5(SA)/n7/n26/n38/n41(SA)	IHDT56AR4	Original Grant	FG411904G	IHDT56AR5	All sections applicable



2.4 Spot Check Verification Data Section

Conducted power test and radiated spurious emission test against the variant model based on the worst-case condition from the original model was performed in this filing to demonstrate the test data from original model remains representative for the variant model.

All test procedures follow the related section of parent report.

Spot-check measurements, while being always compliant with the applicable rule part(s) for the test under consideration, show a deviation d_{dB} from the reference data no larger than 3 dB:

$$d_{dB} = |V_{dB} - R_{dB}| \leq 3 \text{ dB} \tag{1}$$

V_{dB} , the variant spot-check level

R_{dB} , the corresponding measurement level for the reference model

An alternative to the limit of eq. (1) is available, and is based on considering how far the reference data R_{dB} is from the compliance threshold C_{dB} (also expressed in dB), for the particular test under consideration. In this case, if $M_{dB} = |C_{dB} - R_{dB}|$ is the margin in dB from the compliance limit, a spot check may be considered acceptable when the deviation d_{dB} from the reference data satisfies the following condition:

$$d_{dB} = |V_{dB} - R_{dB}| \leq (3 + M_{dB} / 20) \text{ dB} , \text{ for } 0 \leq M_{dB} \leq 60 \text{ dB} \tag{2}$$

$$d_{dB} = |V_{dB} - R_{dB}| = 6 \text{ dB} , \text{ for } M_{dB} > 60 \text{ dB}$$

where “| |” is the absolute value of the measured quantity.

When using the option in eq. (2), d_{dB} increases linearly from 3 dB to 6 dB.

Summary for power and RSE spot check for each rule entry and technology is listed as below:

Test Item	Mode	IHDT56AR4 Parent Worst mode Test Result	IHDT56AR5 Variant Check Test Result	Deviation (dB)	Limit (dB)
Conducted Power (dBm)	BT BR/EDR	13.13	13.08	0.05	3
	BLE 1Mbps	7.03	6.91	0.12	3
	BLE 2Mbps	7.29	7.16	0.13	3
	11B	24.57	24.21	0.36	3
	11G	25.74	25.61	0.13	3
	11n20	25.81	25.66	0.15	3
	11n40	25.45	25.37	0.08	3
	11a UNII-1	20.78	20.51	0.27	3
	11a UNII-2A	20.82	20.54	0.28	3
	11a UNII-2C	20.98	20.63	0.35	3
	11a UNII-3	21.01	20.68	0.33	3
	11n20 UNII-1	21.06	20.90	0.16	3
	11n20 UNII-2A	21.16	20.92	0.24	3
	11n20 UNII-2C	21.52	20.94	0.58	3
	11n20 UNII-3	20.74	20.35	0.39	3
	11n40 UNII-1	19.06	18.75	0.31	3
	11n40 UNII-2A	19.14	18.95	0.19	3
	11n40 UNII-2C	19.20	18.81	0.39	3
	11n40 UNII-3	18.75	18.21	0.54	3
	11ac20 UNII-1	21.10	20.92	0.18	3



11ac20 UNII-2A	21.18	20.93	0.25	3
11ac20 UNII-2C	21.56	20.98	0.58	3
11ac20 UNII-3	20.84	20.40	0.44	3
11ac40 UNII-1	19.14	18.83	0.31	3
11ac40 UNII-2A	19.24	19.01	0.23	3
11ac40 UNII-2C	19.25	18.93	0.32	3
11ac40 UNII-3	18.82	18.27	0.55	3
11ac80 UNII-1	13.48	13.32	0.16	3
11ac80 UNII-2A	15.97	15.84	0.13	3
11ac80 UNII-2C	18.98	18.59	0.39	3
11ac80 UNII-3	18.52	17.97	0.55	3
GSM 850	32.37	31.81	0.56	3
GSM 1900	29.53	29.52	0.01	3
WCDMA Band V	23.20	22.43	0.77	3
WCDMA Band II	23.20	22.44	0.76	3
LTE B2	22.91	22.89	0.02	3
LTE B5	22.98	22.70	0.28	3
LTE B26	23.27	22.60	0.67	3
LTE Part 90S B26	23.25	22.67	0.58	3
LTE B7	23.28	22.79	0.49	3
LTE B7 other PA	23.49	22.92	0.57	3
LTE B7C	22.38	22.32	0.06	3
LTE B38	23.16	23.12	0.04	3
LTE B38 other PA	22.32	22.29	0.03	3
LTE B38C	22.64	22.60	0.04	3
LTE B42	23.36	23.02	0.34	3

Note: Spot checks the conducted power of 5G NR Bands will be issued by separate test report.

Test Item	Mode	IHDT56AR4 Parent Worst Result	IHDT56AR5 Variant Check Result	Deviation (dB)	Limit (dB)
Radiated Spurious Emission (dBuV/m)	Bluetooth BR CH78	55.39	54.83	0.56	3
	BLE 2M CH39	44.82	41.9	2.92	3
	802.11n40 CH03	50.83	50.9	0.07	3
	802.11ac40 CH62	50.6	50.83	0.23	3
	802.11a CH149	44.15	45.68	1.53	3
	15C-NFC	56.34	56.19	0.25	3
Radiated Spurious Emission (dBm)	Part 22H GSM 850	-23.95	-26.85	2.9	3
	Part 24E PCS 1900	-48.9	-49.73	0.83	3
	Part 24E WCDMA1900	-58.47	-55.62	2.85	3
	Part 27M LTE B7	-45.56	-45.24	0.32	3
	Part 27M SA-N7	-43.09	-42.16	0.93	3

Conclusion:

Radiated spurious emission test against the variant model based on the worst-case condition from the original model was performed in this filing to demonstrate the test data from original model remains representative for the variant model.

Based on the spot check test result, the test data from the original model is representative for the variant model. The power level and RSE spot check are shown within expected level compliant to limit line.



We are using power and ERP/EIRP measurements from the original parent model reports to list on the grant.

The same DFS detection is used in the variant. Hence, there is no spot check data for DFS mechanism.

We confirm that the test data referencing policy of FCC KDB 484596 D01 Referencing Test Data v02r02 has been followed and the test data as referenced from the parent model report represents compliance with new FCC ID.



3 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 11, 2023	Mar. 04, 2024~ Mar. 06, 2024	Oct. 10, 2024	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 02, 2024	Mar. 04, 2024~ Mar. 06, 2024	Jan. 01, 2025	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 02, 2024	Mar. 04, 2024~ Mar. 06, 2024	Jan. 01, 2025	Conducted (TH01-KS)
Power divider	STI	STI08-0055	-	0.5~40GHz	NCR	Mar. 04, 2024~ Mar. 06, 2024	NCR	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Max x 30dBm	Oct. 10, 2023	Feb. 04, 2024	Oct. 09, 2024	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY553705 28	10Hz~44G,MAX 30dB	Oct. 10, 2023	Feb. 04, 2024	Oct. 09, 2024	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz-1GHz	Dec. 21, 2023	Feb. 04, 2024	Dec. 20, 2024	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Nov. 23 2023	Feb. 04, 2024	Nov. 22, 2024	Radiation (03CH02-KS)
high gain Amplifier	EM	EM01G18GA	060840	1Ghz-18Ghz	Oct. 10, 2023	Feb. 04, 2024	Oct. 09, 2024	Radiation (03CH02-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2024	Feb. 04, 2024	Jan. 04, 2025	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	380826	9KHz-1GHz	Jul. 06, 2023	Feb. 04, 2024	Jul. 05, 2024	Radiation (03CH02-KS)
Amplifier	EM	EM01G18G	060806	1GHz~18GHz	Oct. 11, 2023	Feb. 04, 2024	Oct. 10, 2024	Radiation (03CH02-KS)
Amplifier	EM	EM18G40GG A	060852	18~40GHz	Jan. 05, 2024	Feb. 04, 2024	Jan. 04, 2025	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002 473	N/A	NCR	Feb. 04, 2024	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Feb. 04, 2024	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Feb. 04, 2024	NCR	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY574710 79	10Hz~44G,MAX 30dB	Oct. 10, 2023	Feb. 07, 2024~ Feb. 23, 2024	Oct. 09, 2024	Radiation (03CH04-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 10, 2023	Feb. 07, 2024~ Feb. 23, 2024	Oct. 09, 2024	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz-1GHz	Apr. 09, 2023	Feb. 07, 2024~ Feb. 23, 2024	Apr. 08, 2024	Radiation (03CH04-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	1284	1GHz~18GHz	Oct. 10, 2023	Feb. 07, 2024~ Feb. 23, 2024	Oct. 09, 2024	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2024	Feb. 07, 2024~ Feb. 23, 2024	Jan. 04, 2025	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	380827	9KHz-1GHz	Jul. 06, 2023	Feb. 07, 2024~ Feb. 23, 2024	Jul. 05, 2024	Radiation (03CH04-KS)
Amplifier	MITEQ	EM18G40GG A	060728	18~40GHz	Jan. 05, 2024	Feb. 07, 2024~ Feb. 23, 2024	Jan. 04, 2025	Radiation (03CH04-KS)
high gain Amplifier	EM	EM01G18GA	060840	1Ghz-18Ghz	Oct. 10, 2023	Feb. 07, 2024~ Feb. 23, 2024	Oct. 09, 2024	Radiation (03CH04-KS)
Amplifier	Agilent	8449B	3008A023 70	1Ghz-18Ghz	Oct. 10, 2023	Feb. 07, 2024~ Feb. 23, 2024	Oct. 09, 2024	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F1040900 04	N/A	NCR	Feb. 07, 2024~ Feb. 23, 2024	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Feb. 07, 2024~ Feb. 23, 2024	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Feb. 07, 2024~ Feb. 23, 2024	NCR	Radiation (03CH04-KS)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz-44GHz	May 15, 2023	Mar. 05, 2024~ Mar. 06, 2024	May 14, 2024	Radiation (03CH05-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz-1GHz	Apr. 09, 2023	Mar. 05, 2024~ Mar. 06, 2024	Apr. 08, 2024	Radiation (03CH05-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218642	1GHz~18GHz	Apr. 06, 2023	Mar. 05, 2024~ Mar. 06, 2024	Apr. 05, 2024	Radiation (03CH05-KS)
SHF-EHF Horn	Com-power	AH-840	101093	18GHz~40GHz	Jan. 05, 2024	Mar. 05, 2024~ Mar. 06, 2024	Jan. 04, 2025	Radiation (03CH05-KS)
Amplifier	SONOMA	310N	380826	9KHz-1GHz	Jul. 06, 2023	Mar. 05, 2024~ Mar. 06, 2024	Jul. 05, 2024	Radiation (03CH05-KS)
Amplifier	EM	EM18G40GA	060852	18~40GHz	Jan. 05, 2023	Mar. 05, 2024~ Mar. 06, 2024	Jan. 04, 2024	Radiation (03CH05-KS)
high gain Amplifier	EM	EM01G18GA	060839	1Ghz-18Ghz	Oct. 10, 2023	Mar. 05, 2024~ Mar. 06, 2024	Oct. 09, 2024	Radiation (03CH05-KS)
Amplifier	EM	EM01G18GA	060833	1Ghz-18Ghz	Jan. 03, 2024	Mar. 05, 2024~ Mar. 06, 2024	Jan. 02, 2025	Radiation (03CH05-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Mar. 05, 2024~ Mar. 06, 2024	NCR	Radiation (03CH05-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Mar. 05, 2024~ Mar. 06, 2024	NCR	Radiation (03CH05-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Mar. 05, 2024~ Mar. 06, 2024	NCR	Radiation (03CH05-KS)

NCR: No Calibration Required.



4 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Power	±0.46 dB

Uncertainty of Radiated Emission Measurement (9 kHz ~ 30 MHz) - 03CH02-KS

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.30dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz) - 03CH02-KS

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.04dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz) - 03CH04-KS

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.82dB
---	--------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz) - 03CH04-KS

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.56dB
---	--------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz) - 03CH04-KS

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.54dB
---	--------



Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz) - 03CH05-KS

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.28dB
---	--------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz) - 03CH05-KS

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.88dB
---	--------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz) - 03CH05-KS

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.26dB
---	--------

-THE END-